



User's Guide

Enhanced Full-Text Search Specialty Data Store

12.5.1

UNIX and Windows NT

DOCUMENT ID: DC36521-01-1251-01

LAST REVISED: August 2003

Copyright © 1989-2003 by Sybase, Inc. All rights reserved.

This publication pertains to Sybase software and to any subsequent release until otherwise indicated in new editions or technical notes. Information in this document is subject to change without notice. The software described herein is furnished under a license agreement, and it may be used or copied only in accordance with the terms of that agreement.

To order additional documents, U.S. and Canadian customers should call Customer Fulfillment at (800) 685-8225, fax (617) 229-9845.

Customers in other countries with a U.S. license agreement may contact Customer Fulfillment via the above fax number. All other international customers should contact their Sybase subsidiary or local distributor. Upgrades are provided only at regularly scheduled software release dates. No part of this publication may be reproduced, transmitted, or translated in any form or by any means, electronic, mechanical, manual, optical, or otherwise, without the prior written permission of Sybase, Inc.

Sybase, the Sybase logo, AccelaTrade, ADA Workbench, Adaptable Windowing Environment, Adaptive Component Architecture, Adaptive Server, Adaptive Server Anywhere, Adaptive Server Enterprise, Adaptive Server Enterprise Monitor, Adaptive Server Enterprise Replication, Adaptive Server Everywhere, Adaptive Server IQ, Adaptive Warehouse, Anywhere Studio, Application Manager, AppModeler, APT Workbench, APT-Build, APT-Edit, APT-Execute, APT-FORMS, APT-Translator, APT-Library, AvantGo, AvantGo Application Alerts, AvantGo Mobile Delivery, AvantGo Mobile Document Viewer, AvantGo Mobile Inspection, AvantGo Mobile Marketing Channel, AvantGo Mobile Pharma, AvantGo Mobile Sales, AvantGo Pylon, AvantGo Pylon Application Server, AvantGo Pylon Conduit, AvantGo Pylon PIM Server, AvantGo Pylon Pro, Backup Server, BizTracker, ClearConnect, Client-Library, Client Services, Convoy/DM, Copernicus, Data Pipeline, Data Workbench, DataArchitect, Database Analyzer, DataExpress, DataServer, DataWindow, DB-Library, dbQueue, Developers Workbench, Direct Connect Anywhere, DirectConnect, Distribution Director, e-ADK, E-Anywhere, e-Biz Integrator, E-Whatever, EC Gateway, ECMAP, ECRTTP, eFulfillment Accelerator, Embedded SQL, EMS, Enterprise Application Studio, Enterprise Client/Server, Enterprise Connect, Enterprise Data Studio, Enterprise Manager, Enterprise SQL Server Manager, Enterprise Work Architecture, Enterprise Work Designer, Enterprise Work Modeler, eProcurement Accelerator, EWA, Financial Fusion, Financial Fusion Server, Gateway Manager, GlobalFIX, ImpactNow, Industry Warehouse Studio, InfoMaker, Information Anywhere, Information Everywhere, InformationConnect, InternetBuilder, iScript, Jaguar CTS, jConnect for JDBC, Mail Anywhere Studio, MainframeConnect, Maintenance Express, Manage Anywhere Studio, M-Business Channel, M-Business Network, M-Business Server, MDI Access Server, MDI Database Gateway, media.splash, MetaWorks, My AvantGo, My AvantGo Media Channel, My AvantGo Mobile Marketing, MySupport, Net-Gateway, Net-Library, New Era of Networks, ObjectConnect, ObjectCycle, OmniConnect, OmniSQL Access Module, OmniSQL Toolkit, Open Biz, Open Client, Open ClientConnect, Open Client/Server, Open Client/Server Interfaces, Open Gateway, Open Server, Open ServerConnect, Open Solutions, Optima++, PB-Gen, PC APT Execute, PC Net Library, PocketBuilder, Pocket PowerBuilder, Power++, power.stop, PowerAMC, PowerBuilder, PowerBuilder Foundation Class Library, PowerDesigner, PowerDimensions, PowerDynamo, PowerJ, PowerScript, PowerSite, PowerSocket, Powersoft, PowerStage, PowerStudio, PowerTips, Powersoft Portfolio, Powersoft Professional, PowerWare Desktop, PowerWare Enterprise, ProcessAnalyst, Rapport, Report Workbench, Report-Execute, Replication Agent, Replication Driver, Replication Server, Replication Server Manager, Replication Toolkit, Resource Manager, RW-DisplayLib, S-Designer, SDF, Secure SQL Server, Secure SQL Toolset, Security Guardian, SKILS, smart.partners, smart.parts, smart.script, SQL Advantage, SQL Anywhere, SQL Anywhere Studio, SQL Code Checker, SQL Debug, SQL Edit, SQL Edit/TPU, SQL Everywhere, SQL Modeler, SQL Remote, SQL Server, SQL Server Manager, SQL SMART, SQL Toolset, SQL Server/CFT, SQL Server/DBM, SQL Server SNMP SubAgent, SQL Station, SQLJ, STEP, SupportNow, S.W.I.F.T. Message Format Libraries, Sybase Central, Sybase Client/Server Interfaces, Sybase Financial Server, Sybase Gateways, Sybase MPP, Sybase SQL Desktop, Sybase SQL Lifecycle, Sybase SQL Workgroup, Sybase User Workbench, SybaseWare, Syber Financial, SyberAssist, SyBooks, System 10, System 11, System XI (logo), SystemTools, Tabular Data Stream, TradeForce, Transact-SQL, Translation Toolkit, UltraLite.NET, UNIBOM, Unilib, Uninull, Unisep, Unistring, URK Runtime Kit for UniCode, Viewer, Visual Components, VisualSpeller, VisualWriter, VQL, WarehouseArchitect, Warehouse Control Center, Warehouse Studio, Warehouse WORKS, Watcom, Watcom SQL, Watcom SQL Server, Web Deployment Kit, Web.PB, Web.SQL, WebSights, WebViewer, WorkGroup SQL Server, XA-Library, XA-Server and XP Server are trademarks of Sybase, Inc. 03/03

Unicode and the Unicode Logo are registered trademarks of Unicode, Inc.

All other company and product names used herein may be trademarks or registered trademarks of their respective companies.

Use, duplication, or disclosure by the government is subject to the restrictions set forth in subparagraph (c)(1)(ii) of DFARS 52.227-7013 for the DOD and as set forth in FAR 52.227-19(a)-(d) for civilian agencies.

Sybase, Inc., One Sybase Drive, Dublin, CA 94568.

Contents

About This Book	ix
CHAPTER 1 Introduction	1
Capabilities of the Enhanced Full-Text Search Engine	1
High availability	3
CHAPTER 2 Understanding the Enhanced Full-Text Search Engine	5
Components of the Enhanced Full-Text Search engine.....	5
The source table.....	5
The Verity collections	6
Filters.....	6
The text_db database.....	6
The index table.....	7
The text_events table	8
Relationships between the components.....	9
How a full-text search works	10
CHAPTER 3 Configuring Adaptive Server for Full-Text Searches.....	13
Configuring Adaptive Server for an Enhanced Full-Text Search engine	13
Enabling configuration parameters.....	14
Running the installtextserver script	14
Running the installmessages script.....	16
Running the installevent script	17
Name the local Adaptive Server	18
Creating and maintaining text indexes	19
Setting up source tables for indexing	19
Creating the text index and index table	20
Bringing the database online for full-text searches	22
Propagating changes to the text index	23
Replicating text indexes	23
Example: enabling a new database for text searches	24
Indexing the euro symbol	26

CHAPTER 4	Setting Up Verity Functions.....	27
	Enabling query-by-example, summarization, and clustering.....	27
	Editing the master style.prm file	29
	Editing individual style.prm files	29
	Setting up a column to use as a sort specification	30
	Using filters on text that contains tags	32
	Creating a custom thesaurus	34
	Examining the default thesaurus (optional)	35
	Creating the control file	35
	Creating the thesaurus	37
	Replacing the default thesaurus with the custom thesaurus... ..	37
	Creating topics	38
	Creating an outline file.....	39
	Creating a topic set directory.....	40
	Creating a knowledge base map.....	40
	Defining the location of the knowledge base map.....	41
	Executing queries against defined topics	41
	Troubleshooting topics	42
CHAPTER 5	Writing Full-Text Search Queries	43
	Components of a full-text search query	43
	Default behaviour	44
	Pseudo columns in the index table	44
	Using the score column to relevance-rank search results.....	45
	Using the sort_by column to specify a sort order	46
	Using the summary column to summarize documents.....	47
	Using pseudo columns to request clustered result sets	48
	Full-text search operators	50
	Considerations when using Verity operators.....	51
	Using the Verity operators.....	52
	Operator modifiers	60
CHAPTER 6	System Administration.....	63
	Starting the Enhanced Full-Text Search engine on UNIX.....	63
	Creating the runserver file	63
	Starting the Enhanced Full-Text Search engine on Windows NT ..	65
	Starting the Enhanced Full-Text Search engine as a service .	65
	Shutting down the Enhanced Full-Text Search engine	66
	Modifying the configuration parameters	67
	Modifying configuration values	69
	Available configuration parameters	69
	Setting the default language.....	70
	Setting the default character set.....	71

Indexing on the euro symbol	71
Setting the default sort order	72
Setting trace flags.....	73
Setting Open Server trace flags	74
Setting case sensitivity	74
Backup and recovery for the Enhanced Full-Text Search engine ..	75
Customizable backup and restore	76
Backing up Verity collections.....	76
Restoring collections and text indexes from backup	77

CHAPTER 7 Performance and Tuning..... 79

Updating existing indexes	79
Increasing query performance	80
Limiting the number of rows	80
Ensuring the correct join order for queries	80
Reconfiguring Adaptive Server	81
cis cursor rows	81
cis packet size	82
Reconfiguring the Enhanced Full-Text Search engine.....	82
batch_size	82
min_sessions and max_sessions.....	83
Using sp_text_notify.....	83
Configuring multiple Enhanced Full-Text Search engines	84
Creating multiple Enhanced Full-Text Search engines at start-up	84
Adding Enhanced Full-Text Search engines	84
Configuring additional Enhanced Full-Text Search engines ...	85
Multiple users	85
File Descriptors and Enhanced Full-Text Search.....	86

CHAPTER 8 Verity Topics 87

What are topics?	87
Topic organization	88
Weight assignments	88
Using a topic outline file	88
Making topics available	89
Setup process	89
Knowledge bases of topics	89
Combining topics into a knowledge base	90
Structure of topics	91
Top-level topics	92
Subtopics.....	92
Evidence topics	93

- Topic and subtopic relationships 93
- Maximum number of topics 94
 - Topic naming issues..... 94
- Verity query language 95
 - Query language summary 95
 - Operator precedence rules..... 99
- Sample topic outlines 100
- Operator reference 102
 - ACCRUE operator..... 102
 - ALL operator..... 102
 - AND operator 102
 - ANY operator..... 102
 - CONTAINS operator 103
 - ENDS operator 103
 - = (EQUALS) operator 103
 - FILTER operator..... 104
 - > (GREATER THAN) operator 104
 - >= (GREATER THAN OR EQUAL TO) operator..... 104
 - < (LESS THAN) operator..... 104
 - <= (LESS THAN OR EQUAL TO) operator 105
 - IN operator 105
 - MATCHES operator 105
 - NEAR operator 106
 - NEAR/N operator 106
 - OR operator..... 107
 - PARAGRAPH operator 107
 - PHRASE operator 107
 - SENTENCE operator 107
 - SOUNDEX operator 108
 - STARTS operator 108
 - STEM operator 108
 - SUBSTRING operator 108
 - THESAURUS operator..... 109
 - TYPO/N operator..... 109
 - WILDCARD operator..... 109
 - Using wildcard special characters 109
 - Searching for nonalphanumeric characters..... 110
 - WORD operator..... 111
- Modifier reference 111
 - CASE modifier..... 112
 - MANY modifier 112
 - NOT modifier 112
 - ORDER modifier..... 113
- Weights and document importance..... 113

Topic weights.....	113
Which operators accept weights.....	114
How weights affect importance.....	115
Assigning weights.....	116
Automatic weight assignments.....	118
Tips for assigning weights.....	118
Changing weights.....	118
Topic scoring and document importance.....	119
Designing topics.....	122
Preparing your topic design.....	122
Understanding your information needs.....	122
Understanding your documents.....	123
Using scanned data.....	124
Categorizing document samples.....	124
Topic design strategies.....	124
Top-down design.....	125
Bottom-up design.....	125
Designing the initial topic.....	126
Outlining a topic.....	126
Top-down topic outline example.....	127
Bottom-up topic outline example.....	131

APPENDIX A

System Procedures.....	137
sp_check_text_index.....	138
sp_clean_text_events.....	139
sp_clean_text_indexes.....	139
sp_create_text_index.....	140
sp_drop_text_index.....	142
sp_help_text_index.....	143
sp_optimize_text_index.....	143
sp_redo_text_events.....	144
sp_refresh_text_index.....	145
sp_show_text_online.....	146
sp_text_cluster.....	147
sp_text_configure.....	149
sp_text_dump_database.....	150
sp_text_kill.....	153
sp_text_load_index.....	154
sp_text_notify.....	155
sp_text_online.....	156

APPENDIX B

Sample Files.....	159
Default textsvr.cfg configuration file.....	159

	The sample_text_main.sql script	163
	Sample files illustrating Enhanced Full-Text Search engine features .	
	164	
	Custom thesaurus.....	164
	Topics	164
	Clustering, summarization, and query-by-example	164
	getsend sample program.....	165
APPENDIX C	Unicode Support	167
	Index.....	169

About This Book

This book explains how to use the Enhanced Full-Text Search Specialty Data Store product with Sybase® Adaptive Server® Enterprise.

This book describes the features and functionality of the enhanced version which is a separately priced product.

Audience

This book is for System Administrators who are configuring Adaptive Server for a Enhanced Full-Text Search Specialty Data Store and for users who are performing full-text searches on Adaptive Server data.

How to Use This Book

This book includes these chapters:

- Chapter 1, “Introduction,” provides an overview of the Enhanced Full-Text Search Specialty Data Store.
- Chapter 2, “Understanding the Enhanced Full-Text Search Engine,” describes the components of the Enhanced Full-Text Search Specialty Data Store and how it works.
- Chapter 3, “Configuring Adaptive Server for Full-Text Searches,” describes how to configure Adaptive Server so that Enhanced Full-Text Search Specialty Data Store can perform full-text searches on the databases.
- Chapter 4, “Setting Up Verity Functions,” describes the setup you need to do before you can issue full-text search queries.
- Chapter 5, “Writing Full-Text Search Queries,” describes the components you use to write full-text search queries.
- Chapter 6, “System Administration,” provides information about system administration issues.
- Chapter 7, “Performance and Tuning,” provides information about performance and tuning issues.
- Chapter 8, “Verity Topics,” provides information about configuring the Verity engine.
- Appendix A, “System Procedures,” describes Enhanced Full-Text Search Specialty Data Store system procedures.

-
- Appendix B, “Sample Files,” contains the text of the *textsvr.cfg* file, describes the sample files included with Enhanced Full-Text Search Specialty Data Store, and discusses issues regarding the *sample_text_main.sql* script.
 - Appendix C, “Unicode Support,” describes how to configure Enhanced Full Text Search Specialty Data Store to use Unicode.

Related documents

The Sybase® Adaptive Server® Enterprise documentation set consists of the following:

- The release bulletin for your platform – contains last-minute information that was too late to be included in the books.

A more recent version of the release bulletin may be available on the World Wide Web. To check for critical product or document information that was added after the release of the product CD, use the Sybase Technical Library.
- The *Installation Guide* for your platform – describes installation, upgrade, and configuration procedures for all Adaptive Server and related Sybase products.
- *What’s New in Adaptive Server Enterprise?* – describes the new features in Adaptive Server version 12.5.1, the system changes added to support those features, and the changes that may affect your existing applications.
- *ASE Replicator User’s Guide* – describes how to use the ASE Replicator feature of Adaptive Server to implement basic replication from a primary server to one or more remote Adaptive Servers.
- *Component Integration Services User’s Guide* – explains how to use the Adaptive Server Component Integration Services feature to connect remote Sybase and non-Sybase databases.
- *Configuring Adaptive Server Enterprise* for your platform – provides instructions for performing specific configuration tasks for Adaptive Server.
- *EJB Server User’s Guide* – explains how to use EJB Server to deploy and execute Enterprise JavaBeans in Adaptive Server.
- *Error Messages and Troubleshooting Guide* – explains how to resolve frequently occurring error messages and describes solutions to system problems frequently encountered by users.

- *Full-Text Search Specialty Data Store User's Guide* – describes how to use the Full-Text Search feature with Verity to search Adaptive Server Enterprise data.
- *Glossary* – defines technical terms used in the Adaptive Server documentation.
- *Historical Server User's Guide* – describes how to use Historical Server to obtain performance information for SQL Server[®] and Adaptive Server.
- *Java in Adaptive Server Enterprise* – describes how to install and use Java classes as data types, functions, and stored procedures in the Adaptive Server database.
- *Job Scheduler User's Guide* – provides instructions on how to install and configure, and create and schedule jobs on a local or remote Adaptive Server using the command line or a graphical user interface (GUI).
- *Monitor Client Library Programmer's Guide* – describes how to write Monitor Client Library applications that access Adaptive Server performance data.
- *Monitor Server User's Guide* – describes how to use Monitor Server to obtain performance statistics from SQL Server and Adaptive Server.
- *Performance and Tuning Guide* – is a series of four books that explains how to tune Adaptive Server for maximum performance:
 - *Basics* – the basics for understanding and investigating performance questions in Adaptive Server.
 - *Locking* – describes how the various locking schemas can be used for improving performance in Adaptive Server.
 - *Optimizer and Abstract Plans* – describes how the optimizer processes queries and how abstract plans can be used to change some of the optimizer plans.
 - *Monitoring and Analyzing* – explains how statistics are obtained and used for monitoring and optimizing performance.
- *Quick Reference Guide* – provides a comprehensive listing of the names and syntax for commands, functions, system procedures, extended system procedures, datatypes, and utilities in a pocket-sized book.
- *Reference Manual* – is a series of four books that contains the following detailed Transact-SQL[®] information:

-
- *Building Blocks* – Transact-SQL datatypes, functions, global variables, expressions, identifiers and wildcards, and reserved words.
 - *Commands* – Transact-SQL commands.
 - *Procedures* – Transact-SQL system procedures, catalog stored procedures, system extended stored procedures, and dbcc stored procedures.
 - *Tables* – Transact-SQL system tables and dbcc tables.
 - *System Administration Guide* – provides in-depth information about administering servers and databases. This manual includes instructions and guidelines for managing physical resources, security, user and system databases, and specifying character conversion, international language, and sort order settings.
 - *System Tables Diagram* – illustrates system tables and their entity relationships in a poster format. Available only in print version.
 - *Transact-SQL User's Guide* – documents Transact-SQL, Sybase's enhanced version of the relational database language. This manual serves as a textbook for beginning users of the database management system. This manual also contains descriptions of the pubs2 and pubs3 sample databases.
 - *Using Adaptive Server Distributed Transaction Management Features* – explains how to configure, use, and troubleshoot Adaptive Server DTM features in distributed transaction processing environments.
 - *Using Sybase Failover in a High Availability System* – provides instructions for using Sybase's Failover to configure an Adaptive Server as a companion server in a high availability system.
 - *Utility Guide* – documents the Adaptive Server utility programs, such as isql and bcp, which are executed at the operating system level.
 - *Web Services User's Guide* – explains how to configure, use, and troubleshoot Web Services for Adaptive Server.
 - *XA Interface Integration Guide for CICS, Encina, and TUXEDO* – provides instructions for using the Sybase DTM XA interface with X/Open XA transaction managers.
 - *XML Services in Adaptive Server Enterprise* – describes the Sybase native XML processor and the Sybase Java-based XML support, introduces XML in the database, and documents the query and mapping functions that comprise XML Services.

Other sources of information

Use the Sybase Getting Started CD, the Sybase Technical Library CD and the Technical Library Product Manuals Web site to learn more about your product:

- The Getting Started CD contains release bulletins and installation guides in PDF format, and may also contain other documents or updated information not included on the Technical Library CD. It is included with your software. To read or print documents on the Getting Started CD you need Adobe Acrobat Reader (downloadable at no charge from the Adobe Web site, using a link provided on the CD).
- The Technical Library CD contains product manuals and is included with your software. The DynaText reader (included on the Technical Library CD) allows you to access technical information about your product in an easy-to-use format.

Refer to the *Technical Library Installation Guide* in your documentation package for instructions on installing and starting the Technical Library.

- The Technical Library Product Manuals Web site is an HTML version of the Technical Library CD that you can access using a standard Web browser. In addition to product manuals, you will find links to EBFs/Updates, Technical Documents, Case Management, Solved Cases, newsgroups, and the Sybase Developer Network.

To access the Technical Library Product Manuals Web site, go to Product Manuals at <http://www.sybase.com/support/manuals/>.

Conventions

Directory paths For readability, directory paths in this manual are in UNIX format. On Windows NT, substitute `$SYBASE` with `%SYBASE%` and replace slashes (/) with backslashes (\). For example, replace this user input:

```
$SYBASE/$SYBASE_FTS/scripts
```

with:

```
%SYBASE%\%SYBASE_FTS%\scripts
```

Formatting SQL statements SQL is a free-form language: there are no rules about the number of words you can put on a line or where you must break a line. However, for readability, all examples and syntax statements in this manual are formatted so that each clause of a statement begins on a new line. Clauses that have more than one part extend to additional lines, which are indented.

SQL syntax conventions The conventions for syntax statements in this manual are as follows:

Table 1: Syntax statement conventions

Key	Definition
command	Command names, command option names, utility names, utility flags, and other keywords are in <code>bold Courier</code> in syntax statements and in bold Helvetica in paragraph text.
<i>variable</i>	Variables, or words that stand for values that you fill in, are in <i>italics</i> .
{ }	Curly braces indicate that you choose at least one of the enclosed options. Do not include braces in your option.
[]	Brackets mean choosing one or more of the enclosed options is optional. Do not include brackets in your option.
()	Parentheses are to be typed as part of the command.
	The vertical bar means you may select only one of the options shown.
,	The comma means you may choose as many of the options shown as you like, separating your choices with commas to be typed as part of the command.

- Syntax statements (displaying the syntax and all options for a command) are printed like this:

```
sp_dropdevice [device_name]
```

or, for a command with more options:

```
select column_name  
from table_name  
where search_conditions
```

In syntax statements, keywords (commands) are in normal font and identifiers are in lowercase: normal font for keywords, italics for user-supplied words.

- Examples showing the use of Transact-SQL commands are printed like this:

```
select * from publishers
```

- Examples of output from the computer are printed like this:

```
pub_id      pub_name      city      state  
-----  
0736       New Age Books    Boston    MA  
0877       Binnet & Hardley Washington    DC  
1389       Algodata Infosystems    Berkeley    CA
```

(3 rows affected)

Case In this manual, most of the examples are in lowercase. However, you can disregard case when typing Transact-SQL keywords. For example, `SELECT`, `Select`, and `select` are the same.

Adaptive Server's sensitivity to the case of database objects, such as table names, depends on the sort order installed on Adaptive Server. You can change case sensitivity for single-byte character sets by reconfiguring the Adaptive Server sort order.

Obligatory options {you must choose at least one} • *Curly Braces and Vertical Bars*: Choose *one and only one* option.

```
{die_on_your_feet | live_on_your_knees | live_on_your_feet}
```

- *Curly Braces and Commas*: Choose one or more options. If you choose more than one, separate your choices with commas.

```
{cash, check, credit}
```

Optional options [you do not have to choose any] • *One Item in Square Brackets*: You don't have to choose it.

```
[anchovies]
```

- *Square Brackets and Vertical Bars*: Choose *none or only one*.

```
[beans | rice | sweet_potatoes]
```

- *Square Brackets and Commas*: Choose *none, one, or more than one* option. If you choose more than one, separate your choices with commas.

```
[extra_cheese, avocados, sour_cream]
```

Ellipsis: Do it again (and again)... An ellipsis (...) means that you can *repeat* the last unit as many times as you like. In this syntax statement, `buy` is a required keyword:

```
buy thing = price [cash | check | credit]
[, thing = price [cash | check | credit]]...
```

You must buy at least one thing and give its price. You may choose a method of payment: one of the items enclosed in square brackets. You may also choose to buy additional things: as many of them as you like. For each thing you buy, give its name, its price, and (optionally) a method of payment.

Sybase certifications on the Web

Technical documentation at the Sybase Web site is updated frequently.

v **Finding the latest information on product certifications**

- 1 Point your Web browser to Technical Documents at <http://www.sybase.com/support/techdocs/>.
- 2 Select Products from the navigation bar on the left.
- 3 Select a product name from the product list and click Go.
- 4 Select the Certification Report filter, specify a time frame, and click Go.
- 5 Click a Certification Report title to display the report.

v **Creating a personalized view of the Sybase Web site (including support pages)**

Set up a MySybase profile. MySybase is a free service that allows you to create a personalized view of Sybase Web pages.

- 1 Point your Web browser to Technical Documents at <http://www.sybase.com/support/techdocs/>.
- 2 Click MySybase and create a MySybase profile.

Sybase EBFs and software updates

v **Finding the latest information on EBFs and software updates**

- 1 Point your Web browser to the Sybase Support Page at <http://www.sybase.com/support>.
- 2 Select EBFs/Updates. Enter user name and password information, if prompted (for existing Web accounts) or create a new account (a free service).
- 3 Select a product.
- 4 Specify a time frame and click Go.
- 5 Click the Info icon to display the EBF/Update report, or click the product description to download the software.

If you need help

Each Sybase installation that has purchased a support contract has one or more designated people who are authorized to contact Sybase Technical Support. If you cannot resolve a problem using the manuals or online help, please have the designated person contact Sybase Technical Support or the Sybase subsidiary in your area.

Introduction

Enhanced Full-Text Search Specialty Data Store (referred to in this book as the Enhanced Full-Text Search engine) is an Open Server™ application built on the Verity technology that is available in the Verity Developer’s Kit. Adaptive Server connects to the Enhanced Full-Text Search engine through Component Integration Services (CIS), allowing queries written in the Verity query language to perform full-text searches on Adaptive Server data.

This book describes the features and functionality of the Enhanced Full-Text Search Specialty Data Store.

Topic	Page
Capabilities of the Enhanced Full-Text Search Engine	1
High availability	3

Capabilities of the Enhanced Full-Text Search Engine

The Enhanced Full-Text Search Specialty Data Store product performs powerful, full-text searches on Adaptive Server data. In Adaptive Server, without the Enhanced Full-Text Search engine, you can search text columns only for data that matches what you specify in a select statement. For example, if a table contains documents about dog breeds, and you perform a search on the words “Saint Bernard,” the query produces only the rows that include “Saint Bernard” in the text column.

With the Enhanced Full-Text Search engine, you can expand queries on text columns to:

- Rank the results by order of how often a searched item appears in the selected document. For example, you can obtain a list of document titles that reference the words “Saint Bernard” five or more times.

- Select documents in which the words you search for appear within n number of words of each other. For example, you can search only for the documents that include the words “Saint Bernard” and “Swiss Alps” and that appear within 10 words of each other.
- Select documents that include all the search elements you specify within a single paragraph or sentence. For example, you can query the documents that include the words “Saint Bernard” in the same paragraph or sentence as the words “Swiss Alps.”
- Select documents that contain one or more synonyms of the word you specify. For example, you can select documents that discuss “dogs,” and it returns documents that contain the words “dogs,” “canine,” “pooch,” “pup,” and so on.
- Create your own custom thesaurus. For example, you can create a custom thesaurus that includes “working dogs,” “St. Bernard,” “large dogs,” and “European Breeds” as synonyms for “Saint Bernard.”
- Create topics that specify the search criteria for a query. For example, you can create a topic that returns documents that include the phrase “Saint Bernard” or “St. Bernard,” followed by documents that include the phrase “working dogs,” “large dogs,” or “European Breeds.”
- Return documents grouped in clusters to give you a sense of the major topics covered in the documents.
- Select a section of relevant text in a document and search for other, similar documents.
- Index many different document types, such as Microsoft Word, and FrameMaker.
- Sort documents using up to 16 sort orders.
- Integrate backup and restore capabilities.
- Change the value of a configuration parameter using a system procedure.
- Optimize indexes for text searches when your server is inactive, to enhance performance.
- Create additional system management reports for viewing setup information.
- Ability to bring databases online automatically for text searches.

High availability

The Enhanced Full-Text Search product supports Sybase Failover. If an Adaptive Server fails, the Enhanced Full-Text Search accepts connections from the companion server. Additionally, if the Adaptive Server has proxy database support enabled, then both the primary and companion servers can use the Enhanced Full-Text Search at the same time.

Understanding the Enhanced Full-Text Search Engine

This chapter describes how an Enhanced Full-Text Search engine works.

Topic	Page
Components of the Enhanced Full-Text Search engine	5
How a full-text search works	10

Components of the Enhanced Full-Text Search engine

The Enhanced Full-Text Search engine uses the following components to provide full-text search capabilities:

- Source table
- Verity collections (text index)
- Filters for a variety of document types
- text_db database
- Index table
- text_events table

The source table

The **source table** is a user table maintained by Adaptive Server. It contains one or more columns using the date, time, text, image, char, varchar, datetime, or small datetime datatype, which holds the data to be searched. With the Enhanced Full-Text Search engine, the source table can also have int, smallint, and tinyint columns, which holds the data to be searched. The source table must have an IDENTITY column, which is used to join the source table with the id column of an index table during text searches.

The source table can be a local table, which holds the actual data, or it can be a proxy table that is mapped to remote data using CIS.

The Verity collections

The Enhanced Full-Text Search engine uses the Verity collections, which are located in `$$SYBASE/$SYBASE_FTS/collections`. When you create the text indexes, as described in “Creating the text index and index table” on page 20, Verity creates a **collection**, which is a directory that implements a text index. This collection is queried by the Enhanced Full-Text Search engine. For more information about Verity collections, see the Verity Web site at <http://www.verity.com>.

Filters

The text index uses a filter to strip out the tags in a document that are not ASCII text. The Enhanced Full-Text Search engine provides filters for a variety of document types (Microsoft Word, PDF, WordPerfect, SGML, and HTML).

The *text_db* database

During the installation of the Enhanced Full-Text Search engine, a database named `text_db` is added to Adaptive Server using the installation script `installtextserver`, as described in “Running the `installtextserver` script” on page 14. The database does not contain any user data, but contains two support tables: `vesaux` and `vesauxcol`. These tables contain the metadata used by the Enhanced Full-Text Search engine to maintain integrity between the Adaptive Server source tables and the Verity collections.

When updating the collections after an insert, update, or delete is made to an indexed column, the Enhanced Full-Text Search engine queries the `vesaux` and `vesauxcol` tables. These tables determine which collections contain the modified columns so that all affected collections are updated. The Enhanced Full-Text Search engine also uses these tables when it is brought online, to make sure that all necessary collections exist.

The *vesaux* table

The columns in the `vesaux` table are described in Table 2-1.

Table 2-1: Columns in the vesaux table

Column name	Description
id	IDENTITY column
object_name	Name of the source table on which the external index is being created
option_string	Text index creation options
collection_id	Name of the Verity collection
key_column	Name of the IDENTITY column in the source table
svrid	Server ID of the Enhanced Full-Text Search engine maintaining the collection

The vesauxcol table

The columns in the vesauxcol table are described in Table 2-2.

Table 2-2: Columns in the vesauxcol table

Column name	Description
id	ID of the referenced row in the vesaux table
col_name	Name of the column for which you are searching
col_type	Column type (date, time, text, image, char, varchar, datetime, smalldatetime; with the Enhanced Full-Text Search engine, also int, smallint, and tinyint)

The index table

The **index table** provides a means of locating and searching documents stored in the source table. The index table is maintained by the Enhanced Full-Text Search engine and has an id column that maps to the IDENTITY column of the corresponding source table. The IDENTITY value from the row in the source table is stored with the data in the Verity collections, which allows the source and index tables to be joined. Although the index table is stored and maintained by the Enhanced Full-Text Search engine, it functions as a proxy table to Adaptive Server through Component Integration Services.

The index table contains special columns, called *pseudo columns*, that are used by the Enhanced Full-Text Search engine to determine the parameters of the search and the location of the text data in the source table. Pseudo columns have no associated physical storage—the values of a pseudo column are valid only for the duration of the query and are removed immediately after the query finishes running.

For example, when you use the `score` pseudo column in a query, to rank each document according to how well the document matches the query, you may have to use a *score* of 15 to find references to the phrase “small Saint Bernards” in the text database. This phrase does not occur very often, and a low *score* value broadens the search to include documents that have a small number of occurrences of the search criteria. However, if you are searching for a phrase that is common, like “large Saint Bernards,” you could use a *score* of 90, which would limit the search to those documents that have many occurrences of the search criteria.

You use the `score` column and the other pseudo columns, `id`, `index_any`, `sort_by`, `summary`, and `max_docs`, to specify the parameters to include in your search. For a description of the pseudo columns, see “Pseudo columns in the index table” on page 44.

The `text_events` table

Each database containing tables for which there is a text index must contain an **events table**, which logs inserts, updates, and deletes to indexed columns. The name of this table is `text_events`. It is used to propagate updated data to the Verity collections.

The columns in the `text_events` table are described in Table 2-3.


Table 2-3: Columns in the `text_events` table

Column name	Description
<code>event_id</code>	IDENTITY column
<code>id</code>	ID of the row that was updated, inserted, or deleted
<code>tableid</code>	Name of the table that contains the row that was updated, inserted, or deleted
<code>columnid</code>	Name of the column on which the text index was created
<code>event_date</code>	Date and time of the update, insert, or delete
<code>event_type</code>	Type of update (update, insert, or delete)
<code>event_status</code>	Indicates whether the update, insert, or delete has been propagated to the collections. <ul style="list-style-type: none"> • 0 – Event Unread • 1 – Event Read • 2 – Event Succeeded • 3 – Event Failed
<code>srvid</code>	Server ID of the Enhanced Full-Text Search engine maintaining the collection

Relationships between the components

The relationships between the Enhanced Full-Text Search engine components are shown in Figure 2-1.

Figure 2-1: Components of the Enhanced Full-Text Search engine



How a full-text search works

To perform a full-text search, you enter a select statement that joins the IDENTITY column from the source table with the id column of the index table, using pseudo columns as needed to define the search. For example, the following query searches for documents in the blurbs table of the pubs2 database in which the word “Greek” appears near the word “Gustibus” (the i_blurbs table is the index table):

```
select t1.score, t2.copy
from i_blurbs t1, blurbs t2
where t1.id=t2.id and t1.score > 20
and t1.max_docs = 10
and t1.index_any = "<near>(Greek, Gustibus)"
```

Adaptive Server and the Enhanced Full-Text Search engine split the query processing, as follows:

- 1 The Enhanced Full-Text Search engine processes the query:

```
select t1.score, t1.id
from i_blurbs t1
where t1.score > 20
and t1.max_docs = 10
and t1.index_any = "<near>(Greek, Gustibus)"
```

The select statement includes the Verity operator near and the pseudo columns score, max_docs, and index_any. The operator and pseudo columns provide the parameters for the search on the Verity collections—they narrow the result set from the entire copy column to the 10 documents in which the words “Greek” and “Gustibus” appear closest to each other.


- 2 Adaptive Server processes the following select statement on the result set that is returned by the Enhanced Full-Text Search engine in step 1:

```
select t1.score, t2.copy
from i_blurbs t1, blurbs t2
where t1.id=t2.id
```

This joins the blurbs and i_blurbs tables (the source table and the index table, respectively) on the IDENTITY column of the blurbs table and the id column of the i_blurbs table.

Figure 2-2 describes how Adaptive Server and the Enhanced Full-Text Search engine process the query.

Figure 2-2: Processing a full-text search query



1. Adaptive Server sends the index query to the Enhanced Full-Text Search engine.
2. The Enhanced Full-Text Search engine processes the Verity operators in the query and produces a result set from the collections.
3. The Enhanced Full-Text Search engine returns the result set to Adaptive Server.
4. Adaptive Server processes the select statement on the local table.
5. Adaptive Server displays the results of the query.

Configuring Adaptive Server for Full-Text Searches

This chapter describes how to configure Adaptive Server to perform full-text searches.

Topic	Page
Configuring Adaptive Server for an Enhanced Full-Text Search engine	13
Creating and maintaining text indexes	19

Configuring Adaptive Server for an Enhanced Full-Text Search engine

The Enhanced Full-Text Search engine is a remote server that Adaptive Server connects to through Component Integration Services (CIS). Before you can use the Enhanced Full-Text Search engine, you must configure Adaptive Server for the Enhanced Full-Text Search engine as follows:

- Enable the enable cis, cis rpc handling and full-text search configuration parameters if you have not done so. You need a license to enable full-text search.
- Run the installtextserver script to define one or more Enhanced Full-Text Search engines.
- Run the installmessages script to install messages for the Enhanced Full-Text Search engine's system procedures.
- Run the installevent script to create the text_events table in each user database that will contain text indexes.
- Name the local server and restart.

Enabling configuration parameters

To connect to the Enhanced Full-Text Search engine, Adaptive Server must be running with the `enable cis` and `cis rpc handling` configuration parameters enabled. If those parameters are not enabled, log in to Adaptive Server using `isql` and use `sp_configure` to enable them. For example:

```
exec sp_configure "enable cis", 1
exec sp_configure "cis rpc handling", 1
exec sp_configure "enable full-text search", 1
```

If you have made changes to enable `cis`, messages display stating that you must restart Adaptive Server for the new configuration parameter to take effect.

Running the *installtextserver* script

The `installtextserver` script:

- Defines the Enhanced Full-Text Search engine as a remote server of server class `sds` to Adaptive Server.
- Creates a database for storing text index metadata. For more information about this database, see “The `text_db` database” on page 6.
- Installs the system procedures required by the Enhanced Full-Text Search engine.

Run the `installtextserver` script only once (see “Starting the `installtextserver` script” on page 16). To add Enhanced Full-Text Search engines at a later time, use `sp_addserver`. See “Configuring multiple Enhanced Full-Text Search engines” on page 84 for more information about `sp_addserver`.

Note If you are putting the *installtextserver* script onto the model database, you must increase the size of the model database to at least 3MB prior to running the script.

All Enhanced Full-Text Search engines use the same database for storing text index metadata. This database is referred to as the `text_db` database, the default name.

For a list and description of the system procedures added with the `installtextserver` script, see Appendix A, “System Procedures.”

Editing the *installtextserver* script

The *installtextserver* script is located in the `$SYBASE/$SYBASE_FTS/scripts` directory. Use a text editor (such as `vi` or `emacs`) to open the script, and make your edits. The edits you can make are as follows:

- Changing the name of the `text_db` database. If you use a different name, replace all occurrences of `text_db` with the appropriate name.

Note If you change the name of the *text_db* database, you must also change the name in the `defaultDb` configuration parameter (see “Modifying the configuration parameters” on page 67).

- Changing the name of the Enhanced Full-Text Search engine. By default, the *installtextserver* script defines a Enhanced Full-Text Search engine named “`textsvr`.” If your Enhanced Full-Text Search engine is named differently, edit this script so that it defines the correct server name.
- Adding multiple Enhanced Full-Text Search engines (for information on how this can enhance performance, see “Configuring multiple Enhanced Full-Text Search engines” on page 84). If you are initially defining more than one Enhanced Full-Text Search engine, edit the *installtextserver* script so that it includes all the Enhanced Full-Text Search engine definitions. *installtextserver* includes the following section for naming the Enhanced Full-Text Search engine you are configuring (“`textsvr`” by default):

```
/*
** Add the text server
*/
exec sp_addserver textsvr,sds,textsvr
go
```

Add an entry for each Enhanced Full-Text Search engine you are configuring. For example, if you are configuring three Enhanced Full-Text Search engines named `KRAZYKAT`, `OFFICAPUP`, and `MOUSE`, replace the default “`textsvr`” line with the following lines:

```
exec sp_addserver KRAZYKAT, sds, KRAZYKAT
exec sp_addserver OFFICAPUP, sds, OFFICAPUP
exec sp_addserver MOUSE, sds, MOUSE
go
```

- If you use OmniConnect to communicate with the Enhanced Full-Text Search engine, change the server name specification in the `sp_addobjectdef` calls for the `vesaux` and `vesauxcol` tables to a valid remote server. For example, if your remote server is named `REMOTE`, change the lines:

```
exec sp_addobjectdef
"vesaux", "SYBASE.master.dbo.vesaux", "table"
exec sp_addobjectdef
"vesauxcol", "SYBASE.master.dbo.vesauxcol",
"table"
```

to:

```
exec sp_addobjectdef
"vesaux", "REMOTE.master.dbo.vesaux", "table"
exec sp_addobjectdef
"vesauxcol", "REMOTE.master.dbo.vesauxcol",
"table"
```

Starting the *installtextserver* script

Use `isql` to run the `installtextserver` script. For example, to run the `installtextserver` script in an Adaptive Server named `MYSVR`, enter:

```
isql -Usa -P -SMYSVR -i
$$SYBASE/$SYBASE_FTS/scripts/installtextserver
```

Running the *installmessages* script

The Enhanced Full-Text Search engine has its own set of system procedure messages that you must install in Adaptive Server. Use the `installmessages` script to install the messages. You run the `installmessages` script only once, even if you have multiple Enhanced Full-Text Search engines.

For example, to run the `installmessages` script in a server named `MYSVR`, enter:

```
isql -Usa -P -SMYSVR -i
$$SYBASE/$SYBASE_FTS/scripts/installmessages
```


Running the *installevent* script

Each database containing tables referenced by a text index must contain a `text_events` table, which logs inserts, updates, and deletes to indexed columns. It is used to propagate updated data to the Verity collections.

Run the `installevent` script, as described below, to create the `text_events` table and associated system procedures in a database. Use the `installevent` script as follows:

- If all databases require text indexes, run the `installevent` script to create a `text_events` table in the model database. Each newly created database will then have a `text_events` table. To add a `text_events` table to existing databases, edit the script as described below to create the `text_events` table in the existing user database.
- If not all databases have text indexes, use the `installevent` script as a sample. For each existing database and each new database that includes tables that require text indexing, run the `installevent` script. You must edit the script as described below, to create the `text_events` table in the correct user database.

Note If a `text_events` table does not exist in a database that includes source tables that require text indexing, changes to the source table are not propagated to the Verity collections.

Editing the *installevent* script

The `installevent` script is located in the `$$SYBASE/$$SYBASE_FTS/scripts` directory. Use a text editor (such as `vi` or `emacs`) to open the script, and make the edits. The edits you can make are:

- Changing the user database name. The `installevent` script creates an events table (named `text_events`) and associated system procedures in the model database. The model database is the default database. To install the `text_events` table in an existing user database, edit the script and replace all references to `model` with the user database name.

- Changing the text_db database name. If your database for storing text index metadata is named something other than text_db, replace all references to text_db with the appropriate name.

Note The name of the text_db database must be the same as the name in the defaultDb configuration parameter (see “Modifying the configuration parameters” on page 67).

Running the *installevent* script

Using isql, run the installevent script to install the text_events table and related system procedures in Adaptive Server. For example, to run the installevent script in a server named MYSVR, enter:

```
isql -Usa -P -SMYSVR -i
$SYBASE/$SYBASE_FTS/scripts/installevent
```

Note The text_db database must exist before you run the installevent script. If it does not exist, run the installtextserver script first.

Note Before installing the EFTS-12_5 scripts on 64-bit platforms(*installtextserver*, *installevents*, *installmessages*) increase the size of the tempdb and the model databases from the default size to 3MB each.

Name the local Adaptive Server

When using the Enhanced Full-Text Search engine with Adaptive Server 12.5 and later, you must name the local Adaptive Server using sp_addserver <servername>, local. After issuing sp_addserver, you must restart the local Adaptive Server. Do not install any system stored procedures in the model database. They should be installed in sybssystemprocs.

Creating and maintaining text indexes

Before the Enhanced Full-Text Search engine can process full-text searches, you must create text indexes for the source tables in the user database. After the text indexes are created, you must update them when the source data changes to keep the text indexes current. To create and maintain the text indexes:

- 1 Set up the source table for indexing (see “Setting up source tables for indexing” on page 19).
- 2 Create the text indexes and index tables (see “Creating the text index and index table” on page 20).
- 3 Bring the databases online for full-text searches (see “Bringing the database online for full-text searches” on page 22).
- 4 Propagate changes in the user data to the text indexes (see “Propagating changes to the text index” on page 23).
- 5 If you are replicating text indexes, set up text indexing in the destination database (see “Replicating text indexes” on page 23).

For an example of setting up a text index, see the sample script `sample_text_main.sql` in the `$SYBASE/$SYBASE_FTS/sample/scripts` directory.

Setting up source tables for indexing

The source table contains the data on which you perform searches (for example, the `blurbs` table in the `pubs2` database). For more information, see “The source table” on page 5.

Before you can create text indexes on a source table, you must:

- Verify that the source table has an `IDENTITY` column
- Create a unique index on the `IDENTITY` column (optional)

Adding an IDENTITY column to a source table

Every source table must contain an IDENTITY column to uniquely identify each row and provide a means of joining the index table and the source table. When you create a text index, the IDENTITY column is passed with the indexed columns to the Enhanced Full-Text Search engine. The IDENTITY column value is stored in the text index and is mapped to the id column in the index table.

For example, to create an IDENTITY column in a table named `composers`, define the table as follows:

```
create table composers (  
    id          numeric(m,n)      identity,  
    comp_fname  char(30)          not null,  
    comp_lname  char(30)          not null,  
    text_col    text  
)
```

where $m \leq 38$ and n always = 0.

To add an IDENTITY column to an existing table, enter:

```
alter table table_name add id numeric(10,0) identity
```

Adding a unique index to an IDENTITY column

For optimum performance, Sybase recommends that you create a unique index on the IDENTITY column. For example, to create a unique index named `comp_id` on the IDENTITY column created above, enter:

```
create unique index comp_id  
on composers(id)
```

For more information about creating a unique index, see Chapter 11, “Creating Indexes on Tables,” in the *Transact-SQL User’s Guide*.

Creating the text index and index table

Use `sp_create_text_index` to create text indexes. `sp_create_text_index`:

- Updates the `vesaux` and `vesauxcol` tables in the `text_db` database
- Creates the text index (Verity collections)
- Populates the Verity collections

- Creates the index table in the user database where the source table is located

Note The Enhance Full-Text Search engine must be running to successfully execute `sp_create_text_index`. For information on starting and stopping the Enhanced Full-Text Search engine, see Chapter 6, “System Administration.”

The text index can contain up to 16 columns. Columns of the following datatypes can be indexed: `char`, `varchar`, `nchar`, `nvarchar`, `date`, `time`, `image`, `datetime`, `smalldatetime`, `int`, `smallint`, `tinyint`, `unichar`, and `univarchar`.

For example, to create a text index and an index table named `i_blurbs` for the `copy` column in the `blurbs` table in `pubs2` on `KRAZYKAT`, enter:

```
sp_create_text_index "KRAZYKAT", "i_blurbs", "blurbs", " ", "copy"
```

where:

- `KRAZYKAT` is the name of the Enhanced Full-Text Search engine.
- `i_blurbs` is the name of the index table and text index you are creating.
- `blurbs` is the source table on which you are creating the text indexes.
- `" "` is a placeholder for text index creation options.
- `copy` is the column in the `blurbs` table that you are indexing.

See `sp_create_text_index` on page 140 for more information.

Note Make sure the `text_db` database name in the configuration file (listed after the `defaultDb` parameter) matches the database name in Adaptive Server. If they do not match, the text index cannot be created. Also, verify that the `text_events` table exists in the user database. If it does not exist, run the `installevent` script for that database (see to “Running the `installevent` script” on page 17).

Populating the Verity collections can take a few minutes or several hours, depending on the amount of data you are indexing. You may want to perform this step when the server is not being heavily used. Increasing the `batch_size` configuration parameter also expedites the process. See “`batch_size`” on page 82 for more information.

Note Do not rename an index; the Verity collection will not be renamed.

Specifying multiple columns when creating a text index

When you create a text index on two or more columns, each column in the text index is placed into its own document zone. The name of the zone is the name of the column. For example, to create a text index and an index table named `i_blurbs` for both the `copy` column and the `au_id` column in the `blurbs` table in `pubs2` on `KRAZYKAT`, enter:

```
sp_create_text_index "KRAZYKAT", "i_blurbs", "blurbs", " ", "copy", "au_id"
```

`sp_create_text_index` creates two zones in the text index named “`copy`” and “`au_id`.” When you issue a query against the `i_blurbs` text index, the search includes the `copy` and `au_id` columns. However, you can limit your search to a particular column by using the `in` operator to specify a document zone (for more information, see “`in`” on page 53).

Bringing the database online for full-text searches

With the Enhanced Full-Text Search engine, the database is automatically brought online when the `auto_online` configuration parameter is set to 1.

When you bring a database online, the Enhanced Full-Text Search engine initializes the internal Verity structures and confirms that the Verity collections exist.

Use `sp_text_online` to bring a database online for full-text searches if it is not automatically brought online. For example, to bring the `pubs2` database online before issuing full-text searches on the `blurbs` table in a Enhanced Full-Text Search engine named `KRAZYKAT`, enter:

```
sp_text_online KRAZYKAT, pubs2
```

This message appears:

```
Database 'pubs2' is now online
```

The `pubs2` database is now available for performing full-text searches.

See `sp_text_online` on page 156 for more information.

Propagating changes to the text index

When you insert, update, or delete data in your source table, the text indexes are not updated automatically. After you update data, run `sp_refresh_text_index` to log the changes to the `text_events` table. Then, run `sp_text_notify` to notify the Enhanced Full-Text Search engine that changes need to be processed. The Enhanced Full-Text Search engine then connects to Adaptive Server, reads the entries in the `text_events` table, determines which indexes, tables, and rows are affected, and updates the appropriate collections.

See `sp_refresh_text_index` on page 145 and `sp_text_notify` on page 155 for more information on these system procedures.

To have `sp_refresh_text_index` run automatically after each insert, update, or delete, you can create triggers on your source tables, as follows:

- Create a trigger that runs `sp_refresh_text_index` after a delete operation.
- Create a trigger that runs `sp_refresh_text_index` after an insert operation.
- Create a trigger that runs `sp_refresh_text_index` after an update operation to an indexed column.

Triggers are not fired when you use `writetext` to update a text column. To have `sp_refresh_text_index` automatically run after a `writetext`:

- Set up a non-text column and update that column after each `writetext`.
- Create a trigger on the non-text column to run `sp_refresh_text_index`. Since the Enhanced Full-Text Search engine reinserts the entire row when you issue `sp_text_notify`, the update to the text column gets propagated to the text index.

For examples of each of these triggers, see the sample script `sample_text_main.sql` in the `$$SYBASE/$$SYBASE_FTS/sample/scripts` directory.

Replicating text indexes

To replicate tables that have text indexes, follow these guidelines:

- Create the table definition in the destination database.
- Run the `installevnt` script to create the `text_events` table in the destination database, if the `text_events` table does not already exist (see “Running the `installevnt` script” on page 17).

- Run `sp_create_text_index` to create the text index on the empty table in the destination database (see “Creating the text index and index table” on page 20).
- Create triggers for running `sp_refresh_text_index` to insert entries into the `text_events` table whenever you insert, update, or delete data into the table (see “Propagating changes to the text index” on page 23).
- Create the replication definition in the Replication Server. This replicates all the data in the source table to the destination table. See the *Replication Server Administration Guide* for more details.
- Run `sp_text_notify` to update the text index; run `sp_text_notify` periodically to process changes to the destination table (see “Propagating changes to the text index” on page 23).

Note You must issue an update against a non-text column whenever a `writetext` command is performed. This ensures that the trigger that inserts data into the `text_events` table is fired.

Example: enabling a new database for text searches

This example describes the steps for creating a text index on the `plot` column of the `reviews` table in the `movies` database. This process assumes that:

- You have created a `reviews` table in a new database named `movies` on the `MYSVR` server
- The `reviews` table has a column named `plot` that you are going to index
- Adaptive Server and the Enhanced Full-Text Search engine named `MYTXTSVR` have been configured to connect to each other

Step 1. Verifying that the `text_events` table exists

Each database containing tables referenced by a text index must contain a `text_events` table, which logs inserts, updates, and deletes to indexed columns.

If a `text_events` table is in your model database, it will be in all new databases. If a `text_events` table is not in your model database, run the `installevent` script to install the `text_events` table in the new database. For example, to install the `text_events` table in the `movies` database:

- Save the `installevent` script as `installeventmovies`.

- Edit the script to replace all references to the word *model* with the word *movies*.
- Run the script as follows:

```
isql -Usa -P -SMYSVR -i
$SYBASE/$SYBASE_FTS/scripts/installeventmovies
```

See “Running the installevent script” on page 17 for information on installing the `text_events` table.

Step 2. Checking for an IDENTITY column

Every source table must contain an IDENTITY column, which uniquely identifies each row and provides a means of joining the index table and the source table.

For example, to add an IDENTITY column to the reviews table, enter:

```
alter table reviews add id numeric(10,0) identity
```

See “Adding an IDENTITY column to a source table” on page 20 for more information.

Step 3. Creating a unique index on the IDENTITY column

This step is optional. To enhance performance, Sybase recommends that you create a unique index that contains only the IDENTITY column. For example, to create a unique index named `reviews_id` on the IDENTITY column created in the previous procedure, issue:

```
create unique index reviews_id on reviews(id)
```

For more information about creating a unique index, see Chapter 11, “Creating Indexes on Tables,” of the *Transact-SQL User’s Guide*.

Step 4. Creating the text index and index table

The source tables in the user database must be indexed so that you can perform full-text searches. For example, to create a text index and an index table named `reviews_idx` for the plot column in the reviews table, enter:

```
sp_create_text_index "MYTXTSVR", "reviews_idx",
"reviews", " ", "plot"
```

The reviews table is now available for running full-text searches.

See `sp_create_text_index` on page 140 for more information.

Step 5. Bringing the database online for a full-text search

To bring the movies database online for the Enhanced Full-Text Search engine named MYTXTSVR, enter:

```
sp_text_online MYTXTSVR, movies
```

Note Omit this step if you have auto_online set to “1”.

See sp_text_online on page 156 for more information.

Indexing the euro symbol

The euro symbol can be indexed and returned properly if the following configuration guidelines are followed. Adaptive Server must have the utf8 charset installed. Enhanced Full-Text Search must have the vdkLanguage set to <language>x and the vdkCharset left blank. For example:

```
ASE 12.5.x charset = utf8
EFTS 12.5.x vdkLanguage = englishx
EFTS 12.5.x vdkCharset =
```

Setting Up Verity Functions

This chapter describes the setup required before you can write queries with certain Verity functionality.

Topic	Page
Enabling query-by-example, summarization, and clustering	27
Setting up a column to use as a sort specification	30
Using filters on text that contains tags	32
Creating a custom thesaurus	34
Creating topics	38

Enabling query-by-example, summarization, and clustering

The *style.prm* file specifies additional data to include in the text indexes to support the following functionality:

- Query-by-example – retrieves documents that are similar to a phrase (see “like” on page 54 for more information).

Note The text indexes need additional data to support phrases in the query-by-example specification of the like operator. If you use a document in the query-by-example specification, additional data is not required.

- Summarization – returns summaries of documents rather than entire documents (see “Using the summary column to summarize documents” on page 47 for more information).
- Clustering – groups documents in result sets by subtopic. See “Using pseudo columns to request clustered result sets” on page 48 for more information.

You can enable these features for all text indexes by editing the master *style.prm* file, or you can enable them for an individual text index by editing its *style.prm* file. Both methods are described below.

Query-by-example
and clustering

To use phrases in a query-by-example specification and to use clustering, you must enable the generation of document feature vectors at indexing time. To do this, uncomment the following line in the *style.prm* file:

```
$define DOC-FEATURES "TF"
```

Summarization

To configure the Enhanced Full-Text Search engine for summarization, uncomment one of the following lines that starts with “#\$define” in the *style.prm* file:

```
# The example below stores the best three sentences of
# the document, but not more than 255 bytes.
#$define DOC-SUMMARIES "XS MaxSents 3 MaxBytes 255"
# The example below stores the first four sentences of
# the document, but not more than 255 bytes.
#$define DOC-SUMMARIES "LS MaxSents 4 MaxBytes 255"
# The example below stores the first 150 bytes of
# the document, with whitespace compressed.
#$define DOC-SUMMARIES "LB MaxBytes 150"
```

Each of those lines reflects a different level of summarization. You can specify how many bytes of data you want the Enhanced Full-Text Search engine to display, by altering the numbers at the ends of these lines. For example, if you want only the first 233 bytes of data summarized, edit the script to read:

```
$define DOC-SUMMARIES "LS MaxSents 4 MaxBytes 233"
```

The maximum number of bytes displayed is 255. Any number greater than that is truncated to 255.

Editing the master *style.prm* file

The master *style.prm* file is located in `$SYBASE/$SYBASE_FTS/verity/common/style`. It contains the default Enhanced Full-Text Search engine style parameters. Edit this file to configure the Enhanced Full-Text Search engine so that all tables on which you create text indexes allow clustering and literal text in your query-by-example specifications, or summarization. Uncomment the applicable lines as described above.

Note If you have existing text indexes, you must re-create the text index with these features enabled as described in “Editing individual *style.prm* files” on page 29.

Editing individual *style.prm* files

Perform the following steps to configure the Enhanced Full-Text Search engine so that the individual text index allows clustering and literal text in your query-by-example specifications, or summarization:

- 1 Create the text index using `sp_create_text_index`. Use the word “empty” in the *option_string* parameter so that the *style.prm* file is created for the text index, but the Verity collections are not populated with data. For example, if you are enabling clustering for the copy column of the blurbs table, use the following syntax:

```
sp_create_text_index "KRAZYKAT", "i_blurbs", "blurbs", "empty", "copy"
```

Note If the text index already exists, omit this step. You do not need to create the text index again.

- 2 Use `sp_drop_text_index` to drop the text index associated with the *style.prm* file you are editing.

For example, to drop the text index created in step 1, enter:

```
sp_drop_text_index "blurbs.i_blurbs"
```

- 3 Edit the *style.prm* file that exists for the text index. The *style.prm* file for an existing collection is located in `$SYBASE/$SYBASE_FTS/collections/db.owner.index/style`.

where *db.owner.index* is the database, the database owner, and the index created with `sp_create_text_index`. For example, if you create a text index called `i_blurbs` on the `pubs2` database, the full path to these files is `$$SYBASE/$SYBASE_FTS/collections/pubs2.dbo.i_blurbs/style`

- 4 Uncomment the applicable lines as described above.

For example, to enable clustering, uncomment the following line:

```
$define DOC-FEATURES "TF"
```

- 5 Re-create the text index you dropped in step 2. For example, to re-create the `i_blurbs` text index, enter:

```
sp_create_text_index "KRAZYKAT", "i_blurbs",  
"blurbs", "", "copy"
```

Setting up a column to use as a sort specification

Before you can sort by specific columns, you must modify the `style.vgw` and `style.ufl` files. (For information on including a column in a sort specification, see “Using the `sort_by` column to specify a sort order” on page 46.) Both files are in `$$SYBASE/$SYBASE_FTS/collections/db.owner.index/style`.

where *db.owner.index* is the database, the database owner, and the index created using `sp_create_text_index`. For example, if you created a text index called `i_blurbs` on the `pubs2` database, the full path to those files would be:

`$$SYBASE/$SYBASE_FTS/collections/pubs2.dbo.i_blurbs/style`

To edit the `style.vgw` and `style.ufl` files, follow these steps:

- 1 Drop the text index that contains the columns for which you are adding definitions. Dropping the text index does not drop the collection directory.

For example, to add definitions for the `copy` column in the `blurbs` table, use the following command to drop the text index:

```
sp_drop_text_index i_blurbs
```

- 2 Edit the `style.vgw` file. Following this line:

```
dda "SybaseTextServer"
```

add an entry for the column you are defining. The syntax is:

```
table: DOCUMENTS  
{
```

```

        copy: fcolumn_number copy_column_number
    }

```

where *column_number* is the number of the column you are defining. Column numbers start with 0; if you want the first column to be sorted, specify “f0”; to sort the second column, specify “f1”; to sort the third column, specify “f2”, and so on.

For example, to define the first column in a table, the syntax is:

```

table: DOCUMENTS
{
    copy: f0 copy_f0
}

```

Then, your *style.vgw* file will be similar to this:

```

#
#       Sybase Text Server Gateway
#
$control: 1
gateway:
{
    dda:    "SybaseTextServer"
    {
        copy: f0 copy_f0
    }
}

```

- 3 Edit the *style.ufl* file by adding the column definition for a data table named *fts*. The syntax is:

```

data-table:    fts
{
    fixwidth:    copy_fcolumn_number precision datatype
}

```

Column numbers start with 0; if you want the first column to be sorted, specify “f0”; to sort the second column, specify “f1”; to sort the third column, specify “f2”, and so on. For example, to add a definition for the first column of a table, with a precision of 4, and a datatype of date, enter:

```

data-table: fts
{
    fixwidth:    copy_f0    4    date
}

```

Similarly, to add a definition for the second column of a table with a precision of 10, and a datatype of character, enter:

```
data-table: fts
{
    fixwidth:      copy_f1   10   text
}
```

- 4 Re-create the index, using `sp_create_text_index`.

Using filters on text that contains tags

To perform accurate searches on documents that contain tags (such as HTML or Post Script), the text index must use a filter to strip out the tags. The Enhanced Full-Text Search engine provides filters for a variety of document types (Microsoft Word, FrameMaker, WordPerfect, SGML, HTML, and others).

When you create the text index to use a filter, the data for each type of tag in the document is placed into its own document zone. For example, if you have a tag called “chapter,” all chapter names are placed into one document zone. You can issue a query that searches the entire document, or that searches only for data in the “chapter” zone (for more information, see “in” on page 53).

To create a text index that uses a filter, modify the *style.dft* file for that text index:

- 1 Create the text index using `sp_create_text_index`. Use the word “empty” in the *option_string* parameter so that the *style.dft* file is created for the text index, but the Verity collections are not populated with data. For example, to create a text index for the copy column of the blurbs table, use the following syntax:

```
sp_create_text_index "KRAZYKAT", "i_blurbs", "blurbs", "empty", "copy"
```

- 2 Drop the text index that you create in step 1. This drops the text index, but not the *style.dft* file. For example, use the following command to drop the *i_blurbs* text index:

```
sp_drop_text_index i_blurbs
```

- 3 Edit the *style.dft* file. The *style.dft* file is in the directory `$$SYBASE/$SYBASE_FTS/collections/db.owner.index/style`, where *db.owner.index* is the database, the database owner, and the index created using `sp_create_text_index`. For example, if you created a text index called *i_blurbs* on the *pubs2* database, the full path to the *style.dft* file would be:


```
$SYBASE/$SYBASE_FTS/collections/pubs2.dbo.i_blurbs/style
```

Following this line:

```
field: f0
```

add syntax to use a filter:

- For SGML documents, use:

```
/filter="zone -nocharmap"
```

- For HTML documents, use:

```
/filter="zone -html -nocharmap"
```

Use the following syntax for all document types:

```
/filter="universal"
```

For example, your *style.dft* file for an SGML document will look like this:

```
$control: 1
dft:
{
    field: f0
        /filter="zone -nocharmap"
    field: f1
    field: f2
    .
    .
    field: f15
}
```

Your *style.dft* file for an SGML document will look like this:

```
$control: 1
dft:
{
    field: f0
        /filter="universal"
    field: f1
    field: f2
    .
    .
    field: f15
}
```

{

Note Use `getsend` to load the database with document data. `getsend` takes the following arguments: `database`, `table`, `column` and `row id`. Insert a null value for the `rowid` for each row of text you want to insert. `getsend` must insert into an `image` column for filtering to work. For more information on `getsend`, refer to the `README.TXT` file and `getsend.c` file in `$SYBASE/$SYBASE_FTS/sample/source` directory.

- 4 Re-create the index, using `sp_create_text_index`. For example:

```
sp_create_text_index "KRAZYKAT", "i_blurbs", "blurbs", "", "copy"
```

Creating a custom thesaurus

The Verity thesaurus operator expands a search to include the specified word and its synonyms (for information on using the thesaurus operator, see “thesaurus” on page 57). You can create a custom thesaurus that contains application-specific synonyms to use in place of the default thesaurus.

For example, the default English language thesaurus contains these words as synonyms for “money:” “cash,” “currency,” “lucre,” “wampum,” and “greenbacks.” You can create a custom thesaurus that contains a different set of synonyms for “money,” such as: “bid,” “tokens,” “credit,” “asset,” and “verbal offer.”

To create a custom thesaurus:

- 1 Make a list of the synonyms that you will use with your application. It may help to examine the default thesaurus (see “Examining the default thesaurus (optional)” on page 35).
- 2 Create a control file that contains the synonyms you are defining for your custom thesaurus (see “Creating the control file” on page 35).
- 3 Create the custom thesaurus using the `mksyd` utility (see “Creating the thesaurus” on page 37). The `mksyd` utility is located in `$SYBASE/$SYBASE_FTS/verity/<verity_platform_directory>/bin`.

This uses the control file as input.

- 4 Replace the default thesaurus with your custom thesaurus (see “Replacing the default thesaurus with the custom thesaurus” on page 37).

For more information on “Custom Thesaurus Support” and the `mksyd` utility, see the Verity Web site at <http://www.verity.com>.

Two sample files illustrate how to set up and use a custom thesaurus:

- `sample_text_thesaurus.ctl` is a sample control file.
- `sample_text_thesaurus.sql` issues queries against the custom thesaurus defined in the sample control file.

These files are in the `$SYBASE/$SYBASE_FTS/sample/scripts` directory.

Examining the default thesaurus (optional)

A control file contains all the synonym definitions for a thesaurus. To examine the default thesaurus, create its control file using the `mksyd` utility. The `mksyd` utility is located in `$SYBASE/$SYBASE_FTS/verity/<verity_platform_directory>/bin`.

Use the syntax:

```
mksyd -dump -syd
$SYBASE/$SYBASE_FTS/verity/common/vdkLanguage/vdk20
.syd -f work_location/control_file.ctl
```

where:

- `vdkLanguage` – is the value of the `vdkLanguage` configuration parameter (for example, “english”).
- `work_location` – is the directory where you want to place the control file.
- `control_file` – is the name of the control file you are creating from the default thesaurus.

To view the default synonym lists, examine the control file (`control_file.ctl`) that is created.

Creating the control file

Create a control file that contains the new synonyms for your custom thesaurus. The control file is an ASCII text file in a structured format. Using a text editor (such as `vi` or `emacs`), either:

- Edit the control file from the default thesaurus and add new synonyms to the existing thesaurus (see “Examining the default thesaurus (optional)” on page 35), or
- Create a new control file that includes only your synonyms.

Control file syntax

The control file contains synonym list definitions in a `synonyms: statement`. For example, the following is a control file named `colors.ctl`:

```
$control: 1
synonyms:
{
list: "red, ruby, scarlet, fuchsia,\
magenta"
list: "electric blue <or> azure"
/key = "lapis"
}
$$
```

The `synonyms: statement` includes:

- `list`: keywords that specify the start of a synonym list. The synonyms in the list are either in query form or in a list of words or phrases separated by commas.
- Each `list`: can optionally have a `/key` modifier that specifies one or more keys separated by commas. In the example above, no keys are specified in the first “list.” This means the list is found when the thesaurus is queried for the word “red,” “ruby,” “scarlet,” “fuchsia,” or “magenta.” The second “list” uses the `/key` modifier to specify one key. This means the words or phrases in the list satisfy a query only when you specify `<thesaurus>lapis`.

Note If you use `emacs` to build a synonym list and any of your lists are longer than one line, turn off auto-fill mode. If you separate your list into multiple lines, include a backslash (`\`) at the end of each line so that the lines are treated as one list.

For more complex examples of control files, see the Verity Web site.

Creating the thesaurus

The `mksyd` utility creates the custom thesaurus using a control file as input. It is located in:

```
$$SYBASE/$SYBASE_FTS/verity/<verity_platform_directory>/bin
```

Run, or define an alias to run, `mksyd` from this `bin` directory. Create your custom thesaurus in any work directory.

The `mksyd` syntax for creating a custom thesaurus is:

```
mksyd -f control_file.ctl -syd custom_thesaurus.syd
```

where:

- `control_file` – is the name of the control file you created in the previous section.
- `custom_thesaurus` – is the name of the custom thesaurus you are creating.

For example, to execute the `mksyd` utility reading the sample control file defined above, and directing output to a work directory, use:

```
mksyd -f /usr/u/sybase/dba/thesaurus/colors.ctl
-syd /usr/u/sybase/dba/thesaurus/custom.syd
```

Replacing the default thesaurus with the custom thesaurus

The default thesaurus named `vdk20.syd` is located in `$$SYBASE/$SYBASE_FTS/verity/common/vdkLanguage`, where `vdkLanguage` is the value of the `vdkLanguage` configuration parameter (for example, the English directory is `$$SYBASE/$SYBASE_FTS/verity/common/english`). Each application and user reading from this location at runtime uses this thesaurus. To replace it with your custom thesaurus:

- 1 Back up the default thesaurus before replacing it with the custom thesaurus. For example:

```
mv /$$SYBASE/$SYBASE_FTS/verity/common/english/vdk20.syd default.syd
```

- 2 Replace the `vdk20.syd` file with your custom thesaurus. For example:

```
cp custom.syd /$$SYBASE/$SYBASE_FTS/verity/common/english/vdk20.syd
```

- 3 Restart your Examine the control file (`control_file.ctl`); no configuration file changes are required. The thesaurus is read from this location when the Examine the control file (`control_file.ctl`) is started, not when a query is executed.

Queries using the thesaurus operator will now use the custom thesaurus.

Creating topics

This section provides a condensed overview of Verity topics. Topics are discussed in detail in Chapter 8, “Verity Topics.”

A topic is a grouping of information related to a concept or subject area. With topic definitions in place, a user can perform searches on the topic instead of having to write queries with complex syntax.

The user creates topics, which can be combinations of words and phrases, Verity operators and modifiers, and weight values. Then, any user can query the topic.

Before you create topics, determine your application requirements, and establish standards for naming conventions and for the location of the following:

- Outline files – contains the topic definitions. Each topic has its own outline file.
- Topic set directories – contains the compiled topic. Each topic has its own topic set directory.
- Knowledge base map file – contains pointers to the topic set directories.

To implement topics, perform the following steps:

- 1 Create one or more outline input files to define your topics (see “Creating an outline file” on page 39). Each outline file is used to populate one topic set.
- 2 Create and populate a topic set directory, using the `mktopics` utility (see “Creating a topic set directory” on page 40). The `mktopics` utility is located in `$$SYBASE/$$SYBASE_FTS/verity/<verity_platform_directory>/bin`.
Each topic set directory is populated based on one topic outline input file.
- 3 Create a *knowledge base map*, specifying the locations of one or more topic set directories (see “Creating a knowledge base map” on page 40).
- 4 Set the `knowledge_base` configuration parameter to point to the location of the knowledge base map (see “Defining the location of the knowledge base map” on page 41).

5 Execute queries against defined topics.

The following sample files illustrate the topics feature:

- *sample_text_topics.otl* is a sample outline file.
- *sample_text_topics.kbm* is a sample knowledge base map.
- *sample_text_topics.sql* issues queries using defined topics.

These files are in the `$SYBASE/$SYBASE_FTS/sample/scripts` directory.

Creating an outline file

A topic outline file specifies all the combinations of words and phrases, Verity operators and modifiers, and weight values that the search engine uses when you issue a query using the topic. The outline file is an ASCII text file in a structured format.

For example, the following outline file defines the topic “saint-bernard”:

```
$control: 1
saint-bernard <accrue>
*0.80 "Saint Bernard"
*0.80 "St. Bernard"
* "working dogs"
* "large dogs"
* "European breeds"
$$
```

When you issue a query specifying the topic “saint-bernard”, the Enhanced Full-Text Search engine:

- Returns documents that contain one or more of the following phrases: “Saint Bernard,” “St. Bernard,” “working dogs,” “large dogs,” and “European breeds”
- Scores documents that contain the phrase “Saint Bernard” or “St. Bernard” higher than documents that contain the phrase “working dogs,” “large dogs,” or “European breeds”

This example is a very basic topic definition. An outline can introduce more complex relationships by using:

- Multiple levels of subtopics
- Combinations of Verity operators (this example uses `accrue`)

- Verity modifiers

Note In Windows NT, you can use the graphical user interface of the Verity Intelligent Classifier product, which is available from Verity, to create topic outlines. If you use Intelligent Classifier, it automatically creates a topic set directory, and you can go to “Creating a knowledge base map” on page 40 to continue setting up your topics.

Creating a topic set directory

Use the `mktopics` utility to create and populate a topic set directory. It is located in `$$SYBASE/$$SYBASE_FTS/verity/<verity_platform_directory>/bin`.

Run, or define an alias to run, `mktopics` from this `bin` directory. You can create a topic set directory or directories in any work directory.

The `mktopics` syntax is:

```
mktopics -outline outline_file.otl -topicset topic_set_directory
```

where:

- *outline_file* – is the name of the outline file you created in “Creating an outline file” on page 39
- *topic_set_directory* – is the name of the topic set directory you are creating.

For example, to execute the `mktopics` utility reading the *saint-bernard.otl* file defined above, and directing output to a work directory, use the syntax:

```
mktopics -outline  
/usr/u/sybase/topic_outlines/saint-bernard.otl  
-topicset /usr/u/sybase/topic_sets/  
saint-bernard_topic
```

Creating a knowledge base map

A *knowledge base map* specifies the locations of one or more topic set directories. Create an ASCII knowledge base map file that defines the fully-qualified directory paths to your topic sets.

For example, the following knowledge base map file illustrates how you can list multiple knowledge bases in the map. The first entry identifies the topic set directory created with `mktopics` above.

```
$control:1
kbases:
{
kb:
/kb-path = /usr/u/sybase/topic_sets/saint-bernard_topic
kb:
/kb-path = /usr/u/sybase/topic_sets/another_topic
}
```

Defining the location of the knowledge base map

Set the `knowledge_base` configuration parameter to point to the location of the knowledge base map. For example:

```
sp_text_configure KRAZYKAT, 'knowledge_base',
'/usr/u/sybase/topic_sets/sample_text_topics.kbm'
```

The `knowledge_base` configuration parameter is static; you must restart the Enhanced Full-Text Search engine for the definition to take effect.

Executing queries against defined topics

You can now execute queries using the defined topic instead of a complex query. For example, before you create the “saint-bernard” topic, you would have to use the following syntax:

```
...where i.index_any = "<accrue> ([80]Saint Bernard, [80]St. Bernard, working dogs, large dogs, European breeds)"
```

to find documents that:

- Contain one or more of the following phrases: “Saint Bernard,” “St. Bernard,” “working dogs,” “large dogs,” and “European breeds”
- Score documents containing the phrase “Saint Bernard” or “St. Bernard” higher than documents containing the phrase “working dogs,” “large dogs,” or “European breeds”

After you create the topic “saint-bernard”, you can use this syntax:

```
...where i.index_any = "<topic>saint-bernard"
```

or:

```
...where i.index_any = "saint bernard"
```

Note If you enter a word in a query expression, the Enhanced Full-Text Search engine tries to match it with a topic name. If you enter a phrase in a query expression, the Enhanced Full-Text Search engine replaces spaces with hyphens (-), and then tries to match it with a topic name. For example, the Enhanced Full-Text Search engine matches “saint bernard” with the topic “saint-bernard”.

See the *sample_text_topics.sql* file for examples of using topics in queries.

Troubleshooting topics

If the `knowledge_base` configuration parameter specifies a knowledge base map file that does not exist, the Enhanced Full-Text Search engine cannot start a session with Verity, and the server will not start. If the map file exists but contains invalid entries, Verity issues warning messages at start-up time. You can correct errors by editing the `<textserver>.cfg` file in the `$SYBASE` directory. You can correct path information and change the line beginning: “`knowledge_base=`”.

Writing Full-Text Search Queries

This chapter describes the pseudo columns, search operators, and modifiers that you can include in a full-text search.

Topic	Page
Components of a full-text search query	43
Pseudo columns in the index table	44
Full-text search operators	50
Operator modifiers	60

Components of a full-text search query

To write a full-text search query, enter the search parameters as part of an Adaptive Server select statement. Then the Enhanced Full-Text Search engine processes the search. The select statement requires:

- A where clause that assigns a Verity language query to the `index_any` pseudo column
- Pseudo columns to further define the parameters of the search (optional)
- A join between the `IDENTITY` column from the source table and the `id` column from the index table

For example, to return the 10 documents from the `copy` column of the `blurbs` table that have the most occurrences of the word “software,” enter:

```
select t1.score, t2.copy
from i_blurbs t1, blurbs t2
where t1.id=t2.id
and t1.index_any = "<many> <word> software"
and t1.max_docs = 10
```

Adaptive Server passes the Verity query to the Enhanced Full-Text Search engine to process the search. See “How a full-text search works” on page 10.

Default behaviour

The default or simple syntax of a query to the Enhanced Full-Text Search engine is treated broadly:

- 1 Searches are case sensitive.
- 2 The STEM operator applies to search words.
- 3 The MANY modifier is applied.
- 4 The ACCRUE operator is activated at the parent level.

Pseudo columns in the index table

Pseudo columns are columns in the index table that define the parameters of the search and provide access to the results data. See “The index table” on page 7. These columns are valid only in the context of a query; that is, the information in the columns is valid only for the duration of the query. If the query that follows contains a different set of parameters, the pseudo columns contain a different set of values.

Each pseudo column in an index table describes a different search attribute. For example, if you indicate the score column, the query displays only the result set that falls within the parameters you define. For example, the following query displays only the results that have a score value greater than 90:

```
index_table_name.score > 90
```

Other pseudo columns (like highlight) are used to retrieve data generated by Verity for a particular document. Table 5-1 describes the pseudo columns that are maintained by the Enhanced Full-Text Search engine.

Table 5-1: Enhanced Full-Text Search engine *pseudo columns*

Pseudo column name	Description	Datatype	Length (in bytes)
cluster_number	Contains the cluster that the row is part of. Clusters are numbered starting with 1. You can use the cluster_number column only in the select clause of a query.	int	4
cluster_keywords	Contains the keywords that Verity uses to build the cluster. You can use cluster_keywords only in the select clause of a query.	varchar	255

Pseudo column name	Description	Datatype	Length (in bytes)
highlight	Offsets within the document all words from the query. You can use highlight only in the select clause of a query.	text	16
id	Uniquely identifies a document within a collection. Used to join with the IDENTITY column of the source table. You can use id in the select clause or where clause of a query.	numeric	6
index_any	Provides a Verity language query to the Enhanced Full-Text Search engine. You can use index_any only in a where clause.	varchar	255
max_docs	Limits results to the first <i>n</i> documents, based on the default sort order. In a clustered result set, limits results to the first <i>n</i> documents in each cluster. You can use max_docs only in a where clause.	int	4
score	The normalized measure of correlation between search strings and indexed columns. The score associated with a specific document has meaning only in reference to the query used to retrieve the document. You can use score in a select clause or a where clause.	int	4
sort_by	Specifies the sort order in which to return the result set. The Enhanced Full-Text Search engine allows up to 16 sort specifications in the sort_by column. You can use sort_by only in a where clause.	varchar	35
summary	Selects summarization data. You can use the summary column only in the select clause of a query.	varchar	255

The following sections describe the functionality of the pseudo columns.

Using the score column to relevance-rank search results

Relevance ranking is the ability of the Enhanced Full-Text Search engine to assign the score parameter a value that indicates how well a document satisfies the query. The score calculation depends on the search operator used in the query. See “Using the Verity operators” on page 52. The closer the document satisfies the query, the higher the score value is for that document.

For example, if you search for documents that contain the word “rain,” a document with 12 occurrences of “rain” receives a higher score value than a document with 6 occurrences of “rain.”

If you set *score* to a high value (such as 90) in your query, you limit the result set to documents that have a *score* value greater than that number.

Note Verity uses decimals for score values; Sybase uses whole numbers. For example, if Verity reports a score value of .85, Sybase reports the same value as 85.

For example, the following query searches for documents that contain the word “raconteur” or “Paris,” or both, and that have a score of 90 or greater:

```
select t1.score, t2.copy
from i_blurbs t1, blurbs t2
where t1.id=t2.id and t1.score > 90
and t1.index_any = "<accrue>(raconteur, Paris)"
score      copy
```

(0 rows affected)

The query does not find any documents that contain the word “raconteur” or “Paris” and that have a score greater than 90. However, if the *score* value in the query is lowered to 39, you find that one document in the *blurbs* table mentions the word “raconteur” or “Paris:”

```
select t1.score, t2.copy
from i_blurbs t1, blurbs t2
where t1.id=t2.id and t1.score > 39
and t1.index_any = "<accrue>(raconteur, Paris)"
score      copy
```

40 A chef's chef and a raconteur's raconteur, Reginald
 Blotchet-Halls calls London
his second home. "Th' palace
 . . .

Using the *sort_by* column to specify a sort order

The sort order specifies the collating sequence used to order the data in the result set. The default sort order is set by the *sort_order* configuration parameter. See “Setting the default sort order” on page 72. Case insensitive sort order is supported.

Use the *sort_by* pseudo column to return a result set with a sort order other than the default. You can specify up to 16 sort specifications in the *sort_by* pseudo column.

Table 5-2 lists the values for the `sort_by` pseudo column.

Table 5-2: Values for the `sort_by` pseudo column

Value	Description
<code>fts_score desc</code>	Returns a result set sorted by score in descending order.
<code>fts_score asc</code>	Returns a result set sorted by score in ascending order.
<code>fts_timestamp desc</code>	Returns a result set sorted by a timestamp in descending order.
<code>fts_timestamp asc</code>	Returns a result set sorted by a timestamp in ascending order.
<code>column_name desc</code>	Returns a result set sorted according to the descending order of a column. <i>column_name</i> is the name of the source table's column.
<code>column_name asc</code>	Returns a result set sorted according to the ascending order of a column. <i>column_name</i> is the name of the source table's column.
<code>fts_cluster asc</code>	Returns a clustered result set. See “Using pseudo columns to request clustered result sets” on page 48.

Note Before you can sort by specific columns, you must modify the *style.vgw* and *style.ufl* files. See “Setting up a column to use as a sort specification” on page 30.

For example, the following query sorts the documents by timestamp in ascending order:

```
select t1.score, t2.copy
from i_blurbs t1, blurbs t2
where t1.id=t2.id and t1.score > 90
and t1.index_any = "<accrue>(raconteur, Paris)"
and t1.sort_by = "fts_timestamp asc"
```

Using the *summary* column to summarize documents

Use the *summary* pseudo column to have queries return only summaries of the documents that meet the search criteria, rather than returning entire documents. The *summary* column is not available by default; you must edit the *style.prm* file prior to creating the text index to enable summarization. See “Enabling query-by-example, summarization, and clustering” on page 27.

For example, the following query returns only summaries of documents that include the words “Iranian” and “book” (in this example, the *style.prm* file is configured to display 255 characters):

```
select t1.score, t1.summary
from i_blurbs t1, blurbs t2
```

```
where t1.id=t2.id and t1.score > 70
and t1.index_any = "(Iranian <and> book) "
score      summary
-----
----- 78      They asked me to write about myself
and my book, so here
           goes: I started a restaurant called "de Gustibus"
with two
           of my fri
(1 row affected)
```

The Enhanced Full-Text Search engine supports summaries of up to 255 bytes.

For additional examples of queries using summarization, see the sample script *sample_text_queries.sql* in the *\$\$SYBASE/\$SYBASE_FTS/sample/scripts* directory.

Using pseudo columns to request clustered result sets

The clustering function analyzes a result set and groups rows into clusters so that the rows in each cluster are semantically more similar to each other, on average, than they are to other rows in other clusters. Ordering rows by subtopics can help you get a sense of the major subject areas covered in the result set.

Returning a clustered result set can be significantly slower than returning a nonclustered result set. If the response time of a query is critical, use a nonclustered result set.

Preparing to use clustering

Before you request a clustered result set, you must build the text index with the clustering function enabled. See “Enabling query-by-example, summarization, and clustering” on page 27.

The Verity clustering algorithm attempts to group similar rows together, based on the values of the following configuration parameters:

- cluster_style
- cluster_max
- cluster_effort
- cluster_order

Use `sp_text_cluster` to have a query use values that are different from the default values of these configuration parameters. See `sp_text_cluster` on page 147.

Writing queries requesting a clustered result set

To obtain a clustered result set, specify “`fts_cluster asc`” as the sort specification in the `sort_by` pseudo column of the query. For example:

```
select t1.score, t2.copy
from i_blurbs t1, blurbs t2
where t1.id=t2.id
and t1.index_any = "<many> <word> software"
and t1.max_docs = 10
and t1.sort_by = "fts_cluster asc"
```

Include any of the following pseudo columns in your query to return additional clustering information:

- `cluster_number` – contains the number of the cluster the row belongs to. Clusters are numbered starting with 1.
- `cluster_keywords` – contains the most common words found in the cluster. The `cluster_keywords` column contains a null value for each row that does not fit into any cluster.
- `max_docs` – limits the number of rows returned for each cluster. In a nonclustered query, the `max_docs` column limits the total number of rows that are returned in a result set.
- `score` – contains a value of 0 to 10000. The higher the score, the closer the row is to the cluster center. A score of 0 indicates the row does not fit into any cluster. In a nonclustered query, the `score` column can contain a value of 0 to 100. The search engine does not return results with a score of 0. A score of 0 represents “no match” but the user never sees a score of 0.

See the sample script named `sample_text_queries.sql` in the `$$SYBASE/$SYBASE_FTS/sample/scripts` directory for examples of SQL statements using clustering.

Full-text search operators

The special search operators that you use to perform full-text searches are part of the Verity search engine. Table 5-3 describes the Verity search operators provided by the Enhanced Full-Text Search engine.

Table 5-3: Verity search operators

Operator name	Description
accrue	Selects documents that contain at least one of the search elements specified in a query. The more search elements there are, the higher the score.
and	Selects documents that contain all the search elements specified in a query.
complement	Returns the complement of the score value (the score value subtracted from 100).
in	Selects documents that contain the search criteria in the document zone specified.
like	Selects documents that are similar to the sample documents or passages specified in a query.
near	Selects documents containing the specified search elements, where the closer the search terms are to each other in a document, the higher the document's score.
near/n	Selects documents containing two or more search terms within <i>n</i> number of words of each other, where <i>n</i> is an integer up to 1000. The closer the search terms are to each other in a document, the higher the document's score.
or	Selects documents that contain at least one of the search elements specified in a query.
paragraph	Selects documents that include all the search elements you specify within the same paragraph.
phrase	Selects documents that include a particular phrase. A phrase is a grouping of two or more words that occur in a specific order.
product	Multiplies the score values for each of the items of the search criteria.
sentence	Selects documents that include all the specified words in the same sentence.
stem	Expands the search to include the specified word and its variations.
sum	Adds the score values for all items in the search criteria.
thesaurus	Expands the search to include the specified word and its synonyms.
topic	Specifies that the search term you enter is a topic.
typo/n	Expands the search to include the specified word plus words that are similar. The optional <i>n</i> variable specifies the maximum number of errors between the query term and the matched term.
wildcard	Matches wildcard characters included in search strings. Certain characters indicate a wildcard specification automatically.
word	Performs a basic word search, selecting documents that include one or more instances of the specified word.
yesno	Converts all nonzero score values to 100.

Considerations when using Verity operators

When you write full-text search queries:

- You *must* enclose the operators in angle brackets (<>) in the query. If they are not enclosed in angle brackets, the Enhanced Full-Text Search engine issues error messages similar to the following:

```
Msg 20200, Level 15, State 0:
Server 'KRAZYKAT', Line 1:
Error E1-0111 (Query Builder): Syntax error in query string near
character 5
Msg 20200, Level 15, State 0:
Server 'KRAZYKAT', Line 1:
Error E1-0114 (Query Builder): Error parsing query: word(tasmanian)
Msg 20101, Level 15, State 0:
Server 'KRAZYKAT', Line 1:
VdkSearchNew failed with vdk error (-40).
Msg 20101, Level 15, State 0:
Server 'KRAZYKAT', Line 1:
VdkSearchGetInfo failed with vdk error (-11).
score      copy
-----
(0 rows affected) score
```

- You must enclose the Verity language query in single quotes (') or double quotes ("). The Enhanced Full-Text Search engine strips off the outermost quotes before it sends the query to Verity. For example, when you enter the query:

```
...where index_any = "'?own'"
```

the Enhanced Full-Text Search engine sends the following query to Verity:

```
'?own'
```

- A query may comprise several "index_any" clauses anded together in SQL. The right and value strings can be prefixed with "<snnn>". All such strings are concatenated in Enhanced Full-Text Search in the order determined by the "nnn" values. The "<snnn>" is removed. For instance:

```
where index_any="<s001>hello"
and index_any="<s002> world"
```

is the same as:

```
where index_any = "hello world"
```

This is a workaround for search strings that are greater than 255 characters.

- Search terms entered in mixed case automatically become case sensitive. Search terms entered in all uppercase or all lowercase are not automatically case sensitive. For example, a query on “Server” finds only the string “Server”. A query on “server” or “SERVER” finds the strings “Server”, “server”, and “SERVER”.
- You can use alternative syntax for the query expressions shown in Table 5-4.

Table 5-4: Alternative Verity syntax

Standard query expression	Alternative syntax
<MANY><WORD> <i>string</i>	" <i>string</i> "
<MANY><STEM> <i>string</i>	' <i>string</i> '

When using the alternative syntax, remember that the Enhanced Full-Text Search engine strips off the outermost quotes before it sends the query to Verity. For example, when you enter the query:

```
...where index_any = "'play'"
```

the Enhanced Full-Text Search engine sends the following query to Verity:

```
'play'
```

This is the same as:

```
<MANY><STEM>play
```

Using the Verity operators

The following sections describe how to use the Verity operators shown in Table 5-3 on page 50.

accrue

The *accrue* operator selects documents that contain at least one of the search items specified in the query. There must be two or more search elements. Each result is relevance-ranked. For example, the following query searches for the word “restaurant” or “deli” or both in the copy column of the blurbs table:

```
select t1.score, t2.copy
from i_blurbs t1, blurbs t2
where t1.id=t2.id and t1.score > 35
and t1.index_any = "<accrue>(restaurant, deli)"
```

and, or

The `and` and `or` operators select documents that contain the specified search elements. Each result is relevance-ranked. The `and` operator selects documents that contain all the elements specified in the query. For example, the following query selects documents that contain both “Iranian” and “business”:

```
select t2.copy
from i_blurbs t1, blurbs t2
where t1.id=t2.id
and t1.index_any = "(Iranian <and> business)"
```

The `or` operator selects the documents that contain any of the search elements. For example, if the preceding query is rewritten to use the `or` operator, the query selects documents that contain the word “Iranian” or “business”:

```
select t2.copy
from i_blurbs t1, blurbs t2
where t1.id=t2.id
and t1.index_any = "(Iranian <or> business)"
```

complement

The complement operator returns the complement of the score value for a document; that is, it subtracts the value of score from 100 and returns the result as the score value for the document.

in

The `in` operator selects documents that contain the specified search element in one or more document zones. Document zones are created for a text index in the following two scenarios:

- When you create an index on two or more columns using `sp_create_text_index`, a document zone is created for each column in the text index. See “Specifying multiple columns when creating a text index” on page 22. A document zone is not created when you create a text index on a single column. For example, if you specify the `au_id` and `copy` columns of the `blurbs` table when you create the text index, you can issue the following query:

```
select t1.score, t2.copy
from i_blurbs t1, blurbs t2
where t1.id=t2.id and t1.score > 35
and t1.index_any = "gorilla <in> copy"
```

This returns rows that contain the word “gorilla” in the copy column. However, if you specify only the copy column of the blurbs table when you create the text index, this query does not return any rows.

- When you create an index that uses a filter, a document zone is created for each tag in the document. See “Using filters on text that contains tags” on page 32. You can limit your search to a particular tag by specifying the tag name after the in operator. For example, to search for the word “automotive” in a “title” tag in an HTML document, specify:

```
select t1.score, t2.copy
from i_blurbs t1, blurbs t2
where t1.id=t2.id and t1.score > 35
and t1.index_any = "automotive <in> title"
```

Text indexes utilizing filters can contain only one column.

like

The like operator selects documents that are similar to the documents or passages you provide. The search engine analyzes the text to find the most important terms to use. If you specify multiple samples, the search engine selects important terms that are common across the samples. Each result is relevance-ranked.

The like operator accepts a single operand, called the query-by-example (QBE) specification. The QBE specification can be either literal text or document IDs. The document IDs are from the IDENTITY column in the source table. For example, to select documents that are similar to the document in the copy column in the row with an IDENTITY of “2”, enter:

```
select t1.score, t2.copy
from i_blurbs t1, blurbs t2
where t1.id=t2.id and t1.score > 35
and t1.index_any = '<like> ( "{2}" )'
```

Before using literal text in the QBE specification, you must uncomment the following line in the *style.prm* file:

```
$define DOC-FEATURES "TF"
```

See “Enabling query-by-example, summarization, and clustering” on page 27.

See the sample script named *sample_text_queries.sql* in the `$SYBASE/$SYBASE_FTS/sample/scripts` directory for examples of SQL statements using QBE.

near, near/n

The `near` operator selects documents that contain the items specified in the query and are near each other (“near” being a relative term). The documents in which the search words appear closest to each other receive the highest relevance-ranking.

The `near/n` operator specifies how far apart the items can be (n has a maximum value of 1000). The following example selects documents in which the words “raconteur” and “home” appear within 10 words of each other:

```
select t2.copy
from i_blurbs t1, blurbs t2
where t1.id=t2.id
and t1.index_any = "<near/10>(raconteur, home)"
```

or

See “and, or” on page 53.

phrase

The `phrase` operator selects documents that contain a particular phrase (a group of two or more items that occur in a specific order). Each result is relevance-ranked. The following example selects the documents that contain the phrase “gorilla’s head”:

```
select t1.score, t2.copy
from i_blurbs t1, blurbs t2
where t1.id=t2.id and t1.score > 50
and t1.index_any = "<phrase>(gorilla's head)"
```

paragraph

The `paragraph` operator selects documents in which the specified search elements appear in the same paragraph. The closer the words are to each other in a paragraph, the higher the score the document receives in relevance-ranking. The following example searches for documents in which the words “text” and “search” occur within the same paragraph:

```
select t1.score, t2.copy
from i_blurbs t1, blurbs t2
where t1.id=t2.id and t1.score > 50
and t1.index_any = "<many><paragraph>(text, search)"
```

product

The product operator multiplies the score value for the documents for each of the search elements. To arrive at a document's score, the Enhanced Full-Text Search engine calculates a score for each search element and multiplies the scores. For example:

```
select t1.score, t2.copy
from i_blurbs t1, blurbs t2
where t1.id=t2.id and t1.score > 50
and t1.index_any = "<product>(cat, created) "
```

The score value for each search element is 78; however, because the score values for the items are multiplied, the document has a score value of 61 ($.78 \times .78 = .61(100) = 61$).

sentence

The sentence operator selects documents in which the specified search elements appear in the same sentence. The closer the words are to each other in a sentence, the higher the score the document receives in relevance-ranking. The following example searches for documents in which the words "tax" and "service" occur within the same sentence:

```
select t1.score, t2.copy
from i_blurbs t1, blurbs t2
where t1.id=t2.id and t1.score > 50
and t1.index_any = "<many><sentence>(tax, service) "
```

stem

The stem operator searches for documents containing the specified word and its variations. For example, if you specify the word "cook," the Enhanced Full-Text Search engine produces documents that contain "cooked," "cooking," "cooks," and so on. To relevance-rank the result set, include the many modifier in the query. See "Operator modifiers" on page 60.

The following query uses the stem operator to find documents that contain variations of the word "create," that is, words that contain the word "create" as a stem. Notice that even though the first document contains a word in which "create" is not a perfect stem ("creative"), the document is still selected:

```
select t1.score, t2.copy
from i_blurbs t1, blurbs t2
where t1.id=t2.id and t1.score > 10
and t1.index_any = "<many><stem>create"
```



```
score      copy
-----
```

```
78      Anne Ringer ran away from the circus as a child.  A
        university creative writing professor and her family
        . . .
78      If Chastity Locksley didn't exist, this troubled world
        would have created her!  Not only did she master the mystic
```

sum

The `sum` operator totals the score values for each search element, up to a maximum of 100. To arrive at a document's score, the Enhanced Full-Text Search engine calculates a score for each search element and totals those scores.

thesaurus

The `thesaurus` operator searches for documents containing a synonym for a search element. For example, you might perform a search using the word "dog," looking for documents that use any of its synonyms ("canine," "pooch," "pup," "watchdog," and so on). Each result is relevance-ranked.

The Enhanced Full-Text Search engine supplies a default thesaurus. You can also create a custom thesaurus. See "Creating a custom thesaurus" on page 34.

The following example uses the `thesaurus` operator to find a result set that contains synonyms for the word "crave." The first document is selected because it contains the word "want;" the second, because it contains the word "hunger:"

```
select t2.copy
from i_blurbs t1, blurbs t2
where t1.id=t2.id
and t1.index_any = "<thesaurus>(crave)"
score      copy
-----
```

```
78      They asked me to write about myself and my book, so here
        goes:  I started a restaurant called "de Gustibus" with two
        . . .
        of restaurant over another, when what they really want is a
        . . .
78      A chef's chef and a raconteur's raconteur, Reginald
        Blotchet-Halls calls London his second home.  "Th' palace
        . . .
        his equal skill in satisfying our perpetual hunger for
```

. . .

topic

The topic operator selects documents that meet the search criteria defined by the specified topic. See “Creating topics” on page 38. For example, use the following syntax to find documents that meet the criteria defined by the topic “engineering:”

```
select t2.copy
from i_blurbs t1, blurbs t2
where t1.id=t2.id
and t1.index_any = "<topic>(engineering) "
```

typo/n

The typo/n operator expands the search to include the specified word plus words that are similar. The optional *n* variable specifies the maximum number of errors between the query and the matched terms. For example, `typo mouse` returns documents that include words such as “house,” “louse,” and “moose.”

wildcard

The wildcard operator allows you to substitute wildcard characters for part of the item for which you are searching. Table 5-5 describes the wildcard characters and their attributes.

Table 5-5: Enhanced Full-Text Search engine *wildcard characters*

Character	Function	Syntax	Locates
?	Specifies one alphanumeric character. You do not need to include the wildcard operator when you include the question mark in your query. The question mark is ignored in a set ([]) or in an alternative pattern ({}).	'?an'	“ran,” “pan,” “can,” and “ban”
*	Specifies zero or more of any alphanumeric character. You do not need to include the wildcard operator when you include the asterisk in your query; you should not use the asterisk to specify the first character of a wildcard-character string. The asterisk is ignored in a set ([]) or in an alternative pattern ({}).	'corp*'	“corporate,” “corporation,” “corporal,” and “corpulent”

Character	Function	Syntax	Locates
[]	Specifies any single character in a set. If a word includes a set, you must enclose the word in backquotes (""). Also, there can be no spaces in a set.	<wildcard> 'c[auo]t'	"cat," "cut," and "cot"
{ }	Specifies one of each pattern separated by a comma. If a word includes a pattern, you must enclose the word in backquotes (""). Also, there can be no spaces in a set.	<wildcard> 'bank{s,er,ing}'	"banks," "banker," and "banking"
^	Specifies one of any character not included in a set. The caret (^) must be the first character after the left bracket ([) that introduces a set.	<wildcard> 'st[^oa]ck'	Excludes "stock" and "stack," but locates "stick" and "stuck"
-	Specifies a range of characters in a set.	<wildcard> 'c[a-r]t'	Includes every three-letter word from "cat" to "crt"

To relevance-rank the result set, include the many modifier in the query. See "Operator modifiers" on page 60.

For example, the following query searches for documents that include variations of the word "slingshot:"

```
select t2.copy
from i_blurbs t1, blurbs t2
where t1.id=t2.id
and t1.index_any = 'slingshot*'
score    copy
-----
100     Albert Ringer was born in a trunk to circus parents, but
        another kind of circus trunk played a more important role
        . . .
        gorilla. "Slingshotting" himself from the ring ropes,
        . . .
```

word

The word operator searches for documents containing the specified word. To relevance-rank the result set, include the many operator in the query. The following example searches the blurbs table for documents containing the word "palates":

```
select t1.score, t2.copy
from i_blurbs t1, blurbs t2
where t1.id=t2.id and t1.score > 50
```

```
and t1.index_any = "<many><word>(palates) "
```

yesno

The `yesno` operator converts all nonzero score values to 100. For example, if the score values for five documents are 86, 45, 89, 89, and 100, each of those documents is returned with a score value of 100. score values of 0 are not changed. The `yesno` operator is helpful for ensuring that all documents containing the search criteria are returned in the result set, regardless of the sort order.

Operator modifiers

The Verity query language includes modifiers that you can use with the operators to refine a search. The modifiers are described in Table 5-6.

Table 5-6: Verity operator modifiers

Modifier name	Description	Works with these operators	Example
case	Performs case-sensitive searches. If you enter search terms in mixed case, the search is automatically case sensitive.	wildcard word	<case><word> (Net)
many	Counts the number of times that a word, stemmed word, or phrase occurs in a document. Relevance-ranks the document according to its density.	paragraph phrase sentence stem word wildcard	<many><stem> (write)
not	Excludes documents that contain the items for which the query is searching.	and or	cat<and><not>elephant

Modifier name	Description	Works with these operators	Example
order	Specifies that the items in the documents occur in the same order in which they appear in the query. Always place the order modifier just before the operator	near/n paragraph sentence	Simple syntax: tidbits<order><paragraph>king Explicit syntax: <order><paragraph>(tidbits,king)

This chapter describes system administration issues for the Enhanced Full-Text Search engine.

Topic	Page
Starting the Enhanced Full-Text Search engine on UNIX	63
Starting the Enhanced Full-Text Search engine on Windows NT	65
Shutting down the Enhanced Full-Text Search engine	66
Modifying the configuration parameters	67
Backup and recovery for the Enhanced Full-Text Search engine	75

Starting the Enhanced Full-Text Search engine on UNIX

Use the `startserver` utility to start the Enhanced Full-Text Search engine on UNIX. The `startserver` utility is included in the `install` directory of Adaptive Server. For example, to start a Enhanced Full-Text Search engine named `KRAZYKAT`, enter:

```
startserver -f
$SYBASE/$SYBASE_FTS/install/RUN_KRAZYKAT
```

where the `-f` flag specifies the relative path to the `runserver` file. After you issue the command, the Enhanced Full-Text Search engine issues a series of messages describing the settings of the configuration parameters.

Creating the `runserver` file

The `runserver` file contains start-up commands for the Enhanced Full-Text Search engine. The `runserver` file can include the flags shown in Table 6-1.

Table 6-1: Definition of flags in the runserver file

Flag	Definition
<i>-Sserver_name</i>	Specifies the name of the Enhanced Full-Text Search engine and is used to locate the configuration file and the network connection information in the interfaces file.
<i>-t</i>	Causes the Enhanced Full-Text Search engine to write start-up messages to standard error.
<i>-lerrorlog_path</i>	Specifies the path to the error log file.
<i>-iinterfaces_file_path</i>	Specifies the path to the interfaces file.

A sample runserver file is copied to the `$$SYBASE/$$SYBASE_FTS/install` directory during installation. Make a copy of this file, renaming it `RUN_server_name`, where `server_name` is the name of the Enhanced Full-Text Search engine. You must include the correct path environment variable for your platform in the runserver file. Table 6-2 shows the path environment variable to use for each platform.

Table 6-2: Path environment variable for the runserver file

Platform	Environment variable
RS/6000 AIX	LIBPATH
Sun Solaris	LD_LIBRARY_PATH
HP 9000(800)	SHLIB_PATH
Compaq Tru64	LD_LIBRARY_PATH
Linux	LD_LIBRARY_PATH
NT	PATH

For example, the runserver file on Sun Solaris for a Enhanced Full-Text Search engine named KRAZYKAT would be `RUN_KRAZYKAT` and would be similar to:

```
#!/bin/sh
#

LD_LIBRARY_PATH="$$SYBASE/$$SYBASE_FTS/lib:$LD_
LIBRARY_PATH"
export LD_LIBRARY_PATH

$$SYBASE/bin/txtsvr -SKRAZYKAT
```

The start-up command in the runserver file must consist of a single line and cannot include a return. If you must carry the contents of the file over to a second or third line, include a backslash (`\`) for a line break.

Starting the Enhanced Full-Text Search engine on Windows NT

You can start the Enhanced Full-Text Search engine from Sybase Central™, as a service, or from the command line:

- From Sybase Central – see your Sybase Central documentation for information about starting servers.
- As a service – see “Starting the Enhanced Full-Text Search engine as a service” on page 65
- From the command line – use the following syntax:

```
%SYBASE%\%SYBASE_FTS%\bin\txtsvr.exe -Sserver_name
[-t] [-i%SYBASE%path_to_sql.ini_file] [-l%SYBASE%path_to_errorlog]
```

where:

- -S is the name of the Enhanced Full-Text Search engine you are starting.
- -t directs start-up messages to standard error.
- -i is the path to the *sql.ini* file. This path must include the *sql.ini* file name.
- -l is the path to the error log. This path must include the name of the error log file.

For example, to start a Enhanced Full-Text Search engine named KRAZYKAT on NT using the default *sql.ini* and error log files, and using -t to trace start-up messages, enter:

```
%SYBASE%\%SYBASE_FTS%\bin\txtsvr.exe -SKRAZYKAT -t
```

The Enhanced Full-Text Search engine is running when you see the start-up complete message.

Starting the Enhanced Full-Text Search engine as a service

Use the *instsvr* utility in Sybase Central to add the Enhanced Full-Text Search engine to the list of items you can start and stop with the Services utility. *instsvr* is located in the *%SYBASE%\%SYBASE_FTS%\bin* directory.

The *instsvr* utility uses the following syntax:

```
instsvr.exe service_name %SYBASE%\%SYBASE_FTS%\bin\txtsvr.exe
```

`"startup_parameters"`

where:

- *service_name* is the name of the Enhanced Full-Text Search engine you are adding as a service. With Sybase Central, Sybase recommends you use a server name with the extension “_TS” (for example, KRAZYKAT_TS).
- *startup_parameters* are any parameters you want used at start-up.

For example, to install an Enhanced Full-Text Search engine named KRAZYKAT_TS as a service, enter:

```
instsvr.exe KRAZYKAT_TS %SYBASE%\sds\text\bin\txtsvr.exe  
"-SKRAZYKAT_TS -t"
```

Note To include more than one parameter (for example, -i), enclose all the parameters in one set of double quotes.

To configure Sybase Central to start and stop your Enhanced Full-Text Search engine, you must provide a service name that begins with “SYBTEXT_*server_name*”, where *server_name* is the name of the Enhanced Full-Text Search engine listed in the interfaces file. For example, if the name in the interfaces file is KRAZYKAT_TS, run the following instsvr command to create a service that can be managed by Sybase Central:

```
instsvr SYBTEXT_KRAZYKAT_TS %SYBASE%\%SYBASE_FTS%\bin\txtsvr.exe  
"-SKRAZYKAT_TS -t"
```

Shutting down the Enhanced Full-Text Search engine

Use the following command to shut down the Enhanced Full-Text Search engine from Adaptive Server:

```
server_name...sp_shutdown
```

where *server_name* is the name of the Enhanced Full-Text Search engine you are shutting down.

For example, to shutdown a Enhanced Full-Text Search engine named KRAZYKAT, enter:

```
KRAZYKAT...sp_shutdown
```

Modifying the configuration parameters

Each Enhanced Full-Text Search engine has configuration parameters with default values, as shown in Table 6-3.

Table 6-3: Configuration parameters

Parameter	Description	Default value
batch_size	Determines the size of the batches sent to the Enhanced Full-Text Search engine.	500
batch_blocksize	When enabled, the text server reads data in smaller chunks. This parameter instructs the text server to retrieve <i>n</i> number of rows at a time. Range is 0 (disabled) to 65535.	0
max_indexes	The maximum number of text indexes that are created in the Enhanced Full-Text Search engine.	126
max_stacksize	Size (in kilobytes) of the stack allocated for client threads.	34,816
max_threads	Maximum number of threads available for the Enhanced Full-Text Search engine.	50
max_packetsize	Packet size sent between the Enhanced Full-Text Search engine and the Adaptive Server.	2048
max_sessions	Maximum number of sessions for the Enhanced Full-Text Search engine.	100
min_sessions	Minimum number of sessions for the Enhanced Full-Text Search engine.	10
language	Language used by the Enhanced Full-Text Search engine.	us_english
charset	Character set used by the Enhanced Full-Text Search engine.	iso_1
vdkCharset	Character set used by Verity search engine.	850
vdkLanguage	Language used by Verity search engine.	english
vdkHome	Verity directory.	UNIX: <i>\$\$SYBASE/\$\$SYBASE_FTS/verity</i> Windows NT: <i>\$\$SYBASE%\%SYBASE_FTS%\verity</i>
collDir	Storage location of the Enhanced Full-Text Search engine's collection.	UNIX: <i>\$\$SYBASE/\$\$SYBASE_FTS/collections</i> Windows NT: <i>\$\$SYBASE%\%SYBASE_FTS%\collections</i>

Parameter	Description	Default value
defaultDb	Name of the Enhanced Full-Text Search engine database that stores text index metadata.	text_db
interfaces	Full path to the directory in which the interfaces file used by the Enhanced Full-Text Search engine is located.	UNIX: \$SYBASE/interfaces Windows NT: %SYBASE%\ini\sql.ini
sort_order	Default sort order.	0
errorLog	Full path name to the error log file.	The directory in which you start Enhanced Full-Text Search engine
traceflags	String containing numeric identifiers used to generate diagnostic information.	0
srv_traceflags	String containing numeric flag identifiers used to generate Open Server diagnostic information.	0
max_session_fd	The maximum number of file descriptors used by an Enhanced Full-Text Search session. See “File Descriptors and Enhanced Full-Text Search” on page 86.	0
cluster_style	Clustering style to use.	Fixed
cluster_max	Maximum number of clusters to generate when cluster_style is set to Fixed.	0
cluster_effort	Amount of effort the Enhanced Full-Text Search engine should expend on finding a good cluster.	Default
cluster_order	The order to return clusters and rows within a cluster.	0
auto_online	Specifies whether to bring indexes online automatically when the Enhanced Full-Text Search engine is started. 0 indicates online is not automatic; 1 indicates automatic.	0
backDir	The default location for the placement of text index backup files.	UNIX: \$SYBASE/\$SYBASE_FTS/backup Windows NT: %SYBASE%\%SYBASE_FTS%\backup
knowledge_base	The location of a knowledge base map for implementing the Verity topics feature.	null
nocase	Sets the case-sensitivity of the Enhanced Full-Text Search engine. If you are using a case-sensitive sort order in Adaptive Server, set to 0. If you are using a case-insensitive sort order, set to 1.	0

A sample configuration file that includes all of these parameters is copied to your installation directory during installation. The sample configuration file, which is named *textsvr.cfg* is listed in Appendix B, “Sample Files.”

Modifying configuration values

Use `sp_text_configure` to change the value of a configuration parameter. The syntax is:

```
sp_text_configure server_name, config_name, config_value
```

where:

- *server_name* is the name of the Enhanced Full-Text Search engine.
- *config_name* is the name of the configuration parameter.
- *config_value* is the value you assign to the configuration parameter.

See `sp_text_configure` on page 149.

Available configuration parameters

Table 6-4 provides a list of available configuration parameters with valid limits:

Table 6-4: Limits to Configuration parameters

Parameter	Values	Static/dynamic
batch_size	0 – MAX_INT	Dynamic
batch_blocksize	0 – 65535	Dynamic
max_indexes	0 – MAX_INT	Static
max_stacksize	0 – MAX_INT	Static
max_threads	0 – MAX_INT	Static
max_packetize	0 – MAX_INT	Static
max_sessions	0 – MAX_INT	Static
min_sessions	0 – max_sessions	Static
language	french, spanish german, us_english	Static
charset	ascii_8, cp037, cp1047, cp437, cp500, cp850, deckanji, eucjis, iso_1, mac, roman8, sjis, utf8	Static
vdkCharset	50, 437, 1252, mac1 (Just the ones listed in the manual)	Static

Parameter	Values	Static/dynamic
vdkLanguage	frenchx, spanishx, germanx, english, englishx, bokmalx, dutchx, finnishx, nynorskx, swedishx, portugx, italianx, danishx	Static
vdkHome	A string < 255 chars	Static
collDir	A string < 255 chars	Static
default_Db	A string < 32 chars	Static
interfaces	A string < 255 chars	Static
sort_order	0, 1, 2, 3	Dynamic
errorLog	A string < 255 chars	Static
traceflags	A string with comma delimited numbers ranging anywhere from 1 to 15	Static
srv_traceflags	A string with comma delimited numbers ranging anywhere from 1 to 8	Static
cluster_style	Coarse, Medium, Fine, Fixed	Dynamic
cluster_max	0 – MAX_INT	Dynamic
cluster_effort	Low, Medium, High, Default	Dynamic
cluster_order	0 or 1	Dynamic
auto_online	0 or 1	Static
backCmd	A string < 255 chars	Dynamic
restoreCmd	A string < 255 chars	Dynamic
backDir	A string < 255 chars	Static
knowledge_base	A string < 255 chars	Static
nocase	0 or 1	Dynamic
max_session_fd	0, 5 – MAX_INT	Static

Setting the default language

The default language for Verity is set with the `vdkLanguage` configuration parameter. By default, `vdkLanguage` is set to “english.” You can configure Verity to use a different default language. Table 6-5 lists the locales supported by Sybase.

Table 6-5: vdkLanguage configuration parameters

Language	Default locale name
English	english
German	german
French	french

Additional language adapters are available in the `$$SYBASE/$SYBASE_FTS/verity/common` directory; however, the Enhanced Full-Text Search engine displays messages only in the languages shown in Table 6-5.

The language parameter is the language the Enhanced Full-Text Search engine uses to display its error messages and Open Server and Open Client error messages. Set the language parameter to the Adaptive Server language.

With the Enhanced Full-Text Search engine, run:

```
sp_text_configure KRAZYKAT, 'vdkLanguage', 'spanish'
```

For more information about the Verity languages, see the Verity Web site at <http://www.verity.com>.

Setting the default character set

Set the default character set for Verity using the `vdkCharset` parameter in the configuration file. The files used for the Verity character sets are in `$$SYBASE/$SYBASE_FTS/verity/common`. Table 6-6 describes the character sets you can use with Verity.

Table 6-6: Verity character sets

Character set	Description
850	Default
437	IBM PC character set
1252	Windows code page for Western European languages
mac1	Macintosh roman

The default character set for the Enhanced Full-Text Search engine is set with the `charset` parameter. Set the `charset` parameter to the Adaptive Server character set.

For example, with the Enhanced Full-Text Search engine, run:

```
sp_text_configure KRAZYKAT, 'vdkCharset', '437'
```

Indexing on the euro symbol

To index the euro symbol, install the `utf8` charset in Adaptive Server. Set `vdkLanguage` to `<language>x` and leave `vdkCharset` blank. For example:

```
ASE 12.5.x charset           = utf8
EFTS 12.5.x vdkLanguage     = englishx
EFTS 12.5.x vdkCharset      =
```

Setting the default sort order

By default, the Enhanced Full-Text Search engine sorts the result set by the score pseudo column in descending order (the higher scores appear first). To change the default sort order, set the `sort_order` configuration parameter to one of the values in Table 6-7.

Table 6-7: Sort order values for the configuration file

Value	Description
0	Returns result sets sorted by the score pseudo column in descending order. The default value.
1	Returns result sets sorted by the score pseudo column in ascending order.
2	Returns result sets sorted by a timestamp in descending order.
3	Returns result sets sorted by a timestamp in ascending order.

For example, enter:

```
sp_text_configure KRAZYKAT, 'sort_order', '2'
```

When you sort a result set by descending timestamp (value 2 in Table 6-7), the Enhanced Full-Text Search engine returns the newest documents first. The newest documents are those that were inserted or updated most recently. When results are sorted by ascending timestamp (value 3 in Table 6-7), the Enhanced Full-Text Search engine returns the oldest documents first.

Setting the default sort order is especially important if your query uses the `max_docs` pseudo column. The `max_docs` pseudo column limits the number of rows of the result set to the first n rows, ordered by the sort order. If you set `max_docs` to a number smaller than the size of the result set, the sort order you select could exclude the rows that contain the information for which you are searching.

For example, if you sort by ascending timestamp, the latest document added to the table appears last in the result set. If the entire result set consists of 11 documents, and you set `max_docs` to 10, the latest document does not appear in the result set. However, if you sort by descending timestamp, the latest document appears first in the result set.

Setting trace flags

The `traceflags` parameter enables the logging of certain events when they occur within the Enhanced Full-Text Search engine. Each trace flag is uniquely identified by a number. Trace flags are described in Table 6-8.

Table 6-8: Enhanced Full-Text Search engine trace flags

Trace flag	Description
1	Traces connects, disconnects, and attention events from Adaptive Server .
2	Traces language events. Traces the SQL statement that Adaptive Server sent to the Enhanced Full-Text Search engine.
3	Traces RPC events.
4	Traces cursor events. Traces the SQL statement sent to the Enhanced Full-Text Search engine by Adaptive Server.
5	Writes the errors that display to the log.
6	Traces information about text indexes. Writes the search string being passed to Verity to the log, and writes the number of records that the search returns to the log.
7	Traces done packets.
8	Traces calls to the interface between the Enhanced Full-Text Search engine and the Verity API.
9	Traces SQL parsing.
10	Traces Verity processing.
11	Disables Verity collection optimization.
12	Disables <code>sp_statistics</code> from returning information.
13	Traces backup operations.
14	Logs Verity status and timing information.
15	Generates ngram index information for collections. ngrams increase the speed of wildcard searches. This trace flag is required for wildcard searches against data in Unicode format.
30	This traceflag enables the Verity MaxClean feature that removes out of date collection files. It should only be used during maintenance since it could take extra time and interfere with normal usage. It is enabled in conjunction with <code>sp_optimize_text_index</code> .

You can enable and disable trace flags interactively, using the remote procedure calls (RPCs) `sp_traceon` and `sp_traceoff` in the Enhanced Full-Text Search engine.

To execute `sp_traceon`, use:

```
textserver...sp_traceon 1,2,3,4
```

where *textserver* is the name of the Enhanced Full-Text Search engine.

The traceflags stay active until the session is terminated or until the `sp_traceoff` RPC is executed using the specific traceflag. To set a traceflag permanently, either set it in the configuration file or use the `sp_text_configure` command.

Setting Open Server trace flags

Use the `srv_traceflags` parameter to turn on trace flags to log Open Server diagnostic information. Open Server trace flags are described in Table 6-9.

Table 6-9: Open Server trace flags

Trace flag	Description
1	Traces TDS headers
2	Traces TDS data
3	Traces attention events
4	Traces message queues
5	Traces TDS tokens
6	Traces Open Server events
7	Traces deferred event queues
8	Traces network requests

For example:

```
sp_text_configure KRAZYKAT, 'srv_traceflags', '3'
```

Setting case sensitivity

By default, the Enhanced Full-Text Search engine is case sensitive. This means you must enter identifiers in the same case or they are not recognized. For example, if you have a table named `blurbs` (lowercase), you cannot issue an `sp_create_text_index` command that specifies the table name `BLURBS`. You must issue a command that uses the same case for the table name argument:

```
sp_create_text_index "KRAZYKAT", "i_blurbs", "blurbs", "", "copy"
```

With Enhanced Full-Text Search engine, use the `nocase` parameter to set the case sensitivity of the Enhanced Full-Text Search engine. 0 indicates case sensitive; 1 indicates case insensitive. Set the `nocase` parameter to the sort order case sensitivity in Adaptive Server.

This example changes the KRAZYKAT server to case insensitive.

```
sp_text_configure KRAZYKAT, 'nocase', '1'
```

Note The `nocase` parameter does not affect the case sensitivity of the Verity query. See “Considerations when using Verity operators” on page 51.

Backup and recovery for the Enhanced Full-Text Search engine

Backup and recovery for the Enhanced Full-Text Search Specialty Data Store is automated with `sp_text_dump_database` and `sp_text_load_index`. These system procedures provide a seamless interface for maintaining data and text index integrity.

The Adaptive Server user database and the Verity collections are physically separate. Backing up your user database does *not* back up the Verity collections, and restoring your database from a backup does *not* restore your Verity collections. The backup and recovery procedures described in Chapter 27, “Backing Up and Restoring User Databases,” of the *System Administration Guide* apply only to the user database and the `text_db` database in Adaptive Server.

Follow the recommended schedule for backing up your databases, as described in Chapter 26, “Developing a Backup and Recovery Plan,” of the *System Administration Guide*. Sybase recommends that when you back up a user database with text indexes, you also back up:

- The `text_db` database

- The text indexes

Note You do not have to back up the user database and text indexes at the same time to recover the text indexes. However, you must restore the user database before you restore the text index. This restores the `text_events` table, which `sp_text_load_index` uses to bring the text indexes in sync with the user database.

A regular backup schedule ensures the integrity of the text indexes, the Adaptive Server data, and the `text_events` table, all of which are integral to recovering your text indexes without having to drop and re-create them.

Customizable backup and restore

`backCmd` and `restoreCmd` allow customizable backup and restore commands to be used instead of `tar` or `zip` commands when backing up collection files. If `backCmd` and `restoreCmd` are blank, the default commands are used; otherwise, the specified command is executed. String substitution is performed before execution to allow specification of input and output directories and collection identification. The string substitution is defined as follows:

- `${backDir}` is replaced by the *backup* directory specified as the “backDir” configuration parameter.
- `${collDir}` is replaced by the full path name for the collection.
- `${colID}` is replaced by the collection ID which is the full name of the backup file.

Backing up Verity collections

The `sp_text_dump_database` system procedure backs up collections and (optionally) the user and `text_db` databases. `sp_text_dump_database` also maintains the `text_events` table by deleting entries that are no longer needed for recovery.

During a backup, the Enhanced Full-Text Search engine processes queries, but defers any update requests until the backup is complete. This eliminates the need to shut down and restart the Enhanced Full-Text Search engine.

Run `sp_text_dump_database` from the database containing the text indexes you are backing up. Make sure all the required servers are running when issuing `sp_text_dump_database`. `sp_text_dump_database` unconditionally backs up all indexes of all enhanced text servers. The backup of the text indexes is placed in the directory specified in the `backDir` configuration parameter. The output of dump database is written to the Enhanced Full-Text Search error log. Sybase recommends dumping the current database and the `text_db` database at the time the text indexes are backed up. However, this is optional.

For example, to back up the text indexes, the `sample_colors_db` database to the `/work2/sybase/colorsbackup` directory, and the `text_db` database to the `/work2/sybase/textdbbackup` directory, enter:

```
sp_text_dump_database @backupdbs =  
INDEXES_AND_DATABASES, @current_to = "to  
' /work2/sybase/colorsbackup' ", @textdb_to="to  
' /work2/sybase/textdbbackup' "
```

Note It is important that you back up the `text_db` database whenever you back up text indexes, since that database contains the metadata for all text indexes.

`sp_text_dump_database` may fail on Solaris if the required file size is greater than 2GB.

See `sp_text_dump_database` on page 150.

Restoring collections and text indexes from backup

`sp_text_load_index` system procedure restores text indexes that have been backed up with the `sp_text_dump_database` system procedure.

As Database Administrator, perform the following procedures to restore your Verity collections:

- 1 Restore your Adaptive Server user database and `text_db` database. This returns the source tables, metadata, and `text_events` table to a consistent and predictable state. Follow the procedures described in Chapter 27, “Backing Up and Restoring User Databases,” in the *System Administration Guide*, to restore user and `text_db` databases.
- 2 Run `sp_text_load_index` to restore the Verity collection from the most recent index dump. The procedure resets the status of all `text_events` table entries made since the last index dump to “unprocessed” and notifies the Enhanced Full-Text Search engine to process those events.

Example: To restore the sample_colors_db database and all of its text indexes:

1 Restore the text_db database:

```
1> use master
2> go
1> load database text_db from '/work2/sybase/textdbbackup'
2> go
```

2 Restore the sample_colors_db database:

```
1> load database sample_colors_db from '/work2/sybase/colorsbackup'
2> go
```

3 Bring the text_db and sample_colors_db databases online:

```
1> online database text_db
2> online database sample_colors_db
3> go
```

4 Restore the text index:

```
1> use sample_colors_db
2> go
1> sp_text_load_index
2> go
```

See sp_text_load_index on page 154.

Performance and Tuning

The Enhanced Full-Text Search engine is shipped with a default configuration. You can optimize the performance of the Enhanced Full-Text Search engine by altering the default configuration so that it better reflects the needs of your site. This chapter describes ways in which you can enhance performance.

Topic	Page
Updating existing indexes	79
Increasing query performance	80
Reconfiguring Adaptive Server	81
Reconfiguring the Enhanced Full-Text Search engine	82
Using <code>sp_text_notify</code>	83
Configuring multiple Enhanced Full-Text Search engines	84
Multiple users	85
File Descriptors and Enhanced Full-Text Search	86

Updating existing indexes

The amount of time it takes to update records in a text index can be reduced by enabling (turning on) trace flag 11 or trace flag 12, or both:

- Enabling trace flag 11 disables Verity collection optimization. This means that Verity does not optimize the text index after you issue `sp_text_notify`, which is a performance gain. If trace flag 11 is turned off (the default), the Enhanced Full-Text Search engine calls Verity to optimize the text index at the end of `sp_text_notify` processing, which can delay the completion of `sp_text_notify`.

With Enhanced Full-Text Search Specialty Data Store, you can use `sp_optimize_text_index` to optimize a text index at a later time if trace flag 11 is enabled. See `sp_optimize_text_index` on page 143.

- Enabling trace flag 12 disables the Enhanced Full-Text Search engine from returning `sp_statistics` information. If trace flag 12 is turned off (the default), an `update statistics` command is issued to the Enhanced Full-Text Search engine, which can delay the completion of `sp_text_notify`.

If updates to the text index occur as often as every few seconds, you may improve performance by disabling the update statistics processing and the Verity optimization, or both, for most of the updates.

Trace flags 11 and 12 can be enabled and disabled interactively using `sp_traceon` and `sp_traceoff` in the Enhanced Full-Text Search engine.

Increasing query performance

Two issues can significantly improve query performance:

- Limiting the number of rows returned by the Enhanced Full-Text Search engine
- Ensuring the correct join order for queries

Limiting the number of rows

Use the `max_docs` pseudo column to limit the number of rows returned by the Enhanced Full-Text Search engine. The fewer the number of rows returned by the Enhanced Full-Text Search engine, the faster Adaptive Server can process the join between the source table and the index table.

Ensuring the correct join order for queries

The more tables and text indexes that are listed in a join, the greater the chance that the query will run slowly because of incorrect join order. Queries run fastest when the text index is queried first during a join between the text index and one or more tables.

To ensure correct join order:

- Make sure that a unique clustered or nonclustered index is created on the `IDENTITY` column of the table being indexed

- Limit joins to one base table and one text index

If a query is running slowly, use showplan or enable trace flag 11205, and examine the join order. Trace flag 11205 dumps remote queries to the Adaptive Server error log file. The fastest queries contain an index_any search condition in the where clause and query the text index first.

The slowest queries contain the id column in the text index where clause and query the indexed table first. In this case, rewrite the query or use forceplan to force the join order that is listed in your query. For more information about forceplan, see Chapter 3, “Advanced Optimizing Techniques,” in the *Performance and Tuning Guide: Optimizer and Abstract Plans*.

Reconfiguring Adaptive Server

You can improve the performance of the Enhanced Full-Text Search engine by resetting the Adaptive Server configuration parameters discussed in this section. (For information about setting configuration parameters with sp_configure, see Chapter 4, “Setting Configuration Parameters,” in the *System Administration Guide*.)

cis cursor rows

cis cursor rows parameter specifies the number of rows received by Adaptive Server during a single fetch operation. The default number for cis cursor rows is 50. Increasing this number increases the number of rows received by Adaptive Server from the Enhanced Full-Text Search engine during a fetch operation. However, the number you set for cis cursor rows, the more memory Adaptive Server dynamically allocates to return the result set.

cis packet size

`cis packet size` determines the number of bytes contained in a single network packet. The default for `cis packet size` is 512. You must specify values for this parameter in multiples of 512. Increasing this parameter improves the performance of the Enhanced Full-Text Search engine because, with a larger packet size, it returns fewer packets for each query. However, the larger the number you set for `cis packet size`, the more memory Adaptive Server allocates for that parameter.

The `cis packet size` parameter is dynamic; you do not need to restart Adaptive Server for this parameter to take effect.

Note If you change the `cis packet size`, you must also change `max_packet_size` in the Enhanced Full-Text Search engine configuration file to the same value. If Component Integration Services is used to access other remote servers, the `max network packet size` on those servers must be increased as well.

You must restart the Enhanced Full-Text Search engine for the `max_packet_size` parameter to take effect.

Reconfiguring the Enhanced Full-Text Search engine

You can improve the performance of the Enhanced Full-Text Search engine by reconfiguring the Enhanced Full-Text Search engine configuration parameters discussed in this section. See “Modifying the configuration parameters” on page 67.

batch_size

`batch_size` determines the number of rows per batch the Enhanced Full-Text Search engine indexes. `batch_size` has a default of 500 (that is, 500 rows of data indexed per batch). Performance improves if you increase the size of the batches that are indexed. However, the larger the batch size, the more memory the Enhanced Full-Text Search engine allocates for this parameter.

When considering how large to set `batch_size`, consider the size of the data on which you are creating a text index. When creating the text index, the Enhanced Full-Text Search engine allocates memory equal to (in bytes):

$(\text{amount of space needed for data}) \times (\text{batch_size}) = \text{memory used}$

For example, if the data you are indexing is 10,000 bytes per row, and `batch_size` is set to 500, then the Enhanced Full-Text Search engine must allocate almost 5MB of memory when creating the text index.

Base the batch size you choose on the typical size of your data and the amount of memory available on your machine.

min_sessions and max_sessions

`min_sessions` and `max_sessions` determine the minimum and maximum number of user connections allowed for the Enhanced Full-Text Search engine. Each user connection requires approximately 5MB of memory. Do not set `max_sessions` to an amount that exceeds your available memory. Also, because the memory for `min_sessions` is allocated at start-up, if you set the number for `min_sessions` extremely high (to allow for a large number of user connections), a large percentage of your memory is dedicated to user connections for the Enhanced Full-Text Search engine.

You may improve the performance of the Enhanced Full-Text Search engine by setting `min_sessions` equal to the average number of user sessions that will be used. Doing so prevents the Enhanced Full-Text Search engine from having to allocate memory at the start of the user session.

Using `sp_text_notify`

Review the needs of your site before you decide how often to issue `sp_text_notify`.

Using `sp_text_notify` produces a load on the Enhanced Full-Text Search engine as the system procedure reads the data and updates the text collections. Depending on the size of this load, the performance hit for issuing `sp_text_notify` can be substantial. Because of the performance implications, you must determine how up-to-date the indexes need to be. If they must be close to real-time, then issue `sp_text_notify` frequently (as often as every 5 seconds). However, if your indexes do not need to be that current, you may want to wait until the system is not active before you issue `sp_text_notify`.

Note You cannot issue `sp_text_notify` from within a transaction.

Configuring multiple Enhanced Full-Text Search engines

For tables that are used frequently, you can improve performance by placing the text indexes for these tables on separate Enhanced Full-Text Search engines. Performance improves because users can spread their queries over a number of Enhanced Full-Text Search engines, instead of sending all queries to a single engine. Each Adaptive Server can connect to multiple Enhanced Full-Text Search engines, but each Enhanced Full-Text Search engine can connect to only one Adaptive Server.

Creating multiple Enhanced Full-Text Search engines at start-up

If you are initially creating multiple Enhanced Full-Text Search engines, you can edit the `installtextserver` script so that it includes all of those Enhanced Full-Text Search engines. See “Editing the `installtextserver` script” on page 15.

Adding Enhanced Full-Text Search engines

You can add Enhanced Full-Text Search engines after your initial start-up by issuing `sp_addserver` from isql:

```
sp_addserver server_name [, server_class [,  
physical_name]]
```

where:

- *server_name* is the name used to address the server on your system (in this case, the Enhanced Full-Text Search engine).
- *server_class* identifies the category of server being added. For the Enhanced Full-Text Search engine, the value is “sds”.
- *physical_name* is the name in the interfaces file used by the server *server_name*.

For more information, see `sp_addserver` in the *Reference Manual*.

For example, to add an Enhanced Full-Text Search engine named BLUE, enter:

```
sp_addserver BLUE, sds, BLUE
```

After you configure and start the Enhanced Full-Text Search engine, you can use the following syntax to see if you can connect to the Enhanced Full-Text Search engine from the Adaptive Server:

```
server_name...sp_show_text_online
```

For example, to connect to a server named BLUE, enter:

```
BLUE...sp_show_text_online
```

Configuring additional Enhanced Full-Text Search engines

Each Enhanced Full-Text Search engine requires its own:

- Interfaces file entry
- Configuration file

All Enhanced Full-Text Search engines use the same database (named `text_db` by default) for storing text index metadata and the same `vesaux` and `vesauxcol` tables.

Multiple users

The following tips may help avoid deadlocks with multiple users:

- 1 Make sure Adaptive Server is using the same number of connections as the Enhanced Full-Text Search. 100 is the default.

```
sp_configure "user connections", 100
```

- 2 Make sure the `vesaux`, `vesauxcol` and `text_events` tables (in the model, or in each of your new databases) are using row-level locking.

For existing tables: `alter table table_name lock datarows`

For new tables: `create table ... lock datarows`

- 3 For large batches of commands, try to break them into smaller transactions.

- 4 If deadlocks still occur, increase the number of locks available to Adaptive Server, and adjust the row lock promotion settings. See the *System Administration Guide*.

File Descriptors and Enhanced Full-Text Search

Enhanced Full-Text Search makes extensive use of file descriptors when executing searches. With concurrent searches and large text indexes, this may cause a connection to receive this error message:

```
ERRORMSG, Error    (): Available files (-1) less than min  
5
```

This message indicates that the Enhanced Full-Text Search process has run out of file descriptors, based on the limit for the process. If you see this error message, raise the process limit for file descriptors for the Enhanced Full-Text Search process.

`max_session_fd` limits the number of file descriptors an Enhanced Full-Text Search session can allocate. You can use this in situations where the file descriptors limit cannot be raised.

The `max_session_fd` defaults to 0, which means that each session is limited only by the Enhanced Full-Text Search process file descriptors limit. The minimum setting for `max_session_fd` is 5.

If you are seeing the error message above and you cannot raise the file descriptor limit for the Enhanced Full-Text Search, the best way to gauge how to set this parameter is to take the $((\text{max file descriptors}) - 20) / (\text{max concurrent connections})$.

For example, if the file descriptors limit is set to 1024 and the maximum number of concurrent connections to the Enhanced Full-Text Search is 50:

```
((1024) - 20) / 50 = ~ 20
```

The more available file descriptors to an Enhanced Full-Text Search session, the better.

Because the maximum number of file descriptors that each Enhanced Full-Text Search session uses is being limited, performance may be decreased. Sybase recommends that you use `max_session_fd` carefully.

You must restart the Enhanced Full-Text Search process for `max_session_fd` changes to take effect.

Verity Topics

This chapter is reproduced with permission from Verity. It is provided to give Enhanced Full-Text Search users insight into Verity Topics.

Topic	Page
What are topics?	87
Using a topic outline file	88
Making topics available	89
Knowledge bases of topics	89
Structure of topics	91
Maximum number of topics	94
Verity query language	95
Sample topic outlines	100
Operator reference	102
Modifier reference	111
Weights and document importance	113
Topic scoring and document importance	119
Designing topics	122
Preparing your topic design	122
Topic design strategies	124
Designing the initial topic	126

What are topics?

A topic is a grouping of information related to a concept, or a subject area. Topics provide a convenient means by which you can encapsulate knowledge, and make it available to end users as a shared resource. By adding topics to your Verity application, users can more easily perform searches over the subject matter which the topics represent.

Topics are combined to form knowledge bases that represent a catalog of knowledge that users can tap into when performing searches. Knowledge bases offer users the ability to find the information they want without having to compose sophisticated queries using complex syntax.

Topic organization

Topics organize groups of related search criteria in a format similar to that of an outline. Operators and modifiers act as the glue that joins related groups of search criteria. You can create topics as independent units, or as units with relationships to other topics in a hierarchical structure.

Weight assignments

You can even give some groups of search criteria more weight than other groups of search criteria in a topic's structure. Assigning weight to search criteria affects the importance of documents selected in a search; the closer a document is to the top of the results list, the more important, or relevant, the document is to the search criteria. A search criteria weight is a number between 0.01 and 1.00. The position of a selected document in the results list can help you determine at a glance how relevant the document is compared to the search criteria.

Using a topic outline file

You can compose topics by creating a topic outline file.

A topic outline file is an ASCII text file in a structured format that contains topic definitions. A topic outline file might appear as follows:

```
$Control:1
art <Accrue>
*performing-arts <Accrue>
**0.80 "ballet"
**0.50 "drama"
**0.50 'dance'
**0.80 "opera"
**0.80 "symphony"
**0.90 "chamber music"
```



```
**"Isaac Stern"  
*film <Accrue>  
**directors <Filter>  
/definition="title CONTAINS Truffaut"  
*visual-arts <Accrue>  
literature <Accrue>  
philosophy <Accrue>  
language <Accrue>  
history <Accrue>  
$$
```

You can create a topic outline file with any text editor.

Making topics available

The topics you make available to users must exist within a topic set that is generated using the `mktopics` utility. Verity topic sets generated by `mktopics` can be used by any Verity application. A single topic set supports a maximum of 20,000 topic definitions, and the exact number of topics allowed for one topic set depends on the Verity query language used to define them.

Setup process

Making topics available to users is a three-step process, as outlined below.

- 1 Create topic definitions using a topic outline file.
- 2 Generate a topic set. You can create a topic set using the `mktopics` utility. The `mktopics` utility creates the topic set and can also index the topics over a specific collection.
- 3 Import the topic set to the Enhanced Full-Text Search engine.

Knowledge bases of topics

This section discusses the principle features of knowledge bases, and the organization format used to define topics for them.

The following aspects of topic knowledge bases are covered:

- Combining topics into a knowledge base
- The structure of topics
- The relationship between topics and subtopics
- Topic types
- Naming topics

Combining topics into a knowledge base


A topic is simply a grouping of information related to a concept, or a subject area. A knowledge base is a grouping of these concepts called topics.

Combining topics into a knowledge base provides users with the ability to look up concepts saved as topics in a convenient fashion.


The subject area of a topic is typically identified by the topic's name. In the example below, the subject of the topic is *performing-arts*. This topic is composed of two structural elements, its name, *performing-arts*, and its evidence topics, *ballet*, *musical*, *dance*, *opera*, *symphony*, and *drama*.

Operators and modifiers act as the glue that joins related evidence topics.

Operators represent logic to be applied to evidence topics. This logic defines the qualifications of the kinds of documents you want to find. Modifiers apply further logic to evidence topics. For example, a modifier can specify that documents containing an evidence topic not be included in the list of results.



A topic's structure becomes more sophisticated as topics are added to it. In the next example, the topic film has been added to the structure to form what is now the top-level topic, art. In this structure, performing-arts and film are subtopics of the topic art.




Sophisticated topics are composed of top-level topics, subtopics, and evidence topics. These elements determine the related subject areas of a topic. Typically, a knowledge base consists of several top-level topics. Subtopics and evidence topics can be used by multiple top-level topics.

Structure of topics

The structure of topics affects how the topic is interpreted during search processing. Designing topics so that they accurately express a concept involves defining a topic structure with the components described below.


Top-level topics

Top-level topics are the highest topics defined in a topic structure. Top-level topics represent the subject areas you want a Verity search agent to find. In the example below you could think of literature, philosophy, languages, history, and art as top-level subtopics that comprise the top-level topic, liberal-arts.



Subtopics

Subtopics form the levels between top-level topics and evidence topics. The name of a subtopic should identify the subject area that its subtopics or evidence topics combine to describe. For example, the subtopic visual-arts includes several related words, or evidence topics, as shown below:




Evidence topics

Evidence topics are the lowest units of a topic structure. Evidence topics are strings, made up of combinations of alphanumeric characters. An evidence topic can contain up to 128 alphanumeric characters.

Topic and subtopic relationships

Each topic and its associated subtopics form a hierarchical parent and child relationship. In the example below, the subtopics performing-arts, film, visual-arts, and video are children of the art topic. The art topic itself is a child of the liberal-arts topic. The liberal-arts topic could in turn be a child of successively higher parent topics within the structure.



When you use a topic to perform a search, the subject area defined by the topic includes its subtopics, their subtopics, and so on, down to the evidence topics of the structure. Topics that are not direct descendants of the topic you use are not included in the search.

In the example above, for instance, a search using the film topic would cause the Verity search engine to find documents containing information on film, motion pictures, movies, and art films. In this example, the search would not find documents related to the performing-arts, visual-arts, or video topics since these topics are not children, of the film topic. However, if the art topic was used, the search would find documents related to all the art topic's children, which includes performing-arts, film, visual-arts, and video.

Maximum number of topics

A single topic set representing a knowledge base can consist of as many as 20,000 topics. This includes top-level topics, subtopics, and evidence topics. Topics containing as many as 1,000 subtopics may exceed memory limitations when used in a search.

Topic naming issues

- A topic name can contain up to 128 alphanumeric characters, including hyphens and underscores.
- Topic names and evidence topics are normally case-insensitive. You can name a evidence topic using all caps, as in APPLE, initial caps, as in Apple, or all lower-case, as in apple. Case is not considered when a search is performed. Thus, if your evidence topic is entered as APPLE, the Verity search engine selects documents containing “APPLE”, “Apple”, or “apple”.

You can, however, use the CASE modifier to specify that case match the entry of a evidence topic.

Verity query language

This section describes the Verity Query Language, consisting of operators and modifiers that you can use to create topics. Operators represent logic to be applied to search elements which can be combined to create a topic. This logic defines the qualifications of the kinds of documents you want to find. Modifiers apply further logic to search elements. For example, a modifier can specify that a search element be case-sensitive.

The information in this section includes the following:

- Query language summary
- Operator precedence rules
- Sample topic outlines
- Operator reference
- Modifier reference

Query language summary

The Verity Query Language consists of operators and modifiers. Both operators and modifiers represent logic to be applied to a search element. This logic defines the qualifications a document must meet to be retrieved. Operators are classified by their type, as follows:

- Evidence operators
- Proximity operators
- Relational operators
- Concept operators
- Boolean operators

Modifiers extend the logic applied by operators and are used in combination with operators.

Evidence operators

Evidence operators expand a search word into a list of related words that are then searched for as well. When you perform a search using an evidence operator, documents containing one or more occurrences of the words in the expanded word list are documents containing the word specified, as well as its synonyms. Documents retrieved using evidence operators are not relevance-ranked unless you use the MANY modifier. See “MANY modifier” on page 112. Table 8-1 describes each evidence operator.

Table 8-1: Evidence operators

Operator name	Description
WORD	Selects documents that include one or more instances of a word you specify.
STEM	Selects documents that include one or more variations of the search word you specify.
THESAURUS	Selects documents that contain one or more synonyms of the word you specify.
WILDCARD	Selects documents that contain matches to a character string containing variables.
SOUNDEX	Selects documents that include one or more words that “sound like,” or whose letter pattern is similar to, the word specified.
NEAR/N	Expands the search to include the word you enter plus words that are similar to the query term. This operator performs “approximate pattern matching” to identify similar words.

Proximity operators

Proximity operators specify the relative location of specific words in the document; that is, specified words must be in the same phrase, paragraph, or sentence for a document to be retrieved. In the case of the NEAR and NEAR/N operators, retrieved documents are relevance-ranked based on the proximity of the specified words. When proximity operators are nested, the ones with the broadest scope should be used first; that is, phrases or individual words can appear within SENTENCE or PARAGRAPH operators, and SENTENCE operators can appear within PARAGRAPH operators. Table 8-2 describes each proximity operator.

Table 8-2: Proximity operators

Operator name	Description
IN	Selects documents that contain specified values in one or more document zones. A document zone represents a region of a document, such as the document's summary, date, or body text.
PHRASE	Selects documents that include a phrase you specify. A phrase is a grouping of two or more words that occur in a specific order.
SENTENCE	Selects documents that include all of the words you specify within a sentence.
PARAGRAPH	Selects documents that include all of the search elements you specify within a paragraph.
NEAR	Selects documents containing specified search terms within close proximity to each other.
NEAR/N	Selects documents containing two or more words within N number of words of each other, where N is an integer.

Relational operators

Relational operators search document fields (such as AUTHOR) that have been defined in the collection. These operators perform a filtering function by selecting documents that contain specified field values. The fields that are used with relational operators can contain alphanumeric characters. Documents retrieved using relational operators are not relevance-ranked, and you cannot use the MANY modifier with relational operators.

When creating topics, relational operators are always used in conjunction with the special FILTER operator. See the example under the topic “visual-arts” in “Sample Topic Outlines” later in this section for the proper syntax.

A number of relational operators are available for numeric and date comparisons, including the following: = (equals), > (greater than), >= (greater than or equal to), < (less than), <= (less than or equal to).

A number of relational operators are available for text comparisons, including the following.

Table 8-3: Relational operators

Operator name	Description
CONTAINS	Selects documents by matching the word or phrase you specify with values stored in a specific document field.
MATCHES	Selects documents by matching the character string you specify with values stored in a specific document field.
STARTS	Selects documents by matching the character string you specify with the starting characters of the values stored in a specific document field.
ENDS	Selects documents by matching the character string you specify with the ending characters of the values stored in a specific document field.
SUBSTRING	Selects documents by matching the character string you specify with a portion of the strings of the values stored in a specific document field.

Concept operators

Concept operators combine the meaning of search elements to identify a concept in a document. Documents retrieved using concept operators are relevance-ranked. Table 8-4 describes each concept operator.

Table 8-4: Concept operators

Operator name	Description
AND	Selects documents that contain all of the search elements you specify.
OR	Selects documents that show evidence of at least one of your search elements.
ACCRUE	Selects documents that include at least one of the search elements you specify.

Boolean operators

Boolean operators can be assigned to topics to retrieve documents containing any or all of the children of that topic. Unlike topics created using the concept operators, Boolean operators do not accept weights. Table 8-5 describes each Boolean operator.

Table 8-5: Boolean operators

Operator name	Description
ALL	Selects documents that contain all children of a topic.
ANY	Selects documents that contain at least one of the children of a topic.

Modifiers

Modifiers affect the behavior of operators. Table 8-6 describes each modifier.

Table 8-6: Modifiers

Operator name	Description
CASE	Performs a case-sensitive search.
MANY	Counts the density of words or phrases in a document and produces a relevance-ranked score for the retrieved documents.
NOT	Excludes documents that show evidence of the specified word or phrase.
ORDER	Specifies the order in which search elements must occur.

Operator precedence rules

The Verity search engine uses precedence rules to determine how operators can be assigned. These rules state that some operators rank higher than others when assigned to topics, and affect how document selections are performed.

Table 8-7 describes how precedence rules apply to operators.

Table 8-7: Precedence rules

Operator	Precedence	How precedence is determined
AND OR ACCRUE	Highest precedence	The concept operators take the highest precedence over the other operators. Thus, subtopics of topics using these operators can be assigned any of the operators listed below under “incremental precedence” or “lowest precedence.”
ALL PARAGRAPH SENTENCE NEAR NEAR/N PHRASE ANY	Incremental precedence (in descending order)	The proximity operators refer to incremental ranges that exist within a document. Subtopics of topics using these operators can be assigned their next lowest operator in the precedence order. Thus, a phrase takes precedence over a word; a sentence takes precedence over a phrase or a word; and a paragraph takes precedence over a sentence, a phrase, or a word.
WORD STEM SOUNDEX WILDCARD THESAURUS	Lowest precedence	The evidence operators reside at the lowest level in a topic structure. Because evidence operators are used with words contained in documents, these operators all have the same precedence.

To avoid a precedence violation, do not use ANY or ALL in a parent topic whose child topic includes a concept operator (AND, OR, ACCRUE). Topics that use ANY or ALL cannot have variable weights assigned to them, so you cannot use these operators in a parent topic with any child topic that allows variable weights (such as AND, OR, ACCRUE). Topics using ANY and ALL limit evaluation to present or not present (a score of 0.00 or 1.00). If the criteria are met, the children of these topics get an automatic score of 1.00; if the criteria are not met, the children of these topics get an automatic score of 0.00; so it is not meaningful to assign these children variable weights such as 0.80.

Sample topic outlines

The following are the same topics as you would create them in a topic outline file:

```

$Control:1
art <Accrue>
*performing-arts <Or>
**0.80 "drama"
**0.50 "theater"
**0.80 'dance'
*film <And>
**0.90 "cinema"
**0.90 "documentary"
**newsreel <Filter>
/definition="DATE >= 05/01/96"
*film-makers <Accrue>
**"Woody Allen"
*film-making <Paragraph>
**"direct"
**"produce"
*visual-arts <Accrue>
**sculpture <In>
/zonespec="title"
**painters <Filter>
/definition="Title MATCHES Famous Painters"
**<Thesaurus>
/wordtext="paint"
literature <Accrue>
*novels <Near>
**0.80 "Proust"
**0.80 "Remembrance" <Case>
*american-novel <Sentence>
**"American"
**"novel"
history <Accrue>
*<Wildcard>
/wordtext="histor*"
music <Accrue>
*jazz
**"bebop"
**<Not> "fusion"
*classical
**"Italian opera"
$$

```

Operator reference

Each operator is listed below alphabetically. Examples for many of these operators can be found in the topic outline in the previous section.

ACCRUE operator

Selects documents that include at least one of the search elements you specify. Valid search elements are two or more words or phrases. Selected documents are relevance-ranked.

The ACCRUE operator scores selected documents according to the presence of each search element in the document using a “the more, the better” approach: the more search elements found in the document, the better the document’s score. Several examples of the ACCRUE operator appear in the sample outline file in “Sample topic outlines” on page 100.

ALL operator

Selects documents that include all of the search elements you specify. Unlike the ACCRUE operator, you cannot assign weights when you use the ALL operator.

AND operator

Selects documents that contain all of the search elements you specify. Documents selected using the AND operator are relevance-ranked. The example in “Sample Topic Outlines” shows how the AND operator might be used with the topic “film.” In the example, only those documents that contain both search words and a date greater than or equal to 05/01/96 are selected and ranked according to their score.

ANY operator

Selects documents include at least one of the search elements you specify. Unlike the ACCRUE operator, you cannot assign weights when you use the ANY operator.

CONTAINS operator

Selects documents by matching the word or phrase you specify with values stored in a specific document field. When you use the CONTAINS operator, you specify the field name to search, and the word or phrase to search for.

With the CONTAINS operator, the words stored in a document field are interpreted as individual, sequential units. You may specify one or more of these units as search criteria. To specify multiple words, each word must be sequential and contiguous, and must be separated by a blank space. Use CONTAINS with the FILTER operator.

The syntax for CONTAINS is the same as that for MATCHES. See the example for MATCHES under the topic “visual arts” in “Sample topic outlines” on page 100. The example assumes that the field TITLE has been created for the collection.

The CONTAINS operator does not recognize non-alphanumeric characters. The CONTAINS operator interprets non-alphanumeric characters as a space and treats the separated values as individual units. For example, if you have defined a slash (/) as a valid character, and you enter search criteria that include this character, as in OS/2, “OS” and “2” are treated as individual units.

The CONTAINS operator does not refer to the *style.lex* file for the definition of which characters are included in a word.

ENDS operator

Selects documents by matching the character string you specify. Use ENDS with the FILTER operator. The syntax for ENDS is the same as that for MATCHES. See the example for MATCHES under the topic “visual arts” in “Sample topic outlines” on page 100. The example assumes that the field TITLE has been created for the collection.

= (EQUALS) operator

Selects documents whose document field values are exactly the same as the search string you specify. Use EQUALS with the FILTER operator. The syntax for EQUALS is the same as that for GREATER THAN OR EQUAL TO. See the example for GREATER THAN OR EQUAL TO under the topic “film” in “Sample topic outlines” on page 100. The example assumes that the field DATE has been created for the collection.

FILTER operator

The special **FILTER** operator is used in conjunction with the relational operators to do field searches. See the example under the topic “visual-arts” in “Sample topic outlines” on page 100 for the proper syntax.

> (GREATER THAN) operator

Selects documents whose document field values are greater than the search string you specify. Use **GREATER THAN** with the **FILTER** operator. The syntax for **GREATER THAN** is the same as that for **GREATER THAN OR EQUAL TO**. See the example for **GREATER THAN OR EQUAL TO** under the topic “film” in “Sample topic outlines” on page 100. The example assumes that the field **DATE** has been created for the collection.

>= (GREATER THAN OR EQUAL TO) operator

Selects documents whose document field values are greater than or equal to the search string you specify. Use **GREATER THAN OR EQUAL TO** with the **FILTER** operator. See the example under the topic “film” in “Sample topic outlines” on page 100. The example assumes that the field **DATE** has been created for the collection.

< (LESS THAN) operator

Selects documents whose document field values are less than the search string you specify. Use **LESS THAN** with the **FILTER** operator. The syntax for **LESS THAN** is the same as that for **GREATER THAN OR EQUAL TO**. See the example for **GREATER THAN OR EQUAL TO** under the topic “film” in “Sample topic outlines” on page 100. The example assumes that the field **DATE** has been created for the collection.

<= (LESS THAN OR EQUAL TO) operator

Selects documents whose document field values are less than or equal to the search string you specify. Use **LESS THAN OR EQUAL TO** with the **FILTER** operator. The syntax for **LESS THAN OR EQUAL TO** is the same as that for **GREATER THAN OR EQUAL TO**. See the example for **GREATER THAN OR EQUAL TO** under the topic “film” in “Sample topic outlines” on page 100. The example assumes that the field **DATE** has been created for the collection.

IN operator

Selects documents that contain specified values in one or more document zones. A document zone represents a region of a document, such as the document’s summary, date, or body text. The **IN** operator only works if document zones have been defined in your collections. If you use the **IN** operator to search collections for which zones are not defined, no documents will be selected. In addition, the zone name you specify must match the zone names defined in your collections. Consult your collection administrator to determine which zones have been defined for specific collections. The example in “Sample topic outlines” on page 100 shows how **IN** might be used with the word “sculpture” and the **TITLE** zone.

MATCHES operator

Selects documents by matching the character string you specify with values stored in a specific document field. When you use the **MATCHES** operator, you specify the field name to search, and the word, phrase, or number to search for.

Unlike the **CONTAINS** operator, the search criteria you specify with a **MATCHES** operator must match the field value exactly for a document to be selected. With the **MATCHES** operator, any occurrence of a search string that appears as a portion of a value is not selected; only values matching the entire search string are selected.

You can use question marks (?) to represent individual variable characters within a string, and asterisks (*) to match multiple variable characters within a string.

Use MATCHES with the FILTER operator. The example in “Sample topic outlines” on page 100 shows how MATCHES might be used with the phrase “famous painters” and the TITLE field. The example assumes that the field TITLE has been created for the collection.

NEAR operator

Selects documents containing specified search terms within close proximity to each other. Document scores are calculated based on the relative number of words between search terms. For example, if the search expression includes two words, and those words occur next to each other in a document (so that the region size is two words long), then the score assigned to that document is 1.00. Thus, the document with the smallest region containing all search terms always receives the highest score. Documents whose search terms are not within 1000 words of each other are not selected, since the search terms are probably too far apart to be meaningful within the context of the document.

The NEAR operator is similar to the other proximity operators in the sense that the search words you enter must be found within close proximity of one another. However, unlike other proximity operators, the NEAR operator calculates relative proximity and assigns scores based on its calculations.

The example in “Sample topic outlines” on page 100 shows how NEAR might be used with the topic “novels.”

NEAR/N operator

Selects documents containing two or more words within N number of words of each other, where N is an integer. Document scores are calculated based on the relative distance of the specified words when they are separated by N words or less. Documents containing the specified words separated by more than N words are not selected. For example, if the search expression NEAR/5 is used to find two words within five words of each other, a document that has the specified words within three words of each other is scored higher than a document that has the specified words within five words of each other.

The N variable can be an integer between 1 and 1,024, where NEAR/1 searches for two words that are next to each other. If N is 1,000 or above, you must specify its value without commas, as in NEAR/1000.

The NEAR/N operator is similar to the other proximity operators in the sense that the search words you enter must be found within a close proximity of one another. However, unlike other proximity operators, the NEAR/N operator assigns scores based on relative proximity.

OR operator

Selects documents that show evidence of at least one of your search elements. Documents selected using the OR operator are relevance-ranked. The example in “Sample topic outlines” on page 100 shows how you might use OR with the topic “performing-arts.”

PARAGRAPH operator

Selects documents that include all of the search elements you specify within a paragraph. Valid search elements are two or more words or phrases. You can specify search elements in a sequential or a random order. Documents are retrieved as long as search elements appear in the same paragraph. The example in “Sample topic outlines” on page 100 shows you how you might use PARAGRAPH with the topic “film-making.”

PHRASE operator

Selects documents that include a phrase you specify. A phrase is a grouping of two or more words that occur in a specific order. You must use the PHRASE operator when you enter more than one word in the evidence field. Words with the PHRASE operator are displayed in double quotes. The example in “Sample topic outlines” on page 100 shows “Woody Allen” and “Italian opera” as uses of the PHRASE operator.

SENTENCE operator

Selects documents that include all of the words you specify within a sentence. You can specify search elements in a sequential or a random order. Documents are retrieved as long as search elements appear in the same sentence. The example in “Sample topic outlines” on page 100 shows how you how you might use SENTENCE with the topic “american-novel.”

SOUNDEX operator

Selects documents that include one or more words that “sound like,” or whose letter pattern is similar to, the word specified. Words have to start with the same letter as the word you specify to be selected. For example, when you use SOUNDEX with “sale,” the documents selected will include words such as “sale,” “sell,” “seal,” “shell,” “soul,” and “scale.” Documents are not relevance-ranked unless the MANY modifier is used.

STARTS operator

Selects documents by matching the character string you specify with the starting characters of the values stored in a specific document field. Use STARTS with the FILTER operator. The syntax for STARTS is the same as that for MATCHES. See the example for MATCHES under the topic “visual arts” in “Sample topic outlines” on page 100. The example assumes that the field TITLE has been created for the collection.

STEM operator

Selects documents that include one or more variations of the search word you specify. Words with the STEM operator are displayed in single quotes. In the example in “Sample Topic Outlines,” the word “dance” is used with the STEM operator. Documents selected will therefore include words such as “dances,” “danced,” and “dancing,” as well as “dance.”

SUBSTRING operator

Selects documents by matching the character string you specify with a portion of the strings of the values stored in a specific document field. The characters that comprise the string can occur at the beginning of a field value, within a field value, or at the end of a field value. The syntax for SUBSTRING is the same as that for MATCHES. See the example for MATCHES under the topic “visual arts” in “Sample Topic Outlines.” The example assumes that the field TITLE has been created for the collection.

THESARUS operator

Selects documents that contain one or more synonyms of the word you specify. For example, when you use the word “altitude” with the THESARUS operator, the documents selected will include words such as “height” and “elevation.” Documents are not relevance-ranked unless the MANY modifier is used.

TYPO/N operator

The TYPO/N operator expands the search to include the specified word plus words that are similar. The optional *N* variable specifies the maximum number of errors between the query and the matched term. For example, TYPO mouse returns documents that include words such as “house,” “louse,” and “moose.”

WILDCARD operator

Selects documents that contain matches to a character string containing variables. The WILDCARD operator lets you define a search string with variables, which can be used to locate related word matches in documents. The example in “Sample topic outlines” on page 100 shows how you might use the string “histor*” to search for words such as “history,” “historical,” and “historian.” Documents are not relevance-ranked unless the MANY modifier is used.

Using wildcard special characters

You can use the following wildcard characters to represent variable portions of search strings with the WILDCARD operator.

Table 8-8: Wildcard Special Characters

Character	Function
?	Specifies one of any alphanumeric character, as in ?an, which locates “ran,” “pan,” “can,” and “ban.” It is not necessary to specify the WILDCARD operator when you use the question mark. The question mark is ignored in a set ([]) or in an alternative pattern ({ }).
*	Specifies zero or more of any alphanumeric character, as in corp*, which locates “corporate,” “corporation,” “corporal,” and “corpulent.” It is not necessary to specify the WILDCARD operator when you use the asterisk, and you should not use the asterisk to specify the first character of a wildcard string. The asterisk is ignored in a set ([]) or in an alternative pattern ({ }).

Character	Function
[]	Specifies one of any character in a set, as in <WILDCARD> `c[auo]t`, which locates “cat,” “cut,” and “cot.” Note that you must enclose the word which includes a set in backquotes (` `), and there can be no spaces in a set.
{ }	Specifies one of each pattern separated by a comma, as in <WILDCARD> `bank{s,er,ing}`, which locates “banks,” “banker,” and “banking.” Note that you must enclose the word which includes a pattern in backquotes (` `), and there can be no spaces in a set.
^	Specifies one of any character not in the set, as in <WILDCARD> `st[^oa]ck`, which excludes “stock” and “stack” but locates “stick” and “stuck.” Note that the caret (^) must be the first character after the left bracket ([) that introduces a set.
-	Specifies a range of characters in a set, as in <WILDCARD> `c[a-r]t`, which locates every three-letter word from “cat” to “crt.”

Searching for nonalphanumeric characters

Remember that you can search for nonalphanumeric characters only if the *style.lex* file used to create the collections you are searching is set up to recognize the characters you want to search for. Consult your collection administrator for information.

Searching for wildcard characters as literals

The wildcard characters listed above are interpreted as wildcard characters, not literal characters, unless they are delimited by a backslash (\). If you want a wildcard character to be interpreted as a literal in a wildcard string, you must precede the character with a backslash. For example, to match the literal asterisk (*) in a wildcard string, you delimit the character as follows:

```
<WILDCARD> a\*
```

Searching for special characters as literals

The following nonalphanumeric characters perform special, internal functions, and by default are not treated as literals in a wildcard string:

- comma ,
- left and right parentheses ()
- double quotation mark “
- backslash \
- at sign @

- left curly brace {
- left bracket [
- less than sign <
- backquote `

To interpret special characters as literals, you must surround the whole wildcard string in backquotes (`). For example, to search for the wildcard string “a{b”, you surround the string with backquotes, as follows:

```
<WILDCARD> `a{b`
```

To search for a wildcard string that includes the literal backquote character (`), you must use two backquotes together and surround the whole wildcard string in backquotes (`), as follows:

```
<WILDCARD> ``n``
```

You can only search on backquotes if the *style.lex* file used to create the collections you are searching is set up to recognize the backquote character. Consult your collection administrator for information.

WORD operator

Selects documents that include one or more instances of a word you specify. Words with the WORD operator are displayed in double quotes. The example in “Sample topic outlines” on page 100 displays many instances of the WORD operator.

Modifier reference

Modifiers further specify the behavior of operators. For example, you can use the CASE modifier with an operator to specify that the case of the search word you enter be considered a search element as well. Modifiers include CASE, MANY, NOT, and ORDER, which are described below.

CASE modifier

Use the CASE modifier with the WORD or WILDCARD operator to perform a case-sensitive search, based on the case of the word or phrase specified.

By default, documents containing any occurrences of a search word or phrase are retrieved regardless of case. To use the CASE modifier, you simply enter the search word or phrase as you wish it to appear in retrieved documents – in all uppercase letters, in mixed uppercase and lowercase letters, or in all lowercase letters. The example in “Sample topic outlines” on page 100 shows how you might use the word “Remembrance” with the CASE modifier to refer to the first word of Proust’s novel, *Remembrance of Things Past*.

MANY modifier

Counts the density of words, stemmed variations, or phrases in a document, and produces a relevance-ranked score for retrieved documents. The more occurrences of a word, stem, or phrase proportional to the amount of document text, the higher the score of that document when retrieved. Because the MANY modifier considers density in proportion to document text, a longer document that contains more occurrences of a word may score lower than a shorter document that contains fewer occurrences.

The MANY modifier can be used with the following operators: WORD, WILDCARD, STEM, SOUNDEX, PHRASE, SENTENCE, PARAGRAPH and THESAURUS.

The MANY modifier cannot be used with AND, OR, ACCRUE, or relational operators.

NOT modifier

Use the NOT modifier with a word or phrase to exclude documents that show evidence of that word or phrase. The example in “Sample topic outlines” on page 100 shows how you might use the NOT modifier to retrieve documents that mention “bebop” but not “fusion.”

ORDER modifier

Use the ORDER modifier to express the order in which search elements must occur. If search values do not occur in the specified order in a document, the document is not selected. Always place the ORDER modifier just before the operator.

You can only use the ORDER modifier with the operators ALL, PARAGRAPH, SENTENCE, and NEAR/N.

Weights and document importance

This section describes assigning weights to search criteria in topics, and the affect of weights on selected documents. The specific information covered includes:

- Which operators accept weights
- How weights affect importance
- Assigning weights
- Topic scoring and document importance

Topic weights

When processing a search agent, the Verity search engine calculates a score for each selected document behind the scenes. A document score can be in the range from 1.0 to 0.01. The higher a document's score, the more relevant it is. Using the score assignments for documents selected by a search agent, Verity applications can present relevance-ranked results in descending order to application users.

The ranking of documents is determined by the elements which comprise your search criteria. Document ranking can be affected depending on whether the search criteria includes topics, and whether topics include weights.

When creating topics, you can assign weights to the topic structure to indicate the relative importance of specific aspects of the topic definition. For example, you may be interested in two related subjects, but one subject is more important than another. You do not have to assign weights when you compose topics because default weights are assigned as appropriate when a topic set is indexed. However, by assigning weights you can fine-tune the importance of things you are looking for.

Which operators accept weights

Weights are used in conjunction with operators to compute scores for parent and child topics during a search. The weight you assign to a topic child can be a number between 0.01 and 1.00. A child's weight indicates its importance relative to the other children that have been defined for its parent. The higher a child's weight, the more important that child is considered to be with respect to its siblings.

Weights can only be assigned to the children of topics that use the concept operators, as follows:

- AND
- OR
- ACCRUE

Topics that use the proximity operators SENTENCE and PARAGRAPH, cannot be assigned a weight. These operators assume a simple "yes" or "no" presence for their children.

If a topic assigned a proximity operator is, in turn, the child of a topic which has been assigned a concept operator, such as the AND operator, that child can be assigned a weight.


It is not mandatory that you assign weights to the children of a topic just because the operator can accept weighted children. When weights are not assigned, the child has an automatic weight assignment based on its operator. Children of topics using AND and OR operators assume a weight of 1.00, and children of topics using the ACCRUE operator assume a weight of 0.50. If these operators are changed – for example, if an OR operator is changed to an ACCRUE operator – the weights of children that have not been specifically assigned a weight change accordingly. Thus, if an unweighted child of an AND topic has an assumed weight of 1.00, this assumed weight changes to 0.50 if the operator is changed to ACCRUE.

If you assign a variable weight to a topic child, then change the operator used with the parent to one that does not accept weighted children, such as the SENTENCE operator. The Verity search engine automatically assumes a weight of 1.00 while this operator is in effect. If the operator is subsequently changed to one which accepts variable-weighted children, the previously-assigned variable weights become effective once again.

How weights affect importance

When you assign a weight to the child of a topic that uses a concept operator, you specify the relative contribution of that child to the overall score produced by a topic. The higher the weight you assign to the child, the higher selected documents that contain that child appear in the list of results. Thus, weights directly affect the importance, or ranking, of selected documents.

For example, assume you have the following topic:



The evidence topics 80286 and 80386 (which describe the microprocessors used in PC products) have an automatic weight assignment of 1.00. The evidence topics 486, 386, and 286 have a relatively high probability of referring to their parent topic, so these evidence topics are assigned weights of 0.80. The evidence topic clone may or may not refer to PC clones at all; therefore, this evidence topic is assigned a weight of 0.40.

A search agent using this topic and its assigned weights might produce the following scores for the matched documents:

Scores

1.00	01-Oct-90	New Toshiba Portable Desktop Computers Offer a Serious Alternative for Desktop Users
1.00	14-Feb-90	Technology: 'Chip Set' Unveiled for Use in Making Faster Computers
0.80	13-Feb-91	CMS Enhancements Inc. Unveils New Products
0.80	01-Oct-90	Top Selling Microsoft Windows Applications Now Available in One Convenient Package
0.80	01-Oct-90	KeyCorp Successful Bidder to Acquire New York State Divisions of Empire of America Federal
0.80	15-Feb-90	Health: U.S. Birth Control Lags

If you change the weights of each evidence topic, the importance of your selection results are affected, as well. In this example, if you change the weights of the evidence topic 486 to 0.60, the evidence topic 386 to 0.45, the evidence topic 286 to 0.35, and the evidence topic clone to 0.20, your selected document scores change as follows:

Scores


1.00	01-Oct-90	New Toshiba Portable Desktop Computers Offer a Serious Alternative for Desktop Users
1.00	14-Feb-90	Technology: 'Chip Set' Unveiled for Use in Making Faster Computers
0.60	13-Feb-91	CMS Enhancements Inc. Unveils New Products
0.60	01-Oct-90	KeyCorp Successful Bidder to Acquire New York State Divisions of Empire of America Federal
0.60	15-Feb-90	Health: U.S. Birth Control Lags
0.45	01-Oct-90	Top Selling Microsoft Windows Applications Now Available in One Convenient Package

Assigning weights

When you assign a weight to a child, keep in mind that the weight you use reflects the importance of a child to its parent topic. The matched documents are ranked by importance to the search; thus, your selection results are directly affected by the weights you assign. If you change a weight, your selection results change as well.

Example:

The topic boeing-people includes three weighted children, binder, shrontz, and woodard, as shown below.



These subtopics are assigned various weights, as follows: the child binder is assigned a weight of 0.80, since this child is considered to be the most important of the three. The subtopic hitsman is assigned a “median” weight of 0.50, since this child is reasonably important with respect to the other two children. The subtopic johnson is assigned a low weight of 0.30, since this child is considered to be the least important with respect to the other children.

When the topic boeing-people is used for a search, the Verity search engine assumes that if the phrase “Paul Binder” is located within a document, there is a high probability that the document is relevant to a search that uses the topic boeing-people. Documents that contain the phrase “Frank Shrontz” are reasonably relevant to this search; documents that contain the phrase “Ron Woodard” are the least relevant.

Because the topic boeing-people has been assigned the ACCRUE operator, the documents displayed at the top of the results list are those that contain the greatest number of children; therefore all documents with references to all three people are given the most importance. Documents that contain only one name will be selected in an order that reflects the weights of each child. Thus, because the binder child has the highest weight, documents that include only one individual are ranked by those that refer to Paul Binder first, followed by Frank Shrontz, and finally Ron Woodard.

Automatic weight assignments

When you create a child, the Verity search engine automatically assigns a default weight of 0.50 for children of topics which use the ACCRUE operator. A weight of 1.00 is assigned automatically to children of topics that use the AND or OR operators. These default weights can be manually adjusted up or down, as described in “Changing weights” on page 118. When you create a evidence topic off of a topic that uses a proximity operator, default weight of 1.00 is assigned, and it cannot be changed.

Tips for assigning weights

When initially assigning weights, start with a weight of 0.50 for children of ACCRUE topics, and 1.00 for children of all other topics.

When assigning weights to children of topics that use the ACCRUE operator, you may select more relevant results if the children do not have overly high weights. For example, assigning all of the children of an ACCRUE topic weights of 1.00 causes all documents to have equal importance, regardless of how many of the children are present within the documents. The Verity search engine assigns equal importance to all documents containing only one child as well as for documents that contain all children, so you cannot distinguish between these documents when you view the selection results.

Assign weights between 0.80 and 0.20 for the best selection results.

Changing weights

Once you have assigned weights to children, you can test these weights by running a search using the parent topics to see if the documents you want are selected. If you find that you need to change the weights, you can edit the existing weight assigned to that subtopic or evidence topic. When you edit topic definitions in the topic outline file, you must rebuild the topic set using `mktopics`. For complete information about using `mktopics`, see your Verity application’s administration guide.

Topic scoring and document importance

When you use a topic to perform a search, the search agent starts its analysis by considering the evidence topics for that topic. If the evidence topic is present, it is given 1.00 score and is considered relevant to the search. If the evidence topic is absent, it is given a 0.00 score and is considered irrelevant to the search. If the evidence topics are weighted, the scores of the evidence topics are multiplied by the weights, then combines the resulting products in a manner specified by the operator of the parent topic. If this parent topic is, in turn, the child of another topic which is being searched, its score is multiplied by its assigned weight, and the resulting product is combined with the products of its siblings in a manner specified by the operator assigned to the parent topic. This process continues until the parent topic is reached.


The operators you use determine how parent and child scores contribute to the importance of a selected document. As each child in the topic is given an importance score, the following calculations are performed:

- If a topic uses an ACCRUE operator, the highest ranking result is taken from the products of each child's weight and score, then adds a little to the score for each child that is present in the document.
- If a topic uses an AND operator, the products of each child's own weight and score are compared, and the lowest product (the minimum) is taken as the score.
- If a child uses an OR operator, the products of each child's weight and score are compared, and highest product (the maximum) is taken as the score.
- If a child uses a proximity operator (PHRASE, SENTENCE, or PARAGRAPH), or a relational operator, the child receives a score of 1.00 if the topic is present, and a score of 0.00 if the topic is not present.
- An evidence topic receives a score of 1.00 if it is present, and no score of 0.00 if it is not present.

Once the final calculations for the parent topic have been performed, a matched document becomes available to the Verity application so that users can view it with its highlights.

The following example provides a breakdown of how evidence topics and subtopics are calculated to illustrate the process by which importance is assigned to selected documents.

In the following illustration, the parent topic BOEINGCO is being used in a search.



The evidence topics of each subtopic are first checked against the documents to determine if they are present. Evidence topics that are present are assigned scores of 1.00; evidence topics that are absent are assigned a score of 0.00.

The operators at the next level of a topic structure are used to combine the scores of the evidence topics. Because the operators at this level are all proximity operators (thus, no weights assigned), they all produce scores that are either 0.00 or 1.00.

For example, assume that the following evidence topics appear within a given document:

- The evidence topic “Boeing Computer Services” appears within a phrase.
- The evidence topic “Boeing Defense” appears within a paragraph. The evidence topic “Boeing Company” appears within the document.
- The evidence topic “Ron Woodard” appears within a phrase.

The other evidence topics are only partially present, or are absent. Table 8-9 shows how the presence or absence of these evidence topics affect topic scores. The score for each topic reflects the presence of all related evidence topics, based on the operators that have been assigned to the parent topics.

Table 8-9: Evidence topics and scores

Topic	Evidence topic	Evidencetopic present	Evidencetopic absent	Topic score
boeing-comp-services	boeing computer services	1		1
		1		
		1		
boeing-aerospace	boeing aerospace electronics	1		0
			1	
			1	
boeing-defense	boeing defense	1		1
		1		
boeing-label	boeing company	1		1
		1		
paul-binder	paul binder		1	0
			1	
frank-shrontz	frank shrontz		1	0
			1	
ron-woodard	ron woodard	1		1
		1		

Given the above topic scores, the operators at the next level of topics in the structure are calculated as follows:

- The subtopic boeing-comps, which uses the AND operator, has a score of 0.50.
- The subtopic boeing-people, which uses the ACCRUE operator, has a score of 0.50.

Finally, the topic BOEINGCO, which uses the OR operator, compares the products of each child's weight and score, and takes the highest product (the maximum) as its score. The selected document is thus scored as 0.50.

This process is repeated for each document. The documents are sorted by the scores of the BOEINGCO topic, and displayed in ranked order.

Designing topics

This section discusses methodologies you can use to design effective topics. You can apply the methodologies and strategies described here whether you plan to compose topics using a topic outline file or one of the Verity clients. The information in this section includes the following:

- Preparing your topic design
- Topic design strategies
- Designing the initial topic

Preparing your topic design

As you prepare your topic design, consider the naming conventions you will use. Your topic names should help identify the subject matter of the kinds of documents you want to find.

To ensure the best search performance, use alphanumeric characters (A through Z, and 0 through 9) for topic names. You can also use foreign characters whose ASCII value is greater than or equal to 128, as well as these symbols: \$ (dollar sign), % (percentage sign), ^ (circumflex), + (plus sign), - (dash), and _ (underscore). Using other nonalphanumeric characters, may cause misinterpretation of the topic name and affect results.

Understanding your information needs

You should have an understanding of the subject areas to be addressed by your topic design and be familiar with the search requirements of users at your site. The next step is to understand your informational needs, as well as the document types to be searched.

In planning your initial topic design, keep in mind that you are developing a strategy, and the topics you define are the tactics you will use to implement that strategy.

As you develop your strategy, try to answer the following questions:

- What do you want to gain by using a Verity search agents?
- What issues are to be solved by Verity search agents?

- Who will use search agents?
- What kinds of source material will be used?
- What kinds of searches will be performed?
- How are searches currently being performed?

Consider the topics you define as questions to be asked. Just as you might ask a reference librarian at your local library for information relating to a subject area, the topics you create should pose questions when creating Verity search agents.

When considering your strategy, and how Verity search applications will be implemented to provide a solution, keep in mind that a topic you design performs several roles, as follows:

- A librarian
- A research assistant
- An information repository
- A knowledge base

Understanding your documents

To build effective topics, you must have a good understanding of the types of documents being used as information sources. For example, your documents may consist of one or more of the following types of information:

- Letters
- Memos
- Reports
- Articles

Collect representative samples of the types of documents to be searched. Note common characteristics you will need to apply to the topics you design. For example, if your documents contain important terms, acronyms, or jargon, highlight them so you can create topics that search for this text.

As you collect your document samples, identify their sources – whether they are internal sources, such as internal auditing reports; or external sources, such as e-mail messages from outside organizations. This information enables you to define the subtopics for top-level topics.

Using scanned data

If your documents are scanned into electronic files using an OCR facility, determine whether the document files will be reviewed for accuracy prior to indexing. If scanned files are reviewed, consult with reviewers to ensure that standards are applied to terms, acronyms, and jargon. If scanned files are not reviewed, note possible variations that may occur. You can develop a topic that uses an OR operator to include variations.

Categorizing document samples

Once you have collected your representative document samples and have performed an initial analysis of their contents, you may want to categorize them further. The categorization process can help you to define the top-level topics and children contained in your topic design, and help determine the operators and weights to assign.

Following are categorization examples:

- Geographic location
- Sit
- Project
- Subject area
- Date

The categorization process can help you understand the common, meaningful elements which exist in your information sources. For example, if you categorize your information by date (such as a month), it makes sense to create topics that use relational operators, such as EQUALS.

Topic design strategies

Once you have an understanding of your documents, you are ready to choose a topic design strategy. There are two topic design strategies

- The “top-down” strategy considers the major subject classifications first, followed by classifications of increasing detail.

- The “bottom-up” strategy considers the detailed areas first, followed by classifications which group each detailed area by a more generalized subject.

Top-down design

A top-down strategy assumes you are designing a topic from the top-level topics down through the individual evidence topics of each subtopic. To design from the top down, you must adopt a taxonomy, or scientific classification approach, to creating a topic, as follows:

- Top-level topics – use general headings to identify the subject area
- Subtopics – use more specific headings to identify the primary groupings within the subject area, as well as topics which are increasingly more specific.
- Evidence topics – use important terms, acronyms, or jargon, to define the subject.

A top-down design works best when you have clearly-defined requirements. This approach is also ideal if your set of searchable documents is constantly growing or changing. With this strategy, for example, you are likely to define subjects which may not yet be evident in your information sources. Keep in mind that you can always add new topics, if you find that a number of new documents contain information which are not identified in your topic design.

If your information sources (that is, your set of indexed documents) changes constantly, specific subjects within documents may be missed, especially at the lowest levels. Periodically analyze the information being selected by your topics to ensure that topics critical to your application are current, and the appropriate information is being found.

Bottom-up design

A bottom-up strategy assumes you are designing a topic from the individual evidence topics up through the top-level topics that will be defined. With this strategy, your topic design objective is to select documents containing information similar to your lower-level topics.

When you use a bottom-up design, you can start with a document which contains a good representative sample of the words or phrases you want to search for. Then you can group these words by successively higher classifications.

A bottom-up design works best when you have documents that are representative of many other documents that contain similar information. This approach is also useful when your information sources are not subject to many changes or additions.

Topic designs based on the contents of specific documents may miss related subject areas in other documents. For example, if a name is used in the sample document and that name changes in other documents, the new name may be missed in searches.

In addition, the bottom-up strategy implies that your topic design is tuned to the specific document set being used to develop your topics. These documents may not be representative of all documents contained in your information sources. Periodically review the effectiveness of your searches.

Designing the initial topic

When you have decided whether to use the top-down approach or the bottom-up approach for your initial topic design, create a topic outline to identify the topic levels to be defined.

Outlining a topic

Making a topic outline can help you determine how information will be categorized at the various levels within a topic. You can use a topic outline with the top-down or the bottom-up design approach, but it is particularly useful for the top-down approach. We recommend that every topic you build be developed as an outline first, so that you can understand the relationships between topics and subtopics, and organize them to be the most useful.

A topic outline helps you understand how information might be searched for by the people who use Verity search agents at your site. You can use a topic outline to fine-tune the information specified by topics and subtopics to pinpoint document selection. Try to do the following as you develop a topic outline:

- Identify the specific areas of information people will use when performing searches.
- Identify any related subtopics which may be grouped as children under a parent topic .
- Consider the initial level of detail to be covered by your topic design.

Keep the scope of your topic outline relatively small to begin with. A smaller, simpler topic outline is easier to define, and you can always add additional information later. As you develop your topic outline, determine how many levels your topic design will include.

Top-down topic outline example

Developing a top-down topic outline involves three steps.

- Establishing an information hierarchy
- Establishing individual search categories
- Establishing the topics to be built

As you work through these steps, meet with the people who use Verity search agents at your site to develop a topic outline that best meets their search needs, as described below.

Establishing an information hierarchy

Talk to the people at your site to learn what types of documents contain the information they need.

For example, assume you are developing a topic design for people in the medical industry to find information relating to current drug testing. Based on discussions with the people who will use Verity search agents at your site, you learn that the following types of documents are prime sources of current drug testing information:

- Research reports
- Product literature

These documents form the information sources to be searched by Verity search agents.

Establishing individual search categories

Review the documents that will form the information sources at your site. Look for ways to categorize documents.

In our example, a review of the medical research reports and product literature shows information contained in these documents is divided into several categories. You determine that the following categories will be used to define the top-level topics in your topic design:

- Lab reports
- Clinical trials, data, or research
- Product literature

Establishing the topics to be built

Discuss categories you define with the people who create Verity search agents at your site to determine the most important concepts that selected documents should contain, and to determine the top-level topics you need to develop for each category.


For example, you determine that the category “clinical trials” includes the following top-level topics:

product-testing

research-methodology


Within these top-level topics, for example, the following subtopics are identified by subject-area experts:

▶ product-testing —▶ drug-names




Once these topics are classified, you consult the people who use Verity search agents at your site to determine subtopics. Following is an example of subtopics classified as children for the topic procedural-aspects:

▶ product-testing —▶ drug-names



As the topic outline is defined, you consult the people who use Verity search agents at your site to ensure the topics select meaningful documents. In the next example, a topic called drug-names enables the users at your site to search clinical trials data for drugs, based on their names.



Bottom-up topic outline example

Developing a bottom-up topic outline involves three steps.

- Identifying the subtopics that will form the lowest levels of the topic design
- Categorizing related subtopics into higher-level topics
- Establishing the top-level topic classifications

As you work through these steps, meet with the people who create Verity search agents at your site to develop a topic outline that best meets your search needs, as described below.

Identifying low-level topics

Find a document you can use as a model whose information is representative of other documents you want to find.

For example, assume you are developing a topic design to find information on the computer industry. As a start, you build a topic that searches for documents related to Apple Computer and related products.

You use the following sample as a model document whose information is representative of other documents you want to find:

A system developed specifically for networked Apple Computer, Inc. Macintosh computers has been announced by Human Designs, Inc.

Dubbed Chorus, the floor-standing unit reportedly can contain up to 16 floating-point processors and connects to networked Macintoshes to create a multiuser desktop environment.

The product offers performance of eight million to 32 million floating-point operations per second and was designed to accommodate software development, according to the vendor. Options include an Ethernet I/O upgrade and a software simulator.


A Chorus 1 single floating-point processor entry-level system costs \$9,700. A Chorus 4 configuration with four floating point processors is available at \$25,000, which includes a dedicated I/O processor with an Apple Appletalk port and system software. Both systems are upgradable.

Human Designs, 322 W. 71st St., New York, N.Y. 10023. 212-580-0257.


This document makes you decide you want to locate other documents which refer to "Appletalk" and "Macintosh," so you define two parent topic names, apple-software and apple-hardware.

You decide you want to add additional evidence topics to select documents containing related information, such as "Macintosh,"

“Mac Classic,” “Quadra,” and “Power Mac.” In addition, you decide you want to include the evidence topics “AppleTalk,” “MacPaint,” “MacWrite,” and “MacDraw,” as related software products. You assign these evidence topics to your apple-hardware and apple-software topics, as follows:




Finally, you want to combine these topics into the topic apple-products, as follows:



Categorizing related subtopics

Discuss subtopics with the people who use Verity search agents at your site to determine if other subtopics exist that can be logically grouped in a category.


In our example, some of the people who use Verity search agents are interested in finding information on personnel at Apple Computer, and others are interested in finding any documents that refer to Apple Computer. In the example below, a logical group of topics addresses several aspects of Apple Computer:



Establishing top-level topics

Determine whether other top-level topics are necessary to find related information.

In the following example, a new topic, dec, is developed for another computer company, Digital Equipment Corporation. This topic was assigned a top-level topic and contains subtopics similar to those defined for the apple topic, as shown below.



Verity® and TOPIC® are registered trademarks of Verity, Inc.

System Procedures

This appendix describes the Sybase-supplied system procedures used for updating and getting reports from system tables. Table A-1 lists the system procedures included with the Enhanced Full-Text Search engine.

Table A-1: System procedures

Procedure	Description
sp_check_text_index	Reports or fixes consistency problems in Enhanced Full-Text Search index and source tables.
sp_clean_text_events	Removes processed entries from the text_events table.
sp_clean_text_indexes	Removes text indexes that are not associated with a table.
sp_create_text_index	Creates an external text index.
sp_drop_text_index	Drops text indexes.
sp_help_text_index	Displays text indexes.
sp_optimize_text_index	Runs the Verity optimization routines.
sp_redo_text_events	Changes the status of entries in the text_events table and forces re-indexing of the modified table.
sp_refresh_text_index	Adds an entry to the text_events table reflecting updates to the corresponding source table.
sp_show_text_online	Displays information about databases or indexes that are currently online.
sp_text_cluster	Displays or modifies clustering options.
sp_text_configure	Displays or modifies Enhanced Full-Text Search engine configuration parameters.
sp_text_dump_database	Makes a backup copy of the text indexes in a database and optionally dumps the text_db and current databases.
sp_text_kill	Terminates all connections to a specific text index.
sp_text_load_index	Restores text indexes from a backup.
sp_text_notify	Notifies the Enhanced Full-Text Search engine that the text_events table has been modified.
sp_text_online	Makes a database available to Adaptive Server.

sp_check_text_index

Description	Reports or fixes consistency problems in the Enhanced Full-Text Search index and source tables.
Syntax	<code>sp_check_text_index server, "index_name", "id_column", "fixit"</code>
Parameters	<p><i>server</i> is the name of the text server.</p> <p><i>index_name</i> is the name of the text server.</p> <p><i>id_column</i> is the source identity column name.</p> <p><i>fixit</i> if FALSE, just reports problems. If TRUE, does not report but repairs problems.</p>
Examples	<pre>sp_check_text_index "textsvr", "text.i_text", "id", "false"</pre> <p>Lists problems on the server named textsvr with the column name text.i_text.</p>
Usage	<ul style="list-style-type: none">• Before using <code>sp_check_text_index</code>, you must issue <code>sp_dboption "select into", true</code>• This procedure:<ul style="list-style-type: none">• Generates an <code>sp_refresh_text_index</code> insert for entries in the source table that do not have a matching entry in the index.• Generates an <code>sp_refresh_text_index</code> delete for entries in the index table that have no source table entry.• Generates an <code>sp_refresh_text_index</code> delete for each extra entry where duplicate index entries exist.• To determine the index duplicates, select all of the ID values from the index table into a temporary table. If the collection has more than 64K ID values, you must change the <code>batch_blocksize</code> configuration parameter from its default of 0 to 65536 to enable blocked reading of the returned Verity information. If you do not do this, Enhanced Full-Text Search attempts to read all ID values in one read and fail with a Verity error of “-27.”
Messages	None.
Permissions	Any user can execute <code>sp_check_text_index</code> .

sp_clean_text_events

Description	Removes processed entries from the text_events table.
Syntax	sp_clean_text_events [<i>up_to_date</i>]
Parameters	<i>up_to_date</i> the date and time through which all processed entries will be deleted.
Examples	<pre>sp_clean_text_events "01/15/98:17:00"</pre> Removes data entered on or before January 15, 1998 at 5:00 p.m.
Usage	<ul style="list-style-type: none"> • If you do not specify the <i>up_to_date</i> parameter, all entries having a date less than or equal to <i>up_to_date</i> and whose status are set to processed is deleted. • If you omit <i>up_to_date</i>, all entries whose status is set to processed is deleted. • Remove entries from the text_events table only after you have backed up the collection associated with the text index. • sp_text_dump_database automatically runs.
Messages	None.
Permissions	Any user can execute sp_clean_text_events.
See also	sp_text_dump_database

sp_clean_text_indexes

Description	Removes indexes from the vesaux table that are not associated with a table.
Syntax	sp_clean_text_indexes
Parameters	None.
Examples	<pre>sp_clean_text_indexes</pre>
Usage	<ul style="list-style-type: none"> • This procedure reads entries from the vesaux and vesauxcol tables, verifying that both the source table and the corresponding index table exist. If either is missing, the index is dropped.
Messages	<ul style="list-style-type: none"> • Fetch resulted in an error. • Unable to drop object definition for <i>index_name</i>!

Permissions Any user can execute `sp_clean_text_indexes`.

sp_create_text_index

Description Creates a text index.

Syntax `sp_create_text_index server_name, index_table_name, table_name, "batch", column_name [, column_name ...]`

Parameters *server_name* is the name of the Enhanced Full-Text Search engine.

index_table_name is the name of the index table. *index_table_name* has the form `[dbname.[owner.]]table`, where:

- `dbname` is the name of the database containing the index table.
- `owner` is the name of the owner of the index table.
- `table` is the name of the index table.

table_name is the name of the source table containing the text being indexed. *table_name* has the form `[dbname.[owner.]]table`.

`batch` the “batch” operator (must be in quotes) tells the Enhanced Full-Text Search to reallocate every session after each batch sent to the VDK.

column_name is the name of the column indexed by the text index.

Examples `sp_create_text_index "blue", "i_blurbs", "blurbs", " ", "copy"`
Creates a text index and an index table named `i_blurbs` on the `copy` column of the `blurbs` table.

Usage

- Up to 16 columns can be indexed in a single text index.
- Columns of the following datatypes can be indexed: `char`, `varchar`, `nchar`, `nvarchar`, `text`, `image`, `date`, `time`, `datetime`, `smalldatetime`, `int`, `smallint`, and `tinyint`.
- The content of *option_string* is not case sensitive.

- *option_string* uses a null string (" ") to specify “No Options.”
- Assign the value “empty” to *option_string* to create a text index that you will immediately drop. This creates the Verity collection directory and the style files, but does not populate the collections. For example, when you configure an individual table for clustering, you create the text index and immediately drop it. After you edit the *style.prm* file, you re-create the text index. See “Editing individual style.prm files” on page 29.
- `sp_create_text_index` writes entries to the `vesaux` table and tells the Enhanced Full-Text Search engine to create the text index.
- Execution of `sp_create_text_index` is synchronous. The Adaptive Server process executing this system procedure remains blocked until the index is created. The time required to index large amounts of data may take as long as several hours to complete.
- When you create a text index on two or more columns, each column in the text index is placed into its own document zone. The name of the zone is the name of the column. The zones can be used to limit your search to a particular column. For more information, see “in” on page 53.

- *Do not rename an index after creating.*

Messages

- Cannot run `sp_create_text_index` from within a transaction.
- ‘*column_name*’ cannot be NULL.
- Column ‘*column_name*’ does not exist in table ‘*table_name*.’
- Index table mapping failed – text index creation aborted.
- Invalid text index name – ‘*index_name*’ already exists.
- ‘*parameter*’ is not in the current database.
- Server name ‘*server_name*’ does not exist in `sys.servers`.
- ‘*table_name*’ does not exist.
- ‘*table_name*’ is not a valid object name.
- Table ‘*table_name*’ does not have an identity column – text index creation aborted.
- Text index creation failed.
- User ‘*user_name*’ is not a valid user in the database.

Permissions

Any user can execute `sp_create_text_index`.

sp_drop_text_index

Description	Drops the index table and text indexes.
Syntax	<pre>sp_drop_text_index "table_name.index_table_name" [,"table_name.index_table_name"...]</pre>
Parameters	<p><i>table_name</i></p> <p>is the name of the table associated with the text indexes you are dropping. <i>table_name</i> has the form [dbname.[owner.]]table, where:</p> <ul style="list-style-type: none">• dbname is the name of the database containing the table.• owner is the name of the owner of the table.• table is the name of the table. <p><i>index_table_name</i></p> <p>is the name of the index table and text index you are dropping. <i>index_table_name</i> has the form [dbname.[owner.]]index.</p>
Examples	<pre>sp_drop_text_index "blurbs.i_blurbs"</pre> <p>Drops the index table and text index associated with the blurbs table.</p>
Usage	<ul style="list-style-type: none">• First, sp_drop_text_index issues a remote procedure call (RPC) to the Enhanced Full-Text Search engine to delete the Verity collection. Then, it removes the associated entries from the vesaux and vesauxcol tables, drops the index table, and removes the index table object definition.• Up to 255 indexes can be specified in a single sp_drop_text_index request.• If <i>database</i> and <i>owner</i> are not specified, the current owner and database are used.
Messages	<ul style="list-style-type: none">• Cannot run sp_drop_text_index from within a transaction.• Index '<i>index_name</i>' is not a text index.• '<i>parameter_name</i>' is not a valid name.• Server name '<i>server_name</i>' does not exist in syssservers.• Unable to drop index table '<i>table_name</i>'. This table must be dropped manually.• User '<i>user_name</i>' is not a valid user in the '<i>database_name</i>' database.• vs_drop_index failed with code '<i>code_name</i>'.
Permissions	Any user can execute sp_drop_text_index.

sp_help_text_index

Description	Displays a list of text indexes for the current database.
Syntax	<code>sp_help_text_index [index_table_name]</code>
Parameters	<i>index_table_name</i> is the name of the text index you want to display.
Examples	<p>Example 1</p> <pre>sp_help_text_index</pre> <p>Displays all indexes.</p> <p>Example 2</p> <pre>sp_help_text_index "i_blurbs"</pre> <p>Displays information about the text index i_blurbs.</p>
Usage	<ul style="list-style-type: none"> • <code>sp_help_text_index</code> is available only with Enhanced Full-Text Search Specialty Data Store. • If you the <i>index_table_name</i> parameter, information about that text index is displayed. This information includes the name of the text index, the name of the Verity collection for the index, the name of the source table, the name of the IDENTITY column, and the name of the Enhanced Full-Text Search engine that created the index. • If <i>index_table_name</i> is omitted, a list of all text indexes in the current database is displayed
Messages	<ul style="list-style-type: none"> • No text indexes found in database '<i>database_name</i>.' • Text index '<i>index_name</i>' does not exist in database '<i>database_name</i>.' • Object must be in the current database
Permissions	Any user can execute <code>sp_help_text_index</code> .

sp_optimize_text_index

Description	Performs optimization on a text index.
Syntax	<code>sp_optimize_text_index index_table_name</code>

Parameters	<p><i>index_table_name</i> is the name of the text index you want to optimize. <i>index_table_name</i> has the form [dbname.[owner.]]table, where:</p> <ul style="list-style-type: none">• dbname is the name of the database containing the index table. If present, the owner or a placeholder is required.• owner is the name of the owner of the index table.• table is the name of the index table.
Examples	<pre>sp_optimize_text_index "i_blurbs"</pre> <p>Optimizes the text index i_blurbs to improve query performance.</p>
Usage	<ul style="list-style-type: none">• sp_optimize_text_index is available only with Enhanced Full-Text Search Specialty Data Store.• This system procedure causes the Enhanced Full-Text Search engine to run the specified text index through the Verity optimization routines.• sp_optimize_text_index is useful for optimizing a text index that has been updated with Verity optimization disabled (trace flag 11 turned on).• To enable MaxClean optimization, turn on trace flag 30. This trace flag should only be used during maintenance since it could take extra time and interfere with normal usage. MaxClean is a Verity optimization feature that removes out-of-date collection files.
Messages	<ul style="list-style-type: none">• ‘<i>index_table_name</i>’ is not in the current database.• ‘<i>index_table_name</i>’ does not exist.• Index ‘<i>index_table_name</i>’ is not a text index.• This procedure is not supported against remote server ‘<i>server_name</i>.’
Permissions	Any user can execute sp_optimize_text_index.
See also	“Updating existing indexes” on page 79

sp_redo_text_events

Description	Changes the status of entries in the text_events table and forces the reindexing of the modified columns.
Syntax	sp_redo_text_events [<i>from_date</i> [, <i>to_date</i>]]

Parameters	<p><i>from_date</i> is the starting date and time in a date range of entries to be modified.</p> <p><i>to_date</i> is the ending date and time in the specified date range of the entries to be modified.</p>
Examples	<pre>sp_redo_text_events "01/05/98:17:00", "02/12/98:08:30"</pre> <p>Re-ndexes columns that were modified between January 5, 1998 at 5:00 p.m. and February 12, 1998 at 8:30 a.m.</p>
Usage	<ul style="list-style-type: none"> Resets the status to “unprocessed” for all entries in the <code>text_events</code> table that currently have a status of “processed.” The Enhanced Full-Text Search engine is notified that a reindex operation is required. Useful for synchronizing a text index after a recovery of the Verity collection from a backup. This procedure is run automatically during <code>sp_text_load_index</code>. If you omit <i>to_date</i>, all entries between <i>from_date</i> and the current date with a status of “processed” are reset to “unprocessed.” If you omit both <i>from_date</i> and <i>to_date</i>, all entries in the <code>text_events</code> table with a status of “processed” are reset to “un-processed.”
Messages	<ul style="list-style-type: none"> <i>to_date</i> cannot be specified without <i>from_date</i>. You have not specified the full range.
Permissions	Any user can execute <code>sp_redo_text_events</code> .

sp_refresh_text_index

Description	Records modifications in the <code>text_events</code> table when you change the text index’s source table data.
Syntax	<code>sp_refresh_text_index table_name, column_name, rowid, mod_type</code>
Parameters	<p><i>table_name</i> is the name of the source table being updated. <i>table_name</i> has the form <code>[dbname.[owner.]]table</code>, where:</p> <ul style="list-style-type: none"> <code>dbname</code> is the name of the database containing the table. <code>owner</code> is the name of the owner of the table. <code>table</code> is the name of the table.

column_name

is the name of the column being updated.

rowid

is the IDENTITY column value of the changed row.

mod_type

specifies the type of the change. Must be insert, update, or delete.

Examples

```
sp_refresh_text_index "blurbs", "copy", 2.000000,  
"update"
```

Records in the `text_events` table that you have updated the copy column of the blurbs table. The row you have updated has an id of 2.000000.

Usage

- The user maintains the consistency of the text index. You must run `sp_refresh_text_index` anytime you update source data that has been indexed so that the `text_events` table reflects the change. This keeps the collections in sync with your source data. The collections are not updated until you run `sp_text_notify`.
- You can create triggers that issue `sp_refresh_text_index` for non-text and non-image columns. See “Propagating changes to the text index” on page 23.

Messages

- Column ‘*column_name*’ does not exist in table ‘*table_name*.’
- Invalid *mod_type* specified (‘*mod_type*’). Correct values: INSERT, UPDATE, DELETE.
- Owner ‘*owner_name*’ does not exist.
- Table ‘*table_name*’ does not exist.
- ‘*table_name*’ is not a valid name.
- Text event table not found.

Permissions

Any user can execute `sp_refresh_text_index`.

See also

`sp_text_notify`

sp_show_text_online

Description

Displays information about databases or text indexes that are currently online.

Syntax

```
sp_show_text_online server_name [{INDEXES | DATABASES}]
```

Parameters	<p><i>server_name</i> is the name of the Enhanced Full-Text Search engine to which the request is sent.</p> <p>INDEXES DATABASES specifies whether the request should contain data about online indexes or online databases. The default is INDEXES.</p>
Examples	<p>Example 1</p> <pre>exec sp_show_text_online KRAZYKAT</pre> <p>Displays all indexes that are currently online in the KRAZYKAT Enhanced Full-Text Search engine.</p> <p>Example 2</p> <pre>exec sp_show_text_online KRAZYKAT, DATABASES</pre> <p>Displays all databases that are currently online in the KRAZYKAT Enhanced Full-Text Search engine.</p>
Usage	<ul style="list-style-type: none"> • <code>sp_show_text_online</code> issues a remote procedure call to the Enhanced Full-Text Search engine to retrieve information about the indexes or the databases that are currently online. • If the results of this procedure do not list a database, use <code>sp_text_online</code> to bring the desired database online.
Messages	<ul style="list-style-type: none"> • <code>sp_show_text_online</code> failed for server <i>server_name</i>. • The parameter value '<i>value</i>' is invalid. • The RPC sent to the server returned a failure return code. • The second parameter must be INDEXES or DATABASE.
Permissions	Any user can execute <code>sp_show_text_online</code> .
See also	<code>sp_text_online</code>

sp_text_cluster

Description	Displays or changes clustering parameters for the active thread.
Syntax	<code>sp_text_cluster server_name, cluster_parameter [, cluster_value]</code>
Parameters	<p><i>server_name</i> is the name of the Enhanced Full-Text Search engine.</p>

cluster_parameter

is the name of the clustering parameter. Values are shown in Table A-2.

cluster_value

is the value you assign to the clustering parameter for the active thread. Values are shown in Table A-2.

Table A-2: Clustering configuration parameters

Values for <i>cluster_parameter</i>	Values for <i>cluster_value</i>
cluster_style	<p>Specifies the type of clustering to use. Valid values are:</p> <ul style="list-style-type: none"> • fixed – generates a fixed number of clusters. The number is set by the cluster_max parameter. • coarse – automatically determines the number of clusters to generate, based on fewer, coarse grained clusters. • medium – automatically determines the number of clusters to generate, based on medium-sized clusters. • fine – automatically determines the number of clusters to generate, based on smaller, finer-grained clusters.
cluster_max	<p>Specifies the maximum number of clusters to generate when cluster_style is set to fixed. A value of 0 means that the search engine determines the number of clusters to generate.</p>
cluster_effort	<p>Specifies the amount of effort (time) that the search engine should expend on finding a good clustering. Valid values are:</p> <ul style="list-style-type: none"> • effort_default – the search engine spends the default amount of time. You can also use the Verity term “default” if you enclose it in double quotes (“ ”). • high – the search engine spends the longest time. • medium – the search engine spends less time. • low – the search engine spends the least amount of time.
cluster_order	<p>Specifies the order in which to return the rows within the clusters. Valid values are:</p> <ul style="list-style-type: none"> • "0" – indicates rows are returned in order of similarity to the cluster center. This means the first row returned for a cluster is the one that is most prototypical of the rows in the cluster. • "1" – indicates that rows are returned in the same relative order in which they were submitted for clustering. For example, if cluster 1 contains the first, third and seventh rows found for the query, they will be returned in that relative order within the cluster.

Examples

Example 1

```
sp_text_cluster KRAZYKAT, cluster_order, "1"
```

Changes the *cluster_order* parameter to 1 for the active thread.

Example 2

```
sp_text_cluster KRAZYKAT, cluster_style
```

Displays the current value of the *cluster_style* parameter.

Usage	<ul style="list-style-type: none"> • The Verity clustering algorithm attempts to group similar rows together, based on the values of the clustering parameters. • If you specify the <i>cluster_parameter</i> parameter, but omit the <i>cluster_value</i> parameter, <code>sp_text_cluster</code> displays the value of the clustering parameter that is specified. • <code>sp_text_cluster</code> does not modify the value of the clustering configuration parameter. The <i>cluster_value</i> is valid only for the thread that is currently executing. To modify the default values, use <code>sp_text_configure</code>. • For information on how to request a clustered result set, see “Using pseudo columns to request clustered result sets” on page 48.
Messages	<ul style="list-style-type: none"> • This procedure is not supported against remote server ‘<i>server_name</i>.’ • The parameter value ‘<i>value</i>’ is invalid. • <code>sp_text_cluster</code> failed (status = <i>status</i>).
Permissions	Any user can execute <code>sp_text_cluster</code> .
See also	<code>sp_text_configure</code>

sp_text_configure

Description	Displays or changes Enhanced Full-Text Search engine configuration parameters.
Syntax	<code>sp_text_configure server_name [, config_name [, config_value]]</code>
Parameters	<p><i>server_name</i> is the name of the Enhanced Full-Text Search engine.</p> <p><i>config_name</i> is the name of the configuration parameter to be displayed or modified.</p> <p><i>config_value</i> is the value you assign to the configuration parameter.</p>
Examples	<p>Example 1</p> <pre>sp_text_configure KRAZYCAT, backdir, "/data/backup"</pre>

Changes the backup destination directory to */data/backup*.

Example 2

```
sp_text_configure KRAZYCAT, backdir
```

Displays the backup destination directory.

Usage

- When you execute `sp_text_configure` to modify a dynamic parameter:
 - The configuration and run values are updated.
 - The configuration file is updated.
 - The change takes effect immediately.
- When you execute `sp_text_configure` to modify a static parameter:
 - The configuration value is updated.
 - The configuration file is updated.
 - The change takes effect only when you restart the Enhanced Full-Text Search engine.
- When issued with no parameters, `sp_text_configure` displays a report of all Enhanced Full-Text Search engine configuration parameters and their current values.
- If you specify the *config_name* parameter, but omit the *config_value* parameter, `sp_text_configure` displays the report for the configuration parameter specified.
- For information on the individual configuration parameters, see “Modifying the configuration parameters” on page 67.

Messages

- Configuration value cannot be specified without a configuration option.
- This procedure is not supported against remote server ‘*server_name*.’
- `sp_text_configure` failed – possible invalid configuration option ‘*config_name*.’

Permissions

Any user can execute `sp_text_configure`.

sp_text_dump_database

Description

Makes a backup copy of a text index.

Syntax	<code>sp_text_dump_database backupdbs [, current_to] [, current_with] [, current_stripe01 [, ... [, current_stripe31]]] [, textdb_to] [, textdb_with] [, textdb_stripe01 [, ... [, textdb_stripe31]]]</code>
Parameters	<i>backupdbs</i> specifies whether the current database and the text_db database are backed up before the text index is backed up. Valid values are shown in Table A-3.

Table A-3: Values for backupdbs

Value	Description
CURRENT_DB_AND_INDEXES	Indicates that the current database is backed up before the text indexes are backed up.
CURRENT_DB_AND_CURRENT_INDEXES	Indicates that the current database is backed up before the text indexes are backed up, and only the indexes associated with the current database are dumped.
TEXT_DB_AND_INDEXES	Indicates that the text_db database is backed up before the text indexes are backed up.
INDEXES_AND_DATABASES	Indicates that the current and text_db databases are backed up before the text indexes are backed up.
ONLY_INDEXES	Indicates that only the text indexes are backed up.

current_to

is the to clause of the dump database command for dumping the current database. Use this only if you specify CURRENT_DB_AND_INDEXES or INDEXES_AND_DATABASES for the *backupdbs* parameter.

current_with

is the with clause of the dump database command for dumping the current database. Use this only if you specify CURRENT_DB_AND_INDEXES or INDEXES_AND_DATABASES for the *backupdbs* parameter.

current_stripe

is the stripe clause of the dump database command for dumping the current database. Use this only if you specify CURRENT_DB_AND_INDEXES or INDEXES_AND_DATABASES for the *backupdbs* parameter.

textdb_to

is the to clause of the dump database command for dumping the text_db database. Use this only if you specify INDEXES_AND_DATABASES for the *backupdbs* parameter. Use this only if you specify TEXT_DB_AND_INDEXES or INDEXES_AND_DATABASES for the *backupdbs* parameter.

textdb_with

is the with clause of the dump database command for dumping the text_db database. Use this only if you specify TEXT_DB_AND_INDEXES or INDEXES_AND_DATABASES for the *backupdbs* parameter.

textdb_stripe

is the stripe clause of the dump database command for dumping the text_db database. Use this only if you specify TEXT_DB_AND_INDEXES or INDEXES_AND_DATABASES for the *backupdbs* parameter.

Examples

Example 1

```
sp_text_dump_database ONLY_INDEXES
```

Only text indexes are backed up.

Example 2

```
sp_text_dump_database CURRENT_DB_AND_INDEXES, "to '/data/db1backup' "
```

The current database is dumped to */data/db1backup* before the text indexes are backed up.

Example 3

```
sp_text_dump_database @backupdbs = "TEXT_DB_AND_INDEXES", @textdb_to = "to  
'/data/textdbbackup' "
```

The *text_db* database is dumped to */data/textdbbackup* before the text indexes are backed up.

Example 4

```
sp_text_dump_database @backupdbs = "INDEXES_AND_DATABASES", @current_to =  
"to '/data/db1backup' ",  
@textdb_to = "to '/data/textdbbackup' "
```

The current database is dumped to */data/db1backup* and the *text_db* database is dumped to */data/textdbbackup* before the text indexes are backed up.

Usage

- The Enhanced Full-Text Search engine concatenates the values of *current_to*, *current_with*, and *current_stripe01* to *current_stripe31* to dump database *currentdbname* and then executes the dump database command. The output from the execution of the dump database command is sent to the Enhanced Full-Text Search error log.
- The Enhanced Full-Text Search engine concatenates the values of *textdb_to*, *textdb_with*, and *textdb_stripe01* to *textdb_stripe31* to the string “dump database *currentdbname*” and then executes the dump database command. The output from the execution of the dump database command is sent to the Enhanced Full-Text Search error log.

- All entries in the text_events table that have a “processed” status in the current database are deleted when all indexes have been backed up.
- The backup files for the Verity collections are stored in the directory specified in the backDir configuration parameter.
- See references to the configuration parameter backCmd for customizing backups.

Messages

- The parameter value ‘value’ is invalid.
- Server name ‘server’ does not exist in sys.servers.
- Attempt to dump database ‘database_name’ failed – use the dump database command.
- Attempt to backup text indexes on server ‘server_name’ failed.
- Attempt to clean text_events in database ‘database_name’ failed (date = ‘date’).
- Parameter ‘parameter_name’ is required when dumping database ‘database_name’.
- Dumping database ‘database_name’ – check Full Text Search SDS error log for status

Permissions

Any user can execute sp_text_dump_database.

See also

dump_database in the *Reference Manual*.

sp_text_kill

Description

Terminates all connections to a specific text index.

Syntax

sp_text_kill *index_table_name*

Parameters	<p><i>index_table_name</i> is the name of the text index from which all connections are terminated. <i>index_table_name</i> has the form [dbname.[owner.]]table, where:</p> <ul style="list-style-type: none">• dbname is the name of the database containing the index table. If present, the owner or a placeholder is required.• owner is the name of the owner of the index table.• table is the name of the index table.
Examples	<pre>sp_text_kill "i_blurbs"</pre> <p>Terminates all existing connections to the text index i_blurbs.</p>
Usage	<ul style="list-style-type: none">• This system procedure causes the Enhanced Full-Text Search engine to terminate all connections to the specified index, except for the connection that initiated the request.• Attempts to drop a text index that is currently in use will fail. <i>sp_text_kill</i> can be used to terminate all existing connections so that the index can be successfully dropped.
Messages	<ul style="list-style-type: none">• Index '<i>index_table_name</i>' is not a text index.• This procedure is not supported against remote server '<i>server_name</i>.'• '<i>index_table_name</i>' does not exist.• Only the System Administrator (SA) may execute this procedure.
Permissions	Only user "sa" can execute <i>sp_text_kill</i> .
See also	<i>sp_drop_text_index</i>

sp_text_load_index

Description	Restores a text index backup.
Syntax	<i>sp_text_load_index</i>
Parameters	None.
Examples	<pre>sp_text_load_index</pre> <p>Restores all text indexes in the current database.</p>

Usage	<ul style="list-style-type: none"> Run <code>sp_text_load_index</code> after the <code>text_db</code> database and the current database have been fully recovered. <code>sp_text_load_index</code> restores the Verity collections from the most recent backup. The Enhanced Full-Text Search engine then runs <code>sp_redo_text_events</code> and <code>sp_text_notify</code> to reapply all entries in the <code>text_events</code> table since the date and time the index was backed up.
Messages	<ul style="list-style-type: none"> Server name '<i>server_name</i>' does not exist in sys.servers. Unable to restore text indexes for server '<i>server_name</i>'. This procedure is not supported against remote server '<i>server_name</i>'. Update to <code>text_events</code> table in database <i>database_name</i> failed for server '<i>server_name</i>' – <code>text_events</code> not rolled forward.
Permissions	Any user can execute <code>sp_text_load_index</code> .
See also	<code>sp_redo_text_events</code> ; <code>sp_text_notify</code>

sp_text_notify

Description	Notifies the Enhanced Full-Text Search engine that the <code>text_events</code> table has been modified.
Syntax	<code>sp_text_notify</code> [{true false}] [, <i>server_name</i>]
Parameters	<p><code>true</code> causes the procedure to run synchronously.</p> <p><code>false</code> causes the procedure to run asynchronously.</p> <p><i>server_name</i> – is the name of the Enhanced Full-Text Search engine you are notifying.</p>
Examples	<code>sp_text_notify true</code>
Usage	<ul style="list-style-type: none"> You must run <code>sp_text_notify</code> after you issue <code>sp_refresh_text_index</code> to inform the Enhanced Full-Text Search engine that the source tables have been modified. If you do not specify <code>true</code> or <code>false</code>, <code>sp_text_notify</code> runs synchronously. If no server name is specified, all Enhanced Full-Text Search engines are notified.

Messages	<ul style="list-style-type: none">• Can't run sp_text_notify from within a transaction.• Notification failed, server = '<i>server_name</i>.'• Server name '<i>server_name</i>' does not exist in syssservers.• The parameter value '<i>value</i>' is invalid.
Permissions	Any user can execute sp_text_notify.
See also	sp_refresh_text_index

sp_text_online

Description	Makes a database available for full-text searches to Adaptive Server.
Syntax	sp_text_online [<i>server_name</i>], [<i>database_name</i>]
Parameters	<p><i>server_name</i> is the name of the Enhanced Full-Text Search engine.</p> <p><i>database_name</i> is the name of the database that you are bringing online.</p>
Examples	<pre>sp_text_online @database_name = pubs2</pre> <p>Makes the pubs2 database available for full-text searches using the Enhanced Full-Text Search engine.</p>
Usage	<ul style="list-style-type: none">• If a database is not specified, all databases are brought online for full-text searches.• If a server name is not specified, all Enhanced Full-Text Search engines listed in the vesaux table are notified.• With the Enhanced Full-Text Search engine, databases are brought online automatically if the auto_online configuration parameter is set to 1.
Messages	<ul style="list-style-type: none">• All Databases using text indexes are now online• Databases containing text indexes on server '<i>database_names</i>' are now online.• Server name <i>server_name</i> is now online.• Server name '<i>server_name</i>' does not exist in syssservers.• The parameter value '<i>value</i>' is invalid.• The specified database does not exist.

- vs_online failed for server '*server_name*.'

Permissions

Any user can execute sp_text_online.

Sample Files

This appendix contains the following:

- The text of the default configuration file (*textsvr.cfg*)
- An overview of the *sample_text_main.sql* sample script
- A list of all the sample files provided by the Enhanced Full-Text Search engine
- An overview of the *getsend* program

Default *textsvr.cfg* configuration file

```

;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;
;  @(#)  File: textsvr.cfg  1.17  07/26/99
;
;  Full Text Search Specialty Data Store
;          Sample Configuration File
;
;  The installation procedure places this file in the
;  "SYBASE" directory.
;
;  Lines with a semi-colon in column 1 are comment lines.
;
;  Modification History:
;  -----
;  11-21-97      Create file for Full Text Search SDS
;  03-02-98      Add trace flags and config values for
;                Enhanced Full Text Search SDS
;  05-26-99      remove references to sds/text
;  07-09-99      added batch block size
;  08-24-99      remove version string and correct copyright
;
;
;
;
;                copyright (c) 1997, 1999

```

```

;           Sybase, Inc. Emeryville, CA
;           All rights reserved.
;
; ::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::
;
;                                     DIRECTIONS
;
; Modifying the textsvr.cfg file:
; -----
; An installation can run the Text Search SDS product
; as supplied, with no modifications to configuration
; parameters. Default values from the executable program
; are in effect.
;
; The "textsvr.cfg" file is supplied with all configuration
; parameters commented out.
;
; The hierarchy for setting configuration values is:
;
;   default value internal to the executable program (lowest)
;   configuration file value (overrides default value)
;   command line argument (overrides default value and *.cfg file)
;
; Command line arguments are available to override
; settings for these options:
;
;   -i<file specification for interfaces file>
;   -l<file specification for log file>
;   -t (no arg) directs text server to write start-up
;       information to stderr (default is DO NOT write start-up information)
;
; To set configuration file parameters, follow these steps:
;
; (1) If changing the server name to other than "textsvr":
;     (1A) Copy "textsvr.cfg" to "your_server_name.cfg"
;           Example: text_server.cfg
;     (1B) Modify the [textsvr] line to [your_server_name]
;           Example: [text_server]
;           The maximum length of "your_server_name" is 30 characters.
;
; (2) Set any configuration values in the CONFIG VALUES SECTION below.
;     Remove the semi-colon from column 1.
;
; ::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::
;
;
;

```



```

;           DEFINITIONS OF TRACE FLAG AND SORT ORDER VALUES
;
; "traceflags" parameter, for text server
; Available "traceflags" values: 1,2,3,4,5,6,7,8,9,10,11,12,13
;
; 1 trace connect/disconnect/attention events
; 2 trace language events
; 3 trace rpc events
; 4 trace cursor events
; 5 log error messages returned to the client
; 6 trace information about indexes
; 7 trace senddone packets
; 8 write text server/Verity api interface records to the log
; 9 trace sql parser
; 10 trace Verity processing
; 11 disable Verity collection optimization
; 12 disable returning of sp_statistics information
; 13 trace backup operations (Enhanced Full Text Search only)
;
; "srv_traceflags" parameter, for Open Server component of text server
; Available "srv_traceflags" values: 1,2,3,4,5,6,7,8
; 1 trace TDS headers
; 2 trace TDS data
; 3 trace attention events
; 4 trace message queues
; 5 trace TDS tokens
; 6 trace open server events
; 7 trace deferred event queue
; 8 trace network requests
;
; "sort_order" parameter
; Available "sort_order" values: 0,1,2,3
; 0 order by score, descending (default)
; 1 order by score, ascending
; 2 order by timestamp, descending
; 3 order by timestamp, ascending
;
; ::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::::
;
;           CONFIG VALUES SECTION
;
; The "textsvr.cfg" file is supplied with the values commented out.
; To override value(s) in the executable program:
;   - Set required value(s) below
;   - Remove the semicolon from column 1
;

```

```
[textsvr]
;min_sessions = 10
;max_sessions = 100
;batch_size = 500
;sort_order = 0
;defaultDb = text_db
;errorLog = textsvr.log
;language = english
;charset = iso_1
;vdkLanguage =
;vdkCharset = 850
;traceflags = 0
;srv_traceflags = 0
;max_indexes = 126
;max_packet_size = 2048
;max_stack_size = 34816
;max_threads = 50
;collDir = <textsvr directory tree location on UNIX>/collections
;collDir = <textsvr directory tree location on Win-NT>\collections
;vdkHome = <textsvr directory tree location on UNIX>/verity
;vdkHome = <textsvr location on Win-NT>\verity
;interfaces = <$SYBASE location on UNIX>/interfaces
;interfaces = <%SYBASE% location on Win-NT>\ini\sql.ini
;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;
;
; The parameters in this section apply only to the Enhanced Full Text Search SDS.
; If defined to a Full Text Search engine they will be ignored.
;
;auto_online = 0
;backDir = <textsvr directory tree location on UNIX>/backup
;backDir = <textsvr directory tree location on Win-NT>\backup
;backCmd =
;restoreCmd =
;knowledge_base =
;nocase = 0
;cluster_max = 0
;cluster_order = 0
;cluster_style = Fixed
;cluster_effort = Default
;batch_blocksize = 0
;max_session_fd = 0
```

The `sample_text_main.sql` script

The Enhanced Full-Text Search engine installation copies the `sample_text_main.sql` script to the `$$SYBASE/$$SYBASE_FTS/sample/scripts` directory. This script illustrates the following operations:

- Setting up a text index.
- Modifying data and propagating changes to the collections. This includes inserts, updates, and deletes.
- Dropping a text index.

Execution of this script is not required for installation or configuration; Sybase supplies the script as a sample.

Before you run the `sample_text_main.sql` script:

- Your Adaptive Server and Enhanced Full-Text Search engine must be configured and running.
- Use a text editor to edit the `sample_text_main.sql` script. Change “YOUR_TEXT_SERVER” to the name of your Enhanced Full-Text Search engine in Step 4 in the `sample_text_main.sql` script.
- Verify that your model database contains a `text_events` table. If your model database is *not* configured this way, you must:
 - Modify the `sample_text_main.sql` script to exit after creating the database
 - Apply the `installevnt` script to the new database. See “Running the `installevnt` script” on page 17.
 - Execute the remainder of the sample script

Direct the script as input to your Adaptive Server. For example, to run the `sample_text_main.sql` script on an Adaptive Server named `MYSVR`:

```
isql -Ulogin -Ppassword -SMYSVR
-i
$$SYBASE/$$SYBASE_FTS/sample/scripts/sample_text_main.sql
l -omain.out
```

When you finish with this sample environment, log in to your Adaptive Server and drop the sample database. For example:

```
1> use master
2> go
1> drop database sample_colors_db
2> go
```

You can re-run the `sample_text_main.sql` necessary.

Sample files illustrating Enhanced Full-Text Search engine features

The Enhanced Full-Text Search engine supplies a set of sample files for illustrating text server operations. The files are located in the `$$YBASE/$SYBASE_FTS/sample/scripts` directory. Execution of the sample files is not required for installation, configuration, or operation of a Enhanced Full-Text Search engine.

Custom thesaurus

The following files illustrate how to set up and use a custom thesaurus:

- `sample_text_thesaurus.ctl` – is a sample control file.
- `sample_text_thesaurus.sql` – provides sample queries using the custom thesaurus created by the sample control file.

Topics

The following files illustrate how to set up and use topics:

- `sample_text_topics.otl` – is a sample outline file.
- `sample_text_topics.kbm` – is a sample knowledge base map.
- `sample_text_topics.sql` – provides sample queries using the defined topics.

Clustering, summarization, and query-by-example

The following files illustrate how to set up and use clustering, summarization and query-by example:

- `sample_text_setup.sql` – creates a sample environment.
- `sample_text_queries.sql` – issues queries against the environment and drops the environment.

***getsend* sample program**

The Enhanced Full-Text Search engine includes a program named *getsend* to load text or image data from a file into a column defined in Adaptive Server .

The required source and header files, a makefile, and directions for building and running the program are included in the directory *\$SYBASE/\$SYBASE_FTS/sample/source*.

See the *README.TXT* file and *getsend.c* file for information on how to use the program.

Unicode Support

The Unicode standard, a subset of the International Standards Organization's ISO 10646 standard, is an international character set. Unicode is identical to the Basic Multilingual Plane (BMP) of ISO 10646, which supports all the major scripts and languages in the world. Therefore, it is a superset of all existing character sets.

Unicode:

- Provides single-source development. This means you develop an application once and it can then be localized for multiple locales and in multiple languages. By using a single unified character set, you do not have to modify your applications to take into account differences between character sets, thus reducing development, testing, and support costs.
- Allows you to mix different languages in the same database. An all-Unicode system does not require that you design your database to keep track of the character set of your data.

The Enhanced Full-Text Search engine supports Unicode. To use this feature, obtain and install the Unicode Developer's Kit (also known as UDK). This contains everything you need to set up a Unicode-enabled client/server database system.

To configure the Enhanced Full-Text Search engine to store data in Unicode format, set the charset configuration value to `utf8`. See "Modifying the configuration parameters" on page 67.

Note If you issue wildcard searches against data in Unicode format, turn on trace flag 15. See "Setting trace flags" on page 73.

Index

Symbols

- , (comma)
 - in SQL statements xiv
- { } (curly braces)
 - in SQL statements xiv
- ... (ellipsis) in SQL statements xv
- () (parentheses)
 - in SQL statements xiv
- [] (square brackets)
 - in SQL statements xiv
- <> (angle brackets), enclosing Verity operators in 51

A

- accrue** operator 50, 52
- Adaptive Server
 - connecting to an Enhanced Full-Text Search engine 1
 - processing a full-text query 10
- and** operator 50, 53
 - with the **not** modifier 60
- angle brackets (<>), enclosing Verity operators in 51
- attention events, tracing 73
- Open Server 74
- auto_online** configuration parameter 22, 68, 70, 156

B

- backDir** configuration parameter 68, 70, 77, 153
- backup and recovery 75
- backup files
 - default location of 68, 70
- backup operations, tracing 73
- batch_blocksize** configuration parameter 67
- batch_size** configuration parameter 67, 69
 - and performance 82–83
- brackets.

See square brackets [] and angle brackets <>

C

- case** operator modifier 60
- case sensitivity
 - in queries 52
 - setting for the Enhanced Full-Text Search engine 74
 - in SQL xv
- character sets
 - setting the default 71
- charset** configuration parameter 67, 69
 - setting the default 71
- cis cursor rows** configuration parameter 81
- cis packet size** configuration parameter 82
- cluster_effort** configuration parameter 48, 68, 70
 - values for 148
- cluster_keywords* pseudo column 44, 49
- cluster_max** configuration parameter 48, 68, 70
 - values for 148
- cluster_number* pseudo column 44, 49
- cluster_order** configuration parameter 48, 68, 70
 - values for 148
- cluster_style** configuration parameter 48, 68, 70
 - values for 148
- clustering 48
 - configuring for all tables 29
 - configuring for individual tables 29
 - enabling 27
 - modifying values of parameters for 147
 - setting up 48
 - in a sort specification 47
 - values of configuration parameters 148
 - writing queries for 49
- colDir** configuration parameter 67, 70
- collections 6, 76
 - See also* text indexes
 - backing up 150

- creating 140
- default character set 71
- default language 70
- disabling optimization 73, 79
- displaying the names of 143
- dropping 142
- location of 6
- setting the location of 67
- modifying data in 23
- optimizing 143
- performance issues when updating 83
- populating with data 20
- and reindexing 144
- restoring from backup 75, 77
- columns
 - valid datatypes to index 5
- comma (,)
 - in SQL statements xiv
- commands in Verity.
 - See* operators (commands)
- complement** operator 50, 53
- Component Integration Services
 - connecting to an Enhanced Full-Text Search engine 1
- configuration file
 - sample 159
- configuration parameters 67–68, 69–70
 - See also* individual configuration parameters
 - auto_online** 156
 - backDir** 77, 153
 - batch_size** parameter and performance 82–83
 - charset** 71
 - cluster_effort** 48, 148
 - cluster_max** 48, 148
 - cluster_order** 48, 148
 - cluster_style** 48, 148
 - displaying values 149
 - language** 70
 - max_sessions** parameter and performance 83
 - min_sessions** parameter and performance 83
 - modifying values 149
 - nocase** 75
 - sort_order** 46, 72
 - srv_traceflags** 74
 - vdkCharset** 71
 - vdkLanguage** 70
- configuration parameters, Adaptive Server
 - cis cursor rows** 81
 - cis packet size** 82
 - connecting to an Enhanced Full-Text Search engine 85
 - connections, number of user 83
 - conventions
 - See also* syntax
 - directory paths xiii
 - used in manuals xiii
 - curly braces ({})
 - in SQL statements xiv
 - cursor events, logging 73
 - custom thesaurus 34
 - and creating the control file 35
 - and examining the default thesaurus 35
 - and the **mksyd** utility 37
 - and replacing the default thesaurus 37

D

- databases
 - bringing online for full-text searches 22
- databases, bringing online
 - automatically 68, 70
- datatypes
 - and indexing 21
 - of indexed columns 5, 140
- default_Db** configuration parameter 68, 70
- defining multiple Enhanced Full-Text Search engines 15
- delete** operations
 - creating triggers for 23
- deletes
 - and updating the text indexes 8
 - from the *text_events* table 139
 - from the *vesaux* table 139
- document filters 6
- document zones
 - and multiple columns in a text index 22
 - using with the **in** operator 53
- dump database** command
 - and the **sp_text_dump_database** system procedure 77, 152

E

- ellipsis (...) in SQL statements xv
- Enhanced Full-Text Search engine
 - changing the name of 15
 - configuring multiple engines 15, 84–85
 - connecting to 85
 - document filters 6
 - how queries are processed 10
 - notifying of updates to the *text_events* table 155
 - operators 50–60
 - relationship of components 9
 - shutting down 66
 - starting as a service 65
 - starting for UNIX platforms 63
 - starting for Windows NT 65–66
 - starting with Sybase Central 65
- Enhanced Full-Text Search Specialty Data Store
 - components of 5–9
- error log file
 - setting the path name of 68
 - specifying in the runserver file 64
- error logging 73
- errorLog** configuration parameter 68, 70
- events, logging 73–74

F

- file descriptors
 - setting limits 68
- filters, document 6
 - creating 32
 - and document zones 54
- forceplan**
 - and forcing join orders 81
- full-text search queries
 - bringing databases online for 22
 - and case sensitivity 52
 - components of 43
 - processing a 10
 - and requesting clustered result sets 49
 - sort order specifications 46–47
 - and using topics 41
 - using alternative syntax 52

G

- getsend** program 165

H

- highlight pseudo column 45

I

- id* pseudo column 7, 45
 - mapping to the IDENTITY column in the source table 20
 - and query optimization 81
- IDENTITY columns
 - adding a unique index 20
 - adding to a source table 20
 - adding to existing source table 20
 - displaying with the text index 143
 - example of adding 25
 - joining with the index table 7, 10
 - in the source table 5
- in** operator 50, 53
- index table
 - and pseudo columns 44–??
 - contents of 7
 - creating 20, 140
 - dropping 142
 - and the *id* column 19
 - in a query 10
 - joining with the source table 7
 - and pseudo columns 7, ??–44
- index_any* pseudo column 45
 - and query optimization 81
- insert** operations
 - creating triggers for 23
- inserts
 - and updating the text indexes 8
- installevent** installation script
 - editing 17
 - example of using 24
 - using 17
- installtextserver** installation script
 - and creating multiple Enhanced Full-Text Search engines 84

Index

- editing 15
- location of 15
- instsvr.exe** utility 66
- integrity, maintaining 6
- Intelligent Classifier 40
- interfaces
 - tracing calls between Enhanced Full-Text Search engine and Verity 73
- interfaces** configuration parameter 68, 70
- interfaces file
 - setting the location of 68, 70
 - specifying in the runserver file 64

J

- join order
 - ensuring correct 80
- joining the source table with the text index 5, 7, 10, 19, 43
 - and increasing performance of 80

K

- /keys** modifier 36
- knowledge base map
 - creating 40
 - defining the location of 41
- knowledge_base** configuration parameter 41, 68, 70

L

- language
 - setting the default 70–71
- language** configuration parameter 67, 69
 - setting the default 70
- language events, logging 73
- like** operator 50, 54
 - enabling literal text in the QBE specification 27
- limits
 - file descriptors 68
- list**
 - keyword 36
- logging events using trace flags 73–74

M

- maintaining integrity 6
- many** operator modifier 60
- max_docs** pseudo column 45
 - with clustered result sets 49
 - and increasing query performance 80
 - and sort orders 72
- max_indexes** configuration parameter 67, 69
- max_packet_size** configuration parameter 67, 69
- max_session_fd** 68, 70
- max_sessions** configuration parameter 67, 69
 - and performance 83
- max_stack_size** configuration parameter 67, 69
- max_threads** configuration parameter 67, 69
- metadata 6
- min_sessions** configuration parameter 67, 69
 - and performance 83
- mksyd** utility
 - and creating a custom thesaurus 37
 - and examining the default thesaurus 35
- mktopics** utility 40
- multiple users 85

N

- naming the Enhanced Full-Text Search engine 68, 70
- near** operator 50, 54, 55
- near/n** operator 50, 55
 - with the **order** modifier 61
- network requests, tracing 74
- nocase** configuration parameter 68, 70, 75
- not** operator modifier 60

O

- online databases.
 - See* databases, bringing online
- Open Server events, tracing 74
- Open Server trace flags 74
- operator modifiers
 - case** 60
 - many** 60
 - not** 60
 - order** 61

- operators (commands) 50–60
 - accrue** 50, 52
 - and** 50, 53
 - complement** 50, 53
 - enclosing in angle brackets 51
 - in** 50, 53
 - like** 50, 54
 - near** 50, 54, 55
 - near/n** 50, 55
 - or** 50, 53
 - paragraph** 50, 55
 - phrase** 50, 55
 - product** 50, 56
 - and relevance-ranking 45–46
 - sentence** 50, 56
 - stem** 50, 56
 - sum** 50, 57
 - thesaurus** 50, 57
 - topic** 50, 58
 - wildcard** 50, 58
 - word** 50, 59
 - yesno** 50, 60
 - optimization, disabling 73, 79
 - or** operator 50, 53
 - with the **not** modifier 60
 - order** operator modifier 61
 - outline file for topics 39
- ## P
- paragraph** operator 50, 55
 - with the **many** modifier 60
 - with the **order** modifier 61
 - parameters
 - of a search 7
 - parentheses ()
 - in SQL statements xiv
 - performance and tuning
 - adding a unique index 20
 - and using multiple Enhanced Full-Text Search engines 84
 - disabling text index optimization 79
 - increasing query performance 80–81
 - reconfiguring Adaptive Server 81–82
 - reconfiguring the Enhanced Full-Text Search engine 82–83
 - and **sp_text_notify** 83
 - phrase** operator 50, 55
 - with the **many** modifier 60
 - procedures.
 - See* system procedures
 - processed events
 - removing from the *text_events* table 139
 - processing full-text searches 10
 - product** operator 50, 56
 - propagating changes to the collections 8
 - proxy tables as a source table 6
 - pseudo columns 7
 - cluster_keywords* 44, 49
 - cluster_number* 44, 49
 - highlight** 45
 - id* 45
 - in a query 10
 - index_any* 45
 - max_docs* 45, 49
 - score* 45–46
 - sort_by* 45, 46–47, 49
 - summary* 45, 47
- ## Q
- QBE specification.
 - See* query-by-example
 - queries
 - and pseudo columns 7
 - queries, full-text search
 - bringing databases online for 22
 - and case sensitivity 52
 - components of 43
 - ensuring the correct join order 80
 - increasing performance of 80–81
 - processing of 10
 - requesting clustered result sets 49
 - sort order specifications 46–47
 - and using topics 41
 - using alternative syntax 52
 - query-by-example
 - configuring for all tables 29
 - configuring for individual tables 29
 - enabling 27

Index

- and the **like** operator 54
- R**
- ranking documents.
 - See relevance-ranking
- recovery 75
 - and synchronizing a text index with the source table 144
- relevance-ranking 45–46
 - See also *score* pseudo column
- remote procedure calls
 - sp_traceoff** 73, 80
 - sp_traceon** 73, 80
- remote tables as a source table 6
- replicating text indexes 23
- RPC events, logging 73
- RPCs.
 - See remote procedure calls
- runserver file 63
 - flags for 64
- S**
- sample files
 - configuration file 159
 - illustrating clustering 164
 - illustrating custom thesaurus 35, 164
 - illustrating query-by-example 164
 - illustrating summarization 164
 - illustrating topics feature 39, 164
- sample program **getsend** 165
- sample scripts
 - sample_text_main.sql* 19, 23, 163
- score* pseudo column 8, 45–46
 - with clustered result sets 49
 - and default sort order 72
 - and the **many** modifier 60
 - sorting by 47
- score* values
 - how Sybase reports 46
- scripts, sample
 - sample_text_main.sql* 19, 23, 163
- search parameters 7
- sentence** operator 50, 56
 - with the **many** modifier 60
 - with the **order** modifier 61
- sessions, number of user 83
- showplan**
 - and examining join orders 81
- shutting down the Enhanced Full-Text Search engine 66
- sort orders
 - and clustered result sets 47, 49
 - by column 30, 47
 - in a query 46–47
 - max_docs* and sort order 72
 - by *score* 47
 - setting the default 72
 - by timestamp 47, 72
- sort specifications
 - setting up a defined column to sort by 30
- sort_by* pseudo column 45
 - and requesting a clustered result set 49
 - and specifying a sort order 46–47
 - and setting up a defined column as a sort specification 30
- sort_order** configuration parameter 46, 68, 70, 72
- source tables
 - adding an **IDENTITY** column to 19
 - changes to data 145, 155
 - contents of 5
 - and displaying text indexes 143
 - in a query 10
- sp_addserver** system procedure 84
- sp_check_text_index** system procedure 138
- sp_clean_text_events** system procedure 139
- sp_clean_text_indexes** system procedure 139
- sp_create_text_index** system procedure 20, 140–141
 - creating indexes that use a filter 32
 - example of using 25
 - specifying multiple columns 22
- sp_drop_text_index** system procedure 142
- sp_help_text_index** system procedure 143
- sp_optimize_text_index** system procedure 79, 143–144
- sp_redo_text_events** system procedure 144–145
- sp_refresh_text_index** system procedure 145–146
 - modifying data in the collections 23
 - running automatically 23

- sp_show_text_online** system procedure 146–147
 - sp_statistics** system procedure
 - disabling 73, 80
 - sp_text_cluster** system procedure 147–149
 - sp_text_configure** system procedure 69, 149–150
 - sp_text_dump_database** system procedure 76, 150–153
 - sp_text_kill** system procedure 153–154
 - sp_text_load_index** system procedure 77, 154–155
 - sp_text_notify** system procedure 155, 156
 - and modifying data in the collections 23
 - and performance issues 83
 - and turning off optimization 79
 - sp_text_online** system procedure 22, 156–157
 - example 26
 - sp_traceoff** remote procedure call 73, 80
 - sp_traceon** remote procedure call 73, 80
 - SQL parsing, tracing 73
 - square brackets []
 - in SQL statements xiv
 - srv_traceflags** configuration parameter 68, 70, 74
 - starting the Enhanced Full-Text Search engine
 - from Sybase Central 65
 - on UNIX platforms 63
 - on Windows NT 65–66
 - as a service 65
 - startserver** utility 63
 - start-up
 - and setting the number of user connections 83
 - start-up commands
 - and the runserver file 63
 - on Windows NT 65
 - stem** operator 50, 56
 - with the **many** modifier 60
 - style.dft* file 32
 - style.prm* file
 - editing an existing collection's 141
 - editing for an existing collection 29
 - editing the master 29
 - and enabling Verity functionality 27
 - location of an existing collection 29
 - location of master 29
 - style.ufl* file 30, 32
 - style.vgw* file 30, 32
 - sum** operator 50, 57
 - summarization
 - configuring for all tables 29
 - configuring for individual tables 29
 - enabling 27
 - writing queries requesting 47
 - summary* pseudo column 45
 - enabling before using 27
 - using 47
 - Sybase Central, starting from 65
 - symbols in SQL statements xiv
 - synonym list for a custom thesaurus 35
 - synonyms**
 - statement 36
 - syntax conventions, Transact-SQL xiii
 - syntax, alternative Verity 52
 - syservers* table
 - adding Enhanced Full-Text Search engines 84
 - system procedures
 - See also individual system procedures*
 - sp_check_text_index** 138
 - sp_clean_text_events** 139
 - sp_clean_text_indexes** 139
 - sp_create_text_index** 140–141
 - sp_drop_text_index** 142
 - sp_help_text_index** 143
 - sp_optimize_text_index** 143–144
 - sp_redo_text_events** 144–145
 - sp_refresh_text_index** 145–146
 - sp_show_text_online** 146–147
 - sp_text_cluster** 147–149
 - sp_text_configure** 149–150
 - sp_text_dump_database** 150–153
 - sp_text_kill** 153–154
 - sp_text_load_index** 154–155
 - sp_text_notify** 155–156
 - sp_text_online** 156–157
 - system tables
 - updating 137
- ## T
- TDS data, tracing 74
 - TDS headers, tracing 74
 - TDS tokens, tracing 74
 - text documents, types of 6
 - text indexes 76, 77

- backing up 150
 - bringing online 156
 - creating 20, 140
 - creating and batch sizes 82
 - displaying a list of 143
 - displaying online 146
 - dropping 142
 - example of creating 24–26
 - and the index table 7
 - metadata 6
 - that include multiple columns 22
 - optimizing 143
 - performance issues when updating 83
 - placing on multiple Enhanced Full-Text Search engines 84
 - and reindexing 144
 - replicating 23
 - restoring from backup in Enhanced version 75
 - setting location of backup files 68, 70
 - and tracing information 73
 - update using *text_events* table 8
 - updating 79
 - using a document filter with 32
 - text_db* database 6, 75, 76
 - backing up 150
 - changing the name of 15, 18
 - restoring from backup 77
 - and the *vesaux* table 6
 - and the *vesauxcol* table 7
 - text_events* table 8, 76
 - changing the status of entries 144
 - columns in 8
 - creating 17
 - example of creating 24
 - recording inserts, updates, and deletes 145
 - removing entries from 139
 - restoring from backup 76, 77
 - and **sp_text_dump_database** 76, 153
 - and **sp_text_load_index** 77
 - textsrvr.cfg* file
 - sample 159
 - thesaurus** operator 50, 57
 - using a custom thesaurus 34
 - thesaurus, custom 34
 - and creating the control file 35
 - and examining the default thesaurus 35
 - and the **mksyd** utility 37
 - and replacing the default thesaurus 37
 - timestamp
 - sorting by 72
 - topic** operator 41, 50, 58
 - topic set directories 40
 - mapping to 41
 - topics
 - creating a knowledge base map 40
 - creating a topic set directory 40
 - creating an outline file 39
 - creating complex relationships 39
 - description of 38
 - executing queries using 41
 - sample files 39
 - troubleshooting 42
 - trace flags 73
 - enabling trace flags 11 and 12 79
 - Open Server 74
 - setting to examine join orders 81
 - traceflags** configuration parameter 68, 70
 - triggers for running **sp_refresh_text_index** 23
- ## U
- Unicode 167
 - and wildcard searches 73
 - Unicode support 167
 - unique index
 - adding to an IDENTITY column 20
 - example of creating 25
 - update** operations
 - creating triggers for 23
 - update statistics**
 - disabling 80
 - updates
 - and updating the text indexes 8
 - updating indexes 79
 - user
 - connections 83
 - sessions 83
 - user databases 75, 76
 - backing up 150
 - bringing online automatically 68, 70
 - bringing online for full-text searches 22, 156

displaying a list of text indexes for 143
 displaying online 146
 restoring from backup 77
 user table.
See source table

V

vdkCharset configuration parameter 67, 69
 setting the default 71
vdkHome configuration parameter 67, 70
vdkLanguage configuration parameter 67, 70
 setting the default 70

Verity

setting the Verity directory 67
 tracing Verity processing 73

Verity collections.

See collections

Verity query.

See full-text search queries

vesaux table

columns in 6
 creating entries 141
 removing entries from 139
 removing entries when dropping text indexes 142
 updating 20

vesauxcol table

columns in 7
 removing entries when dropping text indexes 142
 updating 20

W

wildcard operator 50, 58
 using with data in Unicode format 73
 with the **case** modifier 60
 with the **many** modifier 60

Windows NT

directory paths xiii

word operator 50, 59

with the **case** modifier 60
 with the **many** modifier 60

writetext command, using triggers with 23

Y

yesno operator 50, 60

Z

zones.

See document zones

