



**SAP Sybase IQ Error Messages**

---

**SAP Sybase IQ 16.0 SP2**

DOCUMENT ID: DC00462-01-1602-01

LAST REVISED: November 2013

Copyright © 2013 by SAP AG or an SAP affiliate company. All rights reserved.

No part of this publication may be reproduced or transmitted in any form or for any purpose without the express permission of SAP AG. The information contained herein may be changed without prior notice.

Some software products marketed by SAP AG and its distributors contain proprietary software components of other software vendors. National product specifications may vary.

These materials are provided by SAP AG and its affiliated companies ("SAP Group") for informational purposes only, without representation or warranty of any kind, and SAP Group shall not be liable for errors or omissions with respect to the materials. The only warranties for SAP Group products and services are those that are set forth in the express warranty statements accompanying such products and services, if any. Nothing herein should be construed as constituting an additional warranty.

SAP and other SAP products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of SAP AG in Germany and other countries. Please see <http://www.sap.com/corporate-en/legal/copyright/index.epx#trademark> for additional trademark information and notices.

# Contents

<b>About this guide .....</b>	<b>1</b>
Messages .....	1
Severity Codes .....	2
SQL Preprocessor Errors .....	3
<b>Errors and Warnings .....</b>	<b>5</b>
0 - 262 .....	5
Messages 0 through 91 .....	5
Messages 92 through 105 .....	13
Messages 106 through 116 .....	21
Messages 117 through 128 .....	30
Messages 129 through 140 .....	39
Messages 140 through 150 .....	48
Messages 151 through 180 .....	57
Messages 181 through 200 .....	65
Messages 200 through 218 .....	74
Messages 220 through 262 .....	83
263 - 785 .....	91
Messages 263 through 288 .....	92
Messages 289 through 313 .....	100
Messages 503 through 619 .....	109
Messages 620 through 639 .....	118
Messages 640 through 659 .....	126
Messages 660 through 681 .....	134
Messages 682 through 709 .....	143
Messages 710 through 731 .....	151
Messages 732 through 760 .....	159
Messages 761 through 785 .....	168
786 - 1005 .....	176
Messages 786 through 809 .....	177
Messages 810 through 829 .....	185
Messages 830 through 854 .....	194

Messages 855 through 876 .....	203
Messages 877 through 901 .....	213
Messages 902 through 923 .....	222
Messages 924 through 944 .....	230
Messages 945 through 964 .....	238
Messages 965 through 985 .....	247
Messages 986 through 1005 .....	255
1006 - 1217 .....	264
Messages 1006 through 1028 .....	264
Messages 1029 through 1050 .....	272
Messages 1051 through 1075 .....	281
Messages 1076 through 1096 .....	290
Messages 1097 through 1117 .....	299
Messages 1118 through 1137 .....	308
Messages 1138 through 1157 .....	317
Messages 1158 through 1177 .....	327
Messages 1178 through 1197 .....	336
Messages 1198 through 1217 .....	345
1218 - 1427 .....	353
Messages 1218 through 1237 .....	354
Messages 1239 through 1260 .....	362
Messages 1261 through 1280 .....	371
Messages 1281 through 1301 .....	379
Messages 1302 through 1321 .....	388
Messages 1322 through 1341 .....	397
Messages 1342 through 1363 .....	407
Messages 1366 through 1386 .....	416
Messages 1387 through 1406 .....	424
Messages 1407 through 1427 .....	433
1428 - 1629 .....	441
Messages 1428 through 1448 .....	442
Messages 1449 through 1468 .....	450
Messages 1469 through 1489 .....	458
Messages 1490 through 1509 .....	467
Messages 1510 through 1529 .....	476

Messages 1530 through 1549 .....	486
Messages 1550 through 1569 .....	495
Messages 1570 through 1589 .....	503
Messages 1590 through 1609 .....	512
Messages 1610 through 1629 .....	521
1630 - 1000133 .....	531
Messages 1630 through 1649 .....	531
Messages 1650 through 1669 .....	539
Messages 1670 through 1689 .....	548
Messages 1690 through 1709 .....	557
Messages 1710 through 1000008 .....	566
Messages 1000009 through 1000040 .....	575
Messages 1000041 through 1000061 .....	585
Messages 1000062 through 1000084 .....	594
Messages 1000085 through 1000107 .....	604
Messages 1000108 through 1000133 .....	615
1000134 - 1000328 .....	626
Messages 1000134 through 1000154 .....	626
Messages 1000155 through 1000174 .....	636
Messages 1000175 through 1000197 .....	646
Messages 1000199 through 1000218 .....	656
Messages 1000219 through 1000235 .....	666
Messages 1000235 through 1000245 .....	675
Messages 1000246 through 1000264 .....	686
Messages 1000265 through 1000284 .....	695
Messages 1000285 through 1000306 .....	705
Messages 1000307 through 1000328 .....	714
1000329 - 1006035 .....	723
Messages 1000329 through 1001010 .....	723
Messages 1001011 through 1001030 .....	732
Messages 1001031 through 1001050 .....	741
Messages 1001051 through 1001071 .....	749
Messages 1001072 through 1003001 .....	759
Messages 1003002 through 1004007 .....	768
Messages 1004008 through 1005010 .....	777

Messages 1005011 through 1005030 .....	786
Messages 1005031 through 1006015 .....	795
Messages 1006016 through 1006035 .....	804
1006036 - 1006238 .....	812
Messages 1006036 through 1006055 .....	813
Messages 1006056 through 1006075 .....	821
Messages 1006076 through 1006095 .....	829
Messages 1006096 through 1006116 .....	838
Messages 1006117 through 1006137 .....	846
Messages 1006138 through 1006157 .....	854
Messages 1006158 through 1006177 .....	862
Messages 1006178 through 1006197 .....	871
Messages 1006198 through 1006217 .....	879
Messages 1006218 through 1006238 .....	887
1006239 - 1009145 .....	895
Messages 1006239 through 1006258 .....	895
Messages 1006259 through 1008005 .....	904
Messages 1008006 through 1008027 .....	912
Messages 1008029 through 1009023 .....	921
Messages 1009024 through 1009043 .....	930
Messages 1009044 through 1009064 .....	940
Messages 1009065 through 1009084 .....	950
Messages 1009085 through 1009104 .....	960
Messages 1009105 through 1009124 .....	969
Messages 1009125 through 1009145 .....	979
1009146 - 1013018 .....	990
Messages 1009146 through 1009165 .....	991
Messages 1009166 through 1009185 .....	1000
Messages 1009186 through 1009420 .....	1010
Messages 1010000 through 1010019 .....	1019
Messages 1010020 through 1010040 .....	1029
Messages 1010041 through 1010060 .....	1038
Messages 1010061 through 1012005 .....	1047
Messages 1012006 through 1012025 .....	1055
Messages 1012026 through 1012045 .....	1063

Messages 1012046 through 1013018 .....	1073
1013019 - 1013136 .....	1082
Messages 1013019 through 1013040 .....	1082
Messages 1013041 through 1013062 .....	1092
Messages 1013063 through 1013088 .....	1101
Messages 1013089 through 1013111 .....	1109
Messages 1013112 through 1013131 .....	1118
Messages 1013132 through 1013136 .....	1128
<b>SQL Preprocessor Errors .....</b>	<b>1131</b>
Messages 2601 through 2621 .....	1131
Messages 2622 through 2649 .....	1133
Messages 2650 through 2692 .....	1136
Messages 2694 through 2701 .....	1138

## Contents

# About this guide

The SAP® Sybase® IQ Error Messages Guide is a reference for SAP Sybase IQ errors and warnings.

## *Organization*

This guide references *SAP Sybase Error Codes* on page 1 and *SQL Preprocessor Errors* on page 3. Messages are organized by error number and include all attributes associated with the message.

## *Other sources of information*

- For additional information about SAP Sybase IQ, see the SAP Sybase IQ documentation set.
- The *SAP Sybase Product Documentation Web site* provides online access to all of the books in the SAP Sybase IQ documentation set. The *SAP Sybase Web site* also includes links to *SAP Sybase Product Download Center*, *Platform Certifications*, and the *SAP Sybase Developer Network*. Create a personal profile on the *MySybase* page to simplify your browsing.

## *If you need help*

Each SAP Sybase installation with a valid support contract should have one or more designated people authorized to contact SAP Sybase Technical Support. If you cannot resolve a problem using the manuals or online help, please have that designated person contact SAP Sybase Technical Support or the SAP Sybase subsidiary in your area.

---

# Messages

Messages are grouped by range and include all attributes associated with the error or warning. To find information about a message, choose the appropriate page.

Row Name	Description
Error or Warning	Error number and full text of the message.
Constant	Unique string constant for each message.
SAP Sybase Error Number	<p>SAP Sybase error numbers are a set of error codes used by all SAP Sybase products.</p> <p>For every error code returned by SAP Sybase IQ, there is a pair of matching SQLCODE and SQLSTATE codes. Some error codes are not unique. Many of the errors contain the characters %1, %2 and so on. These are replaced by the parameters to the error message.</p>

## About this guide

Row Name	Description
SQL State	<p>SQLSTATE error codes are defined by the SQL/92 standard. Each SQLSTATE value is a 5-character string containing a 2-character class followed by a 3-character subclass.</p> <p>Each character can be one of the uppercase letters A through Z or the digits 0 through 9. A class that begins with A through H or 0 through 4 has been defined by the ANSI standard; other classes are implementation defined. Similarly, subclasses of standard classes that start with the same characters (A-H, 0-4) are standard. The subclass 000 always means that no subclass code is defined. The most common SQLSTATE value is 00000, which indicates successful completion.</p>
SQL Code	<p>SQLCODE is a numeric code associated with an exception. Negative codes are considered errors; positive codes are warnings.</p> <p>If a SQLCODE has both a negative and a positive value, the first message listed is 'Warning nnn' (the positive SQLCODE), then 'Error nnn' (the negative SQLCODE). The SQLCODE 0 indicates successful completion.</p>
ODBC 2 State	ODBCSTATE 2 is set to OK or ERROR.
ODBC 3 State	ODBCSTATE 3 is set to OK or ERROR.
Severity Codes	Each numbered error message has an associated severity level that indicates the seriousness of the problem.
Parameters	Many error messages contain the characters %1, %2, and so on. These characters are replaced by the parameters to the error message.
Probable Cause	Probable Cause tells you what the problem is, and may suggest how to fix it.

## Severity Codes

Severity codes indicate the degree and source of the error.

Number	Description	Number	Description
0	Comment.	17	Insufficient resources.
1	Information.	18	Non-fatal internal error detected.
10	Status information; warning.	19	Fatal error in resource.
11	Specified database object not found.	20	Fatal error in current process.
12	Wrong data type encountered.	21	Fatal error in database processes.

Number	Description	Number	Description
13	User transaction syntax error.	22	Fatal error: table integrity suspect.
14	Insufficient permission to execute command.	23	Hardware error or system table corruption.
15	Syntax error in SQL statement.	24	Hardware error or system table corruption.
16	Miscellaneous user error (non-fatal).		

## SQL Preprocessor Errors

---

SQL preprocessor errors occur in the C preprocessor.

Embedded SQL is a database programming interface for the C and C++ programming languages. Embedded SQL consists of SQL statements intermixed with (embedded in) C or C++ source code. These SQL statements are translated by a SQL preprocessor into C or C++ source code, which then need to be recompiled by the user. The Sybase IQ SQL preprocessor utility sqlpp translates the SQL statements in an input file `sqc` into C language source that is put into an output file `.c`.

SQL preprocessor errors are grouped by range. To find information about a specific error or warning, choose the appropriate page.

## About this guide

# Errors and Warnings

## 0 - 262

---

### Messages 0 through 91

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Warning 0	No message
<b>Constant</b>	NOERROR
<b>SAP Sybase Error Number</b>	2000
<b>SQL State</b>	00000
<b>SQL Code</b>	0L
<b>ODBC 2 State</b>	00000
<b>ODBC 3 State</b>	00000
<b>Severity Code</b>	<i>10</i> on page 2
<b>Probable Cause</b>	This code indicates that there was no error or warning.

Error 72	"No database file specified"
<b>Constant</b>	NO_DATABASE_FILE
<b>SAP Sybase Error Number</b>	2021
<b>SQL State</b>	08W39
<b>SQL Code</b>	-72L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2
<b>Probable Cause</b>	The database server was started but there was no specified database file. The server is stopped.

## Errors and Warnings

<b>Error 74</b>	<b>"The selected database is currently inactive"</b>
<b>Constant</b>	DATABASE_NOT_ACTIVE
<b>SAP Sybase Error Number</b>	2013
<b>SQL State</b>	08W30
<b>SQL Code</b>	-74L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	The selected database is in an inactive state. The database may be in the process of being started or shut down.
<b>Error 75</b>	<b>"Request to start/stop database denied"</b>
<b>Constant</b>	START_STOP_DATABASE_DENIED
<b>SAP Sybase Error Number</b>	2014
<b>SQL State</b>	08W29
<b>SQL Code</b>	-75L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	You do not have permission to start or stop a database. The required permission is determined on the server command line.
<b>Error 76</b>	<b>"Request denied -- no active databases"</b>
<b>Constant</b>	REQUEST_DENIED_NO_DATABASES
<b>SAP Sybase Error Number</b>	2015
<b>SQL State</b>	08W28
<b>SQL Code</b>	-76L
<b>ODBC 2 State</b>	08004
<b>ODBC 3 State</b>	08004

<b>Error 76</b>	<b>"Request denied -- no active databases"</b>
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	The server has denied your request as there are currently no running databases.
<b>Error 77</b>	<b>"Database name not unique"</b>
<b>Constant</b>	ALIAS_CLASH
<b>SAP Sybase Error Number</b>	2016
<b>SQL State</b>	08W27
<b>SQL Code</b>	-77L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The database cannot be started as its name conflicts with a previously started database.
<b>Error 78</b>	<b>"Dynamic memory exhausted"</b>
<b>Constant</b>	DYNAMIC_MEMORY_EXHAUSTED
<b>SAP Sybase Error Number</b>	2024
<b>SQL State</b>	08W26
<b>SQL Code</b>	-78L
<b>ODBC 2 State</b>	S1001
<b>ODBC 3 State</b>	HY001
<b>Severity Code</b>	<i>17</i> on page 2
<b>Probable Cause</b>	A failure occurred when the database server was trying to allocate dynamic memory.
<b>Error 79</b>	<b>"Invalid local database option"</b>
<b>Constant</b>	INVALID_LOCAL_OPTION
<b>SAP Sybase Error Number</b>	2017

## Errors and Warnings

<b>Error 79</b>	<b>"Invalid local database option"</b>
<b>SQL State</b>	08W25
<b>SQL Code</b>	-79L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>18</i> on page 2
<b>Probable Cause</b>	An invalid database option was found in the DBS (DatabaseSwitches) connection parameter.
<b>Error 80</b>	<b>"Unable to start database server"</b>
<b>Constant</b>	UNABLE_TO_START_ENGINE
<b>SAP Sybase Error Number</b>	2011
<b>SQL State</b>	08W07
<b>SQL Code</b>	-80L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>17</i> on page 2
<b>Probable Cause</b>	It was not possible to start the database server. There may not be enough memory to run the database server. It may also be that the executable cannot be found.
<b>Error 81</b>	<b>"Invalid database server command line"</b>
<b>Constant</b>	INVALID_COMMAND_LINE
<b>SAP Sybase Error Number</b>	2012
<b>SQL State</b>	08W08
<b>SQL Code</b>	-81L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>18</i> on page 2

<b>Error 81</b>	<b>"Invalid database server command line"</b>
<b>Probable Cause</b>	It was not possible to start the database server because the command line was invalid.

<b>Error 82</b>	<b>"Unable to start specified database: %1"</b>
<b>Constant</b>	UNABLE_TO_START_DATABASE
<b>SAP Sybase Error Number</b>	2018
<b>SQL State</b>	08W09
<b>SQL Code</b>	-82L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	Reason the database could not be started, if known.
<b>Probable Cause</b>	The database server was unable to start the specified database. Check the database server messages window for more details. If the server was being started automatically, you can use the database server -o option to view messages from the database server or start the server manually to try to obtain more information about why the database cannot be started.

<b>Error 83</b>	<b>"Specified database not found"</b>
<b>Constant</b>	DATABASE_NOT_FOUND
<b>SAP Sybase Error Number</b>	2019
<b>SQL State</b>	08W10
<b>SQL Code</b>	-83L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>16</i> on page 2

## Errors and Warnings

<b>Error 83</b>	<b>"Specified database not found"</b>
<b>Probable Cause</b>	The database server was unable to find the specified database. The database server may be attempting to start a database file that cannot be opened or that cannot be found on the network. You may be attempting to connect to a database name that is not running.
<b>Error 84</b>	<b>"Specified database is invalid"</b>
<b>Constant</b>	INVALID_DATABASE
<b>SAP Sybase Error Number</b>	2020
<b>SQL State</b>	08W11
<b>SQL Code</b>	-84L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2
<b>Probable Cause</b>	The database file you specified is invalid. The database server is stopped.
<b>Error 85</b>	<b>"Communication error"</b>
<b>Constant</b>	COMMUNICATIONS_ERROR
<b>SAP Sybase Error Number</b>	2022
<b>SQL State</b>	08W12
<b>SQL Code</b>	-85L
<b>ODBC 2 State</b>	08S01
<b>ODBC 3 State</b>	08S01
<b>Severity Code</b>	<i>21</i> on page 2
<b>Probable Cause</b>	There is a communication problem between the application and the server.
<b>Error 86</b>	<b>"Not enough memory to start"</b>
<b>Constant</b>	NO_MEMORY
<b>SAP Sybase Error Number</b>	2025

<b>Error 86</b>	<b>"Not enough memory to start"</b>
<b>SQL State</b>	08W13
<b>SQL Code</b>	-86L
<b>ODBC 2 State</b>	S1001
<b>ODBC 3 State</b>	HY001
<b>Severity Code</b>	<i>17</i> on page 2
<b>Probable Cause</b>	The database server started, but stopped because there was not enough memory.
<b>Error 87</b>	<b>"Database name required to start server"</b>
<b>Constant</b>	DATABASE_NAME_REQUIRED
<b>SAP Sybase Error Number</b>	2026
<b>SQL State</b>	08W14
<b>SQL Code</b>	-87L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>17</i> on page 2
<b>Probable Cause</b>	You did not supply a database name. A database name is required to start a database server.
<b>Error 88</b>	<b>"Client/server communications protocol version mismatch"</b>
<b>Constant</b>	PROTOCOL_MISMATCH
<b>SAP Sybase Error Number</b>	2027
<b>SQL State</b>	08W15
<b>SQL Code</b>	-88L
<b>ODBC 2 State</b>	08S01
<b>ODBC 3 State</b>	08S01
<b>Severity Code</b>	<i>21</i> on page 2

## Errors and Warnings

<b>Error 88</b>	<b>"Client/server communications protocol version mismatch"</b>
<b>Probable Cause</b>	The connection failed because the protocol versions of the client and the server do not match. Ensure the client and server software are the same version.
<b>Error 89</b>	<b>"Database server not running in multi-user mode"</b>
<b>Constant</b>	ENGINE_NOT_MULTIUSER
<b>SAP Sybase Error Number</b>	2029
<b>SQL State</b>	08W16
<b>SQL Code</b>	-89L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>17</i> on page 2
<b>Probable Cause</b>	The database server was started for bulk loading (the -b option) and cannot be used as a network server. Stop the database server, and start again without -b.
<b>Error 90</b>	<b>"Argument %1 of procedure '%2' cannot be NULL"</b>
<b>Constant</b>	ARGUMENT_CANNOT_BE_NULL
<b>SAP Sybase Error Number</b>	2267
<b>SQL State</b>	WP000
<b>SQL Code</b>	-90L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The argument number that cannot be NULL.
<b>Parameter 2</b>	The name of the procedure that cannot receive the NULL parameter.
<b>Probable Cause</b>	You passed a NULL value to a procedure expecting a scalar argument. For example, a Java procedure that has an 'int' argument cannot receive a NULL value.

<b>Error 91</b>	<b>"Procedure '%1' terminated with unhandled exception '%2'"</b>
<b>Constant</b>	UNHANDLED_EXTENV_EXCEPTION
<b>SAP Sybase Error Number</b>	2268
<b>SQL State</b>	WP001
<b>SQL Code</b>	-91L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the procedure that returned the unhandled exception.
<b>Parameter 2</b>	The fully qualified Java class name of the unhandled exception.
<b>Probable Cause</b>	A Java procedure terminated with an active exception, and this exception is reflected in SQL as an error status.

## Messages 92 through 105

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 92</b>	<b>"'%1' is not a valid class file"</b>
<b>Constant</b>	BAD_CLASS_FILE
<b>SAP Sybase Error Number</b>	2269
<b>SQL State</b>	WP002
<b>SQL Code</b>	-92L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the invalid file.
<b>Probable Cause</b>	A file passed to the INSTALL JAVA statement was not a valid Java class file.

## Errors and Warnings

<b>Error 93</b>	<b>"Class '%1' has no public field '%2'"</b>
<b>Constant</b>	FIELD_NOT_FOUND
<b>SAP Sybase Error Number</b>	2273
<b>SQL State</b>	WW013
<b>SQL Code</b>	-93L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the class in which the named field could not be found.
<b>Parameter 2</b>	The name of the field that could not be found.
<b>Probable Cause</b>	An expression referenced a field that either does not exist or is not public.

<b>Error 94</b>	<b>"Invalid type for field reference"</b>
<b>Constant</b>	INVALID_FIELD_REFERENCE
<b>SAP Sybase Error Number</b>	2274
<b>SQL State</b>	WW014
<b>SQL Code</b>	-94L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	An expression attempted to reference a field or a method of a non-Java value. Field references via . and &gt;&gt; are only valid when applied to Java objects.

<b>Error 95</b>	<b>"Parse error: %1"</b>
<b>Constant</b>	INVALID_PARSE_PARAMETER
<b>SAP Sybase Error Number</b>	2380
<b>SQL State</b>	08W49
<b>SQL Code</b>	-95L

<b>Error 95</b>	"Parse error: %1"
<b>ODBC 2 State</b>	08004
<b>ODBC 3 State</b>	08004
<b>Severity Code</b>	<i>18</i> on page 2
<b>Parameter 1</b>	Description of the parsing error.
<b>Probable Cause</b>	An error occurred while parsing a connection string.

<b>Error 96</b>	"Database server already running"
<b>Constant</b>	ENGINE_ALREADY_RUNNING
<b>SAP Sybase Error Number</b>	2028
<b>SQL State</b>	08W23
<b>SQL Code</b>	-96L
<b>ODBC 2 State</b>	S1000
<b>ODBC 3 State</b>	HY000
<b>Severity Code</b>	<i>18</i> on page 2
<b>Probable Cause</b>	The database server was not able to start because a server with the same name was already running.

<b>Error 97</b>	"Database page size too big: %1"
<b>Constant</b>	PAGE_SIZE_TOO_BIG
<b>SAP Sybase Error Number</b>	2031
<b>SQL State</b>	08W22
<b>SQL Code</b>	-97L
<b>ODBC 2 State</b>	08004
<b>ODBC 3 State</b>	08004
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Database name.

## Errors and Warnings

<b>Error 97</b>	<b>"Database page size too big: %1"</b>
<b>Probable Cause</b>	You attempted to start a database with a page size that exceeds the maximum page size of the running server. Either restart the server and include this database name on the command line, or restart the server with the required page size.
<b>Error 98</b>	<b>"Authentication violation"</b>
<b>Constant</b>	AUTHENTICATION_VIOLATION
<b>SAP Sybase Error Number</b>	2034
<b>SQL State</b>	08W21
<b>SQL Code</b>	-98L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to connect to a server that has been authenticated for exclusive use with a specific application.
<b>Error 99</b>	<b>"Connections to database have been disabled"</b>
<b>Constant</b>	CONNECTIONS_DISABLED
<b>SAP Sybase Error Number</b>	2035
<b>SQL State</b>	08W04
<b>SQL Code</b>	-99L
<b>ODBC 2 State</b>	08005
<b>ODBC 3 State</b>	08005
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Connections to the network database server have been disabled. You will receive this error until connections have been enabled.
<b>Warning 100</b>	<b>"Row not found"</b>
<b>Constant</b>	NOTFOUND
<b>SAP Sybase Error Number</b>	2001

<b>Warning 100</b>	<b>"Row not found"</b>
<b>SQL State</b>	02000
<b>SQL Code</b>	100L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You positioned a cursor beyond the beginning or past the end of the query. There is no row at that position.
<b>Error 100</b>	<b>"Database server not found"</b>
<b>Constant</b>	ENGINE_NOT_RUNNING
<b>SAP Sybase Error Number</b>	2036
<b>SQL State</b>	08W01
<b>SQL Code</b>	-100L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The database server is not running, or is in the process of starting up or shutting down, or the interface library is unable to find it.
<b>Warning 101</b>	<b>"Value truncated"</b>
<b>Constant</b>	TRUNCATED
<b>SAP Sybase Error Number</b>	2002
<b>SQL State</b>	01004
<b>SQL Code</b>	101L
<b>ODBC 2 State</b>	01004
<b>ODBC 3 State</b>	01004
<b>Severity Code</b>	<i>10</i> on page 2
<b>Probable Cause</b>	You may have fetched data into a host variable or SQLDA variable not large enough to receive the value.

## Errors and Warnings

<b>Error 101</b>	<b>"Not connected to a database"</b>
<b>Constant</b>	NOT_CONNECTED
<b>SAP Sybase Error Number</b>	2037
<b>SQL State</b>	08003
<b>SQL Code</b>	-101L
<b>ODBC 2 State</b>	08003
<b>ODBC 3 State</b>	08003
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You are not connected to a database, or you executed the DISCONNECT statement and have not connected to a database again.

<b>Warning 102</b>	<b>"Using temporary table"</b>
<b>Constant</b>	TEMPORARY_TABLE
<b>SAP Sybase Error Number</b>	2003
<b>SQL State</b>	01W02
<b>SQL Code</b>	102L
<b>ODBC 2 State</b>	01000
<b>ODBC 3 State</b>	01000
<b>Severity Code</b>	<i>10</i> on page 2
<b>Probable Cause</b>	A temporary table has been created to satisfy the query. This warning can only occur on an OPEN statement.

<b>Error 102</b>	<b>"Database server connection limit exceeded"</b>
<b>Constant</b>	TOO_MANY_CONNECTIONS
<b>SAP Sybase Error Number</b>	2038
<b>SQL State</b>	08W03
<b>SQL Code</b>	-102L
<b>ODBC 2 State</b>	08004
<b>ODBC 3 State</b>	08004

<b>Error 102</b>	<b>"Database server connection limit exceeded"</b>
<b>Severity Code</b>	<i>21</i> on page 2
<b>Probable Cause</b>	You exceeded the number of computers allowed to connect to the server. If you are running the network database server, the limit is specified in your license agreement. The server may be running low on cache, and as a result it cannot accept any more database connections. The personal database server is restricted to 10 connections.

<b>Warning 103</b>	<b>"Invalid data conversion"</b>
<b>Constant</b>	CANNOT_CONVERT
<b>SAP Sybase Error Number</b>	2004
<b>SQL State</b>	01W03
<b>SQL Code</b>	103L
<b>ODBC 2 State</b>	01S01
<b>ODBC 3 State</b>	01S01
<b>Severity Code</b>	<i>10</i> on page 2
<b>Probable Cause</b>	The database could not convert a value to the required type. The value being converted was either supplied to the database on an insert, update, or as a host bind variable, or was a value retrieved from the database into a host variable or SQLDA.

<b>Error 103</b>	<b>"Invalid user ID or password"</b>
<b>Constant</b>	INVALID_LOGON
<b>SAP Sybase Error Number</b>	2039
<b>SQL State</b>	28000
<b>SQL Code</b>	-103L
<b>ODBC 2 State</b>	28000
<b>ODBC 3 State</b>	28000
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	You supplied an invalid user ID or an incorrect password.

## Errors and Warnings

<b>Warning 104</b>	<b>"Row has been updated since last time read"</b>
<b>Constant</b>	ROW_UPDATED_WARNING
<b>SAP Sybase Error Number</b>	2005
<b>SQL State</b>	01W04
<b>SQL Code</b>	104L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Probable Cause</b>	You fetched a row from a SCROLL cursor. The row was previously fetched from the same cursor, and one or more columns in the row has been updated since the previous fetch. The column(s) updated may or may not be fetched by the cursor; this warning just indicates that the row from the table has been updated. If the cursor involves more than one table, a row from one or more of the tables has been updated.
<b>Error 104</b>	<b>"Invalid user ID or password on preprocessed module"</b>
<b>Constant</b>	INVALID_MODULE_LOGON
<b>SAP Sybase Error Number</b>	2041
<b>SQL State</b>	28W01
<b>SQL Code</b>	-104L
<b>ODBC 2 State</b>	28000
<b>ODBC 3 State</b>	28000
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	You specified an invalid user ID or password when a module was preprocessed.
<b>Warning 105</b>	<b>"Procedure has completed"</b>
<b>Constant</b>	PROCEDURE_COMPLETE
<b>SAP Sybase Error Number</b>	2006
<b>SQL State</b>	01W05

<b>Warning 105</b>	"Procedure has completed"
<b>SQL Code</b>	105L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Probable Cause</b>	There are no more result sets available for this procedure. An OPEN or a RESUME statement may have caused the procedure to execute to completion.

<b>Error 105</b>	"Database cannot be started -- %1"
<b>Constant</b>	UNABLE_TO_CONNECT
<b>SAP Sybase Error Number</b>	2042
<b>SQL State</b>	08001
<b>SQL Code</b>	-105L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	Reason that database cannot be started.
<b>Probable Cause</b>	The specified database cannot be started. Either it does not exist, it is not a database, it is corrupt, or it is an older, unsupported format.

## Messages 106 through 116

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Warning 106</b>	"Value for column "%1' in table "%2' has changed"
<b>Constant</b>	COLUMN_VALUE_CHANGED
<b>SAP Sybase Error Number</b>	2007
<b>SQL State</b>	01W06
<b>SQL Code</b>	106L
<b>ODBC 2 State</b>	OK

## Errors and Warnings

<b>Warning 106</b>	<b>"Value for column '%1' in table '%2' has changed"</b>
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	Name of the column whose value has changed.
<b>Parameter 2</b>	Name of the table containing the column.
<b>Probable Cause</b>	A replicated UPDATE has found a value in an updated column that does not match the value when the original UPDATE was made.
<b>Error 106</b>	<b>"Cannot open transaction log file -- %1"</b>
<b>Constant</b>	CANNOT_OPEN_LOG
<b>SAP Sybase Error Number</b>	2043
<b>SQL State</b>	08W05
<b>SQL Code</b>	-106L
<b>ODBC 2 State</b>	08003
<b>ODBC 3 State</b>	08003
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Reason why the transaction log file cannot be opened.
<b>Probable Cause</b>	The database server was unable to open the named transaction log file. The transaction log file name may include an invalid device or directory. If this is the case, you can use the Transaction Log utility (dblog) to find out where the transaction log should be and perhaps change it.
<b>Error 107</b>	<b>"Error writing to transaction log file"</b>
<b>Constant</b>	ERROR_WRITING_LOG
<b>SAP Sybase Error Number</b>	2044
<b>SQL State</b>	08W17
<b>SQL Code</b>	-107L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>17</i> on page 2

<b>Error 107</b>	<b>"Error writing to transaction log file"</b>
<b>Probable Cause</b>	The database server got an I/O error writing the transaction log file. The disk may be full or the log file name could be invalid.
<b>Warning 107</b>	<b>"Language extension detected in syntax near '%1' on line %2"</b>
<b>Constant</b>	SYNTAX_EXTENSION_WARNING
<b>SAP Sybase Error Number</b>	2238
<b>SQL State</b>	01W07
<b>SQL Code</b>	107L
<b>ODBC 2 State</b>	01000
<b>ODBC 3 State</b>	01000
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	The word or symbol where the syntax has been detected.
<b>Parameter 2</b>	Line number.
<b>Probable Cause</b>	The statement you are executing contains syntax that is not allowed with the current setting of the option SQL_FLAGGER_WARNING_LEVEL. Modify the offending statement or set the SQL_FLAGGER_WARNING_LEVEL option to a different value.
<b>Error 108</b>	<b>"Connection not found"</b>
<b>Constant</b>	CONNECTION_NOT_FOUND
<b>SAP Sybase Error Number</b>	2045
<b>SQL State</b>	08W02
<b>SQL Code</b>	-108L
<b>ODBC 2 State</b>	08003
<b>ODBC 3 State</b>	08003
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The specified connection name on a DISCONNECT or SET CONNECTION statement is invalid.

## Errors and Warnings

<b>Error 109</b>	<b>"There are still active database connections"</b>
<b>Constant</b>	STILL_ACTIVE_CONNECTIONS
<b>SAP Sybase Error Number</b>	2046
<b>SQL State</b>	08W06
<b>SQL Code</b>	-109L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to shut down a database that still has active connections.
<b>Warning 109</b>	<b>"Null value eliminated in aggregate function"</b>
<b>Constant</b>	NULL_VALUE_ELIMINATED
<b>SAP Sybase Error Number</b>	2241
<b>SQL State</b>	01003
<b>SQL Code</b>	109L
<b>ODBC 2 State</b>	01000
<b>ODBC 3 State</b>	01003
<b>Severity Code</b>	<i>10</i> on page 2
<b>Probable Cause</b>	The expression argument of the aggregate function evaluated to NULL for one or more rows.
<b>Error 110</b>	<b>"Item '%1' already exists"</b>
<b>Constant</b>	NAME_NOT_UNIQUE
<b>SAP Sybase Error Number</b>	2047
<b>SQL State</b>	52010
<b>SQL Code</b>	-110L
<b>ODBC 2 State</b>	S0001
<b>ODBC 3 State</b>	42S01

<b>Error 110</b>	<b>"Item "%1' already exists"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the item that already exists.
<b>Probable Cause</b>	You attempted to create a file, table, view, column, constraint, foreign key, or publication with the same name as an existing one.
<b>Warning 110</b>	<b>"Transaction log backup page only partially full"</b>
<b>Constant</b>	BACKUP_PAGE_INCOMPLETE
<b>SAP Sybase Error Number</b>	2249
<b>SQL State</b>	01W10
<b>SQL Code</b>	110L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Probable Cause</b>	A DB_LOG_BACKUP_READ_WAIT was issued against the transaction log and the page returned was not full. The application should reissue the request for the same page.
<b>Warning 111</b>	<b>"Statement cannot be executed"</b>
<b>Constant</b>	CANNOT_EXECUTE_STMT
<b>SAP Sybase Error Number</b>	2008
<b>SQL State</b>	01W08
<b>SQL Code</b>	111L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Probable Cause</b>	You specified a SQL statement for the PREPARE...WITH EXECUTE statement that cannot be executed. If you specified an output SQLDA, it may contain a DESCRIBE of the prepared statement. It is normal for this warning to appear in the request log during the successful execution of a statement.

## Errors and Warnings

<b>Error 111</b>	<b>"Index name '%1' not unique"</b>
<b>Constant</b>	INDEX_NAME_NOT_UNIQUE
<b>SAP Sybase Error Number</b>	2048
<b>SQL State</b>	52W04
<b>SQL Code</b>	-111L
<b>ODBC 2 State</b>	S0011
<b>ODBC 3 State</b>	42S11
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the invalid index.
<b>Probable Cause</b>	You attempted to create an index with the same name as an existing index.
<b>Error 112</b>	<b>"Table already has a primary key"</b>
<b>Constant</b>	EXISTING_PRIMARY_KEY
<b>SAP Sybase Error Number</b>	2049
<b>SQL State</b>	55013
<b>SQL Code</b>	-112L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to add a primary key on a table that already has a primary key defined. You must delete the current primary key before adding a new one.
<b>Warning 112</b>	<b>"More information required"</b>
<b>Constant</b>	MORE_INFO
<b>SAP Sybase Error Number</b>	2252
<b>SQL State</b>	01W09
<b>SQL Code</b>	112L
<b>ODBC 2 State</b>	37000

<b>Warning 112</b>	<b>"More information required"</b>
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Probable Cause</b>	More information is required to complete the request. This is used internally in the database interface library to process a unified login. It should not be returned to an application.
<b>Error 113</b>	<b>"Column '%1' in foreign key has a different definition than primary key"</b>
<b>Constant</b>	INVALID_FOREIGN_KEY_DEF
<b>SAP Sybase Error Number</b>	2050
<b>SQL State</b>	53030
<b>SQL Code</b>	-113L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the problematic column.
<b>Probable Cause</b>	The data type of the column in the foreign key is not the same as the data type of the column in the primary key. Change the definition of one of the columns using ALTER TABLE.
<b>Warning 113</b>	<b>"Database option '%1' for user '%2' has an invalid setting"</b>
<b>Constant</b>	INVALID_OPTION_ON_CONNECT
<b>SAP Sybase Error Number</b>	2255
<b>SQL State</b>	01W11
<b>SQL Code</b>	113L
<b>ODBC 2 State</b>	01000
<b>ODBC 3 State</b>	01000
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	Name of the database option that has the invalid value.
<b>Parameter 2</b>	Name of the user attempting to connect.

## Errors and Warnings

<b>Warning 113</b>	<b>"Database option '%1' for user '%2' has an invalid setting"</b>
<b>Probable Cause</b>	Upon processing a connection request for a specific user, the server processed a database option that has an invalid setting. The server will use the default option value.
<b>Error 114</b>	<b>"Number of columns defined for the view does not match SELECT statement"</b>
<b>Constant</b>	VIEW_DEFINITION_ERROR
<b>SAP Sybase Error Number</b>	2051
<b>SQL State</b>	53011
<b>SQL Code</b>	-114L
<b>ODBC 2 State</b>	21S02
<b>ODBC 3 State</b>	21S02
<b>Severity Code</b>	<i>20</i> on page 2
<b>Probable Cause</b>	You attempted to create a view, but the column list specified as part of the CREATE VIEW statement does not correspond to the list of items in the view's SELECT statement.
<b>Warning 114</b>	<b>"Character set conversion to "%1' cannot be performed; "%2' is used instead"</b>
<b>Constant</b>	CANNOT_PERFORM_CHAR_TRANSLATION
<b>SAP Sybase Error Number</b>	2350
<b>SQL State</b>	01W12
<b>SQL Code</b>	114L
<b>ODBC 2 State</b>	01000
<b>ODBC 3 State</b>	01000
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	Name of character set the application requested.
<b>Parameter 2</b>	Name of character set the database will be using.

<b>Warning 114</b>	<b>"Character set conversion to '%1' cannot be performed; '%2' is used instead"</b>
<b>Probable Cause</b>	The server is unable to perform a character conversion from the character set the database is using to the character set the application requested.
<b>Warning 115</b>	<b>"Database server cannot convert data from/to character set '%1', conversion may not be correct"</b>
<b>Constant</b>	UNSUPPORTED_CHARACTER_SET_WARNING
<b>SAP Sybase Error Number</b>	2360
<b>SQL State</b>	01W13
<b>SQL Code</b>	115L
<b>ODBC 2 State</b>	01000
<b>ODBC 3 State</b>	01000
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	Name of the requested character set.
<b>Probable Cause</b>	The database server cannot convert character data from/to the character set requested by the application because the character set is not supported. The connection succeeds, but character conversion may not be correct for all characters.
<b>Error 116</b>	<b>"Table must be empty"</b>
<b>Constant</b>	TABLE_MUST_BE_EMPTY
<b>SAP Sybase Error Number</b>	2053
<b>SQL State</b>	55W02
<b>SQL Code</b>	-116L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to modify a table, and the database server can only perform the change if there are no rows in the table.

## Errors and Warnings

<b>Warning 116</b>	<b>"Language '%1' is not supported, '%2' will be used"</b>
<b>Constant</b>	UNSUPPORTED_LANGUAGE
<b>SAP Sybase Error Number</b>	2375
<b>SQL State</b>	01W14
<b>SQL Code</b>	116L
<b>ODBC 2 State</b>	01000
<b>ODBC 3 State</b>	01000
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	Name of the language that was requested by the client.
<b>Parameter 2</b>	Name of the language that the server will use to send message strings.
<b>Probable Cause</b>	The language that the application requested is not supported by the server to which the application is connecting. Instead, the server will send message strings in the language stated.

## Messages 117 through 128

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Warning 117</b>	<b>"Unsupported character set "%1' and unsupported language "%2'; language used is "%3' instead"</b>
<b>Constant</b>	UNSUPPORTED_CHARSET_AND_LANGUAGE
<b>SAP Sybase Error Number</b>	2376
<b>SQL State</b>	01W15
<b>SQL Code</b>	117L
<b>ODBC 2 State</b>	01000
<b>ODBC 3 State</b>	01000
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	Name of the character set that could not be supported.
<b>Parameter 2</b>	Name of the language that could not be supported.
<b>Parameter 3</b>	Name of the language that the server will use to send language strings.

<b>Warning 117</b>	<b>"Unsupported character set "%1' and unsupported language "%2'; language used is "%3' instead"</b>
<b>Probable Cause</b>	The character set that the application requested is not supported by the server to which the application is connecting. The language that the application requested is not supported either. Language strings will be sent in the language specified.

<b>Error 118</b>	<b>"Table '%1' has no primary key"</b>
<b>Constant</b>	NO_PRIMARY_KEY
<b>SAP Sybase Error Number</b>	2055
<b>SQL State</b>	55008
<b>SQL Code</b>	-118L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the table that does not have a primary key.
<b>Probable Cause</b>	You attempted an operation that required the referenced table to have a primary key. Examples of these operations include adding a foreign key, or using the ON EXISTING clause of an INSERT statement, while referring to a table that does not have a primary key. You must add a primary key to the referenced table.

<b>Warning 118</b>	<b>"Illegal user selectivity estimate specified"</b>
<b>Constant</b>	INVALID_USER_ESTIMATE
<b>SAP Sybase Error Number</b>	2381
<b>SQL State</b>	01W16
<b>SQL Code</b>	118L
<b>ODBC 2 State</b>	01000
<b>ODBC 3 State</b>	01000
<b>Severity Code</b>	<i>10</i> on page 2

## Errors and Warnings

<b>Warning 118</b>	<b>"Illegal user selectivity estimate specified"</b>
<b>Probable Cause</b>	You specified a user selectivity estimate that is either not a literal constant or is outside the range 0.0 to 100.0 (estimates are specified as percentages). The estimate has been ignored.
<b>Error 119</b>	<b>"Primary key column '%1' already defined"</b>
<b>Constant</b>	PRIMARY_KEY_COLUMN_DEFINED
<b>SAP Sybase Error Number</b>	2056
<b>SQL State</b>	52009
<b>SQL Code</b>	-119L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the column that is already in the primary key.
<b>Probable Cause</b>	You listed the same column name twice in the definition of a primary key.
<b>Warning 119</b>	<b>"Unable to open backup log '%1'"</b>
<b>Constant</b>	UNABLE_TO_OPEN_BACKUP_LOG
<b>SAP Sybase Error Number</b>	2412
<b>SQL State</b>	WB011
<b>SQL Code</b>	119L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	Backup log file name.
<b>Probable Cause</b>	The server was unable to open the backup log to record the execution of a BACKUP or RESTORE statement. Check the settings of the environment variables used to locate the backup log file. The directory to contain the log must already exist.

<b>Error 120</b>	<b>"User '%1' already has GRANT OPTION"</b>
<b>Constant</b>	ALREADY_HAS_GRANT_PERMS
<b>SAP Sybase Error Number</b>	2065
<b>SQL State</b>	42W01
<b>SQL Code</b>	-120L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the user that already has GRANT OPTION.
<b>Probable Cause</b>	You attempted to give GRANT OPTION to a user that already has it.
<b>Warning 120</b>	<b>"'%1' is an unknown option"</b>
<b>Constant</b>	UNKNOWN_OPTION
<b>SAP Sybase Error Number</b>	2384
<b>SQL State</b>	01W17
<b>SQL Code</b>	120L
<b>ODBC 2 State</b>	01000
<b>ODBC 3 State</b>	01000
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	The option that is unknown to the server.
<b>Probable Cause</b>	You attempted to set the value of an option that is not known to the server.
<b>Error 121</b>	<b>"Permission denied: %1"</b>
<b>Constant</b>	PERMISSION_DENIED
<b>SAP Sybase Error Number</b>	2066
<b>SQL State</b>	42501
<b>SQL Code</b>	-121L
<b>ODBC 2 State</b>	42000

## Errors and Warnings

<b>Error 121</b>	<b>"Permission denied: %1"</b>
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Description of the type of permission required.
<b>Probable Cause</b>	You do not have the required permission to perform the specified action. The message specifies the actual permission required and the object being acted upon.
<b>Warning 121</b>	<b>"Cursor option values changed"</b>
<b>Constant</b>	CURSOR_OPTIONS_CHANGED
<b>SAP Sybase Error Number</b>	2500
<b>SQL State</b>	01S02
<b>SQL Code</b>	121L
<b>ODBC 2 State</b>	01S02
<b>ODBC 3 State</b>	01S02
<b>Severity Code</b>	<i>10</i> on page 2
<b>Probable Cause</b>	The database server could not support the requested cursor option values for the associated query. Similar option settings were substituted.
<b>Error 122</b>	<b>"Operation would cause a group cycle"</b>
<b>Constant</b>	GROUP_CYCLE
<b>SAP Sybase Error Number</b>	2067
<b>SQL State</b>	42W02
<b>SQL Code</b>	-122L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to add a member to group that would result in a member belonging to itself. The membership may be direct or indirect.

<b>Warning 122</b>	"The result returned is non-deterministic"
<b>Constant</b>	NONDETERMINISTIC_RESULT
<b>SAP Sybase Error Number</b>	2529
<b>SQL State</b>	01W18
<b>SQL Code</b>	122L
<b>ODBC 2 State</b>	01000
<b>ODBC 3 State</b>	01000
<b>Severity Code</b>	<i>10</i> on page 2
<b>Probable Cause</b>	FIRST or TOP n are used in a SELECT statement to limit the size of a result. The statement must also have an ORDER BY if the result is to be well-defined. If it does not have an ORDER BY, then the server is free to return any subset of the result that has the requested number of rows.

<b>Error 123</b>	"User '%1' is not a user group"
<b>Constant</b>	NOT_A_GROUP
<b>SAP Sybase Error Number</b>	2068
<b>SQL State</b>	42W03
<b>SQL Code</b>	-123L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of user you thought was a group.
<b>Probable Cause</b>	You attempted to add a member to group, but the user ID specified as a group has not been granted GROUP permission.

<b>Warning 124</b>	"Invalid data conversion: NULL was inserted for column '%1' on row %2"
<b>Constant</b>	CANNOT_CONVERT_LOAD_TABLE
<b>SAP Sybase Error Number</b>	2532

## Errors and Warnings

<b>Warning 124</b>	<b>"Invalid data conversion: NULL was inserted for column '%1' on row %2"</b>
<b>SQL State</b>	01W01
<b>SQL Code</b>	124L
<b>ODBC 2 State</b>	07006
<b>ODBC 3 State</b>	07006
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	Name of the column where NULL was inserted.
<b>Parameter 2</b>	Row number in the data file where the invalid data conversion took place.
<b>Probable Cause</b>	The database could not convert a value to the required type. The value being converted was supplied to the database in a data file and inserted using LOAD TABLE. A NULL value has been inserted into the column.
<b>Error 124</b>	<b>"Dropping all columns from table '%1' is not allowed"</b>
<b>Constant</b>	TOO_MANY_COLUMNS_DELETED
<b>SAP Sybase Error Number</b>	2253
<b>SQL State</b>	42W44
<b>SQL Code</b>	-124L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the table from which the columns could not be dropped.
<b>Probable Cause</b>	The number of columns in a table can never fall below one. Your ALTER TABLE has more drop/delete column clauses than the current number of columns in the table.
<b>Error 125</b>	<b>"ALTER clause conflict"</b>
<b>Constant</b>	ALTER_CLAUSE_CONFLICT
<b>SAP Sybase Error Number</b>	2057

<b>Error 125</b>	<b>"ALTER clause conflict"</b>
<b>SQL State</b>	53W01
<b>SQL Code</b>	-125L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	A primary key clause, foreign key clause, or a uniqueness clause must be the only clause of an ALTER TABLE statement.
<b>Warning 125</b>	<b>"An invalid multi-byte input character was encountered when converting from %1 to %2"</b>
<b>Constant</b>	ILLEGAL_MULTIBYTE_WARNING
<b>SAP Sybase Error Number</b>	2538
<b>SQL State</b>	01WC1
<b>SQL Code</b>	125L
<b>ODBC 2 State</b>	01000
<b>ODBC 3 State</b>	01000
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	The character set of the input string.
<b>Parameter 2</b>	The character set of the output string.
<b>Probable Cause</b>	While the server was performing character set conversion on an input string, an invalid multi-byte character was encountered. The illegal character was directly copied without conversion. Data following the illegal character may be misinterpreted. See on_charset_conversion_failure option.
<b>Error 126</b>	<b>"Table cannot have two primary keys"</b>
<b>Constant</b>	PRIMARY_KEY_TWICE
<b>SAP Sybase Error Number</b>	2058
<b>SQL State</b>	52W05

## Errors and Warnings

<b>Error 126</b>	<b>"Table cannot have two primary keys"</b>
<b>SQL Code</b>	-126L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You specified the primary key twice in a CREATE TABLE statement.
<b>Error 127</b>	<b>"Cannot alter a column in an index"</b>
<b>Constant</b>	COLUMN_IN_INDEX
<b>SAP Sybase Error Number</b>	2059
<b>SQL State</b>	53W05
<b>SQL Code</b>	-127L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You may have attempted to delete or modify the definition of a column that is part of a primary or foreign key. You may have attempted to delete a column that has an index on it. In this case, DROP the index or key, perform the ALTER statement, and then add the index or key again.
<b>Warning 127</b>	<b>"Character substitution occurred when converting from %1 to %2"</b>
<b>Constant</b>	SIMPLE_SUBSTITUTION_WARNING
<b>SAP Sybase Error Number</b>	2542
<b>SQL State</b>	01WC3
<b>SQL Code</b>	127L
<b>ODBC 2 State</b>	01000
<b>ODBC 3 State</b>	01000
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	The character set of the input string.

<b>Warning 127</b>	<b>"Character substitution occurred when converting from %1 to %2"</b>
<b>Parameter 2</b>	The character set of the output string.
<b>Probable Cause</b>	While the server was performing character set conversion on an input string, some characters could not be represented in the database character set. Those characters were substituted. See on_charset_conversion_failure option.
<b>Error 128</b>	<b>"Cannot drop a user that owns tables in runtime system"</b>
<b>Constant</b>	USER_OWNS_TABLES
<b>SAP Sybase Error Number</b>	2060
<b>SQL State</b>	55W03
<b>SQL Code</b>	-128L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to drop a user that owns tables while running the runtime server. This operation would result in dropping tables. The runtime server cannot drop tables. Use the full server.

## Messages 129 through 140

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Warning 129</b>	<b>"Plan may contain virtual indexes"</b>
<b>Constant</b>	USING_VIRTUAL_INDEXES
<b>SAP Sybase Error Number</b>	2549
<b>SQL State</b>	01W20
<b>SQL Code</b>	129L
<b>ODBC 2 State</b>	01S01
<b>ODBC 3 State</b>	01S01
<b>Severity Code</b>	<i>10</i> on page 2

## Errors and Warnings

<b>Warning 129</b>	<b>"Plan may contain virtual indexes"</b>
<b>Probable Cause</b>	Virtual indexes are currently enabled in this connection. Any plans that are generated may contain virtual indexes.
<b>Warning 130</b>	<b>"A row was dropped because it could not be converted to the new schema format"</b>
<b>Constant</b>	ROW_DROPPED_DURING_SCHEMA_UPGRADE
<b>SAP Sybase Error Number</b>	2559
<b>SQL State</b>	01W21
<b>SQL Code</b>	130L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Probable Cause</b>	A row that was valid in the old schema is no longer valid. This could be because a column domain changed and the old value cannot be cast to the new domain. Rows are also dropped if a uniqueness or foreign key constraint cannot be satisfied.
<b>Error 130</b>	<b>"Invalid statement"</b>
<b>Constant</b>	INVALID_STATEMENT
<b>SAP Sybase Error Number</b>	2070
<b>SQL State</b>	07W02
<b>SQL Code</b>	-130L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The prepared statement is invalid. In embedded SQL, an OPEN or EXECUTE failed.
<b>Error 131</b>	<b>"Syntax error near '%1' %2"</b>
<b>Constant</b>	SYNTAX_ERROR

<b>Error 131</b>	"Syntax error near '%1' %2"
<b>SAP Sybase Error Number</b>	2071
<b>SQL State</b>	42W04
<b>SQL Code</b>	-131L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	The word or symbol where the syntax error has been detected.
<b>Parameter 2</b>	Line number.
<b>Probable Cause</b>	The database server cannot understand the statement you are trying to execute. If you used a keyword (such as DATE) for a column name, try enclosing the keyword in quotation marks ("DATE") or brackets ([DATE]).

<b>Error 132</b>	"SQL statement error"
<b>Constant</b>	STATEMENT_ERROR
<b>SAP Sybase Error Number</b>	2073
<b>SQL State</b>	26501
<b>SQL Code</b>	-132L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The prepared statement identifier is invalid. In embedded SQL, an OPEN or EXECUTE failed.

<b>Warning 132</b>	"Cannot output the histogram for string column '%1'"
<b>Constant</b>	CANNOT_DUMP_STRING_HISTOGRAM
<b>SAP Sybase Error Number</b>	2562
<b>SQL State</b>	01W23
<b>SQL Code</b>	132L

## Errors and Warnings

<b>Warning 132</b>	<b>"Cannot output the histogram for string column "%1"</b>
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	Name of the column containing string data.
<b>Probable Cause</b>	You tried to get the histogram for a column containing strings. Histograms on string information cannot be output in a readable format; as a result, no information was retrieved. Consider using the ESTIMATE function to get information on a specific value or range in the column.
<b>Error 133</b>	<b>"Invalid prepared statement type"</b>
<b>Constant</b>	INVALID_STATEMENT_TYPE
<b>SAP Sybase Error Number</b>	2074
<b>SQL State</b>	07W03
<b>SQL Code</b>	-133L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	This is an internal error. If it can be reproduced, it should be reported to SAP Sybase.
<b>Warning 133</b>	<b>"UltraLite connection was restored"</b>
<b>Constant</b>	CONNECTION_RESTORED
<b>SAP Sybase Error Number</b>	2635
<b>SQL State</b>	WW040
<b>SQL Code</b>	133L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Probable Cause</b>	The connection attempt completed successfully and the transaction was restored from a suspended state.

<b>Error 134</b>	<b>"Feature "%1' not implemented"</b>
<b>Constant</b>	NOT_IMPLEMENTED
<b>SAP Sybase Error Number</b>	2075
<b>SQL State</b>	0A000
<b>SQL Code</b>	-134L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The unimplemented feature.
<b>Probable Cause</b>	You attempted to carry out an operation or use a feature that is not implemented in this version of SQL Anywhere. In UltraLite, this error often occurs because you attempted to perform an unsupported operation on a LONG VARCHAR or LONG BINARY column. For example, the SUBSTRING function cannot be used with a LONG VARCHAR column. As well, an index cannot be created on a LONG column.

<b>Warning 134</b>	<b>"UltraLite cursor (or result set or table) was restored"</b>
<b>Constant</b>	CURSOR_RESTORED
<b>SAP Sybase Error Number</b>	2636
<b>SQL State</b>	WW041
<b>SQL Code</b>	134L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Probable Cause</b>	The cursor (or result set or table) was opened successfully and the cursor position was restored from the suspended state.

<b>Error 135</b>	<b>"Language extension"</b>
<b>Constant</b>	LANGUAGE_EXTENSION
<b>SAP Sybase Error Number</b>	2077

## Errors and Warnings

<b>Error 135</b>	<b>"Language extension"</b>
<b>SQL State</b>	0AW01
<b>SQL Code</b>	-135L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You used a SQL statement that may be valid in some versions of SQL, but not in SQL Anywhere.
<b>Error 136</b>	<b>"Table "%1' is in an outer join cycle"</b>
<b>Constant</b>	OUTER_JOIN_CYCLE
<b>SAP Sybase Error Number</b>	2088
<b>SQL State</b>	52W14
<b>SQL Code</b>	-136L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of a table in the cycle.
<b>Probable Cause</b>	You specified outer joins that create a cycle of tables.
<b>Warning 136</b>	<b>"The database was created"</b>
<b>Constant</b>	DATABASE_CREATED
<b>SAP Sybase Error Number</b>	2666
<b>SQL State</b>	WW061
<b>SQL Code</b>	136L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2

<b>Warning 136</b>	<b>"The database was created"</b>
<b>Probable Cause</b>	The specified UltraLite database was created using the specified schema when the connection was opened.
<b>Error 137</b>	<b>"Table "%1' requires a unique correlation name"</b>
<b>Constant</b>	CORRELATION_NAME_NEEDED
<b>SAP Sybase Error Number</b>	2090
<b>SQL State</b>	52W15
<b>SQL Code</b>	-137L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the table that needs a unique correlation name.
<b>Probable Cause</b>	You specified a join that joins a table to itself. You need to use unique correlation names to have multiple instances of a table.
<b>Warning 137</b>	<b>"Row was dropped from table %1 to maintain referential integrity"</b>
<b>Constant</b>	ROW_DELETED_TO_MAINTAIN_REFERENTIAL_INTEGRITY
<b>SAP Sybase Error Number</b>	2690
<b>SQL State</b>	01W24
<b>SQL Code</b>	137L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	The name of the table.
<b>Probable Cause</b>	A delete of a primary row during a download forced its foreign row(s) to also be deleted to maintain referential integrity.

## Errors and Warnings

<b>Error 138</b>	<b>"Dbspace '%1' not found"</b>
<b>Constant</b>	DBSPACE_NOT_FOUND
<b>SAP Sybase Error Number</b>	2078
<b>SQL State</b>	52W13
<b>SQL Code</b>	-138L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	Name of the dbspace that could not be found.
<b>Probable Cause</b>	You tried to access a dbspace that the database server could not find.
<b>Warning 138</b>	<b>"Publication predicates were not evaluated"</b>
<b>Constant</b>	PUBLICATION_PREDICATE_IGNORED
<b>SAP Sybase Error Number</b>	2761
<b>SQL State</b>	01W25
<b>SQL Code</b>	138L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Probable Cause</b>	Publication predicates were not evaluated because UltraLite was initialized without SQL support. The table will be uploaded as if no publication predicate was specified for the table.
<b>Error 139</b>	<b>"More than one table is identified as '%1'"</b>
<b>Constant</b>	CORRELATION_NAME_AMBIGUOUS
<b>SAP Sybase Error Number</b>	2079
<b>SQL State</b>	52012
<b>SQL Code</b>	-139L
<b>ODBC 2 State</b>	37000

<b>Error 139</b>	<b>"More than one table is identified as "%1"</b>
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Ambiguous correlation name.
<b>Probable Cause</b>	You identified two tables in the same FROM clause with the same correlation name.

<b>Warning 139</b>	<b>"Option '%1' specified more than once"</b>
<b>Constant</b>	DUPLICATE_OPTION
<b>SAP Sybase Error Number</b>	2770
<b>SQL State</b>	01W26
<b>SQL Code</b>	139L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	The name of the duplicated option.
<b>Probable Cause</b>	A particular option has been specified multiple times. Only the last instance of the option is used; the previous ones are ignored.

<b>Error 140</b>	<b>"User ID '%1' does not exist"</b>
<b>Constant</b>	UNKNOWN_USERID
<b>SAP Sybase Error Number</b>	2080
<b>SQL State</b>	08004
<b>SQL Code</b>	-140L
<b>ODBC 2 State</b>	28000
<b>ODBC 3 State</b>	28000
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	Name of the user that could not be found.
<b>Probable Cause</b>	You used a user ID that does not exist.

## Messages 140 through 150

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Warning 140</b>	"Encryption has not been enabled."
<b>Constant</b>	ENCRYPTION_NOT_ENABLED_WARNING
<b>SAP Sybase Error Number</b>	2817
<b>SQL State</b>	01005
<b>SQL Code</b>	140L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Probable Cause</b>	An encryption key was provided, but encryption has not been enabled, nor is the database encrypted.
<b>Error 141</b>	"Table '%1' not found"
<b>Constant</b>	TABLE_NOT_FOUND
<b>SAP Sybase Error Number</b>	2081
<b>SQL State</b>	42W33
<b>SQL Code</b>	-141L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	Name of the table that could not be found.
<b>Probable Cause</b>	You misspelled the name of a table, or you did not qualify a table name with the owner name. For example, you might have referred to "table_name" instead of "owner"."table_name".
<b>Error 142</b>	"Correlation name '%1' not found"
<b>Constant</b>	CORRELATION_NAME_NOT_FOUND
<b>SAP Sybase Error Number</b>	2082

<b>Error 142</b>	<b>"Correlation name '%1' not found"</b>
<b>SQL State</b>	52W02
<b>SQL Code</b>	-142L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the invalid correlation name.
<b>Probable Cause</b>	You misspelled a correlation name, or you used a table name instead of the correlation name.
<b>Warning 142</b>	<b>"UltraLite database state was restored"</b>
<b>Constant</b>	DATABASE_STATE RESTORED
<b>SAP Sybase Error Number</b>	2921
<b>SQL State</b>	WW114
<b>SQL Code</b>	142L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Probable Cause</b>	The database state was restored from the temporary file. This includes suspended connections, transactions, and cursors.
<b>Error 143</b>	<b>"Column '%1' not found"</b>
<b>Constant</b>	COLUMN_NOT_FOUND
<b>SAP Sybase Error Number</b>	2481
<b>SQL State</b>	52003
<b>SQL Code</b>	-143L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S22
<b>Severity Code</b>	<i>16</i> on page 2

## Errors and Warnings

<b>Error 143</b>	<b>"Column '%1' not found"</b>
<b>Parameter 1</b>	Name of the column that could not be found.
<b>Probable Cause</b>	You misspelled the name of a column, or the column you are looking for is in a different table.
<b>Warning 143</b>	<b>"Retrying read of corrupt page (page '%1')"</b>
<b>Constant</b>	CORRUPT_PAGE_READ_RETRY
<b>SAP Sybase Error Number</b>	2922
<b>SQL State</b>	WW115
<b>SQL Code</b>	143L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	The page ID.
<b>Probable Cause</b>	UltraLite detected a corrupt database page and will attempt the read operation again. If a mirror file is enabled, it is used for the retry. If the retry fails, an error will be signaled.
<b>Error 144</b>	<b>"Column '%1' found in more than one table or it is used more than once in the SELECT list -- it needs a correlation name"</b>
<b>Constant</b>	COLUMN_AMBIGUOUS
<b>SAP Sybase Error Number</b>	2084
<b>SQL State</b>	52002
<b>SQL Code</b>	-144L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the ambiguous column.

<b>Error 144</b>	<b>"Column '%1' found in more than one table or it is used more than once in the SELECT list -- it needs a correlation name"</b>
<b>Probable Cause</b>	You have not specified a correlation name on a column which is found in more than one of the tables referenced in a query block or which appears more than once in the SELECT list of a query block. You need to add a correlation name to the column.

<b>Warning 144</b>	<b>"Mirror file requires higher checksum_level"</b>
<b>Constant</b>	MIRROR_FILE_REQUIRES_CHECKSUMS
<b>SAP Sybase Error Number</b>	2923
<b>SQL State</b>	WW116
<b>SQL Code</b>	144L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Probable Cause</b>	To effectively protect against media failures, page checksums must be enabled when using the mirror file. Specify the checksum_level database creation option.

<b>Error 145</b>	<b>"Foreign key name '%1' not found"</b>
<b>Constant</b>	FOREIGN_KEY_NAME_NOT_FOUND
<b>SAP Sybase Error Number</b>	2085
<b>SQL State</b>	52W07
<b>SQL Code</b>	-145L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	Name of the non-existing foreign key.
<b>Probable Cause</b>	You misspelled the name of a foreign key, or the foreign key does not exist.

## Errors and Warnings

<b>Warning 145</b>	<b>"Two rows with the same primary key have been downloaded for table "%1"</b>
<b>Constant</b>	DUPLICATE_ROW_FOUND_IN_DOWNLOAD
<b>SAP Sybase Error Number</b>	2943
<b>SQL State</b>	01W27
<b>SQL Code</b>	145L
<b>ODBC 2 State</b>	01000
<b>ODBC 3 State</b>	01000
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	Name of the table being downloaded.
<b>Probable Cause</b>	The synchronization scripts are producing duplicate rows with the same primary key in your download. Generally this behavior indicates a problem with the synchronization scripts. No guarantees are made about which of the downloaded rows will be applied to the database.

<b>Error 146</b>	<b>"There is no way to join "%1' to "%2"</b>
<b>Constant</b>	CANNOT_JOIN
<b>SAP Sybase Error Number</b>	2086
<b>SQL State</b>	53W04
<b>SQL Code</b>	-146L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of first table that cannot be joined.
<b>Parameter 2</b>	Name of second table that cannot be joined.
<b>Probable Cause</b>	You may have attempted a KEY JOIN between two tables and there is no foreign key on one of the tables that references the primary key of the other table. You may have attempted a NATURAL JOIN between two tables that have no common column names.

<b>Warning 146</b>	<b>"Event notification queue "%1' is full, notification discarded"</b>
<b>Constant</b>	EVENT_NOTIFICATION_QUEUE_FULL
<b>SAP Sybase Error Number</b>	2947
<b>SQL State</b>	WE011
<b>SQL Code</b>	146L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	The name of the event notification queue.
<b>Probable Cause</b>	The named queue is full and will not receive any event notifications until notifications are read from the queue. The pending notification has been discarded.
<b>Error 147</b>	<b>"There is more than one way to join "%1' to "%2'"</b>
<b>Constant</b>	AMBIGUOUS_JOIN
<b>SAP Sybase Error Number</b>	2087
<b>SQL State</b>	52W08
<b>SQL Code</b>	-147L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of first table that cannot be joined.
<b>Parameter 2</b>	Name of second table that cannot be joined.
<b>Probable Cause</b>	You are attempting to KEY JOIN two tables, and there are two or more foreign keys relating the two tables. There may be two foreign keys from the first table to the second table. It may be that each table has a foreign key to the other table. You must use a correlation name for the primary key table that is the same as the role name of the desired foreign key relationship.

## Errors and Warnings

<b>Warning 147</b>	<b>"Event notifications lost on queue "%1"</b>
<b>Constant</b>	EVENT_NOTIFICATIONS_LOST
<b>SAP Sybase Error Number</b>	2948
<b>SQL State</b>	WE012
<b>SQL Code</b>	147L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	The name of the event notification queue.
<b>Probable Cause</b>	Event notifications have been lost on the named queue. This behavior occurs if there are pending notifications when the queue is destroyed. The notifications are discarded.

<b>Error 148</b>	<b>"Unknown function "%1"</b>
<b>Constant</b>	UNKNOWN_FUNC
<b>SAP Sybase Error Number</b>	2091
<b>SQL State</b>	42W05
<b>SQL Code</b>	-148L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	Function name that is not a database function.
<b>Probable Cause</b>	You misspelled the name of a database function (such as MAXIMUM instead of MAX) in a query definition or in a query column name.

<b>Warning 148</b>	<b>"Event notification queue "%1' not found warning"</b>
<b>Constant</b>	EVENT_NOTIFICATION_QUEUE_NOT_FOUND_WARN
<b>SAP Sybase Error Number</b>	2949
<b>SQL State</b>	WE013
<b>SQL Code</b>	148L

<b>Warning 148</b>	<b>"Event notification queue "%1' not found warning"</b>
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	The name of the event notification queue.
<b>Probable Cause</b>	The named event notification queue was not found. The operation will be skipped.
<b>Error 149</b>	<b>"Function or column reference to "%1' must also appear in a GROUP BY"</b>
<b>Constant</b>	INVALID_GROUP_SELECT
<b>SAP Sybase Error Number</b>	2092
<b>SQL State</b>	53003
<b>SQL Code</b>	-149L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	Name of the column referenced directly, or in an expression, that must be in the GROUP BY clause.
<b>Probable Cause</b>	You used a non-aggregate function or column reference in the SELECT list or in a nested query block that does not appear in the GROUP BY clause. In a query using GROUP BY, SELECT list items that are not aggregate functions must also appear in the GROUP BY clause. If the SELECT list item is a column reference or an alias, you may add the column name or alias to the GROUP BY clause. If the SELECT list item is a scalar function, ensure that the function's arguments in the GROUP BY clause match exactly with those in the SELECT list. You may be able to use the MAX function (or another aggregate function) on the column name instead of adding the column to the GROUP BY clause.
<b>Warning 149</b>	<b>"Automatic database upgrade applied"</b>
<b>Constant</b>	DATABASE_UPGRADE_WARNING
<b>SAP Sybase Error Number</b>	2972

## Errors and Warnings

<b>Warning 149</b>	<b>"Automatic database upgrade applied"</b>
<b>SQL State</b>	WW234
<b>SQL Code</b>	149L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Probable Cause</b>	The database is from an older version of the software. An automatic database upgrade occurs during startup. Subsequently the database can no longer be opened with the older version of the software.
<b>Error 150</b>	<b>"Invalid use of an aggregate function"</b>
<b>Constant</b>	AGGREGATES_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	2093
<b>SQL State</b>	42W06
<b>SQL Code</b>	-150L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You attempted to use an aggregate function inappropriately. For example, a SELECT statement cannot contain an aggregate function within a predicate in the WHERE clause unless the aggregate function constitutes an outer reference. Other invalid uses include specifying an aggregate function in the SET clause of an UPDATE statement, or using an aggregate function in a CHECK constraint.
<b>Warning 150</b>	<b>"Database contains no tables to synchronize"</b>
<b>Constant</b>	NO_TABLES_TO_SYNCHRONIZE
<b>SAP Sybase Error Number</b>	3173
<b>SQL State</b>	01W28
<b>SQL Code</b>	150L
<b>ODBC 2 State</b>	OK

<b>Warning 150</b>	"Database contains no tables to synchronize"
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Probable Cause</b>	The database has no tables to synchronize. No attempt was made to contact the MobiLink server.

## Messages 151 through 180

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 151</b>	"Subquery allowed only one SELECT list item"
<b>Constant</b>	SUBQUERY_SELECT_LIST
<b>SAP Sybase Error Number</b>	2094
<b>SQL State</b>	53023
<b>SQL Code</b>	-151L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You entered a subquery that has more than one column in the SELECT list. Change the SELECT list to have only one column.

<b>Warning 151</b>	"UltraLite performed database recovery on startup"
<b>Constant</b>	DATABASE_RECOVERED
<b>SAP Sybase Error Number</b>	3357
<b>SQL State</b>	WW247
<b>SQL Code</b>	151L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2

## Errors and Warnings

<b>Warning 151</b>	<b>"UltraLite performed database recovery on startup"</b>
<b>Probable Cause</b>	The database file was not shut down cleanly. Any uncommitted rows have been rolled back. This indicates that not all connections were closed when the application terminated.
<b>Error 152</b>	<b>"Invalid ORDER BY specification"</b>
<b>Constant</b>	INVALID_ORDER
<b>SAP Sybase Error Number</b>	2095
<b>SQL State</b>	53005
<b>SQL Code</b>	-152L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	Either you used an integer in an ORDER BY list and the integer is larger than the number of columns in the SELECT list, or you specified an ORDER BY expression that is semantically invalid. For example, for UNION, EXCEPT, and INTERSECT queries you can only use integers or column names of the first SELECT query block to specify an ordering of the result.
<b>Error 153</b>	<b>"Select lists in UNION, INTERSECT, or EXCEPT do not match in length"</b>
<b>Constant</b>	INVALID_UNION
<b>SAP Sybase Error Number</b>	2096
<b>SQL State</b>	53026
<b>SQL Code</b>	-153L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You specified a UNION, INTERSECT, or EXCEPT, but the SELECT statements involved in the operation do not have the same number of columns in the SELECT list.

<b>Error 154</b>	<b>"Wrong number of parameters to function "%1"</b>
<b>Constant</b>	WRONG_PARAMETER_COUNT
<b>SAP Sybase Error Number</b>	2100
<b>SQL State</b>	37505
<b>SQL Code</b>	-154L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	Name of the function.
<b>Probable Cause</b>	You supplied an incorrect number of parameters to a database function.
<b>Error 155</b>	<b>"Invalid host variable"</b>
<b>Constant</b>	VARIABLE_INVALID
<b>SAP Sybase Error Number</b>	2102
<b>SQL State</b>	42W07
<b>SQL Code</b>	-155L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>17</i> on page 2
<b>Probable Cause</b>	You supplied an invalid host variable to the database using the C language interface. You may have supplied the variable as a host variable or through a SQLDA.
<b>Error 156</b>	<b>"Invalid expression near "%1"</b>
<b>Constant</b>	EXPRESSION_ERROR
<b>SAP Sybase Error Number</b>	2103
<b>SQL State</b>	42W08
<b>SQL Code</b>	-156L
<b>ODBC 2 State</b>	37000

## Errors and Warnings

<b>Error 156</b>	<b>"Invalid expression near "%1"</b>
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The invalid expression.
<b>Probable Cause</b>	You supplied an expression that the database server cannot understand. For example, you may have tried to add two dates.
<b>Error 157</b>	<b>"Cannot convert %1 to a %2"</b>
<b>Constant</b>	CONVERSION_ERROR
<b>SAP Sybase Error Number</b>	2104
<b>SQL State</b>	53018
<b>SQL Code</b>	-157L
<b>ODBC 2 State</b>	07006
<b>ODBC 3 State</b>	07006
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The value that could not be converted.
<b>Parameter 2</b>	The name of the type for the conversion.
<b>Probable Cause</b>	An error occurred while trying to convert a value to another data type.
<b>Error 158</b>	<b>"Value %1 out of range for destination"</b>
<b>Constant</b>	OVERFLOW_ERROR
<b>SAP Sybase Error Number</b>	2105
<b>SQL State</b>	22003
<b>SQL Code</b>	-158L
<b>ODBC 2 State</b>	22003
<b>ODBC 3 State</b>	22003
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The value that caused the overflow.

<b>Error 158</b>	<b>"Value %1 out of range for destination"</b>
<b>Probable Cause</b>	You supplied to or fetched from the database a value that is out of range for the destination column or host variable. For example, the value 10 may have been supplied for a DECIMAL(3,2) field.
<b>Error 159</b>	<b>"Invalid column number"</b>
<b>Constant</b>	INVALID_COLUMN_NUMBER
<b>SAP Sybase Error Number</b>	2106
<b>SQL State</b>	42W13
<b>SQL Code</b>	-159L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You gave an invalid column number, or the column you are looking for is in a different table.
<b>Error 160</b>	<b>"Can only describe a SELECT statement"</b>
<b>Constant</b>	DESCRIBE_NONSELECT
<b>SAP Sybase Error Number</b>	2107
<b>SQL State</b>	07005
<b>SQL Code</b>	-160L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	In the C language interface, you attempted to describe the SELECT list of a statement other than a SELECT statement. In UltraLite this error can result from trying to retrieve the schema of any statement other than a SELECT.
<b>Error 161</b>	<b>"Invalid type on DESCRIBE statement"</b>
<b>Constant</b>	INVALID_DESCRIBE_TYPE

## Errors and Warnings

<b>Error 161</b>	<b>"Invalid type on DESCRIBE statement"</b>
<b>SAP Sybase Error Number</b>	2108
<b>SQL State</b>	07W01
<b>SQL Code</b>	-161L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A Java type specified on a DESCRIBE statement has no corresponding SQL type.
<b>Error 162</b>	<b>"Cannot convert %1 to a %2. The bad value was supplied for column '%3' on row %4 of the data file"</b>
<b>Constant</b>	CONVERSION_ERROR_LOAD_TABLE
<b>SAP Sybase Error Number</b>	2533
<b>SQL State</b>	53017
<b>SQL Code</b>	-162L
<b>ODBC 2 State</b>	07006
<b>ODBC 3 State</b>	07006
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Value that could not be converted.
<b>Parameter 2</b>	Destination data type.
<b>Parameter 3</b>	Name of the column where the value was to be inserted.
<b>Parameter 4</b>	Line number of the data file where the invalid data occurred.
<b>Probable Cause</b>	The data file supplied to LOAD TABLE contains a value that cannot be converted to the required data type.
<b>Error 163</b>	<b>"Derived table "%1' has no name for column %2"</b>
<b>Constant</b>	NO_COLUMN_NAME
<b>SAP Sybase Error Number</b>	2302
<b>SQL State</b>	52004

<b>Error 163</b>	<b>"Derived table "%1' has no name for column %2"</b>
<b>SQL Code</b>	-163L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the derived table.
<b>Parameter 2</b>	Number of the column for which there is no name.
<b>Probable Cause</b>	The specified column of the derived table has no column name. Use a SELECT list alias in the query specification or use a derived columns specifier.
<b>Error 164</b>	<b>"Namespace heap exhausted at internal function: %1"</b>
<b>Constant</b>	NAMESPACE_HEAP_EXHAUSTED
<b>SAP Sybase Error Number</b>	2310
<b>SQL State</b>	WP007
<b>SQL Code</b>	-164L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The internal function is for debugging purposes.
<b>Probable Cause</b>	The amount of space allocated for the Java Namespace is insufficient to continue loading Java classes. Increase the size by using: SET OPTION PUBLIC.java_namespace_size = nnnnnnnn.
<b>Error 165</b>	<b>"Java VM heap exhausted at internal function: %1"</b>
<b>Constant</b>	JAVA_VM_HEAP_EXHAUSTED
<b>SAP Sybase Error Number</b>	2311
<b>SQL State</b>	WP008
<b>SQL Code</b>	-165L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 165</b>	<b>"Java VM heap exhausted at internal function: %1"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The internal function is for debugging purposes.
<b>Probable Cause</b>	The amount of space allocated for the Java VM is insufficient to continue allocating new objects. Increase the size by using: SET OPTION PUBLIC.java_heap_size = nnnnnnnn.
<b>Error 170</b>	<b>"Cursor has not been declared"</b>
<b>Constant</b>	CURSOR_NOT_DECLARED
<b>SAP Sybase Error Number</b>	2109
<b>SQL State</b>	24W01
<b>SQL Code</b>	-170L
<b>ODBC 2 State</b>	24000
<b>ODBC 3 State</b>	24000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to OPEN a cursor that has not been declared.
<b>Error 171</b>	<b>"Error opening cursor"</b>
<b>Constant</b>	OPEN_CURSOR_ERROR
<b>SAP Sybase Error Number</b>	2110
<b>SQL State</b>	07003
<b>SQL Code</b>	-171L
<b>ODBC 2 State</b>	24000
<b>ODBC 3 State</b>	24000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You attempted to open a cursor on a statement that is not SELECT, CALL or EXEC.

<b>Error 172</b>	<b>"Cursor already open"</b>
<b>Constant</b>	CURSOR_ALREADY_OPEN
<b>SAP Sybase Error Number</b>	2111
<b>SQL State</b>	24502
<b>SQL Code</b>	-172L
<b>ODBC 2 State</b>	24000
<b>ODBC 3 State</b>	24000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to OPEN a cursor that is already open.

<b>Error 180</b>	<b>"Cursor not open"</b>
<b>Constant</b>	CURSOR_NOT_OPEN
<b>SAP Sybase Error Number</b>	2112
<b>SQL State</b>	24501
<b>SQL Code</b>	-180L
<b>ODBC 2 State</b>	34000
<b>ODBC 3 State</b>	34000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to use a cursor that has not been opened.

## Messages 181 through 200

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 181</b>	<b>"No indicator variable provided for NULL result"</b>
<b>Constant</b>	NO_INDICATOR
<b>SAP Sybase Error Number</b>	2113
<b>SQL State</b>	22002
<b>SQL Code</b>	-181L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 181</b>	<b>"No indicator variable provided for NULL result"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You tried to retrieve a value from the database that was NULL, but you did not provide an indicator variable for that value.
<b>Error 182</b>	<b>"Not enough fields allocated in SQLDA"</b>
<b>Constant</b>	SQLDA_TOO_SMALL
<b>SAP Sybase Error Number</b>	2114
<b>SQL State</b>	07002
<b>SQL Code</b>	-182L
<b>ODBC 2 State</b>	07001
<b>ODBC 3 State</b>	07002
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	There are not enough fields in the SQLDA to retrieve all of the values requested.
<b>Error 183</b>	<b>"Cannot find index named "%1"</b>
<b>Constant</b>	INDEX_NOT_FOUND
<b>SAP Sybase Error Number</b>	2063
<b>SQL State</b>	52W03
<b>SQL Code</b>	-183L
<b>ODBC 2 State</b>	S0012
<b>ODBC 3 State</b>	42S12
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the index that cannot be found.
<b>Probable Cause</b>	You attempted to perform an operation using an index that does not exist. Check for spelling errors. Check whether the index name must be qualified with a user ID.

<b>Error 184</b>	<b>"Column '%1' in table '%2' cannot be NULL. The invalid data was supplied to LOAD TABLE in a data file on line %3"</b>
<b>Constant</b>	COLUMN_CANNOT_BE_NULL_LOAD_TABLE
<b>SAP Sybase Error Number</b>	2531
<b>SQL State</b>	23501
<b>SQL Code</b>	-184L
<b>ODBC 2 State</b>	23000
<b>ODBC 3 State</b>	23000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the column that cannot be NULL.
<b>Parameter 2</b>	Name of the table containing the column.
<b>Parameter 3</b>	The line number of the data file containing the invalid data.
<b>Probable Cause</b>	You either have not supplied a value where a value is required or a data conversion was necessary that resulted in a NULL value. The column definition prohibits NULL values or the column is part of a NOT NULL foreign key.

<b>Error 185</b>	<b>"SELECT returns more than one row"</b>
<b>Constant</b>	TOO_MANY_RECORDS
<b>SAP Sybase Error Number</b>	2116
<b>SQL State</b>	21000
<b>SQL Code</b>	-185L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You tried to use a SELECT statement without a cursor, but the statement cursor returns more than one row. Only a single row SELECT statement can be used in this context.

## Errors and Warnings

<b>Error 186</b>	<b>"Subquery cannot return more than one row"</b>
<b>Constant</b>	SUBQUERY_RESULT_NOT_UNIQUE
<b>SAP Sybase Error Number</b>	2117
<b>SQL State</b>	21W01
<b>SQL Code</b>	-186L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You used a subquery that returns more than one row, in a context where only a single row can be used. If the subquery is in the WHERE clause, you might be able to use the IN keyword.
<b>Error 187</b>	<b>"Illegal cursor operation attempt"</b>
<b>Constant</b>	CURSOROP_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	2118
<b>SQL State</b>	09W02
<b>SQL Code</b>	-187L
<b>ODBC 2 State</b>	07005
<b>ODBC 3 State</b>	07005
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted an illegal cursor operation. For example, you may be attempting to OPEN a cursor for a statement that is neither a SELECT nor a BATCH.
<b>Error 188</b>	<b>"Not enough values for host variables"</b>
<b>Constant</b>	NOT_ENOUGH_HOST_VARS
<b>SAP Sybase Error Number</b>	2119
<b>SQL State</b>	07001
<b>SQL Code</b>	-188L
<b>ODBC 2 State</b>	07002

<b>Error 188</b>	<b>"Not enough values for host variables"</b>
<b>ODBC 3 State</b>	07002
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You have not provided enough host variables for either the number of bind variables, or the statement, or the number of SELECT list items.
<b>Error 189</b>	<b>"Unable to find in index "%1' for table "%2"</b>
<b>Constant</b>	NOT_FOUND_IN_INDEX
<b>SAP Sybase Error Number</b>	2120
<b>SQL State</b>	WI005
<b>SQL Code</b>	-189L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	Name of invalid index.
<b>Parameter 2</b>	Name of table containing the invalid index.
<b>Probable Cause</b>	This is an internal error. If it can be reproduced, it should be reported to SAP Sybase. You should be able to work around the error by dropping and recreating the index.
<b>Error 190</b>	<b>"Cannot update an expression"</b>
<b>Constant</b>	NON_UPDATEABLE_COLUMN
<b>SAP Sybase Error Number</b>	2121
<b>SQL State</b>	53W02
<b>SQL Code</b>	-190L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	You tried to update a column in a query that is a database expression rather than a column in a table.

## Errors and Warnings

<b>Error 191</b>	<b>"Cannot modify column '%1' in table '%2'"</b>
<b>Constant</b>	CANNOT_MODIFY
<b>SAP Sybase Error Number</b>	2122
<b>SQL State</b>	42W32
<b>SQL Code</b>	-191L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Name of the column that cannot be changed.
<b>Parameter 2</b>	Name of the table containing the column.
<b>Probable Cause</b>	You may have tried to modify a column that you do not have permission to modify. You may have tried to modify a column defined as an expression (such as column1+column2) in a view.
<b>Error 192</b>	<b>"Update operation attempted on non-updatable query"</b>
<b>Constant</b>	NON_UPDATEABLE_VIEW
<b>SAP Sybase Error Number</b>	2123
<b>SQL State</b>	42W31
<b>SQL Code</b>	-192L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You attempted an insert, update, or delete operation on a query that is implicitly read-only. Queries that contain DISTINCT, GROUP BY, HAVING, EXCEPT, INTERSECT or UNION, or that contain aggregate functions, or that involve a join, are implicitly read-only. If the query references a view then the view may be non-updatable.
<b>Error 193</b>	<b>"Primary key for table '%1' is not unique: Primary key value ('%2')"</b>
<b>Constant</b>	PRIMARY_KEY_NOT_UNIQUE

<b>Error 193</b>	<b>"Primary key for table "%1' is not unique: Primary key value ('%2')"</b>
<b>SAP Sybase Error Number</b>	2124
<b>SQL State</b>	23W01
<b>SQL Code</b>	-193L
<b>ODBC 2 State</b>	23000
<b>ODBC 3 State</b>	23000
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Name of the table where the problem was detected.
<b>Parameter 2</b>	Duplicate primary key values that caused the error.
<b>Probable Cause</b>	You attempted to add a new row to a table, but the new row has the same primary key as an existing row. The database has not added the incorrect row to the database. For example, you might have added a student with student number 86004 and there is already a row for a student with that number.

<b>Error 194</b>	<b>"No primary key value for foreign key "%1' in table "%2"</b>
<b>Constant</b>	INVALID_FOREIGN_KEY
<b>SAP Sybase Error Number</b>	2125
<b>SQL State</b>	23503
<b>SQL Code</b>	-194L
<b>ODBC 2 State</b>	23000
<b>ODBC 3 State</b>	23000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the foreign key.
<b>Parameter 2</b>	Name of the table with the foreign key.
<b>Probable Cause</b>	You attempted to insert or update a row that has a foreign key for another table. The value for the foreign key is not NULL and there is not a corresponding value in the primary key.

<b>Error 195</b>	<b>"Column "%1' in table "%2' cannot be NULL"</b>
<b>Constant</b>	COLUMN_CANNOT_BE_NULL

## Errors and Warnings

<b>Error 195</b>	<b>"Column '%1' in table '%2' cannot be NULL"</b>
<b>SAP Sybase Error Number</b>	2126
<b>SQL State</b>	23502
<b>SQL Code</b>	-195L
<b>ODBC 2 State</b>	23000
<b>ODBC 3 State</b>	23000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the column that cannot be NULL.
<b>Parameter 2</b>	Name of the table containing the column.
<b>Probable Cause</b>	You have not supplied a value where a value is required. The column definition prohibits NULL values or the column is part of a NOT NULL foreign key.
<b>Error 196</b>	<b>"Index '%1' for table '%2' would not be unique"</b>
<b>Constant</b>	INDEX_NOT_UNIQUE
<b>SAP Sybase Error Number</b>	2127
<b>SQL State</b>	23505
<b>SQL Code</b>	-196L
<b>ODBC 2 State</b>	23000
<b>ODBC 3 State</b>	23000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the index that would not be unique.
<b>Parameter 2</b>	Name of the table that contains the index.
<b>Probable Cause</b>	You attempted to insert or update a row that has the same value as another row in some column, and there is a constraint that does not allow two rows to have the same value in that column.
<b>Error 197</b>	<b>"No current row of cursor"</b>
<b>Constant</b>	NO_CURRENT_ROW

<b>Error 197</b>	<b>"No current row of cursor"</b>
<b>SAP Sybase Error Number</b>	2128
<b>SQL State</b>	24503
<b>SQL Code</b>	-197L
<b>ODBC 2 State</b>	24000
<b>ODBC 3 State</b>	24000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to perform an operation on the current row of a cursor, but the cursor is not positioned on a row. The cursor is before the first row of the cursor, after the last row, or is on a row that has since been deleted.
<b>Error 198</b>	<b>"Primary key for row in table '%1' is referenced by foreign key '%2' in table '%3'"</b>
<b>Constant</b>	PRIMARY_KEY_VALUE_REF
<b>SAP Sybase Error Number</b>	2129
<b>SQL State</b>	23W05
<b>SQL Code</b>	-198L
<b>ODBC 2 State</b>	23000
<b>ODBC 3 State</b>	23000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the table containing the row being modified.
<b>Parameter 2</b>	The name of the foreign index (or role) of the referencing table.
<b>Parameter 3</b>	The name of the foreign table referencing the primary row.
<b>Probable Cause</b>	You attempted to delete or modify a row whose primary key value is referenced elsewhere in the database.
<b>Error 199</b>	<b>"INSERT/DELETE on cursor can modify only one table"</b>
<b>Constant</b>	ONLY_ONE_TABLE

## Errors and Warnings

<b>Error 199</b>	" <b>INSERT/DELETE on cursor can modify only one table</b> "
<b>SAP Sybase Error Number</b>	2130
<b>SQL State</b>	09W04
<b>SQL Code</b>	-199L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You attempted to insert into a cursor and have specified values for more than one table, or you attempted to delete from a cursor that involves a join. Insert into one table at a time. For DELETE, use the FROM clause to specify the table you want to delete from.
<b>Warning 200</b>	" <b>Warning: %1</b> "
<b>Constant</b>	WARNING
<b>SAP Sybase Error Number</b>	2009
<b>SQL State</b>	01000
<b>SQL Code</b>	200L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	Warning message.
<b>Probable Cause</b>	A warning has occurred. The message indicates the condition that caused the warning.

## Messages 200 through 218

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 200</b>	" <b>Invalid option "%1' -- no PUBLIC setting exists</b> "
<b>Constant</b>	INVALID_OPTION
<b>SAP Sybase Error Number</b>	2167

<b>Error 200</b>	<b>"Invalid option '%1' -- no PUBLIC setting exists"</b>
<b>SQL State</b>	42W16
<b>SQL Code</b>	-200L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	Name of the invalid option.
<b>Probable Cause</b>	You may have misspelled the name of an option in the SET OPTION statement. You can only define an option for a user if the database administrator has supplied a PUBLIC value for that option.
<b>Error 201</b>	<b>"Invalid setting for option '%1'"</b>
<b>Constant</b>	INVALID_OPTION_SETTING
<b>SAP Sybase Error Number</b>	2168
<b>SQL State</b>	42W17
<b>SQL Code</b>	-201L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the invalid option.
<b>Probable Cause</b>	You supplied an invalid value for an option in the SET statement. Some options allow only numeric values, while other options allow only the values On and Off.
<b>Warning 201</b>	<b>"The ICU collation '%1' has defaulted to another collation"</b>
<b>Constant</b>	COLLATION_DEFAULT_WARNING
<b>SAP Sybase Error Number</b>	2788
<b>SQL State</b>	01WC4
<b>SQL Code</b>	201L
<b>ODBC 2 State</b>	01000

## Errors and Warnings

<b>Warning 201</b>	<b>"The ICU collation "%1' has defaulted to another collation"</b>
<b>ODBC 3 State</b>	01000
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	The ICU collation specifier.
<b>Probable Cause</b>	The specified ICU collation is not available. Another collation was substituted, which may or may not produce suitable results. Due to the structure of ICU, the collation that was used is not known, but was the best alternative to the specified collation. If this database is used on another platform, a different collation may be chosen and the operation may generate different results.
<b>Error 202</b>	<b>"Only PUBLIC settings are allowed for option "%1"</b>
<b>Constant</b>	NOT_PUBLIC_ID
<b>SAP Sybase Error Number</b>	2251
<b>SQL State</b>	42W43
<b>SQL Code</b>	-202L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the option.
<b>Probable Cause</b>	The option specified in the SET OPTION statement is PUBLIC only. You cannot define this option for any other user.
<b>Error 203</b>	<b>"Cannot set a temporary option for user "%1"</b>
<b>Constant</b>	TEMPORARY_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	2254
<b>SQL State</b>	42W45
<b>SQL Code</b>	-203L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000

<b>Error 203</b>	<b>"Cannot set a temporary option for user "%1"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	User ID whose option was to be changed.
<b>Probable Cause</b>	TEMPORARY options are set on a connection basis, and only for specific options known to the database server. To change an option for another user, do not specify TEMPORARY in the SET OPTION statement.
<b>Error 204</b>	<b>"You do not have '%1' system privilege or authority to set the option '%2'"</b>
<b>Constant</b>	OPTION_REQUIRES_DBA
<b>SAP Sybase Error Number</b>	2256
<b>SQL State</b>	42W46
<b>SQL Code</b>	-204L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Name of the system privilege or authority required to set the option.
<b>Parameter 2</b>	Name of the option that could not be set.
<b>Probable Cause</b>	The option specified in the SET OPTION statement can only be set by a user with DBA authority or by a user with SET ANY SYSTEM OPTION / SET ANY SECURITY OPTION / SET ANY PUBLIC OPTION depending on the option.
<b>Error 205</b>	<b>"Integrated logins are not permitted"</b>
<b>Constant</b>	INVALID_STANDARD_LOGON
<b>SAP Sybase Error Number</b>	2257
<b>SQL State</b>	28W02
<b>SQL Code</b>	-205L
<b>ODBC 2 State</b>	28000
<b>ODBC 3 State</b>	28000

## Errors and Warnings

<b>Error 205</b>	<b>"Integrated logins are not permitted"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The login_mode database option is set to Standard, and you attempted an integrated login. Change the option setting or supply an explicit user ID.
<b>Error 206</b>	<b>"Integrated logins are required, standard logins are not permitted"</b>
<b>Constant</b>	INVALID_INTEGRATED_LOGON
<b>SAP Sybase Error Number</b>	2258
<b>SQL State</b>	28W03
<b>SQL Code</b>	-206L
<b>ODBC 2 State</b>	28000
<b>ODBC 3 State</b>	28000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The login_mode database option is set to Integrated, and you attempted a standard login. Change the option setting or use an integrated login.
<b>Error 207</b>	<b>"Wrong number of values for INSERT"</b>
<b>Constant</b>	WRONG_NUM_OF_INSERT_COLS
<b>SAP Sybase Error Number</b>	2133
<b>SQL State</b>	53002
<b>SQL Code</b>	-207L
<b>ODBC 2 State</b>	21S01
<b>ODBC 3 State</b>	21S01
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The number of values you are trying to insert does not match the number of columns specified in the INSERT statement, or the number of columns in the table if no columns are specified.

<b>Error 208</b>	<b>"Row has changed since last read -- operation canceled"</b>
<b>Constant</b>	ROW_UPDATED_SINCE_READ
<b>SAP Sybase Error Number</b>	2132
<b>SQL State</b>	22W02
<b>SQL Code</b>	-208L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted an UPDATE (positioned) or DELETE (positioned) operation on a cursor declared as a SCROLL cursor, and the row you are changing has been updated since you read it. This error prevents the lost update problem.
<b>Error 209</b>	<b>"Constraint '%1' violated: Invalid value for column '%2' in table '%3'"</b>
<b>Constant</b>	INVALID_COLUMN_VALUE
<b>SAP Sybase Error Number</b>	2131
<b>SQL State</b>	23506
<b>SQL Code</b>	-209L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	23000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the constraint (if defined) that was violated by an invalid value.
<b>Parameter 2</b>	Name of the column that was assigned an invalid value.
<b>Parameter 3</b>	Name of the table containing the column.
<b>Probable Cause</b>	You attempted an insert or update that violates a CHECK constraint. A CHECK constraint is violated if it evaluates to FALSE; it is deemed to hold if the condition evaluates to TRUE or UNKNOWN.

## Errors and Warnings

<b>Error 210</b>	<b>"User '%1' has the row in '%2' locked"</b>
<b>Constant</b>	LOCKED
<b>SAP Sybase Error Number</b>	2169
<b>SQL State</b>	42W18
<b>SQL Code</b>	-210L
<b>ODBC 2 State</b>	40001
<b>ODBC 3 State</b>	40001
<b>Severity Code</b>	<i>21</i> on page 2
<b>Parameter 1</b>	Name of another user.
<b>Parameter 2</b>	Table that generates the error.
<b>Probable Cause</b>	The operation failed because another connection holds a lock on the same object you are attempting to modify. With INSERT, UPDATE, DELETE, SELECT, or MERGE statements this error is typically caused by attempting to read or write a row that is locked by another user, while the database option 'blocking' is set to Off. With data definition statements, including CREATE, DROP, GRANT, REVOKE, REFRESH, or ALTER, this error can be generated when the connection executing the DDL statement is unable to obtain an exclusive lock on the object to be modified (table, view, materialized view, or index) so that the operation can proceed.

<b>Error 211</b>	<b>"Not allowed while '%1' is using the database"</b>
<b>Constant</b>	MUST_BE_ONLY_CONNECTION
<b>SAP Sybase Error Number</b>	2170
<b>SQL State</b>	42W19
<b>SQL Code</b>	-211L
<b>ODBC 2 State</b>	40001
<b>ODBC 3 State</b>	40001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the connection that is using the database.
<b>Probable Cause</b>	You attempted a data definition language operation that cannot be completed while another user is connected.

<b>Error 212</b>	<b>"CHECKPOINT statement requires a rollback log"</b>
<b>Constant</b>	CHECKPOINT_REQUIRES_UNDO
<b>SAP Sybase Error Number</b>	2171
<b>SQL State</b>	42W20
<b>SQL Code</b>	-212L
<b>ODBC 2 State</b>	40001
<b>ODBC 3 State</b>	40001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You cannot use a CHECKPOINT statement when the database server is running in bulk mode without a rollback log.
<b>Error 213</b>	<b>"Savepoints require a rollback log"</b>
<b>Constant</b>	SAVEPOINTS_REQUIRE_UNDO
<b>SAP Sybase Error Number</b>	2177
<b>SQL State</b>	3BW01
<b>SQL Code</b>	-213L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You cannot use savepoints when the database server is running in bulk mode without a rollback log.
<b>Error 214</b>	<b>"Table in use"</b>
<b>Constant</b>	TABLE_IN_USE
<b>SAP Sybase Error Number</b>	2172
<b>SQL State</b>	42W21
<b>SQL Code</b>	-214L
<b>ODBC 2 State</b>	40001
<b>ODBC 3 State</b>	40001

## Errors and Warnings

<b>Error 214</b>	<b>"Table in use"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to ALTER or DROP a table that is being used by other active users of the database.
<b>Error 215</b>	<b>"Procedure in use by "%1"</b>
<b>Constant</b>	PROCEDURE_IN_USE
<b>SAP Sybase Error Number</b>	2173
<b>SQL State</b>	42W23
<b>SQL Code</b>	-215L
<b>ODBC 2 State</b>	40001
<b>ODBC 3 State</b>	40001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of user.
<b>Probable Cause</b>	You attempted to DROP a procedure that is being used by other active users of the database.
<b>Error 216</b>	<b>"The option "%1' can only be set as a temporary option"</b>
<b>Constant</b>	OPTION_IS_TEMP_ONLY
<b>SAP Sybase Error Number</b>	2351
<b>SQL State</b>	42W52
<b>SQL Code</b>	-216L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Name of the option that could not be set.
<b>Probable Cause</b>	The option specified in the SET OPTION statement can only be set as a temporary option.

<b>Error 217</b>	<b>"The option '%1' cannot be set from within a procedure"</b>
<b>Constant</b>	OPTION_IN_PROCEDURE
<b>SAP Sybase Error Number</b>	2352
<b>SQL State</b>	42W53
<b>SQL Code</b>	-217L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Name of the option that could not be set.
<b>Probable Cause</b>	The option specified in the SET OPTION statement cannot be set from within a procedure.
<b>Error 218</b>	<b>"Authentication failed"</b>
<b>Constant</b>	AUTHENTICATION_FAILED
<b>SAP Sybase Error Number</b>	2353
<b>SQL State</b>	08W48
<b>SQL Code</b>	-218L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You set the database_authentication or connection_authentication option incorrectly.

## Messages 220 through 262

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 220</b>	<b>"Savepoint '%1' not found"</b>
<b>Constant</b>	SAVEPOINT_NOTFOUND
<b>SAP Sybase Error Number</b>	2174
<b>SQL State</b>	3B001

## Errors and Warnings

<b>Error 220</b>	<b>"Savepoint '%1' not found"</b>
<b>SQL Code</b>	-220L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of savepoint.
<b>Probable Cause</b>	You attempted to rollback to a savepoint that does not exist.
<b>Error 221</b>	<b>"ROLLBACK TO SAVEPOINT not allowed"</b>
<b>Constant</b>	ROLLBACK_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	2175
<b>SQL State</b>	3B002
<b>SQL Code</b>	-221L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted a ROLLBACK TO SAVEPOINT within an atomic operation to a savepoint established before the atomic operation.
<b>Error 222</b>	<b>"Result set not allowed from within an atomic compound statement"</b>
<b>Constant</b>	RESULT_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	2176
<b>SQL State</b>	3BW02
<b>SQL Code</b>	-222L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You used a SELECT statement with no INTO clause or a RESULT CURSOR statement within an atomic compound statement.

<b>Error 230</b>	<b>"sqlpp/dblib version mismatch"</b>
<b>Constant</b>	PP_DBLIB_MISMATCH
<b>SAP Sybase Error Number</b>	2178
<b>SQL State</b>	08W18
<b>SQL Code</b>	-230L
<b>ODBC 2 State</b>	08801
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>21</i> on page 2
<b>Probable Cause</b>	Your executable has Embedded SQL source files that were preprocessed with a version of sqlpp that does not match the database interface library.
<b>Error 231</b>	<b>"Client/database server version mismatch"</b>
<b>Constant</b>	DBLIB_ENGINE_MISMATCH
<b>SAP Sybase Error Number</b>	2179
<b>SQL State</b>	08W19
<b>SQL Code</b>	-231L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>21</i> on page 2
<b>Probable Cause</b>	Your executable uses a database interface library that does not match the version number of the database server.
<b>Error 240</b>	<b>"Unknown backup operation"</b>
<b>Constant</b>	UNKNOWN_BACKUP_OPERATION
<b>SAP Sybase Error Number</b>	2181
<b>SQL State</b>	WB001
<b>SQL Code</b>	-240L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 240</b>	<b>"Unknown backup operation"</b>
<b>Severity Code</b>	<i>20</i> on page 2
<b>Probable Cause</b>	You specified an invalid backup statement operation in a call to db_backup.
<b>Error 241</b>	<b>"Database backup not started"</b>
<b>Constant</b>	BACKUP_NOT_STARTED
<b>SAP Sybase Error Number</b>	2182
<b>SQL State</b>	WB002
<b>SQL Code</b>	-241L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>20</i> on page 2
<b>Probable Cause</b>	A database backup could not be started. Either a backup is already running, or you do not have the required system privileges or authority (BACKUP, DBA or REMOTE DBA).
<b>Error 242</b>	<b>"Incomplete transactions prevent transaction log renaming"</b>
<b>Constant</b>	BACKUP_CANNOT_RENAME_LOG_YET
<b>SAP Sybase Error Number</b>	2183
<b>SQL State</b>	WB003
<b>SQL Code</b>	-242L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>20</i> on page 2
<b>Probable Cause</b>	The last page in the transaction log was read by a call to db_backup. One or more currently active connections have partially completed transactions, preventing the transaction log file from being renamed. Reissue the db_backup call.

<b>Error 243</b>	<b>"Unable to delete database file"</b>
<b>Constant</b>	BACKUP_UNABLE_TO_DELETE_FILE
<b>SAP Sybase Error Number</b>	2184
<b>SQL State</b>	WB004
<b>SQL Code</b>	-243L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to delete a database file, but it could not be deleted. The file name should not be the same as any database file that is currently in use.
<b>Error 244</b>	<b>"Transaction log was truncated"</b>
<b>Constant</b>	LOG_TRUNCATED
<b>SAP Sybase Error Number</b>	2185
<b>SQL State</b>	WB005
<b>SQL Code</b>	-244L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	While an operation was occurring on the transaction log, the transaction log was truncated by another operation.
<b>Error 245</b>	<b>"Integrated login failed"</b>
<b>Constant</b>	INTEGRATED_LOGON_FAILED
<b>SAP Sybase Error Number</b>	2259
<b>SQL State</b>	28W04
<b>SQL Code</b>	-245L
<b>ODBC 2 State</b>	28000
<b>ODBC 3 State</b>	28000

## Errors and Warnings

<b>Error 245</b>	<b>"Integrated login failed"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The integrated login failed. You may not have a system account on the server computer.
<b>Error 246</b>	<b>"Integrated logins are not supported for this database"</b>
<b>Constant</b>	INTEGRATED_LOGON_UNSUPPORTED
<b>SAP Sybase Error Number</b>	2262
<b>SQL State</b>	28W05
<b>SQL Code</b>	-246L
<b>ODBC 2 State</b>	28000
<b>ODBC 3 State</b>	28000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The current database is an older database and does not have the information to map integrated login IDs to database user IDs. You must upgrade your database to use integrated logins.
<b>Error 247</b>	<b>"The integrated login ID guest can only be mapped to the guest database user ID"</b>
<b>Constant</b>	INTEGRATED_LOGON_GUESTMAP
<b>SAP Sybase Error Number</b>	2263
<b>SQL State</b>	28W06
<b>SQL Code</b>	-247L
<b>ODBC 2 State</b>	28000
<b>ODBC 3 State</b>	28000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to map the guest login ID to something other than guest.
<b>Error 248</b>	<b>"Cannot map a login ID to the sys or public user ID"</b>
<b>Constant</b>	LOGON_SYSMAP

<b>Error 248</b>	<b>"Cannot map a login ID to the sys or public user ID"</b>
<b>SAP Sybase Error Number</b>	2264
<b>SQL State</b>	28W07
<b>SQL Code</b>	-248L
<b>ODBC 2 State</b>	28000
<b>ODBC 3 State</b>	28000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to map a login ID to either SYS or PUBLIC.
<b>Error 249</b>	<b>"The login ID '%1' is already mapped to user ID '%2'"</b>
<b>Constant</b>	LOGON_MAPPED
<b>SAP Sybase Error Number</b>	2265
<b>SQL State</b>	28W08
<b>SQL Code</b>	-249L
<b>ODBC 2 State</b>	28000
<b>ODBC 3 State</b>	28000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the login ID that is already mapped.
<b>Parameter 2</b>	Name of the user that the login ID is already mapped to.
<b>Probable Cause</b>	You attempted to map a login ID twice.
<b>Error 250</b>	<b>"Identifier '%1' too long"</b>
<b>Constant</b>	IDENTIFIER_TOO_LONG
<b>SAP Sybase Error Number</b>	2061
<b>SQL State</b>	54003
<b>SQL Code</b>	-250L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2

## Errors and Warnings

<b>Error 250</b>	<b>"Identifier '%1' too long"</b>
<b>Parameter 1</b>	The identifier that is too long.
<b>Probable Cause</b>	An identifier that was specified is longer than 128 bytes.
<b>Error 251</b>	<b>"Foreign key '%1' for table '%2' duplicates an existing foreign key"</b>
<b>Constant</b>	DUPLICATE_FOREIGN_KEY
<b>SAP Sybase Error Number</b>	2062
<b>SQL State</b>	52W06
<b>SQL Code</b>	-251L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The role name of the new foreign key.
<b>Parameter 2</b>	The table containing the foreign key.
<b>Probable Cause</b>	You attempted to define a foreign key that already exists.
<b>Error 260</b>	<b>"Variable '%1' not found"</b>
<b>Constant</b>	VARIABLE_NOT_FOUND
<b>SAP Sybase Error Number</b>	2139
<b>SQL State</b>	42W14
<b>SQL Code</b>	-260L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	Name of the variable that could not be found.
<b>Probable Cause</b>	You attempted to DROP or SET the value of a SQL variable that was not created or was previously dropped.

<b>Error 261</b>	"There is already a variable named "%1"
<b>Constant</b>	VARIABLE_EXISTS
<b>SAP Sybase Error Number</b>	2140
<b>SQL State</b>	42W15
<b>SQL Code</b>	-261L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	Name of the variable that already exists.
<b>Probable Cause</b>	You attempted to create a variable with the name of another variable that already exists.
<b>Error 262</b>	"Label "%1' not found"
<b>Constant</b>	LABEL_NOT_FOUND
<b>SAP Sybase Error Number</b>	2141
<b>SQL State</b>	42W24
<b>SQL Code</b>	-262L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	Name of the label that could not be found.
<b>Probable Cause</b>	You reference a label in a LEAVE statement, but the label could not be found.

**263 - 785**

---

## **Messages 263 through 288**

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 263</b>	<b>"Invalid absolute or relative offset in FETCH"</b>
<b>Constant</b>	INVALID_FETCH_POSITION
<b>SAP Sybase Error Number</b>	2142
<b>SQL State</b>	42W25
<b>SQL Code</b>	-263L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You specified an offset in a FETCH that was invalid or NULL.
<b>Error 264</b>	<b>"Wrong number of variables in FETCH"</b>
<b>Constant</b>	WRONG_NUM_OF_FETCH_VARIABLES
<b>SAP Sybase Error Number</b>	2143
<b>SQL State</b>	42W26
<b>SQL Code</b>	-264L
<b>ODBC 2 State</b>	S1002
<b>ODBC 3 State</b>	07009
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You specified a number of variables in a FETCH statement that does not match the number of SELECT list items.
<b>Error 265</b>	<b>"Procedure '%1' not found"</b>
<b>Constant</b>	PROCEDURE_NOT_FOUND
<b>SAP Sybase Error Number</b>	2144
<b>SQL State</b>	52W09

<b>Error 265</b>	<b>"Procedure "%1' not found"</b>
<b>SQL Code</b>	-265L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	Name of the procedure that could not be found.
<b>Probable Cause</b>	You misspelled the name of a procedure, or you did not qualify a procedure name with a user name.
<b>Error 267</b>	<b>"COMMIT/ROLLBACK not allowed within atomic operation"</b>
<b>Constant</b>	ATOMIC_OPERATION
<b>SAP Sybase Error Number</b>	2146
<b>SQL State</b>	42W28
<b>SQL Code</b>	-267L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted a COMMIT or ROLLBACK statement while executing within an atomic operation.
<b>Error 268</b>	<b>"Trigger "%1' not found"</b>
<b>Constant</b>	TRIGGER_NOT_FOUND
<b>SAP Sybase Error Number</b>	2147
<b>SQL State</b>	52W10
<b>SQL Code</b>	-268L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	Name of the trigger that could not be found.

## Errors and Warnings

<b>Error 268</b>	<b>"Trigger '%1' not found"</b>
<b>Probable Cause</b>	You misspelled the name of a trigger, or you did not qualify a trigger name with a user name.
<b>Error 269</b>	<b>"Cannot delete or rename a column referenced in a trigger definition"</b>
<b>Constant</b>	COLUMN_IN_TRIGGER
<b>SAP Sybase Error Number</b>	2148
<b>SQL State</b>	53W06
<b>SQL Code</b>	-269L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You attempted to delete or rename a column referenced in a trigger definition. Drop the trigger before performing the ALTER statement.
<b>Error 270</b>	<b>"Cannot drop a user that owns procedures in runtime server"</b>
<b>Constant</b>	USER_OWNS_PROCEDURES
<b>SAP Sybase Error Number</b>	2149
<b>SQL State</b>	55W04
<b>SQL Code</b>	-270L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to drop a user that owns procedures while using the runtime server. This operation would result in dropping procedures. The runtime server cannot drop procedures. Use the full server.
<b>Error 271</b>	<b>"Trigger definition conflicts with existing triggers"</b>
<b>Constant</b>	TRIGGER_DEFN_CONFLICT
<b>SAP Sybase Error Number</b>	2150

<b>Error 271</b>	<b>"Trigger definition conflicts with existing triggers"</b>
<b>SQL State</b>	52W11
<b>SQL Code</b>	-271L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S01
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You attempted to create a trigger, but a trigger with the same name already exists.
<b>Error 272</b>	<b>"Invalid REFERENCES clause in trigger definition"</b>
<b>Constant</b>	INVALID_TRIGGER_COL_REFS
<b>SAP Sybase Error Number</b>	2151
<b>SQL State</b>	52W12
<b>SQL Code</b>	-272L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You supplied an invalid REFERENCES clause in a trigger definition. You may have specified an OLD correlation name in a BEFORE INSERT trigger, or a NEW correlation name in an AFTER DELETE trigger. In both cases, the values do not exist and cannot be referenced.
<b>Error 273</b>	<b>"COMMIT/ROLLBACK not allowed within trigger actions"</b>
<b>Constant</b>	INVALID_TRIGGER_STATEMENT
<b>SAP Sybase Error Number</b>	2152
<b>SQL State</b>	2D501
<b>SQL Code</b>	-273L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2

## Errors and Warnings

<b>Error 273</b>	<b>"COMMIT/ROLLBACK not allowed within trigger actions"</b>
<b>Probable Cause</b>	You attempted to execute a statement that is not allowed while performing a trigger action. COMMIT and ROLLBACK statements cannot be executed from a trigger.
<b>Error 274</b>	<b>"Procedure or trigger calls have nested too deeply"</b>
<b>Constant</b>	NESTING_TOO_DEEP
<b>SAP Sybase Error Number</b>	2153
<b>SQL State</b>	42W29
<b>SQL Code</b>	-274L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You may have defined a procedure or trigger that causes unlimited recursion.
<b>Error 280</b>	<b>"Publication '%1' not found"</b>
<b>Constant</b>	PUBLICATION_NOT_FOUND
<b>SAP Sybase Error Number</b>	2155
<b>SQL State</b>	5RW01
<b>SQL Code</b>	-280L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the publication that could not be found.
<b>Probable Cause</b>	You misspelled the name of a publication, or you did not qualify a publication name with a user name.
<b>Error 281</b>	<b>"Table '%1' has publications"</b>
<b>Constant</b>	TABLE_HAS_PUBLICATIONS
<b>SAP Sybase Error Number</b>	2156

<b>Error 281</b>	<b>"Table '%1' has publications"</b>
<b>SQL State</b>	5RW02
<b>SQL Code</b>	-281L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the table that has publications.
<b>Probable Cause</b>	You attempted to drop a table that has publications defined.
<b>Error 282</b>	<b>"Subscription to '%1' for '%2' already exists"</b>
<b>Constant</b>	SUBSCRIPTION_NOT_UNIQUE
<b>SAP Sybase Error Number</b>	2157
<b>SQL State</b>	5RW03
<b>SQL Code</b>	-282L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the publication.
<b>Parameter 2</b>	Name of the user.
<b>Probable Cause</b>	You attempted to create a subscription that already exists.
<b>Error 283</b>	<b>"Subscription to '%1' for '%2' not found"</b>
<b>Constant</b>	SUBSCRIPTION_NOT_FOUND
<b>SAP Sybase Error Number</b>	2158
<b>SQL State</b>	5RW04
<b>SQL Code</b>	-283L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2

## Errors and Warnings

<b>Error 283</b>	<b>"Subscription to '%1' for '%2' not found"</b>
<b>Parameter 1</b>	Name of the publication.
<b>Parameter 2</b>	Name of the user.
<b>Probable Cause</b>	You attempted to drop, start, or synchronize a subscription that does not exist.
<b>Error 284</b>	<b>"User '%1' is already the publisher for this database"</b>
<b>Constant</b>	ONLY_ONE_PUBLISHER
<b>SAP Sybase Error Number</b>	2159
<b>SQL State</b>	5RW05
<b>SQL Code</b>	-284L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the publisher.
<b>Probable Cause</b>	You attempted to GRANT PUBLISH to a user ID, when a publisher already exists.
<b>Error 285</b>	<b>"User '%1' is not a remote user for this database"</b>
<b>Constant</b>	NOT_REMOTE_USER
<b>SAP Sybase Error Number</b>	2160
<b>SQL State</b>	5RW06
<b>SQL Code</b>	-285L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of user.
<b>Probable Cause</b>	You attempted to execute a CREATE SUBSCRIPTION or PASS-THROUGH for a user that is not a remote user of this database. You must GRANT REMOTE or GRANT CONSOLIDATE for this user before proceeding with this operation.

<b>Error 286</b>	<b>"Remote message type "%1' not found"</b>
<b>Constant</b>	NOT_REMOTE_TYPE
<b>SAP Sybase Error Number</b>	2161
<b>SQL State</b>	5RW07
<b>SQL Code</b>	-286L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of remote message type.
<b>Probable Cause</b>	You referred to a remote message type that is not defined in this database. Use CREATE REMOTE TYPE to define remote message types.
<b>Error 287</b>	<b>"Passthrough statement inconsistent with current passthrough"</b>
<b>Constant</b>	PASSTHROUGH_INCONSISTENT
<b>SAP Sybase Error Number</b>	2162
<b>SQL State</b>	5RW08
<b>SQL Code</b>	-287L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Passthrough is additive, in that subsequent PASSTHROUGH statements add to the list of users receiving passthrough. The PASS-THROUGH statements must all be PASSTHROUGH ONLY or none should be PASSTHROUGH ONLY.
<b>Error 288</b>	<b>"Remote statement failed"</b>
<b>Constant</b>	REMOTE_STATEMENT_FAILED
<b>SAP Sybase Error Number</b>	2163

## Errors and Warnings

<b>Error 288</b>	"Remote statement failed"
<b>SQL State</b>	5RW09
<b>SQL Code</b>	-288L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	This SQLSTATE can be signaled within a trigger to prevent the SQL Remote Message Agent (dbremote) from displaying an error message in the output. This exception will only occur when a trigger or procedure signals it. This is useful for ignoring replication errors that are permitted by design.

## Messages 289 through 313

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 289</b>	"Multiple consolidated users cannot be defined"
<b>Constant</b>	CONSOLIDATED_USER_ALREADY_EXISTS
<b>SAP Sybase Error Number</b>	2403
<b>SQL State</b>	5RW10
<b>SQL Code</b>	-289L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to grant consolidated permissions when your database already has a consolidated user, or attempted to grant consolidated permissions to multiple users in a single statement.

<b>Error 294</b>	"Format string argument number %1 is invalid"
<b>Constant</b>	INVALID_FORMAT_STRING_ARG_NUM
<b>SAP Sybase Error Number</b>	2166
<b>SQL State</b>	53W08

<b>Error 294</b>	<b>"Format string argument number %1 is invalid"</b>
<b>SQL Code</b>	-294L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Argument number.
<b>Probable Cause</b>	You supplied an invalid argument number in the format string for a PRINT or RAISERROR statement. The number must be between 1 and 20 and must not exceed the number of arguments provided.
<b>Error 295</b>	<b>"Cannot uniquely identify rows in cursor"</b>
<b>Constant</b>	CANNOT_UNIQUELY_IDENTIFY_ROWS
<b>SAP Sybase Error Number</b>	2164
<b>SQL State</b>	09W05
<b>SQL Code</b>	-295L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You opened a UNIQUE cursor on a SELECT statement for which a set of columns uniquely identifying each row cannot be generated. One of the tables may not be defined with a primary key or uniqueness constraint, or the SELECT statement may involve a UNION, INTERSECT, EXCEPT, or GROUP BY.
<b>Error 296</b>	<b>"Error number %1 for RAISERROR must not be less than 17000"</b>
<b>Constant</b>	ERROR_NUMBER_OUT_OF_RANGE
<b>SAP Sybase Error Number</b>	2165
<b>SQL State</b>	53W07
<b>SQL Code</b>	-296L
<b>ODBC 2 State</b>	37000

## Errors and Warnings

<b>Error 296</b>	"Error number %1 for RAISERROR must not be less than 17000"
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Error number.
<b>Probable Cause</b>	You supplied an invalid error number in a RAISERROR statement. The number must be greater than or equal to 17000.

<b>Error 297</b>	"User-defined exception signaled"
<b>Constant</b>	USER_DEFINED_EXCEPTION
<b>SAP Sybase Error Number</b>	2186
<b>SQL State</b>	99999
<b>SQL Code</b>	-297L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A stored procedure or trigger signaled a user-defined exception. This error state is reserved for use within stored procedures or triggers that contain exception handlers, as a way of signaling an exception that can be guaranteed to not have been caused by the database server. Valid SQLSTATE values range from 99000 to 99999 and are set by the user when executing the SIGNAL SQL statement.

<b>Error 298</b>	"Attempted two active database requests"
<b>Constant</b>	DOUBLE_REQUEST
<b>SAP Sybase Error Number</b>	2187
<b>SQL State</b>	42W22
<b>SQL Code</b>	-298L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 298</b>	<b>"Attempted two active database requests"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	In embedded SQL, you attempted to submit a database request while you have another request in progress. You should either use a separate SQLCA and connection for each thread accessing the database, or use thread synchronization calls to ensure that a SQLCA is only accessed by one thread at a time.

<b>Error 299</b>	<b>"Statement interrupted by user"</b>
<b>Constant</b>	INTERRUPTED
<b>SAP Sybase Error Number</b>	2188
<b>SQL State</b>	57014
<b>SQL Code</b>	-299L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You canceled a statement during its execution. The database was able to stop the operation without doing a rollback. If the statement is an INSERT, UPDATE, or DELETE, any changes made by the statement will be canceled. If the statement is a data definition statement (for example CREATE TABLE), the statement will be canceled, but the COMMIT that was done as a side effect will not be canceled.

<b>Error 300</b>	<b>"Run time SQL error -- %1"</b>
<b>Constant</b>	ERROR
<b>SAP Sybase Error Number</b>	2189
<b>SQL State</b>	40000
<b>SQL Code</b>	-300L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>18</i> on page 2

## Errors and Warnings

<b>Error 300</b>	<b>"Run time SQL error -- %1"</b>
<b>Parameter 1</b>	Identification of the error.
<b>Probable Cause</b>	An internal database error occurred. If it can be reproduced, it should be reported to SAP Sybase. You may be able to work around this problem by modifying the associated query statement.
<b>Error 301</b>	<b>"Internal database error %1 -- transaction rolled back"</b>
<b>Constant</b>	DATABASE_ERROR
<b>SAP Sybase Error Number</b>	2190
<b>SQL State</b>	40W01
<b>SQL Code</b>	-301L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>18</i> on page 2
<b>Parameter 1</b>	Identification of the error.
<b>Probable Cause</b>	An internal database error occurred. If it can be reproduced, it should be reported to SAP Sybase. A ROLLBACK statement has been automatically executed.
<b>Error 302</b>	<b>"Terminated by user -- transaction rolled back"</b>
<b>Constant</b>	TERMINATED_BY_USER
<b>SAP Sybase Error Number</b>	2191
<b>SQL State</b>	40W02
<b>SQL Code</b>	-302L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You canceled a statement while the database was executing. A ROLLBACK statement has been automatically executed.

<b>Error 303</b>	<b>"Disk write failure '%1' -- transaction rolled back"</b>
<b>Constant</b>	DISK_WRITE_FAILED
<b>SAP Sybase Error Number</b>	2513
<b>SQL State</b>	40W05
<b>SQL Code</b>	-303L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>21</i> on page 2
<b>Parameter 1</b>	Name of the file that could not be written.
<b>Probable Cause</b>	A disk write failed. A ROLLBACK statement has been automatically executed.
<b>Error 304</b>	<b>"Disk full '%1' -- transaction rolled back"</b>
<b>Constant</b>	DEVICE_FULL
<b>SAP Sybase Error Number</b>	2192
<b>SQL State</b>	40W03
<b>SQL Code</b>	-304L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>17</i> on page 2
<b>Parameter 1</b>	Name of the file that could not be written to the disk.
<b>Probable Cause</b>	Your hard disk is out of space. A ROLLBACK statement has been automatically executed.
<b>Error 305</b>	<b>"I/O error %1 -- transaction rolled back"</b>
<b>Constant</b>	DEVICE_ERROR
<b>SAP Sybase Error Number</b>	2193
<b>SQL State</b>	40W04
<b>SQL Code</b>	-305L

## Errors and Warnings

<b>Error 305</b>	<b>"I/O error %1 -- transaction rolled back"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	24 on page 2
<b>Parameter 1</b>	A message describing the error that occurred.
<b>Probable Cause</b>	SQL Anywhere has detected a problem with your hard disk. A ROLLBACK statement has been automatically executed.
<b>Error 306</b>	<b>"Deadlock detected"</b>
<b>Constant</b>	DEADLOCK
<b>SAP Sybase Error Number</b>	2194
<b>SQL State</b>	40001
<b>SQL Code</b>	-306L
<b>ODBC 2 State</b>	40001
<b>ODBC 3 State</b>	40001
<b>Severity Code</b>	13 on page 2
<b>Probable Cause</b>	You attempted to read or write a row and it is locked by another user. Also, the other user is blocked directly or indirectly on your own transaction. This is a deadlock situation and your transaction has been chosen as the one to rollback.
<b>Error 307</b>	<b>"All threads are blocked"</b>
<b>Constant</b>	THREAD_DEADLOCK
<b>SAP Sybase Error Number</b>	2195
<b>SQL State</b>	40W06
<b>SQL Code</b>	-307L
<b>ODBC 2 State</b>	40001
<b>ODBC 3 State</b>	40001
<b>Severity Code</b>	13 on page 2

<b>Error 307</b>	<b>"All threads are blocked"</b>
<b>Probable Cause</b>	You attempted to read or write a row and it is locked by another user. Also, all other threads (see the -gn server option) are blocked waiting for a lock to be released. This is a deadlock situation and your transaction has been chosen as the one to rollback.
<b>Error 308</b>	<b>"Connection was terminated"</b>
<b>Constant</b>	CONNECTION_TERMINATED
<b>SAP Sybase Error Number</b>	2196
<b>SQL State</b>	40W07
<b>SQL Code</b>	-308L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Your database connection has been terminated and your transaction has been rolled back. The connection may have been terminated because a DBA executed a DROP CONNECTION statement, or because the database server was shut down, or because your network connection to the database server was interrupted.
<b>Error 309</b>	<b>"Memory error -- transaction rolled back"</b>
<b>Constant</b>	MEMORY_ERROR
<b>SAP Sybase Error Number</b>	2361
<b>SQL State</b>	40W08
<b>SQL Code</b>	-309L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>24</i> on page 2

## Errors and Warnings

<b>Error 309</b>	<b>"Memory error -- transaction rolled back"</b>
<b>Probable Cause</b>	The UltraLite runtime has received an unexpected error from the system calls being used to store the UltraLite database. For example, a write to persistent memory failed. This is an internal error and indicates faulty or corrupt persistent storage on the device. A ROLLBACK statement has been automatically executed.
<b>Error 311</b>	<b>"Internal rollback log corrupted"</b>
<b>Constant</b>	LOG_CORRUPTED
<b>SAP Sybase Error Number</b>	2208
<b>SQL State</b>	WI004
<b>SQL Code</b>	-311L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	22 on page 2
<b>Probable Cause</b>	While processing a COMMIT or ROLLBACK, corruption was found in the internal rollback log. This is a fatal internal error.
<b>Error 312</b>	<b>"User "%1' already has membership in group "%2"</b>
<b>Constant</b>	ALREADY_HAS_GROUP_MEMBERSHIP
<b>SAP Sybase Error Number</b>	2069
<b>SQL State</b>	42W34
<b>SQL Code</b>	-312L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	16 on page 2
<b>Parameter 1</b>	Name of the user that already has membership.
<b>Parameter 2</b>	Name of the group.
<b>Probable Cause</b>	You attempted to give a membership in a group to a user that already has such membership.

<b>Error 313</b>	"The login ID "%1' has not been mapped to any database user ID"
<b>Constant</b>	LOGON_UNMAPPED
<b>SAP Sybase Error Number</b>	2266
<b>SQL State</b>	28W09
<b>SQL Code</b>	-313L
<b>ODBC 2 State</b>	28000
<b>ODBC 3 State</b>	28000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the login ID that is not mapped.
<b>Probable Cause</b>	You attempted to connect using a login ID that is not mapped to a database user ID and there is no guest database user ID, or you attempted to revoke a login ID that has not been mapped. This can also occur when attempting to connect using an integrated login ID that is a member of more than one mapped group.

## **Messages 503 through 619**

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 503</b>	<b>No message</b>
<b>Constant</b>	PREEMPTED
<b>SAP Sybase Error Number</b>	2260
<b>SQL State</b>	WI006
<b>SQL Code</b>	-503L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	No additional information available.

## Errors and Warnings

<b>Error 504</b>	<b>No message</b>
<b>Constant</b>	RETRY
<b>SAP Sybase Error Number</b>	2261
<b>SQL State</b>	WI008
<b>SQL Code</b>	-504L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 601</b>	<b>""%1' is not a known file format for loading or unloading tables"</b>
<b>Constant</b>	UNSUPPORTED_LOAD_FORMAT
<b>SAP Sybase Error Number</b>	2209
<b>SQL State</b>	WL001
<b>SQL Code</b>	-601L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>19</i> on page 2
<b>Parameter 1</b>	The specified format.
<b>Probable Cause</b>	An unsupported file format was specified for LOAD TABLE or UNLOAD TABLE.
<b>Error 602</b>	<b>"Cannot access file '%1' -- %2"</b>
<b>Constant</b>	CANNOT_ACCESS_FILE
<b>SAP Sybase Error Number</b>	2210
<b>SQL State</b>	WL002
<b>SQL Code</b>	-602L
<b>ODBC 2 State</b>	ERROR

<b>Error 602</b>	<b>"Cannot access file '%1' -- %2"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>19</i> on page 2
<b>Parameter 1</b>	The file name.
<b>Parameter 2</b>	The cause of the error.
<b>Probable Cause</b>	A file cannot be accessed. For example, a file referenced by LOAD TABLE does not exist or cannot be read. The message will contain the reason for the error.
<b>Error 604</b>	<b>"A dbspace has reached its maximum file size"</b>
<b>Constant</b>	DBSPACE_FULL
<b>SAP Sybase Error Number</b>	2213
<b>SQL State</b>	04W07
<b>SQL Code</b>	-604L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A dbspace has grown to its maximum number of disk pages, which is usually limited by the maximum operating system file size. This is a fatal error.
<b>Error 605</b>	<b>"The server attempted to access a page beyond the end of the maximum allowable dbspace file size"</b>
<b>Constant</b>	ACCESS_BEYOND_END_OF_MAX_DBSPACE
<b>SAP Sybase Error Number</b>	2214
<b>SQL State</b>	04W08
<b>SQL Code</b>	-605L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

## Errors and Warnings

<b>Error 605</b>	<b>"The server attempted to access a page beyond the end of the maximum allowable dbspace file size"</b>
<b>Probable Cause</b>	The database attempted to access a page whose page number is beyond the maximum possible number of disk pages. This is a fatal internal error.
<b>Error 606</b>	<b>"The pattern is too long"</b>
<b>Constant</b>	PATTERN_TOO_LONG
<b>SAP Sybase Error Number</b>	2215
<b>SQL State</b>	WW001
<b>SQL Code</b>	-606L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The pattern for the LIKE operator is too long. All patterns of 126 characters or less are supported. Some patterns as long as 254 characters are supported, depending on their contents. Patterns longer than 254 characters are not supported.
<b>Error 607</b>	<b>"Cannot stop the database server"</b>
<b>Constant</b>	CANNOT_STOP_SERVER
<b>SAP Sybase Error Number</b>	2216
<b>SQL State</b>	WW002
<b>SQL Code</b>	-607L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The server has determined that it cannot be shut down at this time. Normally, this error should not occur.

<b>Error 608</b>	"Invalid TEXTPTR value used with WRITETEXT or READTEXT"
<b>Constant</b>	INVALID_TEXTPTR_VALUE
<b>SAP Sybase Error Number</b>	2217
<b>SQL State</b>	22W03
<b>SQL Code</b>	-608L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You supplied an invalid value as the TEXTPTR for a WRITETEXT or READTEXT statement.
<b>Error 609</b>	"Invalid data type for column in WRITETEXT or READTEXT"
<b>Constant</b>	INVALID_TEXT_IMAGE_DATATYPE
<b>SAP Sybase Error Number</b>	2218
<b>SQL State</b>	53W09
<b>SQL Code</b>	-609L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You referenced a column in a WRITETEXT or READTEXT statement that is not defined for storing text or image data.
<b>Error 610</b>	"User message %1 already exists"
<b>Constant</b>	MESSAGE_ALREADY_EXISTS
<b>SAP Sybase Error Number</b>	2064
<b>SQL State</b>	52W16
<b>SQL Code</b>	-610L
<b>ODBC 2 State</b>	42000

## Errors and Warnings

<b>Error 610</b>	<b>"User message %1 already exists"</b>
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Error number of the user message that exists in the database.
<b>Probable Cause</b>	The message with this error number already exists in the database.
<b>Error 611</b>	<b>"Transact-SQL feature not supported"</b>
<b>Constant</b>	TSQL FEATURE NOT SUPPORTED
<b>SAP Sybase Error Number</b>	2076
<b>SQL State</b>	0AW02
<b>SQL Code</b>	-611L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You attempted to use a Transact-SQL feature that is not supported in SQL Anywhere.
<b>Error 612</b>	<b>"User message %1 not found"</b>
<b>Constant</b>	MESSAGE_NOT_FOUND
<b>SAP Sybase Error Number</b>	2097
<b>SQL State</b>	52W17
<b>SQL Code</b>	-612L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Message number.
<b>Probable Cause</b>	The message with this error number does not exist in the database.
<b>Error 613</b>	<b>"User-defined type '%1' not found"</b>
<b>Constant</b>	USER_TYPE_NOT_FOUND

<b>Error 613</b>	<b>"User-defined type '%1' not found"</b>
<b>SAP Sybase Error Number</b>	2098
<b>SQL State</b>	52W18
<b>SQL Code</b>	-613L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the user-defined type.
<b>Probable Cause</b>	The user-defined type with this name does not exist in the database.
<b>Error 614</b>	<b>"Cannot drop a user that owns messages or data types"</b>
<b>Constant</b>	USER_OWNS_MESSAGES_OR_DATATYPES
<b>SAP Sybase Error Number</b>	2099
<b>SQL State</b>	55W05
<b>SQL Code</b>	-614L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to drop a user that is the creator of a message or user-defined data type. The message or user-defined data type must be dropped first.
<b>Error 615</b>	<b>"Parameter '%1' not found in procedure '%2'"</b>
<b>Constant</b>	INVALID_PARAMETER_NAME
<b>SAP Sybase Error Number</b>	2101
<b>SQL State</b>	42W47
<b>SQL Code</b>	-615L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000

## Errors and Warnings

<b>Error 615</b>	<b>"Parameter "%1' not found in procedure "%2"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the parameter that was not found.
<b>Parameter 2</b>	Name of the procedure where the parameter was not found.
<b>Probable Cause</b>	You supplied a procedure parameter name that does not match a parameter for this procedure. Check the spelling of the parameter name.
<b>Error 616</b>	<b>"Too many columns in table"</b>
<b>Constant</b>	TOO_MANY_COLUMNS_IN_TABLE
<b>SAP Sybase Error Number</b>	2219
<b>SQL State</b>	52W20
<b>SQL Code</b>	-616L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You executed a CREATE TABLE or ALTER TABLE statement that attempted to add a column to a table. The resulting number of columns in the table would exceed the limit for the current database page size.
<b>Error 617</b>	<b>"Calling functions outside the database server is not supported"</b>
<b>Constant</b>	EXTERNAL_CALLS_NOT_SUPPORTED
<b>SAP Sybase Error Number</b>	2220
<b>SQL State</b>	WW003
<b>SQL Code</b>	-617L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

<b>Error 617</b>	<b>"Calling functions outside the database server is not supported"</b>
<b>Probable Cause</b>	You attempted to call a stored procedure that, in turn, calls a function in a dynamically loaded module. The operating system on which this stored procedure was called does not support such an action.
<b>Error 618</b>	<b>"Mismatch between external function platform specifier and current operating system"</b>
<b>Constant</b>	EXTERNAL_PLATFORM_FAILURE
<b>SAP Sybase Error Number</b>	2221
<b>SQL State</b>	WW004
<b>SQL Code</b>	-618L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A call to an external entry point in a dynamically loaded module was qualified by an operating system that was not the operating system on which the server is currently executing.
<b>Error 619</b>	<b>"Need a dynamic library name"</b>
<b>Constant</b>	REQUIRE_DLL_NAME
<b>SAP Sybase Error Number</b>	2222
<b>SQL State</b>	WW005
<b>SQL Code</b>	-619L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>19</i> on page 2
<b>Probable Cause</b>	You must provide a library name specifier in the name of the external function to call.

## Messages 620 through 639

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 620</b>	<b>"Could not load dynamic library "%1"</b>
<b>Constant</b>	COULD_NOT_LOAD_LIBRARY
<b>SAP Sybase Error Number</b>	2223
<b>SQL State</b>	WW006
<b>SQL Code</b>	-620L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>19</i> on page 2
<b>Parameter 1</b>	Name of the dynamic library that could not be loaded.
<b>Probable Cause</b>	This error is usually caused by a failure to load a dynamic library named in an external function call.
<b>Error 621</b>	<b>"Could not find '%1' in dynamic library "%2"</b>
<b>Constant</b>	COULD_NOT_FIND_FUNCTION
<b>SAP Sybase Error Number</b>	2224
<b>SQL State</b>	WW007
<b>SQL Code</b>	-621L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>19</i> on page 2
<b>Parameter 1</b>	Name of the function that could not be found.
<b>Parameter 2</b>	Name of the dynamic library in which the function could not be found.
<b>Probable Cause</b>	The external function could not be found in the dynamic library.

<b>Error 622</b>	<b>"Could not allocate resources to call external function"</b>
<b>Constant</b>	ERROR_CALLING_FUNCTION
<b>SAP Sybase Error Number</b>	2225
<b>SQL State</b>	WW008
<b>SQL Code</b>	-622L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>19</i> on page 2
<b>Probable Cause</b>	The external function could not be called due to a shortage of operating system resources. If the operating system supports threads, the maximum thread count should be increased.
<b>Error 623</b>	<b>"Data definition statements not allowed in procedures or triggers"</b>
<b>Constant</b>	DDL_NOT_ALLOWED_IN PROCEDURES
<b>SAP Sybase Error Number</b>	2226
<b>SQL State</b>	52W21
<b>SQL Code</b>	-623L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	The procedure or trigger definition contains a data definition statement (such as CREATE, DROP, GRANT, REVOKE, or ALTER). These statements are not allowed within procedures or triggers.
<b>Error 624</b>	<b>"Expression has unsupported data type"</b>
<b>Constant</b>	DATATYPE_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	2227
<b>SQL State</b>	WW009

## Errors and Warnings

<b>Error 624</b>	<b>"Expression has unsupported data type"</b>
<b>SQL Code</b>	-624L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	Either an external function or Java method was declared with a parameter or result data type that is not supported, or a Java field reference with an unsupported result type was attempted.
<b>Error 625</b>	<b>"Too many parameters to this external procedure call"</b>
<b>Constant</b>	TOO_MANY_PARAMETERS
<b>SAP Sybase Error Number</b>	2228
<b>SQL State</b>	WW010
<b>SQL Code</b>	-625L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>19</i> on page 2
<b>Probable Cause</b>	There is a maximum of 256 parameters to an external function call in 32-bit Windows.
<b>Error 626</b>	<b>"A thread used internally could not be started"</b>
<b>Constant</b>	THREAD_START_FAILURE
<b>SAP Sybase Error Number</b>	2229
<b>SQL State</b>	WW011
<b>SQL Code</b>	-626L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>19</i> on page 2
<b>Probable Cause</b>	This is a Windows 95 specific error. An operating system thread could not be started that is required to execute external functions.

<b>Error 627</b>	<b>"Disallowed language extension detected in syntax near '%1' on line %2"</b>
<b>Constant</b>	INVALID_SYNTAX_EXTENSION
<b>SAP Sybase Error Number</b>	2230
<b>SQL State</b>	0AW03
<b>SQL Code</b>	-627L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The word or symbol where the syntax has been detected.
<b>Parameter 2</b>	Line number.
<b>Probable Cause</b>	The statement you are trying to execute contains syntax that is not allowed with the current setting of the option sql_flagger_error_level. Modify the offending statement or set the sql_flagger_error_level option to a different value.
<b>Error 628</b>	<b>"Division by zero"</b>
<b>Constant</b>	DIV_ZERO_ERROR
<b>SAP Sybase Error Number</b>	2231
<b>SQL State</b>	22012
<b>SQL Code</b>	-628L
<b>ODBC 2 State</b>	22012
<b>ODBC 3 State</b>	22012
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A division by zero operation was detected.
<b>Error 629</b>	<b>"Invalid escape character '%1'"</b>
<b>Constant</b>	INVALID_ESCAPE_CHAR
<b>SAP Sybase Error Number</b>	2232
<b>SQL State</b>	22019

## Errors and Warnings

<b>Error 629</b>	<b>"Invalid escape character '%1'"</b>
<b>SQL Code</b>	-629L
<b>ODBC 2 State</b>	S1000
<b>ODBC 3 State</b>	22019
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The escape character that is invalid.
<b>Probable Cause</b>	The escape character string length must be exactly one.
<b>Error 630</b>	<b>"Invalid escape sequence '%1'"</b>
<b>Constant</b>	INVALID_ESCAPE_SEQ
<b>SAP Sybase Error Number</b>	2233
<b>SQL State</b>	22025
<b>SQL Code</b>	-630L
<b>ODBC 2 State</b>	S1000
<b>ODBC 3 State</b>	22025
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The escaped character.
<b>Probable Cause</b>	A LIKE pattern contains an invalid use of the escape character. The escape character may only precede the special characters '%', '_', '[', and the escape character itself.
<b>Error 631</b>	<b>"RAISERROR executed: %1"</b>
<b>Constant</b>	RAISERROR_STMT
<b>SAP Sybase Error Number</b>	2234
<b>SQL State</b>	WW012
<b>SQL Code</b>	-631L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

<b>Error 631</b>	<b>"RAISERROR executed: %1"</b>
<b>Parameter 1</b>	RAISERROR message string.
<b>Probable Cause</b>	A RAISERROR statement has been executed. The string associated with the RAISERROR statement is included in the text of the error message.
<b>Error 632</b>	<b>"WITH CHECK OPTION violated for insert/update on base table "%1"</b>
<b>Constant</b>	WITH_CHECK_OPTION_VIOLATION
<b>SAP Sybase Error Number</b>	2235
<b>SQL State</b>	44000
<b>SQL Code</b>	-632L
<b>ODBC 2 State</b>	S1000
<b>ODBC 3 State</b>	44000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the base table being updated.
<b>Probable Cause</b>	You attempted an insert or update operation on the indicated base table through a view (possibly nested). However, one or more values in the modified row(s) triggered a WITH CHECK OPTION violation. This violation occurs when a modified value causes one or more rows to fall outside the range of the view by making the view's WHERE clause evaluate to FALSE or UNKNOWN for that row.
<b>Error 633</b>	<b>"Update operation attempted on a read-only cursor"</b>
<b>Constant</b>	READ_ONLY_CURSOR
<b>SAP Sybase Error Number</b>	2236
<b>SQL State</b>	42W30
<b>SQL Code</b>	-633L
<b>ODBC 2 State</b>	S1009
<b>ODBC 3 State</b>	HY092
<b>Severity Code</b>	<i>16</i> on page 2

## Errors and Warnings

<b>Error 633</b>	<b>"Update operation attempted on a read-only cursor"</b>
<b>Probable Cause</b>	You attempted an update operation on a cursor that was explicitly declared as read-only.
<b>Error 634</b>	<b>"Unterminated C string"</b>
<b>Constant</b>	UNTERMINATED_C_STR
<b>SAP Sybase Error Number</b>	2237
<b>SQL State</b>	22024
<b>SQL Code</b>	-634L
<b>ODBC 2 State</b>	22024
<b>ODBC 3 State</b>	22024
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The last byte of a C string host variable must contain the null character.
<b>Error 635</b>	<b>"GRANT of column permission on view not allowed"</b>
<b>Constant</b>	NO_COLUMN_PERMS_FOR_VIEWS
<b>SAP Sybase Error Number</b>	2240
<b>SQL State</b>	52W22
<b>SQL Code</b>	-635L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You cannot grant permissions on columns for views.
<b>Error 636</b>	<b>"Duplicate referencing column"</b>
<b>Constant</b>	DUPLICATE_REFERENCING_COLUMN
<b>SAP Sybase Error Number</b>	2242
<b>SQL State</b>	42W40
<b>SQL Code</b>	-636L

<b>Error 636</b>	<b>"Duplicate referencing column"</b>
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You supplied a duplicate column name in the list of referencing columns.
<b>Error 637</b>	<b>"Duplicate insert column"</b>
<b>Constant</b>	DUPLICATE_INSERT_COLUMN
<b>SAP Sybase Error Number</b>	2243
<b>SQL State</b>	42W41
<b>SQL Code</b>	-637L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You supplied a duplicate column name in the list of insert columns.
<b>Error 638</b>	<b>"Right truncation of string data"</b>
<b>Constant</b>	STRING_RIGHT_TRUNCATION
<b>SAP Sybase Error Number</b>	2244
<b>SQL State</b>	22001
<b>SQL Code</b>	-638L
<b>ODBC 2 State</b>	22001
<b>ODBC 3 State</b>	22001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Non-space characters were truncated upon the assignment of string data.
<b>Error 639</b>	<b>"Parameter name missing in call to procedure "%1"</b>
<b>Constant</b>	PARAMETER_NAME_MISSING

<b>Error 639</b>	<b>"Parameter name missing in call to procedure "%1"</b>
<b>SAP Sybase Error Number</b>	2245
<b>SQL State</b>	42W42
<b>SQL Code</b>	-639L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the procedure.
<b>Probable Cause</b>	Positional parameters were specified after named parameters in a call to this procedure.

## Messages 640 through 659

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 640</b>	<b>"Invalid descriptor index"</b>
<b>Constant</b>	INVALID_DESCRIPTOR_INDEX
<b>SAP Sybase Error Number</b>	2246
<b>SQL State</b>	07009
<b>SQL Code</b>	-640L
<b>ODBC 2 State</b>	S1002
<b>ODBC 3 State</b>	07009
<b>Severity Code</b>	<i>26</i> on page 2
<b>Probable Cause</b>	The index number used with respect to a descriptor area is out of range.

<b>Error 641</b>	<b>"Error in assignment"</b>
<b>Constant</b>	ERROR_IN_ASSIGNMENT
<b>SAP Sybase Error Number</b>	2247
<b>SQL State</b>	22005
<b>SQL Code</b>	-641L

<b>Error 641</b>	"Error in assignment"
<b>ODBC 2 State</b>	22005
<b>ODBC 3 State</b>	22018
<b>Severity Code</b>	<i>20</i> on page 2
<b>Probable Cause</b>	In a GET DESCRIPTOR statement, the data type of the host variable must correspond to the data type of the descriptor item.
<b>Error 642</b>	"Invalid SQL descriptor name"
<b>Constant</b>	INVALID_DESCRIPTOR_NAME
<b>SAP Sybase Error Number</b>	2248
<b>SQL State</b>	33000
<b>SQL Code</b>	-642L
<b>ODBC 2 State</b>	33000
<b>ODBC 3 State</b>	33000
<b>Severity Code</b>	<i>21</i> on page 2
<b>Probable Cause</b>	You attempted to deallocate a descriptor that has not been allocated.
<b>Error 643</b>	"UNLOAD TABLE cannot be used to unload a view"
<b>Constant</b>	CANNOT_UNLOAD_A_VIEW
<b>SAP Sybase Error Number</b>	2212
<b>SQL State</b>	WL004
<b>SQL Code</b>	-643L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	UNLOAD TABLE was specified with the name of a view. UNLOAD TABLE may only be used to unload tables.
<b>Error 644</b>	"Invalid database page size"
<b>Constant</b>	PAGE_SIZE_INVALID

## Errors and Warnings

<b>Error 644</b>	<b>"Invalid database page size"</b>
<b>SAP Sybase Error Number</b>	2032
<b>SQL State</b>	08W32
<b>SQL Code</b>	-644L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	You attempted to create a database with an invalid page size. The page size for a SQL Anywhere database must be either 2048, 4096, 8192, 16384, or 32768 bytes. The page size for an UltraLite database must be either 1024, 2048, 4096, 8192, or 16384 bytes.
<b>Error 645</b>	<b>"Database creation failed: %1"</b>
<b>Constant</b>	DATABASE_NOT_CREATED
<b>SAP Sybase Error Number</b>	2033
<b>SQL State</b>	08W33
<b>SQL Code</b>	-645L
<b>ODBC 2 State</b>	08004
<b>ODBC 3 State</b>	08004
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Reason that the database was not created.
<b>Probable Cause</b>	Your attempt to initialize a file for a database failed.
<b>Error 646</b>	<b>"Could not load the store DLL \%"No message</b>
<b>Constant</b>	STORE_NOT_LOADED
<b>SAP Sybase Error Number</b>	2270
<b>SQL State</b>	08W34
<b>SQL Code</b>	-646L
<b>ODBC 2 State</b>	ERROR

<b>Error 646</b>	<b>"Could not load the store DLL \%"%1\No message</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>19</i> on page 2
<b>Parameter 1</b>	Name of the store DLL that could not be loaded.
<b>Probable Cause</b>	An attempt to load the store DLL failed.
<b>Error 647</b>	<b>"Could not execute store DLL (%1) entry point"</b>
<b>Constant</b>	STORE_ENTRY_NOT_FOUND
<b>SAP Sybase Error Number</b>	2271
<b>SQL State</b>	08W35
<b>SQL Code</b>	-647L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>19</i> on page 2
<b>Parameter 1</b>	Name of the store DLL where the entry point failed.
<b>Probable Cause</b>	An attempt to locate or execute the store DLL entry point failed.
<b>Error 648</b>	<b>"Cannot create item (%1) in the specified dbspace"</b>
<b>Constant</b>	INVALID_DBSPACE_FOR_CREATE
<b>SAP Sybase Error Number</b>	2272
<b>SQL State</b>	08W36
<b>SQL Code</b>	-648L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the item that could not be created.
<b>Probable Cause</b>	The specified dbspace is invalid. For example, an index must be created in a dbspace of the same type as the underlying table.

## Errors and Warnings

<b>Error 649</b>	<b>"Field '%1' of class '%2' cannot be NULL"</b>
<b>Constant</b>	FIELD_CANNOT_BE_NULL
<b>SAP Sybase Error Number</b>	2275
<b>SQL State</b>	WW015
<b>SQL Code</b>	-649L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the field that cannot be NULL.
<b>Parameter 2</b>	The name of the class that has the field.
<b>Probable Cause</b>	An attempt was made to store a SQL NULL value in a Java object field that has a Java type that cannot be NULL. For example, the Java 'int' type cannot be NULL.
<b>Error 650</b>	<b>"Index type specification of '%1' is invalid"</b>
<b>Constant</b>	INVALID_INDEX_TYPE
<b>SAP Sybase Error Number</b>	2276
<b>SQL State</b>	WW016
<b>SQL Code</b>	-650L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The index type specification that is invalid.
<b>Probable Cause</b>	In UltraLite, you cannot specify indexes on LONG column types. Sybase IQ index types can be specified for SAP Sybase IQ indexes only.
<b>Error 651</b>	<b>"An attempt to delete database '%1' failed"</b>
<b>Constant</b>	DROP_DATABASE_FAILED
<b>SAP Sybase Error Number</b>	2277

<b>Error 651</b>	<b>"An attempt to delete database '%1' failed"</b>
<b>SQL State</b>	WW017
<b>SQL Code</b>	-651L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the database that could not be deleted.
<b>Probable Cause</b>	Your attempt to delete a database file failed. You may have attempted to delete a running database. Some parts of the database may have been deleted before failure.
<b>Error 652</b>	<b>"Could not decompress class '%1' from JAR"</b>
<b>Constant</b>	CANNOT_DECOMPRESS_CLASS
<b>SAP Sybase Error Number</b>	2278
<b>SQL State</b>	WP003
<b>SQL Code</b>	-652L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the class file in the JAR.
<b>Probable Cause</b>	The Java runtime library must be installed to extract class files from ZIP or JAR files.
<b>Error 653</b>	<b>"Cannot remove class '%1': member of JAR"</b>
<b>Constant</b>	CLASS_MEMBER_OF_JAR
<b>SAP Sybase Error Number</b>	2279
<b>SQL State</b>	WP004
<b>SQL Code</b>	-653L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 653</b>	<b>"Cannot remove class "%1": member of JAR"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the class file that cannot be removed.
<b>Probable Cause</b>	You attempted to remove a class file that is still part of a JAR. It must be removed with the JAR.
<b>Error 654</b>	<b>"The connection parameters file could not be found"</b>
<b>Constant</b>	NO_PROFILE_FILE
<b>SAP Sybase Error Number</b>	2280
<b>SQL State</b>	08W37
<b>SQL Code</b>	-654L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	An attempt was made to parse a connection string containing a connection profile but the connection parameters file could not be found.
<b>Error 655</b>	<b>"Error parsing connection parameter string"</b>
<b>Constant</b>	GEN_PARSE_ERROR
<b>SAP Sybase Error Number</b>	2281
<b>SQL State</b>	08W38
<b>SQL Code</b>	-655L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The connection string could not be parsed. The string or connection parameter file contains a syntax error.
<b>Error 656</b>	<b>"Unable to connect to server "%1": %2"</b>
<b>Constant</b>	OMNI_CONNECT_ERROR

<b>Error 656</b>	<b>"Unable to connect to server '%1': %2"</b>
<b>SAP Sybase Error Number</b>	2282
<b>SQL State</b>	WO001
<b>SQL Code</b>	-656L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the server that could not be connected to.
<b>Parameter 2</b>	A more specific reason returned from the server class driver.
<b>Probable Cause</b>	You attempted to connect to a remote server. Check that the remote server is running.
<b>Error 657</b>	<b>"Unable to connect, server definition is circular"</b>
<b>Constant</b>	OMNI_CIRCULAR_CONNECT
<b>SAP Sybase Error Number</b>	2552
<b>SQL State</b>	WO002
<b>SQL Code</b>	-657L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to connect to a remote server that maps to the local database.
<b>Error 658</b>	<b>"Remote server '%1' is currently configured as read-only"</b>
<b>Constant</b>	OMNI_READONLY
<b>SAP Sybase Error Number</b>	2284
<b>SQL State</b>	WO003
<b>SQL Code</b>	-658L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 658</b>	<b>"Remote server '%1' is currently configured as read-only"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the remote server.
<b>Probable Cause</b>	You attempted to perform an update on an object located on a server that is configured as read-only. Use ALTER SERVER to reconfigure the remote server to be updatable.
<b>Error 659</b>	<b>"Remote server '%1' could not be found"</b>
<b>Constant</b>	OMNI_SERVER_NOT_FOUND
<b>SAP Sybase Error Number</b>	2285
<b>SQL State</b>	WO004
<b>SQL Code</b>	-659L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	Name of the remote server.
<b>Probable Cause</b>	You attempted to define an object on a server that has not been added. Use CREATE SERVER to add the remote server definition.

## Messages 660 through 681

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 660</b>	<b>"Server '%1': %2"</b>
<b>Constant</b>	OMNI_REMOTE_ERROR
<b>SAP Sybase Error Number</b>	2286
<b>SQL State</b>	WO005
<b>SQL Code</b>	-660L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 660</b>	<b>"Server "%1": %2"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the remote server.
<b>Parameter 2</b>	The message from the remote server.
<b>Probable Cause</b>	A message was generated by a remote server. The message text is included.
<b>Error 661</b>	<b>"Backward scrolling cursors are not supported for remote objects"</b>
<b>Constant</b>	OMNI_BACKWARDS_CURSOR
<b>SAP Sybase Error Number</b>	2287
<b>SQL State</b>	WO006
<b>SQL Code</b>	-661L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Backward scrolling cursors are not supported for remote objects. Use forward scrolling cursors only.
<b>Error 662</b>	<b>"Cannot serialize Java object with class "%1"</b>
<b>Constant</b>	JAVA_SERIALIZATION_ERROR
<b>SAP Sybase Error Number</b>	2288
<b>SQL State</b>	WI009
<b>SQL Code</b>	-662L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The class of the value that cannot be serialized.
<b>Probable Cause</b>	The Java object cannot be serialized as a persistent database column.

## Errors and Warnings

<b>Error 663</b>	<b>"Cannot deserialize Java object"</b>
<b>Constant</b>	JAVA_DESERIALIZATION_ERROR
<b>SAP Sybase Error Number</b>	2289
<b>SQL State</b>	WW018
<b>SQL Code</b>	-663L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The persistent Java object cannot be read from the database column. Possibly, the class of the object has been removed or modified.
<b>Error 664</b>	<b>"Database is active"</b>
<b>Constant</b>	DATABASE_ACTIVE
<b>SAP Sybase Error Number</b>	2290
<b>SQL State</b>	08W40
<b>SQL Code</b>	-664L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The attempted operation (CREATE ENCRYPTED, CREATE DECRYPTED, ALTER DATABASE) cannot be performed while the database is running. Stop the database to perform the operation.
<b>Error 665</b>	<b>"Database \'%1\' needs recovery"</b>
<b>Constant</b>	DATABASE_NEEDS_RECOVERY
<b>SAP Sybase Error Number</b>	2291
<b>SQL State</b>	08W41
<b>SQL Code</b>	-665L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 665</b>	<b>"Database \"%1\" needs recovery"</b>
<b>Severity Code</b>	<i>21</i> on page 2
<b>Parameter 1</b>	The file name of the database that needs recovery.
<b>Probable Cause</b>	The database quit abnormally the last time it was used. Database recovery must be performed before proceeding.
<b>Error 666</b>	<b>"The remote table '%1' could not be found"</b>
<b>Constant</b>	OMNI_RMT_TABLE_NOTFOUND
<b>SAP Sybase Error Number</b>	2292
<b>SQL State</b>	WO007
<b>SQL Code</b>	-666L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The complete name of the remote table.
<b>Probable Cause</b>	The table could not be found on the remote server. Check the remote table name and the user privileges on that table.
<b>Error 667</b>	<b>"Could not access column information for the table "%1"</b>
<b>Constant</b>	OMNI_RMT_COLUMNS_NOTFOUND
<b>SAP Sybase Error Number</b>	2293
<b>SQL State</b>	WO008
<b>SQL Code</b>	-667L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The complete name of the remote table.
<b>Probable Cause</b>	Column information for the table could not be accessed. Check permissions for the table.

## Errors and Warnings

<b>Error 668</b>	<b>"Cursor is restricted to FETCH NEXT operations"</b>
<b>Constant</b>	NO_SCROLL_CURSOR
<b>SAP Sybase Error Number</b>	2294
<b>SQL State</b>	09W06
<b>SQL Code</b>	-668L
<b>ODBC 2 State</b>	S1106
<b>ODBC 3 State</b>	HY106
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	An illegal FETCH operation has been detected for a NO SCROLL cursor. For a forward-only cursor the only permitted FETCH operations are FETCH RELATIVE 0 and FETCH NEXT (FETCH RELATIVE 1).
<b>Error 669</b>	<b>"Method '%1' cannot be called at this time"</b>
<b>Constant</b>	METHOD_CANNOT_BE_CALLED
<b>SAP Sybase Error Number</b>	2295
<b>SQL State</b>	WJ001
<b>SQL Code</b>	-669L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the method.
<b>Probable Cause</b>	The method cannot be called at this time. Check that the method is not being called out of order.
<b>Error 670</b>	<b>"Invalid class byte code"</b>
<b>Constant</b>	BAD_CLASS_BYTE_CODE
<b>SAP Sybase Error Number</b>	2296
<b>SQL State</b>	WP005
<b>SQL Code</b>	-670L

<b>Error 670</b>	<b>"Invalid class byte code"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A binary expression passed to the INSTALL JAVA statement was not a valid Java class.
<b>Error 672</b>	<b>"Database upgrade failed"</b>
<b>Constant</b>	DATABASE_UPGRADE_FAILED
<b>SAP Sybase Error Number</b>	2298
<b>SQL State</b>	08W42
<b>SQL Code</b>	-672L
<b>ODBC 2 State</b>	08004
<b>ODBC 3 State</b>	08004
<b>Severity Code</b>	<i>20</i> on page 2
<b>Probable Cause</b>	Your attempt to upgrade a database failed. This could be caused by a failure to locate one of the SQL script files used to define the system table changes.
<b>Error 673</b>	<b>"Database upgrade not possible"</b>
<b>Constant</b>	DATABASE_UPGRADE_NOT_POSSIBLE
<b>SAP Sybase Error Number</b>	2299
<b>SQL State</b>	08W43
<b>SQL Code</b>	-673L
<b>ODBC 2 State</b>	08004
<b>ODBC 3 State</b>	08004
<b>Severity Code</b>	<i>21</i> on page 2
<b>Probable Cause</b>	An attempt to upgrade a database failed. The database is too old to be upgraded.

## Errors and Warnings

<b>Error 674</b>	<b>"Statement's size limit is invalid"</b>
<b>Constant</b>	INVALID_CURSOR_RANGE
<b>SAP Sybase Error Number</b>	2300
<b>SQL State</b>	09W07
<b>SQL Code</b>	-674L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	FIRST or TOP n are used in a SELECT statement to limit the size of a result. The size limit must be a constant integer greater than 0 and less than 32767.
<b>Error 675</b>	<b>"External environment could not be started, "%1' could not be found"</b>
<b>Constant</b>	EXTENV_NOT_STARTED
<b>SAP Sybase Error Number</b>	2301
<b>SQL State</b>	WP006
<b>SQL Code</b>	-675L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The component (executable or file) that could not be found and is needed to run the VM.
<b>Probable Cause</b>	A problem was encountered starting the External Environment. A component that is needed to run the environment could not be found.
<b>Error 676</b>	<b>"The specified transaction isolation is invalid"</b>
<b>Constant</b>	INVALID_TRANSACTION_ISOLATION
<b>SAP Sybase Error Number</b>	2303
<b>SQL State</b>	WJ003

<b>Error 676</b>	<b>"The specified transaction isolation is invalid"</b>
<b>SQL Code</b>	-676L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	The specified transaction isolation is invalid.
<b>Error 677</b>	<b>"Table '%1' has a foreign key with a referential action"</b>
<b>Constant</b>	TABLE_HAS_REFACTION
<b>SAP Sybase Error Number</b>	2304
<b>SQL State</b>	56001
<b>SQL Code</b>	-677L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the table with the referential action.
<b>Probable Cause</b>	The table could not be renamed as it has a foreign key with a referential action. To rename the table, first drop the foreign key constraints.
<b>Error 678</b>	<b>"Index name '%1' is ambiguous"</b>
<b>Constant</b>	AMBIGUOUS_INDEX_NAME
<b>SAP Sybase Error Number</b>	2305
<b>SQL State</b>	52W40
<b>SQL Code</b>	-678L
<b>ODBC 2 State</b>	S0011
<b>ODBC 3 State</b>	42S11
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the ambiguous index.

## Errors and Warnings

<b>Error 678</b>	<b>"Index name '%1' is ambiguous"</b>
<b>Probable Cause</b>	A statement has referred to an index name that is not unique. Preface the index name with the table and/or owner name.
<b>Error 680</b>	<b>"Invalid expression in WHERE clause of Transact-SQL outer join"</b>
<b>Constant</b>	INVALID_TSQL_OJ_EXPRESSION
<b>SAP Sybase Error Number</b>	2307
<b>SQL State</b>	52W23
<b>SQL Code</b>	-680L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	An expression in the WHERE clause of a query that uses Transact-SQL syntax contains a comparison of a column from the NULL-supplying table with a subquery or an expression that references a column from another table.
<b>Error 681</b>	<b>"Invalid join type used with Transact-SQL outer join"</b>
<b>Constant</b>	INVALID_TSQL_JOIN_TYPE
<b>SAP Sybase Error Number</b>	2308
<b>SQL State</b>	52W24
<b>SQL Code</b>	-681L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	An invalid join type was used with a query that contains Transact-SQL outer join comparison operators.

## Messages 682 through 709

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 682</b>	"%1"
<b>Constant</b>	OMNI_DEBUG
<b>SAP Sybase Error Number</b>	2309
<b>SQL State</b>	WO010
<b>SQL Code</b>	-682L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The debug message for the console.
<b>Probable Cause</b>	This message is used for displaying component integration services debug messages in the messages window.
<b>Error 683</b>	<b>"The cursor name "%1' already exists"</b>
<b>Constant</b>	DUPLICATE_CURSOR_NAME
<b>SAP Sybase Error Number</b>	2312
<b>SQL State</b>	WJ004
<b>SQL Code</b>	-683L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the cursor.
<b>Probable Cause</b>	You attempted to declare a cursor with a name that already exists. Cursor names must be unique within a connection.
<b>Error 684</b>	<b>"Rollback occurred due to deadlock during prefetch"</b>
<b>Constant</b>	ROLLBACK_ON_PREFETCH

## Errors and Warnings

<b>Error 684</b>	<b>"Rollback occurred due to deadlock during prefetch"</b>
<b>SAP Sybase Error Number</b>	2313
<b>SQL State</b>	WW019
<b>SQL Code</b>	-684L
<b>ODBC 2 State</b>	40001
<b>ODBC 3 State</b>	40001
<b>Severity Code</b>	<i>13</i> on page 2
<b>Probable Cause</b>	One of the cursors that was opened with prefetch enabled was performing fetch operations, and a deadlock occurred during a prefetch. This is a deadlock situation and your transaction has been chosen as the one to rollback. The request that received this error was not executed, unless the request was to close the cursor, in which case the cursor was closed.

<b>Error 685</b>	<b>"Resource governor for '%1' exceeded"</b>
<b>Constant</b>	RESOURCE_GOVERNOR_EXCEEDED
<b>SAP Sybase Error Number</b>	2314
<b>SQL State</b>	WP009
<b>SQL Code</b>	-685L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>19</i> on page 2
<b>Parameter 1</b>	The resource whose limit has been exceeded.
<b>Probable Cause</b>	The resource governor for the stated resource has determined that the usage of the resource has exceeded its limit.

<b>Error 686</b>	<b>"Insufficient cache to start Java VM"</b>
<b>Constant</b>	JAVA_VM_INSUFFICIENT_CACHE
<b>SAP Sybase Error Number</b>	2524
<b>SQL State</b>	WP015
<b>SQL Code</b>	-686L

<b>Error 686</b>	<b>"Insufficient cache to start Java VM"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Insufficient cache was available to start the Java VM. Restart the database server with a larger cache size.
<b>Error 687</b>	<b>"Syntax error, cannot specify SAP Sybase IQ specific options without specifying IQ PATH"</b>
<b>Constant</b>	IQ_PATH_SYNTAX_ERROR
<b>SAP Sybase Error Number</b>	2072
<b>SQL State</b>	42W48
<b>SQL Code</b>	-687L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	The IQ PATH clause must be specified when one or more options specified in the CREATE DATABASE statement are SAP Sybase IQ specific.
<b>Error 689</b>	<b>"Input parameter index out of range"</b>
<b>Constant</b>	BAD_PARAM_INDEX
<b>SAP Sybase Error Number</b>	2317
<b>SQL State</b>	WJ005
<b>SQL Code</b>	-689L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The range for valid parameters is from 1 up to the number of host variables specified in the prepared/callable statement.

## Errors and Warnings

<b>Error 691</b>	<b>"Could not load the backup/restore DLL \%"1\No message</b>
<b>Constant</b>	BACKUP_NOT_LOADED
<b>SAP Sybase Error Number</b>	2319
<b>SQL State</b>	08W44
<b>SQL Code</b>	-691L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>19</i> on page 2
<b>Parameter 1</b>	The name of the DLL that could not be loaded.
<b>Probable Cause</b>	An attempt to load the backup/restore DLL failed.
<b>Error 692</b>	<b>"Could not execute backup/restore DLL (%1) entry point"</b>
<b>Constant</b>	BACKUP_ENTRY_NOT_FOUND
<b>SAP Sybase Error Number</b>	2320
<b>SQL State</b>	08W45
<b>SQL Code</b>	-692L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>19</i> on page 2
<b>Parameter 1</b>	The name of the entry point that could not be found.
<b>Probable Cause</b>	An attempt to locate or execute the backup/restore DLL entry point failed.
<b>Error 697</b>	<b>"Error during backup/restore: %1"</b>
<b>Constant</b>	BACKUP_ERROR
<b>SAP Sybase Error Number</b>	2325
<b>SQL State</b>	08W46
<b>SQL Code</b>	-697L
<b>ODBC 2 State</b>	ERROR

<b>Error 697</b>	"Error during backup/restore: %1"
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>21</i> on page 2
<b>Parameter 1</b>	A message describing the error that occurred.
<b>Probable Cause</b>	An error occurred during a BACKUP or RESTORE statement.
<b>Error 698</b>	<b>"The remote server does not support an auto-incrementing data type"</b>
<b>Constant</b>	OMNI_AUTOINC_NOT_SUPPORTED
<b>SAP Sybase Error Number</b>	2329
<b>SQL State</b>	WO011
<b>SQL Code</b>	-698L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>12</i> on page 2
<b>Probable Cause</b>	Auto-incrementing data types can only be supported in a proxy table when the remote server supports this feature.
<b>Error 700</b>	<b>"SQLDA fields inconsistent for a multi-row SQLDA"</b>
<b>Constant</b>	SQLDA_INCONSISTENT
<b>SAP Sybase Error Number</b>	2328
<b>SQL State</b>	07W04
<b>SQL Code</b>	-700L
<b>ODBC 2 State</b>	07001
<b>ODBC 3 State</b>	07W04
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Not all of the rows in a multi-row SQLDA have been defined identically for an array operation (insert, fetch, or execute). A given column must be defined the same (type and length) in each row.

## Errors and Warnings

<b>Error 702</b>	<b>"TRUNCATE TABLE statement cannot be used on a view"</b>
<b>Constant</b>	CANNOT_TRUNCATE_VIEW
<b>SAP Sybase Error Number</b>	2330
<b>SQL State</b>	42W49
<b>SQL Code</b>	-702L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to use TRUNCATE TABLE on a view, which is not permitted.
<b>Error 703</b>	<b>"Cannot insert or update computed column '%1'"</b>
<b>Constant</b>	COMPUTED_COLUMN_WRITE_ATTEMPTED
<b>SAP Sybase Error Number</b>	2331
<b>SQL State</b>	WW023
<b>SQL Code</b>	-703L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the column.
<b>Probable Cause</b>	Computed column values cannot be modified explicitly. Their value is determined implicitly from the computed expression value.
<b>Error 704</b>	<b>"Cannot create an index on Java class '%1'"</b>
<b>Constant</b>	CANNOT_INDEX_ON_JAVA_CLASS
<b>SAP Sybase Error Number</b>	2332
<b>SQL State</b>	WW022
<b>SQL Code</b>	-704L
<b>ODBC 2 State</b>	ERROR

<b>Error 704</b>	<b>"Cannot create an index on Java class "%1"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the class.
<b>Probable Cause</b>	An operation requiring an index was attempted in which an attempt was made to create an index on a Java class type.
<b>Error 705</b>	<b>"Return type of void from procedure '%1' cannot be used in any expression"</b>
<b>Constant</b>	PROCEDURE RETURNS VOID
<b>SAP Sybase Error Number</b>	2333
<b>SQL State</b>	53019
<b>SQL Code</b>	-705L
<b>ODBC 2 State</b>	07006
<b>ODBC 3 State</b>	07006
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the procedure.
<b>Probable Cause</b>	The Java type void does not map onto any SQL type, hence a procedure returning void cannot be used in any SQL expression.
<b>Error 706</b>	<b>"Remote server does not have the ability to support this statement"</b>
<b>Constant</b>	OMNI_SERVER_NOT_CAPABLE
<b>SAP Sybase Error Number</b>	2334
<b>SQL State</b>	WO012
<b>SQL Code</b>	-706L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to execute a statement that requires a capability that is not supported by a remote server.

## Errors and Warnings

<b>Error 707</b>	<b>"Statement is not allowed in passthrough mode"</b>
<b>Constant</b>	STMT_NOT_ALLOWED_IN_PASSTHROUGH
<b>SAP Sybase Error Number</b>	2335
<b>SQL State</b>	0AW05
<b>SQL Code</b>	-707L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You tried to execute a statement that cannot be executed while in passthrough mode. For example, you may have executed a batch statement.
<b>Error 708</b>	<b>"READTEXT or WRITETEXT statement cannot refer to a view"</b>
<b>Constant</b>	TEXT_OPERATION_ON_VIEW
<b>SAP Sybase Error Number</b>	2336
<b>SQL State</b>	42W50
<b>SQL Code</b>	-708L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A Transact-SQL READTEXT or WRITETEXT statement cannot refer to text columns in a view. Replace the view reference with the name of a base table.
<b>Error 709</b>	<b>"Computed columns are not supported in this database"</b>
<b>Constant</b>	COMPUTED_COLUMNS_NOT_SUPPORTED
<b>SAP Sybase Error Number</b>	2337
<b>SQL State</b>	0AW06
<b>SQL Code</b>	-709L

<b>Error 709</b>	"Computed columns are not supported in this database"
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The current database is an older database and does not have catalog support for computed (materialized) columns. To use this feature, upgrade your database to the most recent version.

## Messages 710 through 731

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 710</b>	"Invalid comparison"
<b>Constant</b>	INVALID_COMPARISON
<b>SAP Sybase Error Number</b>	2338
<b>SQL State</b>	52W25
<b>SQL Code</b>	-710L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	An attempt was made to compare two arguments that do not support comparison. For example, it is not valid to compare a Java object with another Java object, unless the class of the object supports a valid compareTo method.

<b>Error 711</b>	"Incorrect database store DLL (%1) version"
<b>Constant</b>	STORE_VERSION_MISMATCH
<b>SAP Sybase Error Number</b>	2340
<b>SQL State</b>	08W47
<b>SQL Code</b>	-711L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 711</b>	<b>"Incorrect database store DLL (%1) version"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>19</i> on page 2
<b>Parameter 1</b>	The name of the database store DLL.
<b>Probable Cause</b>	The database store DLL and server DLL versions do not match.
<b>Error 712</b>	<b>"External login for server '%1' could not be found"</b>
<b>Constant</b>	OMNI_EXTLOGIN_NOT_FOUND
<b>SAP Sybase Error Number</b>	2339
<b>SQL State</b>	WO013
<b>SQL Code</b>	-712L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The name of the remote server.
<b>Probable Cause</b>	An external login for the server and user does not exist.
<b>Error 715</b>	<b>"Contents of backup files are inconsistent"</b>
<b>Constant</b>	RESTORE_INCONSISTENT
<b>SAP Sybase Error Number</b>	2344
<b>SQL State</b>	WB006
<b>SQL Code</b>	-715L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Probable Cause</b>	During a RESTORE, the contents of a backup that was done to two or more disk or tape devices were found to be inconsistent.
<b>Error 716</b>	<b>"Backup file format is invalid"</b>
<b>Constant</b>	RESTORE_INVALID_FORMAT

<b>Error 716</b>	<b>"Backup file format is invalid"</b>
<b>SAP Sybase Error Number</b>	2345
<b>SQL State</b>	WB007
<b>SQL Code</b>	-716L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>21</i> on page 2
<b>Probable Cause</b>	The format of an archive file to be used during a RESTORE is invalid.
<b>Error 717</b>	<b>"RESTORE unable to open file "%1"</b>
<b>Constant</b>	RESTORE_UNABLE_TO_OPEN
<b>SAP Sybase Error Number</b>	2346
<b>SQL State</b>	WB008
<b>SQL Code</b>	-717L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>21</i> on page 2
<b>Parameter 1</b>	File name of database file.
<b>Probable Cause</b>	RESTORE was unable to open one of the database files.
<b>Error 718</b>	<b>"RESTORE unable to write to file "%1"</b>
<b>Constant</b>	RESTORE_UNABLE_TO_WRITE
<b>SAP Sybase Error Number</b>	2347
<b>SQL State</b>	WB009
<b>SQL Code</b>	-718L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>21</i> on page 2
<b>Parameter 1</b>	File name of database file.

## Errors and Warnings

<b>Error 718</b>	<b>"RESTORE unable to write to file "%1"</b>
<b>Probable Cause</b>	RESTORE was unable to write to one of the database files.
<b>Error 719</b>	<b>"RESTORE unable to start database "%1"</b>
<b>Constant</b>	RESTORE_UNABLE_TO_START
<b>SAP Sybase Error Number</b>	2348
<b>SQL State</b>	WB010
<b>SQL Code</b>	-719L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>21</i> on page 2
<b>Parameter 1</b>	File name of database file.
<b>Probable Cause</b>	After a RESTORE, the resulting database could not be started.
<b>Error 720</b>	<b>"VALIDATE statement must refer to a base table"</b>
<b>Constant</b>	CANNOT_VALIDATE_OBJECT
<b>SAP Sybase Error Number</b>	2349
<b>SQL State</b>	42W51
<b>SQL Code</b>	-720L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The VALIDATE statement must refer to a local base table; it cannot refer to a view, an SAP Sybase IQ table, or an object on a remote server.
<b>Error 721</b>	<b>"The data type specified for column "%1' is not compatible with the actual data type"</b>
<b>Constant</b>	OMNI_DATATYPE_MISMATCH
<b>SAP Sybase Error Number</b>	2354

<b>Error 721</b>	<b>"The data type specified for column '%1' is not compatible with the actual data type"</b>
<b>SQL State</b>	WO015
<b>SQL Code</b>	-721L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>12</i> on page 2
<b>Parameter 1</b>	The name of the column.
<b>Probable Cause</b>	The data type of the column specified in the CREATE EXISTING statement is not compatible with the actual data type of the column in the remote table.

<b>Error 722</b>	<b>"The column '%1' does not exist in the remote table"</b>
<b>Constant</b>	OMNI_NOSUCH_COLUMN
<b>SAP Sybase Error Number</b>	2355
<b>SQL State</b>	WO016
<b>SQL Code</b>	-722L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The name of the column.
<b>Probable Cause</b>	The column specified in the CREATE EXISTING statement does not exist in the remote table.

<b>Error 723</b>	<b>"The length specified for column '%1' is different than the actual length"</b>
<b>Constant</b>	OMNI_LENGTH_MISMATCH
<b>SAP Sybase Error Number</b>	2356
<b>SQL State</b>	WO017
<b>SQL Code</b>	-723L
<b>ODBC 2 State</b>	OK

## Errors and Warnings

<b>Error 723</b>	<b>"The length specified for column '%1' is different than the actual length"</b>
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the column.
<b>Probable Cause</b>	The length of the column specified in the CREATE EXISTING statement is different than the length of the column in the remote table.
<b>Error 724</b>	<b>"NULL attribute mismatch for column '%1'"</b>
<b>Constant</b>	OMNI_NULL_MISMATCH
<b>SAP Sybase Error Number</b>	2357
<b>SQL State</b>	WO018
<b>SQL Code</b>	-724L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the column.
<b>Probable Cause</b>	The NULL attribute of the column specified in the CREATE EXISTING statement differs from the NULL attribute of the actual column.
<b>Error 725</b>	<b>"Identity attribute mismatch for column '%1'"</b>
<b>Constant</b>	OMNI_IDENTITY_MISMATCH
<b>SAP Sybase Error Number</b>	2358
<b>SQL State</b>	WO019
<b>SQL Code</b>	-725L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the column.

<b>Error 725</b>	<b>"Identity attribute mismatch for column "%1"</b>
<b>Probable Cause</b>	The identity attribute of the column specified in the CREATE EXISTING statement differs from the identity attribute of the actual column.
<b>Error 726</b>	<b>"The table specification "%1' identifies more than one remote table"</b>
<b>Constant</b>	OMNI_RMT_TABLE_NOTUNIQUE
<b>SAP Sybase Error Number</b>	2359
<b>SQL State</b>	WO020
<b>SQL Code</b>	-726L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The complete name of the remote table.
<b>Probable Cause</b>	More than one table was found on the remote server for the given table specification. Add a database or owner name to the specification.
<b>Error 727</b>	<b>"The optimizer was unable to construct a valid access plan"</b>
<b>Constant</b>	CANNOT_OPTIMIZE_QUERY
<b>SAP Sybase Error Number</b>	2362
<b>SQL State</b>	WI010
<b>SQL Code</b>	-727L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>18</i> on page 2
<b>Probable Cause</b>	The database server was unable to construct a valid access plan for the given request. This is a SQL Anywhere internal error. If it can be reproduced, it should be reported to SAP Sybase. You may be able to work around this problem by modifying the query statement.

## Errors and Warnings

<b>Error 728</b>	<b>"Update operation attempted on non-updatable remote query"</b>
<b>Constant</b>	NON_UPDATEABLE_EXT_TAB
<b>SAP Sybase Error Number</b>	2372
<b>SQL State</b>	42W35
<b>SQL Code</b>	-728L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You attempted an update or delete operation on a remote table that is currently not supported. Examples of such operations include positioned updates or deletes and updates or deletes that involve a join between local and proxy tables. Updates or deletes that involve a join between proxy tables on different remote servers will also give this error.

<b>Error 729</b>	<b>"The specified foreign key (%1) cannot be enforced"</b>
<b>Constant</b>	UNENFORCEABLE_FOREIGN_KEY
<b>SAP Sybase Error Number</b>	2373
<b>SQL State</b>	23507
<b>SQL Code</b>	-729L
<b>ODBC 2 State</b>	23000
<b>ODBC 3 State</b>	23000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the foreign key.
<b>Probable Cause</b>	You attempted to create a foreign key that cannot be enforced. To be enforceable, the primary and foreign table for the specified key must exist on the same server. You can use the UNENFORCED keyword to create a foreign key specification that is not to be enforced.

<b>Error 730</b>	<b>"Invalid JAR file"</b>
<b>Constant</b>	BAD_JAR_FILE

<b>Error 730</b>	<b>"Invalid JAR file"</b>
<b>SAP Sybase Error Number</b>	2374
<b>SQL State</b>	WP010
<b>SQL Code</b>	-730L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A file passed to the INSTALL JAVA statement was not a valid JAR file.
<b>Error 731</b>	<b>"Cannot drop a user that owns objects involved in replication"</b>
<b>Constant</b>	USER_OWNS_REPLICATED_OBJECTS
<b>SAP Sybase Error Number</b>	2377
<b>SQL State</b>	55W06
<b>SQL Code</b>	-731L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to drop a user that is the creator of a database object involved in replication. For example, the user may own a table that is part of a publication.

## Messages 732 through 760

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 732</b>	<b>"Creating remote tables with computed columns is not supported"</b>
<b>Constant</b>	OMNI_COMPUTED_NOT_SUPPORTED
<b>SAP Sybase Error Number</b>	2366

## Errors and Warnings

<b>Error 732</b>	<b>"Creating remote tables with computed columns is not supported"</b>
<b>SQL State</b>	WO021
<b>SQL Code</b>	-732L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>12</i> on page 2
<b>Probable Cause</b>	Computed columns are not supported in CREATE TABLE statements that specify a remote location.
<b>Error 733</b>	<b>"Number of columns allowing NULLs exceeds limit"</b>
<b>Constant</b>	TOO_MANY_NULL_COLUMNS
<b>SAP Sybase Error Number</b>	2378
<b>SQL State</b>	23504
<b>SQL Code</b>	-733L
<b>ODBC 2 State</b>	23000
<b>ODBC 3 State</b>	23000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to create or modify a table definition such that the number of columns that allow NULLS is now more than the limit on such columns. The limit is a function of database page size and is approximately 8*(page-size - 30).
<b>Error 734</b>	<b>"Cannot update or delete an all-NULL row from table "%1"</b>
<b>Constant</b>	CANNOT_UPDATE_NULL_ROW
<b>SAP Sybase Error Number</b>	2379
<b>SQL State</b>	09W08
<b>SQL Code</b>	-734L
<b>ODBC 2 State</b>	42000

<b>Error 734</b>	<b>"Cannot update or delete an all-NULL row from table "%1"</b>
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the table that cannot be modified.
<b>Probable Cause</b>	You attempted to modify or delete a row in the specified table, which is part of the NULL-supplying side of an outer join. However, the cursor is currently positioned on a derived row that contains an all-NULL row for this table, which is the result of the failure of one or more ON conditions to evaluate to TRUE. Verify that the UPDATE or DELETE statement is correct.

<b>Error 735</b>	<b>"Invalid parameter"</b>
<b>Constant</b>	INVALID_PARAMETER
<b>SAP Sybase Error Number</b>	2030
<b>SQL State</b>	08W24
<b>SQL Code</b>	-735L
<b>ODBC 2 State</b>	08004
<b>ODBC 3 State</b>	08004
<b>Severity Code</b>	<i>18</i> on page 2
<b>Probable Cause</b>	An error occurred while evaluating a parameter.

<b>Error 736</b>	<b>"The data type of column or variable "%1' is not supported"</b>
<b>Constant</b>	OMNI_UNSUPPORTED_DATATYPE
<b>SAP Sybase Error Number</b>	2367
<b>SQL State</b>	WO022
<b>SQL Code</b>	-736L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>12</i> on page 2
<b>Parameter 1</b>	The name of the column or variable.

## Errors and Warnings

<b>Error 736</b>	<b>"The data type of column or variable "%1' is not supported"</b>
<b>Probable Cause</b>	The column is defined with a data type that is not supported for remote tables or the variable is defined with a datatype that is not supported for using and location clauses.
<b>Error 737</b>	<b>"Signature '%1' does not match procedure parameters"</b>
<b>Constant</b>	SIGNATURE_MISMATCH
<b>SAP Sybase Error Number</b>	2382
<b>SQL State</b>	42W54
<b>SQL Code</b>	-737L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The value of the signature.
<b>Probable Cause</b>	The number of types in the signature must match the number of procedure parameters. If a DYNAMIC RESULT SETS clause was specified, the number of dynamic result sets must match the quantity found in the signature.
<b>Error 738</b>	<b>"Password must be at least %1 characters"</b>
<b>Constant</b>	PASSWORD_TOO_SHORT
<b>SAP Sybase Error Number</b>	2383
<b>SQL State</b>	54W07
<b>SQL Code</b>	-738L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	54000
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	The password is shorter than that allowed by the current min_password_length option setting.
<b>Error 739</b>	<b>"db_init has not been called or the call to db_init failed"</b>
<b>Constant</b>	DB_INIT_NOT_CALLED

<b>Error 739</b>	<b>"db_init has not been called or the call to db_init failed"</b>
<b>SAP Sybase Error Number</b>	2386
<b>SQL State</b>	55W07
<b>SQL Code</b>	-739L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The SQLCA passed to a dblib entry point has not been initialized by a call to db_init or the call to db_init failed.
<b>Error 740</b>	<b>"The communications environment could not be created"</b>
<b>Constant</b>	FAILED_TO_CREATE_STREAMS_ENV
<b>SAP Sybase Error Number</b>	2385
<b>SQL State</b>	WW024
<b>SQL Code</b>	-740L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The communications environment could not be created. Either there are insufficient resources to create the environment or the language resource file cannot be found.
<b>Error 744</b>	<b>"Invalid SAP Sybase IQ database command line option or parameter value: %1"</b>
<b>Constant</b>	IQ_INVALID_COMMAND_LINE
<b>SAP Sybase Error Number</b>	2390
<b>SQL State</b>	08W51
<b>SQL Code</b>	-744L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001

## Errors and Warnings

<b>Error 744</b>	<b>"Invalid SAP Sybase IQ database command line option or parameter value: %1"</b>
<b>Severity Code</b>	<i>18</i> on page 2
<b>Parameter 1</b>	The command line option that is invalid.
<b>Probable Cause</b>	An invalid command line option was used. The option began with -iq, but is either invalid or contained a bad parameter.
<b>Error 745</b>	<b>"Cannot initialize SAP Sybase IQ memory manager: %1"</b>
<b>Constant</b>	IQ_MEMORY_MANAGER_FAILED
<b>SAP Sybase Error Number</b>	2391
<b>SQL State</b>	08W52
<b>SQL Code</b>	-745L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>18</i> on page 2
<b>Parameter 1</b>	A message describing the error that occurred.
<b>Probable Cause</b>	System V shared memory was requested but could not be allocated.
<b>Error 746</b>	<b>"Cannot allocate System V resources"</b>
<b>Constant</b>	IQ_SYSTEM_V_FAILURE
<b>SAP Sybase Error Number</b>	2392
<b>SQL State</b>	08W53
<b>SQL Code</b>	-746L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>18</i> on page 2
<b>Probable Cause</b>	SAP Sybase IQ was unable to allocate System V resources. Delete unused System V semaphores and shared memory segments or increase operating system configuration values for these resources.

<b>Error 749</b>	<b>"Feature not available with UltraLite"</b>
<b>Constant</b>	NOT_SUPPORTED_IN_ULTRALITE
<b>SAP Sybase Error Number</b>	2395
<b>SQL State</b>	0AW07
<b>SQL Code</b>	-749L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to execute a statement or use a feature that is not supported in an UltraLite database.
<b>Error 750</b>	<b>"User owns procedures in use"</b>
<b>Constant</b>	USER_OWNS_PROCEDURES_IN_USE
<b>SAP Sybase Error Number</b>	2396
<b>SQL State</b>	42W55
<b>SQL Code</b>	-750L
<b>ODBC 2 State</b>	40001
<b>ODBC 3 State</b>	40001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to drop a user that owns a procedure being used by other active users of the database.
<b>Error 751</b>	<b>"User owns tables in use"</b>
<b>Constant</b>	USER_OWNS_TABLES_IN_USE
<b>SAP Sybase Error Number</b>	2397
<b>SQL State</b>	42W56
<b>SQL Code</b>	-751L
<b>ODBC 2 State</b>	40001
<b>ODBC 3 State</b>	40001

## Errors and Warnings

<b>Error 751</b>	<b>"User owns tables in use"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to REVOKE CONNECT from a user that owns a table being used by other active users of the database.
<b>Error 754</b>	<b>"Parse error: %1"</b>
<b>Constant</b>	INVALID_DSN_NAME
<b>SAP Sybase Error Number</b>	2400
<b>SQL State</b>	08W54
<b>SQL Code</b>	-754L
<b>ODBC 2 State</b>	08004
<b>ODBC 3 State</b>	08004
<b>Severity Code</b>	<i>18</i> on page 2
<b>Parameter 1</b>	The invalid data source name.
<b>Probable Cause</b>	An invalid data source name was used in the connection string.
<b>Error 755</b>	<b>"You cannot synchronize or upgrade with uncommitted transactions"</b>
<b>Constant</b>	UNCOMMITTED_TRANSACTIONS
<b>SAP Sybase Error Number</b>	2401
<b>SQL State</b>	0AW08
<b>SQL Code</b>	-755L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to synchronize or upgrade the schema of an UltraLite database and there are changes in the UltraLite database that have not been committed.
<b>Error 757</b>	<b>"Modifications not permitted for read-only database"</b>
<b>Constant</b>	READ_ONLY_DATABASE

<b>Error 757</b>	<b>"Modifications not permitted for read-only database"</b>
<b>SAP Sybase Error Number</b>	2404
<b>SQL State</b>	55W08
<b>SQL Code</b>	-757L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	You attempted an update operation on a database that was declared as read-only.

<b>Error 759</b>	<b>"SQLDA data type invalid"</b>
<b>Constant</b>	SQLDA_INVALID_DATATYPE
<b>SAP Sybase Error Number</b>	2406
<b>SQL State</b>	07W05
<b>SQL Code</b>	-759L
<b>ODBC 2 State</b>	07001
<b>ODBC 3 State</b>	07W05
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The data type specified for a SQLDA variable is invalid.

<b>Error 760</b>	<b>"Invalid SQL identifier"</b>
<b>Constant</b>	INVALID_SQL_IDENTIFIER
<b>SAP Sybase Error Number</b>	2407
<b>SQL State</b>	07W06
<b>SQL Code</b>	-760L
<b>ODBC 2 State</b>	07001
<b>ODBC 3 State</b>	07W06
<b>Severity Code</b>	<i>16</i> on page 2

<b>Error 760</b>	<b>"Invalid SQL identifier"</b>
<b>Probable Cause</b>	An invalid identifier was supplied through the C language interface. For example, you may have supplied a NULL string for a cursor name.

## Messages 761 through 785

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 761</b>	<b>"Server capability name '%1' could not be found in the database."</b>
<b>Constant</b>	CAPABILITY_NOT_FOUND
<b>SAP Sybase Error Number</b>	2343
<b>SQL State</b>	WO014
<b>SQL Code</b>	-761L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of server capability.
<b>Probable Cause</b>	An ALTER SERVER statement was attempted on a capability that was not defined.

<b>Error 764</b>	<b>"Server not found and unable to automatically start"</b>
<b>Constant</b>	UNABLE_TO_CONNECT_OR_START
<b>SAP Sybase Error Number</b>	2410
<b>SQL State</b>	08W55
<b>SQL Code</b>	-764L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2

<b>Error 764</b>	<b>"Server not found and unable to automatically start"</b>
<b>Probable Cause</b>	The client could not connect to a server, and was unable to automatically start a server. The automatic start may have failed because no database file was specified.
<b>Error 765</b>	<b>"Synchronization message type '%1' not found"</b>
<b>Constant</b>	NOT_SYNC_TYPE
<b>SAP Sybase Error Number</b>	2411
<b>SQL State</b>	5RW11
<b>SQL Code</b>	-765L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of synchronization message type.
<b>Probable Cause</b>	You referred to a synchronization message type that is not defined in this database.
<b>Error 766</b>	<b>"View references '%1', which is a temporary object. Views can only refer to permanent objects"</b>
<b>Constant</b>	VIEW_OVER_TEMP_OBJECT
<b>SAP Sybase Error Number</b>	2413
<b>SQL State</b>	42U00
<b>SQL Code</b>	-766L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Temporary object name.
<b>Probable Cause</b>	Views must refer only to permanent objects, not to temporary objects such as local temporary tables.

## Errors and Warnings

<b>Error 767</b>	<b>"Cannot find synchronization subscription with the name "%1"</b>
<b>Constant</b>	SYNCHRONIZATION_NOT_FOUND
<b>SAP Sybase Error Number</b>	2414
<b>SQL State</b>	5RW12
<b>SQL Code</b>	-767L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the subscription.
<b>Probable Cause</b>	You misspelled the name of a synchronization subscription or you did not qualify it correctly with a user name.
<b>Error 768</b>	<b>"Cannot subscribe to "%1"</b>
<b>Constant</b>	CANNOT_SUBSCRIBE
<b>SAP Sybase Error Number</b>	2415
<b>SQL State</b>	5RW13
<b>SQL Code</b>	-768L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the publication.
<b>Probable Cause</b>	Some publications cannot be subscribed to, such as a synchronization publication.
<b>Error 769</b>	<b>"Cannot modify synchronization entry using ALTER PUBLICATION"</b>
<b>Constant</b>	CANNOT_MODIFY_SYNC_AS_PUB
<b>SAP Sybase Error Number</b>	2416
<b>SQL State</b>	5RW14

<b>Error 769</b>	<b>"Cannot modify synchronization entry using ALTER PUBLICATION"</b>
<b>SQL Code</b>	-769L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to modify a synchronization entry using an ALTER PUBLICATION statement.
<b>Error 770</b>	<b>"Cannot modify publication entry using ALTER SYNCHRONIZATION"</b>
<b>Constant</b>	CANNOT_MODIFY_PUB_AS_SYNC
<b>SAP Sybase Error Number</b>	2417
<b>SQL State</b>	5RW15
<b>SQL Code</b>	-770L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to modify a publication entry using an ALTER SYNCHRONIZATION statement.
<b>Error 771</b>	<b>"Event '%1' not found"</b>
<b>Constant</b>	EVENT_NOT_FOUND
<b>SAP Sybase Error Number</b>	2418
<b>SQL State</b>	WE001
<b>SQL Code</b>	-771L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	Name of the event that could not be found.

## Errors and Warnings

<b>Error 771</b>	<b>"Event "%1' not found"</b>
<b>Probable Cause</b>	You have attempted to reference an event with a name that does not exist in the database.
<b>Error 772</b>	<b>"Event "%1' already exists"</b>
<b>Constant</b>	EVENT_ALREADY_EXISTS
<b>SAP Sybase Error Number</b>	2419
<b>SQL State</b>	WE002
<b>SQL Code</b>	-772L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the event that already exists.
<b>Probable Cause</b>	You have attempted to create an event with a name that already exists in the database.
<b>Error 773</b>	<b>"Schedule "%1' for event "%2' not found"</b>
<b>Constant</b>	SCHEDEULE_NOT_FOUND
<b>SAP Sybase Error Number</b>	2420
<b>SQL State</b>	WE003
<b>SQL Code</b>	-773L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	Name of the schedule that could not be found.
<b>Parameter 2</b>	Name of the event being scheduled.
<b>Probable Cause</b>	You have attempted to reference a schedule with a name that does not exist in the database for the named event.

<b>Error 774</b>	<b>"Schedule '%1' for event '%2' already exists"</b>
<b>Constant</b>	SCHEDULE_ALREADY_EXISTS
<b>SAP Sybase Error Number</b>	2421
<b>SQL State</b>	WE004
<b>SQL Code</b>	-774L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the schedule that already exists.
<b>Parameter 2</b>	Name of the event being scheduled.
<b>Probable Cause</b>	You have attempted to create a schedule with a name that already exists in the database for the named event.

<b>Error 777</b>	<b>"Cannot synchronize table '%1' since it does not have a primary key"</b>
<b>Constant</b>	CANNOT_SYNC_TABLE_WITHOUT_PK
<b>SAP Sybase Error Number</b>	2424
<b>SQL State</b>	5RW16
<b>SQL Code</b>	-777L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the table.
<b>Probable Cause</b>	Tables being synchronized must contain a primary key.

<b>Error 778</b>	<b>"Must include primary key for table '%1' in the synchronization"</b>
<b>Constant</b>	PK_NOT_IN_SYNC_ARTICLE
<b>SAP Sybase Error Number</b>	2425
<b>SQL State</b>	5RW17

## Errors and Warnings

<b>Error 778</b>	<b>"Must include primary key for table '%1' in the synchronization"</b>
<b>SQL Code</b>	-778L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the table.
<b>Probable Cause</b>	The primary key of the table must be included in the synchronization entry.
<b>Error 779</b>	<b>"Cannot create synchronization entry for table '%1' with BLOB primary key"</b>
<b>Constant</b>	BLOB_IN_SYNC_TABLE_PK
<b>SAP Sybase Error Number</b>	2426
<b>SQL State</b>	5RW18
<b>SQL Code</b>	-779L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the table.
<b>Probable Cause</b>	You attempted to create a synchronization entry on a table with a BLOB primary key.
<b>Error 780</b>	<b>"Cannot update primary key for table '%1' involved in a publication"</b>
<b>Constant</b>	ARTICLE_PK_CANNOT_BE_UPDATED
<b>SAP Sybase Error Number</b>	2427
<b>SQL State</b>	5RW19
<b>SQL Code</b>	-780L
<b>ODBC 2 State</b>	42000

<b>Error 780</b>	<b>"Cannot update primary key for table '%1' involved in a publication"</b>
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the table.
<b>Probable Cause</b>	The primary key of a table involved in a publication cannot be updated. The prevent_article_pkey_update database option can be set to Off to allow updates to the primary key of the table involved in the publication.
<b>Error 782</b>	<b>"Cannot register '%1' since another exclusive instance is running"</b>
<b>Constant</b>	SAME_EXCLUSIVE_APP_RUNNING
<b>SAP Sybase Error Number</b>	2429
<b>SQL State</b>	5RW21
<b>SQL Code</b>	-782L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the application.
<b>Probable Cause</b>	You attempted to start an application, but another exclusive instance of the same application is already registered.
<b>Error 783</b>	<b>"Cannot register another '%1' as an exclusive application"</b>
<b>Constant</b>	SAME_APP_RUNNING
<b>SAP Sybase Error Number</b>	2430
<b>SQL State</b>	5RW22
<b>SQL Code</b>	-783L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2

## Errors and Warnings

<b>Error 783</b>	<b>"Cannot register another "%1' as an exclusive application"</b>
<b>Parameter 1</b>	Name of the application.
<b>Probable Cause</b>	You attempted to register an exclusive application but another instance of the same application is already registered.
<b>Error 784</b>	<b>"Cannot register connection because of invalid application cookie"</b>
<b>Constant</b>	CANNOT_REG_CONN
<b>SAP Sybase Error Number</b>	2431
<b>SQL State</b>	5RW23
<b>SQL Code</b>	-784L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Application registration cannot be found for the given cookie.
<b>Error 785</b>	<b>"Cannot deregister application because of invalid cookie"</b>
<b>Constant</b>	DEREG_APP_NOT_FOUND
<b>SAP Sybase Error Number</b>	2432
<b>SQL State</b>	5RW24
<b>SQL Code</b>	-785L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The application has not been registered successfully or it was previously deregistered.

## 786 - 1005

---

## Messages 786 through 809

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 786</b>	<b>"Cannot deregister '%1' since active registered connection exists"</b>
<b>Constant</b>	DEREG_APP_IN_USE
<b>SAP Sybase Error Number</b>	2433
<b>SQL State</b>	5RW25
<b>SQL Code</b>	-786L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the application.
<b>Probable Cause</b>	You attempted to deregister an application while there are still active connections registered to that application.

<b>Error 787</b>	<b>"Current connection is already registered to '%1' as '%2'"</b>
<b>Constant</b>	CONN_ALREADY_REGISTERED
<b>SAP Sybase Error Number</b>	2434
<b>SQL State</b>	5RW26
<b>SQL Code</b>	-787L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the application.
<b>Parameter 2</b>	Registered connection label.
<b>Probable Cause</b>	You attempted to register this connection more than once.

## Errors and Warnings

<b>Error 788</b>	<b>"Another connection has already registered as "%1"</b>
<b>Constant</b>	NOT_UNIQUE_CONN_REG_LABEL
<b>SAP Sybase Error Number</b>	2435
<b>SQL State</b>	5RW27
<b>SQL Code</b>	-788L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Registered connection label.
<b>Probable Cause</b>	You attempted to register a connection with a label already in use for the same application.

<b>Error 789</b>	<b>"Cannot register '%1' since registration cookie exhausted"</b>
<b>Constant</b>	APP_REG_COOKIE_EXHAUSTED
<b>SAP Sybase Error Number</b>	2436
<b>SQL State</b>	5RW28
<b>SQL Code</b>	-789L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the application.
<b>Probable Cause</b>	Cannot register the application until one is unregistered.

<b>Error 790</b>	<b>"Cannot register connection to '%1' since automatic label exhausted"</b>
<b>Constant</b>	CONN_REG_AUTO_LABEL_EXHAUSTED
<b>SAP Sybase Error Number</b>	2437
<b>SQL State</b>	5RW29
<b>SQL Code</b>	-790L

<b>Error 790</b>	<b>"Cannot register connection to "%1' since automatic label exhausted"</b>
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the application.
<b>Probable Cause</b>	You may register using a specified label instead.
<b>Error 791</b>	<b>"Invalid day of week or month '%1' for event "%2"</b>
<b>Constant</b>	INVALID_EVENT_DAY
<b>SAP Sybase Error Number</b>	2438
<b>SQL State</b>	WE005
<b>SQL Code</b>	-791L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	Day-of-week name or day-of-month number.
<b>Parameter 2</b>	Name of the event being scheduled.
<b>Probable Cause</b>	You have attempted to create a schedule with an invalid day-of-week name or day-of-month number.
<b>Error 792</b>	<b>"Invalid time '%1' for event "%2"</b>
<b>Constant</b>	INVALID_EVENT_TIME
<b>SAP Sybase Error Number</b>	2439
<b>SQL State</b>	WE006
<b>SQL Code</b>	-792L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2

## Errors and Warnings

<b>Error 792</b>	<b>"Invalid time "%1' for event "%2"</b>
<b>Parameter 1</b>	Time value.
<b>Parameter 2</b>	Name of the event being scheduled.
<b>Probable Cause</b>	You have attempted to create a schedule with an invalid start or stop time.
<b>Error 793</b>	<b>"Invalid start date/time for event "%1"</b>
<b>Constant</b>	INVALID_EVENT_START
<b>SAP Sybase Error Number</b>	2440
<b>SQL State</b>	WE007
<b>SQL Code</b>	-793L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	Name of the event being scheduled.
<b>Probable Cause</b>	You have specified an event starting date that is invalid.
<b>Error 794</b>	<b>"Synchronization server failed to commit the upload"</b>
<b>Constant</b>	UPLOAD_FAILED_AT_SERVER
<b>SAP Sybase Error Number</b>	2441
<b>SQL State</b>	0AW09
<b>SQL Code</b>	-794L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to synchronize an UltraLite database. During the synchronization session, a complete upload stream was sent that could not be committed to the consolidated database. The reason for the upload failure can be found in the synchronization log file.

<b>Error 797</b>	<b>"Synchronization option '%1' contains semicolon, equal sign, curly brace, or is null"</b>
<b>Constant</b>	BAD_SYNC_OPTION_VALUE
<b>SAP Sybase Error Number</b>	2444
<b>SQL State</b>	5RW32
<b>SQL Code</b>	-797L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the synchronization option.
<b>Probable Cause</b>	You attempted to set a synchronization option with an invalid value.
<b>Error 799</b>	<b>"DTC transactions are not supported on this platform"</b>
<b>Constant</b>	DTC_TRANSACTIONS_NOT_SUPPORTED
<b>SAP Sybase Error Number</b>	2446
<b>SQL State</b>	0AW10
<b>SQL Code</b>	-799L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You tried to enlist a DTC transaction on a platform that does not support this feature.
<b>Error 800</b>	<b>"Cannot commit or rollback while enlisted in a transaction"</b>
<b>Constant</b>	CANNOT_COMMIT_OR_ROLLBACK_WHILE_ENLISTED
<b>SAP Sybase Error Number</b>	2447
<b>SQL State</b>	55W09
<b>SQL Code</b>	-800
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 800</b>	<b>"Cannot commit or rollback while enlisted in a transaction"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You tried to explicitly commit or rollback on a connection that is enlisted in a transaction. You must use the Commit/Abort protocol of the transaction instead.
<b>Error 801</b>	<b>"Cannot enlist in a transaction while already enlisted in a transaction"</b>
<b>Constant</b>	CANNOT_ENLIST_WHILE_ALREADY_ENLISTED
<b>SAP Sybase Error Number</b>	2448
<b>SQL State</b>	55W10
<b>SQL Code</b>	-801L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You tried to enlist a second transaction on a connection that is already enlisted in a transaction.
<b>Error 802</b>	<b>"Cannot enlist in a transaction with uncommitted data pending"</b>
<b>Constant</b>	CANNOT_ENLIST_WITH_UNCOMMITTED_DATA
<b>SAP Sybase Error Number</b>	2449
<b>SQL State</b>	55W11
<b>SQL Code</b>	-802L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You tried to enlist a transaction on a connection that has pending uncommitted data.

<b>Error 803</b>	<b>"Unable to enlist transaction; DTC may be down"</b>
<b>Constant</b>	FAILED_TO_ENLIST
<b>SAP Sybase Error Number</b>	2450
<b>SQL State</b>	WL005
<b>SQL Code</b>	-803L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>17</i> on page 2
<b>Probable Cause</b>	You tried to enlist a transaction but DTC does not seem to be available at this time.
<b>Error 804</b>	<b>"Unable to re-enlist transaction; DTC may be down"</b>
<b>Constant</b>	FAILED_TO_REENLIST
<b>SAP Sybase Error Number</b>	2451
<b>SQL State</b>	WL006
<b>SQL Code</b>	-804L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>17</i> on page 2
<b>Probable Cause</b>	You tried to recover a transaction but DTC does not seem to be available at this time.
<b>Error 805</b>	<b>"Synchronization option '%1' not found"</b>
<b>Constant</b>	SYNC_OPTION_NOT_FOUND
<b>SAP Sybase Error Number</b>	2452
<b>SQL State</b>	5RW33
<b>SQL Code</b>	-805L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42S02

## Errors and Warnings

<b>Error 805</b>	<b>"Synchronization option '%1' not found"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the synchronization option.
<b>Probable Cause</b>	You attempted to delete an undefined synchronization option.
<b>Error 806</b>	<b>"System event type '%1' not found"</b>
<b>Constant</b>	EVENT_TYPE_NOT_FOUND
<b>SAP Sybase Error Number</b>	2453
<b>SQL State</b>	WE008
<b>SQL Code</b>	-806L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	Name of the system event type that could not be found.
<b>Probable Cause</b>	You have attempted to create an event with a system event type name that does not exist in the database.
<b>Error 807</b>	<b>"Host variables must not be used within a batch"</b>
<b>Constant</b>	HOSTVARS_IN_BATCH
<b>SAP Sybase Error Number</b>	2454
<b>SQL State</b>	07W07
<b>SQL Code</b>	-807L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You have attempted to execute a batch that contains host variable references. Host variables are not supported within a batch.
<b>Error 809</b>	<b>"Synchronization option is too long"</b>
<b>Constant</b>	SYNC_OPTION_TOO_LONG

<b>Error 809</b>	<b>"Synchronization option is too long"</b>
<b>SAP Sybase Error Number</b>	2456
<b>SQL State</b>	5RW34
<b>SQL Code</b>	-809L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Synchronization option list cannot be longer than the database page size.

## Messages 810 through 829

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 810</b>	<b>"External object '%1' not found"</b>
<b>Constant</b>	EXTENV_OBJECT_NOT_FOUND
<b>SAP Sybase Error Number</b>	2457
<b>SQL State</b>	42W57
<b>SQL Code</b>	-810L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the Java class or external object.
<b>Probable Cause</b>	The Java class or external object with this name does not exist in the database.

<b>Error 811</b>	<b>"JAR '%1' not found"</b>
<b>Constant</b>	JAR_NOT_FOUND
<b>SAP Sybase Error Number</b>	2458
<b>SQL State</b>	42W58
<b>SQL Code</b>	-811L

## Errors and Warnings

<b>Error 811</b>	<b>"JAR '%1' not found"</b>
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the JAR.
<b>Probable Cause</b>	The JAR with this name does not exist in the database.
<b>Error 812</b>	<b>"The SELECT list for the derived table '%1' has no expression to match '%2'"</b>
<b>Constant</b>	NO_MATCHING_SELECT_ITEM
<b>SAP Sybase Error Number</b>	2459
<b>SQL State</b>	42W59
<b>SQL Code</b>	-812L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	Name of the derived table.
<b>Parameter 2</b>	Name of the alias for which there is no matching expression.
<b>Probable Cause</b>	The specified alias from the derived table's AS clause has no matching expression from the SELECT statement for that derived table. Ensure that each SELECT list item has a matching alias in the derived table's AS clause, and vice-versa.
<b>Error 813</b>	<b>"FOR UPDATE has been incorrectly specified for a READ ONLY cursor"</b>
<b>Constant</b>	NON_UPDATEABLE_CURSOR
<b>SAP Sybase Error Number</b>	2460
<b>SQL State</b>	42W36
<b>SQL Code</b>	-813L

<b>Error 813</b>	<b>"FOR UPDATE has been incorrectly specified for a READ ONLY cursor"</b>
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You attempted to declare a cursor FOR UPDATE on a query that is not updatable. Queries that contain DISTINCT, GROUP BY, HAVING, INTERSECT, EXCEPT, or UNION, or that contain aggregate functions are read-only. If the ansi_update_constraints option is on, then queries that contain a join are read-only. If the query references a view then the view may be non-updatable.
<b>Error 814</b>	<b>"Cannot update column '%1' since it appears in the ORDER BY clause"</b>
<b>Constant</b>	CANNOT_UPDATE_ORDER_BY_COLUMN
<b>SAP Sybase Error Number</b>	2461
<b>SQL State</b>	42W37
<b>SQL Code</b>	-814L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	Name of the column that appears in the ORDER BY clause.
<b>Probable Cause</b>	You attempted to update a column that appears in the ORDER BY clause. The ansi_update_constraints option controls whether this update is allowed.
<b>Error 815</b>	<b>"Cannot update column '%1' since it does not appear in the SELECT clause"</b>
<b>Constant</b>	UPDATE_NOT_IN_SELECT
<b>SAP Sybase Error Number</b>	2462
<b>SQL State</b>	42W38
<b>SQL Code</b>	-815L

## Errors and Warnings

<b>Error 815</b>	<b>"Cannot update column "%1' since it does not appear in the SELECT clause"</b>
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	Name of the column that does not appear in the SELECT clause.
<b>Probable Cause</b>	You attempted to update a column that does not explicitly appear in the SELECT list. The ansi_update_constraints option controls whether this update is allowed.
<b>Error 816</b>	<b>"Specified database file already in use"</b>
<b>Constant</b>	FILE_IN_USE
<b>SAP Sybase Error Number</b>	2463
<b>SQL State</b>	08W56
<b>SQL Code</b>	-816L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	The database server could not start the specified database because the file is already in use.
<b>Error 817</b>	<b>"Too many temporary tables in connection"</b>
<b>Constant</b>	TOO_MANY_TEMP_TABLES
<b>SAP Sybase Error Number</b>	2464
<b>SQL State</b>	52W41
<b>SQL Code</b>	-817L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

<b>Error 817</b>	<b>"Too many temporary tables in connection"</b>
<b>Probable Cause</b>	A CREATE TABLE or DECLARE LOCAL TEMPORARY TABLE statement attempted to create a temporary table, but the resulting number of distinct table IDs used for temporary tables in the current connection would exceed the limit.
<b>Error 818</b>	<b>"Version 'V%1' interface used by external function call '%2' is not supported for execution in the current context."</b>
<b>Constant</b>	INCOMPATIBLE_EXTERNAL_CALL
<b>SAP Sybase Error Number</b>	2465
<b>SQL State</b>	WW026
<b>SQL Code</b>	-818L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	API version of the external function that is being called.
<b>Parameter 2</b>	Name of the external function that is being called.
<b>Probable Cause</b>	You attempted to call an external function. The attempt to load the associated library failed because of incompatibility with the server. Incompatibility may arise because the dynamic library is using an external function API that is either not supported by the server or is newer than the one supported by the server. It may also arise if the external API is not compatible with the data in the current context.
<b>Error 819</b>	<b>"Table '%1' is part of a synchronization subscription and can only be ALTERed within a synchronization schema change"</b>
<b>Constant</b>	SYNC_CONTAINS_TABLE
<b>SAP Sybase Error Number</b>	2466
<b>SQL State</b>	5RW35
<b>SQL Code</b>	-819L
<b>ODBC 2 State</b>	42000

## Errors and Warnings

<b>Error 819</b>	<b>"Table '%1' is part of a synchronization subscription and can only be ALTERed within a synchronization schema change"</b>
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the table.
<b>Probable Cause</b>	A table belonging to a synchronization subscription cannot be altered except within a synchronization schema change or by using dbmlsync.
<b>Error 820</b>	<b>"Invalid scroll position "%1"</b>
<b>Constant</b>	INVALID_POSITION
<b>SAP Sybase Error Number</b>	2467
<b>SQL State</b>	24504
<b>SQL Code</b>	-820L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The scroll position that is invalid.
<b>Probable Cause</b>	You attempted to scroll to a position that is not supported. Scroll positions must be between -2147483647 and 2147483646.
<b>Error 821</b>	<b>"Dbspace for table '%1' not found"</b>
<b>Constant</b>	DBSPACE_FOR_TABLE_UNAVAILABLE
<b>SAP Sybase Error Number</b>	2468
<b>SQL State</b>	52W19
<b>SQL Code</b>	-821L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2

<b>Error 821</b>	<b>"Dbspace for table "%1' not found"</b>
<b>Parameter 1</b>	Name of the table whose dbspace could not be found.
<b>Probable Cause</b>	You tried to access a table in a dbspace that the database server could not find. You may need to change the file name associated with the dbspace using the ALTER DBSPACE statement.
<b>Error 822</b>	<b>"Table '%1' is already included"</b>
<b>Constant</b>	TABLE_ALREADY_INCLUDED
<b>SAP Sybase Error Number</b>	2469
<b>SQL State</b>	5RW36
<b>SQL Code</b>	-822L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the table.
<b>Probable Cause</b>	You attempted to add or modify a publication or synchronization definition such that the same table is included twice.
<b>Error 823</b>	<b>"Cannot handle expressions involving remote tables inside stored procedures"</b>
<b>Constant</b>	OMNI_EXPRESSION_IN_PROC
<b>SAP Sybase Error Number</b>	2470
<b>SQL State</b>	WO023
<b>SQL Code</b>	-823L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>12</i> on page 2
<b>Probable Cause</b>	The server encountered an expression involving remote tables inside a stored procedure. The expression was too complicated to process.

## Errors and Warnings

<b>Error 824</b>	<b>"Illegal reference to correlation name "%1"</b>
<b>Constant</b>	INVALID_CORRELATION_NAME_REFERENCE
<b>SAP Sybase Error Number</b>	2471
<b>SQL State</b>	42U01
<b>SQL Code</b>	-824L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	The correlation name that is incorrectly referenced.
<b>Probable Cause</b>	Your query contains a reference in a table expression to a correlation name that is not contained in that table expression.
<b>Error 825</b>	<b>"Previous error lost before RESIGNAL"</b>
<b>Constant</b>	PREVIOUS_ERROR_LOST
<b>SAP Sybase Error Number</b>	2472
<b>SQL State</b>	WP011
<b>SQL Code</b>	-825L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A RESIGNAL statement in an exception handler of a stored procedure was executed but the context of the previous error was unavailable. A possible cause of this error is a SELECT statement that returns a result set in the exception handler.
<b>Error 826</b>	<b>"Database upgrade not possible; RowGenerator table not owned by user dbo"</b>
<b>Constant</b>	DBO_DOES_NOT_OWN_ROWGENERATOR
<b>SAP Sybase Error Number</b>	2473

<b>Error 826</b>	<b>"Database upgrade not possible; RowGenerator table not owned by user dbo"</b>
<b>SQL State</b>	08W57
<b>SQL Code</b>	-826L
<b>ODBC 2 State</b>	08004
<b>ODBC 3 State</b>	08004
<b>Severity Code</b>	<i>21</i> on page 2
<b>Probable Cause</b>	An attempt to upgrade a database failed. The RowGenerator table is not owned by user dbo.
<b>Error 827</b>	<b>"Database upgrade not possible; user tables have table IDs in system table range"</b>
<b>Constant</b>	USER_TABLES_IN_SYSTEM_RANGE
<b>SAP Sybase Error Number</b>	2474
<b>SQL State</b>	08W58
<b>SQL Code</b>	-827L
<b>ODBC 2 State</b>	08004
<b>ODBC 3 State</b>	08004
<b>Severity Code</b>	<i>21</i> on page 2
<b>Probable Cause</b>	An attempt to upgrade a database failed. User table IDs should not be in system table ID range.
<b>Error 828</b>	<b>"A conflict with the dbmlsync download phase was detected"</b>
<b>Constant</b>	RECORDING_CONFLICT_DETECTED
<b>SAP Sybase Error Number</b>	2475
<b>SQL State</b>	WW027
<b>SQL Code</b>	-828L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2

## Errors and Warnings

<b>Error 828</b>	<b>"A conflict with the dbmlsync download phase was detected"</b>
<b>Probable Cause</b>	Dbmlsync uses this error to detect download phase conflicts with rows modified by other connections.
<b>Error 829</b>	<b>"TLS handshake failure"</b>
<b>Constant</b>	TLS_HANDSHAKE_FAILED
<b>SAP Sybase Error Number</b>	2476
<b>SQL State</b>	08W59
<b>SQL Code</b>	-829L
<b>ODBC 2 State</b>	08S01
<b>ODBC 3 State</b>	08S01
<b>Severity Code</b>	<i>21</i> on page 2
<b>Probable Cause</b>	The connection failed because of a failure in the TLS handshaking process.

## Messages 830 through 854

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 830</b>	<b>"Alias '%1' is not unique"</b>
<b>Constant</b>	ALIAS_NOT_UNIQUE
<b>SAP Sybase Error Number</b>	2477
<b>SQL State</b>	42W60
<b>SQL Code</b>	-830L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	Name of the alias.
<b>Probable Cause</b>	The same alias is used more than once in a SELECT list.

<b>Error 831</b>	"Definition for alias '%1' must appear before its first reference"
<b>Constant</b>	ALIAS_NOT_YET_DEFINED
<b>SAP Sybase Error Number</b>	2478
<b>SQL State</b>	42W61
<b>SQL Code</b>	-831L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	Name of the alias.
<b>Probable Cause</b>	An expression contains a reference to an alias, but the alias is defined later in the SELECT list. The alias definition must appear before its first reference.

<b>Error 832</b>	"Connection error: %1"
<b>Constant</b>	CONNECTION_ERROR
<b>SAP Sybase Error Number</b>	2479
<b>SQL State</b>	08W60
<b>SQL Code</b>	-832L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Description of the connection error.
<b>Probable Cause</b>	An error occurred while attempting to establish a connection with the database server, but before attempting to connect to a database. Failure to initialize a communication link during the connection attempt is an example of this error. Creating a debug log file using the LogFile connection parameter may provide more information.

## Errors and Warnings

<b>Error 833</b>	<b>"Row in table '%1' was modified or deleted in BEFORE trigger"</b>
<b>Constant</b>	ROW_REMODIFIED_OR_DELETED
<b>SAP Sybase Error Number</b>	2480
<b>SQL State</b>	42W62
<b>SQL Code</b>	-833L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the table.
<b>Probable Cause</b>	A BEFORE trigger has updated or deleted the row that caused the trigger to fire, preventing the original operation from completing. The trigger must be re-written so that it does not attempt to change the row via UPDATE or DELETE statements.
<b>Error 834</b>	<b>"Column '%1' not found in table '%2'"</b>
<b>Constant</b>	COLUMN_NOT_FOUND_IN_TABLE
<b>SAP Sybase Error Number</b>	2083
<b>SQL State</b>	52005
<b>SQL Code</b>	-834L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S22
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	Name of the column that could not be found.
<b>Parameter 2</b>	Name of the table that was supposed to contain the column.
<b>Probable Cause</b>	You misspelled the name of a column, or the column you are looking for is in a different table.

<b>Error 835</b>	"Event '%1' in use"
<b>Constant</b>	EVENT_IN_USE
<b>SAP Sybase Error Number</b>	2482
<b>SQL State</b>	WE009
<b>SQL Code</b>	-835L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the event that is in use.
<b>Probable Cause</b>	You have attempted to drop an event that is currently in use.

<b>Error 836</b>	"Procedure '%1' is no longer valid"
<b>Constant</b>	PROCEDURE_NO_LONGER_VALID
<b>SAP Sybase Error Number</b>	2483
<b>SQL State</b>	42W63
<b>SQL Code</b>	-836L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	Name of the procedure.
<b>Probable Cause</b>	A procedure definition cannot be loaded from the catalog. Check for tables or columns that have been renamed or that may be reserved words. If this procedure is an internal procedure, you may have an older version. Database upgrade may be needed to run it successfully.

<b>Error 837</b>	"Trigger or foreign key for table '%1' is no longer valid"
<b>Constant</b>	TRIGGER_NO_LONGER_VALID
<b>SAP Sybase Error Number</b>	2484
<b>SQL State</b>	42W64

## Errors and Warnings

<b>Error 837</b>	<b>"Trigger or foreign key for table '%1' is no longer valid"</b>
<b>SQL Code</b>	-837L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	Name of the table.
<b>Probable Cause</b>	A trigger definition cannot be loaded from the catalog. Check for tables or columns that have been renamed or that may be reserved words. The trigger may be a system-generated trigger to enforce the referential actions of a foreign key.
<b>Error 838</b>	<b>"TLS initialization on server failed"</b>
<b>Constant</b>	TLS_INIT_FAILED_ON_SRV
<b>SAP Sybase Error Number</b>	2485
<b>SQL State</b>	08W61
<b>SQL Code</b>	-838L
<b>ODBC 2 State</b>	08S01
<b>ODBC 3 State</b>	08S01
<b>Severity Code</b>	<i>21</i> on page 2
<b>Probable Cause</b>	The connection failed because the initialization of the TLS library on the server failed.
<b>Error 839</b>	<b>"Download failed because of conflicts with existing rows on table '%1' (row: %2)"</b>
<b>Constant</b>	DOWNLOAD_CONFLICT
<b>SAP Sybase Error Number</b>	2486
<b>SQL State</b>	0AW11
<b>SQL Code</b>	-839L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000

<b>Error 839</b>	<b>"Download failed because of conflicts with existing rows on table '%1' (row: %2)"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the table with the conflict.
<b>Parameter 2</b>	The value of the primary key of the row that conflicted.
<b>Probable Cause</b>	During synchronization, there was a conflict between one or more rows in the download stream and rows modified locally in the UltraLite database. The download has been rolled back. You can avoid this error by coordinating local database modifications with synchronization, or synchronizing again when the local modifications are complete.

<b>Error 840</b>	<b>"Incorrect or missing encryption key"</b>
<b>Constant</b>	BAD_ENCRYPTION_KEY
<b>SAP Sybase Error Number</b>	2487
<b>SQL State</b>	08W62
<b>SQL Code</b>	-840L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>21</i> on page 2
<b>Probable Cause</b>	The database is encrypted with a key. There was no key given to start the database, or the specified key was incorrect.

<b>Error 843</b>	<b>"Cannot find synchronization user with the name '%1'"</b>
<b>Constant</b>	SYNC_SITE_NOT_FOUND
<b>SAP Sybase Error Number</b>	2490
<b>SQL State</b>	5RW37
<b>SQL Code</b>	-843L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the synchronization user.

## Errors and Warnings

<b>Error 843</b>	<b>"Cannot find synchronization user with the name '%1'"</b>
<b>Probable Cause</b>	You misspelled the name of a synchronization site or you did not qualify it correctly with a user name.
<b>Error 845</b>	<b>"Owner '%1' used in a qualified column reference does not match correlation name '%2'"</b>
<b>Constant</b>	INVALID_COLUMN_QUALIFICATION
<b>SAP Sybase Error Number</b>	2492
<b>SQL State</b>	42U02
<b>SQL Code</b>	-845L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	The owner name specified in the column reference.
<b>Parameter 2</b>	The correlation name that is incorrectly referenced.
<b>Probable Cause</b>	Your query contains a qualified column reference to a table name, but either a correlation name has been used for that table, or the owner of the table does not match the owner name specified in the column reference. Remove the owner qualification, and qualify column references only by correlation name.
<b>Error 846</b>	<b>"SET clause for column '%1' used incorrectly"</b>
<b>Constant</b>	INVALID_SET_CLAUSE
<b>SAP Sybase Error Number</b>	2493
<b>SQL State</b>	42U03
<b>SQL Code</b>	-846L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S03
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	The SET clause that is invalid.

<b>Error 846</b>	<b>"SET clause for column '%1' used incorrectly"</b>
<b>Probable Cause</b>	Your UPDATE statement contains an invalid SET clause, for example, there are multiple SET clauses for the same column.
<b>Error 849</b>	<b>"Referential integrity actions other than RESTRICT not allowed for temporary tables"</b>
<b>Constant</b>	INVALID_FOREIGN_KEY_ACTION
<b>SAP Sybase Error Number</b>	2496
<b>SQL State</b>	42R01
<b>SQL Code</b>	-849L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to specify an unsupported referential integrity action for a temporary table.
<b>Error 850</b>	<b>"Tables related by key constraint must both be permanent, or both be temporary and not created with ON COMMIT DELETE ROWS. For global temporary tables they must both be shared if one is shared."</b>
<b>Constant</b>	INVALID_FOREIGN_KEY_TABLE
<b>SAP Sybase Error Number</b>	2497
<b>SQL State</b>	42R02
<b>SQL Code</b>	-850L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Tables involved in a key constraint relationship must both be permanent user tables or both be temporary tables not created with ON COMMIT DELETE ROWS. Change the definition of one or both tables using ALTER TABLE.

## Errors and Warnings

<b>Error 851</b>	"Decryption error: %1"
<b>Constant</b>	DECRYPT_ERROR
<b>SAP Sybase Error Number</b>	2498
<b>SQL State</b>	08W63
<b>SQL Code</b>	-851L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	Description of the error that occurred.
<b>Probable Cause</b>	An error occurred during decryption.

<b>Error 852</b>	"Table name '%1' is ambiguous"
<b>Constant</b>	AMBIGUOUS_TABLE_NAME
<b>SAP Sybase Error Number</b>	2499
<b>SQL State</b>	52W42
<b>SQL Code</b>	-852L
<b>ODBC 2 State</b>	S0013
<b>ODBC 3 State</b>	42S13
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of an ambiguous table.
<b>Probable Cause</b>	A statement has referred to a table name that is not unique. Preface the table name by an owner name.

<b>Error 853</b>	"Cursor not in a valid state"
<b>Constant</b>	CURSOR_INVALID_STATE
<b>SAP Sybase Error Number</b>	2501
<b>SQL State</b>	24000
<b>SQL Code</b>	-853L

<b>Error 853</b>	<b>"Cursor not in a valid state"</b>
<b>ODBC 2 State</b>	24000
<b>ODBC 3 State</b>	24000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to use a cursor that is not in a valid state for the attempted operation. For example, the cursor may have encountered an error. In UltraLite, this error occurs if you attempt to set parameters for a prepared statement while a result set (cursor) is open for the statement.
<b>Error 854</b>	<b>"Function or column reference to "%1' in the ORDER BY clause is invalid"</b>
<b>Constant</b>	INVALID_ORDERBY_COLUMN
<b>SAP Sybase Error Number</b>	2502
<b>SQL State</b>	42W65
<b>SQL Code</b>	-854L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	Name of the column referenced directly, or in an expression, in the ORDER BY clause.
<b>Probable Cause</b>	You specified a function or column reference in the ORDER BY clause that is semantically invalid. For example, for DISTINCT queries the ORDER BY clause may only refer to items in the query's SELECT list.

## Messages 855 through 876

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 855</b>	<b>"Trigger name "%1' is ambiguous"</b>
<b>Constant</b>	AMBIGUOUS_TRIGGER_NAME
<b>SAP Sybase Error Number</b>	2503
<b>SQL State</b>	42W66

## Errors and Warnings

<b>Error 855</b>	<b>"Trigger name "%1' is ambiguous"</b>
<b>SQL Code</b>	-855L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the ambiguous trigger.
<b>Probable Cause</b>	A statement has referred to a trigger name that is not unique. Qualify the trigger name with the table and/or owner name.
<b>Error 856</b>	<b>"Invalid sqllen field in SQLDA"</b>
<b>Constant</b>	INVALID_SQLLEN
<b>SAP Sybase Error Number</b>	2504
<b>SQL State</b>	07W08
<b>SQL Code</b>	-856L
<b>ODBC 2 State</b>	HY090
<b>ODBC 3 State</b>	HY090
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	An invalid length was specified in a SQLDA sqllen field. All variable length types must have a non-negative length. The DT_BINARY and DT_VARCHAR types must have length greater than one.
<b>Error 857</b>	<b>"Synchronization failed due to an error on the MobiLink server: %1"</b>
<b>Constant</b>	SERVER_SYNCHRONIZATION_ERROR
<b>SAP Sybase Error Number</b>	2505
<b>SQL State</b>	0AW12
<b>SQL Code</b>	-857L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2

<b>Error 857</b>	<b>"Synchronization failed due to an error on the MobiLink server: %1"</b>
<b>Parameter 1</b>	The description of the error from the MobiLink server.
<b>Probable Cause</b>	Synchronization failed at the MobiLink server. More details can be found in the MobiLink server log file.

<b>Error 858</b>	<b>"CREATE/DROP STATISTICS statement cannot refer to virtual tables"</b>
<b>Constant</b>	HISTOGRAMS_NOT_SUPPORTED_ON_OBJECT
<b>SAP Sybase Error Number</b>	2506
<b>SQL State</b>	42W67
<b>SQL Code</b>	-858L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to use CREATE/DROP STATISTICS to create/drop one or more histograms on a virtual database object, such as a view or remote table. The CREATE STATISTICS and DROP STATISTICS statements can only refer to base tables, local temporary tables, or global temporary tables in the SQL Anywhere database that you are connected to.

<b>Error 860</b>	<b>"At least one of the specified dbspaces was not calibrated"</b>
<b>Constant</b>	DBSPACE_NOT_CALIBRATED
<b>SAP Sybase Error Number</b>	2509
<b>SQL State</b>	WW028
<b>SQL Code</b>	-860L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to calibrate a dbspace that was not open or was too small.

## Errors and Warnings

<b>Error 861</b>	<b>"Aggregated expression '%1' contains multiple columns of which one or more are outer references"</b>
<b>Constant</b>	MULTIPLE_AGGREGATE_COLUMNS
<b>SAP Sybase Error Number</b>	2510
<b>SQL State</b>	42W68
<b>SQL Code</b>	-861L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	The aggregated expression in error.
<b>Probable Cause</b>	A subselect within the nested query contains an aggregate function whose parameters include an outer reference. In such cases, the outer reference must be the only column referenced in the expression.
<b>Error 862</b>	<b>"The aggregate expression '%1' must appear in either the SELECT list or a HAVING clause subquery"</b>
<b>Constant</b>	INVALID_AGGREGATE_PLACEMENT
<b>SAP Sybase Error Number</b>	2511
<b>SQL State</b>	42W69
<b>SQL Code</b>	-862L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	The aggregated expression in error.
<b>Probable Cause</b>	An aggregated expression containing an outer reference must either appear in a SELECT list expression (a subselect), or in a HAVING clause subquery in the query whose FROM clause contains the table with the column being aggregated.

<b>Error 863</b>	<b>"Grouped query contains more than one distinct aggregate function"</b>
<b>Constant</b>	INVALID_DISTINCT_AGGREGATE
<b>SAP Sybase Error Number</b>	2512
<b>SQL State</b>	42W70
<b>SQL Code</b>	-863L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	Two or more DISTINCT aggregate functions were specified in the same grouped query. This is only permitted if the Hash Group By operator is available. Any query block can only contain at most one DISTINCT aggregate function if the Hash Group By operator is not available.
<b>Error 864</b>	<b>"Statement contains an illegal usage of the NUMBER(*) function"</b>
<b>Constant</b>	INVALID_NUMBER
<b>SAP Sybase Error Number</b>	2514
<b>SQL State</b>	42W71
<b>SQL Code</b>	-864L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	The NUMBER and IDENTITY functions can only appear in the SELECT list of the outer-most SELECT block. It cannot be used in any subquery or in a predicate.
<b>Error 865</b>	<b>"Key constraint between temporary tables requires a primary key (not unique constraint)"</b>
<b>Constant</b>	INVALID_FOREIGN_KEY_INDEX

## Errors and Warnings

<b>Error 865</b>	<b>"Key constraint between temporary tables requires a primary key (not unique constraint)"</b>
<b>SAP Sybase Error Number</b>	2515
<b>SQL State</b>	42R03
<b>SQL Code</b>	-865L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The key constraint between temporary tables requires a primary key (not a UNIQUE constraint) if the database uses combined indexes. Change the definition of the primary table using ALTER TABLE or rebuild the database.
<b>Error 866</b>	<b>"%1 returned a result set with a different schema than expected"</b>
<b>Constant</b>	BAD_RESULT_SET
<b>SAP Sybase Error Number</b>	2516
<b>SQL State</b>	WP012
<b>SQL Code</b>	-866L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>12</i> on page 2
<b>Parameter 1</b>	Name of the procedure that returned the incorrect result set.
<b>Probable Cause</b>	When calling a procedure in the FROM clause of a SELECT statement, the expected schema of the result is taken from the WITH clause. If no WITH clause is given, the expected schema is taken from the system catalog. The result set returned from the call must match the expected schema or it must be possible to convert every column so that it matches.

<b>Error 867</b>	<b>"Cannot change synchronization user_name when status of the last upload is unknown"</b>
<b>Constant</b>	CANNOT_CHANGE_USER_NAME
<b>SAP Sybase Error Number</b>	2517
<b>SQL State</b>	0AW13
<b>SQL Code</b>	-867L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The MobiLink server uses the user_name to track synchronizations. If the status of the previous upload is unknown then you must resolve this condition before changing the user.

<b>Error 868</b>	<b>"'%1' is an unknown character set encoding label"</b>
<b>Constant</b>	UNKNOWN_CHARSET
<b>SAP Sybase Error Number</b>	2518
<b>SQL State</b>	WC001
<b>SQL Code</b>	-868L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The character set encoding label that is not recognized.
<b>Probable Cause</b>	The specified character set label is not recognized, so conversion from/to that character set is not possible.

<b>Error 869</b>	<b>"Database server cannot convert data from/to character set '%1'"</b>
<b>Constant</b>	UNSUPPORTED_CHARACTER_SET_ERROR
<b>SAP Sybase Error Number</b>	2519
<b>SQL State</b>	08W64

## Errors and Warnings

<b>Error 869</b>	<b>"Database server cannot convert data from/to character set "%1"</b>
<b>SQL Code</b>	-869L
<b>ODBC 2 State</b>	08S01
<b>ODBC 3 State</b>	08S01
<b>Severity Code</b>	<i>21</i> on page 2
<b>Parameter 1</b>	Name of the requested character set.
<b>Probable Cause</b>	The database server cannot convert character data from/to the character set requested by the application because the character set is not supported. The connection fails.
<b>Error 870</b>	<b>"Cannot convert between requested character set '%1' and database character set '%2'"</b>
<b>Constant</b>	FAILED_TO_START_CONVERTER
<b>SAP Sybase Error Number</b>	2520
<b>SQL State</b>	WC002
<b>SQL Code</b>	-870L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the requested character set encoding.
<b>Parameter 2</b>	The name of the database character set encoding.
<b>Probable Cause</b>	The server is unable to convert between the connection character set that was specified and the database character set. This could happen when the dbicu and dbicutd DLLs are not installed.
<b>Error 872</b>	<b>"%1 does not return a result set"</b>
<b>Constant</b>	NO_RESULT_SET
<b>SAP Sybase Error Number</b>	2522
<b>SQL State</b>	WP014

<b>Error 872</b>	"%1 does not return a result set"
<b>SQL Code</b>	-872L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the procedure.
<b>Probable Cause</b>	A procedure called in the FROM clause of a SELECT statement must return a result set.

<b>Error 873</b>	"%1 returned multiple result sets"
<b>Constant</b>	TOO_MANY_RESULT_SETS
<b>SAP Sybase Error Number</b>	2523
<b>SQL State</b>	WP013
<b>SQL Code</b>	-873L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the procedure.
<b>Probable Cause</b>	A procedure called in the FROM clause of a SELECT statement cannot return multiple result sets.

<b>Error 874</b>	"Column must be named: %1"
<b>Constant</b>	NO_XML_IDENTIFIER
<b>SAP Sybase Error Number</b>	2526
<b>SQL State</b>	WX001
<b>SQL Code</b>	-874L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

## Errors and Warnings

<b>Error 874</b>	<b>"Column must be named: %1"</b>
<b>Parameter 1</b>	The number of the column that must be named.
<b>Probable Cause</b>	Unnamed columns cannot be used as XML element or attribute names. Unnamed JSON columns can only be used within the top-level SELECT where the tag and parent are defined. In this context, the unnamed column is a directive to generate a JSON value rather than a JSON object for the given column. Name unnamed columns in the SELECT list by using AS.

<b>Error 875</b>	<b>"There is no way to join to "%1"</b>
<b>Constant</b>	CANNOT_JOIN_TABEXPR
<b>SAP Sybase Error Number</b>	2527
<b>SQL State</b>	42W73
<b>SQL Code</b>	-875L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<a href="#">15 on page 2</a>
<b>Parameter 1</b>	Name of table or view that cannot be joined.
<b>Probable Cause</b>	The server cannot discover a valid join condition involving this table. If the join is an outer join, you may be missing an ON clause. If the join is a KEY JOIN, the server cannot discover a foreign key-primary key relationship with this table that can be used to generate the join condition. If the join is a NATURAL JOIN, the table has no common column names with the table expression it is being joined to.

<b>Error 876</b>	<b>"Client out of memory"</b>
<b>Constant</b>	CLIENT_OUT_OF_MEMORY
<b>SAP Sybase Error Number</b>	2528
<b>SQL State</b>	08W65
<b>SQL Code</b>	-876L
<b>ODBC 2 State</b>	S1001
<b>ODBC 3 State</b>	HY001

<b>Error 876</b>	"Client out of memory"
<b>Severity Code</b>	<i>17</i> on page 2
<b>Probable Cause</b>	A failure occurred when the database client was trying to allocate memory.

## Messages 877 through 901

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 877</b>	"SETUSER not allowed in procedures, triggers, events, or batches"
<b>Constant</b>	SETUSER_NOT_IN_PROCEDURES
<b>SAP Sybase Error Number</b>	2534
<b>SQL State</b>	42W09
<b>SQL Code</b>	-877L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The SETUSER statement is not allowed in stored procedures, triggers, event handlers, or batches, and cannot be called from an EXECUTE IMMEDIATE statement.

<b>Error 878</b>	"Index '%1' cannot be clustered"
<b>Constant</b>	CLUSTERED_INDEX_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	2535
<b>SQL State</b>	42W74
<b>SQL Code</b>	-878L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the index that could not be made clustered.

## Errors and Warnings

<b>Error 878</b>	<b>"Index '%1' cannot be clustered"</b>
<b>Probable Cause</b>	You attempted to create a clustered index (including key indexes) but the new index cannot be created, for example, because the table already has a clustered index.
<b>Error 879</b>	<b>"An invalid multi-byte input character was encountered when converting from %1 to %2"</b>
<b>Constant</b>	ILLEGAL_MULTIBYTE_ERROR
<b>SAP Sybase Error Number</b>	2536
<b>SQL State</b>	WC003
<b>SQL Code</b>	-879L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The character set of the input string.
<b>Parameter 2</b>	The character set of the output string.
<b>Probable Cause</b>	While the server was performing character set conversion on an input string, an invalid multi-byte character was encountered. The operation was aborted.
<b>Error 881</b>	<b>"Character substitution was required when converting from %1 to %2"</b>
<b>Constant</b>	SIMPLE_SUBSTITUTION_ERROR
<b>SAP Sybase Error Number</b>	2540
<b>SQL State</b>	WC005
<b>SQL Code</b>	-881L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The character set of the input string.
<b>Parameter 2</b>	The character set of the output string.

<b>Error 881</b>	<b>"Character substitution was required when converting from %1 to %2"</b>
<b>Probable Cause</b>	While the server was performing character set conversion on an input string, some characters could not be represented in the database character set. The operation was aborted. See on_charset_conversion_failure option.

<b>Error 883</b>	<b>"Character conversion error or warning report is not available when the single-byte converter is used"</b>
<b>Constant</b>	CHARACTER_CONVERSION_REPORT_NOT_AVAILABLE
<b>SAP Sybase Error Number</b>	2544
<b>SQL State</b>	WC007
<b>SQL Code</b>	-883L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to set the on_charset_conversion_failure option to produce either a warning or error report. This setting is not available when the single-byte to single-byte converter is used.

<b>Error 887</b>	<b>"Virtual index creation with more than %1 columns"</b>
<b>Constant</b>	TOO_MANY_VIRTUAL_INDEX_COLUMNS
<b>SAP Sybase Error Number</b>	2548
<b>SQL State</b>	54W50
<b>SQL Code</b>	-887L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The maximum number of virtual index columns.
<b>Probable Cause</b>	You attempted to create a virtual index with more than the maximum number of columns.

## Errors and Warnings

<b>Error 888</b>	<b>"XML parser error: %1"</b>
<b>Constant</b>	XML_PARSER_ERROR
<b>SAP Sybase Error Number</b>	2550
<b>SQL State</b>	WX002
<b>SQL Code</b>	-888L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The error message returned by the XML parser.
<b>Probable Cause</b>	An XML instance will only parse correctly if it is well-formed as defined by the XML 1.0 specification.
<b>Error 889</b>	<b>"Statement contains an illegal usage of the non-deterministic function '%1'"</b>
<b>Constant</b>	NONDETERMINISTIC_FUNCTION
<b>SAP Sybase Error Number</b>	2551
<b>SQL State</b>	42W79
<b>SQL Code</b>	-889L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	The name of the non-deterministic user-defined function used in error.
<b>Probable Cause</b>	Non-deterministic functions cannot appear in a CHECK constraint, or any other type of integrity constraint. They may appear anywhere within a query, view, or derived table. However, if an aliased SELECT list expression contains a non-deterministic function, that alias cannot be referred to elsewhere in the query.
<b>Error 890</b>	<b>"Statement size or complexity exceeds server limits"</b>
<b>Constant</b>	SYNTACTIC_LIMIT

<b>Error 890</b>	<b>"Statement size or complexity exceeds server limits"</b>
<b>SAP Sybase Error Number</b>	2553
<b>SQL State</b>	54W01
<b>SQL Code</b>	-890L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	54000
<b>Severity Code</b>	<i>19</i> on page 2
<b>Probable Cause</b>	The statement contains one or more constructs whose size make it impossible to process. Increasing the maximum cache size, page size, or stack size may resolve this error. Consider rewriting the query so that the internal limit is not exceeded. For example, if the query contains a large IN-list, consider inserting the IN-list's values into a temporary table. Then rewrite the query to join this temporary table to the other table(s) in the original statement.
<b>Error 891</b>	<b>"Cannot convert between requested character sets '%1' and '%2'"</b>
<b>Constant</b>	FAILED_TO_START_CONVERTER_2_CHARSETS
<b>SAP Sybase Error Number</b>	2554
<b>SQL State</b>	WC008
<b>SQL Code</b>	-891L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the first requested character set encoding.
<b>Parameter 2</b>	The name of the second requested character set encoding.
<b>Probable Cause</b>	The server is unable to convert between the two specified character sets. This could happen when the dbicu and dbicutd DLLs are not installed.
<b>Error 892</b>	<b>"XPath parser error: %1"</b>
<b>Constant</b>	XQUERY_PARSER_ERROR

## Errors and Warnings

<b>Error 892</b>	"XPath parser error: %1"
<b>SAP Sybase Error Number</b>	2555
<b>SQL State</b>	WX003
<b>SQL Code</b>	-892L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The error message returned by the XPath parser.
<b>Probable Cause</b>	The XPath expression is illegal or uses features that are not currently supported.
<b>Error 893</b>	"Illegal flags value passed to OPENXML"
<b>Constant</b>	BAD_OPENXML_FLAG
<b>SAP Sybase Error Number</b>	2556
<b>SQL State</b>	WX004
<b>SQL Code</b>	-893L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The flags value passed to OPENXML as the third argument must be either 1 (attribute-centric mapping), or 2 (element-centric mapping).
<b>Error 894</b>	"Plan cannot be generated for this type of statement"
<b>Constant</b>	STMT_NOT_ALLOWED_IN_PLAN
<b>SAP Sybase Error Number</b>	2557
<b>SQL State</b>	0AW14
<b>SQL Code</b>	-894L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 894</b>	<b>"Plan cannot be generated for this type of statement"</b>
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You tried to get the execution plan for a statement type that is not supported.
<b>Error 895</b>	<b>"Encryption error: %1"</b>
<b>Constant</b>	ENCRYPT_ERROR
<b>SAP Sybase Error Number</b>	2558
<b>SQL State</b>	08W66
<b>SQL Code</b>	-895L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	Description of the error that occurred.
<b>Probable Cause</b>	An error occurred during encryption.
<b>Error 896</b>	<b>"Cannot delete PUBLIC option '%1' since user settings exist"</b>
<b>Constant</b>	UNSET_PUBLIC_ID
<b>SAP Sybase Error Number</b>	2560
<b>SQL State</b>	42W82
<b>SQL Code</b>	-896L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	Name of the option.
<b>Probable Cause</b>	You tried to delete a PUBLIC option, but there are user settings for the same option. The user settings must be deleted before the PUBLIC option is deleted.

## Errors and Warnings

<b>Error 897</b>	<b>"Illegal tag value: "%1"</b>
<b>Constant</b>	BAD_FOR_XML_EXPLICIT_TAG
<b>SAP Sybase Error Number</b>	2563
<b>SQL State</b>	WX005
<b>SQL Code</b>	-897L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The illegal tag value.
<b>Probable Cause</b>	FOR XML EXPLICIT and FOR JSON EXPLICIT tag values must be greater than 0 and less than 256. NULL values are not allowed in the Tag column.
<b>Error 898</b>	<b>"Unknown FOR XML EXPLICIT directive: "%1"</b>
<b>Constant</b>	BAD_FOR_XML_EXPLICIT_DIRECTIVE
<b>SAP Sybase Error Number</b>	2564
<b>SQL State</b>	WX006
<b>SQL Code</b>	-898L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The unknown directive.
<b>Probable Cause</b>	Legal FOR XML EXPLICIT directives are: id, idref, idrefs, hide, element, xml, and cdata. Legal FOR JSON EXPLICIT directives are: hide, and element.
<b>Error 899</b>	<b>"Illegal column name: "%1"</b>
<b>Constant</b>	BAD_FOR_XML_EXPLICIT_COLUMN_NAME
<b>SAP Sybase Error Number</b>	2565
<b>SQL State</b>	WX007

<b>Error 899</b>	<b>"Illegal column name: "%1"</b>
<b>SQL Code</b>	-899L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The reason the column name was illegal.
<b>Probable Cause</b>	FOR XML EXPLICIT and FOR JSON EXPLICIT column names can consist of up to four fields separated by exclamation marks. The first two columns must be named Tag and Parent.

<b>Error 900</b>	<b>"Parent not open: "%1"</b>
<b>Constant</b>	EXPLICIT_TAG_NOT_OPEN
<b>SAP Sybase Error Number</b>	2566
<b>SQL State</b>	WX008
<b>SQL Code</b>	-900L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The parent tag ID that is not among the open tags.
<b>Probable Cause</b>	FOR XML EXPLICIT and FOR JSON EXPLICIT require the parent tag for a row to be opened when that row is read. Check the order of the rows returned by the query with the FOR XML EXPLICIT or FOR JSON EXPLICIT clause removed.

<b>Error 901</b>	<b>"Undeclared tag ID: "%1"</b>
<b>Constant</b>	UNDECLARED_FOR_XML_EXPLICIT_TAG
<b>SAP Sybase Error Number</b>	2567
<b>SQL State</b>	WX009
<b>SQL Code</b>	-901L
<b>ODBC 2 State</b>	ERROR

<b>Error 901</b>	"Undeclared tag ID: '%1'"
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The value of the undeclared tag ID.
<b>Probable Cause</b>	Every value appearing in the Tag column of the table must be declared in the TagNumber field of at least one column name.

## Messages 902 through 923

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 902</b>	"Too few columns"
<b>Constant</b>	FOR_XML_EXPLICIT_TOO_FEW_COLUMNS
<b>SAP Sybase Error Number</b>	2568
<b>SQL State</b>	WX010
<b>SQL Code</b>	-902L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	FOR XML EXPLICIT and FOR JSON EXPLICIT require at least three columns: the tag column, the parent column, and one or more data columns.

<b>Error 903</b>	"CDATA has a name"
<b>Constant</b>	FOR_XML_EXPLICIT_NAMED_CDATA
<b>SAP Sybase Error Number</b>	2569
<b>SQL State</b>	WX011
<b>SQL Code</b>	-903L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

<b>Error 903</b>	<b>"CDATA has a name"</b>
<b>Probable Cause</b>	A CDATA directive in a FOR XML EXPLICIT query must not be given a name.

<b>Error 904</b>	<b>"Illegal ORDER BY in aggregate function"</b>
<b>Constant</b>	INVALID_ORDERBY_IN_AGGREGATE
<b>SAP Sybase Error Number</b>	2570
<b>SQL State</b>	42W90
<b>SQL Code</b>	-904L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	An ORDER BY can be used in an aggregate function only if there are no DISTINCT aggregates in the SELECT list, or there is a single DISTINCT aggregate with the DISTINCT column equal to the first column of the ORDER BY. Also, multiple ordered aggregates cannot be used in the same SELECT list unless they have the exact same ORDER BY clause.

<b>Error 905</b>	<b>"Invalid XQuery constructor"</b>
<b>Constant</b>	INVALID_XQUERY_CONSTRUCTOR
<b>SAP Sybase Error Number</b>	2571
<b>SQL State</b>	WX012
<b>SQL Code</b>	-905L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The XQuery constructor passed as the first argument to XMLGEN was not valid.

<b>Error 906</b>	<b>"XMLGEN evaluation failure"</b>
<b>Constant</b>	XMLGEN_EVALUATION_FAILURE

## Errors and Warnings

<b>Error 906</b>	<b>"XMLGEN evaluation failure"</b>
<b>SAP Sybase Error Number</b>	2572
<b>SQL State</b>	WX013
<b>SQL Code</b>	-906L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	One of the variables referenced in the XQuery constructor was not found in the list of arguments.
<b>Error 907</b>	<b>"No name for argument"</b>
<b>Constant</b>	NO_SQLX_ARGUMENT_NAME
<b>SAP Sybase Error Number</b>	2573
<b>SQL State</b>	WX014
<b>SQL Code</b>	-907L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Unnamed arguments cannot be used as XML element or attribute names. Name unnamed items in the argument list using AS.
<b>Error 908</b>	<b>"Invalid operation on a closed object"</b>
<b>Constant</b>	ULTRALITE_OBJ_CLOSED
<b>SAP Sybase Error Number</b>	2574
<b>SQL State</b>	55W14
<b>SQL Code</b>	-908L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

<b>Error 908</b>	<b>"Invalid operation on a closed object"</b>
<b>Probable Cause</b>	An illegal attempt was made to access a closed UltraLite object.
<b>Error 910</b>	<b>"System command failed with return code %1"</b>
<b>Constant</b>	SYSTEM_COMMAND_FAILED
<b>SAP Sybase Error Number</b>	2575
<b>SQL State</b>	38W01
<b>SQL Code</b>	-910L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Return code value.
<b>Probable Cause</b>	A non-zero return code resulted when executing a system command.
<b>Error 911</b>	<b>"Control character in XML output"</b>
<b>Constant</b>	CONTROL_CHARACTER_IN_XML_OUTPUT
<b>SAP Sybase Error Number</b>	2576
<b>SQL State</b>	WX015
<b>SQL Code</b>	-911L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A non-space character less than hex 20 was encountered while generating XML content. Consider base64 encoding strings that contain control characters before using them as XML content. This can be accomplished in a FOR XML query or SQLX function by casting the string to a type such as LONG BINARY.
<b>Error 912</b>	<b>"Insufficient memory for OPENXML query"</b>
<b>Constant</b>	XQUERY_MEMORY_ERROR

## Errors and Warnings

<b>Error 912</b>	<b>"Insufficient memory for OPENXML query"</b>
<b>SAP Sybase Error Number</b>	2577
<b>SQL State</b>	WX016
<b>SQL Code</b>	-912L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>17</i> on page 2
<b>Probable Cause</b>	The memory used by an OPENXML query may be proportional to the maximum distance between elements or attributes returned by a single row. For example, a query where some row uses the value from both the first and last element in the document may use memory proportional to the size of the document. One solution is to increase the cache size. Another is to break a query that refers to distant elements into several queries that refer to nearby elements and join the results.

<b>Error 913</b>	<b>"A transaction log file is required for auditing"</b>
<b>Constant</b>	AUDITING_WITHOUT_TRANSACTION_LOG
<b>SAP Sybase Error Number</b>	2578
<b>SQL State</b>	42W91
<b>SQL Code</b>	-913L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	This database is running without a transaction log file. You must use the Transaction Log utility (dblog) to create a transaction log file before using auditing.

<b>Error 914</b>	<b>"Cycle in common table expression references"</b>
<b>Constant</b>	COMMON_TABLE_EXPRESSION_CYCLE
<b>SAP Sybase Error Number</b>	2579
<b>SQL State</b>	42W93

<b>Error 914</b>	<b>"Cycle in common table expression references"</b>
<b>SQL Code</b>	-914L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Cycles involving multiple common table expressions are not allowed.
<b>Error 915</b>	<b>"Service type required for CREATE SERVICE"</b>
<b>Constant</b>	SERVICE_TYPE_REQUIRED
<b>SAP Sybase Error Number</b>	2580
<b>SQL State</b>	42W92
<b>SQL Code</b>	-915L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The CREATE SERVICE statement requires a service type to be specified.
<b>Error 916</b>	<b>"'%1' is an unrecognized service type"</b>
<b>Constant</b>	UNKNOWN_SERVICE_TYPE
<b>SAP Sybase Error Number</b>	2581
<b>SQL State</b>	42W94
<b>SQL Code</b>	-916L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The service type that is unrecognized.
<b>Probable Cause</b>	An unrecognized service type was specified.

## Errors and Warnings

<b>Error 918</b>	<b>"A user name must be specified if AUTHORIZATION is Off"</b>
<b>Constant</b>	SERVICE_REQUIRES_USER_NAME
<b>SAP Sybase Error Number</b>	2583
<b>SQL State</b>	42W96
<b>SQL Code</b>	-918L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A valid user name must be specified if AUTHORIZATION is Off.
<b>Error 919</b>	<b>"Service '%1' already exists"</b>
<b>Constant</b>	SERVICE_ALREADY_EXISTS
<b>SAP Sybase Error Number</b>	2584
<b>SQL State</b>	42W97
<b>SQL Code</b>	-919L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the service that already exists.
<b>Probable Cause</b>	You have attempted to create a service with a name that already exists in the database.
<b>Error 920</b>	<b>"Service '%1' not found"</b>
<b>Constant</b>	SERVICE_NOT_FOUND
<b>SAP Sybase Error Number</b>	2585
<b>SQL State</b>	42W98
<b>SQL Code</b>	-920L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 920</b>	<b>"Service "%1' not found"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the specified service that could not be found.
<b>Probable Cause</b>	You have attempted to reference a service with a name that does not exist in the database.

<b>Error 921</b>	<b>"Invalid recursive query"</b>
<b>Constant</b>	INVALID_RECURSION
<b>SAP Sybase Error Number</b>	2586
<b>SQL State</b>	42W99
<b>SQL Code</b>	-921L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A recursive query must consist of the UNION ALL of an initial query and an iteration query. The only set operation allowed in the iteration query is UNION ALL. A recursive reference to the name of the common table expression can only appear in the iteration query, and must not be in a SELECT that uses DISTINCT, ORDER BY, or an aggregate function. A recursive reference also cannot appear on the NULL-supplying side of an outer join, or in a subquery.

<b>Error 922</b>	<b>"No column list for recursive query"</b>
<b>Constant</b>	NO_RECURSIVE_COLUMN_LIST
<b>SAP Sybase Error Number</b>	2587
<b>SQL State</b>	42W9A
<b>SQL Code</b>	-922L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A common table expression defining a recursive query must have a column list.

<b>Error 923</b>	"Too many recursive iterations"
<b>Constant</b>	TOO_MANY_RECURSIVE_ITERATIONS
<b>SAP Sybase Error Number</b>	2588
<b>SQL State</b>	57015
<b>SQL Code</b>	-923L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A recursive query ran for more iterations than allowed by the current max_recursive_iterations option setting.

## Messages 924 through 944

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 924</b>	"Service '%1' in use"
<b>Constant</b>	SERVICE_IN_USE
<b>SAP Sybase Error Number</b>	2582
<b>SQL State</b>	55W15
<b>SQL Code</b>	-924L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the service that is in use.
<b>Probable Cause</b>	You have attempted to drop a service that is currently in use.

<b>Error 925</b>	"Invalid service name '%1'"
<b>Constant</b>	INVALID_SERVICE_NAME
<b>SAP Sybase Error Number</b>	2589
<b>SQL State</b>	42W95

<b>Error 925</b>	<b>"Invalid service name "%1"</b>
<b>SQL Code</b>	-925L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the service.
<b>Probable Cause</b>	You have attempted to create a service with an invalid name. The name may contain characters that are not allowed, or it may conflict with the URL PATH setting specified for the service.
<b>Error 926</b>	<b>"Host variable reference in service definition must be named"</b>
<b>Constant</b>	HOSTVAR_MUST_BE_NAMED
<b>SAP Sybase Error Number</b>	2590
<b>SQL State</b>	42W9B
<b>SQL Code</b>	-926L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You have attempted to create a service with an unnamed host variable reference.
<b>Error 927</b>	<b>"Service statement definition is inconsistent with service type"</b>
<b>Constant</b>	SERVICE_STATEMENT_MISMATCH
<b>SAP Sybase Error Number</b>	2591
<b>SQL State</b>	42W9C
<b>SQL Code</b>	-927L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

## Errors and Warnings

<b>Error 927</b>	<b>"Service statement definition is inconsistent with service type"</b>
<b>Probable Cause</b>	Either no statement was provided for a service whose type requires one, or a statement was provided when the service type does not allow one to be defined.
<b>Error 928</b>	<b>"Constant expressions must not appear in GROUP BY clause"</b>
<b>Constant</b>	NO_CONSTANTS_IN_GROUP_BY
<b>SAP Sybase Error Number</b>	2592
<b>SQL State</b>	42W9D
<b>SQL Code</b>	-928L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You used a constant in the GROUP BY clause. Constants must not appear in the GROUP BY clause for a query. References to columns in a view that are constant are permitted in a GROUP BY clause. Also, expressions that use a view column that is constant are permitted.
<b>Error 929</b>	<b>"Constraint "%1' not found"</b>
<b>Constant</b>	CONSTRAINT_NOT_FOUND
<b>SAP Sybase Error Number</b>	2593
<b>SQL State</b>	42U04
<b>SQL Code</b>	-929L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S23
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the constraint that could not be found.
<b>Probable Cause</b>	You misspelled the name of a constraint, or the constraint you are looking for is on a different table.

<b>Error 930</b>	<b>"Attempt to alter unnamed column constraint when named constraints exist"</b>
<b>Constant</b>	AMBIGUOUS_CONSTRAINT
<b>SAP Sybase Error Number</b>	2594
<b>SQL State</b>	42U05
<b>SQL Code</b>	-930
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S24
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You have asked for an unnamed column constraint to be altered, but there is at least one named constraint.
<b>Error 931</b>	<b>"Service definition requires a statement when authorization is off"</b>
<b>Constant</b>	SERVICE_AUTH_REQUIRED
<b>SAP Sybase Error Number</b>	2595
<b>SQL State</b>	42W9E
<b>SQL Code</b>	-931L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The service definition for the specified service type requires a statement to be specified when authorization is set to Off.
<b>Error 933</b>	<b>"A log is required for SAP Sybase IQ databases"</b>
<b>Constant</b>	IQ_LOG_REQUIRED
<b>SAP Sybase Error Number</b>	2597
<b>SQL State</b>	0AQ48
<b>SQL Code</b>	-933L
<b>ODBC 2 State</b>	37000

## Errors and Warnings

<b>Error 933</b>	<b>"A log is required for SAP Sybase IQ databases"</b>
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	SAP Sybase IQ databases require the use of a transaction log file.
<b>Error 934</b>	<b>"Unable to start specified database: Server must be upgraded to start database %1"</b>
<b>Constant</b>	UNABLE_TO_START_DATABASE_VER_NEWER
<b>SAP Sybase Error Number</b>	2598
<b>SQL State</b>	08W67
<b>SQL Code</b>	-934L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	Name of the database that could not be started, if known.
<b>Probable Cause</b>	The database server was unable to start the database since the database version is newer than the server version. The server must be upgraded to at least the version of the database to be able to start the database.
<b>Error 935</b>	<b>"Unable to start specified database: Log file error"</b>
<b>Constant</b>	UNABLE_TO_START_DATABASE_LOG_ERROR
<b>SAP Sybase Error Number</b>	2599
<b>SQL State</b>	08W68
<b>SQL Code</b>	-935L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2

<b>Error 935</b>	<b>"Unable to start specified database: Log file error"</b>
<b>Probable Cause</b>	The database server was unable to start the database since the log file is missing, for a different database, or some other reason. Check the server messages window for more details.
<b>Error 936</b>	<b>"Too many constraints in database"</b>
<b>Constant</b>	TOO_MANY_CONSTRAINTS
<b>SAP Sybase Error Number</b>	2600
<b>SQL State</b>	54W02
<b>SQL Code</b>	-936L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	An attempt to create a new constraint failed because the corresponding system table is full. Reloading the database will reclaim any unused space.
<b>Error 937</b>	<b>"Invalid reference to or operation on constraint "%1"</b>
<b>Constant</b>	INVALID_CONSTRAINT_REF
<b>SAP Sybase Error Number</b>	2601
<b>SQL State</b>	42U06
<b>SQL Code</b>	-937L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S23
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the constraint that cannot be used for the specified purpose.
<b>Probable Cause</b>	You specified an invalid operation on a constraint. For example, you tried to alter a primary key constraint.
<b>Error 938</b>	<b>"Recursion is not allowed without the RECURSIVE keyword"</b>
<b>Constant</b>	RECURSIVE_KEYWORD_REQUIRED

## Errors and Warnings

<b>Error 938</b>	<b>"Recursion is not allowed without the RECURSIVE keyword"</b>
<b>SAP Sybase Error Number</b>	2602
<b>SQL State</b>	42WA0
<b>SQL Code</b>	-938L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The common table expressions for a recursive query must be defined using a WITH RECURSIVE clause.
<b>Error 939</b>	<b>"Invalid setting for HTTP option '%1'"</b>
<b>Constant</b>	INVALID_HTTP_OPTION_SETTING
<b>SAP Sybase Error Number</b>	2603
<b>SQL State</b>	42W83
<b>SQL Code</b>	-939L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the invalid HTTP option.
<b>Probable Cause</b>	You supplied an invalid value for an HTTP option. Some options allow only numeric values, while other options allow only the values On and Off.
<b>Error 940</b>	<b>"Invalid setting for HTTP header '%1'"</b>
<b>Constant</b>	INVALID_HTTP_HEADER_SETTING
<b>SAP Sybase Error Number</b>	2604
<b>SQL State</b>	42W84
<b>SQL Code</b>	-940L
<b>ODBC 2 State</b>	37000

<b>Error 940</b>	"Invalid setting for HTTP header "%1"
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the invalid HTTP header.
<b>Probable Cause</b>	You supplied an invalid value for an HTTP header.

<b>Error 941</b>	"jConnect does not support encryption"
<b>Constant</b>	NO_ENCRYPTION_FOR_JCONNECT
<b>SAP Sybase Error Number</b>	2605
<b>SQL State</b>	08W69
<b>SQL Code</b>	-941L
<b>ODBC 2 State</b>	08004
<b>ODBC 3 State</b>	08004
<b>Severity Code</b>	<i>18</i> on page 2
<b>Probable Cause</b>	You supplied an encryption type for a connection using jConnect. jConnect does not support encryption.

<b>Error 942</b>	"A workload capture (%1) is already in progress"
<b>Constant</b>	WORKLOAD_CAPTURE_ALREADY_EXISTS
<b>SAP Sybase Error Number</b>	2606
<b>SQL State</b>	WW029
<b>SQL Code</b>	-942L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the workload capture that is already in progress.
<b>Probable Cause</b>	You have tried to initiate a workload capture when one is already in progress. You need to wait for the other capture to complete.

## Errors and Warnings

<b>Error 943</b>	<b>"No workload capture currently exists"</b>
<b>Constant</b>	WORKLOAD_CAPTURE_DOES_NOT_EXIST
<b>SAP Sybase Error Number</b>	2607
<b>SQL State</b>	WW030
<b>SQL Code</b>	-943L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You have tried to stop, pause, resume, or get the status of a workload capture, but no workload captures exist.
<b>Error 944</b>	<b>"Too many expressions in GROUP BY list for ROLLUP, CUBE, or GROUPING SETS operation"</b>
<b>Constant</b>	TOO_MANY_GROUPING_EXPRESSIONS
<b>SAP Sybase Error Number</b>	2608
<b>SQL State</b>	42WA1
<b>SQL Code</b>	-944L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You specified too many expressions in the GROUP BY list for the requested ROLLUP, CUBE, or GROUPING SETS operation. The current environment where SQL Anywhere is executing cannot support this number of expressions in the GROUP BY list for the requested operation.

## Messages 945 through 964

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 945</b>	<b>"Recursive column %1: conversion from '%2' to '%3' loses precision"</b>
<b>Constant</b>	BAD_RECURSIVE_COLUMN_CONVERSION

<b>Error 945</b>	<b>"Recursive column %1: conversion from '%2' to '%3' loses precision"</b>
<b>SAP Sybase Error Number</b>	2609
<b>SQL State</b>	42WA2
<b>SQL Code</b>	-945L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Column number of the recursive subquery.
<b>Parameter 2</b>	Type converted from.
<b>Parameter 3</b>	Type converted to.
<b>Probable Cause</b>	Every column in the recursive subquery must be convertible to the type of the corresponding column in the initial subquery without loss of precision. Try casting the column in the initial subquery to an appropriate type.
<b>Error 946</b>	<b>"Result set not permitted in '%1'"</b>
<b>Constant</b>	RESULT_SET_NOT_PERMITTED
<b>SAP Sybase Error Number</b>	2610
<b>SQL State</b>	09W03
<b>SQL Code</b>	-946L
<b>ODBC 2 State</b>	07005
<b>ODBC 3 State</b>	07005
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of object containing the invalid statement.
<b>Probable Cause</b>	You attempted to execute a SELECT statement in a context where a result set is not permitted.
<b>Error 947</b>	<b>"Window '%1' not found"</b>
<b>Constant</b>	WINDOW_NOT_FOUND
<b>SAP Sybase Error Number</b>	2611

## Errors and Warnings

<b>Error 947</b>	<b>"Window '%1' not found"</b>
<b>SQL State</b>	42WA3
<b>SQL Code</b>	-947L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the window that could not be found.
<b>Probable Cause</b>	You have attempted to reference a window name that is not defined in the window list of the SELECT statement.
<b>Error 948</b>	<b>"PARTITION BY not allowed in reference to window '%1'"</b>
<b>Constant</b>	PARTITIONBY_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	2612
<b>SQL State</b>	42WA4
<b>SQL Code</b>	-948L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the window.
<b>Probable Cause</b>	When an existing window name is referenced from an inline window specification, the inline specification must not have a PARTITION BY clause.
<b>Error 949</b>	<b>"ORDER BY not allowed in window '%1'"</b>
<b>Constant</b>	ORDERBY_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	2613
<b>SQL State</b>	42WA5
<b>SQL Code</b>	-949L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 949</b>	<b>"ORDER BY not allowed in window "%1"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the window.
<b>Probable Cause</b>	When an existing window name is referenced from an inline window specification, either the inline window or the referenced window may have an ORDER BY, but not both.
<b>Error 950</b>	<b>"Frame not allowed for window "%1"</b>
<b>Constant</b>	FRAME_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	2614
<b>SQL State</b>	42WA6
<b>SQL Code</b>	-950L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the window.
<b>Probable Cause</b>	Frames are not allowed on windows referenced from inline window specifications.
<b>Error 951</b>	<b>"Cannot access schema file "%1"</b>
<b>Constant</b>	CANNOT_ACCESS_SCHEMA_FILE
<b>SAP Sybase Error Number</b>	2615
<b>SQL State</b>	WW031
<b>SQL Code</b>	-951L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the file or indication that no name was given.
<b>Probable Cause</b>	UltraLite requires a schema file to perform the current operation. Either no schema file was specified or the one specified was not accessible or was corrupt.

## Errors and Warnings

<b>Error 952</b>	<b>"The status of the last synchronization upload is unknown"</b>
<b>Constant</b>	SYNC_STATUS_UNKNOWN
<b>SAP Sybase Error Number</b>	2616
<b>SQL State</b>	WW032
<b>SQL Code</b>	-952L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The status of the last synchronization upload is unknown. The current operation cannot proceed until a successful upload is synchronized.
<b>Error 953</b>	<b>"A schema upgrade is not currently allowed"</b>
<b>Constant</b>	SCHEMA_UPGRADE_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	2617
<b>SQL State</b>	WW033
<b>SQL Code</b>	-953L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A schema upgrade cannot proceed because of concurrent use of the database. For example, all cursors must be closed before a schema upgrade can occur.
<b>Error 954</b>	<b>"The database '%1' was not found"</b>
<b>Constant</b>	ULTRALITE_DATABASE_NOT_FOUND
<b>SAP Sybase Error Number</b>	2618
<b>SQL State</b>	WW034
<b>SQL Code</b>	-954L
<b>ODBC 2 State</b>	ERROR

<b>Error 954</b>	<b>"The database "%1' was not found"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the database specified or the default database name.
<b>Probable Cause</b>	The named database was not found. Ensure your connection string properly names the desired database.
<b>Error 955</b>	<b>"This connection already exists"</b>
<b>Constant</b>	CONNECTION_ALREADY_EXISTS
<b>SAP Sybase Error Number</b>	2619
<b>SQL State</b>	WW035
<b>SQL Code</b>	-955L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A connection with the given SQLCA and name (or no name) already exists. Before connecting you must disconnect the existing connection, or specify a different connection name.
<b>Error 956</b>	<b>"Information for synchronization is incomplete or invalid, check "%1"</b>
<b>Constant</b>	SYNC_INFO_INVALID
<b>SAP Sybase Error Number</b>	2620
<b>SQL State</b>	WW036
<b>SQL Code</b>	-956L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the parameter not properly initialized.

## Errors and Warnings

<b>Error 956</b>	<b>"Information for synchronization is incomplete or invalid, check \"%1\""</b>
<b>Probable Cause</b>	Information for synchronization is incomplete or invalid. Correct the indicated parameter before attempting to synchronize again. If 'init_verify' is indicated, the InitSyncInfo function was not called.
<b>Error 957</b>	<b>"Invalid preceding or following size in OLAP function"</b>
<b>Constant</b>	INVALID_FRAME_BOUNDARY
<b>SAP Sybase Error Number</b>	2621
<b>SQL State</b>	22X13
<b>SQL Code</b>	-957L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The expression for the preceding or following size evaluated to NULL or a negative value.
<b>Error 958</b>	<b>"Password cannot be longer than %1 characters"</b>
<b>Constant</b>	PASSWORD_TOO_LONG
<b>SAP Sybase Error Number</b>	2622
<b>SQL State</b>	54W08
<b>SQL Code</b>	-958L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	54000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	The password is longer than that allowed by the server.
<b>Error 959</b>	<b>"Compression error: %1"</b>
<b>Constant</b>	COMPRESSION_ERROR
<b>SAP Sybase Error Number</b>	2623
<b>SQL State</b>	WW037

<b>Error 959</b>	"Compression error: %1"
<b>SQL Code</b>	-959L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	An error occurred during compression.
<b>Error 960</b>	"Decompression error: %1"
<b>Constant</b>	DECOMPRESSION_ERROR
<b>SAP Sybase Error Number</b>	2624
<b>SQL State</b>	WW038
<b>SQL Code</b>	-960L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	An error occurred during decompression.
<b>Error 961</b>	"Input string is not base64-encoded"
<b>Constant</b>	BASE64_DECODING_ERROR
<b>SAP Sybase Error Number</b>	2625
<b>SQL State</b>	WW039
<b>SQL Code</b>	-961L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	An error occurred during base64 decoding.
<b>Error 962</b>	"Argument to GROUPING aggregate must be a grouping column in the GROUP BY clause"
<b>Constant</b>	INVALID_GROUPING_AGGREGATE

## Errors and Warnings

<b>Error 962</b>	<b>"Argument to GROUPING aggregate must be a grouping column in the GROUP BY clause"</b>
<b>SAP Sybase Error Number</b>	2626
<b>SQL State</b>	42WA7
<b>SQL Code</b>	-962L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	Only a grouping column is permitted as an argument to the GROUPING aggregate function. An argument that contains anything other than a single grouping column expression will not be accepted.
<b>Error 963</b>	<b>"Password contains an illegal character"</b>
<b>Constant</b>	ILLEGAL_PASSWORD
<b>SAP Sybase Error Number</b>	2627
<b>SQL State</b>	08005
<b>SQL Code</b>	-963L
<b>ODBC 2 State</b>	28000
<b>ODBC 3 State</b>	28000
<b>Severity Code</b>	<i>11</i> on page 2
<b>Probable Cause</b>	The specified password contains an illegal character.
<b>Error 964</b>	<b>"Window function used in predicate"</b>
<b>Constant</b>	ILLEGAL_WINDOW_PREDICATE
<b>SAP Sybase Error Number</b>	2628
<b>SQL State</b>	42WA8
<b>SQL Code</b>	-964L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 964</b>	"Window function used in predicate"
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A window function was used in the WHERE or HAVING clause of a SELECT statement. Consider making the SELECT into a derived table, putting the window function in the SELECT list of the derived table, and changing the predicate to reference the derived column.

## Messages 965 through 985

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 965</b>	"Window function requires ORDER BY"
<b>Constant</b>	OBSOLETE_ORDERBY_REQUIRED
<b>SAP Sybase Error Number</b>	2629
<b>SQL State</b>	42WA9
<b>SQL Code</b>	-965L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Rank functions and window functions that use the RANGE keyword must specify an ORDER BY clause.

<b>Error 966</b>	"Composite ORDER BY not allowed with RANGE"
<b>Constant</b>	ILLEGAL_COMPOSITE_ORDERBY
<b>SAP Sybase Error Number</b>	2630
<b>SQL State</b>	42WAA
<b>SQL Code</b>	-966L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Window functions that use the RANGE keyword may only ORDER BY a single column.

## Errors and Warnings

<b>Error 967</b>	<b>"Backup file "%1' already exists"</b>
<b>Constant</b>	BACKUP_FILE_EXISTS
<b>SAP Sybase Error Number</b>	2631
<b>SQL State</b>	WB012
<b>SQL Code</b>	-967L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the file.
<b>Probable Cause</b>	A file that would normally be created by this BACKUP statement already exists.
<b>Error 968</b>	<b>"User "%1' already has EXECUTE permission"</b>
<b>Constant</b>	ALREADY_HAS_EXEC_PERMS
<b>SAP Sybase Error Number</b>	2632
<b>SQL State</b>	42WAB
<b>SQL Code</b>	-968L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the user that already has EXECUTE permission.
<b>Probable Cause</b>	You attempted to give EXECUTE permission on a stored procedure to a user that already has EXECUTE permission on that procedure.
<b>Error 969</b>	<b>"Required operators excluded"</b>
<b>Constant</b>	REQUIRED_OPERATORS_EXCLUDED
<b>SAP Sybase Error Number</b>	2633
<b>SQL State</b>	WI011
<b>SQL Code</b>	-969L

<b>Error 969</b>	<b>"Required operators excluded"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>18</i> on page 2
<b>Probable Cause</b>	The database server was unable to construct a valid access plan for the given request because required data flow operators were excluded by the exclude_operators option. Re-enable the required operators to execute the statement.
<b>Error 970</b>	<b>"Invalid hint specified for table "%1"</b>
<b>Constant</b>	INVALID_HINT
<b>SAP Sybase Error Number</b>	2634
<b>SQL State</b>	42U07
<b>SQL Code</b>	-970L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	The name of the table for which the hint was specified.
<b>Probable Cause</b>	A hint was specified for the current statement is not valid in this context. In a single statement, all references to a table must specify the same hint or none at all.
<b>Error 971</b>	<b>"Checksums are not enabled in this database"</b>
<b>Constant</b>	CHECKSUMS_NOT_ENABLED
<b>SAP Sybase Error Number</b>	2637
<b>SQL State</b>	WW042
<b>SQL Code</b>	-971L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

## Errors and Warnings

<b>Error 971</b>	<b>"Checksums are not enabled in this database"</b>
<b>Probable Cause</b>	An attempt was made to perform checksum validation but the database does not have checksums enabled.
<b>Error 972</b>	<b>"Database page size too small: %1"</b>
<b>Constant</b>	PAGE_SIZE_TOO_SMALL
<b>SAP Sybase Error Number</b>	2638
<b>SQL State</b>	54W03
<b>SQL Code</b>	-972L
<b>ODBC 2 State</b>	08004
<b>ODBC 3 State</b>	08004
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Database name.
<b>Probable Cause</b>	You attempted to load statistics that were too large for the current database page size. Rebuilding this database with a larger page size could prevent this error.
<b>Error 973</b>	<b>"The string is too long (%1)"</b>
<b>Constant</b>	STRING_PARM_TOO_LONG
<b>SAP Sybase Error Number</b>	2639
<b>SQL State</b>	54W06
<b>SQL Code</b>	-973L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	54000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	The string that is longer than that allowed by the server.
<b>Probable Cause</b>	The string is longer than that allowed by the server.
<b>Error 974</b>	<b>"File I/O failed for "%1"</b>
<b>Constant</b>	DEVICE_IO_FAILED

<b>Error 974</b>	<b>"File I/O failed for '%1'"</b>
<b>SAP Sybase Error Number</b>	2640
<b>SQL State</b>	WW043
<b>SQL Code</b>	-974L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The file name.
<b>Probable Cause</b>	An error occurred while trying to access the file. If the file is located on a removable media card, the card may have been removed.
<b>Error 975</b>	<b>"Incorrect volume ID for '%1'"</b>
<b>Constant</b>	INCORRECT_VOLUME_ID
<b>SAP Sybase Error Number</b>	2641
<b>SQL State</b>	WW044
<b>SQL Code</b>	-975L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The file name.
<b>Probable Cause</b>	The file can be accessed, but the volume ID has changed. Insert the original removable media card.
<b>Error 976</b>	<b>"Could not load the encryption DLL \'%1\No message</b>
<b>Constant</b>	MISSING_ENCRYPTION_DLL
<b>SAP Sybase Error Number</b>	2643
<b>SQL State</b>	08W70
<b>SQL Code</b>	-976L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 976</b>	<b>"Could not load the encryption DLL \\"%1\No message</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	19 on page 2
<b>Parameter 1</b>	The name of the encryption DLL that could not be loaded.
<b>Probable Cause</b>	An attempt to load the encryption DLL failed.
<b>Error 978</b>	<b>"Directory for output file does not exist"</b>
<b>Constant</b>	DIRECTORY_INACCESSIBLE
<b>SAP Sybase Error Number</b>	2645
<b>SQL State</b>	WW047
<b>SQL Code</b>	-978L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	20 on page 2
<b>Probable Cause</b>	The file cannot be written because the directory does not exist.
<b>Error 979</b>	<b>"Output file cannot be written"</b>
<b>Constant</b>	CANNOT_WRITE_FILE
<b>SAP Sybase Error Number</b>	2646
<b>SQL State</b>	WW048
<b>SQL Code</b>	-979L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	20 on page 2
<b>Probable Cause</b>	Unable to create or write an output file. The file may be locked or read-only.
<b>Error 980</b>	<b>"The URI \"%1' is invalid"</b>
<b>Constant</b>	INVALID_URI
<b>SAP Sybase Error Number</b>	2647

<b>Error 980</b>	<b>"The URI '%1' is invalid"</b>
<b>SQL State</b>	WW049
<b>SQL Code</b>	-980L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The invalid URI.
<b>Probable Cause</b>	The specified URI is not valid.
<b>Error 981</b>	<b>"Unable to connect to the remote host specified by "%1"</b>
<b>Constant</b>	UNABLE_TO_CONNECT_TO_HOST
<b>SAP Sybase Error Number</b>	2648
<b>SQL State</b>	WW050
<b>SQL Code</b>	-981L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>19</i> on page 2
<b>Parameter 1</b>	The URI referencing the remote host.
<b>Probable Cause</b>	A connection could not be initiated to the remote server.
<b>Error 982</b>	<b>"Connection timed out"</b>
<b>Constant</b>	REMOTE_CONNECTION_TIMED_OUT
<b>SAP Sybase Error Number</b>	2649
<b>SQL State</b>	WW051
<b>SQL Code</b>	-982L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>19</i> on page 2
<b>Probable Cause</b>	The connection to the remote host timed out due to inactivity.

## Errors and Warnings

<b>Error 983</b>	<b>"HTTP request failed. Status code "%1"</b>
<b>Constant</b>	HTTP_REQUEST_FAILED
<b>SAP Sybase Error Number</b>	2650
<b>SQL State</b>	WW052
<b>SQL Code</b>	-983L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>19</i> on page 2
<b>Parameter 1</b>	The HTTP status code.
<b>Probable Cause</b>	The HTTP request returned a status code that indicated failure.
<b>Error 984</b>	<b>"Could not initialize the encryption DLL: "%1"</b>
<b>Constant</b>	ENCRYPTION_INITIALIZATION_FAILED
<b>SAP Sybase Error Number</b>	2651
<b>SQL State</b>	WW053
<b>SQL Code</b>	-984L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>19</i> on page 2
<b>Parameter 1</b>	Reason the initialization failed, if known.
<b>Probable Cause</b>	An attempt to initialize the encryption DLL failed.
<b>Error 985</b>	<b>"The database name 'utility_db' is reserved for the utility database."</b>
<b>Constant</b>	DB_ALIAS_RESERVED_UTILDB
<b>SAP Sybase Error Number</b>	2845
<b>SQL State</b>	08W20
<b>SQL Code</b>	-985L
<b>ODBC 2 State</b>	ERROR

<b>Error 985</b>	"The database name 'utility_db' is reserved for the utility database."
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>19</i> on page 2
<b>Probable Cause</b>	You are attempting to start a database with the name "utility_db". This name is reserved for the utility database.

## Messages 986 through 1005

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 986</b>	"Invalid procedure type '%1'"
<b>Constant</b>	INVALID_PROCEDURE_TYPE
<b>SAP Sybase Error Number</b>	2653
<b>SQL State</b>	WW055
<b>SQL Code</b>	-986L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The procedure type.
<b>Probable Cause</b>	A procedure or function was specified with an invalid type.

<b>Error 987</b>	"Invalid procedure subtype '%1' for type '%2'"
<b>Constant</b>	INVALID_PROCEDURE_SUBTYPE
<b>SAP Sybase Error Number</b>	2654
<b>SQL State</b>	WW056
<b>SQL Code</b>	-987L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The procedure subtype.

## Errors and Warnings

<b>Error 987</b>	<b>"Invalid procedure subtype "%1' for type "%2"</b>
<b>Parameter 2</b>	The procedure type.
<b>Probable Cause</b>	A procedure or function was specified with an invalid subtype for the given procedure type.
<b>Error 988</b>	<b>"Invalid response from the HTTP server"</b>
<b>Constant</b>	INVALID_HTTP_RESPONSE
<b>SAP Sybase Error Number</b>	2655
<b>SQL State</b>	WW057
<b>SQL Code</b>	-988L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>19</i> on page 2
<b>Probable Cause</b>	The response from the remote HTTP server was invalid. It may have been empty, malformed, missing header information, and so on.
<b>Error 989</b>	<b>"NAMESPACE attribute is not valid with procedure type "%1"</b>
<b>Constant</b>	INVALID_NAMESPACE_ATTRIBUTE
<b>SAP Sybase Error Number</b>	2656
<b>SQL State</b>	WW058
<b>SQL Code</b>	-989L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The NAMESPACE attribute on the procedure.
<b>Probable Cause</b>	The NAMESPACE attribute is only applicable to procedures of type SOAP.
<b>Error 990</b>	<b>"The secure connection to the remote host failed: %1"</b>
<b>Constant</b>	SECURE_CONNECTION_FAILED

<b>Error 990</b>	<b>"The secure connection to the remote host failed: %1"</b>
<b>SAP Sybase Error Number</b>	2657
<b>SQL State</b>	WW059
<b>SQL Code</b>	-990L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>19</i> on page 2
<b>Parameter 1</b>	A message describing the error that occurred.
<b>Probable Cause</b>	The server was unable to initiate a secure connection with the remote host.

<b>Error 991</b>	<b>"Clause "%1' has invalid attribute "%2"</b>
<b>Constant</b>	INVALID_PROCEDURE_ATTRIBUTE
<b>SAP Sybase Error Number</b>	2658
<b>SQL State</b>	WW060
<b>SQL Code</b>	-991L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The attribute on the procedure.
<b>Parameter 2</b>	The attribute value or cause of failure.
<b>Probable Cause</b>	The attribute value specified on the procedure is not valid.

<b>Error 992</b>	<b>"The specified listener could not be registered"</b>
<b>Constant</b>	CANNOT_REGISTER_LISTENER
<b>SAP Sybase Error Number</b>	2659
<b>SQL State</b>	54W04
<b>SQL Code</b>	-992L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 992</b>	<b>"The specified listener could not be registered"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>17</i> on page 2
<b>Probable Cause</b>	The specified listener could not be registered because the maximum number of listeners has been reached, the class name is already in use, or system resources are not available.
<b>Error 993</b>	<b>"LOAD TABLE not allowed on temporary table with ON COMMIT DELETE ROWS"</b>
<b>Constant</b>	INVALID_TEMP_TABLE_COMMIT_ACTION
<b>SAP Sybase Error Number</b>	2660
<b>SQL State</b>	WL007
<b>SQL Code</b>	-993L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The LOAD TABLE statement automatically commits at completion. If a temporary table being loaded was declared with ON COMMIT DELETE ROWS, the rows are discarded at completion.
<b>Error 994</b>	<b>"Too many arguments for function or procedure "%1"</b>
<b>Constant</b>	TOO_MANY_ARGUMENTS
<b>SAP Sybase Error Number</b>	2661
<b>SQL State</b>	42WAC
<b>SQL Code</b>	-994L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the function or procedure.

<b>Error 994</b>	<b>"Too many arguments for function or procedure "%1"</b>
<b>Probable Cause</b>	You supplied an argument list that the database server cannot handle. This can happen if the argument list of the function or stored procedure is too long. Rebuilding the database with a larger page size could prevent this error.
<b>Error 995</b>	<b>"Warning detected when optimizing SELECT INTO is treated as an error"</b>
<b>Constant</b>	SELECT_INTO_WARNING_TREATED_AS_ERROR
<b>SAP Sybase Error Number</b>	2662
<b>SQL State</b>	WP016
<b>SQL Code</b>	-995L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The SELECT...INTO #TEMPTABLE statement cannot proceed if a warning is detected while optimizing the query. To fix the problem, test the query by removing the INTO clause, and resolve the reported warning.
<b>Error 996</b>	<b>"Specified local connection ID not found"</b>
<b>Constant</b>	LOCAL_CONNECTION_NOT_FOUND
<b>SAP Sybase Error Number</b>	2663
<b>SQL State</b>	WO024
<b>SQL Code</b>	-996L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	There is no connection with the specified connection ID.

## Errors and Warnings

<b>Error 997</b>	<b>"Local connection ID does not refer to the current database"</b>
<b>Constant</b>	LOCAL_CONNECTION_NOT_TO_CURRENT_DB
<b>SAP Sybase Error Number</b>	2664
<b>SQL State</b>	WO025
<b>SQL Code</b>	-997L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The specified connection ID is for a connection to a database other than the current database.
<b>Error 998</b>	<b>"Cannot close a remote JDBC connection that is not the current connection"</b>
<b>Constant</b>	CANNOT_CLOSE_JDBC_CONNECTION
<b>SAP Sybase Error Number</b>	2665
<b>SQL State</b>	WO026
<b>SQL Code</b>	-998L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	When attempting to close a remote JDBC connection, the specified connection must be the local connection.
<b>Error 999</b>	<b>"Invalid request log format on line %1"</b>
<b>Constant</b>	INVALID_REQUEST_LOG_FORMAT
<b>SAP Sybase Error Number</b>	2667
<b>SQL State</b>	WW020
<b>SQL Code</b>	-999L
<b>ODBC 2 State</b>	ERROR

<b>Error 999</b>	"Invalid request log format on line %1"
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The line number in the log file.
<b>Probable Cause</b>	The request log file format is invalid. The request log may have been created with an older version of the software.

<b>Error 1000</b>	"Temporary space limit exceeded"
<b>Constant</b>	TEMP_SPACE_LIMIT
<b>SAP Sybase Error Number</b>	2668
<b>SQL State</b>	54W05
<b>SQL Code</b>	-1000L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>19</i> on page 2
<b>Probable Cause</b>	The connection has exceeded its temporary-space usage limit. This limit is based in part on the amount of free-space remaining on the drive containing the temporary file. Try deleting unused files from the drive, or placing the temporary file on a drive with more space available. See the -dt server option to specify a directory for temporary files.

<b>Error 1001</b>	"Parameter '%1' in procedure or function '%2' does not have a default value"
<b>Constant</b>	NO_DEFAULT_FOR_PARM
<b>SAP Sybase Error Number</b>	2669
<b>SQL State</b>	08W71
<b>SQL Code</b>	-1001L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

## Errors and Warnings

<b>Error 1001</b>	<b>"Parameter "%1' in procedure or function "%2' does not have a default value"</b>
<b>Parameter 1</b>	The name of the parameter.
<b>Parameter 2</b>	The name of the procedure or function.
<b>Probable Cause</b>	An attempt was made to use DEFAULT as a procedure or function argument, but the corresponding parameter does not have a default value.
<b>Error 1002</b>	<b>"The option "%1' is not recognized"</b>
<b>Constant</b>	UNRECOGNIZED_OPTION
<b>SAP Sybase Error Number</b>	2670
<b>SQL State</b>	WW062
<b>SQL Code</b>	-1002L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the option.
<b>Probable Cause</b>	The specified option was not recognized. The option may have been spelled incorrectly.
<b>Error 1003</b>	<b>"Too many distinct group mappings for integrated user"</b>
<b>Constant</b>	INTEGRATED_LOGON_TOO_MANY_MAPPINGS
<b>SAP Sybase Error Number</b>	2671
<b>SQL State</b>	28W10
<b>SQL Code</b>	-1003L
<b>ODBC 2 State</b>	28000
<b>ODBC 3 State</b>	28000
<b>Severity Code</b>	<i>16</i> on page 2

<b>Error 1003</b>	<b>"Too many distinct group mappings for integrated user"</b>
<b>Probable Cause</b>	The integrated user does not have an explicit mapping in the database but does have group mappings. There are too many distinct group mappings. You must either reduce the number of distinct group mappings or add an explicit mapping for the user.
<b>Error 1004</b>	<b>"Unable to start specified database: "%1' is not a database"</b>
<b>Constant</b>	FILE_NOT_DB
<b>SAP Sybase Error Number</b>	2672
<b>SQL State</b>	08W85
<b>SQL Code</b>	-1004L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The name of the database file.
<b>Probable Cause</b>	The specified file is not a valid database file.
<b>Error 1005</b>	<b>"Unable to start specified database: "%1' was created by a different version of the software"</b>
<b>Constant</b>	FILE_WRONG_VERSION
<b>SAP Sybase Error Number</b>	2673
<b>SQL State</b>	08W86
<b>SQL Code</b>	-1005L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The name of the database file.
<b>Probable Cause</b>	The specified database file was created by a different version of the software, and it cannot be read by this version.

## 1006 - 1217

---

### Messages 1006 through 1028

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1006</b>	<b>"Unable to start specified database: '%1' is not a valid database file"</b>
<b>Constant</b>	FILE_BAD_DB
<b>SAP Sybase Error Number</b>	2674
<b>SQL State</b>	08W87
<b>SQL Code</b>	-1006L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The name of the database file.
<b>Probable Cause</b>	The specified file is not a valid database.
<b>Error 1007</b>	<b>"Unable to start specified database: '%1' is an invalid transaction log"</b>
<b>Constant</b>	CORRUPT_REDO
<b>SAP Sybase Error Number</b>	2675
<b>SQL State</b>	08W88
<b>SQL Code</b>	-1007L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The name of the transaction log file.
<b>Probable Cause</b>	The specified file is not a valid transaction log.

<b>Error 1008</b>	<b>"Unable to start specified database: '%1' is an invalid transaction log mirror"</b>
<b>Constant</b>	CORRUPT_REDO_MIRROR
<b>SAP Sybase Error Number</b>	2676
<b>SQL State</b>	08W72
<b>SQL Code</b>	-1008L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The name of the transaction log mirror file.
<b>Probable Cause</b>	The specified file is not a valid transaction log mirror.
<b>Error 1009</b>	<b>"Unable to start specified database: The transaction log '%1' or its mirror '%2' is invalid"</b>
<b>Constant</b>	CORRUPT_REDO_OR_MIRROR
<b>SAP Sybase Error Number</b>	2677
<b>SQL State</b>	08W73
<b>SQL Code</b>	-1009L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The name of the transaction log file.
<b>Parameter 2</b>	The name of the transaction log mirror file.
<b>Probable Cause</b>	The transaction log differs from the transaction log mirror. Either the transaction log or its mirror is invalid.
<b>Error 1010</b>	<b>"Unable to start specified database: '%1' not expecting any operations in transaction log"</b>
<b>Constant</b>	EXPECTING_NO_REDO
<b>SAP Sybase Error Number</b>	2678

## Errors and Warnings

<b>Error 1010</b>	<b>"Unable to start specified database: "%1' not expecting any operations in transaction log"</b>
<b>SQL State</b>	08W74
<b>SQL Code</b>	-1010L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The name of the transaction log file.
<b>Probable Cause</b>	The transaction log contains operations, but the database server was not expecting any.
<b>Error 1011</b>	<b>"Unable to start specified database: Unknown encryption algorithm"</b>
<b>Constant</b>	UNKNOWN_ENCRYPTION_ALGORITHM
<b>SAP Sybase Error Number</b>	2679
<b>SQL State</b>	08W75
<b>SQL Code</b>	-1011L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2
<b>Probable Cause</b>	The database is encrypted with an algorithm not supported by this server.
<b>Error 1012</b>	<b>"Unable to start specified database: "%1' must be upgraded to start with this server (capability %2 missing)"</b>
<b>Constant</b>	UPGRADE_DATABASE
<b>SAP Sybase Error Number</b>	2680
<b>SQL State</b>	08W76
<b>SQL Code</b>	-1012L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001

<b>Error 1012</b>	<b>"Unable to start specified database: '%1' must be upgraded to start with this server (capability %2 missing)"</b>
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The name of the database file.
<b>Parameter 2</b>	The capability that is missing from the database file.
<b>Probable Cause</b>	The specified database must be upgraded to start with this server.
<b>Error 1016</b>	<b>"Unable to start specified database: Cannot use log file '%1' since it has been used more recently than the database file"</b>
<b>Constant</b>	LOG_NEWER_THAN_DB
<b>SAP Sybase Error Number</b>	2684
<b>SQL State</b>	08W80
<b>SQL Code</b>	-1016L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The name of the transaction log mirror file.
<b>Probable Cause</b>	The transaction log file has been used more recently than the database file.
<b>Error 1017</b>	<b>"Unable to start specified database: '%1': transaction log file not found"</b>
<b>Constant</b>	LOG_NOT_FOUND
<b>SAP Sybase Error Number</b>	2685
<b>SQL State</b>	08W81
<b>SQL Code</b>	-1017L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The name of the transaction log file.

## Errors and Warnings

<b>Error 1017</b>	<b>"Unable to start specified database: '%1': transaction log file not found"</b>
<b>Probable Cause</b>	The transaction log file was not found.
<b>Error 1018</b>	<b>"Unable to start specified database: Cannot use log file '%1' since the offsets do not match the offsets in the database file"</b>
<b>Constant</b>	LOG_OFFSETS_DONT_MATCH
<b>SAP Sybase Error Number</b>	2686
<b>SQL State</b>	08W82
<b>SQL Code</b>	-1018L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The name of the transaction log file.
<b>Probable Cause</b>	The transaction log file has an offset that does not match the offset expected by the database file.
<b>Error 1019</b>	<b>"Unable to start specified database: Cannot use log file '%1' since the database file has been used more recently"</b>
<b>Constant</b>	LOG_OLDER_THAN_DB
<b>SAP Sybase Error Number</b>	2687
<b>SQL State</b>	08W83
<b>SQL Code</b>	-1019L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The name of the transaction log file.
<b>Probable Cause</b>	The database file has been used more recently than the transaction log file.

<b>Error 1020</b>	<b>"Unable to start specified database: Cannot use log file '%1' since it is shorter than expected"</b>
<b>Constant</b>	LOG_TOO_SHORT
<b>SAP Sybase Error Number</b>	2688
<b>SQL State</b>	08W84
<b>SQL Code</b>	-1020L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The name of the transaction log file.
<b>Probable Cause</b>	The transaction log file is shorter than expected.
<b>Error 1021</b>	<b>"Invalid backup operation"</b>
<b>Constant</b>	INVALID_BACKUP_OPERATION
<b>SAP Sybase Error Number</b>	2689
<b>SQL State</b>	WB013
<b>SQL Code</b>	-1021L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The specified backup operation is not valid because of previous backup operation(s).
<b>Error 1022</b>	<b>"Invalid value for attribute '%1' in service"</b>
<b>Constant</b>	SERVICE_PARM_INVALID_VALUE
<b>SAP Sybase Error Number</b>	2691
<b>SQL State</b>	42WAD
<b>SQL Code</b>	-1022L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1022</b>	<b>"Invalid value for attribute '%1' in service"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the invalid attribute.
<b>Probable Cause</b>	The service definition contains a USING, FORMAT, or GROUP attribute with an invalid value.
<b>Error 1023</b>	<b>"Missing value for attribute '%1' in service"</b>
<b>Constant</b>	SERVICE_PARM_MISSING_VALUE
<b>SAP Sybase Error Number</b>	2692
<b>SQL State</b>	42WAE
<b>SQL Code</b>	-1023L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the invalid attribute.
<b>Probable Cause</b>	The service definition contains a USING, FORMAT, or GROUP attribute with a missing value.
<b>Error 1024</b>	<b>"Unsupported property '%1' in service USING attribute"</b>
<b>Constant</b>	SERVICE_PARM_UNSUPPORTED_PROPERTY
<b>SAP Sybase Error Number</b>	2693
<b>SQL State</b>	42WAF
<b>SQL Code</b>	-1024L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the unsupported property.
<b>Probable Cause</b>	The service definition contains a USING attribute with an unsupported property.

<b>Error 1025</b>	<b>"Duplicate attribute '%1' in service"</b>
<b>Constant</b>	SERVICE_PARM_DUPLICATE_PROPERTY
<b>SAP Sybase Error Number</b>	2694
<b>SQL State</b>	42WB0
<b>SQL Code</b>	-1025L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the duplicate attribute.
<b>Probable Cause</b>	The service definition contains a duplicate attribute.
<b>Error 1026</b>	<b>"USING attribute cannot coexist with FORMAT or GROUP attributes"</b>
<b>Constant</b>	SERVICE_ATTR_COEXIST
<b>SAP Sybase Error Number</b>	2695
<b>SQL State</b>	42WB1
<b>SQL Code</b>	-1026L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The service definition for the specified service type cannot specify a USING attribute along with a FORMAT or GROUP attribute.
<b>Error 1027</b>	<b>"Service type does not allow '%1' attribute"</b>
<b>Constant</b>	SERVICE_ATTR_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	2696
<b>SQL State</b>	42WB2
<b>SQL Code</b>	-1027L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1027</b>	"Service type does not allow '%1' attribute"
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the attribute that is not allowed.
<b>Probable Cause</b>	The service definition for the specified service type does not allow the given attribute to be specified.
<b>Error 1028</b>	"Connection attempting BACKUP has uncommitted transactions"
<b>Constant</b>	BACKUP_HAS_UNCOMMITTED_TRANS
<b>SAP Sybase Error Number</b>	2697
<b>SQL State</b>	WB014
<b>SQL Code</b>	-1028L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A connection attempting to perform a BACKUP...WAIT BEFORE START or BACKUP...WAIT AFTER END has uncommitted transactions. A COMMIT or ROLLBACK must be performed before executing the backup.

## Messages 1029 through 1050

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1029</b>	"Support for materialized views is not available for this database"
<b>Constant</b>	MAT_VIEWS_NOT_SUPPORTED
<b>SAP Sybase Error Number</b>	2698
<b>SQL State</b>	0AW15
<b>SQL Code</b>	-1029L
<b>ODBC 2 State</b>	ERROR

<b>Error 1029</b>	<b>"Support for materialized views is not available for this database"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	The statement being executed requires support for materialized views, but the database being used does not have the materialized view capability.
<b>Error 1030</b>	<b>"Secure HTTP connections are not supported on this platform"</b>
<b>Constant</b>	SECURE_CONNECTION_UNAVAILABLE
<b>SAP Sybase Error Number</b>	2699
<b>SQL State</b>	WW063
<b>SQL Code</b>	-1030L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>19</i> on page 2
<b>Probable Cause</b>	A Secure HTTP connection was attempted, but is not supported on this platform.
<b>Error 1031</b>	<b>"Syntax error near '%1' -- Materialized view definition must not use the following construct: '%2'"</b>
<b>Constant</b>	MATVIEW_SYNTAX_ERROR
<b>SAP Sybase Error Number</b>	2700
<b>SQL State</b>	42WB3
<b>SQL Code</b>	-1031L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	Location of the feature used that is not permitted.
<b>Parameter 2</b>	The feature used that is not permitted.

## Errors and Warnings

<b>Error 1031</b>	<b>"Syntax error near '%1' -- Materialized view definition must not use the following construct: '%2'"</b>
<b>Probable Cause</b>	You attempted to create a materialized view whose definition violates one of the restrictions.
<b>Error 1032</b>	<b>"Syntax error near '%1' -- The materialized view cannot be changed to immediate because its definition contains an illegal construct: '%2'"</b>
<b>Constant</b>	UPDATABLE_MATVIEW_SYNTAX_ERROR
<b>SAP Sybase Error Number</b>	2701
<b>SQL State</b>	42WB4
<b>SQL Code</b>	-1032L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	Location of the feature used that is not permitted.
<b>Parameter 2</b>	The feature used that is not permitted.
<b>Probable Cause</b>	You attempted to change the refresh type to immediate for a materialized view whose definition violates one of the restrictions.
<b>Error 1033</b>	<b>"Unable to start database server: Server fatal error"</b>
<b>Constant</b>	UNABLE_TO_START_ENGINE_FATAL_ERROR
<b>SAP Sybase Error Number</b>	2702
<b>SQL State</b>	08W89
<b>SQL Code</b>	-1033L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>17</i> on page 2
<b>Probable Cause</b>	The database server failed to start because a fatal error or assertion failure occurred. More information may be available in the Windows event log or Unix system log or by manually starting the database server.

<b>Error 1034</b>	<b>"The '%1' attribute is not valid with procedure type "%2"'</b>
<b>Constant</b>	INVALID_ATTRIBUTE_WITH_TYPE
<b>SAP Sybase Error Number</b>	2703
<b>SQL State</b>	WW064
<b>SQL Code</b>	-1034L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The attribute on the procedure.
<b>Parameter 2</b>	The procedure type.
<b>Probable Cause</b>	This attribute is not applicable to the given procedure type.
<b>Error 1035</b>	<b>"LOAD TABLE ... WITH FILE NAME LOGGING not permitted on mirrored database"</b>
<b>Constant</b>	LOAD_TABLE_ON_MIRRORED_DB
<b>SAP Sybase Error Number</b>	2704
<b>SQL State</b>	WL008
<b>SQL Code</b>	-1035L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	LOAD TABLE ... WITH FILE NAME LOGGING statements are not permitted when a database is being mirrored, since the file being loaded might not be accessible by the other server.
<b>Error 1036</b>	<b>"The DBN/DBF parameters do not match the database for this alternate server name"</b>
<b>Constant</b>	WRONG_DB_ON_ALT_SERVER_NAME
<b>SAP Sybase Error Number</b>	2705
<b>SQL State</b>	08W90

## Errors and Warnings

<b>Error 1036</b>	<b>"The DBN/DBF parameters do not match the database for this alternate server name"</b>
<b>SQL Code</b>	-1036L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2
<b>Probable Cause</b>	The DBN or DBF parameters specified do not match the database using the specified alternate server name.
<b>Error 1037</b>	<b>"Cannot drop or modify object '%1' because at least one other object ( %2 '%3') depends upon it"</b>
<b>Constant</b>	OBJECT_HAS_DEPENDENTS
<b>SAP Sybase Error Number</b>	2706
<b>SQL State</b>	55W16
<b>SQL Code</b>	-1037L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the object that could not be dropped or modified.
<b>Parameter 2</b>	The type of the object that depends on the object that could not be dropped or modified.
<b>Parameter 3</b>	The name of the object that depends on the object that could not be dropped or modified.
<b>Probable Cause</b>	You attempted to drop or modify an object, such as a table or a column, that is used by another object, such as a materialized view, that cannot be automatically invalidated. The dependent object must be disabled or dropped before a drop or modification can be permitted.
<b>Error 1038</b>	<b>"Cannot use view '%1' because it has been disabled"</b>
<b>Constant</b>	VIEW_DISABLED
<b>SAP Sybase Error Number</b>	2707

<b>Error 1038</b>	<b>"Cannot use view '%1' because it has been disabled"</b>
<b>SQL State</b>	55W17
<b>SQL Code</b>	-1038L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the view.
<b>Probable Cause</b>	You attempted to reference a view that has been disabled. The view must be enabled before it can be used again.
<b>Error 1039</b>	<b>"Cannot connect to mirror server. Use server name '%1' to find the primary server"</b>
<b>Constant</b>	CONNECTED_TO_MIRROR_SERVER
<b>SAP Sybase Error Number</b>	2708
<b>SQL State</b>	08W91
<b>SQL Code</b>	-1039L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The server name for the mirroring system.
<b>Probable Cause</b>	You have attempted to connect to the mirror server in a mirroring system. You should change your connection string or DSN to use the server name for the mirroring system.
<b>Error 1040</b>	<b>"Cannot use view '%1' because it is invalid"</b>
<b>Constant</b>	VIEW_INVALID
<b>SAP Sybase Error Number</b>	2709
<b>SQL State</b>	55W18
<b>SQL Code</b>	-1040L
<b>ODBC 2 State</b>	42000

## Errors and Warnings

<b>Error 1040</b>	<b>"Cannot use view '%1' because it is invalid"</b>
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the view.
<b>Probable Cause</b>	You attempted to reference an invalid view. The view must be enabled before it can be used again.
<b>Error 1041</b>	<b>"Materialized View '%1' not found"</b>
<b>Constant</b>	MATVIEW_NOT_FOUND
<b>SAP Sybase Error Number</b>	2710
<b>SQL State</b>	42WB5
<b>SQL Code</b>	-1041L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	Name of the materialized view that could not be found.
<b>Probable Cause</b>	You misspelled the name of a materialized view, or you did not qualify a materialized view name with a user name. For example, you might have referred to "mat_view" instead of "owner"."mat_view".
<b>Error 1042</b>	<b>"Cannot add a comment to a table declared as LOCAL TEMPORARY"</b>
<b>Constant</b>	COMMENT_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	2711
<b>SQL State</b>	WW065
<b>SQL Code</b>	-1042L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2

<b>Error 1042</b>	<b>"Cannot add a comment to a table declared as LOCAL TEMPORARY"</b>
<b>Probable Cause</b>	You attempted to add a comment to a table that has been declared as LOCAL TEMPORARY. This is not allowed.

<b>Error 1043</b>	<b>"Request interrupted due to timeout"</b>
<b>Constant</b>	REQUEST_TIMEOUT
<b>SAP Sybase Error Number</b>	2712
<b>SQL State</b>	57W01
<b>SQL Code</b>	-1043L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The current request was canceled during its execution since it ran for longer than the request_timeout database option value. The database was able to stop the operation without doing a rollback. If the statement is an INSERT, UPDATE, or DELETE, any changes made by the statement will be canceled. If the statement is a data definition statement (for example CREATE TABLE), the statement will be canceled, but the COMMIT that was done as a side effect will not be canceled.

<b>Error 1044</b>	<b>"Invalid password: %1"</b>
<b>Constant</b>	INVALID_NEW_PASSWORD
<b>SAP Sybase Error Number</b>	2713
<b>SQL State</b>	28W11
<b>SQL Code</b>	-1044L
<b>ODBC 2 State</b>	28000
<b>ODBC 3 State</b>	28000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The attempt to create a new user ID or change a password failed. The function specified by the verify_password_function option disallowed the password.

## Errors and Warnings

<b>Error 1045</b>	"Invalid backup parameter value"
<b>Constant</b>	INVALID_BACKUP_PARM_VALUE
<b>SAP Sybase Error Number</b>	2714
<b>SQL State</b>	WB015
<b>SQL Code</b>	-1045L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	One or more of the parameters supplied to the backup operation has an invalid value.
<b>Error 1046</b>	"Illegal column definition: %1"
<b>Constant</b>	ILLEGAL_COLUMN_DEFINITION
<b>SAP Sybase Error Number</b>	2715
<b>SQL State</b>	55W19
<b>SQL Code</b>	-1046L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	A message describing the error that occurred.
<b>Probable Cause</b>	You are attempting to define a column in a way that is not allowed.
<b>Error 1047</b>	"This database does not support encrypted tables"
<b>Constant</b>	ENCRYPTED_TABLES_NOT_SUPPORTED
<b>SAP Sybase Error Number</b>	2716
<b>SQL State</b>	55W20
<b>SQL Code</b>	-1047L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000

<b>Error 1047</b>	<b>"This database does not support encrypted tables"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You tried to create an encrypted table in a database that does not support them.
<b>Error 1050</b>	<b>"Cannot return NULL result as requested data type"</b>
<b>Constant</b>	VALUE_IS_NULL
<b>SAP Sybase Error Number</b>	2719
<b>SQL State</b>	22030
<b>SQL Code</b>	-1050L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You tried to retrieve a value from the database that was NULL and assign it to a variable that cannot be NULL.

## Messages 1051 through 1075

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1051</b>	<b>"Cannot create a materialized view because option '%1' has an inappropriate setting"</b>
<b>Constant</b>	CANNOT_CREATE_MATVIEW
<b>SAP Sybase Error Number</b>	2720
<b>SQL State</b>	42WB6
<b>SQL Code</b>	-1051L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Name of the option with the incorrect setting.

## Errors and Warnings

<b>Error 1051</b>	<b>"Cannot create a materialized view because option '%1' has an inappropriate setting"</b>
<b>Probable Cause</b>	You attempted to create a materialized view, but one of the database options is currently set to a value not permitted while creating a materialized view.
<b>Error 1052</b>	<b>"Cannot update materialized view because option '%1' has an inappropriate setting"</b>
<b>Constant</b>	CANNOT_UPDATE_MATVIEW
<b>SAP Sybase Error Number</b>	2721
<b>SQL State</b>	42WB7
<b>SQL Code</b>	-1052L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Name of the option with the incorrect setting.
<b>Probable Cause</b>	You attempted to update/refresh a materialized view but one of the database options is currently set to a value that is not permitted while updating a materialized view, or, the option's setting does not match the value when the view was created.
<b>Error 1053</b>	<b>"'%1' is an invalid value for '%2'"</b>
<b>Constant</b>	INVALID_OPTION_VALUE
<b>SAP Sybase Error Number</b>	2722
<b>SQL State</b>	42W85
<b>SQL Code</b>	-1053L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The invalid value.
<b>Parameter 2</b>	Name of the option.

<b>Error 1053</b>	<b>"'%1' is an invalid value for '%2'"</b>
<b>Probable Cause</b>	You supplied an invalid value for an option. Some options only allow numeric values and some options only allow true or false. Also, many options do not permit the empty string as a value.
<b>Error 1054</b>	<b>"Snapshot isolation disabled or pending"</b>
<b>Constant</b>	SNAPSHOT_ISOLATION_DISABLED
<b>SAP Sybase Error Number</b>	2723
<b>SQL State</b>	55W23
<b>SQL Code</b>	-1054L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Snapshot isolation is disabled or its activation is still pending. You must enable snapshot isolation before using it.
<b>Error 1057</b>	<b>"BACKUP clause '%1' conflicts with '%2'"</b>
<b>Constant</b>	INVALID_BACKUP_STATEMENT
<b>SAP Sybase Error Number</b>	2726
<b>SQL State</b>	WB016
<b>SQL Code</b>	-1057L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	First BACKUP clause.
<b>Parameter 2</b>	Second BACKUP clause.
<b>Probable Cause</b>	Clauses specified in the BACKUP STATEMENT are mutually exclusive.
<b>Error 1060</b>	<b>"Operation conflict with publication type"</b>
<b>Constant</b>	CONFLICTING_PUB_TYPE

## Errors and Warnings

<b>Error 1060</b>	<b>"Operation conflict with publication type"</b>
<b>SAP Sybase Error Number</b>	2729
<b>SQL State</b>	5RW38
<b>SQL Code</b>	-1060L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to perform an operation not applicable to the type of publication. For example, you applied operations specific to a scripted upload publication to a logscan publication.
<b>Error 1061</b>	<b>"Table created or altered after start of snapshot"</b>
<b>Constant</b>	SNAPSHOT_TABLE_CHANGED
<b>SAP Sybase Error Number</b>	2730
<b>SQL State</b>	42WB8
<b>SQL Code</b>	-1061L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A snapshot transaction attempted to use a table that was created or altered after the transaction began.
<b>Error 1062</b>	<b>"Statement not allowed during snapshot"</b>
<b>Constant</b>	STATEMENT_NOT_ALLOWED_IN_SNAPSHOT
<b>SAP Sybase Error Number</b>	2731
<b>SQL State</b>	42WB9
<b>SQL Code</b>	-1062L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1062</b>	<b>"Statement not allowed during snapshot"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A connection with an outstanding snapshot attempted to use CREATE INDEX, DROP INDEX, ALTER INDEX or ALTER TABLE. Make sure all cursors for the connection are closed.
<b>Error 1063</b>	<b>"Unable to start database %1: Cannot use read-only mode if auditing is enabled"</b>
<b>Constant</b>	AUDITING_DB_READ_ONLY
<b>SAP Sybase Error Number</b>	2732
<b>SQL State</b>	08W93
<b>SQL Code</b>	-1063L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	Name of the database.
<b>Probable Cause</b>	The specified database has auditing enabled, and cannot be started read-only.
<b>Error 1064</b>	<b>"Update conflict on snapshot transaction"</b>
<b>Constant</b>	SNAPSHOT_UPDATE_CONFLICT
<b>SAP Sybase Error Number</b>	2733
<b>SQL State</b>	42WBA
<b>SQL Code</b>	-1064L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A snapshot transaction attempted to update or delete a row that was changed by another transaction after the snapshot began.

## Errors and Warnings

<b>Error 1065</b>	<b>"Attempt to use snapshot isolation in a non-snapshot transaction"</b>
<b>Constant</b>	NON_SNAPSHOT_TRANSACTION
<b>SAP Sybase Error Number</b>	2734
<b>SQL State</b>	42WBB
<b>SQL Code</b>	-1065L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A transaction tried to use snapshot isolation but did not begin with snapshot isolation.
<b>Error 1066</b>	<b>"File system error: %1"</b>
<b>Constant</b>	OMNI_FILE_SYSTEM_ERROR
<b>SAP Sybase Error Number</b>	2735
<b>SQL State</b>	WO027
<b>SQL Code</b>	-1066L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>12</i> on page 2
<b>Parameter 1</b>	Error description.
<b>Probable Cause</b>	This error results from an error in the underlying file system that was encountered while accessing a file directory as a proxy table.
<b>Error 1068</b>	<b>"Default dbspace '%1' not found"</b>
<b>Constant</b>	DEFAULT_DBSPACE_NOT_FOUND
<b>SAP Sybase Error Number</b>	2737
<b>SQL State</b>	52W43
<b>SQL Code</b>	-1068L
<b>ODBC 2 State</b>	S0002

<b>Error 1068</b>	"Default dbspace '%1' not found"
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	Name of the default dbspace that could not be found.
<b>Probable Cause</b>	You tried to create a table with the default_dbspace option set to a dbspace that could not be found.

<b>Error 1069</b>	"Kerberos login failed"
<b>Constant</b>	KERBEROS_LOGON_FAILED
<b>SAP Sybase Error Number</b>	2738
<b>SQL State</b>	28W12
<b>SQL Code</b>	-1069L
<b>ODBC 2 State</b>	28000
<b>ODBC 3 State</b>	28000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The Kerberos login failed due to a failure of the client to authenticate the user's principal with the KDC or a failure of the server to authenticate the client. The most likely causes are the Kerberos principal may not be signed in, the principal's ticket may have expired, or the client, server, or KDC's system time are not within a few minutes of each other. The LogFile connection parameter or the server's -z option may provide more information.

<b>Error 1070</b>	"Kerberos logins are not supported"
<b>Constant</b>	KERBEROS_LOGONS_UNSUPPORTED
<b>SAP Sybase Error Number</b>	2739
<b>SQL State</b>	28W13
<b>SQL Code</b>	-1070L
<b>ODBC 2 State</b>	28000
<b>ODBC 3 State</b>	28000
<b>Severity Code</b>	<i>16</i> on page 2

## Errors and Warnings

<b>Error 1070</b>	<b>"Kerberos logins are not supported"</b>
<b>Probable Cause</b>	The client and/or server does not support Kerberos logins. Kerberos may not be supported by the platform, the Kerberos client software including the GSS-API runtime may not be installed or found on the client, or Kerberos was not enabled on the server. The LogFile connection parameter or the server's -z option may provide more information.
<b>Error 1071</b>	<b>"The %1 algorithm is not available in FIPS mode"</b>
<b>Constant</b>	FIPS_NOT_AVAILABLE
<b>SAP Sybase Error Number</b>	2740
<b>SQL State</b>	0AW16
<b>SQL Code</b>	-1071L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>19</i> on page 2
<b>Parameter 1</b>	Name of the algorithm.
<b>Probable Cause</b>	The specified algorithm is not available when the server is running in FIPS mode.
<b>Error 1072</b>	<b>"'%1' is not a valid character set encoding for use with collation '%2'"</b>
<b>Constant</b>	INVALID_ENCODING_FOR_COLLATION
<b>SAP Sybase Error Number</b>	2741
<b>SQL State</b>	WC009
<b>SQL Code</b>	-1072L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The character set encoding that is invalid.
<b>Parameter 2</b>	The collation for which the character set encoding is invalid.

<b>Error 1072</b>	<b>"'%1' is not a valid character set encoding for use with collation '%2'"</b>
<b>Probable Cause</b>	The specified character set cannot be used with the specified collation.
<b>Error 1073</b>	<b>"'%1' cannot be used as the NCHAR collation: only UCA and UTF8BIN may be used"</b>
<b>Constant</b>	INVALID_NCHAR_COLLATION
<b>SAP Sybase Error Number</b>	2742
<b>SQL State</b>	WC010
<b>SQL Code</b>	-1073L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The collation that cannot be used as the NCHAR collation.
<b>Probable Cause</b>	The specified collation cannot be used as the NCHAR collation. NCHAR always uses UTF-8, so the collation must be either UCA or UTF8BIN.
<b>Error 1074</b>	<b>"Login mode '%1' not permitted by login_mode setting"</b>
<b>Constant</b>	LOGON_MODE_NOT_PERMITTED
<b>SAP Sybase Error Number</b>	2743
<b>SQL State</b>	28W14
<b>SQL Code</b>	-1074L
<b>ODBC 2 State</b>	28000
<b>ODBC 3 State</b>	28000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the login mode not included in the current login_mode database option setting.

<b>Error 1074</b>	<b>"Login mode '%1' not permitted by login_mode setting"</b>
<b>Probable Cause</b>	You attempted to connect using a login mode not included in the current login_mode database option setting. Change the option setting or connect using a different login mode.
<b>Error 1075</b>	<b>"Failed to convert from character set '%1' to '%2'"</b>
<b>Constant</b>	FAILED_TO_CONVERT_CHARSET
<b>SAP Sybase Error Number</b>	2744
<b>SQL State</b>	WC011
<b>SQL Code</b>	-1075L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The character set of the input string.
<b>Parameter 2</b>	The character set of the output string.
<b>Probable Cause</b>	The server failed to convert between the two specified character sets. This could happen when the dbicu and dbicut DLLs are not installed.

## Messages 1076 through 1096

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1076</b>	<b>"dbicu libraries are required but not installed"</b>
<b>Constant</b>	ICU_NOT_AVAILABLE
<b>SAP Sybase Error Number</b>	2745
<b>SQL State</b>	WC012
<b>SQL Code</b>	-1076L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

<b>Error 1076</b>	<b>"dbicu libraries are required but not installed"</b>
<b>Probable Cause</b>	The server is unable to load ICU components that are required by this database. Ensure that the dbicu and dbicudt DLLs are installed.
<b>Error 1077</b>	<b>"Cannot use materialized view '%1' because it has not yet been initialized"</b>
<b>Constant</b>	CANNOT_USE_MATVIEW
<b>SAP Sybase Error Number</b>	2746
<b>SQL State</b>	42WBC
<b>SQL Code</b>	-1077L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Name of the materialized view.
<b>Probable Cause</b>	You attempted to use a materialized view but it has not yet been initialized. In order for a materialized view to become available for first use after being created or enabled, it must be initialized at least once using the REFRESH MATERIALIZED VIEW statement.
<b>Error 1078</b>	<b>"Cycle in computed column dependencies"</b>
<b>Constant</b>	COMPUTED_COLUMN_CYCLE
<b>SAP Sybase Error Number</b>	2747
<b>SQL State</b>	42WBD
<b>SQL Code</b>	-1078L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The table has a cycle in the dependencies between its computed columns. Cycles are not allowed.

## Errors and Warnings

<b>Error 1079</b>	<b>"Backup is unable to open database file "%1"</b>
<b>Constant</b>	BACKUP_UNABLE_TO_OPEN_FILE
<b>SAP Sybase Error Number</b>	2748
<b>SQL State</b>	WB017
<b>SQL Code</b>	-1079L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the file.
<b>Probable Cause</b>	The database file cannot be opened by the backup. It may have been erased or otherwise corrupted.
<b>Error 1080</b>	<b>"Cannot revoke these permissions while user '%1' is actively replicating transactions"</b>
<b>Constant</b>	MUST_NOT_BE_REPLICATING
<b>SAP Sybase Error Number</b>	2749
<b>SQL State</b>	42WBE
<b>SQL Code</b>	-1080L
<b>ODBC 2 State</b>	40001
<b>ODBC 3 State</b>	40001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the user.
<b>Probable Cause</b>	You attempted to revoke permissions from a user while there are transactions currently being replicated for that user. This is not allowed.
<b>Error 1081</b>	<b>"Could not refresh tracing: at least one enabled tracing level must be specified"</b>
<b>Constant</b>	NO_TRACING_LEVELS
<b>SAP Sybase Error Number</b>	2750
<b>SQL State</b>	55W24

<b>Error 1081</b>	<b>"Could not refresh tracing: at least one enabled tracing level must be specified"</b>
<b>SQL Code</b>	-1081L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Table sa_diagnostic_tracing_level contains no rows (tracing levels) or no tracing levels are enabled.
<b>Error 1082</b>	<b>"Could not refresh tracing: invalid tracing specification on sa_diagnostic_tracing_level row %1"</b>
<b>Constant</b>	INVALID_TRACING_SPEC
<b>SAP Sybase Error Number</b>	2751
<b>SQL State</b>	WW066
<b>SQL Code</b>	-1082L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The primary key of the row that is invalid.
<b>Probable Cause</b>	You specified an invalid combination of values for the tracing level. Some invalid combinations are: specified condition is not valid for the tracing type, or specified tracing type is not valid for the scope.
<b>Error 1083</b>	<b>"Could not refresh tracing: failed to find object %1 on row %2"</b>
<b>Constant</b>	TRACING_OBJ_NOT_FOUND
<b>SAP Sybase Error Number</b>	2752
<b>SQL State</b>	WW067
<b>SQL Code</b>	-1083L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1083</b>	<b>"Could not refresh tracing: failed to find object %1 on row %2"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The specified name of the object.
<b>Parameter 2</b>	The primary key of the row on which the check failed.
<b>Probable Cause</b>	You misspelled the object name, or you did not qualify the name with user (and, possibly, table) name. For example, you might have referred to table_name instead of "owner"."table_name", or you might have referred to table_name_trigger instead of "owner"."table_names"."table_name_trigger".
<b>Error 1084</b>	<b>"Use of feature '%1' is not allowed"</b>
<b>Constant</b>	SECURE_FEATURE
<b>SAP Sybase Error Number</b>	2753
<b>SQL State</b>	57W02
<b>SQL Code</b>	-1084L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Name of the SQL statement or feature.
<b>Probable Cause</b>	You have attempted to use a feature that was disabled by the server administrator when the database server was started.
<b>Error 1085</b>	<b>"Duplicate key column (%1)"</b>
<b>Constant</b>	DUPLICATE_KEY_COLUMN
<b>SAP Sybase Error Number</b>	2754
<b>SQL State</b>	42WC0
<b>SQL Code</b>	-1085L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2

<b>Error 1085</b>	<b>"Duplicate key column (%1)"</b>
<b>Parameter 1</b>	The name of the duplicate column.
<b>Probable Cause</b>	You supplied a duplicate column name in the list of columns for the key of a primary key, foreign key, or unique constraint, or an index.
<b>Error 1087</b>	<b>"Could not refresh tracing: volatile_statistics have to be collected in order for %1 specified on row %2 to be collected"</b>
<b>Constant</b>	NO_VOLATILE_LEVEL_SPEC
<b>SAP Sybase Error Number</b>	2756
<b>SQL State</b>	WW068
<b>SQL Code</b>	-1087L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The tracing level that caused the error.
<b>Parameter 2</b>	The primary key of the row on which the check failed.
<b>Probable Cause</b>	Volatile statistics have to be collected in order for the non-volatile and connection statistics to be collected.
<b>Error 1088</b>	<b>"ATTACH TRACING TO LOCAL DATABASE cannot be used with a strongly encrypted database"</b>
<b>Constant</b>	NO_LOCAL_CONNECTIONS_TO_ENCRYPTED
<b>SAP Sybase Error Number</b>	2757
<b>SQL State</b>	WW069
<b>SQL Code</b>	-1088L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

## Errors and Warnings

<b>Error 1088</b>	<b>"ATTACH TRACING TO LOCAL DATABASE cannot be used with a strongly encrypted database"</b>
<b>Probable Cause</b>	The local database is strongly encrypted, so you cannot use the LOCAL DATABASE clause of the ATTACH TRACING statement. You must specify a connection string with the encryption key for the database.
<b>Error 1089</b>	<b>"Invalid commit action for shared temporary table"</b>
<b>Constant</b>	INVALID_SHARED_COMMIT_ACTION
<b>SAP Sybase Error Number</b>	2758
<b>SQL State</b>	52W26
<b>SQL Code</b>	-1089L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A global shared temporary table must be declared as ON COMMIT PRESERVE ROWS or NOT TRANSACTIONAL.
<b>Error 1090</b>	<b>"Function "%1' has invalid parameter "%2' ("%3')"</b>
<b>Constant</b>	INVALID_PARAMETER_W_PARM
<b>SAP Sybase Error Number</b>	2759
<b>SQL State</b>	08W94
<b>SQL Code</b>	-1090L
<b>ODBC 2 State</b>	08004
<b>ODBC 3 State</b>	08004
<b>Severity Code</b>	<i>18</i> on page 2
<b>Parameter 1</b>	The name of the function.
<b>Parameter 2</b>	The name of the parameter.
<b>Parameter 3</b>	Information about the parameter that caused the error.
<b>Probable Cause</b>	An error occurred while evaluating a parameter.

<b>Error 1091</b>	<b>"Constraint '%1' violated: Invalid value in table '%2'"</b>
<b>Constant</b>	TABLE_CONSTRAINT_VIOLATED
<b>SAP Sybase Error Number</b>	2760
<b>SQL State</b>	23508
<b>SQL Code</b>	-1091L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	23000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the constraint (if defined) that was violated by an invalid value.
<b>Parameter 2</b>	Name of the table containing the column.
<b>Probable Cause</b>	You attempted an insert or update that violates a CHECK constraint. A CHECK constraint is violated if it evaluates to FALSE; it is deemed to hold if the condition evaluates to TRUE or UNKNOWN.
<b>Error 1092</b>	<b>"The method you attempted to invoke was not enabled for your application"</b>
<b>Constant</b>	FEATURE_NOT_ENABLED
<b>SAP Sybase Error Number</b>	2762
<b>SQL State</b>	0A001
<b>SQL Code</b>	-1092L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to call a method or use a feature that has not been enabled. In UltraLite, features are enabled using ULEnable functions or by using ULInitDatabaseManager instead of ULInitDatabaseManagerNoSQL.

## Errors and Warnings

<b>Error 1093</b>	<b>"The size of the character column, variable, or value data type exceeds 32767"</b>
<b>Constant</b>	CHAR_FIELD_SIZE_EXCEEDED
<b>SAP Sybase Error Number</b>	2763
<b>SQL State</b>	54W09
<b>SQL Code</b>	-1093L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>19</i> on page 2
<b>Probable Cause</b>	The declaration or conversion has specified a character type with byte length greater than 32767.
<b>Error 1094</b>	<b>"The HTTP header '%1' is reserved and cannot be modified"</b>
<b>Constant</b>	HTTP_HEADER_ATTRIBUTE_RESERVED_XXX
<b>SAP Sybase Error Number</b>	2764
<b>SQL State</b>	WW070
<b>SQL Code</b>	-1094L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The header causing the failure.
<b>Probable Cause</b>	The specified HTTP header is reserved and cannot be modified.
<b>Error 1095</b>	<b>"The specified HTTP header contains illegal or non-ASCII characters"</b>
<b>Constant</b>	HTTP_HEADER_ATTRIBUTE_ASCII
<b>SAP Sybase Error Number</b>	2765
<b>SQL State</b>	WW071
<b>SQL Code</b>	-1095L

<b>Error 1095</b>	"The specified HTTP header contains illegal or non-ASCII characters"
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	HTTP headers must contain printable ASCII characters.
<b>Error 1096</b>	"The specified HTTP header is malformed"
<b>Constant</b>	HTTP_HEADER_ATTRIBUTE_MALFORMED
<b>SAP Sybase Error Number</b>	2766
<b>SQL State</b>	WW072
<b>SQL Code</b>	-1096L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The HTTP header is missing the colon delimiter or a folding construct is malformed.

## Messages 1097 through 1117

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1097</b>	"ATTACH TRACING could not connect to the tracing database"
<b>Constant</b>	ATTACH_TRACING_FAILED
<b>SAP Sybase Error Number</b>	2767
<b>SQL State</b>	08W95
<b>SQL Code</b>	-1097L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 1097</b>	"ATTACH TRACING could not connect to the tracing database"
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A connection to the tracing database could not be established. Check your connection string and verify that other clients can connect. Note that if you are trying to attach tracing to another server, perhaps the connection is being blocked by a firewall.
<b>Error 1098</b>	"A tracing connection is already active"
<b>Constant</b>	TRACING_ALREADY_ATTACHED
<b>SAP Sybase Error Number</b>	2768
<b>SQL State</b>	08W96
<b>SQL Code</b>	-1098L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	This database is already participating in a tracing connection, either as the sender (the database being traced) or as the receiver (the tracing database). A database can only send or receive one stream of tracing data at a time.
<b>Error 1099</b>	"Transact-SQL outer joins are currently disabled"
<b>Constant</b>	TSQL_OUTER_JOINS_DISABLED
<b>SAP Sybase Error Number</b>	2769
<b>SQL State</b>	55W25
<b>SQL Code</b>	-1099L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2

<b>Error 1099</b>	<b>"Transact-SQL outer joins are currently disabled"</b>
<b>Probable Cause</b>	The ability to specify a Transact-SQL outer join in a query is currently disabled by the setting of the tsql_outer_joins connection option. Transact-SQL outer joins are deprecated in this release of SQL Anywhere.
<b>Error 1100</b>	<b>"The operation failed because column "%1"s type does not support streaming"</b>
<b>Constant</b>	COLUMN_NOT_STREAMABLE
<b>SAP Sybase Error Number</b>	2771
<b>SQL State</b>	WW045
<b>SQL Code</b>	-1100L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The number of the column whose type is invalid.
<b>Probable Cause</b>	The only column types that support streaming are: BINARY, LONG BINARY, VARCHAR and LONG VARCHAR. This error could also occur when allocating a stream object twice on the same column.
<b>Error 1101</b>	<b>"Column '%1' not part of any indexes in its containing table"</b>
<b>Constant</b>	COLUMN_NOT_INDEXED
<b>SAP Sybase Error Number</b>	2772
<b>SQL State</b>	WW073
<b>SQL Code</b>	-1101L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the column not found in any index.

## Errors and Warnings

<b>Error 1101</b>	<b>"Column '%1' not part of any indexes in its containing table"</b>
<b>Probable Cause</b>	The specified column is not part of any indexes belonging to the containing table.
<b>Error 1102</b>	<b>"Unable to retry download because upload is not finished"</b>
<b>Constant</b>	DOWNLOAD_RESTART_FAILED
<b>SAP Sybase Error Number</b>	2773
<b>SQL State</b>	WW074
<b>SQL Code</b>	-1102L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The MobiLink server could not restart the download because the MobiLink server has not received the entire upload stream.
<b>Error 1103</b>	<b>"No partial download was found"</b>
<b>Constant</b>	PARTIAL_DOWNLOAD_NOT_FOUND
<b>SAP Sybase Error Number</b>	2774
<b>SQL State</b>	WW075
<b>SQL Code</b>	-1103L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A partial download was not found for the synchronizing user. This error could occur if trying to resume from a non-existent partial download or trying to rollback a non-existent partial download.
<b>Error 1104</b>	<b>"Too many users in database"</b>
<b>Constant</b>	TOO_MANY_USERS

<b>Error 1104</b>	<b>"Too many users in database"</b>
<b>SAP Sybase Error Number</b>	2775
<b>SQL State</b>	54W10
<b>SQL Code</b>	-1104L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You have exceeded the maximum number of users permitted to access the database. The maximum number of users that are allowed granted access to a single UltraLite database is four.
<b>Error 1106</b>	<b>"Too many publications specified for operation"</b>
<b>Constant</b>	TOO_MANY_PUBLICATIONS
<b>SAP Sybase Error Number</b>	2777
<b>SQL State</b>	WW077
<b>SQL Code</b>	-1106L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You have specified too many publications for the required operation. For example, when retrieving the last download timestamp, you are only allowed to select one publication.
<b>Error 1107</b>	<b>"Too many references to a BLOB"</b>
<b>Constant</b>	TOO_MANY_BLOB_REFS
<b>SAP Sybase Error Number</b>	2778
<b>SQL State</b>	54W11
<b>SQL Code</b>	-1107L

## Errors and Warnings

<b>Error 1107</b>	<b>"Too many references to a BLOB"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You have exceeded the maximum number of references to a particular BLOB. In UltraLite you may have at most 256 references to any one particular BLOB.
<b>Error 1108</b>	<b>"Unable to access the file system on the device"</b>
<b>Constant</b>	CANNOT_ACCESS_FILESYSTEM
<b>SAP Sybase Error Number</b>	2779
<b>SQL State</b>	WW078
<b>SQL Code</b>	-1108L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	On a Palm device, you have tried to utilize the VFS file system, but that feature has not been enabled on the device.
<b>Error 1109</b>	<b>"Unable to perform requested operation since this database uses keyless encryption"</b>
<b>Constant</b>	KEYLESS_ENCRYPTION
<b>SAP Sybase Error Number</b>	2780
<b>SQL State</b>	WW079
<b>SQL Code</b>	-1109L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

<b>Error 1109</b>	<b>"Unable to perform requested operation since this database uses keyless encryption"</b>
<b>Probable Cause</b>	The operation you requested on the encryption key failed since the UltraLite database uses keyless encryption. This can occur when you try to change the encryption key for a database that uses keyless encryption (obfuscation for example).

<b>Error 1110</b>	<b>"UltraLite cannot synchronize because a synchronization is already running"</b>
<b>Constant</b>	SYNC_NOT_REENTRANT
<b>SAP Sybase Error Number</b>	2781
<b>SQL State</b>	WW080
<b>SQL Code</b>	-1110L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to synchronize an UltraLite database which is already synchronizing. You must wait until the current synchronization completes before starting another. UltraLite allows most operations to run concurrently with synchronization, but only a single synchronization can be active at a time. This is generally caused by two different threads attempting a synchronize call or statement at the same time.

<b>Error 1111</b>	<b>"Information for synchronization was not provided"</b>
<b>Constant</b>	SYNC_INFO_REQUIRED
<b>SAP Sybase Error Number</b>	2782
<b>SQL State</b>	WW081
<b>SQL Code</b>	-1111L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

## Errors and Warnings

<b>Error 1111</b>	<b>"Information for synchronization was not provided"</b>
<b>Probable Cause</b>	You must supply information for synchronization in the synchronization call.
<b>Error 1112</b>	<b>"Specified file system volume not found for database "%1"</b>
<b>Constant</b>	FILE_VOLUME_NOT_FOUND
<b>SAP Sybase Error Number</b>	2783
<b>SQL State</b>	WW082
<b>SQL Code</b>	-1112L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the database.
<b>Probable Cause</b>	The file system volume you specified in the database file name was not found. Check the volume name or ordinal.
<b>Error 1113</b>	<b>"Correlation name "%1' is not valid for use with the ROWID function"</b>
<b>Constant</b>	INVALID_CORRELATION_FOR_ROWID
<b>SAP Sybase Error Number</b>	2784
<b>SQL State</b>	42WBF
<b>SQL Code</b>	-1113L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	Name of the invalid correlation name.
<b>Probable Cause</b>	The correlation name used was not valid for the ROWID function. Only the correlation names of base tables, temporary tables, global temporary tables or proxy tables may be used with the ROWID function. The argument of a ROWID function should not refer to a view, derived table, common table expression, or a procedure.

<b>Error 1114</b>	<b>"Invalid setting for SOAP header '%1'"</b>
<b>Constant</b>	INVALID_SOAP_HEADER_SETTING
<b>SAP Sybase Error Number</b>	2785
<b>SQL State</b>	42W86
<b>SQL Code</b>	-1114L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the invalid SOAP header.
<b>Probable Cause</b>	You supplied an invalid value for a SOAP header.
<b>Error 1115</b>	<b>"Table '%1' contains an invalid reference to the ROWID function"</b>
<b>Constant</b>	INVALID_ROWID_PLACEMENT
<b>SAP Sybase Error Number</b>	2786
<b>SQL State</b>	42WC1
<b>SQL Code</b>	-1115L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	Name of the table that contains the invalid reference.
<b>Probable Cause</b>	The ROWID function cannot be used in a computed column expression or in a CHECK constraint.
<b>Error 1116</b>	<b>"Collation '%1' not supported on this platform"</b>
<b>Constant</b>	COLLATION_NOT_SUPPORTED
<b>SAP Sybase Error Number</b>	2787
<b>SQL State</b>	WC013
<b>SQL Code</b>	-1116L

## Errors and Warnings

<b>Error 1116</b>	<b>"Collation '%1' not supported on this platform"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The collation that is not supported.
<b>Probable Cause</b>	The specified collation is not supported on the current platform.
<b>Error 1117</b>	<b>"A row cannot be stored because it exceeds the database page size"</b>
<b>Constant</b>	ROW_EXCEEDS_PAGE_SIZE
<b>SAP Sybase Error Number</b>	2789
<b>SQL State</b>	WW083
<b>SQL Code</b>	-1117L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to insert or update a row which is too large to be stored on a database page. For UltraLite, with the exception of BLOB columns, a row must fit entirely on a single database page. Larger page sizes may be used to accommodate larger rows.

## Messages 1118 through 1137

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1118</b>	<b>"Cannot change the MobiLink remote ID when the status of the last upload is unknown"</b>
<b>Constant</b>	CANNOT_CHANGE_ML_REMOTE_ID
<b>SAP Sybase Error Number</b>	2790
<b>SQL State</b>	0AW17
<b>SQL Code</b>	-1118L

<b>Error 1118</b>	<b>"Cannot change the MobiLink remote ID when the status of the last upload is unknown"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The MobiLink server uses the remote ID to track synchronization progress. If the status of the previous upload is unknown then you must resolve this condition before changing the remote ID.
<b>Error 1119</b>	<b>"The '%1' property is no longer supported"</b>
<b>Constant</b>	UNSUPPORTED_PROPERTY
<b>SAP Sybase Error Number</b>	2791
<b>SQL State</b>	42WC2
<b>SQL Code</b>	-1119L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the invalid property.
<b>Probable Cause</b>	The specified property is not supported in the current release.
<b>Error 1120</b>	<b>"The dbspace '%1' cannot be dropped because it contains tables or indexes"</b>
<b>Constant</b>	DBSPACE_CONTAINS_TABLES
<b>SAP Sybase Error Number</b>	2792
<b>SQL State</b>	55W26
<b>SQL Code</b>	-1120L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the dbspace

## Errors and Warnings

<b>Error 1120</b>	<b>"The dbspace '%1' cannot be dropped because it contains tables or indexes"</b>
<b>Probable Cause</b>	You attempted to drop the named dbspace, but it contains tables or indexes. You must drop the tables and/or indexes before dropping the dbspace.
<b>Error 1121</b>	<b>"Not enough free space on device to grow dbspace '%1' by requested amount"</b>
<b>Constant</b>	NO_ROOM_TO_GROW_DBSPACE
<b>SAP Sybase Error Number</b>	2793
<b>SQL State</b>	57W03
<b>SQL Code</b>	-1121L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the dbspace
<b>Probable Cause</b>	You attempted to grow a dbspace using the ALTER DBSPACE statement, but there is not enough free space on the device to grow by the amount specified.
<b>Error 1122</b>	<b>"Exceeded maximum of '%1' allowable parameters"</b>
<b>Constant</b>	INVALID_MAXIMUM_PARAMETERS
<b>SAP Sybase Error Number</b>	2794
<b>SQL State</b>	WW084
<b>SQL Code</b>	-1122L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The maximum number of allowable parameters
<b>Probable Cause</b>	The maximum allowable parameters for the given web client procedure or function has been exceeded.

<b>Error 1123</b>	<b>"Invalid mime type "%1"</b>
<b>Constant</b>	INVALID_MIMETYPE
<b>SAP Sybase Error Number</b>	2795
<b>SQL State</b>	WW085
<b>SQL Code</b>	-1123L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the mime type
<b>Probable Cause</b>	The mime type specifier is invalid.

<b>Error 1124</b>	<b>"The dbicu library and server versions do not match."</b>
<b>Constant</b>	ICU_DLL_VERSION_MISMATCH
<b>SAP Sybase Error Number</b>	2796
<b>SQL State</b>	WC014
<b>SQL Code</b>	-1124L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The server is unable to load ICU components that are required by this database. Ensure that the correct version of the dbicu libraries are installed.

<b>Error 1125</b>	<b>"Conflicting INSTEAD OF trigger and WITH CHECK OPTION on view "%1"</b>
<b>Constant</b>	CHECK_TRIGGER_CONFLICT
<b>SAP Sybase Error Number</b>	2797
<b>SQL State</b>	42W39
<b>SQL Code</b>	-1125L

## Errors and Warnings

<b>Error 1125</b>	<b>"Conflicting INSTEAD OF trigger and WITH CHECK OPTION on view "%1"</b>
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	Name of the view with an INSTEAD OF trigger
<b>Probable Cause</b>	You attempted an operation that involves a WITH CHECK OPTION clause that conflicts with an INSTEAD OF trigger. A view defined with the WITH CHECK OPTION clause cannot refer to a view (possibly nested) with an INSTEAD OF trigger.
<b>Error 1126</b>	<b>"Operation failed because table or view "%1' has an INSTEAD OF trigger"</b>
<b>Constant</b>	INSTEAD_TRIGGER
<b>SAP Sybase Error Number</b>	2798
<b>SQL State</b>	42W3A
<b>SQL Code</b>	-1126L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	Name of the view or table with an INSTEAD OF trigger
<b>Probable Cause</b>	You attempted an operation that cannot succeed because an INSTEAD OF trigger is defined on a target table or view (possibly nested in another view).
<b>Error 1127</b>	<b>"Positioned update operation attempted on a view with an INSTEAD OF trigger"</b>
<b>Constant</b>	INSTEAD_TRIGGER_POSITIONED
<b>SAP Sybase Error Number</b>	2799
<b>SQL State</b>	42W3B
<b>SQL Code</b>	-1127L

<b>Error 1127</b>	<b>"Positioned update operation attempted on a view with an INSTEAD OF trigger"</b>
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You attempted a positioned update, positioned delete, put, or wide insert operation that would involve an INSTEAD OF trigger on a view (possibly nested). These operations are not supported with INSTEAD OF triggers on views.
<b>Error 1128</b>	<b>"Start date/time for non-recurring event "%1' is in the past"</b>
<b>Constant</b>	EVENT_START_TIME_IN_PAST
<b>SAP Sybase Error Number</b>	2800
<b>SQL State</b>	WE010
<b>SQL Code</b>	-1128L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	Name of the event being scheduled.
<b>Probable Cause</b>	You have specified an event starting date or time that has already passed, and the event is not recurring.
<b>Error 1129</b>	<b>"The '%1' attribute contains mismatched parentheses within '%2'"</b>
<b>Constant</b>	INVALID_ATTRIBUTE_MISMATCH_BRACES
<b>SAP Sybase Error Number</b>	2801
<b>SQL State</b>	WW086
<b>SQL Code</b>	-1129L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 1129</b>	<b>"The '%1' attribute contains mismatched parentheses within '%2'"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The attribute on the procedure.
<b>Parameter 2</b>	The value of the attribute.
<b>Probable Cause</b>	The value of the attribute is not valid due to mismatched parenthesis (or possibly braces if specifying a port option).
<b>Error 1130</b>	<b>"The '%1' attribute is missing a comma within '%2'"</b>
<b>Constant</b>	INVALID_ATTRIBUTE_MISSING_COMMA
<b>SAP Sybase Error Number</b>	2802
<b>SQL State</b>	WW087
<b>SQL Code</b>	-1130L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The attribute on the procedure.
<b>Parameter 2</b>	The value of the attribute.
<b>Probable Cause</b>	The value of the attribute is not valid due to a missing comma.
<b>Error 1131</b>	<b>"The attribute '%1' sets an option '%2' that is incompatible with '%3'"</b>
<b>Constant</b>	INVALID_ATTRIBUTE_OPTIONS
<b>SAP Sybase Error Number</b>	2803
<b>SQL State</b>	WW088
<b>SQL Code</b>	-1131L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The attribute on the procedure.

<b>Error 1131</b>	<b>"The attribute '%1' sets an option '%2' that is incompatible with '%3'"</b>
<b>Parameter 2</b>	The first option of the attribute.
<b>Parameter 3</b>	The second option of the attribute.
<b>Probable Cause</b>	The options specified for this attribute are not compatible.

<b>Error 1132</b>	<b>"Maximum row size for table '%1' would be exceeded"</b>
<b>Constant</b>	MAX_ROW_SIZE_EXCEEDED
<b>SAP Sybase Error Number</b>	2804
<b>SQL State</b>	WW089
<b>SQL Code</b>	-1132L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Table name.
<b>Probable Cause</b>	You tried to create or alter a table with a maximum row size greater than 64 KB. In UltraLite, tables must be defined such that the maximum row size (the sum of the bytes required to store each column) is less than 64 KB.

<b>Error 1133</b>	<b>"Invalid trigger type for view '%1'"</b>
<b>Constant</b>	INVALID_TRIGGER_VIEW
<b>SAP Sybase Error Number</b>	2805
<b>SQL State</b>	42W3C
<b>SQL Code</b>	-1133L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Name of the view

## Errors and Warnings

<b>Error 1133</b>	<b>"Invalid trigger type for view "%1"</b>
<b>Probable Cause</b>	You attempted to create a trigger on a view, but the type of trigger is supported on base tables only. Only INSTEAD OF triggers can be created on views.
<b>Error 1134</b>	<b>"Triggers cannot be created on materialized view "%1"</b>
<b>Constant</b>	INVALID_TRIGGER_MATVIEW
<b>SAP Sybase Error Number</b>	2806
<b>SQL State</b>	42W3D
<b>SQL Code</b>	-1134L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Name of the materialized view
<b>Probable Cause</b>	You attempted to create a trigger on a materialized view. A materialized view is not a valid target for a trigger.
<b>Error 1135</b>	<b>"Invalid regular expression: %1 in "%2"</b>
<b>Constant</b>	INVALID_REGULAR_EXPRESSION
<b>SAP Sybase Error Number</b>	2808
<b>SQL State</b>	2201B
<b>SQL Code</b>	-1135L
<b>ODBC 2 State</b>	S1000
<b>ODBC 3 State</b>	2201B
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The reason the regular expression is invalid.
<b>Parameter 2</b>	The invalid regular expression.
<b>Probable Cause</b>	The specified regular expression is invalid.

<b>Error 1136</b>	<b>"Invalid use of escape character "%1"</b>
<b>Constant</b>	INVALID_USE_OF_ESCAPE_CHARACTER
<b>SAP Sybase Error Number</b>	2809
<b>SQL State</b>	2200C
<b>SQL Code</b>	-1136L
<b>ODBC 2 State</b>	S1000
<b>ODBC 3 State</b>	2200C
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The escape character that is invalid.
<b>Probable Cause</b>	The specified escape character cannot be used.
<b>Error 1137</b>	<b>"Escape character conflict "%1"</b>
<b>Constant</b>	ESCAPE_CHARACTER_CONFLICT
<b>SAP Sybase Error Number</b>	2810
<b>SQL State</b>	2200B
<b>SQL Code</b>	-1137L
<b>ODBC 2 State</b>	S1000
<b>ODBC 3 State</b>	2200B
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The escape character that is invalid.
<b>Probable Cause</b>	The specified escape character cannot be used.

## Messages 1138 through 1157

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1138</b>	<b>"The mirror "%1' does not match database "%2"</b>
<b>Constant</b>	MIRROR_FILE_MISMATCH
<b>SAP Sybase Error Number</b>	2811

## Errors and Warnings

<b>Error 1138</b>	<b>"The mirror '%1' does not match database '%2'"</b>
<b>SQL State</b>	WW090
<b>SQL Code</b>	-1138L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the mirror file
<b>Parameter 2</b>	The name of the database file
<b>Probable Cause</b>	The named mirror file does not correspond to the database file. This could happen if the database was not shut down properly, or if the wrong mirror file was specified. The mirror file must be moved or discarded before proceeding, or a different mirror specified.
<b>Error 1139</b>	<b>"The remote data access feature is not supported on this platform"</b>
<b>Constant</b>	OMNI FEATURE NOT SUPPORTED
<b>SAP Sybase Error Number</b>	2812
<b>SQL State</b>	0AW18
<b>SQL Code</b>	-1139L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You attempted to use a remote data access feature; however, remote data access is not supported on this platform.
<b>Error 1140</b>	<b>"Unable to start database '\%"1\": CHAR collation or tailoring not supported on this platform"</b>
<b>Constant</b>	CHAR_COLLATION_NOT_SUPPORTED
<b>SAP Sybase Error Number</b>	2813
<b>SQL State</b>	WC015
<b>SQL Code</b>	-1140L

<b>Error 1140</b>	<b>"Unable to start database \'%1\': CHAR collation or tailoring not supported on this platform"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The database name.
<b>Probable Cause</b>	The specified CHAR collation is not supported on the current platform.
<b>Error 1141</b>	<b>"Unable to start database \'%1\': NCHAR collation or tailoring not supported on this platform"</b>
<b>Constant</b>	NCHAR_COLLATION_NOT_SUPPORTED
<b>SAP Sybase Error Number</b>	2814
<b>SQL State</b>	WC016
<b>SQL Code</b>	-1141L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The database name.
<b>Probable Cause</b>	The specified NCHAR collation is not supported on the current platform.
<b>Error 1142</b>	<b>"Use of statement '%1', which requires feature '%2', is not allowed"</b>
<b>Constant</b>	SECURE_STATEMENT
<b>SAP Sybase Error Number</b>	2815
<b>SQL State</b>	57W04
<b>SQL Code</b>	-1142L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2

## Errors and Warnings

<b>Error 1142</b>	<b>"Use of statement '%1', which requires feature '%2', is not allowed"</b>
<b>Parameter 1</b>	Name of the SQL statement.
<b>Parameter 2</b>	Name of the feature.
<b>Probable Cause</b>	You have attempted to use a statement which requires a feature that was disabled by the server administrator when the database server was started.
<b>Error 1143</b>	<b>"Encryption has not been enabled."</b>
<b>Constant</b>	ENCRYPTION_NOT_ENABLED
<b>SAP Sybase Error Number</b>	2816
<b>SQL State</b>	55W27
<b>SQL Code</b>	-1143L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to use encryption without first enabling it. Call ULEnableAesDBEncryption or ULEnableAesFipsDBEncryption to enable encryption.
<b>Error 1144</b>	<b>"'%1' cannot be used as the encoding specification for '%2' data"</b>
<b>Constant</b>	INVALID_OPENSTRING_ENCODING
<b>SAP Sybase Error Number</b>	2818
<b>SQL State</b>	WC017
<b>SQL Code</b>	-1144L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The encoding that has been specified

<b>Error 1144</b>	<b>"'%1' cannot be used as the encoding specification for '%2' data"</b>
<b>Parameter 2</b>	The data type for which the encoding has been specified
<b>Probable Cause</b>	The specified encoding cannot be used for interpreting the given data. For CHAR data, the encoding must be the database's CHAR character encoding and for NCHAR data, it must be the database's NCHAR character encoding.
<b>Error 1145</b>	<b>"Unable to connect: The server did not accept the requested encryption type"</b>
<b>Constant</b>	ENCRYPTION_TYPE_NOT_ACCEPTED
<b>SAP Sybase Error Number</b>	2819
<b>SQL State</b>	08W97
<b>SQL Code</b>	-1145L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The server only accepts certain encryption types, and the connection's encryption type is not one of the accepted types. The -ec server option is used to configure the encryption types that the server accepts.
<b>Error 1146</b>	<b>"LOAD TABLE not allowed on temporary table which has foreign key references from another table"</b>
<b>Constant</b>	INVALID_LOAD_TABLE_WITH_FOREIGN_KEY
<b>SAP Sybase Error Number</b>	2820
<b>SQL State</b>	WL009
<b>SQL Code</b>	-1146L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

## Errors and Warnings

<b>Error 1146</b>	<b>"LOAD TABLE not allowed on temporary table which has foreign key references from another table"</b>
<b>Probable Cause</b>	The LOAD TABLE statement removes all rows in a temporary table upon failure. If a temporary table being loaded caused an error then the foreign rows would be orphaned.
<b>Error 1147</b>	<b>"Database "%1' cannot be started on this platform. See <a href="http://ianywhere.com/developer/product_manuals/sqlanywhere/notes/en/endian_corruption_warning.html">http://ianywhere.com/developer/product_manuals/sqlanywhere/notes/en/endian_corruption_warning.html</a>"</b>
<b>Constant</b>	POSSIBLE_DATABASE_CORRUPTION
<b>SAP Sybase Error Number</b>	2821
<b>SQL State</b>	08W98
<b>SQL Code</b>	-1147L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The name of the database.
<b>Probable Cause</b>	It was determined that the database may be corrupt. More information and instructions on how to proceed are available at: <a href="http://ianywhere.com/developer/product_manuals/sqlanywhere/notes/en/endian_corruption_warning.html">http://ianywhere.com/developer/product_manuals/sqlanywhere/notes/en/endian_corruption_warning.html</a>
<b>Error 1148</b>	<b>"Feature not supported by the client version or the client interface"</b>
<b>Constant</b>	NOT_SUPPORTED_BY_CLIENT
<b>SAP Sybase Error Number</b>	2824
<b>SQL State</b>	0AW19
<b>SQL Code</b>	-1148L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

<b>Error 1148</b>	<b>"Feature not supported by the client version or the client interface"</b>
<b>Probable Cause</b>	You have attempted to use a feature which the server supports but the client does not. To use the feature, you must upgrade the client library or use a different client interface. Some features are not supported by the jConnect or Open Client client interfaces.
<b>Error 1149</b>	<b>"Database '%1' cannot be started on this platform. See <a href="http://anywhere.com/developer/product_manuals/sqlanywhere/notes/en/endian_cant_change_platform.html">http://anywhere.com/developer/product_manuals/sqlanywhere/notes/en/endian_cant_change_platform.html</a>"</b>
<b>Constant</b>	DATABASE_ENDIAN_FAILURE
<b>SAP Sybase Error Number</b>	2825
<b>SQL State</b>	08W99
<b>SQL Code</b>	-1149L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The name of the database.
<b>Probable Cause</b>	It was determined that the database cannot be started on the current platform because doing so could possibly cause an endian related database file corruption. It will continue to start without problems on a platform with the opposite endian. More information and instructions on how to proceed are available at: <a href="http://anywhere.com/developer/product_manuals/sqlanywhere/notes/en/endian_cant_change_platform.html">http://anywhere.com/developer/product_manuals/sqlanywhere/notes/en/endian_cant_change_platform.html</a>
<b>Error 1150</b>	<b>"The SQL scripts DLL cannot be loaded"</b>
<b>Constant</b>	INVALID_SCRIPT_DLL
<b>SAP Sybase Error Number</b>	2826
<b>SQL State</b>	WW091
<b>SQL Code</b>	-1150L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 1150</b>	<b>"The SQL scripts DLL cannot be loaded"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The SQL scripts DLL cannot be loaded. The DLL might be missing or the version found might not match the version of the database server being used.
<b>Error 1151</b>	<b>"The logging type ('%1') specified is invalid, not supported or incompatible"</b>
<b>Constant</b>	INVALID_LOAD_LOGGING_TYPE
<b>SAP Sybase Error Number</b>	2827
<b>SQL State</b>	WL010
<b>SQL Code</b>	-1151L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>19</i> on page 2
<b>Parameter 1</b>	The specified logging type.
<b>Probable Cause</b>	The logging type specified for LOAD TABLE is not supported for the version of the database being used, is incompatible with other specifications of the statement or is not supported for the specific table being loaded into.
<b>Error 1152</b>	<b>"Password has expired"</b>
<b>Constant</b>	PASSWORD_EXPIRED
<b>SAP Sybase Error Number</b>	2828
<b>SQL State</b>	08WA0
<b>SQL Code</b>	-1152L
<b>ODBC 2 State</b>	28000
<b>ODBC 3 State</b>	28000
<b>Severity Code</b>	<i>16</i> on page 2

<b>Error 1152</b>	<b>"Password has expired"</b>
<b>Probable Cause</b>	You attempted to connect using a valid user ID, but with an expired password. You can change your password by supplying the New-Password connection parameter along with the current expired password.
<b>Error 1153</b>	<b>"Password has expired but cannot be changed because the database is read-only"</b>
<b>Constant</b>	PASSWORD_EXPIRED_READONLY_DB
<b>SAP Sybase Error Number</b>	2829
<b>SQL State</b>	08WA1
<b>SQL Code</b>	-1153L
<b>ODBC 2 State</b>	28000
<b>ODBC 3 State</b>	28000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to connect to a read-only database using a valid user ID, but with an expired password. The password cannot be changed unless the database is started without the -r option on the database server command line. Removing -r will permit modifications to the database.
<b>Error 1154</b>	<b>"Traced query (%1, %2) does not exist"</b>
<b>Constant</b>	INVALID_TRACED_PLAN
<b>SAP Sybase Error Number</b>	2830
<b>SQL State</b>	55W28
<b>SQL Code</b>	-1154L
<b>ODBC 2 State</b>	28000
<b>ODBC 3 State</b>	28000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The specified logging session ID.
<b>Parameter 2</b>	The specified query ID.

## Errors and Warnings

<b>Error 1154</b>	<b>"Traced query (%1, %2) does not exist"</b>
<b>Probable Cause</b>	You attempted to generate a graphical plan for a query saved by diagnostic tracing, identified by a logging_session_id and query ID. However, no such query exists in this database. If it was traced, it was sent to a different database.
<b>Error 1155</b>	<b>"Unable to close the cursor on table \"%1\". LOAD TABLE cannot be executed."</b>
<b>Constant</b>	CANNOT_LOAD_TEMP_WITH_CURSOR
<b>SAP Sybase Error Number</b>	2831
<b>SQL State</b>	WL011
<b>SQL Code</b>	-1155L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the table.
<b>Probable Cause</b>	You cannot perform LOAD TABLE on a temporary table that has an open cursor on it. An attempt to close the cursor failed. A failed LOAD TABLE would cause all of the rows in the temporary table to be deleted thereby invalidating the cursor.
<b>Error 1156</b>	<b>"Argument \"%1\" must be a column reference."</b>
<b>Constant</b>	TEXT_BAD_COLUMN_REFERENCE
<b>SAP Sybase Error Number</b>	2832
<b>SQL State</b>	WT001
<b>SQL Code</b>	-1156L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The argument number.
<b>Probable Cause</b>	The CONTAINS argument must be a column reference.

<b>Error 1157</b>	"All column reference arguments must refer to the same table."
<b>Constant</b>	TEXT_TOO_MANY_TABLE_REFERENCES
<b>SAP Sybase Error Number</b>	2833
<b>SQL State</b>	WT002
<b>SQL Code</b>	-1157L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	All column references in a CONTAINS query must refer to the same table.

## Messages 1158 through 1177

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1158</b>	"No matching text index."
<b>Constant</b>	TEXT_NO_MATCHING_INDEX
<b>SAP Sybase Error Number</b>	2834
<b>SQL State</b>	WT003
<b>SQL Code</b>	-1158L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A single text index must exist on all columns referenced in a CONTAINS query.
<b>Error 1159</b>	"Non-constant or unknown text query string."
<b>Constant</b>	TEXT_QUERY_NOT_KNOWN
<b>SAP Sybase Error Number</b>	2835
<b>SQL State</b>	WT004

## Errors and Warnings

<b>Error 1159</b>	"Non-constant or unknown text query string."
<b>SQL Code</b>	-1159L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The query string argument to a CONTAINS query must be a constant, or a non-null value in a variable.
<b>Error 1160</b>	"Text configuration \"%1%\\".%2\\" not found."
<b>Constant</b>	TEXT_CONFIG_NOT_FOUND
<b>SAP Sybase Error Number</b>	2836
<b>SQL State</b>	WT005
<b>SQL Code</b>	-1160L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The text configuration creator.
<b>Parameter 2</b>	The text configuration name.
<b>Probable Cause</b>	The specified text configuration does not exist.
<b>Error 1161</b>	"Text configuration \"%1\\" already exists."
<b>Constant</b>	TEXT_CONFIG_ALREADY_EXISTS
<b>SAP Sybase Error Number</b>	2837
<b>SQL State</b>	WT006
<b>SQL Code</b>	-1161L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The text configuration name.

<b>Error 1161</b>	<b>"Text configuration \%"1\%" already exists."</b>
<b>Probable Cause</b>	The specified text configuration name already exists.
<b>Error 1162</b>	<b>"Term length outside allowed range."</b>
<b>Constant</b>	TEXT_BAD_TERM_LENGTH
<b>SAP Sybase Error Number</b>	2838
<b>SQL State</b>	WT007
<b>SQL Code</b>	-1162L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The minimum and maximum term lengths must both be greater than 0 and less than or equal to 60 characters.
<b>Error 1163</b>	<b>"Invalid collation: \%"1\%"."</b>
<b>Constant</b>	TEXT_BAD_COLLATION
<b>SAP Sybase Error Number</b>	2839
<b>SQL State</b>	WT008
<b>SQL Code</b>	-1163L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The invalid collation string.
<b>Probable Cause</b>	The collation was not found, or the tailoring options were invalid.
<b>Error 1164</b>	<b>"Text query parser error: %1"</b>
<b>Constant</b>	TEXT_PARSER_ERROR
<b>SAP Sybase Error Number</b>	2840
<b>SQL State</b>	WT009
<b>SQL Code</b>	-1164L

## Errors and Warnings

<b>Error 1164</b>	"Text query parser error: %1"
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The error message returned by the text query parser.
<b>Probable Cause</b>	The text query could not be parsed.
<b>Error 1165</b>	<b>"Error creating text index \"%1\" on table \"%2\No message</b>
<b>Constant</b>	TEXT_INDEX_CREATION_ERROR
<b>SAP Sybase Error Number</b>	2841
<b>SQL State</b>	WT010
<b>SQL Code</b>	-1165L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the text index.
<b>Parameter 2</b>	The name of the table.
<b>Probable Cause</b>	There was an internal error creating a text index.
<b>Error 1166</b>	<b>"Text indexes are not supported for this database."</b>
<b>Constant</b>	TEXT_UPGRADE_REQUIRED
<b>SAP Sybase Error Number</b>	2842
<b>SQL State</b>	WT011
<b>SQL Code</b>	-1166L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The current database does not have catalog support for text indexes. To use this feature, upgrade your database to the most recent version.

<b>Error 1167</b>	<b>"Cannot drop a user that owns text configurations"</b>
<b>Constant</b>	USER_OWNS_TEXT_CONFIG
<b>SAP Sybase Error Number</b>	2843
<b>SQL State</b>	55W12
<b>SQL Code</b>	-1167L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to drop a user that is the creator of a text configuration. The text configuration must be dropped first.

<b>Error 1168</b>	<b>"Cannot alter or drop a text configuration referenced by a text index."</b>
<b>Constant</b>	TEXT_CANNOT_ALTER_CONFIG
<b>SAP Sybase Error Number</b>	2844
<b>SQL State</b>	WT012
<b>SQL Code</b>	-1168L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	It is not possible to alter or drop a text configuration referenced by a populated text index or currently being used by a text procedure. Either copy the configuration and alter the copy, or close all cursors on text procedures and truncate all indexes that use the configuration.

<b>Error 1169</b>	<b>"Cannot access a table that is part of a text index."</b>
<b>Constant</b>	TEXT_CANNOT_USE_TEXT_INDEX
<b>SAP Sybase Error Number</b>	2846
<b>SQL State</b>	WT013
<b>SQL Code</b>	-1169L

## Errors and Warnings

<b>Error 1169</b>	<b>"Cannot access a table that is part of a text index."</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	It is not possible to directly manipulate tables created as part of a text index.
<b>Error 1170</b>	<b>"The materialized view %1 cannot be changed to immediate because it has already been initialized"</b>
<b>Constant</b>	IMMEDIATE_MV_REFRESH_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	2847
<b>SQL State</b>	42WC3
<b>SQL Code</b>	-1170L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Name of the materialized view.
<b>Probable Cause</b>	You attempted to change the refresh type to immediate for a materialized view which is already in an initialized state. Truncate the view before changing the refresh type.
<b>Error 1171</b>	<b>"Client application does not allow transfer of data ("%1)"</b>
<b>Constant</b>	CLIENT_TRANSFER_NO_VALIDATION
<b>SAP Sybase Error Number</b>	2848
<b>SQL State</b>	WW092
<b>SQL Code</b>	-1171L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

<b>Error 1171</b>	<b>"Client application does not allow transfer of data ("%1")"</b>
<b>Parameter 1</b>	The name of the object being transferred to/from the application.
<b>Probable Cause</b>	The client application does not allow the transfer of server initiated data. To allow transfer of server initiated data, the application must register a validation callback mechanism with the client library.
<b>Error 1172</b>	<b>"Client application disallowed the transfer of data ("%1")"</b>
<b>Constant</b>	CLIENT_TRANSFER_DISALLOWED
<b>SAP Sybase Error Number</b>	2849
<b>SQL State</b>	WW093
<b>SQL Code</b>	-1172L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the object being transferred to/from the application.
<b>Probable Cause</b>	The client application rejected the transfer of server initiated data. To allow transfer of server initiated data, the application registered a validation callback which rejected the transfer of requested data.
<b>Error 1173</b>	<b>"Client library reported an error accessing data during transfer ("%1")"</b>
<b>Constant</b>	CLIENT_TRANSFER_ACCESS_ERROR
<b>SAP Sybase Error Number</b>	2850
<b>SQL State</b>	WW094
<b>SQL Code</b>	-1173L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the object being transferred to/from the application.

## Errors and Warnings

<b>Error 1173</b>	<b>"Client library reported an error accessing data during transfer ('%1')"</b>
<b>Probable Cause</b>	The client application reported an error while attempting to access the data for a transfer request from the server. Reasons could include the client application lacking permissions to the data object or other operating system reported errors.
<b>Error 1174</b>	<b>"Cannot create text configuration '%1' because option '%2' has an inappropriate setting"</b>
<b>Constant</b>	TEXT_BAD_OPTION
<b>SAP Sybase Error Number</b>	2851
<b>SQL State</b>	WT014
<b>SQL Code</b>	-1174L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the configuration.
<b>Parameter 2</b>	Name of the option with the incorrect setting.
<b>Probable Cause</b>	You attempted an operation that needs to create or alter the database options settings for a text configuration, but one of the options is currently set to a value not permitted for a text configuration.
<b>Error 1175</b>	<b>"Unable to acquire table locks in specified time"</b>
<b>Constant</b>	LOCK_TIMEOUT
<b>SAP Sybase Error Number</b>	2852
<b>SQL State</b>	42WC4
<b>SQL Code</b>	-1175L
<b>ODBC 2 State</b>	40001
<b>ODBC 3 State</b>	40001
<b>Severity Code</b>	<i>21</i> on page 2

<b>Error 1175</b>	<b>"Unable to acquire table locks in specified time"</b>
<b>Probable Cause</b>	The LOCK TABLE statement could not acquire all the locks in specified time period.
<b>Error 1176</b>	<b>"Plan not available. NOEXEC plan cannot be generated for this type of statement"</b>
<b>Constant</b>	STMT_NOT_ALLOWED_FOR_NOEXEC_PLAN
<b>SAP Sybase Error Number</b>	2853
<b>SQL State</b>	0AW20
<b>SQL Code</b>	-1176L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You tried to get the NOEXEC plan for a statement type for which SAP Sybase IQ cannot generate a NOEXEC plan.
<b>Error 1177</b>	<b>"No plan. HTML_PLAN function is not supported for this type of statement or database."</b>
<b>Constant</b>	HTML_PLAN_NOT_SUPPORTED
<b>SAP Sybase Error Number</b>	2854
<b>SQL State</b>	0AW21
<b>SQL Code</b>	-1177L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You tried to get the HTML plan for a query which is either a SQL Anywhere query or a remote data access/CIS decomposed query. HTML_PLAN is supported for a pure SAP Sybase IQ query.

## Messages 1178 through 1197

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1178</b>	"Transaction log mirroring cannot be used with database mirroring"
<b>Constant</b>	MIRROR_LOG_WITH_DB_MIRROR
<b>SAP Sybase Error Number</b>	2855
<b>SQL State</b>	WW095
<b>SQL Code</b>	-1178L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Transaction log mirroring cannot be used with database mirroring. Use the dblog utility to disable transaction log mirroring.
<b>Error 1179</b>	"Unable to start database server: missing license file"
<b>Constant</b>	UNABLE_TO_START_ENGINE_MISSING_LICENSE
<b>SAP Sybase Error Number</b>	2856
<b>SQL State</b>	08WA2
<b>SQL Code</b>	-1179L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>17</i> on page 2
<b>Probable Cause</b>	It was not possible to start the database server because the server license file was not found. The server license file has the same name as the server executable with the extension ".lic".

<b>Error 1180</b>	<b>"Cannot set database option \'%1\' because it is on the options watch list"</b>
<b>Constant</b>	OPTION_ON_WATCH_LIST
<b>SAP Sybase Error Number</b>	2857
<b>SQL State</b>	WW096
<b>SQL Code</b>	-1180L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the option.
<b>Probable Cause</b>	An attempt was made to set a database option that is on the options watch list. The options watch list is used to help find references to options that have been removed or deprecated.
<b>Error 1181</b>	<b>"The materialized view cannot be changed to immediate because its definition must not contain more than one query block"</b>
<b>Constant</b>	UPDATABLE_MATVIEW_MULTIBLE_BLOCK_ERR
<b>SAP Sybase Error Number</b>	2858
<b>SQL State</b>	42WC5
<b>SQL Code</b>	-1181L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You attempted to change the refresh type to immediate for a materialized view whose definition contains more than one query block.
<b>Error 1182</b>	<b>"Statement not allowed on IMMEDIATE REFRESH text index"</b>
<b>Constant</b>	TEXT_IMMEDIATE_NOT_ALLOWED

## Errors and Warnings

<b>Error 1182</b>	"Statement not allowed on IMMEDIATE REFRESH text index"
<b>SAP Sybase Error Number</b>	2859
<b>SQL State</b>	WT015
<b>SQL Code</b>	-1182L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You cannot use REFRESH TEXT INDEX or TRUNCATE TEXT INDEX on an index that is created with immediate refresh. You cannot alter a text index to use or stop using immediate refresh.
<b>Error 1183</b>	"Support for permissions on dbspaces is not available for this database"
<b>Constant</b>	DBSPACE_PERMS_NOT_SUPPORTED
<b>SAP Sybase Error Number</b>	2860
<b>SQL State</b>	0AW22
<b>SQL Code</b>	-1183L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	The statement being executed requires support for permissions on dbspaces, but the database being used does not have this capability. The database must be recreated or upgraded using a version of the server that supports permissions on dbspaces.
<b>Error 1184</b>	"Cannot drop last unique index of an immediate materialized view"
<b>Constant</b>	DELETE_UPDATABLE_MATVIEW_INDEX_ERR
<b>SAP Sybase Error Number</b>	2861

<b>Error 1184</b>	<b>"Cannot drop last unique index of an immediate materialized view"</b>
<b>SQL State</b>	55W21
<b>SQL Code</b>	-1184L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to drop the last unique index on non-nullable columns of an immediate materialized view. Immediate materialized view needs at least one unique index on non-nullable columns to be valid.
<b>Error 1185</b>	<b>"Index validation failed for table %1, index %2 with code: %3"</b>
<b>Constant</b>	CORRUPT_ULTRALITE_INDEX
<b>SAP Sybase Error Number</b>	2862
<b>SQL State</b>	WI002
<b>SQL Code</b>	-1185L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	The name of the table.
<b>Parameter 2</b>	The name of the index.
<b>Parameter 3</b>	The specific kind of corruption that was found.
<b>Probable Cause</b>	UltraLite database validation failed while validating the specified index. The code provides more specific information on the validation failure.
<b>Error 1186</b>	<b>"Database page validation failed with code: %1"</b>
<b>Constant</b>	CORRUPT_ULTRALITE_DATABASE
<b>SAP Sybase Error Number</b>	2863
<b>SQL State</b>	WI003

## Errors and Warnings

<b>Error 1186</b>	<b>"Database page validation failed with code: %1"</b>
<b>SQL Code</b>	-1186L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	The specific kind of corruption that was found.
<b>Probable Cause</b>	UltraLite database validation failed while validating the database pages. The code provides more specific information on the validation failure.
<b>Error 1187</b>	<b>"Cannot append when using compression or encryption"</b>
<b>Constant</b>	UNLOAD_CANNOT_APPEND
<b>SAP Sybase Error Number</b>	2864
<b>SQL State</b>	WL012
<b>SQL Code</b>	-1187L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	16 on page 2
<b>Probable Cause</b>	The UNLOAD statement cannot append to a file when using compression or encryption. Either the compressed or encrypted keywords were specified, or the file being appended to is compressed or encrypted.
<b>Error 1188</b>	<b>"LOAD TABLE error: %1"</b>
<b>Constant</b>	LOAD_TABLE_ERROR
<b>SAP Sybase Error Number</b>	2865
<b>SQL State</b>	WL013
<b>SQL Code</b>	-1188L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1188</b>	"LOAD TABLE error: %1"
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Description of the failure encountered
<b>Probable Cause</b>	The LOAD TABLE statement failed. The message specifies the actual problem that occurred.

<b>Error 1189</b>	<b>"The UTF-16 endian specified does not match the Byte Order Mark found in the data"</b>
<b>Constant</b>	UTF16_ENDIAN_MISMATCH
<b>SAP Sybase Error Number</b>	2866
<b>SQL State</b>	WC004
<b>SQL Code</b>	-1189L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The specified UTF-16 encoding explicitly specifies the expected endian of the data; however, the Byte Order Mark found at the beginning of the data indicates that the data is encoded in the opposite endian.

<b>Error 1190</b>	<b>"LOAD TABLE is not allowed on a materialized view %1"</b>
<b>Constant</b>	LOAD_TABLE_ON_MATVIEW_ERROR
<b>SAP Sybase Error Number</b>	2867
<b>SQL State</b>	WL014
<b>SQL Code</b>	-1190L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the materialized view on which load was attempted.
<b>Probable Cause</b>	LOAD TABLE statement is not allowed on a materialized view.

## Errors and Warnings

<b>Error 1191</b>	<b>"LOAD TABLE not allowed: initialized immediate materialized view %1 depends on %2"</b>
<b>Constant</b>	LOAD_TABLE_WITH_IMV
<b>SAP Sybase Error Number</b>	2868
<b>SQL State</b>	WL015
<b>SQL Code</b>	-1191L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the dependent initialized immediate materialized view.
<b>Parameter 2</b>	Name of the table on which load was performed.
<b>Probable Cause</b>	LOAD TABLE is not permitted on any table that has dependent initialized immediate materialized views.
<b>Error 1192</b>	<b>"Cannot update multiple tables immediate materialized view %1 depends on"</b>
<b>Constant</b>	CANNOT_UPDATE_TWO_TABLES_IMV
<b>SAP Sybase Error Number</b>	2869
<b>SQL State</b>	55W29
<b>SQL Code</b>	-1192L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the view that depends on two or more tables in the update statement.
<b>Probable Cause</b>	You attempted to simultaneously update two or more tables initialized immediate materialized view depends on. No more than one base table an immediate materialized view depends on can be updated in a statement.

<b>Error 1193</b>	<b>"TRUNCATE TABLE not allowed: initialized immediate materialized view %1 depends on %2"</b>
<b>Constant</b>	TRUNCATE_TABLE_WITH_IMV
<b>SAP Sybase Error Number</b>	2870
<b>SQL State</b>	55W30
<b>SQL Code</b>	-1193L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the dependent initialized immediate materialized view.
<b>Parameter 2</b>	Name of the table on which TRUNCATE TABLE was performed.
<b>Probable Cause</b>	TRUNCATE TABLE is not permitted on any table that has dependent initialized immediate materialized views.
<b>Error 1194</b>	<b>"Login policy \"%1\" already exists"</b>
<b>Constant</b>	LOGIN_POLICY_ALREADY_EXISTS
<b>SAP Sybase Error Number</b>	2871
<b>SQL State</b>	WW097
<b>SQL Code</b>	-1194L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the login policy.
<b>Probable Cause</b>	An attempt was made to create a login policy that already exists in the database.
<b>Error 1195</b>	<b>"Login policy \"%1\" not found"</b>
<b>Constant</b>	LOGIN_POLICY_NOT_FOUND
<b>SAP Sybase Error Number</b>	2872
<b>SQL State</b>	WW098

## Errors and Warnings

<b>Error 1195</b>	<b>"Login policy \"%1\" not found"</b>
<b>SQL Code</b>	-1195L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the login policy.
<b>Probable Cause</b>	The named login policy was not found in the database.
<b>Error 1196</b>	<b>"Login policies are not supported for this database"</b>
<b>Constant</b>	LOGIN_POLICY_UPGRADE
<b>SAP Sybase Error Number</b>	2873
<b>SQL State</b>	WW099
<b>SQL Code</b>	-1196L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The current database does not have catalog support for login policies. To use this feature, upgrade your database to the most recent version.
<b>Error 1197</b>	<b>"Login policy \"%1\" in use"</b>
<b>Constant</b>	LOGIN_POLICY_IN_USE
<b>SAP Sybase Error Number</b>	2874
<b>SQL State</b>	WW100
<b>SQL Code</b>	-1197L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the login policy.

<b>Error 1197</b>	<b>"Login policy \"%1\" in use"</b>
<b>Probable Cause</b>	The named login policy is associated with a user in the database. Any users associated with the login policy must be assigned a different login policy before the named login policy can be dropped.

## Messages 1198 through 1217

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1198</b>	<b>"User \"%1\" already exists"</b>
<b>Constant</b>	USER_ALREADY_EXISTS
<b>SAP Sybase Error Number</b>	2875
<b>SQL State</b>	WW101
<b>SQL Code</b>	-1198L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the user.
<b>Probable Cause</b>	An attempt was made to create a user that already exists in the database.
<b>Error 1199</b>	<b>"The materialized view cannot be changed to immediate because COUNT(*) must be part of the SELECT list."</b>
<b>Constant</b>	UPDATABLE_MATVIEW_MISSING_COUNT
<b>SAP Sybase Error Number</b>	2876
<b>SQL State</b>	42WC6
<b>SQL Code</b>	-1199L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2

## Errors and Warnings

<b>Error 1199</b>	<b>"The materialized view cannot be changed to immediate because COUNT(*) must be part of the SELECT list."</b>
<b>Probable Cause</b>	You attempted to change the refresh type to immediate for a materialized view whose definition does not include COUNT(*) in the SELECT list.
<b>Error 1200</b>	<b>"Client library reported a permissions error accessing object ("%1') during transfer"</b>
<b>Constant</b>	CLIENT_TRANSFER_PERMS_ERROR
<b>SAP Sybase Error Number</b>	2877
<b>SQL State</b>	WW103
<b>SQL Code</b>	-1200L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the object being transferred to/from the application.
<b>Probable Cause</b>	The client application reported a permissions error while attempting to access the object for a data transfer request from the server. The client application likely does not have the necessary operating system authorization required to access the object.
<b>Error 1201</b>	<b>"Client library reported an error opening object ("%1') during transfer"</b>
<b>Constant</b>	CLIENT_TRANSFER_OPEN_ERROR
<b>SAP Sybase Error Number</b>	2878
<b>SQL State</b>	WW102
<b>SQL Code</b>	-1201L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

<b>Error 1201</b>	<b>"Client library reported an error opening object ('%1') during transfer"</b>
<b>Parameter 1</b>	The name of the object being transferred to/from the application.
<b>Probable Cause</b>	The client application reported an error while attempting to open the object for a data transfer request from the server. Reasons could include an invalid name for the object or a missing object.
<b>Error 1202</b>	<b>"Operation not allowed on a table with dependent immediate materialized views"</b>
<b>Constant</b>	INVALID_OPERATION_FOR_TBL_WITH_IMV
<b>SAP Sybase Error Number</b>	2879
<b>SQL State</b>	55W31
<b>SQL Code</b>	-1202L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Requested operation cannot be applied to a table with dependent immediate materialized views.
<b>Error 1203</b>	<b>"WRITETEXT not allowed: immediate materialized view %1 depends on %2"</b>
<b>Constant</b>	WRITETEXT_TABLE_WITH_IMV
<b>SAP Sybase Error Number</b>	2880
<b>SQL State</b>	55W32
<b>SQL Code</b>	-1203L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the dependent immediate materialized view.
<b>Parameter 2</b>	Name of the base table.

## Errors and Warnings

<b>Error 1203</b>	<b>"WRITETEXT not allowed: immediate materialized view %1 depends on %2"</b>
<b>Probable Cause</b>	WRITETEXT is not allowed on base tables that have dependent initialized immediate materialized views. No operation that does not fire triggers is allowed on base tables with dependent initialized immediate materialized views.
<b>Error 1204</b>	<b>"INSERT...ON EXISTING UPDATE not allowed: immediate materialized view %1 depends on %2"</b>
<b>Constant</b>	UPDATE_ON_EXISTING_DEP_IMV
<b>SAP Sybase Error Number</b>	2881
<b>SQL State</b>	55W33
<b>SQL Code</b>	-1204L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of dependent immediate materialized view.
<b>Parameter 2</b>	The name of the base table into which the insert was performed.
<b>Probable Cause</b>	Insert statement with ON EXISTING clause is not permitted on a base table if the base table has dependent initialized immediate materialized view.
<b>Error 1205</b>	<b>"External environment "%1' could not be found"</b>
<b>Constant</b>	EXTERN_ENV_NOT_FOUND
<b>SAP Sybase Error Number</b>	2882
<b>SQL State</b>	WJ030
<b>SQL Code</b>	-1205L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	Name of the external environment.

<b>Error 1205</b>	<b>"External environment "%1' could not be found"</b>
<b>Probable Cause</b>	You attempted to define an object for an external environment that has not been added.
<b>Error 1206</b>	<b>"External environments are not supported for this database"</b>
<b>Constant</b>	EXTERN_ENV_UPGRADE
<b>SAP Sybase Error Number</b>	2883
<b>SQL State</b>	WW104
<b>SQL Code</b>	-1206L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The current database does not have catalog support for external environments. To use this feature, upgrade your database to the most recent version.
<b>Error 1207</b>	<b>"Invalid use of NEAR operator in text query."</b>
<b>Constant</b>	TEXT_INVALID_NEAR
<b>SAP Sybase Error Number</b>	2884
<b>SQL State</b>	WT016
<b>SQL Code</b>	-1207L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	Only terms and prefixes are allowed as arguments to a NEAR operator.
<b>Error 1208</b>	<b>"Invalid partition bound value "%1"</b>
<b>Constant</b>	BAD_PARTITION_BOUND_VALUE
<b>SAP Sybase Error Number</b>	2885

## Errors and Warnings

<b>Error 1208</b>	<b>"Invalid partition bound value '%1'"</b>
<b>SQL State</b>	WW105
<b>SQL Code</b>	-1208L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The partition bound value.
<b>Probable Cause</b>	The partition bound value is invalid and cannot be used.
<b>Error 1209</b>	<b>"Cannot convert value '%1' to an %2"</b>
<b>Constant</b>	PARTITION_BOUND_VALUE_CONVERSION
<b>SAP Sybase Error Number</b>	2886
<b>SQL State</b>	WW106
<b>SQL Code</b>	-1209L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The partition bound value.
<b>Parameter 2</b>	The type of the partition key.
<b>Probable Cause</b>	The value is not compatible with the type of the partition key.
<b>Error 1210</b>	<b>"Partition bound value '%1' out of order"</b>
<b>Constant</b>	PARTITION_BOUND_VALUE_ORDER
<b>SAP Sybase Error Number</b>	2887
<b>SQL State</b>	WW107
<b>SQL Code</b>	-1210L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

<b>Error 1210</b>	<b>"Partition bound value "%1' out of order"</b>
<b>Parameter 1</b>	The partition bound value.
<b>Probable Cause</b>	Range partition bound values must be provided in ascending order.
<b>Error 1211</b>	<b>"MERGE statement ANSI cardinality violation on table "%1"</b>
<b>Constant</b>	MERGE_CARDINALITY_VIOLATION
<b>SAP Sybase Error Number</b>	2888
<b>SQL State</b>	23509
<b>SQL Code</b>	-1211L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the table being updated
<b>Probable Cause</b>	You have attempted to execute the MERGE statement and the same row is the target of a WHEN MATCHED clause more than once.
<b>Error 1212</b>	<b>"Connection disallowed by login policy for this user"</b>
<b>Constant</b>	CONNECTION_DISALLOWED_BY_LOGIN_POLICY
<b>SAP Sybase Error Number</b>	2889
<b>SQL State</b>	28W15
<b>SQL Code</b>	-1212L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A connection attempt was disallowed based on the login policy for the user. It may be necessary for a user with DBA authority to reset this user via the ALTER USER statement.
<b>Error 1213</b>	<b>"External environment does not support result sets"</b>
<b>Constant</b>	EXTERN_ENV_NO_RESULT_SET_SUPPORT

## Errors and Warnings

<b>Error 1213</b>	<b>"External environment does not support result sets"</b>
<b>SAP Sybase Error Number</b>	2891
<b>SQL State</b>	WJ031
<b>SQL Code</b>	-1213L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Probable Cause</b>	You attempted to define dynamic result sets for an external environment that does not support result sets.
<b>Error 1214</b>	<b>"External library "%1' is in use"</b>
<b>Constant</b>	EXTERNAL_LIBRARY_IN_USE
<b>SAP Sybase Error Number</b>	2892
<b>SQL State</b>	WW108
<b>SQL Code</b>	-1214L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The external library that is in use
<b>Probable Cause</b>	The external library cannot be unloaded as it is currently in use.
<b>Error 1215</b>	<b>"External library "%1' not loaded"</b>
<b>Constant</b>	EXTERNAL_LIBRARY_NOT_LOADED
<b>SAP Sybase Error Number</b>	2893
<b>SQL State</b>	WW109
<b>SQL Code</b>	-1215L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

<b>Error 1215</b>	<b>"External library "%1' not loaded"</b>
<b>Parameter 1</b>	The external library that is not loaded
<b>Probable Cause</b>	The external library cannot be unloaded as it is not current loaded.
<b>Error 1216</b>	<b>"The arguments to this procedure must be literal strings."</b>
<b>Constant</b>	TEXT_NEED_CONSTANT_ARGUMENT
<b>SAP Sybase Error Number</b>	2894
<b>SQL State</b>	WT017
<b>SQL Code</b>	-1216L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	This procedure only accepts literal strings as arguments.
<b>Error 1217</b>	<b>"Synchronization profile "%1' not found"</b>
<b>Constant</b>	SYNC_PROFILE_NOT_FOUND
<b>SAP Sybase Error Number</b>	2895
<b>SQL State</b>	42W75
<b>SQL Code</b>	-1217L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the synchronization profile.
<b>Probable Cause</b>	You tried to access a synchronization profile that the database could not find.

## 1218 - 1427

## Messages 1218 through 1237

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1218</b>	<b>"The materialized view cannot be changed to immediate because it does not have a unique index on non-aggregate, non-nullable columns"</b>
<b>Constant</b>	UPDATABLE_MATVIEW_NON_AGGR_INDEX
<b>SAP Sybase Error Number</b>	2896
<b>SQL State</b>	42WC7
<b>SQL Code</b>	-1218L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to change the refresh type to immediate for a materialized view which does not have a unique index on non-aggregate non-nullable columns. Create a unique index on the materialized view before changing the refresh type.

<b>Error 1219</b>	<b>"Maintenance of dependent immediate materialized view(s) failed"</b>
<b>Constant</b>	MAINTENANCE_OF_IMV_FAILED
<b>SAP Sybase Error Number</b>	2897
<b>SQL State</b>	42WC8
<b>SQL Code</b>	-1219L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Maintenance of immediate materialized view(s) dependent on the base table failed.

<b>Error 1220</b>	"User cannot be dropped because external logins exist for this user."
<b>Constant</b>	USER_HAS_EXTERNLOGINS
<b>SAP Sybase Error Number</b>	2898
<b>SQL State</b>	WO028
<b>SQL Code</b>	-1220L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Probable Cause</b>	The user cannot be dropped while an external login for the user still exists.
<b>Error 1221</b>	"Duplicate options not allowed in the CREATE DATABASE statement"
<b>Constant</b>	DUPLICATE_CREATE_DB_OPTION
<b>SAP Sybase Error Number</b>	2899
<b>SQL State</b>	42U08
<b>SQL Code</b>	-1221L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Probable Cause</b>	You have specified one of the options more than once when executing the CREATE DATABASE statement.
<b>Error 1222</b>	"Multiplex Server '%1' not found"
<b>Constant</b>	IQ_MULTIPLEX_SERVER_NOT_FOUND
<b>SAP Sybase Error Number</b>	2900
<b>SQL State</b>	WW110
<b>SQL Code</b>	-1222L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1222</b>	<b>"Multiplex Server '%1' not found"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of Multiplex Server.
<b>Probable Cause</b>	Multiplex Server with this name does not exist.
<b>Error 1223</b>	<b>"Synchronization profile '%1' already exists"</b>
<b>Constant</b>	SYNC_PROFILE_ALREADY_EXISTS
<b>SAP Sybase Error Number</b>	2901
<b>SQL State</b>	42W76
<b>SQL Code</b>	-1223L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the synchronization profile.
<b>Probable Cause</b>	You tried to create a synchronization profile that already exists.
<b>Error 1224</b>	<b>"Synchronization profile '%1' has invalid parameter '%2'"</b>
<b>Constant</b>	SYNC_PROFILE_INVALID
<b>SAP Sybase Error Number</b>	2902
<b>SQL State</b>	42W77
<b>SQL Code</b>	-1224L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the synchronization profile that is invalid.
<b>Parameter 2</b>	Name of the parameter in the profile that has the problem.
<b>Probable Cause</b>	You tried to create or alter a synchronization profile using a string containing an invalid parameter setting.

<b>Error 1225</b>	<b>"Synchronization profiles are not supported for this database"</b>
<b>Constant</b>	SYNC_PROFILE_UPGRADE
<b>SAP Sybase Error Number</b>	2903
<b>SQL State</b>	42W78
<b>SQL Code</b>	-1225L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The current database does not have catalog support for synchronization profiles. To use this feature, upgrade your database to the most recent version.
<b>Error 1226</b>	<b>"Foreign key columns do not match the primary key or a uniqueness constraint in \"%1\No message"</b>
<b>Constant</b>	NO_MATCHING_INDEX
<b>SAP Sybase Error Number</b>	2904
<b>SQL State</b>	42R04
<b>SQL Code</b>	-1226L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the primary table.
<b>Probable Cause</b>	An attempt was made to create a foreign key, but the columns specified do not match the primary key or a uniqueness constraint for the referenced table.
<b>Error 1227</b>	<b>"Internal error. Contact SAP Sybase IQ support. %1."</b>
<b>Constant</b>	IQ_MPX_INTERNAL_ERROR
<b>SAP Sybase Error Number</b>	2905
<b>SQL State</b>	WI111

## Errors and Warnings

<b>Error 1227</b>	<b>"Internal error. Contact SAP Sybase IQ support. %1."</b>
<b>SQL Code</b>	-1227L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The error description.
<b>Probable Cause</b>	The multiplex DDL statement (CREATE/ALTER/DROP) failed with internal error due to specified reason.
<b>Error 1228</b>	<b>"Syntax error, cannot specify SAP Sybase IQ specific options (%1) when creating a table in a SQL Anywhere database"</b>
<b>Constant</b>	IQ_ONLY_SYNTAX_ERROR
<b>SAP Sybase Error Number</b>	2907
<b>SQL State</b>	42W72
<b>SQL Code</b>	-1228L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	SAP Sybase IQ option used.
<b>Probable Cause</b>	An attempt was made to use SAP Sybase IQ specific create table syntax when creating a table in a SQL Anywhere database.
<b>Error 1229</b>	<b>"Reorganize table is already being run on table \'%1\No message</b>
<b>Constant</b>	REORG_ALREADY_IN_PROGRESS
<b>SAP Sybase Error Number</b>	2908
<b>SQL State</b>	54W51
<b>SQL Code</b>	-1229L
<b>ODBC 2 State</b>	54000
<b>ODBC 3 State</b>	54000

<b>Error 1229</b>	"Reorganize table is already being run on table \'%1\No message
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the table.
<b>Probable Cause</b>	There is already a REORGANIZE TABLE statement being run on this table. Only one such statement can be executing on a table at any time.
<b>Error 1230</b>	<b>"Too many open cursors"</b>
<b>Constant</b>	TOO_MANY_CURSORS
<b>SAP Sybase Error Number</b>	2909
<b>SQL State</b>	54W12
<b>SQL Code</b>	-1230L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>17</i> on page 2
<b>Probable Cause</b>	You exceeded the number of cursors that can be open on a single UltraLite database. Check to ensure you are freeing statements when you are done with them.
<b>Error 1231</b>	<b>"Statement timed out: "%1!s!"</b>
<b>Constant</b>	STATEMENT_TIMEOUT
<b>SAP Sybase Error Number</b>	2910
<b>SQL State</b>	57W05
<b>SQL Code</b>	-1231L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Statement type
<b>Probable Cause</b>	The statement failed because it did not complete within the allotted or specified time.

## Errors and Warnings

<b>Error 1232</b>	<b>"Attempt to start a second snapshot in a transaction"</b>
<b>Constant</b>	SNAPSHOT_ALREADY_STARTED
<b>SAP Sybase Error Number</b>	2911
<b>SQL State</b>	42WC9
<b>SQL Code</b>	-1232L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A transaction tried to start a snapshot (for example, using the BEGIN SNAPSHOT statement) while another snapshot was already active.
<b>Error 1233</b>	<b>"The materialized view %1 cannot be changed to immediate because it does not have a unique index on non-nullable columns."</b>
<b>Constant</b>	IMMEDIATE_MV_NO_UNIQUE_INDEX
<b>SAP Sybase Error Number</b>	2912
<b>SQL State</b>	42WCA
<b>SQL Code</b>	-1233L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Name of the materialized view.
<b>Probable Cause</b>	You attempted to change the refresh type to immediate for a materialized view which does not have a unique index on non-nullable columns. Create a unique index on the materialized view before changing the refresh type.
<b>Error 1234</b>	<b>"Dbspace file with name or path "%1' already exists."</b>
<b>Constant</b>	IQ_DBSPACEFILE_UPDATE_ERROR
<b>SAP Sybase Error Number</b>	2913
<b>SQL State</b>	42W7A

<b>Error 1234</b>	"Dbspace file with name or path "%1' already exists."
<b>SQL Code</b>	-1234L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	Logical file name or physical path from CREATE/ALTER DBSPACE SQL statement.
<b>Probable Cause</b>	Error code to use for catalog update errors in SAP Sybase IQ code.
<b>Error 1235</b>	"Too many columns in SELECT list"
<b>Constant</b>	TOO_MANY_COLUMNS_IN_SELECT
<b>SAP Sybase Error Number</b>	2914
<b>SQL State</b>	54W13
<b>SQL Code</b>	-1235L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You executed a statement with too many expressions in the SELECT list. The number of expressions within a SELECT list is limited to 60000.
<b>Error 1236</b>	"Too many expressions in GROUP BY list"
<b>Constant</b>	TOO_MANY_COLUMNS_IN_GROUPBY
<b>SAP Sybase Error Number</b>	2915
<b>SQL State</b>	54W14
<b>SQL Code</b>	-1236L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

## Errors and Warnings

<b>Error 1236</b>	<b>"Too many expressions in GROUP BY list"</b>
<b>Probable Cause</b>	You executed a statement with too many expressions in the GROUP BY list. The number of expressions within a GROUP BY list is limited to 60000.
<b>Error 1237</b>	<b>"Too many columns in procedure result set"</b>
<b>Constant</b>	TOO_MANY_COLUMNS_IN_PROC_RES
<b>SAP Sybase Error Number</b>	2916
<b>SQL State</b>	54W15
<b>SQL Code</b>	-1237L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You executed a statement with too many expressions in the GROUP BY list. The number of expressions within a GROUP BY list is limited to 60000. You executed a CREATE PROCEDURE or ALTER PROCEDURE statement. The resulting number of columns in the result set of the procedure would exceed the server's limit.

## Messages 1239 through 1260

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1239</b>	<b>"Partition name "%1' is not part of table "%2"</b>
<b>Constant</b>	UNKNOWN_PARTITION_NAME
<b>SAP Sybase Error Number</b>	2918
<b>SQL State</b>	WW113
<b>SQL Code</b>	-1239L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The partition name.

<b>Error 1239</b>	<b>"Partition name "%1' is not part of table "%2"</b>
<b>Parameter 2</b>	The table name.
<b>Probable Cause</b>	This partition name is not part or this table.
<b>Error 1240</b>	<b>"The provided stoplist is too long."</b>
<b>Constant</b>	TEXT_STOPLIST_TOO_LONG
<b>SAP Sybase Error Number</b>	2920
<b>SQL State</b>	WT018
<b>SQL Code</b>	-1240L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A text configuration stop list must be less than 8000 bytes.
<b>Error 1241</b>	<b>"Value-sensitive cursor used after a TRUNCATE"</b>
<b>Constant</b>	HOLD_CURSOR_AFTER_TRUNCATE
<b>SAP Sybase Error Number</b>	2924
<b>SQL State</b>	24001
<b>SQL Code</b>	-1241L
<b>ODBC 2 State</b>	24000
<b>ODBC 3 State</b>	24000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to use a value-sensitive cursor opened WITH HOLD after a TRUNCATE or after a COMMIT removed all rows from a temporary table declared as ON COMMIT DELETE ROWS.
<b>Error 1242</b>	<b>"Parameter ("%1') is already in the configuration specification of the specified Multiplex Server"</b>
<b>Constant</b>	IQ_MULTIPLEX_ALTERTOSAMECONFIG
<b>SAP Sybase Error Number</b>	2925

## Errors and Warnings

<b>Error 1242</b>	<b>"Parameter ("%1") is already in the configuration specification of the specified Multiplex Server"</b>
<b>SQL State</b>	WW117
<b>SQL Code</b>	-1242L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Current configuration of a Multiplex Server.
<b>Probable Cause</b>	The ALTER MULTIPLEX SERVER statement tried to alter configuration parameters with values that are the same as the current values.
<b>Error 1243</b>	<b>"An attempt to encrypt database "%1" failed"</b>
<b>Constant</b>	ENCRYPT_DATABASE_FAILED
<b>SAP Sybase Error Number</b>	2926
<b>SQL State</b>	WW118
<b>SQL Code</b>	-1243L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the database that could not be encrypted.
<b>Probable Cause</b>	Your attempt to encrypt a database file failed.
<b>Error 1244</b>	<b>"An attempt to decrypt database "%1" failed"</b>
<b>Constant</b>	DECRYPT_DATABASE_FAILED
<b>SAP Sybase Error Number</b>	2927
<b>SQL State</b>	WW119
<b>SQL Code</b>	-1244L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1244</b>	<b>"An attempt to decrypt database '%1' failed"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the database that could not be decrypted.
<b>Probable Cause</b>	Your attempt to decrypt a database file failed.
<b>Error 1245</b>	<b>"Partition name '%1' already used"</b>
<b>Constant</b>	CANNOT_USE_PARTITION_NAME
<b>SAP Sybase Error Number</b>	2928
<b>SQL State</b>	WW221
<b>SQL Code</b>	-1245L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The partition name.
<b>Probable Cause</b>	This partition name has already been used.
<b>Error 1246</b>	<b>"Partition '%1' is not adjacent to or before partition '%2'"</b>
<b>Constant</b>	PARTITIONS_NOT_ADJACENT
<b>SAP Sybase Error Number</b>	2929
<b>SQL State</b>	WW222
<b>SQL Code</b>	-1246L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The partition name.
<b>Parameter 2</b>	The partition name.
<b>Probable Cause</b>	These partitions are not adjacent - they cannot be merged.

## Errors and Warnings

<b>Error 1249</b>	<b>"Logical file "%1' is not part of dbspace "%2"</b>
<b>Constant</b>	UNKNOWN_LOGICALFILE_NAME
<b>SAP Sybase Error Number</b>	2932
<b>SQL State</b>	WW224
<b>SQL Code</b>	-1249L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The logical file name.
<b>Parameter 2</b>	The dbspace name.
<b>Probable Cause</b>	This logical file is not part of this dbspace.

<b>Error 1250</b>	<b>"Table '%1' is not a partitioned table"</b>
<b>Constant</b>	TABLE_NOT_PARTITIONED
<b>SAP Sybase Error Number</b>	2933
<b>SQL State</b>	WW225
<b>SQL Code</b>	-1250L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The table name.
<b>Probable Cause</b>	This table is not partitioned.

<b>Error 1251</b>	<b>"Table '%1' is already partitioned or subpartitioned"</b>
<b>Constant</b>	TABLE_PARTITIONED
<b>SAP Sybase Error Number</b>	2934
<b>SQL State</b>	WW226
<b>SQL Code</b>	-1251L

<b>Error 1251</b>	<b>"Table "%1' is already partitioned or subpartitioned"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The table name.
<b>Probable Cause</b>	This table is already partitioned or the table is incorrectly partitioned for this command. If a table is range partitioned, a user can "partition by hash" to create a hash-range partitioned table but if a table is partitioned by hash, it is incorrect to "partition by range".
<b>Error 1252</b>	<b>"Dbspace '%1' is the incorrect type"</b>
<b>Constant</b>	WRONG_DBSPACE_TYPE
<b>SAP Sybase Error Number</b>	2935
<b>SQL State</b>	WW227
<b>SQL Code</b>	-1252L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The dbspace name.
<b>Probable Cause</b>	Tried to put data into the incorrect dbspace (for example, putting a primary key into the wrong store).
<b>Error 1253</b>	<b>"The text index %1 needs to be refreshed"</b>
<b>Constant</b>	TEXT_MATCHING_INDEX_NOT_REFRESHED
<b>SAP Sybase Error Number</b>	2936
<b>SQL State</b>	WT019
<b>SQL Code</b>	-1253L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

## Errors and Warnings

<b>Error 1253</b>	<b>"The text index %1 needs to be refreshed"</b>
<b>Parameter 1</b>	The name of the text index that needs to be refreshed.
<b>Probable Cause</b>	There is a text index that matches the query, but it needs to be refreshed before it is used.
<b>Error 1254</b>	<b>"MERGE statement for table '%1' failed because of a RAISERROR specification in the statement"</b>
<b>Constant</b>	MERGE_USER_SPECIFIED_ERROR
<b>SAP Sybase Error Number</b>	2937
<b>SQL State</b>	23510
<b>SQL Code</b>	-1254L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the table being merged into
<b>Probable Cause</b>	You have attempted to execute a MERGE statement that contains the RAISERROR clause in one or more merge operation branches and one of the input rows satisfies the conditions for one of these branches.
<b>Error 1255</b>	<b>"Cannot merge partition '%1' into '%2' for column '%3'"</b>
<b>Constant</b>	CANNOT_MERGE_COLUMN_PARTITION
<b>SAP Sybase Error Number</b>	2938
<b>SQL State</b>	WW228
<b>SQL Code</b>	-1255L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	merge partition.
<b>Parameter 2</b>	merge to partition.
<b>Parameter 3</b>	column name.

<b>Error 1255</b>	<b>"Cannot merge partition "%1' into "%2' for column '%3'"</b>
<b>Probable Cause</b>	These column partitions cannot be merged.
<b>Error 1256</b>	<b>"Event of %1 type already exists"</b>
<b>Constant</b>	IQ_EVENT_TYPE_ALREADY_EXISTS
<b>SAP Sybase Error Number</b>	2939
<b>SQL State</b>	42WD0
<b>SQL Code</b>	-1256L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Event type
<b>Probable Cause</b>	An attempt was made to define a new event of the type that already exists.
<b>Error 1257</b>	<b>"Multiple event conditions cannot be specified with this event type"</b>
<b>Constant</b>	IQ_EVENT_MULTIPLE_CONDITIONS
<b>SAP Sybase Error Number</b>	2940
<b>SQL State</b>	42WD1
<b>SQL Code</b>	-1257L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	An attempt was made to specify more than one condition for an event type.
<b>Error 1258</b>	<b>"&lt;' or '&lt;=' operator can only be used in the event condition with this event type"</b>
<b>Constant</b>	IQ_EVENT_WRONG_OPERATOR
<b>SAP Sybase Error Number</b>	2941

## Errors and Warnings

<b>Error 1258</b>	<b>"&lt;' or '&lt;=' operator can only be used in the event condition with this event type"</b>
<b>SQL State</b>	42WD2
<b>SQL Code</b>	-1258L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Event of this type can be defined with a condition having < or <= operator only.

<b>Error 1259</b>	<b>"Hash error: %1"</b>
<b>Constant</b>	HASH_ERROR
<b>SAP Sybase Error Number</b>	2942
<b>SQL State</b>	08W92
<b>SQL Code</b>	-1259L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	Description of the error that occurred.
<b>Probable Cause</b>	An error occurred during hashing.

<b>Error 1260</b>	<b>"This server is not licensed to support the "%1' feature"</b>
<b>Constant</b>	FEATURE_NOT_LICENSED
<b>SAP Sybase Error Number</b>	2944
<b>SQL State</b>	0A002
<b>SQL Code</b>	-1260L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

<b>Error 1260</b>	<b>"This server is not licensed to support the "%1' feature"</b>
<b>Parameter 1</b>	The unlicensed feature.
<b>Probable Cause</b>	You attempted to carry out an operation or use a feature that is not licensed in this edition of SQL Anywhere.

## Messages 1261 through 1280

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1261</b>	<b>"This server is not licensed to support '%1' connections"</b>
<b>Constant</b>	CONNECTION_PROTOCOL_NOT_LICENSED
<b>SAP Sybase Error Number</b>	2945
<b>SQL State</b>	0A003
<b>SQL Code</b>	-1261L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The unlicensed connection type.
<b>Probable Cause</b>	You attempted to use a connection protocol or API that is not licensed in this edition of SQL Anywhere.

<b>Error 1262</b>	<b>"This edition of SQL Anywhere is not available on this platform"</b>
<b>Constant</b>	PLATFORM_NOT_LICENSED
<b>SAP Sybase Error Number</b>	2946
<b>SQL State</b>	0A004
<b>SQL Code</b>	-1262L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

## Errors and Warnings

<b>Error 1262</b>	<b>"This edition of SQL Anywhere is not available on this platform"</b>
<b>Probable Cause</b>	This edition of SQL Anywhere is not available on this platform. You must use a different license key to use SQL Anywhere on this platform.
<b>Error 1263</b>	<b>"Event notification queue "%1' not found"</b>
<b>Constant</b>	EVENT_NOTIFICATION_QUEUE_NOT_FOUND
<b>SAP Sybase Error Number</b>	2950
<b>SQL State</b>	WE014
<b>SQL Code</b>	-1263L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The name of the event notification queue
<b>Probable Cause</b>	The named event notification queue was not found. The operation failed.
<b>Error 1264</b>	<b>"Event object name "%1' is not valid"</b>
<b>Constant</b>	INVALID_EVENT_OBJECT_NAME
<b>SAP Sybase Error Number</b>	2951
<b>SQL State</b>	WE015
<b>SQL Code</b>	-1264L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the event object
<b>Probable Cause</b>	The given name is not valid for an event object (notification queue or user event). Names are limited in length to 32 characters (bytes), and cannot contain certain characters such as '*' or '@'.

<b>Error 1265</b>	<b>"Event object named '%1' already exists"</b>
<b>Constant</b>	EVENT_OBJECT_ALREADY_EXISTS
<b>SAP Sybase Error Number</b>	2952
<b>SQL State</b>	WE016
<b>SQL Code</b>	-1265L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the event object
<b>Probable Cause</b>	An event object (notification queue or user event) with the given name already exists.
<b>Error 1266</b>	<b>"No notification within timeout on queue '%1'"</b>
<b>Constant</b>	EVENT_NOTIFICATION_QUEUE_TIMEOUT
<b>SAP Sybase Error Number</b>	2953
<b>SQL State</b>	WE017
<b>SQL Code</b>	-1266L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the event notification queue
<b>Probable Cause</b>	The pending get-notification operation has timed out. No notification arrived before the given timeout elapsed.
<b>Error 1267</b>	<b>"Event parameter '%1' not found"</b>
<b>Constant</b>	EVENT_PARAMETER_NOT_FOUND
<b>SAP Sybase Error Number</b>	2954
<b>SQL State</b>	WE018
<b>SQL Code</b>	-1267L

## Errors and Warnings

<b>Error 1267</b>	<b>"Event parameter '%1' not found"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The name of the event parameter
<b>Probable Cause</b>	The named event parameter was not found in the event notification.
<b>Error 1268</b>	<b>"The materialized view cannot be changed to immediate because its definition contains an illegal construct."</b>
<b>Constant</b>	UPDATABLE_MATVIEW_ERR
<b>SAP Sybase Error Number</b>	2955
<b>SQL State</b>	42WCB
<b>SQL Code</b>	-1268L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You attempted to change the refresh type to immediate for a materialized view whose definition contains an illegal construct.
<b>Error 1269</b>	<b>"Service statement definition is invalid or unsupported"</b>
<b>Constant</b>	SERVICE_STATEMENT_INVALID
<b>SAP Sybase Error Number</b>	2956
<b>SQL State</b>	42WCC
<b>SQL Code</b>	-1269L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Either the statement provided is invalid or it is unsupported within the context of a service.

<b>Error 1270</b>	<b>"Must own table "%1' to make an immediate view reference it"</b>
<b>Constant</b>	NO_PERMS_FOR_IMV
<b>SAP Sybase Error Number</b>	2957
<b>SQL State</b>	42WD3
<b>SQL Code</b>	-1270L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the table
<b>Probable Cause</b>	You have attempted to change the refresh type of a materialized view to immediate and the view references a table that is not owned by you. To perform this operation, you must either own all the tables referenced by the materialized view or have DBA privileges.
<b>Error 1271</b>	<b>"Synchronization download failed to complete"</b>
<b>Constant</b>	INCOMPLETE_SYNCHRONIZATION
<b>SAP Sybase Error Number</b>	2958
<b>SQL State</b>	0AW23
<b>SQL Code</b>	-1271L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to synchronize an UltraLite database. During the synchronization session, an incomplete download stream was received from the consolidated database. The reason for the upload failure can be found in the synchronization log file.
<b>Error 1272</b>	<b>"Synchronization is already in progress"</b>
<b>Constant</b>	SYNCHRONIZATION_IN_PROGRESS
<b>SAP Sybase Error Number</b>	2959

## Errors and Warnings

<b>Error 1272</b>	<b>"Synchronization is already in progress"</b>
<b>SQL State</b>	0AW24
<b>SQL Code</b>	-1272L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to synchronize an UltraLite database but this database is being synchronized on another thread.
<b>Error 1273</b>	<b>"Table '%1' has no columns"</b>
<b>Constant</b>	TABLE_HAS_NO_COLUMNS
<b>SAP Sybase Error Number</b>	2960
<b>SQL State</b>	0EW00
<b>SQL Code</b>	-1273L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the table.
<b>Probable Cause</b>	You attempted to create a table without columns.
<b>Error 1274</b>	<b>"Index '%1' has no columns"</b>
<b>Constant</b>	INDEX_HAS_NO_COLUMNS
<b>SAP Sybase Error Number</b>	2961
<b>SQL State</b>	0EW01
<b>SQL Code</b>	-1274L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the index.

<b>Error 1274</b>	<b>"Index "%1' has no columns"</b>
<b>Probable Cause</b>	You attempted to create an index without columns.
<b>Error 1275</b>	<b>"Invalid domain "%1"</b>
<b>Constant</b>	INVALID_DOMAIN
<b>SAP Sybase Error Number</b>	2962
<b>SQL State</b>	54W52
<b>SQL Code</b>	-1275L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The invalid domain specification.
<b>Probable Cause</b>	You attempted to create an invalid domain. The size/scale/precision is invalid.
<b>Error 1276</b>	<b>"Configuration cannot not be modified while in use"</b>
<b>Constant</b>	CONFIG_IN_USE
<b>SAP Sybase Error Number</b>	2963
<b>SQL State</b>	55W34
<b>SQL Code</b>	-1276L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to modify a configuration object that is in use by an open connection.
<b>Error 1277</b>	<b>"Parameter "%1' cannot be null"</b>
<b>Constant</b>	PARAMETER_CANNOT_BE_NULL
<b>SAP Sybase Error Number</b>	2964
<b>SQL State</b>	WW229

## Errors and Warnings

<b>Error 1277</b>	"Parameter "%1' cannot be null"
<b>SQL Code</b>	-1277L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the parameter.
<b>Probable Cause</b>	The specified parameter cannot be null.

<b>Error 1278</b>	"Operation is not allowed"
<b>Constant</b>	ULTRALITEJ_OPERATION_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	2965
<b>SQL State</b>	WW230
<b>SQL Code</b>	-1278L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The requested operation is not allowed while schema is being modified.

<b>Error 1279</b>	"Operation '%1' failed for reason: '%2'"
<b>Constant</b>	ULTRALITEJ_OPERATION_FAILED
<b>SAP Sybase Error Number</b>	2966
<b>SQL State</b>	WW231
<b>SQL Code</b>	-1279L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the operation.
<b>Parameter 2</b>	The cause of the failure.

<b>Error 1279</b>	<b>"Operation '%1' failed for reason: '%2'"</b>
<b>Probable Cause</b>	The requested operation failed.
<b>Error 1280</b>	<b>"Underflow when converting '%1'"</b>
<b>Constant</b>	UNDERFLOW
<b>SAP Sybase Error Number</b>	2967
<b>SQL State</b>	WW232
<b>SQL Code</b>	-1280L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The type being converted.
<b>Probable Cause</b>	An underflow occurred when converting the specified type. The source type may be too small (for example zero length binary) or value may be too small to be represented by the destination type.

## Messages 1281 through 1301

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1281</b>	<b>"Another connection has the row in '%1' locked"</b>
<b>Constant</b>	ROW_LOCKED
<b>SAP Sybase Error Number</b>	2968
<b>SQL State</b>	42W80
<b>SQL Code</b>	-1281L
<b>ODBC 2 State</b>	40001
<b>ODBC 3 State</b>	40001
<b>Severity Code</b>	<i>21</i> on page 2
<b>Parameter 1</b>	Table that generates the error.

## Errors and Warnings

<b>Error 1281</b>	<b>"Another connection has the row in '%1' locked"</b>
<b>Probable Cause</b>	You attempted modify or delete a row that is locked by another connection. The row will be unlocked once that connection commits or rolls back.
<b>Error 1283</b>	<b>"A CONTAINS query is not allowed on the view or derived table '%1'."</b>
<b>Constant</b>	TEXT_INVALID_VIEW_FOR_CONTAINS
<b>SAP Sybase Error Number</b>	2970
<b>SQL State</b>	WT020
<b>SQL Code</b>	-1283L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the view or derived table that cannot be queried with CONTAINS.
<b>Probable Cause</b>	A view or derived table can only be queried using CONTAINS if it does not use TOP, FIRST, DISTINCT, GROUP BY, or FOR XML. In addition, the list of columns to search must all come from a single base table in the FROM clause of the view. They cannot come from multiple tables, or from another view or derived table in the FROM clause.
<b>Error 1284</b>	<b>"Invalid partition key specification: must use '%1'."</b>
<b>Constant</b>	CANNOT_CHANGE_PARTITION_KEY
<b>SAP Sybase Error Number</b>	2971
<b>SQL State</b>	WW233
<b>SQL Code</b>	-1284L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The partition key column name.

<b>Error 1284</b>	<b>"Invalid partition key specification: must use "%1". "</b>
<b>Probable Cause</b>	Partition key cannot be changed for ALTER TABLE ADD PARTITION. It must specify the same partition key column as the CREATE TABLE did.
<b>Error 1285</b>	<b>"%1 -- Transaction rolled back"</b>
<b>Constant</b>	IQ_TRANSACTION_ROLLBACK
<b>SAP Sybase Error Number</b>	2973
<b>SQL State</b>	40W09
<b>SQL Code</b>	-1285L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Error because of which the transaction rolled back.
<b>Probable Cause</b>	This transaction has been rolled back because the server encountered an error during a critical operation.
<b>Error 1286</b>	<b>"Immediate materialized view definition cannot contain a SUM function over a nullable expression."</b>
<b>Constant</b>	UPDATABLE_MATVIEW_SUM_NULL_EXPR
<b>SAP Sybase Error Number</b>	2974
<b>SQL State</b>	42WCD
<b>SQL Code</b>	-1286L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You attempted to change the refresh type to immediate for a materialized view whose definition contains a SUM function over a nullable expression.

## Errors and Warnings

<b>Error 1287</b>	<b>"Operation not allowed on global temporary table %1 as it is in use. Reconnect and try again."</b>
<b>Constant</b>	IQ_GTT_ALTER_DROP_NOTALLOWED
<b>SAP Sybase Error Number</b>	2975
<b>SQL State</b>	55W35
<b>SQL Code</b>	-1287L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the table.
<b>Probable Cause</b>	A global temporary table cannot be modified if it is in use. The user must reconnect and re-execute the statement.
<b>Error 1288</b>	<b>"'%1' statement is not allowed on a mirrored database"</b>
<b>Constant</b>	STMT_NOT_ALLOWED_WITH_MIRRORING
<b>SAP Sybase Error Number</b>	2976
<b>SQL State</b>	WW120
<b>SQL Code</b>	-1288L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Statement that generates the error.
<b>Probable Cause</b>	You attempted to execute a statement that is not allowed when using a mirrored database.
<b>Error 1289</b>	<b>"LOAD TABLE option '%1' not allowed with FORMAT %2"</b>
<b>Constant</b>	INVALID_LOAD_TABLE_OPTION
<b>SAP Sybase Error Number</b>	2977
<b>SQL State</b>	WL016
<b>SQL Code</b>	-1289L

<b>Error 1289</b>	<b>"LOAD TABLE option "%1' not allowed with FORMAT %2"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the option.
<b>Parameter 2</b>	The load table format.
<b>Probable Cause</b>	The specified LOAD TABLE option is not meaningful for the LOAD TABLE FORMAT.
<b>Error 1290</b>	<b>"FOR UPDATE or FOR READ ONLY clause must be specified on PREPARE (not on DECLARE CURSOR)"</b>
<b>Constant</b>	CURSOR_UPDATABILITY_CHANGED
<b>SAP Sybase Error Number</b>	2978
<b>SQL State</b>	42WD4
<b>SQL Code</b>	-1290L
<b>ODBC 2 State</b>	S1009
<b>ODBC 3 State</b>	HY092
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You specified the FOR UPDATE or FOR READ ONLY clause on a DECLARE CURSOR statement. The FOR UPDATE or FOR READ ONLY clause must be specified on the PREPARE statement and not the DECLARE CURSOR statement.
<b>Error 1291</b>	<b>"Column '%1' Partition "%2' may not be assigned to a dbspace because partitioning is not supported for datatype '%3'."</b>
<b>Constant</b>	INVALID_COL_PARTITION_PLACEMENT
<b>SAP Sybase Error Number</b>	2979
<b>SQL State</b>	WW235
<b>SQL Code</b>	-1291L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1291</b>	<b>"Column '%1' Partition '%2' may not be assigned to a dbspace because partitioning is not supported for datatype '%3'."</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The column name
<b>Parameter 2</b>	The partition name
<b>Parameter 3</b>	The data type
<b>Probable Cause</b>	The column storage for certain datatypes (such as the BIT datatype) cannot be assigned to a dbspace.
<b>Error 1292</b>	<b>"Column '%1' may not be assigned to a dbspace because partitioning is not supported for datatype '%2'."</b>
<b>Constant</b>	INVALID_COL_PLACEMENT
<b>SAP Sybase Error Number</b>	2980
<b>SQL State</b>	WW236
<b>SQL Code</b>	-1292L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The column name
<b>Parameter 2</b>	The data type
<b>Probable Cause</b>	The column storage for certain datatypes (such as the BIT datatype) cannot be assigned to a dbspace.
<b>Error 1293</b>	<b>"Partition key of '%1' is unsupported."</b>
<b>Constant</b>	UNSUPPORTED_PARTITION_KEY
<b>SAP Sybase Error Number</b>	2981
<b>SQL State</b>	WW237
<b>SQL Code</b>	-1293L
<b>ODBC 2 State</b>	ERROR

<b>Error 1293</b>	<b>"Partition key of '%1' is unsupported."</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The column datatype
<b>Probable Cause</b>	Partitioning over the specified datatype is not supported.

<b>Error 1294</b>	<b>"Parameter (%1) length has exceeded its limit (%2)."</b>
<b>Constant</b>	IQ_PARAM_LENGTH_EXCEED_LIMIT
<b>SAP Sybase Error Number</b>	2983
<b>SQL State</b>	WW122
<b>SQL Code</b>	-1294L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Parameter name.
<b>Parameter 2</b>	Allowed Maximum length.
<b>Probable Cause</b>	Given parameter's length has exceeded the specified limit.

<b>Error 1295</b>	<b>"Database path must be absolute."</b>
<b>Constant</b>	IQ_MPX_ABS_DBPATH
<b>SAP Sybase Error Number</b>	2984
<b>SQL State</b>	WW123
<b>SQL Code</b>	-1295L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Specified Database path must be absolute.

## Errors and Warnings

<b>Error 1296</b>	<b>"(%1) is not unique."</b>
<b>Constant</b>	IQ_PARAM_VALUE_NOT_UNIQUE
<b>SAP Sybase Error Number</b>	2985
<b>SQL State</b>	WW124
<b>SQL Code</b>	-1296L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Parameter name.
<b>Probable Cause</b>	Specified value for a given parameter already exist in the multiplex configuration.
<b>Error 1297</b>	<b>"No of servers in multiplex setup has reached to the maximum limit."</b>
<b>Constant</b>	IQ_MULTIPLEX_SERVER_LIMIT_EXCEEDED
<b>SAP Sybase Error Number</b>	2986
<b>SQL State</b>	WW125
<b>SQL Code</b>	-1297L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	No of servers in multiplex setup has reached to the maximum limit. User cannot add any more secondary servers.
<b>Error 1298</b>	<b>"Cannot alter multiplex failover node and other multiplex server properties in the same statement."</b>
<b>Constant</b>	IQ_INVALID_CONFIG_FAILOVER_COMBINATION
<b>SAP Sybase Error Number</b>	2987
<b>SQL State</b>	WW126
<b>SQL Code</b>	-1298L

<b>Error 1298</b>	<b>"Cannot alter multiplex failover node and other multiplex server properties in the same statement."</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Users are not allowed to alter the multiplex failover node status and other multiplex server properties in the same statement.
<b>Error 1299</b>	<b>"Drop multiplex server is allowed only in a multiplex setup."</b>
<b>Constant</b>	IQ_DROP_MPX_ALLOWED_ONLY_IN_MPX
<b>SAP Sybase Error Number</b>	2988
<b>SQL State</b>	WW127
<b>SQL Code</b>	-1299L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Drop multiplex server is allowed only in a multiplex setup.
<b>Error 1300</b>	<b>"Cannot add first multiplex server with excluded status."</b>
<b>Constant</b>	IQ_FIRST_SECONDARY_SERVER_CANNOT_BE_EXCLUDED
<b>SAP Sybase Error Number</b>	2989
<b>SQL State</b>	WW128
<b>SQL Code</b>	-1300L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Users are not allowed to add the first multiplex server with status excluded.

<b>Error 1301</b>	" <b>Cannot create multiplex server with role coordinator.</b> "
<b>Constant</b>	IQ_CANNOT_CREATE_MPX_COORDINATOR
<b>SAP Sybase Error Number</b>	2990
<b>SQL State</b>	WW129
<b>SQL Code</b>	-1301L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Users are not allowed to create a multiplex server with role as coordinator.

## Messages 1302 through 1321

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1302</b>	" <b>Host Port specification (%1) is invalid.</b> "
<b>Constant</b>	IQ_INVALID_HOSTNAME
<b>SAP Sybase Error Number</b>	2982
<b>SQL State</b>	WW121
<b>SQL Code</b>	-1302L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Host Port Specification.
<b>Probable Cause</b>	Host port specification is invalid.

<b>Error 1303</b>	" <b>Too many MESSAGE...FOR CONNECTION messages</b> "
<b>Constant</b>	CONNECTION_MESSAGE_QUEUE_FULL
<b>SAP Sybase Error Number</b>	2991
<b>SQL State</b>	54W16

<b>Error 1303</b>	<b>"Too many MESSAGE...FOR CONNECTION messages"</b>
<b>SQL Code</b>	-1303L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	54000
<b>Severity Code</b>	<i>19</i> on page 2
<b>Probable Cause</b>	You executed a MESSAGE...FOR CONNECTION statement and the maximum number of messages for the connection have already been queued.
<b>Error 1304</b>	<b>"Could not create a new text index for this table with the same settings as \'%"1\No message</b>
<b>Constant</b>	TEXT_INDEX_SAME_SETTING_IDX
<b>SAP Sybase Error Number</b>	2992
<b>SQL State</b>	WT021
<b>SQL Code</b>	-1304L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the other text index with the same settings.
<b>Probable Cause</b>	Two text indexes with the same column list and configuration settings cannot be created for a table.
<b>Error 1305</b>	<b>"MobiLink communication error -- code: %1, parameter: %2, system code: %3"</b>
<b>Constant</b>	MOBILINK_COMMUNICATIONS_ERROR
<b>SAP Sybase Error Number</b>	2993
<b>SQL State</b>	0AWD5
<b>SQL Code</b>	-1305L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2

## Errors and Warnings

<b>Error 1305</b>	<b>"MobiLink communication error -- code: %1, parameter: %2, system code: %3"</b>
<b>Parameter 1</b>	The MobiLink communication error code.
<b>Parameter 2</b>	The parameter to the MobiLink communication error if one exists.
<b>Parameter 3</b>	The system error code.
<b>Probable Cause</b>	An error was encountered while communicating with a MobiLink server.
<b>Error 1306</b>	<b>"IN DBSPACE clause cannot be used for column '%1' since table '%2' is a partitioned table."</b>
<b>Constant</b>	IN_DBSPACE_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	2994
<b>SQL State</b>	WW238
<b>SQL Code</b>	-1306L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The column name
<b>Parameter 2</b>	The table name
<b>Probable Cause</b>	Entire column cannot be assigned to a dbspace using the IN DBSPACE clause, if the table is a partitioned table.
<b>Error 1307</b>	<b>"Database mirroring options are not supported for this database"</b>
<b>Constant</b>	MIRRORING_OPTIONS_NOT_SUPPORTED
<b>SAP Sybase Error Number</b>	2995
<b>SQL State</b>	WW130
<b>SQL Code</b>	-1307L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1307</b>	<b>"Database mirroring options are not supported for this database"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The current database does not have catalog support for database mirroring servers and options. To use this feature, upgrade your database to the most recent version.
<b>Error 1308</b>	<b>"Mirror server \%" not found"</b>
<b>Constant</b>	MIRROR_SERVER_NOT_FOUND
<b>SAP Sybase Error Number</b>	2996
<b>SQL State</b>	WW131
<b>SQL Code</b>	-1308L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the mirror server.
<b>Probable Cause</b>	The named mirror server was not found in the database.
<b>Error 1309</b>	<b>"Mirror server \%" already exists"</b>
<b>Constant</b>	MIRROR_SERVER_ALREADY_EXISTS
<b>SAP Sybase Error Number</b>	2997
<b>SQL State</b>	WW132
<b>SQL Code</b>	-1309L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the mirror server.
<b>Probable Cause</b>	An attempt was made to create a mirror server that already exists in the database.

## Errors and Warnings

<b>Error 1310</b>	<b>"Mirror server \%" is referenced by another server"</b>
<b>Constant</b>	MIRROR_SERVER_IN_USE
<b>SAP Sybase Error Number</b>	2998
<b>SQL State</b>	WW133
<b>SQL Code</b>	-1310L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the mirror server.
<b>Probable Cause</b>	An attempt was made to drop a mirror server that is referenced by another mirror server in the database.
<b>Error 1311</b>	<b>"Principal mirror servers are already defined"</b>
<b>Constant</b>	MIRROR_PARTNERS_ALREADY_DEFINED
<b>SAP Sybase Error Number</b>	2999
<b>SQL State</b>	WW134
<b>SQL Code</b>	-1311L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	An attempt was made to create a mirror server without a parent server, but two principal mirror servers are already defined in the database.
<b>Error 1312</b>	<b>"Mirror server \%" is not a valid parent server"</b>
<b>Constant</b>	INVALID_MIRROR_PARENT
<b>SAP Sybase Error Number</b>	3000
<b>SQL State</b>	WW135
<b>SQL Code</b>	-1312L
<b>ODBC 2 State</b>	ERROR

<b>Error 1312</b>	<b>"Mirror server \\"%1\\" is not a valid parent server"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the mirror server.
<b>Probable Cause</b>	An attempt was made to define a parent for a mirror server that would result in a cycle.

<b>Error 1313</b>	<b>"Maximum string length exceeded"</b>
<b>Constant</b>	MAX_STRING_LENGTH_EXCEEDED
<b>SAP Sybase Error Number</b>	2969
<b>SQL State</b>	54W17
<b>SQL Code</b>	-1313L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	54000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	A string operation attempted to create a string longer than the maximum allowed by the server.

<b>Error 1314</b>	<b>"Cannot force failover when current server is marked as preferred"</b>
<b>Constant</b>	CANNOT_FORCE_FAILOVER_ON_PREFERRED
<b>SAP Sybase Error Number</b>	3001
<b>SQL State</b>	WW136
<b>SQL Code</b>	-1314L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	An attempt was made to execute ALTER DATABASE SET PARTNER FAILOVER but the current server is marked as preferred. Attempting to force a failover in this situation is not allowed.

## Errors and Warnings

<b>Error 1315</b>	<b>"Script file missing statement \"go\" delimiter on a separate line"</b>
<b>Constant</b>	SCRIPT_MISSING_DELIMITER
<b>SAP Sybase Error Number</b>	2931
<b>SQL State</b>	WW046
<b>SQL Code</b>	-1315L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	For UltraLite, all non-comment SQL statements in a script file (including the final one) must be followed by "go" on a line by itself. For strings, you can use "\ngo" to end a statement.
<b>Error 1316</b>	<b>"Unsupported load column specification used for a catalog store table."</b>
<b>Constant</b>	IQ_LOAD_TABLE_UNSUPPORTED_COLUMN_SPEC
<b>SAP Sybase Error Number</b>	2930
<b>SQL State</b>	0AW25
<b>SQL Code</b>	-1316L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	For catalog store tables, only some of the load column specifications (for example, filler) are permitted.
<b>Error 1317</b>	<b>"Multiplex server '%1' is shutting down due to a successful configuration change"</b>
<b>Constant</b>	MPX_CONFIG_CHANGES_SRV_SHUTDOWN
<b>SAP Sybase Error Number</b>	2919
<b>SQL State</b>	WW239

<b>Error 1317</b>	<b>"Multiplex server '%1' is shutting down due to a successful configuration change"</b>
<b>SQL Code</b>	-1317L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the multiplex server.
<b>Probable Cause</b>	Successful execution of certain statements to change multiplex configuration forces a server shutdown. You will get the above error if you issue such a command.
<b>Error 1318</b>	<b>"More articles are being dropped from publication '%1' than are defined"</b>
<b>Constant</b>	TOO_MANY_ARTICLES_DELETED
<b>SAP Sybase Error Number</b>	2890
<b>SQL State</b>	42W89
<b>SQL Code</b>	-1318L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the publication from which the article could not be dropped.
<b>Probable Cause</b>	The number of articles in a publication can never fall below one. Your ALTER PUBLICATION has more drop/delete article clauses than the current number of articles in the publication.
<b>Error 1319</b>	<b>"Synchronization schema changes and script versions are not supported for this database"</b>
<b>Constant</b>	SYNC_SCHEMA_UPGRADE
<b>SAP Sybase Error Number</b>	3002
<b>SQL State</b>	WW137

## Errors and Warnings

<b>Error 1319</b>	<b>"Synchronization schema changes and script versions are not supported for this database"</b>
<b>SQL Code</b>	-1319L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The current database does not have catalog support for synchronization schema changes and script versions. To use this feature, upgrade your database to the most recent version.
<b>Error 1320</b>	<b>"Error raised by user-defined function: %1"</b>
<b>Constant</b>	EMSG_UDF_RAISED_ERROR
<b>SAP Sybase Error Number</b>	2822
<b>SQL State</b>	QFA62
<b>SQL Code</b>	-1320L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Error message provided by UDF to accompany UDF SQLCODE.
<b>Probable Cause</b>	An error was raised by a user-defined function.
<b>Error 1321</b>	<b>"Table or view '%1' is not valid for use with this statement"</b>
<b>Constant</b>	INVALID_TABLE_TYPE
<b>SAP Sybase Error Number</b>	3004
<b>SQL State</b>	WW139
<b>SQL Code</b>	-1321L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of table

<b>Error 1321</b>	<b>"Table or view '%1' is not valid for use with this statement"</b>
<b>Probable Cause</b>	The named table or view cannot be used with this statement. For example, the statement may not allow temporary tables or views.

## Messages 1322 through 1341

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1322</b>	<b>"A synchronization schema change is already in progress"</b>
<b>Constant</b>	SYNC_SCHEMA_IN_PROGRESS
<b>SAP Sybase Error Number</b>	3005
<b>SQL State</b>	WW140
<b>SQL Code</b>	-1322L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A START SYNCHRONIZATION SCHEMA CHANGE statement is already in progress.

<b>Error 1323</b>	<b>"Subscription to publication '%1' for '%2' omitted from statement"</b>
<b>Constant</b>	SUBSCRIPTION OMITTED
<b>SAP Sybase Error Number</b>	3006
<b>SQL State</b>	WW141
<b>SQL Code</b>	-1323L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of publication
<b>Parameter 2</b>	Name of MobiLink user

## Errors and Warnings

<b>Error 1323</b>	<b>"Subscription to publication '%1' for '%2' omitted from statement"</b>
<b>Probable Cause</b>	A START SYNCHRONIZATION SCHEMA CHANGE statement lists a table that will be modified, but a subscription which refers to that table was omitted from the statement.
<b>Error 1324</b>	<b>"Connection is not allowed to have table locks when executing this statement"</b>
<b>Constant</b>	CONNECTION_HAS_LOCKS
<b>SAP Sybase Error Number</b>	3007
<b>SQL State</b>	WW142
<b>SQL Code</b>	-1324L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	An attempt was made to execute a statement by a connection that is holding table locks. Because the statement could release all locks, including those held before the statement started, the locks must be released before the statement can be executed.
<b>Error 1325</b>	<b>"Column subset for table '%1' in publication '%2' does not match that specified in publication '%3'"</b>
<b>Constant</b>	COLUMN_SUBSET_MISMATCH
<b>SAP Sybase Error Number</b>	3003
<b>SQL State</b>	WW138
<b>SQL Code</b>	-1325L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of table
<b>Parameter 2</b>	Name of first publication

<b>Error 1325</b>	<b>"Column subset for table '%1' in publication '%2' does not match that specified in publication '%3'"</b>
<b>Parameter 3</b>	Name of second publication
<b>Probable Cause</b>	The columns included for a table must be identical for all subscribed publications which reference the table.
<b>Error 1326</b>	<b>"Subscription '%1' not found"</b>
<b>Constant</b>	SUBSCRIPTION_NAME_NOT_FOUND
<b>SAP Sybase Error Number</b>	3008
<b>SQL State</b>	5RW40
<b>SQL Code</b>	-1326L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of subscription
<b>Probable Cause</b>	You attempted to ALTER, DROP, or otherwise reference a subscription that does not exist.
<b>Error 1327</b>	<b>"The materialized view cannot be changed to immediate because its SELECT list contains a SUM function over a nullable expression and it doesn't contain a COUNT function over the same expression"</b>
<b>Constant</b>	UPDATABLE_MATVIEW_COUNT_NULL_EXPR
<b>SAP Sybase Error Number</b>	3009
<b>SQL State</b>	42WCE
<b>SQL Code</b>	-1327L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2

## Errors and Warnings

<b>Error 1327</b>	<b>"The materialized view cannot be changed to immediate because its SELECT list contains a SUM function over a nullable expression and it doesn't contain a COUNT function over the same expression"</b>
<b>Probable Cause</b>	You attempted to change the refresh type to immediate for a materialized view whose definition contains a SUM function over a nullable expression but it doesn't contain COUNT function over the same expression.
<b>Error 1328</b>	<b>"Table "%1' must synchronize to be in publication "%2"</b>
<b>Constant</b>	TABLE_MUST_SYNCHRONIZE_IN_PUB
<b>SAP Sybase Error Number</b>	3010
<b>SQL State</b>	WW143
<b>SQL Code</b>	-1328L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of table
<b>Parameter 2</b>	Name of publication
<b>Probable Cause</b>	A publication cannot contain a table with a SYNCHRONIZE OFF constraint; all tables in a publication must synchronize. You attempted to add a table with a SYNCHRONIZE OFF constraint to a publication, or to alter a table to use SYNCHRONIZE OFF when the table is already in a publication.
<b>Error 1329</b>	<b>"This operation is only allowed within a synchronization schema change"</b>
<b>Constant</b>	REQUIRES_SYNC_SCHEMA_CHANGE
<b>SAP Sybase Error Number</b>	3011
<b>SQL State</b>	5RW41
<b>SQL Code</b>	-1329L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1329</b>	<b>"This operation is only allowed within a synchronization schema change"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted an operation that is only allowed within a synchronization schema change.
<b>Error 1330</b>	<b>"The function '%1' does not allow use of the '%2' clause"</b>
<b>Constant</b>	FUNCTION_DOES_NOT_ALLOW
<b>SAP Sybase Error Number</b>	2823
<b>SQL State</b>	42WE0
<b>SQL Code</b>	-1330L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the function.
<b>Parameter 2</b>	The SQL clause not allowed.
<b>Probable Cause</b>	You have attempted to use the specified SQL clause within the context of a function that does not permit such use. Note that the function may have been used directly in the query or indirectly within a named window.
<b>Error 1331</b>	<b>"The function '%1' requires the use of the '%2' clause"</b>
<b>Constant</b>	FUNCTIONQUIRES
<b>SAP Sybase Error Number</b>	2807
<b>SQL State</b>	42WE1
<b>SQL Code</b>	-1331L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the function.
<b>Parameter 2</b>	The SQL clause required.

## Errors and Warnings

<b>Error 1331</b>	<b>"The function '%1' requires the use of the "%2' clause"</b>
<b>Probable Cause</b>	You have attempted to invoke the specified function without the use of a mandatory SQL clause within the context of the function. Note that the function may have been used directly in the query or indirectly within a named window.
<b>Error 1332</b>	<b>"Feature "%1' is unknown or invalid"</b>
<b>Constant</b>	FEATURE_UNKNOWN_OR_INVALID
<b>SAP Sybase Error Number</b>	3012
<b>SQL State</b>	WW144
<b>SQL Code</b>	-1332L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Feature name
<b>Probable Cause</b>	You attempted to lock or unlock an unknown feature.
<b>Error 1333</b>	<b>"Feature '%1' was not locked by this connection"</b>
<b>Constant</b>	FEATURE_NOT_LOCKED
<b>SAP Sybase Error Number</b>	3013
<b>SQL State</b>	WW145
<b>SQL Code</b>	-1333L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Feature name
<b>Probable Cause</b>	You attempted to unlock a feature that was not previously locked by this connection.
<b>Error 1334</b>	<b>"Feature '%1' is locked by another connection"</b>
<b>Constant</b>	FEATURE_LOCKED

<b>Error 1334</b>	<b>"Feature '%1' is locked by another connection"</b>
<b>SAP Sybase Error Number</b>	3014
<b>SQL State</b>	WW146
<b>SQL Code</b>	-1334L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Feature name
<b>Probable Cause</b>	You attempted to use a feature that was previously locked by another connection.
<b>Error 1335</b>	<b>"Type '%1' does not support method calls (near '%2')."</b>
<b>Constant</b>	METHOD_ON_NON_EXT
<b>SAP Sybase Error Number</b>	3015
<b>SQL State</b>	42X00
<b>SQL Code</b>	-1335L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The name of the data type.
<b>Parameter 2</b>	The invalid expression.
<b>Probable Cause</b>	You attempted to invoke a method on a value of a data type that does not define any methods.
<b>Error 1336</b>	<b>"Type '%1' has no method named '%2' (near '%3')."</b>
<b>Constant</b>	METHOD_NOT_FOUND
<b>SAP Sybase Error Number</b>	3016
<b>SQL State</b>	42X01
<b>SQL Code</b>	-1336L

## Errors and Warnings

<b>Error 1336</b>	<b>"Type '%1' has no method named '%2' (near '%3')."</b>
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The name of the type with the unmatched method.
<b>Parameter 2</b>	Name of the method that could not be matched.
<b>Parameter 3</b>	The invalid expression.
<b>Probable Cause</b>	When attempting to match a method invocation, no method was found with the appropriate name. Check for spelling errors.
<b>Error 1337</b>	<b>"Method invocation '%1' does not match an overload (near '%2'). Available overloads are '%3'."</b>
<b>Constant</b>	METHOD_NO_OVERLOAD
<b>SAP Sybase Error Number</b>	3017
<b>SQL State</b>	42X02
<b>SQL Code</b>	-1337L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The method name and data types used in the method invocation.
<b>Parameter 2</b>	The invalid expression.
<b>Parameter 3</b>	The available method overloads.
<b>Probable Cause</b>	When attempting to match a method invocation, none of the defined overloads was found to match the provided argument types. You may need to use CAST to select the appropriate call.
<b>Error 1338</b>	<b>"Type '%1' is not instantiable (near '%2')"</b>
<b>Constant</b>	METHOD_NO_CONSTRUCTOR
<b>SAP Sybase Error Number</b>	3018
<b>SQL State</b>	42X03

<b>Error 1338</b>	<b>"Type '%1' is not instantiable (near '%2')"</b>
<b>SQL Code</b>	-1338L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The name of the type that is not instantiable.
<b>Parameter 2</b>	The invalid expression.
<b>Probable Cause</b>	A NEW expression was used for a data type that does not define any constructor methods.
<b>Error 1339</b>	<b>"Method '%1' cannot be called with %2 arguments (near '%3')"</b>
<b>Constant</b>	METHOD_NO_OVERLOAD_N_ARGS
<b>SAP Sybase Error Number</b>	3019
<b>SQL State</b>	42X04
<b>SQL Code</b>	-1339L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The name of the method.
<b>Parameter 2</b>	The number of arguments supplied.
<b>Parameter 3</b>	The invalid expression.
<b>Probable Cause</b>	No overload of the specified method can be called with the number of arguments provided.
<b>Error 1340</b>	<b>"Type '%1' cannot be instantiated with %2 arguments (near '%3')"</b>
<b>Constant</b>	METHOD_NO_CONSTRUCTOR_N_ARGS
<b>SAP Sybase Error Number</b>	3020
<b>SQL State</b>	42X05

## Errors and Warnings

<b>Error 1340</b>	<b>"Type '%1' cannot be instantiated with %2 arguments (near '%3)'"</b>
<b>SQL Code</b>	-1340L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The name of the type that cannot be instantiated.
<b>Parameter 2</b>	The number of arguments supplied.
<b>Parameter 3</b>	The invalid expression.
<b>Probable Cause</b>	A NEW expression was used for a data type that does not define any constructor methods.
<b>Error 1341</b>	<b>"The instantiation '%1' does not match an overload (near '%2'). Available overloads are '%3'."</b>
<b>Constant</b>	METHOD_NO_CONSTRUCTOR_OVERLOAD
<b>SAP Sybase Error Number</b>	3021
<b>SQL State</b>	42X06
<b>SQL Code</b>	-1341L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S02
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The type name and data types used in the new specification.
<b>Parameter 2</b>	The invalid expression.
<b>Parameter 3</b>	The available constructor overloads.
<b>Probable Cause</b>	When attempting to match a new specification, none of the defined constructor overloads was found to match the provided argument types. You may need to use CAST to select the appropriate call.

## Messages 1342 through 1363

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1342</b>	<b>"Data modifications are not allowed in a synchronization schema change"</b>
<b>Constant</b>	SYNC_SCHEMA_CHANGE_DISALLOWS_DML
<b>SAP Sybase Error Number</b>	3022
<b>SQL State</b>	5RW42
<b>SQL Code</b>	-1342L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted a data modification operation within a synchronization schema change.
<b>Error 1343</b>	<b>"Feature '%1' is locked because synchronization is in progress"</b>
<b>Constant</b>	FEATURE_LOCKED_SYNC
<b>SAP Sybase Error Number</b>	3023
<b>SQL State</b>	WW147
<b>SQL Code</b>	-1343L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Feature name
<b>Probable Cause</b>	You attempted to use a feature that was previously locked because a synchronization is in progress.
<b>Error 1344</b>	<b>"Rollback occurred due to blocking_others_timeout"</b>
<b>Constant</b>	BLOCKING_OTHERS_ROLLBACK

## Errors and Warnings

<b>Error 1344</b>	<b>"Rollback occurred due to blocking_others_timeout"</b>
<b>SAP Sybase Error Number</b>	3024
<b>SQL State</b>	WW148
<b>SQL Code</b>	-1344L
<b>ODBC 2 State</b>	40001
<b>ODBC 3 State</b>	40001
<b>Severity Code</b>	<i>13</i> on page 2
<b>Probable Cause</b>	This connection has been rolled back because another connection was blocked on this connection for longer than the blocking_others_timeout option setting. All requests on this connection will get this error until it is disconnected.
<b>Error 1347</b>	<b>"Use of authority '%1' is not supported on the current database"</b>
<b>Constant</b>	OLIN_AUTHORITIES_UNSUPPORTED
<b>SAP Sybase Error Number</b>	2776
<b>SQL State</b>	28W16
<b>SQL Code</b>	-1347L
<b>ODBC 2 State</b>	28000
<b>ODBC 3 State</b>	28000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The unsupported authority.
<b>Probable Cause</b>	The current database is an older database and does not have the capability to support given authority. You must upgrade your database to use this authority.
<b>Error 1348</b>	<b>"Mirror server name '%1' does not match current server name"</b>
<b>Constant</b>	INVALID_CHILD_SERVER_NAME
<b>SAP Sybase Error Number</b>	3027
<b>SQL State</b>	WW151

<b>Error 1348</b>	<b>"Mirror server name '%1' does not match current server name"</b>
<b>SQL Code</b>	-1348L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The server name
<b>Probable Cause</b>	The server name specified in a CREATE MIRROR SERVER statement must match the current server name when the statement is executed on a child server.
<b>Error 1349</b>	<b>"The parent of this mirror server is not currently connected"</b>
<b>Constant</b>	PARENT_NOT_CONNECTED
<b>SAP Sybase Error Number</b>	3028
<b>SQL State</b>	WW152
<b>SQL Code</b>	-1349L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The statement being executed requires a connection from this mirror server to its parent, but the parent is not currently connected.
<b>Error 1350</b>	<b>"The parent of this mirror server is not the primary server"</b>
<b>Constant</b>	PARENT_NOT_PRIMARY
<b>SAP Sybase Error Number</b>	3029
<b>SQL State</b>	WW153
<b>SQL Code</b>	-1350L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 1350</b>	<b>"The parent of this mirror server is not the primary server"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The statement being executed requires a connection from this mirror server to the primary server, but the parent is not the primary server. The connection string to this server's parent does not match the connection string for the primary server.
<b>Error 1351</b>	<b>"Mirror child server creation failed"</b>
<b>Constant</b>	CHILD_SERVER_CREATION_FAILED
<b>SAP Sybase Error Number</b>	3030
<b>SQL State</b>	WW154
<b>SQL Code</b>	-1351L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The creation of a child server on the primary server failed or was disallowed.
<b>Error 1352</b>	<b>"Mirror server with type "%1' is already defined"</b>
<b>Constant</b>	MIRROR_SERVER_TYPE_ALREADY_DEFINED
<b>SAP Sybase Error Number</b>	3031
<b>SQL State</b>	WW155
<b>SQL Code</b>	-1352L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The server type
<b>Probable Cause</b>	A CREATE MIRROR SERVER statement specified a server type that has already been defined.

<b>Error 1353</b>	<b>"Invalid operation "%2' on sequence "%1"</b>
<b>Constant</b>	INVALID_SEQUENCE_OPERATION
<b>SAP Sybase Error Number</b>	3033
<b>SQL State</b>	52W46
<b>SQL Code</b>	-1353L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the operation attempted.
<b>Parameter 2</b>	Name of the sequence.
<b>Probable Cause</b>	An invalid operation has been attempted on a sequence object. The only valid operations on a sequence are currval and nextval.

<b>Error 1354</b>	<b>"Sequence '%1' already exists"</b>
<b>Constant</b>	SEQUENCE_ALREADY_EXISTS
<b>SAP Sybase Error Number</b>	3034
<b>SQL State</b>	52W47
<b>SQL Code</b>	-1354L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the sequence.
<b>Probable Cause</b>	A sequence with the specified name already exists.

<b>Error 1355</b>	<b>"No more values available in sequence %1"</b>
<b>Constant</b>	SEQUENCE_EXHAUSTED
<b>SAP Sybase Error Number</b>	3035
<b>SQL State</b>	52W48
<b>SQL Code</b>	-1355L

## Errors and Warnings

<b>Error 1355</b>	<b>"No more values available in sequence %1"</b>
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the sequence.
<b>Probable Cause</b>	No more values can be supplied by the sequence; the next value to be supplied would be either larger than the maximum value, or smaller than the minimum value, and this sequence has been specified with NO CYCLE.
<b>Error 1356</b>	<b>"Definition for sequence "%1' is invalid"</b>
<b>Constant</b>	INVALID_SEQUENCE_DEFINITION
<b>SAP Sybase Error Number</b>	3036
<b>SQL State</b>	52W49
<b>SQL Code</b>	-1356L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the sequence.
<b>Probable Cause</b>	An invalid combination of modifiers has been used for the sequence. Make sure that the MAXVAL is greater than the MINVAL and that START WITH is between MINVAL and MAXVAL.
<b>Error 1357</b>	<b>"Multiple settings of same option specified for sequence "%1"</b>
<b>Constant</b>	DUPPLICATE_SEQUENCE_OPTION
<b>SAP Sybase Error Number</b>	3037
<b>SQL State</b>	52W50
<b>SQL Code</b>	-1357L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000

<b>Error 1357</b>	<b>"Multiple settings of same option specified for sequence '%1'"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the sequence.
<b>Probable Cause</b>	Multiple settings of the same sequence option have been specified in the sequence definition. Even if the setting is the same, you can only specify each option once.
<b>Error 1358</b>	<b>"Sequence name '%1' is ambiguous"</b>
<b>Constant</b>	AMBIGUOUS_SEQUENCE_NAME
<b>SAP Sybase Error Number</b>	3038
<b>SQL State</b>	52W45
<b>SQL Code</b>	-1358L
<b>ODBC 2 State</b>	S0013
<b>ODBC 3 State</b>	42S13
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of an ambiguous sequence.
<b>Probable Cause</b>	A statement has referred to a sequence name that is not unique. Preface the sequence name by an owner name.
<b>Error 1359</b>	<b>"Sequence "%1' not found"</b>
<b>Constant</b>	SEQUENCE_NOT_FOUND
<b>SAP Sybase Error Number</b>	3039
<b>SQL State</b>	52W44
<b>SQL Code</b>	-1359L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the sequence.
<b>Probable Cause</b>	The sequence with this name does not exist in the database.

## Errors and Warnings

<b>Error 1360</b>	<b>"Cannot assign automatic mirror server parent"</b>
<b>Constant</b>	CANNOT_ASSIGN_AUTO_PARENT
<b>SAP Sybase Error Number</b>	3040
<b>SQL State</b>	WW156
<b>SQL Code</b>	-1360L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A CREATE MIRROR SERVER or ALTER MIRROR SERVER statement requested that a mirror parent be automatically assigned, but a parent server could not be found. The auto_add_server option may not be set, or might be set to an invalid server name.
<b>Error 1361</b>	<b>"TREAT AS can only be used with extended types. Cannot treat %1 as a %2."</b>
<b>Constant</b>	TREAT_AS_ONLY_EXTENDED
<b>SAP Sybase Error Number</b>	3041
<b>SQL State</b>	53020
<b>SQL Code</b>	-1361L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The value that could not be converted.
<b>Parameter 2</b>	The name of the type for the conversion.
<b>Probable Cause</b>	An error occurred while trying to treat a value as another data type.
<b>Error 1362</b>	<b>"Cannot treat value "%1' as type %2. The dynamic type is %3."</b>
<b>Constant</b>	TREAT_AS_DYNAMIC_MISMATCH
<b>SAP Sybase Error Number</b>	3042

<b>Error 1362</b>	<b>"Cannot treat value '%1' as type %2. The dynamic type is %3."</b>
<b>SQL State</b>	53021
<b>SQL Code</b>	-1362L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The value that could not be converted.
<b>Parameter 2</b>	The name of the type for the conversion.
<b>Parameter 3</b>	The type of the value that could not be converted.
<b>Probable Cause</b>	An error occurred while trying to treat a value as another data type. The dynamic type of the value does not match the destination type.
<b>Error 1363</b>	<b>"The 'currval' operator is not defined yet for sequence '%1' for this connection"</b>
<b>Constant</b>	SEQUENCE_CURRVAL_NOT_DEFINED
<b>SAP Sybase Error Number</b>	3043
<b>SQL State</b>	52W51
<b>SQL Code</b>	-1363L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the sequence.
<b>Probable Cause</b>	The currval operator of a sequence generator is only defined once nextval has been called for the sequence within the current connection.

## Messages 1366 through 1386

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1366</b>	<b>"Sequence '%1' in use by another connection"</b>
<b>Constant</b>	SEQUENCE_IN_USE
<b>SAP Sybase Error Number</b>	3046
<b>SQL State</b>	42WE3
<b>SQL Code</b>	-1366L
<b>ODBC 2 State</b>	40001
<b>ODBC 3 State</b>	40001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of user.
<b>Probable Cause</b>	You have attempted to drop a sequence that is currently being used by another connection.
<b>Error 1367</b>	<b>"User owns sequences in use"</b>
<b>Constant</b>	USER_OWNS_SEQUENCES_IN_USE
<b>SAP Sybase Error Number</b>	3047
<b>SQL State</b>	42WE2
<b>SQL Code</b>	-1367L
<b>ODBC 2 State</b>	40001
<b>ODBC 3 State</b>	40001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to drop a user that owns a sequence being used by other active users of the database.
<b>Error 1369</b>	<b>"Sequence generators are not supported for this database"</b>
<b>Constant</b>	SEQUENCES_NOT_SUPPORTED
<b>SAP Sybase Error Number</b>	3049

<b>Error 1369</b>	<b>"Sequence generators are not supported for this database"</b>
<b>SQL State</b>	52W52
<b>SQL Code</b>	-1369L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The current database does not have catalog support for sequence generators. To use this feature, upgrade your database to the most recent version.
<b>Error 1370</b>	<b>"Text queries cannot contain more than 300 terms."</b>
<b>Constant</b>	TEXT_QUERY_TOO_LONG
<b>SAP Sybase Error Number</b>	3050
<b>SQL State</b>	WT022
<b>SQL Code</b>	-1370L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A text query should contain 300 terms or less.
<b>Error 1371</b>	<b>"The materialized view cannot be changed to immediate because the ON conditions must refer to both sides of the OUTER JOIN."</b>
<b>Constant</b>	UPDATABLE_MATVIEW_PSNS_ON_CONDITION
<b>SAP Sybase Error Number</b>	3051
<b>SQL State</b>	42WE4
<b>SQL Code</b>	-1371L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 1371</b>	"The materialized view cannot be changed to immediate because the ON conditions must refer to both sides of the OUTER JOIN."
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You attempted to change the refresh type to immediate for a materialized view whose definition contains an illegal ON condition.

<b>Error 1372</b>	"The server is not able to establish TCP/IP connections."
<b>Constant</b>	TCP_CONNECTIONS_NOT_ENABLED
<b>SAP Sybase Error Number</b>	2736
<b>SQL State</b>	08WA3
<b>SQL Code</b>	-1372L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	This database server is not able to establish TCP/IP connections. The personal server (dbeng) does not permit TCP/IP connections by default. This error may also occur if a network server (dbsrv) was started with the -xd command line option. The ability to establish TCP/IP connections is required to use diagnostic tracing and application profiling.

<b>Error 1373</b>	"Synchronization failed with internal error: %1"
<b>Constant</b>	SYNCCMD_INTERNAL_ERROR
<b>SAP Sybase Error Number</b>	3052
<b>SQL State</b>	5RW43
<b>SQL Code</b>	-1373L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The internal error number

<b>Error 1373</b>	<b>"Synchronization failed with internal error: %1"</b>
<b>Probable Cause</b>	An internal error occurred during the execution of the SYNCHRONIZE statement.
<b>Error 1374</b>	<b>"Synchronization failed. Check the results of the call to sp_get_last_synchronize_result( %1 ) for more information."</b>
<b>Constant</b>	SYNCCMD_SYNCH_FAILED
<b>SAP Sybase Error Number</b>	3053
<b>SQL State</b>	5RW44
<b>SQL Code</b>	-1374L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The connection ID on which the failed synchronization took place
<b>Probable Cause</b>	The synchronization completed, but the exit code from the synchronization indicates that the synchronization was not successful. Check the results of the call to sp_get_last_synchronize_result() for more information.
<b>Error 1375</b>	<b>"Failed to start the dbmlsync server"</b>
<b>Constant</b>	SYNCCMD_START_SERVER_FAIL
<b>SAP Sybase Error Number</b>	3054
<b>SQL State</b>	5RW45
<b>SQL Code</b>	-1375L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The database server failed to start a new dbmlsync process or failed to connect to an existing dbmlsync server running on the port number specified in the SYNCHRONIZE statement.

## Errors and Warnings

<b>Error 1376</b>	<b>"Failed to connect to the dbmlsync server"</b>
<b>Constant</b>	SYNCCMD_CONNECT_SERVER_FAIL
<b>SAP Sybase Error Number</b>	3055
<b>SQL State</b>	5RW46
<b>SQL Code</b>	-1376L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The database server failed to make a connection to the dbmlsync server.
<b>Error 1377</b>	<b>"The SYNCHRONIZE statement timed out"</b>
<b>Constant</b>	SYNCCMD_TIMEOUT
<b>SAP Sybase Error Number</b>	3056
<b>SQL State</b>	5RW47
<b>SQL Code</b>	-1377L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The SYNCHRONIZE statement did not complete within the timeout value specified. Check the results of the call to sp_get_last_syncronize_result() for more information.
<b>Error 1378</b>	<b>"The database server failed to shut down the dbmlsync server"</b>
<b>Constant</b>	SYNCCMD_SHUTDOWN_FAIL
<b>SAP Sybase Error Number</b>	3057
<b>SQL State</b>	5RW48
<b>SQL Code</b>	-1378L
<b>ODBC 2 State</b>	ERROR

<b>Error 1378</b>	<b>"The database server failed to shut down the dbmlsync server"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The database server started a new dbmlsync server to process the SYNCHRONIZE statement, but encountered an error while attempting to shut the process down.
<b>Error 1379</b>	<b>"The dbmlsync server failed to shut down in a timely manner"</b>
<b>Constant</b>	SYNCCMD_SHUTDOWN_SLOW
<b>SAP Sybase Error Number</b>	3058
<b>SQL State</b>	5RW49
<b>SQL Code</b>	-1379L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The database server started a new dbmlsync server to process the SYNCHRONIZE statement, was successful in requesting that the process shut down, but the process did not shut down within the timeout value that was specified.
<b>Error 1380</b>	<b>"Client redirected more than once"</b>
<b>Constant</b>	TOO_MANY_REDIRECTS
<b>SAP Sybase Error Number</b>	3059
<b>SQL State</b>	08WA4
<b>SQL Code</b>	-1380L
<b>ODBC 2 State</b>	08S01
<b>ODBC 3 State</b>	08S01
<b>Severity Code</b>	<i>21</i> on page 2
<b>Probable Cause</b>	The connection was redirected by the primary server to another server, which also attempted to redirect the connection.

## Errors and Warnings

<b>Error 1381</b>	"Database server name '%1' cannot be the same as either the primary or mirror server"
<b>Constant</b>	MIRROR_SERVER_NAME_CONFLICT
<b>SAP Sybase Error Number</b>	3060
<b>SQL State</b>	WW159
<b>SQL Code</b>	-1381L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The server name
<b>Probable Cause</b>	The mirror servers defined with type PRIMARY or MIRROR cannot have names that match actual server names.
<b>Error 1382</b>	"Download failed due to an invalid or unsupported row value"
<b>Constant</b>	INVALID_DOWNLOAD_VALUE
<b>SAP Sybase Error Number</b>	3061
<b>SQL State</b>	0AW26
<b>SQL Code</b>	-1382L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The synchronization download failed because a downloaded row contained a column value that was either invalid or not supported.
<b>Error 1383</b>	"The licensed maximum number of mirror servers with type COPY has been exceeded"
<b>Constant</b>	MIRROR_COPY_SERVER_LIMIT_EXCEEDED
<b>SAP Sybase Error Number</b>	3062
<b>SQL State</b>	WW160

<b>Error 1383</b>	<b>"The licensed maximum number of mirror servers with type COPY has been exceeded"</b>
<b>SQL Code</b>	-1383L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The maximum number of mirror servers with type COPY that may be defined is limited by the database server license. An attempt was made to create a new mirror server with type COPY when the maximum allowed number of such servers already existed.

<b>Error 1384</b>	<b>"Unable to stop specified database: %1"</b>
<b>Constant</b>	UNABLE_TO_STOP_DATABASE
<b>SAP Sybase Error Number</b>	2728
<b>SQL State</b>	08WA5
<b>SQL Code</b>	-1384L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	Reason the database could not be stopped, if known.
<b>Probable Cause</b>	The database server was unable to stop the specified database.

<b>Error 1385</b>	<b>"Synchronization failed. Check the dbmIsync log file for more details."</b>
<b>Constant</b>	MLA_SYNC_FAILED
<b>SAP Sybase Error Number</b>	3063
<b>SQL State</b>	WW161
<b>SQL Code</b>	-1385L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

## Errors and Warnings

<b>Error 1385</b>	<b>"Synchronization failed. Check the dbmlsync log file for more details."</b>
<b>Probable Cause</b>	The synchronization was not successful. Check the dbmlsync log file for more details.
<b>Error 1386</b>	<b>"Failed to connect to the dbmlsync server. Check the dbmlsync log file for more details."</b>
<b>Constant</b>	MLA_SYNC_CONNECT_SERVER_FAIL
<b>SAP Sybase Error Number</b>	3064
<b>SQL State</b>	WW162
<b>SQL Code</b>	-1386L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The MobiLink agent adapter failed to make a connection to the dbmlsync server. Check the dbmlsync log file for more details.

## Messages 1387 through 1406

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1387</b>	<b>"Failed to shut down the dbmlsync server. Check the dbmlsync log file for more details."</b>
<b>Constant</b>	MLA_SYNC_SHUTDOWN_FAIL
<b>SAP Sybase Error Number</b>	3065
<b>SQL State</b>	WW163
<b>SQL Code</b>	-1387L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The MobiLink agent adapter encountered an error while attempting to shut down the server. Check the dbmlsync log file for more details.

<b>Error 1388</b>	"Failed to start the dbmlsync server. Check the dbmlsync log file for more details."
<b>Constant</b>	MLA_SYNC_START_SERVER_FAIL
<b>SAP Sybase Error Number</b>	3066
<b>SQL State</b>	WW164
<b>SQL Code</b>	-1388L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The MobiLink agent adapter failed to start a new dbmlsync process or the server did not begin processing requests before the timeout expired. Check the dbmlsync log file for more details.

<b>Error 1389</b>	"The value for the stoplist cannot be NULL."
<b>Constant</b>	TEXT_STOPLIST_NULL
<b>SAP Sybase Error Number</b>	2727
<b>SQL State</b>	WT023
<b>SQL Code</b>	-1389L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The value for a text configuration stoplist cannot be NULL. To remove a stoplist, use the ALTER TEXT CONFIGURATION...DROP STOPLIST statement.

<b>Error 1390</b>	"An incremental refresh is not possible when handles are exhausted."
<b>Constant</b>	TEXT_HANDLES_EXHAUSTED
<b>SAP Sybase Error Number</b>	2724
<b>SQL State</b>	WT024

## Errors and Warnings

<b>Error 1390</b>	"An incremental refresh is not possible when handles are exhausted."
<b>SQL Code</b>	-1390L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Incremental refresh of a MANUAL or AUTO REFRESH text index is not possible when handles are exhausted. You need to rebuild the text index before you can use incremental refresh.

<b>Error 1391</b>	"Invalid stoplist value."
<b>Constant</b>	TEXT_INVALID_STOPLIST_VALUE
<b>SAP Sybase Error Number</b>	2725
<b>SQL State</b>	WT025
<b>SQL Code</b>	-1391L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The value specified for the stoplist is not valid.

<b>Error 1392</b>	"Unique indexes with the clause WITH NULLS NOT DISTINCT are not supported for this database"
<b>Constant</b>	UNIQUE_INDEX_NULLS_NOT_DISTINCT_NOT_SUPPORTED
<b>SAP Sybase Error Number</b>	3067
<b>SQL State</b>	52W53
<b>SQL Code</b>	-1392L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

<b>Error 1392</b>	<b>"Unique indexes with the clause WITH NULLS NOT DISTINCT are not supported for this database"</b>
<b>Probable Cause</b>	The current database does not have support for unique indexes with the clause WITH NULLS NOT DISTINCT. To use this feature, upgrade your database to the most recent version.
<b>Error 1393</b>	<b>"Error initializing external term breaker"</b>
<b>Constant</b>	ERROR_INITIALIZING_EXT_TERMBREAKER
<b>SAP Sybase Error Number</b>	2717
<b>SQL State</b>	WT028
<b>SQL Code</b>	-1393L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The external term breaker could not be initialized because of an internal error.
<b>Error 1394</b>	<b>"Invalid external prefILTER name specified"</b>
<b>Constant</b>	INVALID_EXT_PREFILTER_NAME
<b>SAP Sybase Error Number</b>	2682
<b>SQL State</b>	WT029
<b>SQL Code</b>	-1394L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	External prefILTER name specified in the text configuration is invalid.
<b>Error 1395</b>	<b>"Invalid external term breaker name specified"</b>
<b>Constant</b>	INVALID_EXT_TERMBREAKER_NAME
<b>SAP Sybase Error Number</b>	2683
<b>SQL State</b>	WT026

## Errors and Warnings

<b>Error 1395</b>	<b>"Invalid external term breaker name specified"</b>
<b>SQL Code</b>	-1395L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	External term breaker name specified in the text configuration is invalid.
<b>Error 1396</b>	<b>"Error initializing external prefILTER"</b>
<b>Constant</b>	ERROR_INITIALIZING_EXT_PREFILTER
<b>SAP Sybase Error Number</b>	2718
<b>SQL State</b>	WT027
<b>SQL Code</b>	-1396L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The external prefILTER could not be initialized because of an internal error.
<b>Error 1397</b>	<b>"The definition of temporary table '%1' has changed since last used"</b>
<b>Constant</b>	TEMP_TABLE_DEFINITION_CHANGED
<b>SAP Sybase Error Number</b>	3068
<b>SQL State</b>	WW165
<b>SQL Code</b>	-1397L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The table name

<b>Error 1397</b>	<b>"The definition of temporary table '%1' has changed since last used"</b>
<b>Probable Cause</b>	The definition of a temporary table has changed since it was last used in a stored procedure or trigger. The procedure must be recompiled.
<b>Error 1398</b>	<b>"VERIFY and RENAME cannot be used together"</b>
<b>Constant</b>	RENAME_WITH_VERIFY_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	2681
<b>SQL State</b>	42WE5
<b>SQL Code</b>	-1398L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	Since VERIFY will never write to any dbspaces, renaming dbspaces cannot be done during restore verification.
<b>Error 1399</b>	<b>"Invalid intersection matrix '%1'"</b>
<b>Constant</b>	SLERR_INVALID_RELATE_MATRIX
<b>SAP Sybase Error Number</b>	3069
<b>SQL State</b>	2FF04
<b>SQL Code</b>	-1399L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The intersection matrix string.
<b>Probable Cause</b>	The provided value is not a valid intersection matrix string. A valid string contains nine characters, each is one of T, F, *, 0, 1, or 2.
<b>Error 1400</b>	<b>"Point is duplicated %1"</b>
<b>Constant</b>	SLERR_DUPLICATE_POINT
<b>SAP Sybase Error Number</b>	3070

## Errors and Warnings

<b>Error 1400</b>	<b>"Point is duplicated %1"</b>
<b>SQL State</b>	2FF05
<b>SQL Code</b>	-1400L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The duplicated point
<b>Probable Cause</b>	A linestring or circularstring geometry contains two adjacent points that are identical. This represents an invalid geometry.
<b>Error 1401</b>	<b>"Element is an empty set (near "%1")"</b>
<b>Constant</b>	SLERR_ELEMENT_IS_EMPTY
<b>SAP Sybase Error Number</b>	3071
<b>SQL State</b>	2FF06
<b>SQL Code</b>	-1401L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The value or method where the empty geometry has been detected.
<b>Probable Cause</b>	An element of a geometry is the empty set. Empty geometries cannot be used as the points in linestrings or circularstrings; empty curves cannot be used as elements of compoundcurves; empty curves cannot be used as rings of polygons.
<b>Error 1402</b>	<b>"Mixed spatial reference systems %1 and %2 (near %3)"</b>
<b>Constant</b>	SLERR_MIXED_SRS
<b>SAP Sybase Error Number</b>	3072
<b>SQL State</b>	2FF10
<b>SQL Code</b>	-1402L
<b>ODBC 2 State</b>	ERROR

<b>Error 1402</b>	<b>"Mixed spatial reference systems %1 and %2 (near %3)"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The SRID of the first spatial reference system.
<b>Parameter 2</b>	The SRID of the second spatial reference system.
<b>Parameter 3</b>	The value or method where the mixed spatial reference systems were detected.
<b>Probable Cause</b>	The method does not support working with geometries from different spatial reference systems.

<b>Error 1403</b>	<b>"Non-contiguous curves near '%1'"</b>
<b>Constant</b>	SLERR_COMPOUNDCURVE_NOT_CONTIGUOUS
<b>SAP Sybase Error Number</b>	3073
<b>SQL State</b>	2FF11
<b>SQL Code</b>	-1403L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The value or method where the non-contiguous curves were detected.
<b>Probable Cause</b>	A compoundcurve geometry is composed of curves, and adjacent curves must be joined at their endpoints.

<b>Error 1404</b>	<b>"Unknown unit of measure "%1'"</b>
<b>Constant</b>	SLERR_UNKNOWN_UOM
<b>SAP Sybase Error Number</b>	3074
<b>SQL State</b>	2FF14
<b>SQL Code</b>	-1404L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

## Errors and Warnings

<b>Error 1404</b>	<b>"Unknown unit of measure '%1'"</b>
<b>Parameter 1</b>	The name of the unit of measure.
<b>Probable Cause</b>	The name does not match a defined unit of measure.
<b>Error 1405</b>	<b>"Failed to transform geometry (error %1)"</b>
<b>Constant</b>	SLERR_TRANSFORM_FAIL
<b>SAP Sybase Error Number</b>	3075
<b>SQL State</b>	2FF15
<b>SQL Code</b>	-1405L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The error code from the projection library.
<b>Probable Cause</b>	An error occurred when performing a transform from one spatial reference system to another. This error may occur if a point in the first geometry is outside of the bounds for the transform definition. The error may also be reported for particular transform definitions. The integer error code from the transform library may be used to diagnose the transform definition.
<b>Error 1406</b>	<b>"Error parsing well-known-text (WKT) scanning '%1' at offset %2"</b>
<b>Constant</b>	SLERR_WKT_PARSE_NEAR
<b>SAP Sybase Error Number</b>	3076
<b>SQL State</b>	2FF22
<b>SQL Code</b>	-1406L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The text where the problem was detected.

<b>Error 1406</b>	"Error parsing well-known-text (WKT) scanning '%1' at offset %2"
<b>Parameter 2</b>	The offset within the input string where the problem was detected.
<b>Probable Cause</b>	An error was detected while parsing the well-known text of a geometry.

## Messages 1407 through 1427

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1407</b>	"Error parsing well-known-binary (WKB) at offset %1"
<b>Constant</b>	SLERR_WKB_PARSE
<b>SAP Sybase Error Number</b>	3077
<b>SQL State</b>	2FF23
<b>SQL Code</b>	-1407L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The byte offset within the binary string where the error was detected.
<b>Probable Cause</b>	An error was detected while parsing the well-known binary of a geometry.

<b>Error 1408</b>	"Mixed coordinate dimensions"
<b>Constant</b>	SLERR_MIXED_DIM
<b>SAP Sybase Error Number</b>	3078
<b>SQL State</b>	2FF25
<b>SQL Code</b>	-1408L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

## Errors and Warnings

<b>Error 1408</b>	<b>"Mixed coordinate dimensions"</b>
<b>Probable Cause</b>	The method contains geometries that have a mixture of coordinate dimensions (Z and M values).
<b>Error 1409</b>	<b>"Unknown spatial reference system (%1)"</b>
<b>Constant</b>	SLERR_SRID_UNKNOWN
<b>SAP Sybase Error Number</b>	3079
<b>SQL State</b>	2FF59
<b>SQL Code</b>	-1409L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The spatial reference system identifier.
<b>Probable Cause</b>	The provided SRID does not match a defined spatial reference system.
<b>Error 1410</b>	<b>"An ST_CircularString cannot be constructed from %1 points (near '%2')"</b>
<b>Constant</b>	SLERR_CIRC_NUM_POINTS
<b>SAP Sybase Error Number</b>	3080
<b>SQL State</b>	2FF71
<b>SQL Code</b>	-1410L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The incorrect number of points given.
<b>Parameter 2</b>	The value or method where the error was detected.
<b>Probable Cause</b>	A circularstring geometry should consist of three points followed optionally by an arbitrary number of pairs of points.

<b>Error 1411</b>	<b>"Cannot convert from %1 to %2 (near %3)."</b>
<b>Constant</b>	SLERR_ST_TO_XXX_FAILN
<b>SAP Sybase Error Number</b>	3081
<b>SQL State</b>	2FF16
<b>SQL Code</b>	-1411L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The geometry type of the value.
<b>Parameter 2</b>	The geometry type of the target.
<b>Parameter 3</b>	The value or method where the error was detected.
<b>Probable Cause</b>	The value could not be converted to the specified target type.

<b>Error 1412</b>	<b>"Support for spatial is not available for this database"</b>
<b>Constant</b>	SLERR_NEED_UPGRADE
<b>SAP Sybase Error Number</b>	3082
<b>SQL State</b>	2FW02
<b>SQL Code</b>	-1412L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Operations involving spatial support cannot be used with this database because it needs to be upgraded to use spatial features.

<b>Error 1413</b>	<b>"Spatial feature %1 is not supported"</b>
<b>Constant</b>	SLERR_NYI
<b>SAP Sybase Error Number</b>	3083
<b>SQL State</b>	2FW03
<b>SQL Code</b>	-1413L

## Errors and Warnings

<b>Error 1413</b>	<b>"Spatial feature %1 is not supported"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the unsupported feature.
<b>Probable Cause</b>	The specified feature is not supported.
<b>Error 1414</b>	<b>"Error parsing well-known-text (WKT): inconsistent dimensions at offset %1"</b>
<b>Constant</b>	SLERR_WKT_PARSE_INCONSISTENT_ZM
<b>SAP Sybase Error Number</b>	3084
<b>SQL State</b>	2FW05
<b>SQL Code</b>	-1414L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The offset within the well-known text string where the error was detected.
<b>Probable Cause</b>	There was a mixture of coordinate dimensions detected at the specified offset. For example, one geometry in a collection might have a Z value while another doesn't.
<b>Error 1415</b>	<b>"Error parsing geometry internal serialization at offset %1"</b>
<b>Constant</b>	SLERR_SERIAL_PARSE
<b>SAP Sybase Error Number</b>	3085
<b>SQL State</b>	2FW06
<b>SQL Code</b>	-1415L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

<b>Error 1415</b>	<b>"Error parsing geometry internal serialization at offset %1"</b>
<b>Parameter 1</b>	The byte offset within the internal serialization.
<b>Probable Cause</b>	There was an error parsing the internal serialization string.
<b>Error 1417</b>	<b>"Error parsing well-known-binary (WKB): type code %1 at offset %2 is invalid"</b>
<b>Constant</b>	SLERR_WKB_PARSE_TYPE
<b>SAP Sybase Error Number</b>	3087
<b>SQL State</b>	2FW08
<b>SQL Code</b>	-1417L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The unsupported type code value.
<b>Parameter 2</b>	The byte offset within the binary string where the error was detected.
<b>Probable Cause</b>	The well-known binary string contains a type code that is not supported.
<b>Error 1418</b>	<b>"Error parsing well-known-binary (WKB): type code %1 at offset %2 is not a valid subtype of the parent"</b>
<b>Constant</b>	SLERR_WKB_PARSE_TYPE_NOT_PERMITTED
<b>SAP Sybase Error Number</b>	3088
<b>SQL State</b>	2FW09
<b>SQL Code</b>	-1418L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The unsupported type code value.
<b>Parameter 2</b>	The byte offset within the binary string where the error was detected.

## Errors and Warnings

<b>Error 1418</b>	<b>"Error parsing well-known-binary (WKB): type code %1 at offset %2 is not a valid subtype of the parent"</b>
<b>Probable Cause</b>	The well-known binary string contains a child geometry within a parent geometry and the child is not one of the types allowed by the parent.
<b>Error 1419</b>	<b>"Error parsing well-known-binary (WKB): unexpected end of input"</b>
<b>Constant</b>	SLERR_WKB_PARSE_UNEXPECTED_EOF
<b>SAP Sybase Error Number</b>	3089
<b>SQL State</b>	2FW10
<b>SQL Code</b>	-1419L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A well-known binary string was shorter than expected.
<b>Error 1420</b>	<b>"Error parsing well-known-binary (WKB): inconsistent dimensions at offset %1"</b>
<b>Constant</b>	SLERR_WKB_PARSE_INCONSISTENT_ZM
<b>SAP Sybase Error Number</b>	3090
<b>SQL State</b>	2FW11
<b>SQL Code</b>	-1420L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The byte offset within the binary string where the error was detected.
<b>Probable Cause</b>	The well-known binary string contains geometries with different numbers of coordinate dimensions. For example, it could contain a point with a Z value and another without a Z value.

<b>Error 1421</b>	"Error parsing well-known-binary (WKB): invalid byte order mark %1 at offset %2"
<b>Constant</b>	SLERR_WKB_PARSE_INVALID_BOM
<b>SAP Sybase Error Number</b>	3091
<b>SQL State</b>	2FW12
<b>SQL Code</b>	-1421L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The value of the byte-order mark.
<b>Parameter 2</b>	The byte offset within the binary string where the error was detected.
<b>Probable Cause</b>	The well-known binary string has an invalid byte order mark. This could happen if a binary string that is not in the well-known binary format is used.
<b>Error 1422</b>	"Error parsing shapefile record"
<b>Constant</b>	SLERR_SHAPE_PARSE
<b>SAP Sybase Error Number</b>	3092
<b>SQL State</b>	2FW13
<b>SQL Code</b>	-1422L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The shapefile contains an invalid record.
<b>Error 1423</b>	"Error parsing shapefile attributes"
<b>Constant</b>	SLERR_SHAPE_PARSE_ATTRIBUTES
<b>SAP Sybase Error Number</b>	3093
<b>SQL State</b>	2FW14

## Errors and Warnings

<b>Error 1423</b>	<b>"Error parsing shapefile attributes"</b>
<b>SQL Code</b>	-1423L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The shapefile contains invalid attributes.
<b>Error 1424</b>	<b>"Invalid shapefile filename"</b>
<b>Constant</b>	SLERR_SHAPE_INVALID_FILENAME
<b>SAP Sybase Error Number</b>	3094
<b>SQL State</b>	2FW15
<b>SQL Code</b>	-1424L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The specified shapefile filename is not valid.
<b>Error 1425</b>	<b>"The multi patch shapefile shape is not supported"</b>
<b>Constant</b>	SLERR_SHAPE_MULTIPATCH
<b>SAP Sybase Error Number</b>	3095
<b>SQL State</b>	2FW16
<b>SQL Code</b>	-1425L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The shapefile contains a multi patch object; this type is not supported.
<b>Error 1426</b>	<b>"The embedded SRID (%1) conflicts with the provided SRID (%2)."</b>
<b>Constant</b>	SLERR_SRID_CONFLICT_EMBED_PARAM

<b>Error 1426</b>	"The embedded SRID (%1) conflicts with the provided SRID (%2)."
<b>SAP Sybase Error Number</b>	3096
<b>SQL State</b>	2FW19
<b>SQL Code</b>	-1426L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The SRID within the parsed string.
<b>Parameter 2</b>	The SRID provided as a parameter.
<b>Probable Cause</b>	A call to a spatial method had a string with an embedded SRID that differed from the SRID parameter to the method.
<b>Error 1427</b>	"The embedded SRID are inconsistent (%1 and %2)."
<b>Constant</b>	SLERR_SRID_CONFLICT_EMBED_EMBED
<b>SAP Sybase Error Number</b>	3097
<b>SQL State</b>	2FW20
<b>SQL Code</b>	-1427L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The first SRID.
<b>Parameter 2</b>	The second SRID.
<b>Probable Cause</b>	A geometry in a string representation contains objects from different spatial reference systems.

## 1428 - 1629

## Messages 1428 through 1448

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1428</b>	"The format type "%1' is not recognized."
<b>Constant</b>	SLERR_FMT_UNKNOWN
<b>SAP Sybase Error Number</b>	3098
<b>SQL State</b>	2FW21
<b>SQL Code</b>	-1428L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The invalid format type.
<b>Probable Cause</b>	The specified format type is not recognized.
<b>Error 1429</b>	"The format type "%1' cannot be used here."
<b>Constant</b>	SLERR_FMT_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	3099
<b>SQL State</b>	2FW22
<b>SQL Code</b>	-1429L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The invalid format type.
<b>Probable Cause</b>	The specified format type cannot be used in this context.
<b>Error 1430</b>	"An input string in "%1' format cannot be used here."
<b>Constant</b>	SLERR_WRONG_FORMAT
<b>SAP Sybase Error Number</b>	3100
<b>SQL State</b>	2FW23

<b>Error 1430</b>	<b>"An input string in '%1' format cannot be used here."</b>
<b>SQL Code</b>	-1430L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The invalid format.
<b>Probable Cause</b>	A string with the specified format cannot be used in this context.
<b>Error 1431</b>	<b>"The format specification syntax is invalid."</b>
<b>Constant</b>	SLERR_INVALID_FORMAT_SPECIFICATION
<b>SAP Sybase Error Number</b>	3101
<b>SQL State</b>	2FW24
<b>SQL Code</b>	-1431L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The format specification is invalid.
<b>Error 1432</b>	<b>"The format specification option '%1' is not recognized."</b>
<b>Constant</b>	SLERR_INVALID_FORMAT_SPECIFICATION_OPTION
<b>SAP Sybase Error Number</b>	3102
<b>SQL State</b>	2FW25
<b>SQL Code</b>	-1432L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The invalid option.
<b>Probable Cause</b>	The named option is not supported for the format specification.

## Errors and Warnings

<b>Error 1433</b>	"The value '%2' is not a valid setting for the '%1' format specification option."
<b>Constant</b>	SLERR_INVALID_FORMAT_SPECIFICATION_OPTION_VALUE
<b>SAP Sybase Error Number</b>	3103
<b>SQL State</b>	2FW26
<b>SQL Code</b>	-1433L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The invalid value.
<b>Parameter 2</b>	The format specification option.
<b>Probable Cause</b>	The value is not accepted by the specification option.

<b>Error 1434</b>	"The data is not in a recognized format."
<b>Constant</b>	SLERR_UNKOWNN_FORMAT
<b>SAP Sybase Error Number</b>	3104
<b>SQL State</b>	2FW27
<b>SQL Code</b>	-1434L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The provided string is not in a recognized format to parse a geometry.

<b>Error 1435</b>	"A geometry with SRID=%1 is not supported for method %2."
<b>Constant</b>	SLERR_ROUND_EARTH_UNSUPPORTED
<b>SAP Sybase Error Number</b>	3105
<b>SQL State</b>	2FW28
<b>SQL Code</b>	-1435L

<b>Error 1435</b>	<b>"A geometry with SRID=%1 is not supported for method %2."</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The SRID of the geometry.
<b>Parameter 2</b>	The name of the method that does not support this SRID.
<b>Probable Cause</b>	The named method does not support geometries in the specified spatial reference system. For example, the method might not support round-Earth data.
<b>Error 1436</b>	<b>"A geometry with SRID=%1 is not supported when computing distance between non-point geometries."</b>
<b>Constant</b>	SLERR_ROUND_EARTH_UNSUPPORTED_DIS
<b>SAP Sybase Error Number</b>	3106
<b>SQL State</b>	2FW29
<b>SQL Code</b>	-1436L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The SRID of the geometry.
<b>Probable Cause</b>	When operating with round-Earth data, distance between non-point geometries is not supported.
<b>Error 1438</b>	<b>"Error reading configuration file."</b>
<b>Constant</b>	SLERR_CONFIG_FILE_ERR
<b>SAP Sybase Error Number</b>	3108
<b>SQL State</b>	2FW31
<b>SQL Code</b>	-1438L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 1438</b>	<b>"Error reading configuration file."</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	An error occurred while reading a configuration file for spatial support. This error can occur if the "st_geometry_config.tgz" file is not installed.
<b>Error 1439</b>	<b>"Invalid configuration name %1"</b>
<b>Constant</b>	SLERR_CONFIG_NO_SUBFILE
<b>SAP Sybase Error Number</b>	3109
<b>SQL State</b>	2FW32
<b>SQL Code</b>	-1439L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The invalid configuration name.
<b>Probable Cause</b>	The named configuration is not supported.
<b>Error 1440</b>	<b>"The comparison '%1' cannot be used with geometries."</b>
<b>Constant</b>	SLERR_COMPARISON_PREDICATE
<b>SAP Sybase Error Number</b>	3110
<b>SQL State</b>	2FW33
<b>SQL Code</b>	-1440L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The type of comparison relation.
<b>Probable Cause</b>	Geometry values cannot be compared with operators such as < or >. Geometries can only be compared with = and <>.

<b>Error 1441</b>	<b>"Invalid spatial reference system well-known-text (WKT)." </b>
<b>Constant</b>	SLERR_SRS_PARSE_ERROR
<b>SAP Sybase Error Number</b>	3111
<b>SQL State</b>	2FW34
<b>SQL Code</b>	-1441L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The provided string does not represent a valid spatial reference system definition in well-known text format.
<b>Error 1442</b>	<b>"Invalid transform definition '%1'."</b>
<b>Constant</b>	SLERR_INVALID_TRANSFORM_DEF
<b>SAP Sybase Error Number</b>	3112
<b>SQL State</b>	2FW35
<b>SQL Code</b>	-1442L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The invalid transform definition string.
<b>Probable Cause</b>	The provided string does not represent a valid transform definition.
<b>Error 1443</b>	<b>"Transform definition is too long."</b>
<b>Constant</b>	SLERR_TRANSFORM_DEF_TOO_LONG
<b>SAP Sybase Error Number</b>	3113
<b>SQL State</b>	2FW36
<b>SQL Code</b>	-1443L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 1443</b>	"Transform definition is too long."
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The provided transform definition is too long.
<b>Error 1444</b>	"Transform from SRID %1 to %2 not supported."
<b>Constant</b>	SLERR_NO_XFORM_DEF
<b>SAP Sybase Error Number</b>	3114
<b>SQL State</b>	2FW37
<b>SQL Code</b>	-1444L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The SRID of the value.
<b>Parameter 2</b>	The SRID of the destination.
<b>Probable Cause</b>	There is no way to transform from the value's spatial reference system to the specified target.
<b>Error 1445</b>	"Transform from SRID %1 not supported."
<b>Constant</b>	SLERR_NO_SRC_XFORM_DEF
<b>SAP Sybase Error Number</b>	3115
<b>SQL State</b>	2FW38
<b>SQL Code</b>	-1445L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The SRID of the value.
<b>Probable Cause</b>	There is no way to transform from values of the specified spatial reference system.

<b>Error 1446</b>	<b>"Unit of measure \"%1\" is not a linear unit."</b>
<b>Constant</b>	SLERR_UOM_NOT_LINEAR
<b>SAP Sybase Error Number</b>	3116
<b>SQL State</b>	2FW39
<b>SQL Code</b>	-1446L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the invalid unit of measure.
<b>Probable Cause</b>	The specified unit of measure is not a linear unit of measure.
<b>Error 1447</b>	<b>"Unit of measure \"%1\" is not an angular unit."</b>
<b>Constant</b>	SLERR_UOM_NOT_ANGULAR
<b>SAP Sybase Error Number</b>	3117
<b>SQL State</b>	2FW40
<b>SQL Code</b>	-1447L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the invalid unit of measure.
<b>Probable Cause</b>	The specified unit of measure is not a linear unit of measure.
<b>Error 1448</b>	<b>"Invalid polygon format \"%1\""</b>
<b>Constant</b>	SLERR_INVALID_POLY_ORD
<b>SAP Sybase Error Number</b>	3118
<b>SQL State</b>	2FW41
<b>SQL Code</b>	-1448L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1448</b>	" <b>Invalid polygon format "%1"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The invalid polygon format.
<b>Probable Cause</b>	The specified polygon format is not a valid format.

## Messages 1449 through 1468

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1449</b>	" <b>Invalid polygon: no exterior ring</b> "
<b>Constant</b>	SLERR_INVALID_POLY_NO_EXT
<b>SAP Sybase Error Number</b>	3119
<b>SQL State</b>	2FW42
<b>SQL Code</b>	-1449L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The provided polygon is invalid as it does not have an exterior ring.

<b>Error 1450</b>	" <b>Invalid polygon nesting</b> "
<b>Constant</b>	SLERR_INVALID_POLY_NESTING
<b>SAP Sybase Error Number</b>	3120
<b>SQL State</b>	2FW43
<b>SQL Code</b>	-1450L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The provided rings cannot be interpreted as a valid polygons.

<b>Error 1451</b>	" <b>Invalid polygon: multiple exterior rings</b> "
<b>Constant</b>	SLERR_INVALID_POLY_MULT_EXT

<b>Error 1451</b>	<b>"Invalid polygon: multiple exterior rings"</b>
<b>SAP Sybase Error Number</b>	3121
<b>SQL State</b>	2FW44
<b>SQL Code</b>	-1451L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	There are multiple exterior rings that do not form a single valid polygon.
<b>Error 1452</b>	<b>"Table '%1' contains a spatial column '%2' and no primary key"</b>
<b>Constant</b>	SLERR_UPDDEL_NO_PK
<b>SAP Sybase Error Number</b>	3122
<b>SQL State</b>	2FW45
<b>SQL Code</b>	-1452L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The table name.
<b>Parameter 2</b>	The spatial column name.
<b>Probable Cause</b>	An update or delete statement cannot be performed for a table that contains a spatial column unless there is a primary key defined for the table.
<b>Error 1453</b>	<b>"Spatial column '%1' cannot be included in a primary key or unique index"</b>
<b>Constant</b>	SLERR_CREATE_INDEX_UNIQUE
<b>SAP Sybase Error Number</b>	3123
<b>SQL State</b>	2FW46
<b>SQL Code</b>	-1453L

## Errors and Warnings

<b>Error 1453</b>	<b>"Spatial column '%1' cannot be included in a primary key or unique index"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the spatial column.
<b>Probable Cause</b>	A spatial column cannot be included in a primary key or unique index.
<b>Error 1454</b>	<b>"Spatial column '%1' cannot be included in an index because it is not constrained to a single SRID"</b>
<b>Constant</b>	SLERR_CREATE_INDEX_NOSRID
<b>SAP Sybase Error Number</b>	3124
<b>SQL State</b>	2FW47
<b>SQL Code</b>	-1454L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the spatial column.
<b>Probable Cause</b>	The named spatial column cannot be included in a spatial index because the column is not constrained to have values from a single spatial reference system. The column definition should be of the form "col ST_Geometry(SRID=0)".
<b>Error 1455</b>	<b>"The CONVERT USING clause must be specified when creating a unit of measure"</b>
<b>Constant</b>	SLERR_DDL_UOM_NOFACT
<b>SAP Sybase Error Number</b>	3125
<b>SQL State</b>	2FW48
<b>SQL Code</b>	-1455L
<b>ODBC 2 State</b>	ERROR

<b>Error 1455</b>	"The CONVERT USING clause must be specified when creating a unit of measure"
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A CREATE SPATIAL UNIT OF MEASURE statement was used without including the CONVERT USING clause.

<b>Error 1456</b>	"The string "%1" is not a valid axis order"
<b>Constant</b>	SLERR_DDL_SRS_AXISORDER
<b>SAP Sybase Error Number</b>	3126
<b>SQL State</b>	2FW49
<b>SQL Code</b>	-1456L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The invalid axis order.
<b>Probable Cause</b>	The specified string is not a valid axis order.

<b>Error 1457</b>	"The string "%1" is not a valid coordinate name"
<b>Constant</b>	SLERR_DDL_SRS_COORDNAME
<b>SAP Sybase Error Number</b>	3127
<b>SQL State</b>	2FW50
<b>SQL Code</b>	-1457L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The invalid coordinate name.
<b>Probable Cause</b>	The provided string is not the name of a coordinate. Coordinate names are X, Y, Z, M, Latitude and Longitude.

## Errors and Warnings

<b>Error 1458</b>	<b>"Unit of measure '%1' not found"</b>
<b>Constant</b>	SLERR_DDL_NO_UOM
<b>SAP Sybase Error Number</b>	3128
<b>SQL State</b>	2FW51
<b>SQL Code</b>	-1458L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The unit of measure name.
<b>Probable Cause</b>	The named unit of measure is not defined.
<b>Error 1459</b>	<b>"Spatial reference system '%1' not found"</b>
<b>Constant</b>	SLERR_DDL_NO_SRS
<b>SAP Sybase Error Number</b>	3129
<b>SQL State</b>	2FW52
<b>SQL Code</b>	-1459L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the spatial reference system.
<b>Probable Cause</b>	The named spatial reference system is not defined.
<b>Error 1460</b>	<b>"Unit of measure '%1' already exists"</b>
<b>Constant</b>	SLERR_DDL_UOM_EXISTS
<b>SAP Sybase Error Number</b>	3130
<b>SQL State</b>	2FW53
<b>SQL Code</b>	-1460L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1460</b>	<b>"Unit of measure "%1' already exists"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the unit of measure.
<b>Probable Cause</b>	The named unit of measure is already defined.
<b>Error 1461</b>	<b>"Spatial reference system "%1' already exists"</b>
<b>Constant</b>	SLERR_DDL_SRS_EXISTS
<b>SAP Sybase Error Number</b>	3131
<b>SQL State</b>	2FW54
<b>SQL Code</b>	-1461L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the spatial reference system.
<b>Probable Cause</b>	The named spatial reference system already exists.
<b>Error 1462</b>	<b>"Spatial reference system must specify the SRID to use"</b>
<b>Constant</b>	SLERR_DDL_SRS_NOSRID
<b>SAP Sybase Error Number</b>	3132
<b>SQL State</b>	2FW55
<b>SQL Code</b>	-1462L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	When creating a spatial reference system, the statement must specify IDENTIFIED BY to specify the SRID to use.
<b>Error 1463</b>	<b>"Error parsing definition string "%1"</b>
<b>Constant</b>	SLERR_DDL_SRS_BADWKT
<b>SAP Sybase Error Number</b>	3133

## Errors and Warnings

<b>Error 1463</b>	<b>"Error parsing definition string "%1"</b>
<b>SQL State</b>	2FW56
<b>SQL Code</b>	-1463L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Coordinate system name
<b>Probable Cause</b>	The provided definition string is not a valid well known text of the coordinate system.
<b>Error 1464</b>	<b>"The spatial reference system type is not supported ("%1")"</b>
<b>Constant</b>	SLERR_DDL_SRS_BAD_SRS_TYPE
<b>SAP Sybase Error Number</b>	3134
<b>SQL State</b>	2FW57
<b>SQL Code</b>	-1464L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The unsupported spatial reference system type.
<b>Probable Cause</b>	The specified spatial reference system type is not supported.
<b>Error 1465</b>	<b>"Ellipsoid parameters missing for geographic spatial reference system"</b>
<b>Constant</b>	SLERR_DDL_SRS_NOELLIPSOID
<b>SAP Sybase Error Number</b>	3135
<b>SQL State</b>	2FW58
<b>SQL Code</b>	-1465L
<b>ODBC 2 State</b>	ERROR

<b>Error 1465</b>	<b>"Ellipsoid parameters missing for geographic spatial reference system"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	When creating a geographic spatial reference system, the ellipsoid parameters must be specified, either in the DEFINITION clause or explicitly. These parameters are used to calculate the distance between points.

<b>Error 1466</b>	<b>"Ellipsoid parameters specified for non-geographic spatial reference system"</b>
<b>Constant</b>	SLERR_DDL_SRS_ELLIPSOID
<b>SAP Sybase Error Number</b>	3136
<b>SQL State</b>	2FW59
<b>SQL Code</b>	-1466L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The ELLIPSOID parameters can only be specified for geographic spatial reference systems.

<b>Error 1467</b>	<b>"Coordinate bounds missing for coordinate %1"</b>
<b>Constant</b>	SLERR_DDL_SRS_MUSTBOUND
<b>SAP Sybase Error Number</b>	3137
<b>SQL State</b>	2FW60
<b>SQL Code</b>	-1467L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The coordinate name.
<b>Probable Cause</b>	No bounds were specified for the named coordinate.

<b>Error 1468</b>	"The specified axis order is not supported for this type of spatial reference system"
<b>Constant</b>	SLERR_DDL_SRS_AXISORD
<b>SAP Sybase Error Number</b>	3138
<b>SQL State</b>	2FW61
<b>SQL Code</b>	-1468L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The specified axis order is not supported for this type of spatial reference system.

## Messages 1469 through 1489

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1469</b>	"The specified polygon format '%1' is not supported for this type of spatial reference system"
<b>Constant</b>	SLERR_DDL_SRS_POLYFORMAT
<b>SAP Sybase Error Number</b>	3139
<b>SQL State</b>	2FW62
<b>SQL Code</b>	-1469L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The polygon format string.
<b>Probable Cause</b>	The specified polygon format is not supported for this type of spatial reference system.
<b>Error 1470</b>	"Invalid storage format '%1'"
<b>Constant</b>	SLERR_DDL_SRS_STGFORMAT

<b>Error 1470</b>	<b>"Invalid storage format "%1"</b>
<b>SAP Sybase Error Number</b>	3140
<b>SQL State</b>	2FW63
<b>SQL Code</b>	-1470L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The invalid storage format string.
<b>Probable Cause</b>	The specified storage format string is not valid.

<b>Error 1471</b>	<b>"Spatial reference system %1 cannot be modified because it is in use"</b>
<b>Constant</b>	SLERR_DDL_SRS_INUSE
<b>SAP Sybase Error Number</b>	3141
<b>SQL State</b>	2FW64
<b>SQL Code</b>	-1471L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The coordinate system name
<b>Probable Cause</b>	The coordinate system is currently in use and cannot be dropped.

<b>Error 1472</b>	<b>"Spatial reference system \'%1\' is reserved"</b>
<b>Constant</b>	SLERR_DDL_SRS_RESERVED
<b>SAP Sybase Error Number</b>	3142
<b>SQL State</b>	2FW65
<b>SQL Code</b>	-1472L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 1472</b>	<b>"Spatial reference system \"%1\" is reserved"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the reserved spatial reference system.
<b>Probable Cause</b>	The named spatial reference system is reserved for system use.
<b>Error 1473</b>	<b>"Spatial unit of measure \"%1\" is reserved"</b>
<b>Constant</b>	SLERR_DDL_UOM_RESERVED
<b>SAP Sybase Error Number</b>	3143
<b>SQL State</b>	2FW66
<b>SQL Code</b>	-1473L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the reserved unit of measure.
<b>Probable Cause</b>	The named unit of measure is reserved for system use.
<b>Error 1474</b>	<b>"SRID %1 is referenced by column \"%2' of table \"%3""</b>
<b>Constant</b>	SLERR_SRS_INUSE_TAB
<b>SAP Sybase Error Number</b>	3144
<b>SQL State</b>	2FW67
<b>SQL Code</b>	-1474L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The spatial reference system identifier.
<b>Parameter 2</b>	The name of the referencing column.
<b>Parameter 3</b>	The name of the referencing table.
<b>Probable Cause</b>	The specified spatial reference system is in use by the column of a table, and it cannot be modified.

<b>Error 1475</b>	<b>"SRID %1 is referenced by parameter '%2' of procedure '%3'"</b>
<b>Constant</b>	SLERR_SRS_INUSE_PROC
<b>SAP Sybase Error Number</b>	3145
<b>SQL State</b>	2FW68
<b>SQL Code</b>	-1475L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The spatial reference system identifier.
<b>Parameter 2</b>	The referencing parameter name.
<b>Parameter 3</b>	The referencing procedure name.
<b>Probable Cause</b>	The specified spatial reference system is in use by the parameter of a procedure, and it cannot be modified.
<b>Error 1476</b>	<b>"SRID %1 is referenced by domain \"%3\".\"%2\\No message"</b>
<b>Constant</b>	SLERR_SRS_INUSE_TYPE
<b>SAP Sybase Error Number</b>	3146
<b>SQL State</b>	2FW69
<b>SQL Code</b>	-1476L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The spatial reference system identifier.
<b>Parameter 2</b>	The owner of the domain.
<b>Parameter 3</b>	The name of the domain.
<b>Probable Cause</b>	The specified spatial reference system is in use by a user-defined domain, and it cannot be modified.

## Errors and Warnings

<b>Error 1477</b>	<b>"The SRID %1 does not identify a geographic spatial reference system"</b>
<b>Constant</b>	SLERR_NOT_GEOGRAPHIC
<b>SAP Sybase Error Number</b>	3147
<b>SQL State</b>	2FW70
<b>SQL Code</b>	-1477L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The spatial reference system identifier.
<b>Probable Cause</b>	The methods ST_Lat() and ST_Long() can only be used for geographic spatial reference systems.
<b>Error 1478</b>	<b>"ST_Geometry arguments not supported by SQL function %1"</b>
<b>Constant</b>	SLERR_SPATIAL_IN_BUILTIN
<b>SAP Sybase Error Number</b>	3148
<b>SQL State</b>	2FW71
<b>SQL Code</b>	-1478L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the SQL function.
<b>Probable Cause</b>	The specified SQL function does not support geometry parameters.
<b>Error 1479</b>	<b>"An expression of type %1 is not union-compatible with type %2"</b>
<b>Constant</b>	SLERR_NOT_UNION_COMPAT
<b>SAP Sybase Error Number</b>	3149
<b>SQL State</b>	2FW72

<b>Error 1479</b>	<b>"An expression of type %1 is not union-compatible with type %2"</b>
<b>SQL Code</b>	-1479L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The type of expression 1.
<b>Parameter 2</b>	The type of expression 2.
<b>Probable Cause</b>	The two types cannot be combined, for example in a set operation such as UNION or in a SQL function such as COALESCE.
<b>Error 1480</b>	<b>"An internal error has occurred in the spatial library"</b>
<b>Constant</b>	SLERR_INTERNAL_ERROR
<b>SAP Sybase Error Number</b>	3150
<b>SQL State</b>	2FW73
<b>SQL Code</b>	-1480L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	An unexpected error occurred.
<b>Error 1482</b>	<b>"Curve contains nearly antipodal points %1 and %2 (near '%3')"</b>
<b>Constant</b>	SLERR_NEARLY_ANTIPODAL
<b>SAP Sybase Error Number</b>	3152
<b>SQL State</b>	2FW77
<b>SQL Code</b>	-1482L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

## Errors and Warnings

<b>Error 1482</b>	<b>"Curve contains nearly antipodal points %1 and %2 (near '%3)"</b>
<b>Parameter 1</b>	The first point.
<b>Parameter 2</b>	The second point.
<b>Parameter 3</b>	The value or method where the error was detected.
<b>Probable Cause</b>	A curve contains two points that are nearly antipodal. These define an ambiguous segment in a round-Earth spatial reference system.
<b>Error 1483</b>	<b>"LineString must contain at least 2 points (near '%1)"</b>
<b>Constant</b>	SLERR_LINESTRING_MIN_POINTS
<b>SAP Sybase Error Number</b>	3153
<b>SQL State</b>	2FW78
<b>SQL Code</b>	-1483L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The value or method where the error was detected.
<b>Probable Cause</b>	The linestring contains only a single point.
<b>Error 1484</b>	<b>"Value %1 out of range for coordinate %2 (SRS bounds [%3, %4] exceeded by more than 50%)"</b>
<b>Constant</b>	SLERR_OBJECT_OUT_OF_SRS_BOUNDS
<b>SAP Sybase Error Number</b>	3154
<b>SQL State</b>	2FW79
<b>SQL Code</b>	-1484L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The value is out of the defined bounds.

<b>Error 1484</b>	<b>"Value %1 out of range for coordinate %2 (SRS bounds [%3, %4] exceeded by more than 50%)"</b>
<b>Parameter 2</b>	The coordinate name that is out of range.
<b>Parameter 3</b>	The minimum value allowed by the spatial reference system.
<b>Parameter 4</b>	The maximum value allowed by the spatial reference system.
<b>Probable Cause</b>	The geometry contains a point outside of the bounds specified by the spatial reference system.

<b>Error 1485</b>	<b>"Invalid polygon: ring is not closed (near '%1')"</b>
<b>Constant</b>	SLERR_INVALID_POLY_RING_CLOSE
<b>SAP Sybase Error Number</b>	3155
<b>SQL State</b>	2FW80
<b>SQL Code</b>	-1485L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The value or method where the error was detected.
<b>Probable Cause</b>	One of the provided curves is not a closed ring.

<b>Error 1486</b>	<b>"Invalid polygon: ring has zero area (near '%1')"</b>
<b>Constant</b>	SLERR_INVALID_POLY_EMPTY_RING
<b>SAP Sybase Error Number</b>	3156
<b>SQL State</b>	2FW81
<b>SQL Code</b>	-1486L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The value or method where the error was detected.
<b>Probable Cause</b>	One of the provided rings has zero area and cannot be a valid polygon ring.

## Errors and Warnings

<b>Error 1487</b>	<b>"Invalid polygon: curve is not a ring"</b>
<b>Constant</b>	SLERR_INVALID_POLY_NON_RING
<b>SAP Sybase Error Number</b>	3157
<b>SQL State</b>	2FW82
<b>SQL Code</b>	-1487L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	One of the curves is not a ring and cannot be used to form a polygon.
<b>Error 1488</b>	<b>"Invalid polygon: ring is larger than allowed for SRID=%1 (near '%2')"</b>
<b>Constant</b>	SLERR_INVALID_POLY_RE_SIZE
<b>SAP Sybase Error Number</b>	3158
<b>SQL State</b>	2FW83
<b>SQL Code</b>	-1488L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The spatial reference system identifier.
<b>Parameter 2</b>	The value or method where the error was detected.
<b>Probable Cause</b>	One of the rings is larger than the specified spatial reference system supports.
<b>Error 1489</b>	<b>"Position %1 is invalid (should be between %2 and %3)"</b>
<b>Constant</b>	SLWARN_INVALID_POSITION
<b>SAP Sybase Error Number</b>	3159
<b>SQL State</b>	01F01
<b>SQL Code</b>	-1489L

<b>Error 1489</b>	"Position %1 is invalid (should be between %2 and %3)"
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The provided position.
<b>Parameter 2</b>	The minimum supported position.
<b>Parameter 3</b>	The maximum supported position.
<b>Probable Cause</b>	The provided position is not valid. It should be between the specified minimum and maximum.

## Messages 1490 through 1509

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1490</b>	"Polygon ring order has been reoriented"
<b>Constant</b>	SLWARN_POLYGON_RING_REORIENTED
<b>SAP Sybase Error Number</b>	3160
<b>SQL State</b>	01FW1
<b>SQL Code</b>	-1490L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The rings of a polygon were automatically reoriented on input. This is a notification only.
<b>Error 1491</b>	"CircularString with 3 points has been converted to use 5 points"
<b>Constant</b>	SLWARN_CIRCULARSTRING_3POINT
<b>SAP Sybase Error Number</b>	3161
<b>SQL State</b>	01FW2
<b>SQL Code</b>	-1491L

## Errors and Warnings

<b>Error 1491</b>	"CircularString with 3 points has been converted to use 5 points"
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A curve containing a CircularString with a 3-point circle has been converted to use a 5-point circle. This is a notification only.
<b>Error 1492</b>	<b>"Could not create a text index without external prefilter library on column \'%1\No message</b>
<b>Constant</b>	TEXT_INDEX_NO_PREFILTER
<b>SAP Sybase Error Number</b>	2652
<b>SQL State</b>	WT030
<b>SQL Code</b>	-1492L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the column for which external prefilter library is required.
<b>Probable Cause</b>	A text configuration object with a specified external prefilter library is required to build a text index on a binary column.
<b>Error 1493</b>	<b>"Could not create a text index with external prefilter library on column \'%1\No message</b>
<b>Constant</b>	TEXT_INDEX_PREFILTER_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	2644
<b>SQL State</b>	WT031
<b>SQL Code</b>	-1493L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1493</b>	<b>"Could not create a text index with external prefilter library on column \'%"1\No message</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the column for which external prefilter library is not allowed.
<b>Probable Cause</b>	A text configuration object without external prefilter library is required if any column in the text index is not of a binary or string data type.
<b>Error 1494</b>	<b>"Geometries with CircularString not supported (near \'%"1\'")"</b>
<b>Constant</b>	SLERR_CIRCULAR_METHOD
<b>SAP Sybase Error Number</b>	3162
<b>SQL State</b>	2FW84
<b>SQL Code</b>	-1494L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The method or context where the CircularString was detected.
<b>Probable Cause</b>	The method or operation does not support geometries with CircularString elements.
<b>Error 1495</b>	<b>"Geometries with CircularString are not supported in spatial reference system %1"</b>
<b>Constant</b>	SLERR_CIRCULAR_SRS
<b>SAP Sybase Error Number</b>	3163
<b>SQL State</b>	2FW85
<b>SQL Code</b>	-1495L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The SRID of the round-Earth spatial reference system.

## Errors and Warnings

<b>Error 1495</b>	<b>"Geometries with CircularString are not supported in spatial reference system %1"</b>
<b>Probable Cause</b>	The method does not support geometries with CircularString elements.
<b>Error 1496</b>	<b>"LOAD TABLE error: Invalid content encountered on row %1 of the data file"</b>
<b>Constant</b>	LOAD_TABLE_DATA_FILE_ERROR
<b>SAP Sybase Error Number</b>	3164
<b>SQL State</b>	WL017
<b>SQL Code</b>	-1496L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Line number of the data file where the invalid content occurred.
<b>Probable Cause</b>	The LOAD TABLE statement failed because a scanning error occurred on the indicated line of the data file specified in the statement. This error can occur if a line is truncated or if delimiters are missing.
<b>Error 1497</b>	<b>"The synchronization failed because MobiLink returned authentication status '%1' with value '%2'"</b>
<b>Constant</b>	MOBILINK_AUTHENTICATION_FAILED
<b>SAP Sybase Error Number</b>	3165
<b>SQL State</b>	28W17
<b>SQL Code</b>	-1497L
<b>ODBC 2 State</b>	28000
<b>ODBC 3 State</b>	28000
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	The authentication status number.
<b>Parameter 2</b>	The authentication value number.

<b>Error 1497</b>	"The synchronization failed because MobiLink returned authentication status '%1' with value '%2'"
<b>Probable Cause</b>	MobiLink returned an authentication status to the remote database indicating failure. The status and value numbers indicate why the authentication failed. For example, the password was invalid, or a synchronization is already in progress for this remote.

<b>Error 1498</b>	"'%1' is an unknown property"
<b>Constant</b>	UNKNOWN_PROPERTY
<b>SAP Sybase Error Number</b>	3166
<b>SQL State</b>	WU001
<b>SQL Code</b>	-1498L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The property name (or ID).
<b>Probable Cause</b>	The specified property is unknown.

<b>Error 1499</b>	"Invalid grid size %1"
<b>Constant</b>	SLERR_INVALID_GRID_SIZE
<b>SAP Sybase Error Number</b>	3167
<b>SQL State</b>	2FW86
<b>SQL Code</b>	-1499L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The grid size that is not valid.
<b>Probable Cause</b>	The specified grid size cannot be used with the spatial reference system. The grid size must be selected based on the bounds of space.

## Errors and Warnings

<b>Error 1500</b>	<b>"Invalid tolerance %1"</b>
<b>Constant</b>	SLERR_INVALID_TOLERANCE
<b>SAP Sybase Error Number</b>	3168
<b>SQL State</b>	2FW87
<b>SQL Code</b>	-1500L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The invalid tolerance.
<b>Probable Cause</b>	The specified tolerance cannot be used with the spatial reference system. The tolerance must be selected based on the bounds of space.
<b>Error 1501</b>	<b>"Invalid bounds for coordinate %1 (near \"BETWEEN %2 AND %3\")"</b>
<b>Constant</b>	SLERR_INVALID_BOUNDS
<b>SAP Sybase Error Number</b>	3169
<b>SQL State</b>	2FW88
<b>SQL Code</b>	-1501L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The coordinate with the invalid bounds.
<b>Parameter 2</b>	The first value of the invalid bounds.
<b>Parameter 3</b>	The second value of the invalid bounds.
<b>Probable Cause</b>	The specified coordinate bounds are not valid.
<b>Error 1502</b>	<b>"ST_MultiSurface contains elements with an invalid intersection (near \"%1\")"</b>
<b>Constant</b>	SLERR_INVALID_MULTISURF_I

<b>Error 1502</b>	<b>"ST_MultiSurface contains elements with an invalid intersection (near \"%1\")"</b>
<b>SAP Sybase Error Number</b>	3170
<b>SQL State</b>	2FW89
<b>SQL Code</b>	-1502L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The method or context where the invalid ST_MultiSurface was detected.
<b>Probable Cause</b>	The interiors of any two ST_Surface values in an ST_MultiSurface shall not intersect. The boundaries of any two elements in an ST_MultiSurface may intersect at a finite number of points (and not, for example, in a line segment).

<b>Error 1503</b>	<b>"Operation not supported for ST_GeomCollection with intersecting elements (near \"%1\")"</b>
<b>Constant</b>	SLERR_GEOM_COLL_INTERSECT
<b>SAP Sybase Error Number</b>	3171
<b>SQL State</b>	2FW90
<b>SQL Code</b>	-1503L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The method or context where the invalid ST_GeomCollection was detected.
<b>Probable Cause</b>	The ST_GeomCollection contains elements that intersect in a way that is not valid for an ST_MultiSurface. The operation is not supported for this kind of geometry.

## Errors and Warnings

<b>Error 1504</b>	"Error from external library: -%1: %2"
<b>Constant</b>	TEXT_USER_SPECIFIED_ERROR
<b>SAP Sybase Error Number</b>	2642
<b>SQL State</b>	WT032
<b>SQL Code</b>	-1504L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Error number specified by the external library
<b>Parameter 2</b>	Error message specified by the external library
<b>Probable Cause</b>	The external library used by the text index has reported the specified error.
<b>Error 1505</b>	<b>"Mirror server '\%"1\'' defined with type COPY does not include a parent definition"</b>
<b>Constant</b>	COPY_SERVER_NEEDS_PARENT
<b>SAP Sybase Error Number</b>	3172
<b>SQL State</b>	42WE6
<b>SQL Code</b>	-1505L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The mirror server name
<b>Probable Cause</b>	In a CREATE MIRROR SERVER statement for a server with type COPY, a parent server is not defined.
<b>Error 1506</b>	<b>"Unknown collation '\%"1\''</b>
<b>Constant</b>	UNKNOWN_COLLATION
<b>SAP Sybase Error Number</b>	3174
<b>SQL State</b>	WC018

<b>Error 1506</b>	"Unknown collation '%1'"
<b>SQL Code</b>	-1506L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name that is not a database collation.
<b>Probable Cause</b>	The specified collation is unknown. Ensure the name is spelled correctly.
<b>Error 1507</b>	<b>"The materialized view cannot be changed to immediate because the ON conditions refer to tables which are not in the null-supplying and preserved sides of the OUTER JOINs."</b>
<b>Constant</b>	UPDATABLE_MATVIEW_OUTERREFERENCE_ON_CONDITION
<b>SAP Sybase Error Number</b>	3175
<b>SQL State</b>	42WE7
<b>SQL Code</b>	-1507L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You attempted to change the refresh type to immediate for a materialized view whose definition contains an illegal ON condition.
<b>Error 1508</b>	<b>"The materialized view cannot be changed to immediate because at least one non-nullable column from any null-supplying side of an OUTER JOIN must exist in the SELECT list."</b>
<b>Constant</b>	UPDATABLE_MATVIEW_ISNOTNULL
<b>SAP Sybase Error Number</b>	3176
<b>SQL State</b>	42WE8
<b>SQL Code</b>	-1508L

<b>Error 1508</b>	<b>"The materialized view cannot be changed to immediate because at least one non-nullable column from any null-supplying side of an OUTER JOIN must exist in the SELECT list."</b>
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You attempted to change the refresh type to immediate for a materialized view whose SELECT list doesn't contain at least one non-nullable column for any null-supplying side of an OUTER JOIN.
<b>Error 1509</b>	<b>"The materialized view cannot be changed to immediate because the primary key columns of any table in the preserved side of an OUTER JOIN must exist in the SELECT list."</b>
<b>Constant</b>	UPDATABLE_MATVIEW_PK
<b>SAP Sybase Error Number</b>	3177
<b>SQL State</b>	42WE9
<b>SQL Code</b>	-1509L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	You attempted to change the refresh type to immediate for a materialized view whose SELECT list doesn't contain the primary key columns of any table in the preserved side of an OUTER JOIN.

## Messages 1510 through 1529

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1510</b>	<b>"Cannot specify range that excludes next value for sequence %1"</b>
<b>Constant</b>	INVALID_ALTER_SEQUENCE

<b>Error 1510</b>	"Cannot specify range that excludes next value for sequence %1"
<b>SAP Sybase Error Number</b>	3178
<b>SQL State</b>	52W54
<b>SQL Code</b>	-1510L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the sequence.
<b>Probable Cause</b>	You attempted to modify either the MINVAL or MAXVAL boundary of a sequence to a value that would make the next invocation of the nextval expression for the sequence invalid. If you want to change the range boundaries to these values, you must also specify a RESTART WITH clause and supply a value within the new range.

<b>Error 1511</b>	"Text indexes are not allowed across server types."
<b>Constant</b>	TEXT_NOT_ALLOWED_ACROSS_SERVERS
<b>SAP Sybase Error Number</b>	2596
<b>SQL State</b>	WT033
<b>SQL Code</b>	-1511L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Text indexes are not allowed across server types if the query is processed in full-passthrough mode.

<b>Error 1512</b>	"Text index with external prefilter cannot contain both binary and string columns"
<b>Constant</b>	TEXT_INDEX_MIXED_COLUMNS
<b>SAP Sybase Error Number</b>	2561

## Errors and Warnings

<b>Error 1512</b>	<b>"Text index with external prefilter cannot contain both binary and string columns"</b>
<b>SQL State</b>	WT034
<b>SQL Code</b>	-1512L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	One or more, but not all, of the columns specified for the text index is of type binary, and the text configuration object has a prefilter library specified. Text indexes using a prefilter library can contain either binary columns or string data type columns, but not both.
<b>Error 1513</b> <b>"Sysam License Manager initialization failed."</b>	
<b>Constant</b>	IQ_LICENSE_INITIALIZATION_FAILURE
<b>SAP Sybase Error Number</b>	2547
<b>SQL State</b>	0A005
<b>SQL Code</b>	-1513L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Sysam License Manager initialization failed.
<b>Error 1514</b> <b>"Failed to checkout a SAP Sybase IQ core license."</b>	
<b>Constant</b>	IQ_CORE_LICENSE_CHECKOUT_FAILURE
<b>SAP Sybase Error Number</b>	2546
<b>SQL State</b>	0A006
<b>SQL Code</b>	-1514L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

<b>Error 1514</b>	<b>"Failed to checkout a SAP Sybase IQ core license."</b>
<b>Probable Cause</b>	Sysam License Manager was unable to obtain a valid IQ_CORE license.
<b>Error 1515</b>	<b>"Support for spatial is not available for this CPU."</b>
<b>Constant</b>	SLERR_CPU_NEED_SSE
<b>SAP Sybase Error Number</b>	3179
<b>SQL State</b>	2FW91
<b>SQL Code</b>	-1515L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Spatial data support for 32-bit Windows and 32-bit Linux requires a CPU that supports the SSE2 instructions.
<b>Error 1516</b>	<b>"The intermediate point (%3) of the ST_CircularString segment between %1 and %2 is collinear with but not between the start and end points."</b>
<b>Constant</b>	SLERR_CIRC_COLLINEAR_MIDPOINT
<b>SAP Sybase Error Number</b>	3180
<b>SQL State</b>	2FF72
<b>SQL Code</b>	-1516L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The start point of the ST_CircularString segment
<b>Parameter 2</b>	The end point of the ST_CircularString segment
<b>Parameter 3</b>	The specified intermediate point of the ST_CircularString segment

## Errors and Warnings

<b>Error 1516</b>	<b>"The intermediate point (%3) of the ST_CircularString segment between %1 and %2 is collinear with but not between the start and end points."</b>
<b>Probable Cause</b>	When the intermediate point of a ST_CircularString segment is collinear with the start and end point the result is interpreted as a straight line between the start and the end point. In this case, the intermediate point must be located on the line segment between the start and end point.
<b>Error 1517</b>	<b>"Logical Server \"%1\" not found"</b>
<b>Constant</b>	LOGICAL_SERVER_NOT_FOUND
<b>SAP Sybase Error Number</b>	2545
<b>SQL State</b>	WQ001
<b>SQL Code</b>	-1517L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the logical server.
<b>Probable Cause</b>	The named logical server was not found in the database.
<b>Error 1518</b>	<b>"Logical Server Policy \"%1\" does not allow coordinator membership in logical servers."</b>
<b>Constant</b>	LS_COORD_MEMBERSHIP_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	2543
<b>SQL State</b>	WQ002
<b>SQL Code</b>	-1518L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the logical server policy.
<b>Probable Cause</b>	Logical server policy does not allow coordinator as a member of logical server.

<b>Error 1519</b>	<b>"Cannot determine the logical server context due to overlapping logical server memberships for login policy \%"."</b>
<b>Constant</b>	LS_MEMBERSHIP_OVERLAP_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	2541
<b>SQL State</b>	WQ003
<b>SQL Code</b>	-1519L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the login policy.
<b>Probable Cause</b>	Cannot determine the logical server context for named login policy. Specify the logical server in the connection string.
<b>Error 1520</b>	<b>"Cannot recreate an already existing logical server membership."</b>
<b>Constant</b>	LS_MEMBERSHIP_ALREADY_EXISTS
<b>SAP Sybase Error Number</b>	2539
<b>SQL State</b>	WQ004
<b>SQL Code</b>	-1520L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Multiplex server which is to be added as a member is already a member of logical server.
<b>Error 1521</b>	<b>"Cannot drop a non-existing logical server membership."</b>
<b>Constant</b>	LS_MEMBERSHIP_NOT_FOUND
<b>SAP Sybase Error Number</b>	2537
<b>SQL State</b>	WQ005
<b>SQL Code</b>	-1521L

## Errors and Warnings

<b>Error 1521</b>	"Cannot drop a non-existing logical server membership."
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Multiplex server membership about to be dropped was not found.
<b>Error 1522</b>	"Database needs to be upgraded to support the use of external libraries with text indexes."
<b>Constant</b>	TEXT_EXT_UPGRADE_REQUIRED
<b>SAP Sybase Error Number</b>	2530
<b>SQL State</b>	WT035
<b>SQL Code</b>	-1522L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The current database does not have catalog support for prefilter and term breaker external libraries. To use this feature, upgrade your database to the most recent version.
<b>Error 1523</b>	"Cannot reassign logical server "%1' to login policy "%2'."
<b>Constant</b>	LS_LP_ASSIGNMENT_EXISTS
<b>SAP Sybase Error Number</b>	2507
<b>SQL State</b>	WQ006
<b>SQL Code</b>	-1523L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the logical server.
<b>Parameter 2</b>	The name of the login policy.

<b>Error 1523</b>	<b>"Cannot reassign logical server "%1' to login policy "%2'."</b>
<b>Probable Cause</b>	Logical Server - Login Policy assignment already exists.
<b>Error 1524</b>	<b>"Cannot drop a non-existing assignment between logical server "%1' and login policy "%2'."</b>
<b>Constant</b>	LS_LP_NON_EXISTING_ASSIGNMENT
<b>SAP Sybase Error Number</b>	2508
<b>SQL State</b>	WQ007
<b>SQL Code</b>	-1524L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the logical server.
<b>Parameter 2</b>	The name of the login policy.
<b>Probable Cause</b>	Logical Server - Login Policy assignment does not exist.
<b>Error 1525</b>	<b>"Cannot perform specified operation, number of administrators for role "%1' falls below min_role_admins option value"</b>
<b>Constant</b>	MIN_ROLE_ADMIN_VIOLATION
<b>SAP Sybase Error Number</b>	3181
<b>SQL State</b>	55W36
<b>SQL Code</b>	-1525L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the role that violates minimum number of administrators condition

<b>Error 1525</b>	<b>"Cannot perform specified operation, number of administrators for role "%1' falls below min_role_admins option value"</b>
<b>Probable Cause</b>	Specified operation cannot be performed because it will make the number of administrators for the specified role go below the threshold value set through database option min_role_admins.
<b>Error 1526</b>	<b>"Text index %1 cannot be used with text procedure %2"</b>
<b>Constant</b>	TEXT_INVALID_INDEX_FOR_PROC
<b>SAP Sybase Error Number</b>	2010
<b>SQL State</b>	WT036
<b>SQL Code</b>	-1526L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the text index.
<b>Parameter 2</b>	The name of the procedure for which the specified index is invalid.
<b>Probable Cause</b>	The specified text procedure cannot be used with the text index. The text procedure charset has to correspond to the charset of the text index it is accessing.
<b>Error 1527</b>	<b>"Task "%1' is not allowed"</b>
<b>Constant</b>	SYSPRIV_CREATION_NOT_ALLLOWED
<b>SAP Sybase Error Number</b>	3182
<b>SQL State</b>	28W18
<b>SQL Code</b>	-1527L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the internal task that was provided by the user.

<b>Error 1527</b>	<b>"Task '%1' is not allowed"</b>
<b>Probable Cause</b>	Creation of system privilege is an internal task, allowed only during database creation or upgrade.
<b>Error 1528</b>	<b>"No more role grant permitted"</b>
<b>Constant</b>	ROLE_GRANT_ID_NOT_AVAILABLE
<b>SAP Sybase Error Number</b>	3183
<b>SQL State</b>	28W19
<b>SQL Code</b>	-1528L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Maximum limit for role grants has been reached. No more role grants are permitted. Remove some role grants and try again.
<b>Error 1529</b>	<b>"Outer reference not permitted in DML derived table"</b>
<b>Constant</b>	SELECT_DML_OUTER_REFERENCE
<b>SAP Sybase Error Number</b>	3184
<b>SQL State</b>	42U09
<b>SQL Code</b>	-1529L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Outer references are not permitted in derived tables based on INSERT, UPDATE, DELETE, or MERGE statements. These derived tables may only appear in subqueries that are uncorrelated.

## Messages 1530 through 1549

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1530</b>	<b>"Format "%1' is not supported in the UNLOAD statement"</b>
<b>Constant</b>	UNSUPPORTED_UNLOAD_FORMAT
<b>SAP Sybase Error Number</b>	3185
<b>SQL State</b>	WL018
<b>SQL Code</b>	-1530L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>19</i> on page 2
<b>Parameter 1</b>	The specified format.
<b>Probable Cause</b>	An unsupported file format was specified for the UNLOAD statement.

<b>Error 1531</b>	<b>"Geometry expressions cannot be used in the ORDER BY specification (near "%1")"</b>
<b>Constant</b>	SLERR_GEOM_ORDER_BY
<b>SAP Sybase Error Number</b>	3186
<b>SQL State</b>	2FW92
<b>SQL Code</b>	-1531L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The geometry expression.
<b>Probable Cause</b>	Geometry expressions cannot be used in the ORDER BY clause. The ST_LinearHash() method may be used in the ORDER BY specification to order geometry values using the same rules used for spatial indexes, or a conversion method such as ST_AsText() may be used to order the rows by their string representation.

<b>Error 1532</b>	<b>"Failed to transform point %1 (error %2)"</b>
<b>Constant</b>	SLERR_TRANSFORM_POINT_FAIL
<b>SAP Sybase Error Number</b>	3187
<b>SQL State</b>	2FF17
<b>SQL Code</b>	-1532L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The point that could not be transformed.
<b>Parameter 2</b>	The error code from the projection library.
<b>Probable Cause</b>	An error occurred when performing a transform from one spatial reference system to another. This error may occur if a point in the first geometry is outside of the bounds for the transform definition. The error may also be reported for particular transform definitions. The integer error code from the transform library may be used to diagnose the transform definition.

<b>Error 1533</b>	<b>"Logical server policy \\"%1\\" not found"</b>
<b>Constant</b>	LS_POLICY_NOT_FOUND
<b>SAP Sybase Error Number</b>	2445
<b>SQL State</b>	WQ008
<b>SQL Code</b>	-1533L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the logical server policy.
<b>Probable Cause</b>	The named logical server policy was not found in the database.

<b>Error 1534</b>	<b>"Logical server operations not allowed on a simplex database."</b>
<b>Constant</b>	LS_OPS_DISALLOWED_ON_SIMPLEX

## Errors and Warnings

<b>Error 1534</b>	"Logical server operations not allowed on a simplex database."
<b>SAP Sybase Error Number</b>	2443
<b>SQL State</b>	WQ009
<b>SQL Code</b>	-1534L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Logical server operations are disallowed on a simplex database.
<b>Error 1535</b>	<b>"System Privileges and Roles feature is not supported in this database"</b>
<b>Constant</b>	ROLES_NOT_SUPPORTED
<b>SAP Sybase Error Number</b>	3188
<b>SQL State</b>	0AW27
<b>SQL Code</b>	-1535L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The current database is an older database and does not have catalog support for System Privileges and Roles feature. To use this feature, upgrade your database to the most recent version.
<b>Error 1536</b>	<b>"Invalid user ID or role name '%1' specified"</b>
<b>Constant</b>	INVALID_USER_ROLE_NAME
<b>SAP Sybase Error Number</b>	3189
<b>SQL State</b>	28000
<b>SQL Code</b>	-1536L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1536</b>	<b>"Invalid user ID or role name '%1' specified"</b>
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Name of the invalid user or role that was specified.
<b>Probable Cause</b>	You supplied an invalid name for a user or role.
<b>Error 1537</b>	<b>"Role \"%1\" already exists"</b>
<b>Constant</b>	ROLE_ALREADY_EXISTS
<b>SAP Sybase Error Number</b>	3190
<b>SQL State</b>	28000
<b>SQL Code</b>	-1537L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the role.
<b>Probable Cause</b>	An attempt was made to create a role that already exists in the database.
<b>Error 1538</b>	<b>"User or Role ID '%1' does not exist"</b>
<b>Constant</b>	UNKNOWN_USER_ROLE_ID
<b>SAP Sybase Error Number</b>	3191
<b>SQL State</b>	28000
<b>SQL Code</b>	-1538L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Name of the user or role that could not be found.
<b>Probable Cause</b>	You used a user or role ID that does not exist.

## Errors and Warnings

<b>Error 1539</b>	<b>"Use of WITH NO SYSTEM PRIVILEGE INHERITANCE option is not allowed with %1"</b>
<b>Constant</b>	INVALID_ROLE_GRANT_OPTION
<b>SAP Sybase Error Number</b>	3192
<b>SQL State</b>	28000
<b>SQL Code</b>	-1539L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	The name of the role.
<b>Probable Cause</b>	WITH NO SYSTEM PRIVILEGE INHERITANCE option can be specified only with user defined roles corresponding to legacy non-inheritable authorities.
<b>Error 1540</b>	<b>"Operation would cause a role cycle"</b>
<b>Constant</b>	ROLE_CYCLE
<b>SAP Sybase Error Number</b>	3193
<b>SQL State</b>	28000
<b>SQL Code</b>	-1540L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	You attempted to grant role to a grantee that would result in a grantee belonging to itself. Role membership may be direct or indirect.
<b>Error 1541</b>	<b>"Specified System Privilege '%1' is Invalid"</b>
<b>Constant</b>	INVALID_SYSTEM_PRIVILEGE
<b>SAP Sybase Error Number</b>	3194
<b>SQL State</b>	28000
<b>SQL Code</b>	-1541L

<b>Error 1541</b>	<b>"Specified System Privilege '%1' is Invalid"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	The name of the system privilege.
<b>Probable Cause</b>	System Privilege specified does not exist in the database.
<b>Error 1542</b>	<b>"Invalid logical server combination for ADD or SET clause."</b>
<b>Constant</b>	LS_INVALID_COMBINATION_FOR_ADD_SET
<b>SAP Sybase Error Number</b>	2442
<b>SQL State</b>	WQ010
<b>SQL Code</b>	-1542L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The specified logical server combination for ADD or SET clause of ALTER LOGIN POLICY is invalid. SERVER and NONE cannot be specified with ADD clause. SERVER and NONE cannot be specified with any other logical server.
<b>Error 1543</b>	<b>"Logical server configuration of the user's login policy does not allow access to the current multiplex server."</b>
<b>Constant</b>	CONNECTION_DISALLOWED_BY_LOGIN_POLICY_LS_CONFIG
<b>SAP Sybase Error Number</b>	2428
<b>SQL State</b>	WQ011
<b>SQL Code</b>	-1543L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

## Errors and Warnings

<b>Error 1543</b>	<b>"Logical server configuration of the user's login policy does not allow access to the current multiplex server."</b>
<b>Probable Cause</b>	Logical server configuration of the user's login policy does not allow access to the current multiplex server. You may need to change logical server configuration of user's login policy to allow access to the current multiplex server.
<b>Error 1544</b>	<b>"Login disallowed. User does not have sufficient authority to access SERVER logical server."</b>
<b>Constant</b>	CONNECTION_DISALLOWED_TO_SERVER_LS
<b>SAP Sybase Error Number</b>	2423
<b>SQL State</b>	WQ012
<b>SQL Code</b>	-1544L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Accessing SERVER logical server requires either DBA or MULTIPLEX ADMIN authority.
<b>Error 1545</b>	<b>"Cannot create logical server named '%1'. Choose another name for logical server."</b>
<b>Constant</b>	INVALID_LS_NAME
<b>SAP Sybase Error Number</b>	2422
<b>SQL State</b>	WQ013
<b>SQL Code</b>	-1545L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of logical server.
<b>Probable Cause</b>	Logical server names ALL, NONE, SERVER, OPEN, DEFAULT and COORDINATOR are reserved for the current or future releases.

<b>Error 1546</b>	<b>"Cannot drop Multiplex server '%1' as it is part of a Logical Server. Use the \"WITH DROP MEMBERSHIP\" clause."</b>
<b>Constant</b>	IQ_MPX_SRV_IS_LS_MEMBER
<b>SAP Sybase Error Number</b>	2387
<b>SQL State</b>	WQ014
<b>SQL Code</b>	-1546L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of multiplex server.
<b>Probable Cause</b>	If an MPX server is part of a Logical Server then the DROP MPX command should have WITH MEMBERSHIP clause to drop it.
<b>Error 1547</b>	<b>"Cannot drop Multiplex server '%1' without dropping all the logical servers as it will convert the Multiplex to Simplex. Use the \"WITH DROP LOGICAL SERVER\" clause."</b>
<b>Constant</b>	IQ_MPX_SRV_IS_LAST_SEC_MEMBER
<b>SAP Sybase Error Number</b>	2371
<b>SQL State</b>	WQ015
<b>SQL Code</b>	-1547L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of multiplex server.
<b>Probable Cause</b>	If dropping the secondary server will result in conversion from MPX to SPX then all the user created logical servers should be dropped.

## Errors and Warnings

<b>Error 1548</b>	<b>"Cannot drop Multiplex server '%1'. This is not the last secondary server. Remove the \"WITH DROP LOGICAL SERVER\" clause."</b>
<b>Constant</b>	IQ_MPX_SRV_IS_NOT_LAST_SEC_MEMBER
<b>SAP Sybase Error Number</b>	2370
<b>SQL State</b>	WQ016
<b>SQL Code</b>	-1548L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of multiplex server.
<b>Probable Cause</b>	WITH DROP LOGICAL SERVER clause should be used ONLY when dropping the last secondary Server.
<b>Error 1549</b>	<b>"Cannot set the '%1' option as Login Policy option '%2' is set to off."</b>
<b>Constant</b>	LS_LP MODIFY_OPT_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	2369
<b>SQL State</b>	WQ017
<b>SQL Code</b>	-1549L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the temporary option
<b>Parameter 2</b>	The name of the Login Policy Option.
<b>Probable Cause</b>	If an option of the login policy is set to off then user cannot set the temporary option which is directly depending on it. For example, if the login policy option DQP_ENABLED is set to Off, then the temporary option DQP_ENABLED cannot be set to On.

## Messages 1550 through 1569

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1550</b>	<b>"Overriding ROOT login policy options for logical servers is not allowed."</b>
<b>Constant</b>	LS_ROOT_LP_OVERRIDE_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	2368
<b>SQL State</b>	WQ018
<b>SQL Code</b>	-1550L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A user cannot override login policy options of ROOT login policy for logical servers.
<b>Error 1551</b>	<b>"Login redirection is required to complete the connection, but it is not supported by the client"</b>
<b>Constant</b>	LOGIN_REDIRECTION_REQUIRED
<b>SAP Sybase Error Number</b>	3195
<b>SQL State</b>	08WA6
<b>SQL Code</b>	-1551L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The connection needs to be redirected to another server, but the version of the client library does not support login redirection. You must upgrade the client library to use login redirection. Alternatively, you can connect to a different server or change the logical server configuration.

## Errors and Warnings

<b>Error 1552</b>	"Invalid text index type for the materialized view"
<b>Constant</b>	TEXT_MV_INVALID_COMBO
<b>SAP Sybase Error Number</b>	3196
<b>SQL State</b>	WT037
<b>SQL Code</b>	-1552L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Text index with the specified refresh type cannot be created on the materialized view. Only IMMEDIATE REFRESH text indexes are allowed on materialized views.
<b>Error 1553</b>	"Cannot perform specified operation, set user condition violated"
<b>Constant</b>	SET_USER_VIOLATION
<b>SAP Sybase Error Number</b>	3197
<b>SQL State</b>	55W37
<b>SQL Code</b>	-1553L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Specified operation cannot be performed because it will invalidate the on going SET USER statements in the database.
<b>Error 1554</b>	"Specified LDAP server '%1' is not found"
<b>Constant</b>	UNKNOWN_LDAP_SERVER
<b>SAP Sybase Error Number</b>	3198
<b>SQL State</b>	28000
<b>SQL Code</b>	-1554L
<b>ODBC 2 State</b>	ERROR

<b>Error 1554</b>	<b>"Specified LDAP server "%1' is not found"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The name of the LDAP server.
<b>Probable Cause</b>	The LDAP server specified does not exist in the database.

<b>Error 1555</b>	<b>"Statement not allowed on text index for a materialized view"</b>
<b>Constant</b>	TEXT_MV_TIND_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	3199
<b>SQL State</b>	WT038
<b>SQL Code</b>	-1555L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You cannot use REFRESH TEXT INDEX or TRUNCATE TEXT INDEX on a text index that is created for a materialized view. You cannot alter the text index to use a different refresh type.

<b>Error 1556</b>	<b>"External environment failed to start and establish a connection within the %1 second timeout"</b>
<b>Constant</b>	EXTENV_START_TIMED_OUT
<b>SAP Sybase Error Number</b>	3200
<b>SQL State</b>	WP017
<b>SQL Code</b>	-1556L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The amount of time in seconds the server will wait for the external environment to start and establish a connection.

## Errors and Warnings

<b>Error 1556</b>	<b>"External environment failed to start and establish a connection within the %1 second timeout"</b>
<b>Probable Cause</b>	The External Environment took too long to start up and establish a connection with the server. The problem may be due to the system being over stressed or incorrectly configured.
<b>Error 1557</b>	<b>"External environment cannot be started during database startup"</b>
<b>Constant</b>	EXTENV_START_ON_STARTUP
<b>SAP Sybase Error Number</b>	3201
<b>SQL State</b>	WP018
<b>SQL Code</b>	-1557L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	An external environment cannot be started while a database is starting up. Wait for the database startup to complete before attempting to start an external environment.
<b>Error 1558</b>	<b>"Specified user "%1' is a role"</b>
<b>Constant</b>	CAN_NOT_DROP_ROLE
<b>SAP Sybase Error Number</b>	3202
<b>SQL State</b>	28000
<b>SQL Code</b>	-1558L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Name of the user being dropped.
<b>Probable Cause</b>	You attempted to drop a role. Use DROP ROLE statement.

<b>Error 1559</b>	<b>"Specified role '%1' is not a user extended as role"</b>
<b>Constant</b>	NOT_AN_EXTENDED_USER
<b>SAP Sybase Error Number</b>	3203
<b>SQL State</b>	28000
<b>SQL Code</b>	-1559L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Name of the role being dropped.
<b>Probable Cause</b>	The role name provided is not a user extended as role. Use of FROM USER clause is not allowed in such cases.
<b>Error 1560</b>	<b>"Specified role '%1' is a user extended as role"</b>
<b>Constant</b>	AN_EXTENDED_USER
<b>SAP Sybase Error Number</b>	3204
<b>SQL State</b>	28000
<b>SQL Code</b>	-1560L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Name of the role being dropped.
<b>Probable Cause</b>	Specified role is a user extended as role but FROM USER clause is not specified in DROP ROLE command.
<b>Error 1561</b>	<b>"Use of WITH DROP OBJECTS is not allowed with '%1'"</b>
<b>Constant</b>	WITH_DROP_OBJECTS_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	3205
<b>SQL State</b>	28000
<b>SQL Code</b>	-1561L

## Errors and Warnings

<b>Error 1561</b>	<b>"Use of WITH DROP OBJECTS is not allowed with "%1"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Name of the role being dropped.
<b>Probable Cause</b>	Use of WITH DROP OBJECTS is not allowed with user extended as role.
<b>Error 1562</b>	<b>"The role '%1' was not dropped because it is granted to other users or roles. Use the 'WITH REVOKE' option to drop it."</b>
<b>Constant</b>	CONTAINS_PRIV_GRANTS
<b>SAP Sybase Error Number</b>	3206
<b>SQL State</b>	28000
<b>SQL Code</b>	-1562L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Name of the role being dropped.
<b>Probable Cause</b>	The role being dropped has been granted to other users or roles with WITH NO ADMIN OPTION or with WITH ADMIN OPTION. A role can be dropped when either all of its grants are with WITH ADMIN ONLY OPTION or WITH REVOKE option is specified in DROP ROLE command. Either revoke all such grants or use WITH REVOKE option for DROP ROLE.
<b>Error 1563</b>	<b>"Cannot drop a role that owns sequences in runtime server"</b>
<b>Constant</b>	USER_OWNS_SEQUENCES
<b>SAP Sybase Error Number</b>	3207
<b>SQL State</b>	55W38
<b>SQL Code</b>	-1563L
<b>ODBC 2 State</b>	42000

<b>Error 1563</b>	<b>"Cannot drop a role that owns sequences in runtime server"</b>
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to drop a role that owns sequences while using the runtime server. This operation would result in dropping sequences. The runtime server cannot drop sequences.
<b>Error 1564</b>	<b>"Cannot drop a role that owns events in runtime server"</b>
<b>Constant</b>	USER_OWNS_EVENTS
<b>SAP Sybase Error Number</b>	3208
<b>SQL State</b>	55W39
<b>SQL Code</b>	-1564L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to drop a role that owns events while using the runtime server. This operation would result in dropping events. The runtime server cannot drop events.
<b>Error 1565</b>	<b>"Cannot drop a role that owns web services in runtime server"</b>
<b>Constant</b>	USER_OWNS_WEB_SERVICES
<b>SAP Sybase Error Number</b>	3209
<b>SQL State</b>	55W40
<b>SQL Code</b>	-1565L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to drop a role that owns web services while using the runtime server. This operation would result in dropping web services. The runtime server cannot drop web services.

## Errors and Warnings

<b>Error 1566</b>	<b>"Cannot drop a role that owns external environment objects in runtime server"</b>
<b>Constant</b>	USER_OWNS_EXTERNENVOBJECTS
<b>SAP Sybase Error Number</b>	3210
<b>SQL State</b>	55W41
<b>SQL Code</b>	-1566L
<b>ODBC 2 State</b>	42000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to drop a role that owns external environment objects while using the runtime server. This operation would result in dropping external environment objects. The runtime server cannot drop external environment objects.
<b>Error 1567</b>	<b>"External environment cannot be started, external process terminated on start up"</b>
<b>Constant</b>	EXTENV_PID_NOT_FOUND
<b>SAP Sybase Error Number</b>	3211
<b>SQL State</b>	WP019
<b>SQL Code</b>	-1567L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The request to start an external environment could not be completed due to the fact that the external process terminated on start up. This problem is usually due to a client configuration issue.
<b>Error 1568</b>	<b>"Unable to generate a logical server ID."</b>
<b>Constant</b>	LS_MAX_ID_LIMIT_REACHED
<b>SAP Sybase Error Number</b>	2365

<b>Error 1568</b>	"Unable to generate a logical server ID."
<b>SQL State</b>	WQ019
<b>SQL Code</b>	-1568L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Last generated logical server ID reached maximum limit. The database catalog needs to be rebuilt.
<b>Error 1569</b>	"LDAP Server \%"1%" already exists"
<b>Constant</b>	LDAPSERVER_ALREADY_EXISTS
<b>SAP Sybase Error Number</b>	3212
<b>SQL State</b>	WW202
<b>SQL Code</b>	-1569L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the LDAP Server.
<b>Probable Cause</b>	An attempt was made to create an LDAP server that already exists in the database.

## Messages 1570 through 1589

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1570</b>	"Attempt to allocate memory for LDAP server \%"1%" failed."
<b>Constant</b>	LDAPSERVER_ALLOC_FAILED
<b>SAP Sybase Error Number</b>	3213
<b>SQL State</b>	WW203
<b>SQL Code</b>	-1570L

## Errors and Warnings

<b>Error 1570</b>	"Attempt to allocate memory for LDAP server \"%1\" failed."
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the LDAP Server.
<b>Probable Cause</b>	An attempt to allocate memory for an LDAP Server class object failed.
<b>Error 1571</b>	"The attempt to drop LDAP server \"%1\" failed, suspend the server to drop it."
<b>Constant</b>	INVALID_STATE_CHANGE
<b>SAP Sybase Error Number</b>	3214
<b>SQL State</b>	WW204
<b>SQL Code</b>	-1571L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the LDAP Server.
<b>Probable Cause</b>	An attempt to drop an LDAP Server failed because it was in the READY or ACTIVE state. Use WITH SUSPEND to change state before dropping server.
<b>Error 1572</b>	"LDAP User Authentication feature is not supported in this database"
<b>Constant</b>	LDAPUA_NOT_SUPPORTED
<b>SAP Sybase Error Number</b>	3215
<b>SQL State</b>	WW205
<b>SQL Code</b>	-1572L
<b>ODBC 2 State</b>	ERROR

<b>Error 1572</b>	<b>"LDAP User Authentication feature is not supported in this database"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The current database is an older database and does not have catalog support for LDAP User Authentication feature. To use this feature, upgrade your database to the most recent version.
<b>Error 1573</b>	<b>"MIRROR server class is not supported for SAP Sybase IQ databases"</b>
<b>Constant</b>	OMNI_NO_MIRROR_FOR_IQ
<b>SAP Sybase Error Number</b>	3216
<b>SQL State</b>	WO029
<b>SQL Code</b>	-1573L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to create a remote data access server of type MIRROR while connected to an SAP Sybase IQ database. The MIRROR server class is not supported for SAP Sybase IQ databases.
<b>Error 1574</b>	<b>"You must upgrade your database in order to use the MIRROR server class"</b>
<b>Constant</b>	OMNI_MIRROR_NEEDS_UPGRADE
<b>SAP Sybase Error Number</b>	3217
<b>SQL State</b>	WO030
<b>SQL Code</b>	-1574L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

## Errors and Warnings

<b>Error 1574</b>	<b>"You must upgrade your database in order to use the MIRROR server class"</b>
<b>Probable Cause</b>	You attempted to create a remote data access server of type mirror while connected to a database that was created with older software. You must upgrade your database in order to make use of the mirror server class.
<b>Error 1575</b>	<b>"Database upgrade not possible; the name or ID of new IQ_SHARED_TEMP dbspace is already in use."</b>
<b>Constant</b>	IQ_SHTEMP_DBSPACE_CONFLICT
<b>SAP Sybase Error Number</b>	2364
<b>SQL State</b>	WQ020
<b>SQL Code</b>	-1575L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	An attempt to upgrade a database failed. Retry upgrade of the database when no existing dbspace is using the name or ID of the IQ_SHARED_TEMP dbspace.
<b>Error 1576</b>	<b>"LDAP server \"%1\" is in use by login policy \"%2\"."</b>
<b>Constant</b>	LDAPSERVER_IN_USE
<b>SAP Sybase Error Number</b>	3218
<b>SQL State</b>	WW206
<b>SQL Code</b>	-1576L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the LDAP server.
<b>Parameter 2</b>	The name of the login policy.

<b>Error 1576</b>	<b>"LDAP server '\"%1\" is in use by login policy '\"%2\"."</b>
<b>Probable Cause</b>	The named login policy references the LDAP server. The login policy must be changed to avoid referencing the LDAP server before the LDAP server can be dropped. Otherwise, use DROP LDAP SERVER <server name> WITH DROP ALL REFERENCES to remove any references in login policies to the LDAP server.
<b>Error 1577</b>	<b>"Invalid error raised by user-defined function: (%1) %2."</b>
<b>Constant</b>	EMSG_UDF_RAISED_INVALID_ERROR
<b>SAP Sybase Error Number</b>	3219
<b>SQL State</b>	QFA67
<b>SQL Code</b>	-1577L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Invalid error code used by UDF.
<b>Parameter 2</b>	Error message provided by UDF to accompany UDF SQLCODE.
<b>Probable Cause</b>	An error was raised by a user-defined function that is outside reserved range.
<b>Error 1578</b>	<b>"Table parameterized functions are not allowed across server types."</b>
<b>Constant</b>	TPF_NOT_ALLOWED_ACROSS_SERVERS
<b>SAP Sybase Error Number</b>	3220
<b>SQL State</b>	WO009
<b>SQL Code</b>	-1578L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Table parameterized functions are not allowed across server types if a query is not processed in full-passthrough mode.

## Errors and Warnings

<b>Error 1579</b>	<b>"External procedures or functions are not allowed across server types."</b>
<b>Constant</b>	PROC_NOT_ALLOWED_ACROSS_SERVERS
<b>SAP Sybase Error Number</b>	3221
<b>SQL State</b>	WO031
<b>SQL Code</b>	-1579L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	External procedure or function calls are not allowed across server types if the query is not processed in full-passthrough mode.
<b>Error 1580</b>	<b>"Failed to load the MobiLink client support libraries."</b>
<b>Constant</b>	COULD_NOT_LOAD_SYNC_LIBRARY
<b>SAP Sybase Error Number</b>	3222
<b>SQL State</b>	WW207
<b>SQL Code</b>	-1580L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>19</i> on page 2
<b>Probable Cause</b>	To use the SYNCHRONIZE command, a MobiLink client must be installed on the same computer where the database server is running.
<b>Error 1581</b>	<b>"Database name must be specified when connecting to a cloud database server"</b>
<b>Constant</b>	NO_DEFAULT_DATABASE
<b>SAP Sybase Error Number</b>	3223
<b>SQL State</b>	08WA7
<b>SQL Code</b>	-1581L
<b>ODBC 2 State</b>	08001

<b>Error 1581</b>	<b>"Database name must be specified when connecting to a cloud database server"</b>
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	When connecting to a cloud database server, a database name must be specified by the connection string. Cloud database servers do not have a default database.
<b>Error 1582</b>	<b>"Server name can only be specified when connecting to a cloud database server with NODETYPE=DIRECT"</b>
<b>Constant</b>	SERVER_NAME_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	3224
<b>SQL State</b>	08WA8
<b>SQL Code</b>	-1582L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	When connecting to a cloud database server, specifying a server name on the connection string is only allowed for NODETYPE=DIRECT. When using other NODETYPE values to connect to a cloud database server, specifying the server name is not allowed. Typically, for connections to a cloud database server the HOST connection parameter or HOST protocol option is used to specify the address of one or more cloud database servers.
<b>Error 1583</b>	<b>"Cannot upgrade the database. The database can be upgraded only after starting the coordinator in single node mode."</b>
<b>Constant</b>	IQ_MPX_MUST_BE_SINGLE_NODE
<b>SAP Sybase Error Number</b>	3225
<b>SQL State</b>	WQ021
<b>SQL Code</b>	-1583L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1583</b>	" <b>Cannot upgrade the database. The database can be upgraded only after starting the coordinator in single node mode.</b> "
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	In order to run ALTER DATABASE UPGRADE on the database, the coordinator must be started in single node mode using the '-iqmpx_sn 1' server startup option.
<b>Error 1584</b>	<b>"Unable to load the dbrsakp shared object"</b>
<b>Constant</b>	RSA_LOAD_FAILED
<b>SAP Sybase Error Number</b>	3226
<b>SQL State</b>	08WA9
<b>SQL Code</b>	-1584L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The server was unable to load the dbrsakp DLL on Windows platforms or the libdbrsakp shared object on Unix platforms.
<b>Error 1585</b>	<b>"Invalid tool name or admin user for generating security token"</b>
<b>Constant</b>	INVALID_TOOL_NAME_OR_ADMIN_USER
<b>SAP Sybase Error Number</b>	3227
<b>SQL State</b>	08WB1
<b>SQL Code</b>	-1585L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The tool name or admin user supplied is invalid for generating a security token.

<b>Error 1586</b>	<b>"Error modifying refresh type for text index \'%1\' on materialized view \'%2\No message"</b>
<b>Constant</b>	TEXT_INDEX_MV_ALTER_ERROR
<b>SAP Sybase Error Number</b>	3228
<b>SQL State</b>	WT039
<b>SQL Code</b>	-1586L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the text index.
<b>Parameter 2</b>	The name of the materialized view.
<b>Probable Cause</b>	Internal error encountered while changing the refresh type of the text index dependent on the materialized view.

<b>Error 1587</b>	<b>"Storing certificates is not supported for this database"</b>
<b>Constant</b>	CERTIFICATES_NOT_SUPPORTED
<b>SAP Sybase Error Number</b>	3229
<b>SQL State</b>	55W42
<b>SQL Code</b>	-1587L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The current database does not have catalog support for certificates. To use this feature, upgrade your database to the most recent version.

<b>Error 1588</b>	<b>"The specified certificate is not valid"</b>
<b>Constant</b>	INVALID_CERTIFICATE
<b>SAP Sybase Error Number</b>	3230
<b>SQL State</b>	55W43
<b>SQL Code</b>	-1588L

## Errors and Warnings

<b>Error 1588</b>	<b>"The specified certificate is not valid"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The certificate value does not represent a valid certificate.

<b>Error 1589</b>	<b>"Certificate "%1' not found"</b>
<b>Constant</b>	CERTIFICATE_NOT_FOUND
<b>SAP Sybase Error Number</b>	3231
<b>SQL State</b>	55W44
<b>SQL Code</b>	-1589L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the certificate that could not be found
<b>Probable Cause</b>	You misspelled the name of a certificate, or the certificate does not exist.

## Messages 1590 through 1609

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1590</b>	<b>"You cannot use a security token when making remote connections"</b>
<b>Constant</b>	INVALID_USE_OF_SECURITY_TOKEN
<b>SAP Sybase Error Number</b>	3232
<b>SQL State</b>	WO032
<b>SQL Code</b>	-1590L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

<b>Error 1590</b>	<b>"You cannot use a security token when making remote connections"</b>
<b>Probable Cause</b>	A security token cannot be used to make remote data access connections.
<b>Error 1591</b>	<b>"Invalid use of BEFORE operator in text query."</b>
<b>Constant</b>	TEXT_INVALID_BEFORE
<b>SAP Sybase Error Number</b>	3233
<b>SQL State</b>	WT040
<b>SQL Code</b>	-1591L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	Only terms and prefixes are allowed as arguments to a BEFORE operator.
<b>Error 1592</b>	<b>"Text indexes on materialized views are not supported for this database."</b>
<b>Constant</b>	TEXT_MV_UPGRADE_REQUIRED
<b>SAP Sybase Error Number</b>	3234
<b>SQL State</b>	WT041
<b>SQL Code</b>	-1592L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The current database does not have catalog support for text indexes on materialized views. To use this feature, upgrade your database to the most recent version.
<b>Error 1593</b>	<b>"Unable to copy file %1 to destination %2"</b>
<b>Constant</b>	UNABLE_TO_COPY_DB_FILE_INTO_CLOUD

## Errors and Warnings

<b>Error 1593</b>	<b>"Unable to copy file %1 to destination %2"</b>
<b>SAP Sybase Error Number</b>	3235
<b>SQL State</b>	08WB2
<b>SQL Code</b>	-1593L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The file name of the file on the client computer
<b>Parameter 2</b>	The file name of the destination within the cloud
<b>Probable Cause</b>	The client database file could not be copied to the requested cloud destination.
<b>Error 1594</b>	<b>"LDAP server definition of \"%1\" is incomplete. A search URL, access distinguished name, password, and authentication URL are required."</b>
<b>Constant</b>	LDAPSERVER_INCOMPLETE_DEF
<b>SAP Sybase Error Number</b>	3236
<b>SQL State</b>	WW208
<b>SQL Code</b>	-1594L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the LDAP server.
<b>Probable Cause</b>	The named LDAP server is missing one or more of the values required to search for a user's distinguished name or authenticate a user. Use ALTER LDAP SERVER <server name> to specify any missing values.
<b>Error 1595</b>	<b>"Column \"%1\" not found in variable \"%2\""</b>
<b>Constant</b>	COLUMN_NOT_FOUND_IN_VARIABLE

<b>Error 1595</b>	<b>"Column '%1' not found in variable '%2'"</b>
<b>SAP Sybase Error Number</b>	3237
<b>SQL State</b>	52006
<b>SQL Code</b>	-1595L
<b>ODBC 2 State</b>	S0002
<b>ODBC 3 State</b>	42S22
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	Name of the column that could not be found.
<b>Parameter 2</b>	Name of the row variable that was supposed to contain the column.
<b>Probable Cause</b>	You misspelled the name of a column or variable, or the variable has a different schema than you expect.
<b>Error 1596</b>	<b>"Database contains users with 'SYS_' prefix and '_ROLE' suffix."</b>
<b>Constant</b>	INVALID_USER_NAME
<b>SAP Sybase Error Number</b>	3238
<b>SQL State</b>	08WB3
<b>SQL Code</b>	-1596L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The database to be upgraded contains users with 'SYS_' prefix and '_ROLE' suffix. Drop or migrate these users before upgrading the database.
<b>Error 1597</b>	<b>"The transaction may not be committed because the primary server lost quorum"</b>
<b>Constant</b>	LOST_QUORUM_ON_COMMIT
<b>SAP Sybase Error Number</b>	2363

## Errors and Warnings

<b>Error 1597</b>	<b>"The transaction may not be committed because the primary server lost quorum"</b>
<b>SQL State</b>	WW166
<b>SQL Code</b>	-1597L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to commit a transaction on a primary server that just lost quorum with the partner and arbiter servers. The transaction may or may not have been committed. The partner servers will attempt to determine which server will become the new primary server.
<b>Error 1598</b>	<b>"Array element error: array index "%1' is out of range"</b>
<b>Constant</b>	INVALID_ARRAY_INDEX
<b>SAP Sybase Error Number</b>	3239
<b>SQL State</b>	2202E
<b>SQL Code</b>	-1598L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Value of the array index expression
<b>Probable Cause</b>	You tried to access an array element with an index outside the declared size of the array. For an array of size N, valid array elements are numbered 1 through N.
<b>Error 1599</b>	<b>"Invalid use of collection type"</b>
<b>Constant</b>	INVALID_USE_OF_COLLECTION
<b>SAP Sybase Error Number</b>	3240
<b>SQL State</b>	WW210
<b>SQL Code</b>	-1599L

<b>Error 1599</b>	<b>"Invalid use of collection type"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You tried to use an ARRAY or ROW type in an unsupported context. You cannot store these values in tables or read them directly from client interfaces such as ODBC, ESQL, and JDBC. You must extract the individual values you are interested in.
<b>Error 1600</b>	<b>"The bind to URL "%1' failed. The most recently reported LDAP API error is: "%2"</b>
<b>Constant</b>	LDAPUA_BINDFAIL
<b>SAP Sybase Error Number</b>	3241
<b>SQL State</b>	WW211
<b>SQL Code</b>	-1600L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The LDAP URL used with bind().
<b>Parameter 2</b>	The LDAP API error message.
<b>Probable Cause</b>	The message is reported from the LDAP API client with context from the LDAP User Authentication methods. An LDAP administrator or Sybase Tech Support may use these low level messages to direct the DBA how to resolve a problem.
<b>Error 1601</b>	<b>"Password encryption failed. Error message '%1'."</b>
<b>Constant</b>	PWD_CIPHER_ERROR
<b>SAP Sybase Error Number</b>	3242
<b>SQL State</b>	WW212
<b>SQL Code</b>	-1601L
<b>ODBC 2 State</b>	OK

## Errors and Warnings

<b>Error 1601</b>	<b>"Password encryption failed. Error message '%1'."</b>
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The error message reported by block encrypter.
<b>Probable Cause</b>	Run-time block encrypter initialization failed.
<b>Error 1602</b>	<b>"The specified distinguished name '%1' does not match the search result '%2'."</b>
<b>Constant</b>	LDAPUA_DN_NOMAT
<b>SAP Sybase Error Number</b>	3243
<b>SQL State</b>	WW213
<b>SQL Code</b>	-1602L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The expected distinguished name that was specified in command.
<b>Parameter 2</b>	The result distinguished name returned by LDAP search.
<b>Probable Cause</b>	VALIDATE LDAP SERVER command did a successful search to find a user distinguished name, but the value differs from the expected distinguished name specified in the command.
<b>Error 1603</b>	<b>"The search using '%1' failed due to one or more invalid values set."</b>
<b>Constant</b>	LDAPUA_SEARCHFAIL
<b>SAP Sybase Error Number</b>	3244
<b>SQL State</b>	WW214
<b>SQL Code</b>	-1603L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1603</b>	<b>"The search using "%1' failed due to one or more invalid values set."</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The LDAP server name or search URL specifying the search.
<b>Probable Cause</b>	An LDAPUA search or validate failed returning LDAP_INVALID_CREDENTIALS, LDAP_INSUFFICIENT_ACCESS, LDAP_INVALID_DN_SYNTAX, LDAP_NO SUCH_OBJECT, or LDAP_FILTER_ERROR due to the invalid settings. Check the access account values for the named LDAP server or search URL.
<b>Error 1604</b>	<b>"Cannot use logical server policy clause more than once"</b>
<b>Constant</b>	LS_POLICY_USED_TWICE
<b>SAP Sybase Error Number</b>	3245
<b>SQL State</b>	WQ022
<b>SQL Code</b>	-1604L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	ls policy clause appeared more than once in a create/alter logical server policy statement
<b>Error 1605</b>	<b>"Table Parameterized Functions and V4 TableUDFs are not supported for this database."</b>
<b>Constant</b>	TPF_UPGRADE_REQUIRED
<b>SAP Sybase Error Number</b>	3246
<b>SQL State</b>	WP020
<b>SQL Code</b>	-1605L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

## Errors and Warnings

<b>Error 1605</b>	<b>"Table Parameterized Functions and V4 TableUDFs are not supported for this database."</b>
<b>Probable Cause</b>	The current database does not have catalog support for table parameterized functions. To use this feature, upgrade your database to the most recent version.
<b>Error 1606</b>	<b>"Multiple table parameters are not supported."</b>
<b>Constant</b>	ONLY_SINGLE_TABLE_PARM_SUPPORTED
<b>SAP Sybase Error Number</b>	3247
<b>SQL State</b>	WP021
<b>SQL Code</b>	-1606L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Table parameterized functions are limited to only having at most a single table parameter.
<b>Error 1607</b>	<b>"Outer references are not allowed for TPF input tables."</b>
<b>Constant</b>	TPF_OUTER_REFERENCES_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	3249
<b>SQL State</b>	WP022
<b>SQL Code</b>	-1607L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Outer references in the select list for a TPF input table are not allowed.
<b>Error 1608</b>	<b>"Unable to delete file %1"</b>
<b>Constant</b>	UNABLE_TO_DELETE_FILE
<b>SAP Sybase Error Number</b>	3250
<b>SQL State</b>	08WB4

<b>Error 1608</b>	<b>"Unable to delete file %1"</b>
<b>SQL Code</b>	-1608L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The file name of the file to be deleted
<b>Probable Cause</b>	The request to delete a file failed.
<b>Error 1609</b>	<b>"File %1 already exists"</b>
<b>Constant</b>	FILE_ALREADY_EXISTS
<b>SAP Sybase Error Number</b>	3251
<b>SQL State</b>	08WB5
<b>SQL Code</b>	-1609L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The file name of the file that already exists
<b>Probable Cause</b>	The request to create a file or directory failed because the file or directory already exists.

## Messages 1610 through 1629

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1610</b>	<b>"Unable to create directory %1"</b>
<b>Constant</b>	UNABLE_TO_CREATE_DIRECTORY
<b>SAP Sybase Error Number</b>	3252
<b>SQL State</b>	08WB6
<b>SQL Code</b>	-1610L
<b>ODBC 2 State</b>	08001

## Errors and Warnings

<b>Error 1610</b>	" <b>Unable to create directory %1</b> "
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The file name of the directory that could not be created
<b>Probable Cause</b>	The request to create a directory failed.

<b>Error 1611</b>	" <b>Unable to copy file %1</b> "
<b>Constant</b>	UNABLE_TO_COPY_FILE
<b>SAP Sybase Error Number</b>	3253
<b>SQL State</b>	08WB7
<b>SQL Code</b>	-1611L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The file name of the file to be copied
<b>Probable Cause</b>	The request to copy a file failed.

<b>Error 1612</b>	" <b>Cannot ALTER LDAP SERVER "%1' while ldap server is in active state.</b> "
<b>Constant</b>	LDAPSERVER_IS_ACTIVE
<b>SAP Sybase Error Number</b>	3254
<b>SQL State</b>	WW215
<b>SQL Code</b>	-1612L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The LDAP SERVER name.

<b>Error 1612</b>	<b>"Cannot ALTER LDAP SERVER '%1' while ldap server is in active state."</b>
<b>Probable Cause</b>	When an LDAP server is active, an ALTER statement may not change the ldap server options without also specifying WITH SUSPEND clause to also put the server in suspended state. This is an invalid LDAP server state change.
<b>Error 1613</b>	<b>"Tag ID: '%1' specifies a value not bounded by an array"</b>
<b>Constant</b>	FOR_JSON_EXPLICIT_NOT_IN_ARRAY
<b>SAP Sybase Error Number</b>	3255
<b>SQL State</b>	WX017
<b>SQL Code</b>	-1613L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The value of the tag ID which is not bounded by an array.
<b>Probable Cause</b>	A union of multiple queries whose tags have the same parent may generate this error when the queries mix object and value notation.
<b>Error 1614</b>	<b>"Logical Server '%1' is used in both add and drop clauses"</b>
<b>Constant</b>	LS_IN_ADD_DROP
<b>SAP Sybase Error Number</b>	3256
<b>SQL State</b>	WQ023
<b>SQL Code</b>	-1614L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the logical server.
<b>Probable Cause</b>	A logical Server appears in both the add and drop clauses of an alter logical server statement.

## Errors and Warnings

<b>Error 1615</b>	<b>"LS Policy "%1' cannot be dropped because this policy is currently being used by a logical server"</b>
<b>Constant</b>	LSP_IN_USE_BY_LS
<b>SAP Sybase Error Number</b>	3257
<b>SQL State</b>	WQ024
<b>SQL Code</b>	-1615L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	LS policy name.
<b>Probable Cause</b>	A logical server policy cannot be dropped if a logical server is using it.
<b>Error 1616</b>	<b>""&gt;%1' being used incorrectly in ls policy statement"</b>
<b>Constant</b>	LSP_USING_INCORRECT_ARGS
<b>SAP Sybase Error Number</b>	3258
<b>SQL State</b>	WQ025
<b>SQL Code</b>	-1616L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	LS policy option name.
<b>Probable Cause</b>	A clause in a ls policy sql statement has been used incorrectly.
<b>Error 1617</b>	<b>"The %1 remote data access class is no longer supported, please use %2 instead"</b>
<b>Constant</b>	OMNI_JDBC_NO_LONGER_SUPPORTED
<b>SAP Sybase Error Number</b>	3259
<b>SQL State</b>	WO033

<b>Error 1617</b>	<b>"The %1 remote data access class is no longer supported, please use %2 instead"</b>
<b>SQL Code</b>	-1617L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The JDBC based remote data access class.
<b>Parameter 2</b>	The preferred ODBC based remote data access class.
<b>Probable Cause</b>	You attempted to use a JDBC based remote data access class which is no longer supported. Please use the appropriate ODBC based class instead.
<b>Error 1618</b>	<b>"The %1 remote data access class has been deprecated, please use %2 instead or change cis_option"</b>
<b>Constant</b>	OMNI_JDBC_DEPRECATED
<b>SAP Sybase Error Number</b>	3260
<b>SQL State</b>	WO034
<b>SQL Code</b>	-1618L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The JDBC based remote data access class.
<b>Parameter 2</b>	The preferred ODBC based remote data access class.
<b>Probable Cause</b>	You attempted to use a JDBC based remote data access class which has been deprecated. Please use the appropriate ODBC based class instead; or change the cis_option setting to re-enable this feature.
<b>Error 1619</b>	<b>"logical server '%1' cannot be used in a connect string"</b>
<b>Constant</b>	LS_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	3261

## Errors and Warnings

<b>Error 1619</b>	<b>"logical server '%1' cannot be used in a connect string"</b>
<b>SQL State</b>	WQ026
<b>SQL Code</b>	-1619L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	logical servername.
<b>Probable Cause</b>	This logical server cannot be used as an argument to the connection string parameter logicalserver.
<b>Error 1620</b>	<b>"The value specified is not within the required range %1 to %2."</b>
<b>Constant</b>	LDAPUA_OPT_OUT_OF_RANGE
<b>SAP Sybase Error Number</b>	3262
<b>SQL State</b>	WW217
<b>SQL Code</b>	-1620L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The minimum value for this option.
<b>Parameter 2</b>	The maximum value for this option.
<b>Probable Cause</b>	The specified value for an LDAP server option is too big or too small.
<b>Error 1621</b>	<b>"LDAP server %1 may not accept anonymous binds."</b>
<b>Constant</b>	LDAPUA_ANONBINDERR
<b>SAP Sybase Error Number</b>	3263
<b>SQL State</b>	WW218
<b>SQL Code</b>	-1621L
<b>ODBC 2 State</b>	ERROR

<b>Error 1621</b>	<b>"LDAP server %1 may not accept anonymous binds."</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The LDAP server name or search URL specifying the search.
<b>Probable Cause</b>	An LDAPUA search or validate failed returning LDAP_INAPPROPRIATE_AUTH due to invalid settings for the target LDAP server. Check the access account values for the named LDAP server or search URL.
<b>Error 1622</b>	<b>"Bind to LDAP server %1 without a password is not allowed."</b>
<b>Constant</b>	LDAPUA_UTP
<b>SAP Sybase Error Number</b>	3264
<b>SQL State</b>	WW219
<b>SQL Code</b>	-1622L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The LDAP server name or search URL specifying the search.
<b>Probable Cause</b>	An LDAPUA search or validate failed returning LDAP_UNWILLING_TO_PERFORM due to invalid settings for the target LDAP server. Check access account values for the named LDAP server or search URL.
<b>Error 1623</b>	<b>"The search on LDAP server %1 completed with no matching results."</b>
<b>Constant</b>	LDAPUA_NO_SEARCH_RESULTS
<b>SAP Sybase Error Number</b>	3265
<b>SQL State</b>	WW220
<b>SQL Code</b>	-1623L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1623</b>	<b>"The search on LDAP server %1 completed with no matching results."</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The LDAP server name or search URL specifying the search.
<b>Probable Cause</b>	An LDAPUA search or validate failed returning LDAP_NO_RESULTS_RETURNED. This error is expected when the user does not exist in the LDAP server.
<b>Error 1624</b>	<b>"The length of the value specified is too long, it exceeds the limit of %1 bytes."</b>
<b>Constant</b>	LDAPUA_OPT_TOO_LONG
<b>SAP Sybase Error Number</b>	3266
<b>SQL State</b>	WW216
<b>SQL Code</b>	-1624L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The maximum length of the value.
<b>Probable Cause</b>	The specified value for an LDAP server option is too long. Specify a shorter string.
<b>Error 1625</b>	<b>"The UltraLite database deploy file is invalid (code: %1, file: %2)"</b>
<b>Constant</b>	ULTRALITE_DEPLOY_FILE_INVALID
<b>SAP Sybase Error Number</b>	3267
<b>SQL State</b>	WU002
<b>SQL Code</b>	-1625L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1625</b>	<b>"The UltraLite database deploy file is invalid (code: %1, file: %2)"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The diagnostic code.
<b>Parameter 2</b>	The associated filename, if applicable.
<b>Probable Cause</b>	The UltraLite database deploy file is invalid. This can occur if the wrong file is deployed, or if the file is damaged. Diagnostic code 1 indicates the file is not a deploy file or has subsequently been corrupted. Diagnostic code 2 indicates the file is not a valid size.
<b>Error 1626</b>	<b>"The logical server policy for logical server '%1' does not allow 'redirect=yes' in the connection string"</b>
<b>Constant</b>	LS_POLICY_DOES_NOT_ALLOW_REDIRECT
<b>SAP Sybase Error Number</b>	3268
<b>SQL State</b>	WQ027
<b>SQL Code</b>	-1626L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	logical servername.
<b>Probable Cause</b>	This logical server policy for this logical server does not allow redirection.
<b>Error 1627</b>	<b>"TLS ON cannot be used with URL %1"</b>
<b>Constant</b>	LDAPUA_TLS_WITH_LDAPS
<b>SAP Sybase Error Number</b>	3269
<b>SQL State</b>	WW240
<b>SQL Code</b>	-1627L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 1627</b>	<b>"TLS ON cannot be used with URL %1"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The LDAP URL that is using Secure LDAP.
<b>Probable Cause</b>	The LDAP server is specified with TLS ON and the specified LDAP URL uses Secure LDAP, that is, 'ldaps' instead of 'ldap', which is not a valid combination. Use either TLS ON or an 'ldaps' URL.
<b>Error 1628</b>	<b>"logical server '%1' cannot be used as a default logical server"</b>
<b>Constant</b>	LS_NOT_ALLOWED_AS_DEFAULT
<b>SAP Sybase Error Number</b>	3270
<b>SQL State</b>	WQ028
<b>SQL Code</b>	-1628L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	logical servername.
<b>Probable Cause</b>	This logical server cannot be used as a default logical server.
<b>Error 1629</b>	<b>"Only one IDENTIFIED BY value may be specified."</b>
<b>Constant</b>	LDAPUA_TOO_MANY_IDENTBY
<b>SAP Sybase Error Number</b>	3271
<b>SQL State</b>	WW241
<b>SQL Code</b>	-1629L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The LDAP server is specified with more than one password or is specified with both IDENTIFIED BY and IDENTIFIED BY ENCRYPTED. Set only one password.

## 1630 - 1000133

---

### Messages 1630 through 1649

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1630</b>	<b>"Server '%1' is not allowed to have different values for ls policy option temp_data_in_shared_temp"</b>
<b>Constant</b>	LS_POLICY_OPTION_VALUE_DIFFERENT
<b>SAP Sybase Error Number</b>	3272
<b>SQL State</b>	WQ029
<b>SQL Code</b>	-1630L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	multiplex servername.
<b>Probable Cause</b>	A server is not allowed to have different values for temp_da-ta_in_shared_temp ls policy option.
<b>Error 1631</b>	<b>"Use of table privilege '%1' is not supported on the current database"</b>
<b>Constant</b>	TABPRIV_LOAD_TRUNCATE_UNSUPPORTED
<b>SAP Sybase Error Number</b>	3273
<b>SQL State</b>	0A007
<b>SQL Code</b>	-1631L
<b>ODBC 2 State</b>	28000
<b>ODBC 3 State</b>	28000
<b>Severity Code</b>	<i>16</i> on page 2

## Errors and Warnings

<b>Error 1631</b>	<b>"Use of table privilege '%1' is not supported on the current database"</b>
<b>Parameter 1</b>	The table privilege, load or truncate.
<b>Probable Cause</b>	The current database is an older database and does not have the capability to support table privileges load or truncate. You must upgrade your database to use these table privileges.

<b>Error 1632</b>	<b>"Dropping or altering arbiter \'%1\' requires a connection to the partner."</b>
<b>Constant</b>	MIRROR_DROP_ARBITER_REQUIRES_PARTNER_CONN
<b>SAP Sybase Error Number</b>	3274
<b>SQL State</b>	WW242
<b>SQL Code</b>	-1632L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the arbiter server.
<b>Probable Cause</b>	An attempt was made to drop or alter an arbiter that is not connected to the partner server.

<b>Error 1633</b>	<b>"Trace event '%1' is not valid"</b>
<b>Constant</b>	INVALID_TRACE_EVENT_NAME
<b>SAP Sybase Error Number</b>	3275
<b>SQL State</b>	WE019
<b>SQL Code</b>	-1633L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The trace event name.
<b>Probable Cause</b>	The specified trace event name is not valid.

<b>Error 1634</b>	<b>"The specified session name '%1' is not valid"</b>
<b>Constant</b>	INVALID_TRACE_EVENT_SESSION_NAME
<b>SAP Sybase Error Number</b>	3276
<b>SQL State</b>	WE020
<b>SQL Code</b>	-1634L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The trace event session name.
<b>Probable Cause</b>	The specified trace event session name is not valid.

<b>Error 1635</b>	<b>"Trace event '%1' already exists"</b>
<b>Constant</b>	TRACE_EVENT_ALREADY_EXISTS
<b>SAP Sybase Error Number</b>	3277
<b>SQL State</b>	WE021
<b>SQL Code</b>	-1635L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The trace event name.
<b>Probable Cause</b>	The specified trace event name already exists.

<b>Error 1636</b>	<b>"Trace event '%1' is referenced by one or more sessions. Drop referencing sessions first."</b>
<b>Constant</b>	TRACE_EVENT_IS_IN_USE
<b>SAP Sybase Error Number</b>	3278
<b>SQL State</b>	WE022
<b>SQL Code</b>	-1636L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1636</b>	<b>"Trace event '%1' is referenced by one or more sessions. Drop referencing sessions first."</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The trace event name.
<b>Probable Cause</b>	The specified trace event name is used and cannot be dropped before dropping referencing sessions.
<b>Error 1637</b>	<b>"Trace event session '%1' is active. Stop active session before dropping the session."</b>
<b>Constant</b>	TRACE_EVENT_SESSION_IS_ACTIVE
<b>SAP Sybase Error Number</b>	3279
<b>SQL State</b>	WE023
<b>SQL Code</b>	-1637L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The trace event session name.
<b>Probable Cause</b>	The specified trace event session is active. The session must be not be active in order to be dropped.
<b>Error 1638</b>	<b>"Too many arguments for trace event '%1'."</b>
<b>Constant</b>	TOO_MANY_PARAMETERS_FOR_TRACE_EVENT
<b>SAP Sybase Error Number</b>	3280
<b>SQL State</b>	WE024
<b>SQL Code</b>	-1638L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The trace event name.

<b>Error 1638</b>	<b>"Too many arguments for trace event '%1'."</b>
<b>Probable Cause</b>	Too many arguments were provided for the trace event specified.
<b>Error 1639</b>	<b>"Database alter failed: %1"</b>
<b>Constant</b>	DATABASE_NOT_ALTERED
<b>SAP Sybase Error Number</b>	3281
<b>SQL State</b>	08WB8
<b>SQL Code</b>	-1639L
<b>ODBC 2 State</b>	08004
<b>ODBC 3 State</b>	08004
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Reason that the database was not altered.
<b>Probable Cause</b>	Your attempt to alter a database failed.
<b>Error 1640</b>	<b>"Too many active trace event sessions."</b>
<b>Constant</b>	TOO_MANY_ACTIVE_TRACE_SESSIONS
<b>SAP Sybase Error Number</b>	3282
<b>SQL State</b>	WE025
<b>SQL Code</b>	-1640L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Probable Cause</b>	Too many active trace sessions.
<b>Error 1641</b>	<b>"Trace event session '%1' already active."</b>
<b>Constant</b>	TRACE_SESSION_ALREADY_ACTIVE
<b>SAP Sybase Error Number</b>	3283
<b>SQL State</b>	WE026
<b>SQL Code</b>	-1641L

## Errors and Warnings

<b>Error 1641</b>	<b>"Trace event session '%1' already active."</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The trace event session name.
<b>Probable Cause</b>	The specified trace event session is already active.
<b>Error 1642</b>	<b>"One or more targets in the trace event session '%1' failed to start."</b>
<b>Constant</b>	ONE_OR_MORE_TRACE_SESSION_TARGETS_FAILED_TO_START
<b>SAP Sybase Error Number</b>	3284
<b>SQL State</b>	WE027
<b>SQL Code</b>	-1642L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The trace event session name.
<b>Probable Cause</b>	The specified trace event session is already active.
<b>Error 1643</b>	<b>"Trace event session '%1' failed to start."</b>
<b>Constant</b>	TRACE_SESSION_FAILED_TO_START
<b>SAP Sybase Error Number</b>	3285
<b>SQL State</b>	WE028
<b>SQL Code</b>	-1643L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The trace event session name.

<b>Error 1643</b>	<b>"Trace event session "%1' failed to start."</b>
<b>Probable Cause</b>	The specified trace event session failed to start.
<b>Error 1644</b>	<b>"Trace event session "%1' is already stopped."</b>
<b>Constant</b>	TRACE_SESSION_ALREADY_STOPPED
<b>SAP Sybase Error Number</b>	3286
<b>SQL State</b>	WE029
<b>SQL Code</b>	-1644L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The trace event session name.
<b>Probable Cause</b>	The specified trace event session is already stopped.
<b>Error 1645</b>	<b>"Trace event session "%1' already has trace event "%2'."</b>
<b>Constant</b>	TRACE_SESSION_ALREADY_HAS_EVENT
<b>SAP Sybase Error Number</b>	3287
<b>SQL State</b>	WE030
<b>SQL Code</b>	-1645L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The trace event session name.
<b>Parameter 2</b>	The trace event name.
<b>Probable Cause</b>	The specified trace event session already has the specified event.
<b>Error 1646</b>	<b>"The specified target type "%1' is not valid"</b>
<b>Constant</b>	INVALID_TRACE_EVENT_TARGET_TYPE
<b>SAP Sybase Error Number</b>	3288

## Errors and Warnings

<b>Error 1646</b>	<b>"The specified target type "%1' is not valid"</b>
<b>SQL State</b>	WE031
<b>SQL Code</b>	-1646L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The trace event target type.
<b>Probable Cause</b>	The specified trace event target type is not valid.
<b>Error 1647</b>	<b>"Unknown option '%1' specified for target type '%2'."</b>
<b>Constant</b>	UNKNOWN_OPTION_FOR_TARGET_TYPE
<b>SAP Sybase Error Number</b>	3289
<b>SQL State</b>	WE032
<b>SQL Code</b>	-1647L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The option name.
<b>Parameter 2</b>	The trace event target type.
<b>Probable Cause</b>	An unknown option name was specified for given target type.
<b>Error 1648</b>	<b>"The option '%1' was not specified for target type "%2'."</b>
<b>Constant</b>	OPTION_FOR_TARGET_TYPE_NOT_SPECIFIED
<b>SAP Sybase Error Number</b>	3290
<b>SQL State</b>	WE033
<b>SQL Code</b>	-1648L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2

<b>Error 1648</b>	<b>"The option "%1' was not specified for target type "%2'."</b>
<b>Parameter 1</b>	The option name.
<b>Parameter 2</b>	The trace event target type.
<b>Probable Cause</b>	A required option for target type was not specified.
<b>Error 1649</b>	<b>"Trace event session '%1' already has target type '%2'."</b>
<b>Constant</b>	TRACE_SESSION_ALREADY_HAS_TARGET_TYPE
<b>SAP Sybase Error Number</b>	3291
<b>SQL State</b>	WE034
<b>SQL Code</b>	-1649L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The trace event session name.
<b>Parameter 2</b>	The trace event target type.
<b>Probable Cause</b>	The specified trace event session already has the specified target type.

## Messages 1650 through 1669

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1650</b>	<b>"Trace event session '%1' does not have trace event "%2'."</b>
<b>Constant</b>	TRACE_SESSION_DOES_NOT_HAVE_TRACE_EVENT
<b>SAP Sybase Error Number</b>	3292
<b>SQL State</b>	WE035
<b>SQL Code</b>	-1650L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2

## Errors and Warnings

<b>Error 1650</b>	<b>"Trace event session "%1' does not have trace event "%2'."</b>
<b>Parameter 1</b>	The trace event session name.
<b>Parameter 2</b>	The trace event name.
<b>Probable Cause</b>	The trace event session does not have the specified trace event.
<b>Error 1651</b>	<b>"Trace event session "%1' does not have trace event "%2'."</b>
<b>Constant</b>	TRACE_SESSION_DOES_NOT_HAVE_TARGET_TYPE
<b>SAP Sybase Error Number</b>	3293
<b>SQL State</b>	WE036
<b>SQL Code</b>	-1651L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The trace event session name.
<b>Parameter 2</b>	The trace event target type.
<b>Probable Cause</b>	The trace event session does not have the specified trace target type.
<b>Error 1652</b>	<b>"Trace event session "%1' already exists."</b>
<b>Constant</b>	TRACE_SESSION_ALREADY_EXISTS
<b>SAP Sybase Error Number</b>	3294
<b>SQL State</b>	WE037
<b>SQL Code</b>	-1652L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The trace event session name.
<b>Probable Cause</b>	A trace event session with that name already exists.

<b>Error 1653</b>	"RLV dbspace already exists. Cannot create more than one RLV dbspace."
<b>Constant</b>	RLV_DBSPACE_CREATION_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	3295
<b>SQL State</b>	WQ030
<b>SQL Code</b>	-1653L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	Creation of more than one user defined RLV dbspace is not allowed.
<b>Error 1654</b>	"Cannot enable RLV storage for table '%1'. A RLV dbspace does not exist."
<b>Constant</b>	RLV_DBSPACE_DOES_NOT_EXIST
<b>SAP Sybase Error Number</b>	3296
<b>SQL State</b>	WQ031
<b>SQL Code</b>	-1654L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	table name.
<b>Probable Cause</b>	Creation of more than one user defined RLV dbspace is not allowed.
<b>Error 1655</b>	"Invalid value for login policy option \'%1\No message
<b>Constant</b>	INVALID_LOGIN_POLICY_OPTION_VALUE
<b>SAP Sybase Error Number</b>	3297
<b>SQL State</b>	WW243
<b>SQL Code</b>	-1655L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1655</b>	<b>"Invalid value for login policy option \%"1\No message</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of login policy option.
<b>Probable Cause</b>	The value supplied for login policy option is not within valid bounds.
<b>Error 1656</b>	<b>"Database upgrade not possible; the name of a new SYSTEM logical server is already in use."</b>
<b>Constant</b>	IQ_LOGICAL_SERVER_CONFLICT
<b>SAP Sybase Error Number</b>	3298
<b>SQL State</b>	WQ032
<b>SQL Code</b>	-1656L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	An attempt to upgrade a database failed. Retry upgrade of the database when no existing logical server is using the name of the documented system logical servers.
<b>Error 1657</b>	<b>"Database upgrade not possible; Join Index in use."</b>
<b>Constant</b>	IQ_JOININDEX_PRESENT
<b>SAP Sybase Error Number</b>	3299
<b>SQL State</b>	WQ033
<b>SQL Code</b>	-1657L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	An attempt to upgrade a database failed. Retry upgrade of the database when join indexes have been dropped from the database.

<b>Error 1658</b>	"To '%1' column '%2' Table '%3' must be partitioned by '%4'"
<b>Constant</b>	COLUMN_PARTITIONED_INCORRECTLY
<b>SAP Sybase Error Number</b>	3300
<b>SQL State</b>	WW244
<b>SQL Code</b>	-1658L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Partition type
<b>Parameter 2</b>	The column name
<b>Parameter 3</b>	The table name
<b>Parameter 4</b>	Partition type
<b>Probable Cause</b>	The partitioning of this column must be consistent with the table partitioning.

<b>Error 1659</b>	"File or directory %1 not found"
<b>Constant</b>	FILE_NOT_FOUND
<b>SAP Sybase Error Number</b>	3301
<b>SQL State</b>	08WB9
<b>SQL Code</b>	-1659L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The file or directory name that does not exist or fail to access
<b>Probable Cause</b>	You attempted to perform an operation using a file or directory name that does not exist or fail to access.

<b>Error 1660</b>	"Fail to compare %1 and %2"
<b>Constant</b>	FILE_COMPARE_FAIL

## Errors and Warnings

<b>Error 1660</b>	<b>"Fail to compare %1 and %2"</b>
<b>SAP Sybase Error Number</b>	3302
<b>SQL State</b>	08WC1
<b>SQL Code</b>	-1660L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The source file or directory name that fails to compare
<b>Parameter 2</b>	The target file or directory name that fails to compare
<b>Probable Cause</b>	Failed to compare files or directories.
<b>Error 1661</b>	<b>"%1 is not a directory"</b>
<b>Constant</b>	NOT_A_DIRECTORY
<b>SAP Sybase Error Number</b>	3303
<b>SQL State</b>	08WC2
<b>SQL Code</b>	-1661L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The path name that is not a directory
<b>Probable Cause</b>	Failed to perform an operation using directory name.
<b>Error 1662</b>	<b>"%1 and %2 must not be the same"</b>
<b>Constant</b>	SAME_SOURCE_TARGET
<b>SAP Sybase Error Number</b>	3304
<b>SQL State</b>	08WC3
<b>SQL Code</b>	-1662L
<b>ODBC 2 State</b>	08001
<b>ODBC 3 State</b>	08001

<b>Error 1662</b>	<b>"%1 and %2 must not be the same"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The source file or directory name
<b>Parameter 2</b>	The target file or directory name
<b>Probable Cause</b>	You attempted to perform an operation using the same source and target file or directory.

<b>Error 1663</b>	<b>"Prevented removal of LDAP server because it is referenced by login policy \"%1\" which is the only login policy with an LDAP server and the value of login_mode is \"LDAPUA\"."</b>
<b>Constant</b>	ONLY_LDAP_POLICY
<b>SAP Sybase Error Number</b>	3305
<b>SQL State</b>	WW245
<b>SQL Code</b>	-1663L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the login policy.
<b>Probable Cause</b>	The setting for server-wide login_mode option is LDAPUA so to avoid locking out users from connecting, prevent the only login policy supporting LDAPUA reference removal. Change login_mode before proceeding to DROP LDAP SERVER <server name> WITH DROP ALL REFERENCES.

<b>Error 1664</b>	<b>"Prevented removal of LDAP server \"%1\" because it is the only LDAP server and the value of login_mode is \"LDAPUA\"."</b>
<b>Constant</b>	ONLY_LDAP_SERVER
<b>SAP Sybase Error Number</b>	3306
<b>SQL State</b>	WW246
<b>SQL Code</b>	-1664L

## Errors and Warnings

<b>Error 1664</b>	<b>"Prevented removal of LDAP server \"%1\" because it is the only LDAP server and the value of login_mode is \"LDAPUA \\\"."</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the LDAP server.
<b>Probable Cause</b>	The setting for server-wide login_mode option is LDAPUA so to avoid locking out users from connecting, prevent the removal of the only LDAP server. Change login_mode before proceeding to DROP LDAP SERVER <server name>.
<b>Error 1665</b>	<b>"Cannot change password because change_password_dual_control process is in progress"</b>
<b>Constant</b>	CHANGE_PWD_DUAL_CONTROL_INPROGRESS
<b>SAP Sybase Error Number</b>	3307
<b>SQL State</b>	28W20
<b>SQL Code</b>	-1665L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to change password while changing password by change_password_dual_control option is in progress.
<b>Error 1666</b>	<b>"Expression is not an array"</b>
<b>Constant</b>	NOT_AN_ARRAY
<b>SAP Sybase Error Number</b>	3308
<b>SQL State</b>	42X07
<b>SQL Code</b>	-1666L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1666</b>	<b>"Expression is not an array"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You either tried to apply an ARRAY dereference (using double square brackets) to an expression that does not evaluate to an array, or else you tried to pass a non-ARRAY expression to UNNEST.

<b>Error 1667</b>	<b>"The option '%1' cannot be set in user-defined logical server policies."</b>
<b>Constant</b>	LSP_OPTION_OVERRIDE_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	3309
<b>SQL State</b>	WQ034
<b>SQL Code</b>	-1667L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the option
<b>Probable Cause</b>	There are certain options that can only be set in the root logical server policy, not in user-defined logical server policies.

<b>Error 1668</b>	<b>"'%1' is not a valid logical server policy option"</b>
<b>Constant</b>	LSP_OPTION_DOES_NOT_EXIST
<b>SAP Sybase Error Number</b>	3310
<b>SQL State</b>	WQ035
<b>SQL Code</b>	-1668L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the option
<b>Probable Cause</b>	The LSP option specified by the user does not exist.

<b>Error 1669</b>	"The value given for the option '%1' is not of the correct type or value."
<b>Constant</b>	INVALID_LSP_OPTION_VALUE
<b>SAP Sybase Error Number</b>	3311
<b>SQL State</b>	WQ036
<b>SQL Code</b>	-1669L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the option
<b>Probable Cause</b>	Different options accept different types of values, such as boolean, string or integer.

## Messages 1670 through 1689

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1670</b>	"Cannot create table '%1' in a RLV dbspace."
<b>Constant</b>	RLV_TABLE_CREATION_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	3312
<b>SQL State</b>	WQ037
<b>SQL Code</b>	-1670L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	table name.
<b>Probable Cause</b>	Creation of a table in a RLV dbspace is not allowed.
<b>Error 1671</b>	"The file '%1' is invalid when the disk sandbox feature is enabled for database '%2'"
<b>Constant</b>	DISKSANDBOX_INVALID_PATH

<b>Error 1671</b>	<b>"The file '%1' is invalid when the disk sandbox feature is enabled for database '%2'"</b>
<b>SAP Sybase Error Number</b>	3313
<b>SQL State</b>	57W06
<b>SQL Code</b>	-1671L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	The name of the invalid file.
<b>Parameter 2</b>	The name of the database that the disk sandbox feature is enabled for.
<b>Probable Cause</b>	The file passed to the operation is invalid when the sandbox feature is enabled.
<b>Error 1672</b>	<b>"A disk sandbox error occurred for database '%1' when determining the disk sandbox status for file '%2'"</b>
<b>Constant</b>	DISKSANDBOX_UNABLE_TO_DETERMINE
<b>SAP Sybase Error Number</b>	3314
<b>SQL State</b>	57W07
<b>SQL Code</b>	-1672L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	The name of the database that could not determine the disk sandbox status of the file.
<b>Parameter 2</b>	The name of the invalid file.
<b>Probable Cause</b>	The file passed to the operation caused an error when determining the disk sandbox status.
<b>Error 1673</b>	<b>"A disk sandbox error occurred for database '%1' when finding the full path for file '%1'"</b>
<b>Constant</b>	DISKSANDBOX_FULLPATH_ERROR

## Errors and Warnings

<b>Error 1673</b>	<b>"A disk sandbox error occurred for database '%1' when finding the full path for file '%1'"</b>
<b>SAP Sybase Error Number</b>	3315
<b>SQL State</b>	57W08
<b>SQL Code</b>	-1673L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	The name of the database that could not find the full path of the file.
<b>Parameter 2</b>	The name of the invalid file.
<b>Probable Cause</b>	There was an error in finding the full path of the file that was passed to the operation.

<b>Error 1674</b>	<b>"Error at offset '%1': unexpected token '%2'"</b>
<b>Constant</b>	PARSE_JSON_UNEXPECTED_TOKEN
<b>SAP Sybase Error Number</b>	3316
<b>SQL State</b>	WX018
<b>SQL Code</b>	-1674L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The offset where the error occurred.
<b>Parameter 2</b>	The unexpected token.
<b>Probable Cause</b>	An unexpected token such as a comma, bracket, or brace was encountered.

<b>Error 1675</b>	<b>"Error at offset '%1': unexpected trailing text"</b>
<b>Constant</b>	PARSE_JSON_UNEXPECTED_TEXT
<b>SAP Sybase Error Number</b>	3317
<b>SQL State</b>	WX019

<b>Error 1675</b>	<b>"Error at offset '%1': unexpected trailing text"</b>
<b>SQL Code</b>	-1675L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The offset where the error occurred.
<b>Probable Cause</b>	Trailing text was encountered after parsing the JSON data.
<b>Error 1676</b>	<b>"Error at offset '%1': invalid data"</b>
<b>Constant</b>	PARSE_JSON_INVALID_DATA
<b>SAP Sybase Error Number</b>	3318
<b>SQL State</b>	WX020
<b>SQL Code</b>	-1676L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The offset where the error occurred.
<b>Probable Cause</b>	A JSON object or array contains invalid data.
<b>Error 1677</b>	<b>"Error at offset '%1': expected token '%2'"</b>
<b>Constant</b>	PARSE_JSON_EXPECTED_TOKEN
<b>SAP Sybase Error Number</b>	3319
<b>SQL State</b>	WX021
<b>SQL Code</b>	-1677L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The offset where the error occurred.
<b>Parameter 2</b>	The token that was expected.

## Errors and Warnings

<b>Error 1677</b>	<b>"Error at offset '%1': expected token '%2'"</b>
<b>Probable Cause</b>	The expected token was missing in the JSON data.
<b>Error 1678</b>	<b>"Error at offset '%1': expected JSON name/value pair"</b>
<b>Constant</b>	PARSE_JSON_EXPECTED_PAIR
<b>SAP Sybase Error Number</b>	3320
<b>SQL State</b>	WX022
<b>SQL Code</b>	-1678L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The offset where the error occurred.
<b>Probable Cause</b>	A name/value pair was expected within the JSON object.
<b>Error 1679</b>	<b>"Error at offset '%1': mismatched object or array terminator"</b>
<b>Constant</b>	PARSE_JSON_MISMATCH_TERMINATOR
<b>SAP Sybase Error Number</b>	3321
<b>SQL State</b>	WX023
<b>SQL Code</b>	-1679L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The offset where the error occurred.
<b>Probable Cause</b>	Encountered a mismatched terminator for a JSON object or array.
<b>Error 1680</b>	<b>"Invalid variable or type"</b>
<b>Constant</b>	PARSE_JSON_INVALID_VARIABLE_TYPE
<b>SAP Sybase Error Number</b>	3322
<b>SQL State</b>	WX024

<b>Error 1680</b>	<b>"Invalid variable or type"</b>
<b>SQL Code</b>	-1680L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The named variable is invalid or of the wrong data type for the JSON result.
<b>Error 1681</b>	<b>"Procedure is currently being altered or dropped"</b>
<b>Constant</b>	PROCEDURE_IN_USE_DDL
<b>SAP Sybase Error Number</b>	3323
<b>SQL State</b>	42WF0
<b>SQL Code</b>	-1681L
<b>ODBC 2 State</b>	40001
<b>ODBC 3 State</b>	40001
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You have attempted to use a procedure that is currently being altered or dropped.
<b>Error 1682</b>	<b>"The RLV dbspace "%1' cannot be made read only because it contains RLV enabled tables"</b>
<b>Constant</b>	RLV_DBSPACE_CONTAINS_TABLES
<b>SAP Sybase Error Number</b>	3324
<b>SQL State</b>	WQ038
<b>SQL Code</b>	-1682L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the dbspace

## Errors and Warnings

<b>Error 1682</b>	<b>"The RLV dbspace "%1' cannot be made read only because it contains RLV enabled tables"</b>
<b>Probable Cause</b>	You attempted to make the named RLV dbspace read only, but it contains RLV enabled tables. You must drop or disable the tables before making the dbspace read only.
<b>Error 1683</b>	<b>"Cannot change the mirror server type from %1 to %2"</b>
<b>Constant</b>	CANNOT_CHANGE_MIRROR_SERVER_TYPE
<b>SAP Sybase Error Number</b>	3325
<b>SQL State</b>	42WF2
<b>SQL Code</b>	-1683L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The original mirror server type
<b>Parameter 2</b>	The proposed new mirror server type
<b>Probable Cause</b>	You attempted to use the CREATE OR REPLACE MIRROR SERVER or ALTER MIRROR SERVER statement to change the mirror server type, but the proposed change is not supported.
<b>Error 1684</b>	<b>"Trace target option '%1' conflicts with already used option '%2'."</b>
<b>Constant</b>	TARGET_OPTIONS_CONFLICT
<b>SAP Sybase Error Number</b>	3326
<b>SQL State</b>	WE038
<b>SQL Code</b>	-1684L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The trace target option name.

<b>Error 1684</b>	<b>"Trace target option '%1' conflicts with already used option '%2'."</b>
<b>Parameter 2</b>	The trace target option name.
<b>Probable Cause</b>	A trace target option conflict with another target option used.
<b>Error 1685</b>	<b>"There was insufficient memory to complete the %1 operation"</b>
<b>Constant</b>	SFC_MEM_ERROR
<b>SAP Sybase Error Number</b>	3327
<b>SQL State</b>	08S01
<b>SQL Code</b>	-1685L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>17</i> on page 2
<b>Parameter 1</b>	The name of the procedure that detected the error.
<b>Probable Cause</b>	A call to the specified procedure could not complete the operation due to insufficient memory.
<b>Error 1686</b>	<b>"Invalid parameter was used in the call to %1"</b>
<b>Constant</b>	SFC_INVALID_PARM
<b>SAP Sybase Error Number</b>	3328
<b>SQL State</b>	08S02
<b>SQL Code</b>	-1686L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	The name of the procedure.
<b>Probable Cause</b>	An invalid parameter value was passed to the specified procedure.

## Errors and Warnings

<b>Error 1687</b>	<b>"The secure feature key name '%2' is not valid in the call to %1"</b>
<b>Constant</b>	SFC_INVALID_NAME
<b>SAP Sybase Error Number</b>	3329
<b>SQL State</b>	08S03
<b>SQL Code</b>	-1687L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	The name of the procedure.
<b>Parameter 2</b>	The secure feature key name.
<b>Probable Cause</b>	An invalid secure feature key name was passed to the specified procedure.
<b>Error 1688</b>	<b>"An invalid authorization key was specified in the call to %1"</b>
<b>Constant</b>	SFC_INVALID_KEY
<b>SAP Sybase Error Number</b>	3330
<b>SQL State</b>	08S04
<b>SQL Code</b>	-1688L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	The name of the procedure.
<b>Probable Cause</b>	An invalid secure feature key value was passed to the specified procedure.
<b>Error 1689</b>	<b>"An invalid secure feature list '%2' was specified in the call to %1"</b>
<b>Constant</b>	SFC_INVALID_FEAT
<b>SAP Sybase Error Number</b>	3331

<b>Error 1689</b>	<b>"An invalid secure feature list '%2' was specified in the call to %1"</b>
<b>SQL State</b>	08S05
<b>SQL Code</b>	-1689L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	The name of the procedure.
<b>Parameter 2</b>	The secure feature list.
<b>Probable Cause</b>	An invalid list of secure features was passed to the specified procedure.

## Messages 1690 through 1709

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1690</b>	<b>"You are not authorized to assign the feature list '%2' to a secure feature key using %1"</b>
<b>Constant</b>	SFC_NO_AUTH_FOR_FEAT
<b>SAP Sybase Error Number</b>	3332
<b>SQL State</b>	08S06
<b>SQL Code</b>	-1690L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	The name of the procedure.
<b>Parameter 2</b>	The secure feature list.
<b>Probable Cause</b>	An attempt was made to define a secure feature key to use a secure feature that the user is not authorized to use or assign.

## Errors and Warnings

<b>Error 1691</b>	<b>"You are not authorized to change the secure feature key named '%2' using %1"</b>
<b>Constant</b>	SFC_NO_AUTH_FOR_KEY
<b>SAP Sybase Error Number</b>	3333
<b>SQL State</b>	08S07
<b>SQL Code</b>	-1691L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	The name of the procedure.
<b>Parameter 2</b>	The secure feature key name.
<b>Probable Cause</b>	The user is not authorized to change the named secure feature key.
<b>Error 1692</b>	<b>"Call to %1 failed - the maximum number of secure feature keys has already been created"</b>
<b>Constant</b>	SFC_HIT_MAX_LIMIT
<b>SAP Sybase Error Number</b>	3334
<b>SQL State</b>	08S08
<b>SQL Code</b>	-1692L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>17</i> on page 2
<b>Parameter 1</b>	The name of the procedure.
<b>Probable Cause</b>	The limit on the number of secure feature keys has been reached.
<b>Error 1693</b>	<b>"Call to %1 failed - the secure feature key named '%2' already exists"</b>
<b>Constant</b>	SFC_KEY_EXISTS
<b>SAP Sybase Error Number</b>	3335
<b>SQL State</b>	08S09

<b>Error 1693</b>	<b>"Call to %1 failed - the secure feature key named "%2' already exists"</b>
<b>SQL Code</b>	-1693L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	The name of the procedure.
<b>Parameter 2</b>	The secure feature key name.
<b>Probable Cause</b>	The user attempted to create a secure feature key with the name of a key that already exists.
<b>Error 1694</b>	<b>"Call to %1 failed - the secure feature key named "%2' does not exist"</b>
<b>Constant</b>	SFC_NOT_FOUND
<b>SAP Sybase Error Number</b>	3336
<b>SQL State</b>	08S10
<b>SQL Code</b>	-1694L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	The name of the procedure.
<b>Parameter 2</b>	The secure feature key name.
<b>Probable Cause</b>	The user attempted to reference a secure feature key that does not exist.
<b>Error 1695</b>	<b>"Call to %1 failed - the authorization key specified for the secure feature key named "%2' is incorrect"</b>
<b>Constant</b>	SFC_NOT_MATCH
<b>SAP Sybase Error Number</b>	3337
<b>SQL State</b>	08S11
<b>SQL Code</b>	-1695L

## Errors and Warnings

<b>Error 1695</b>	<b>"Call to %1 failed - the authorization key specified for the secure feature key named '%2' is incorrect"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	The name of the procedure.
<b>Parameter 2</b>	The secure feature key name.
<b>Probable Cause</b>	The provided authorization key did not match the value stored for the specified named key.
<b>Error 1696</b>	<b>"Call to %1 failed - the key named '%2' is the last key with the MANAGE_FEATURES and MANAGE_KEYS features"</b>
<b>Constant</b>	SFC_CANNOT_REMOVE_LAST
<b>SAP Sybase Error Number</b>	3338
<b>SQL State</b>	08S12
<b>SQL Code</b>	-1696L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the procedure.
<b>Parameter 2</b>	The secure feature key name.
<b>Probable Cause</b>	The call attempted to remove the last secure feature key that would enable both MANAGE_FEATURES and MANAGE_KEYS and this is not allowed.
<b>Error 1697</b>	<b>"Database upgrade not possible; LD Index in use."</b>
<b>Constant</b>	IQ_LDINDEX_PRESENT
<b>SAP Sybase Error Number</b>	3339
<b>SQL State</b>	WQ039
<b>SQL Code</b>	-1697L
<b>ODBC 2 State</b>	ERROR

<b>Error 1697</b>	"Database upgrade not possible; LD Index in use."
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	An attempt to upgrade a database failed. Retry upgrade of the database when LD indexes have been dropped from the database.

<b>Error 1698</b>	" <b>change_password_dual_control</b> is enabled for this user. Use <b>ALTER USER</b> to change password."
<b>Constant</b>	CHANGE_PWD_DUAL_CONTROL_ENABLED
<b>SAP Sybase Error Number</b>	3340
<b>SQL State</b>	28W21
<b>SQL Code</b>	-1698L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to change a password while the <b>change_password_dual_control</b> option is set for this user. When this option is set, you must use the <b>ALTER USER</b> statement to change the dual password.

<b>Error 1699</b>	"Cannot convert database to multiplex. An RLV dbspace exists."
<b>Constant</b>	MPX_CONVERSION_NOT_ALLOWED_WITH_RLV_STORE
<b>SAP Sybase Error Number</b>	3341
<b>SQL State</b>	WQ040
<b>SQL Code</b>	-1699L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A simplex database with RLV dbspace cannot be converted to a multiplex database.

## Errors and Warnings

<b>Error 1700</b>	<b>"TDS login requests with unencrypted passwords are not permitted"</b>
<b>Constant</b>	UNENCRYPTED_TDS_LOGIN_REQUESTS_NOT_PERMITTED
<b>SAP Sybase Error Number</b>	3342
<b>SQL State</b>	28W22
<b>SQL Code</b>	-1700L
<b>ODBC 2 State</b>	28000
<b>ODBC 3 State</b>	28000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to perform a TDS login without using RSA encryption for the password. The current TDS login setting does not allow unencrypted TDS login requests. Change the tds1 server option setting or connect using an RSA encrypted password.

<b>Error 1701</b>	<b>"TDS login requests with RSA encrypted passwords must also use a nonce"</b>
<b>Constant</b>	RSA_ENCRYPTED_TDS_LOGIN_MUST_HAVE_NONCE
<b>SAP Sybase Error Number</b>	3343
<b>SQL State</b>	28W23
<b>SQL Code</b>	-1701L
<b>ODBC 2 State</b>	28000
<b>ODBC 3 State</b>	28000
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to perform a TDS login with a client that does not use a nonce with the RSA encrypted password. The current TDS login setting does not allow RSA encrypted TDS login requests without a nonce. Change the tds1 server option setting or connect using a TDS client that supports a nonce with the RSA encrypted password.

<b>Error 1702</b>	<b>"Collection types not supported"</b>
<b>Constant</b>	COLLECTION_TYPES_NOT_SUPPORTED

<b>Error 1702</b>	<b>"Collection types not supported"</b>
<b>SAP Sybase Error Number</b>	3344
<b>SQL State</b>	0AW28
<b>SQL Code</b>	-1702L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Probable Cause</b>	The current database is an older database and does not have support for row or array types. To use this feature, upgrade your database to the most recent version.
<b>Error 1703</b>	<b>"The user name specified must be the user name of the current connection"</b>
<b>Constant</b>	CREATE_SCHEMA_USER_DOES_NOT_MATCH
<b>SAP Sybase Error Number</b>	3345
<b>SQL State</b>	42WD5
<b>SQL Code</b>	-1703L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	In the CREATE SCHEMA AUTHORIZATION clause, you specified a user name other than the user name of the current connection.
<b>Error 1704</b>	<b>"Remote column %1 has been specified with the wrong case"</b>
<b>Constant</b>	OMNI_RMT_COLUMN_WRONG_CASE
<b>SAP Sybase Error Number</b>	3346
<b>SQL State</b>	WO035
<b>SQL Code</b>	-1704L

## Errors and Warnings

<b>Error 1704</b>	<b>"Remote column %1 has been specified with the wrong case"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>11</i> on page 2
<b>Parameter 1</b>	The complete name of the remote column.
<b>Probable Cause</b>	The remote server requires that columns be specified in the correct case.

<b>Error 1705</b>	<b>"Illegal RLV Merge Type "%1"</b>
<b>Constant</b>	RLV_ILLEGAL_MERGE_TYPE
<b>SAP Sybase Error Number</b>	3347
<b>SQL State</b>	WQ041
<b>SQL Code</b>	-1705L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The illegal merge string
<b>Probable Cause</b>	Legal RLV merge types are: BLOCKING, NONBLOCKING.

<b>Error 1706</b>	<b>"The use of foreign keys in a RLV table is not supported"</b>
<b>Constant</b>	RLV_FOREIGNKEY_UNSUPPORTED
<b>SAP Sybase Error Number</b>	3348
<b>SQL State</b>	WQ043
<b>SQL Code</b>	-1706L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to use a foreign key within a RLV table which is unsupported.

<b>Error 1707</b>	<b>"The datatype "%1' cannot be used with an RLV enabled table"</b>
<b>Constant</b>	RLV_UNSUPPORTED_DATATYPE
<b>SAP Sybase Error Number</b>	3349
<b>SQL State</b>	WQ042
<b>SQL Code</b>	-1707L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the unsupported datatype
<b>Probable Cause</b>	You attempted to use an datatype that is not supported in combination with RLV.
<b>Error 1708</b>	<b>"The option "%1' cannot be used with RLV enabled"</b>
<b>Constant</b>	RLV_UNSUPPORTED_OPTION
<b>SAP Sybase Error Number</b>	3350
<b>SQL State</b>	WQ044
<b>SQL Code</b>	-1708L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the unsupported option
<b>Probable Cause</b>	You attempted to use an option that is not supported in combination with RLV.
<b>Error 1709</b>	<b>"Invalid DEFAULT value near '%1' on line %2"</b>
<b>Constant</b>	INVALID_DEFAULT_VALUE
<b>SAP Sybase Error Number</b>	3351
<b>SQL State</b>	42W10
<b>SQL Code</b>	-1709L

## Errors and Warnings

<b>Error 1709</b>	"Invalid DEFAULT value near '%1' on line %2"
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	The word or symbol where the invalid DEFAULT value has been detected.
<b>Parameter 2</b>	Line number.
<b>Probable Cause</b>	An invalid DEFAULT value was specified when creating or altering a table column.

## Messages 1710 through 1000008

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1710</b>	"Invalid value for INSERT near '%1' on line %2"
<b>Constant</b>	INVALID_INSERT_VALUE
<b>SAP Sybase Error Number</b>	3352
<b>SQL State</b>	42W11
<b>SQL Code</b>	-1710L
<b>ODBC 2 State</b>	37000
<b>ODBC 3 State</b>	42000
<b>Severity Code</b>	<i>15</i> on page 2
<b>Parameter 1</b>	The word or symbol where the invalid value has been detected.
<b>Parameter 2</b>	Line number.
<b>Probable Cause</b>	An invalid value was specified for a value in an INSERT statements.
<b>Error 1711</b>	"Cannot use a RLV DBSpace in this context."
<b>Constant</b>	RLV_DBSPACE_INVALID
<b>SAP Sybase Error Number</b>	3353
<b>SQL State</b>	WQ045
<b>SQL Code</b>	-1711L

<b>Error 1711</b>	"Cannot use a RLV DBSpace in this context."
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	A RLV dbspace is not a valid type of dbspace for the specified operation.

<b>Error 1712</b>	"An RLV forced merge on table '%1' has failed"
<b>Constant</b>	RLV_FORCED_MERGE_FAILED
<b>SAP Sybase Error Number</b>	3354
<b>SQL State</b>	WQ046
<b>SQL Code</b>	-1712L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The table name for the merge that failed
<b>Probable Cause</b>	A forced DDL merge has failed.

<b>Error 1713</b>	"The index type '%1' cannot be used with an RLV enabled table"
<b>Constant</b>	RLV_UNSUPPORTED_INDEX
<b>SAP Sybase Error Number</b>	3355
<b>SQL State</b>	WQ047
<b>SQL Code</b>	-1713L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	Name of the unsupported index type
<b>Probable Cause</b>	You attempted to use an index type that is not supported in combination with RLV.

## Errors and Warnings

<b>Error 1714</b>	<b>"The dbmIsync server did not have sufficient database permissions"</b>
<b>Constant</b>	SYNCCMD_CANT_ACCESS_RESULT
<b>SAP Sybase Error Number</b>	3356
<b>SQL State</b>	5RW50
<b>SQL Code</b>	-1714L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The SYNCHRONIZE statement attempts to store the results of the synchronization in the synchronize_results and synchronize_parameters tables. The user who executed the command, or the user specified in the USER clause of the SYNCHRONIZE statement must have permission to insert rows into these tables.
<b>Error 1715</b>	<b>"Invalid options for UPGRADE: SCRIPT FILE can only be specified with RESTART"</b>
<b>Constant</b>	UPGRADE_SCRIPT_EXTRA_CLAUSE
<b>SAP Sybase Error Number</b>	3387
<b>SQL State</b>	08X01
<b>SQL Code</b>	-1715L
<b>ODBC 2 State</b>	08004
<b>ODBC 3 State</b>	08004
<b>Severity Code</b>	<i>21</i> on page 2
<b>Probable Cause</b>	ALTER DATABASE UPGRADE statement with SCRIPT FILE clause cannot be combined with any other clause except for RESTART ON/OFF.
<b>Error 1716</b>	<b>"Statement %1 disallowed during upgrade from script"</b>
<b>Constant</b>	UPGRADE_DISALLOWED_STMT
<b>SAP Sybase Error Number</b>	3386

<b>Error 1716</b>	<b>"Statement %1 disallowed during upgrade from script"</b>
<b>SQL State</b>	08X02
<b>SQL Code</b>	-1716L
<b>ODBC 2 State</b>	08004
<b>ODBC 3 State</b>	08004
<b>Severity Code</b>	<i>21</i> on page 2
<b>Parameter 1</b>	Disallowed statement.
<b>Probable Cause</b>	Upgrade from script is not allowed to use the following statements: BACKUP, ALTER DATABASE UPGRADE.
<b>Error 1717</b>	<b>"The LOCK TABLE command is not supported for RLV tables"</b>
<b>Constant</b>	RLV_LOCK_TABLE_UNSUPPORTED
<b>SAP Sybase Error Number</b>	3388
<b>SQL State</b>	WQ048
<b>SQL Code</b>	-1717L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	You attempted to use the LOCK TABLE command on an RLV enabled table.
<b>Error 1718</b>	<b>"A local main cache already exists for this node"</b>
<b>Constant</b>	CACHE_DBSPACE_CREATION_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	3389
<b>SQL State</b>	WQ049
<b>SQL Code</b>	-1718L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2

## Errors and Warnings

<b>Error 1718</b>	<b>"A local main cache already exists for this node"</b>
<b>Probable Cause</b>	Creation of more than one user defined CACHE dbspace is not allowed per node.
<b>Error 1719</b>	<b>"The RENAME PATH of file for local main cache is not allowed"</b>
<b>Constant</b>	ALTER_DBSPACE_RENAME_PATH_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	3399
<b>SQL State</b>	WQ050
<b>SQL Code</b>	-1719L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Probable Cause</b>	The ALTER DBSPACE to RENAME PATH is not allowed for local main cache.
<b>Error 1720</b>	<b>"Multiplex Agent for Server '%1' not found"</b>
<b>Constant</b>	IQ_MULTIPLEX_AGENT_NOT_FOUND
<b>SAP Sybase Error Number</b>	3400
<b>SQL State</b>	WW111
<b>SQL Code</b>	-1720L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	There is no Agent assigned to this Multiplex Server.
<b>Probable Cause</b>	This Multiplex Server has no agent assigned to it.
<b>Error 1721</b>	<b>"Multiplex Agent for Server '%1' exists"</b>
<b>Constant</b>	IQ_MULTIPLEX_AGENT_EXISTS
<b>SAP Sybase Error Number</b>	3401

<b>Error 1721</b>	<b>"Multiplex Agent for Server '%1' exists"</b>
<b>SQL State</b>	WW157
<b>SQL Code</b>	-1721L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	There is already an Agent assigned to this Multiplex Server.
<b>Probable Cause</b>	This Multiplex Server already has an agent assigned to it.
<b>Error 1726</b>	<b>"The length of the agent password must be &gt; 0 and cannot exceeds %1 bytes."</b>
<b>Constant</b>	IQ_MULTIPLEX_INCORRECT_AGENT_PWD_LEN
<b>SAP Sybase Error Number</b>	3406
<b>SQL State</b>	WW158
<b>SQL Code</b>	-1726L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The maximum length of the value.
<b>Probable Cause</b>	The specified value for an agent password is 0 or too long. Specify a string or shorter string.
<b>Error 1728</b>	<b>"Function '%1' has invalid parameter '%2' ('%3')"</b>
<b>Constant</b>	SLERR_INVALID_PARAMETER_W_PARM
<b>SAP Sybase Error Number</b>	3408
<b>SQL State</b>	2FW93
<b>SQL Code</b>	-1728L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 1728</b>	<b>"Function '%1' has invalid parameter '%2' ('%3')"</b>
<b>Severity Code</b>	<i>16</i> on page 2
<b>Parameter 1</b>	The name of the function.
<b>Parameter 2</b>	The name of the parameter.
<b>Parameter 3</b>	Information about the parameter that caused the error.
<b>Probable Cause</b>	An error occurred while evaluating a parameter.
<b>Error 1000000</b>	<b>"ESCAPES option must be OFF. %1"</b>
<b>Constant</b>	EMSG_INVALIDQUOTEESCAPES
<b>SAP Sybase Error Number</b>	20660
<b>SQL State</b>	QDA00
<b>SQL Code</b>	-1000000L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Sybase IQ only supports 'LOAD TABLE' commands where the ESCAPES options must be OFF.
<b>Error 1000002</b>	<b>"Cannot get the index id for %2 from the catalog. %1"</b>
<b>Constant</b>	EMSG_CAT_CANTGETINDEXID
<b>SAP Sybase Error Number</b>	20662
<b>SQL State</b>	QDA02
<b>SQL Code</b>	-1000002L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	index id

<b>Error 1000002</b>	<b>"Cannot get the index id for %2 from the catalog. %1"</b>
<b>Probable Cause</b>	This is an internal error. Join processing is not able to find an index in the catalog. If this error occurs, it should be reported to Sybase.
<b>Error 1000003</b>	<b>"Cross-database joins are not supported. (%2 and %3) %1"</b>
<b>Constant</b>	EMSG_CAT_CROSSDBJOIN
<b>SAP Sybase Error Number</b>	20663
<b>SQL State</b>	QDA03
<b>SQL Code</b>	-1000003L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Fully qualified name of table specified in join.
<b>Parameter 3</b>	Fully qualified name of table specified in join.
<b>Probable Cause</b>	Cannot join tables from different databases.
<b>Error 1000004</b>	<b>"Index '%2' already exists in the catalog. %1"</b>
<b>Constant</b>	EMSG_CAT_DUPINDEXID
<b>SAP Sybase Error Number</b>	20664
<b>SQL State</b>	QDA04
<b>SQL Code</b>	-1000004L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Name of index that already exists.
<b>Probable Cause</b>	This is an internal error. Join processing is trying to create an index id that already exists. If this error occurs, it should be reported to Sybase.

## Errors and Warnings

<b>Error 1000006</b>	<b>"Only %2 NULL specifications on a column are permitted. %1"</b>
<b>Constant</b>	EMSG_TOO_MANY_NULL_STRINGS
<b>SAP Sybase Error Number</b>	20666
<b>SQL State</b>	QDA06
<b>SQL Code</b>	-1000006L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	maximum NULL specifications permitted
<b>Probable Cause</b>	A column specification in a LOAD statement can have a maximum number of NULL clauses.

<b>Error 1000008</b>	<b>"Unknown error. %1"</b>
<b>Constant</b>	EMSG_CAT_UNKNOWN
<b>SAP Sybase Error Number</b>	20668
<b>SQL State</b>	QDA08
<b>SQL Code</b>	-1000008L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	An error condition was encountered for which there is no message. If this error occurs, it should be reported to Sybase.

## Messages 1000009 through 1000040

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1000009</b>	<b>"Cannot DISABLE index "%2". It is open Read/Write and may have updates pending. %1"</b>
<b>Constant</b>	EMSG_CAT_INDEXENABLERW
<b>SAP Sybase Error Number</b>	20669
<b>SQL State</b>	QDA09
<b>SQL Code</b>	-1000009L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Name of the index user is attempting to disable.
<b>Parameter 2</b>	The index the user is attempting to disable.
<b>Probable Cause</b>	This index cannot be DISABLED. It is open for write access and may have updates pending. Wait until no other users are using the index.
<b>Error 1000010</b>	<b>"Cannot DISABLE index "%2". The index is in use. %1"</b>
<b>Constant</b>	EMSG_CAT_INDEXENABLESINDEX
<b>SAP Sybase Error Number</b>	20670
<b>SQL State</b>	QDA10
<b>SQL Code</b>	-1000010L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Name of the index user is attempting to disable.
<b>Probable Cause</b>	This index cannot be DISABLED. It is in use. Wait until no other users are using the index.

## Errors and Warnings

<b>Error 1000011</b>	<b>"Transaction %2 attempted to access '%4' created by transaction %3. %1"</b>
<b>Constant</b>	EMSG_CAT_FUTUREVERSION
<b>SAP Sybase Error Number</b>	20671
<b>SQL State</b>	QDA11
<b>SQL Code</b>	-1000011L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	The current transaction ID.
<b>Parameter 3</b>	The transaction ID that created the object the user is attempting to access.
<b>Parameter 4</b>	table or join index name
<b>Probable Cause</b>	Table Level Versioning doesn't allow access to versions newer than your current transaction ID.
<b>Error 1000012</b>	<b>"Index '%2' cannot be closed because it has %3 users. %1"</b>
<b>Constant</b>	EMSG_CAT_INDEXINUSE
<b>SAP Sybase Error Number</b>	20672
<b>SQL State</b>	QDA12
<b>SQL Code</b>	-1000012L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Name of the index that is being closed.
<b>Parameter 3</b>	The number of users currently using the index.

<b>Error 1000012</b>	<b>"Index '%2' cannot be closed because it has %3 users. %1"</b>
<b>Probable Cause</b>	This is an internal error. The index cannot be closed because it is in use. If this error occurs, it should be reported to Sybase.
<b>Error 1000014</b>	<b>"%2 MB is not sufficient for the load, update, or delete. %1"</b>
<b>Constant</b>	EMSG_INSUFFICIENT_LOAD_MEMORY
<b>SAP Sybase Error Number</b>	20674
<b>SQL State</b>	QDA14
<b>SQL Code</b>	-1000014L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	user specified upper bound on megabytes of heap memory load/delete/update can actually use
<b>Probable Cause</b>	The user can control the amount of heap memory a load/delete/update process (LOAD, INSERT VALUE, DELETE, SYNCHRONIZE, UPDATE) can use via the Load_Memory_MB option. If this memory limit isn't sufficient for the load/delete/update to run, then this exception is raised. To proceed, the user must either turnoff the limit (i.e., set Load_Memory_MB to zero) or increase the limit.
<b>Error 1000018</b>	<b>"The object cannot be opened for DROP or ALTER. It is already open. %1"</b>
<b>Constant</b>	EMSG_CAT_CANNOTOPENFORMETA
<b>SAP Sybase Error Number</b>	20678
<b>SQL State</b>	QDA18
<b>SQL Code</b>	-1000018L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 1000018</b>	"The object cannot be opened for DROP or ALTER. It is already open. %1"
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	The object that you have requested to DROP or ALTER cannot be opened for META access. Either the current connection or another connection has a cursor open on the table you are trying to DROP or ALTER or on the table to which the field or index you are trying open for META belongs. In order to proceed, all cursors open on this object must be closed.
<b>Error 1000022</b>	"Index '%2' has an invalid index type: %3. %1"
<b>Constant</b>	EMSG_CAT_INDEXBADTYPE
<b>SAP Sybase Error Number</b>	20682
<b>SQL State</b>	QDA22
<b>SQL Code</b>	-1000022L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	The index which has a bad type.
<b>Parameter 3</b>	The bad index type in question.
<b>Probable Cause</b>	This is an internal error. The index is of a type that is unknown to ASIQ. If this error occurs, it should be reported to Sybase.
<b>Error 1000024</b>	"For table pair %2, table "%3' has a datatype mismatch for column %4. %1"
<b>Constant</b>	EMSG_CAT_JINDEXDATATYPE
<b>SAP Sybase Error Number</b>	20684
<b>SQL State</b>	QDA24
<b>SQL Code</b>	-1000024L
<b>ODBC 2 State</b>	ERROR

<b>Error 1000024</b>	<b>"For table pair %2, table "%3' has a datatype mismatch for column %4. %1"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	tablename
<b>Parameter 3</b>	table number
<b>Parameter 4</b>	column number
<b>Probable Cause</b>	Corresponding columns' in the table pairs must be of the same data-type. (For example, INTEGER and INTEGER or CHAR and CHAR.) Matching datatypes such as CHAR and VARCHAR or INT and SMALLINT are not allowed.
<b>Error 1000026</b>	<b>"The join virtual table for table "%2' has duplicate columns in positions %3 and %4. %1"</b>
<b>Constant</b>	EMSG_CAT_JINDEXDUPFIELDS
<b>SAP Sybase Error Number</b>	20686
<b>SQL State</b>	QDA26
<b>SQL Code</b>	-1000026L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	tablename
<b>Parameter 3</b>	column position
<b>Parameter 4</b>	column position
<b>Probable Cause</b>	The join virtual table for table has duplicate columns. Perhaps the join predicate is improperly specified.

## Errors and Warnings

<b>Error 1000028</b>	"For table pair %2, table "%3' has a length value mismatch for column %4. %1"
<b>Constant</b>	EMSG_CAT_JINDEXKEYSIZE
<b>SAP Sybase Error Number</b>	20688
<b>SQL State</b>	QDA28
<b>SQL Code</b>	-1000028L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	table pair
<b>Parameter 3</b>	table name
<b>Parameter 4</b>	column number
<b>Probable Cause</b>	Corresponding columns in the table pair must be of the same length.
<b>Error 1000029</b>	"Cannot open the requested object for write in the current transaction (%2). Another user has write access in transaction %3. %1"
<b>Constant</b>	EMSG_CAT_ONLY1WRITER
<b>SAP Sybase Error Number</b>	20689
<b>SQL State</b>	QDA29
<b>SQL Code</b>	-1000029L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	The transaction id of the hopeful writer.
<b>Parameter 3</b>	The transaction id of the user currently writing.

<b>Error 1000029</b>	" <b>Cannot open the requested object for write in the current transaction (%2). Another user has write access in transaction %3. %1</b> "
<b>Probable Cause</b>	The ASIQ catalog allows only one transaction at a time to have write access to an object. The id of the user that is currently writing to the object can be found by running sp_iqtransaction and scanning the output for the transaction id of the writer that currently has write access.
<b>Warning 1000030</b>	"\nMaster archive header information\n"
<b>Constant</b>	EMSG__DB_HEADER_MSG1
<b>SAP Sybase Error Number</b>	20690
<b>SQL State</b>	QDA30
<b>SQL Code</b>	1000030L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> on page 2
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.
<b>Warning 1000032</b>	" <b>The ultimate/top table is %1\n</b> "
<b>Constant</b>	EMSG_CAT_JINDEXLOADMSGLINKTABLE1
<b>SAP Sybase Error Number</b>	20692
<b>SQL State</b>	00A32
<b>SQL Code</b>	1000032L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	table name
<b>Probable Cause</b>	This information message appears in the log when the CREATE JOIN command is executed.

## Errors and Warnings

<b>Warning 1000033</b>	"Database: %1"
<b>Constant</b>	EMSG_DB_HEADER_MSG2
<b>SAP Sybase Error Number</b>	20693
<b>SQL State</b>	QDA33
<b>SQL Code</b>	1000033L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	Database
<b>Probable Cause</b>	This message is displayed in context with other messages.
<b>Warning 1000034</b>	" Table Name Relationship"
<b>Constant</b>	EMSG_CAT_JINDEXLOADMSGLINKTABLE3
<b>SAP Sybase Error Number</b>	20694
<b>SQL State</b>	00A34
<b>SQL Code</b>	1000034L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Probable Cause</b>	This information message appears in the log when the CREATE JOIN command is executed.
<b>Warning 1000036</b>	"%1. %2 joined to "%3' %4"
<b>Constant</b>	EMSG_CAT_JINDEXLOADMSGTABLE
<b>SAP Sybase Error Number</b>	20696
<b>SQL State</b>	00A36
<b>SQL Code</b>	1000036L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK

<b>Warning 1000036</b>	"%1. %2 joined to "%3' %4"
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	argument 1 comment
<b>Parameter 2</b>	argument 2 comment
<b>Parameter 3</b>	argument 3 comment
<b>Parameter 4</b>	argument 4 comment
<b>Probable Cause</b>	This information message appears in the log when the CREATE JOIN command is executed.

<b>Warning 1000037</b>	"-----"
<b>Constant</b>	EMSG_CAT_JINDEXLOADMSGTRAILER
<b>SAP Sybase Error Number</b>	20697
<b>SQL State</b>	00A37
<b>SQL Code</b>	1000037L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Probable Cause</b>	This information message appears in the log when the CREATE JOIN command is executed.

<b>Warning 1000038</b>	"Backup date: %1"
<b>Constant</b>	EMSG_DB_HEADER_MSG3
<b>SAP Sybase Error Number</b>	20698
<b>SQL State</b>	QDA38
<b>SQL Code</b>	1000038L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	backup date

## Errors and Warnings

<b>Warning 1000038</b>	<b>"Backup date: %1"</b>
<b>Probable Cause</b>	This message displays the backup date.
<b>Warning 1000039</b>	<b>"Backup created by: %1"</b>
<b>Constant</b>	EMSG_DB_HEADER_MSG4
<b>SAP Sybase Error Number</b>	20699
<b>SQL State</b>	QDA39
<b>SQL Code</b>	1000039L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	user name
<b>Probable Cause</b>	This message displays the user who created the backup.
<b>Warning 1000040</b>	<b>"Comment: %1"</b>
<b>Constant</b>	EMSG_DB_HEADER_MSG5
<b>SAP Sybase Error Number</b>	20700
<b>SQL State</b>	QDA40
<b>SQL Code</b>	1000040L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	comment
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.

## Messages 1000041 through 1000061

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Warning 1000041</b>	<b>"Backup version: %1"</b>
<b>Constant</b>	EMSG_DB_HEADER_MSG6
<b>SAP Sybase Error Number</b>	20701
<b>SQL State</b>	QDA41
<b>SQL Code</b>	1000041L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	backup version
<b>Probable Cause</b>	This message displays the backup version.
<b>Warning 1000042</b>	<b>"Number of archive media in backup: %1"</b>
<b>Constant</b>	EMSG_DB_HEADER_MSG7
<b>SAP Sybase Error Number</b>	20702
<b>SQL State</b>	QDA42
<b>SQL Code</b>	1000042L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	number of archive media in backup
<b>Probable Cause</b>	This message displays how many media are in the backup.
<b>Warning 1000043</b>	<b>"Number of files in backup: %1"</b>
<b>Constant</b>	EMSG_DB_HEADER_MSG8
<b>SAP Sybase Error Number</b>	20703
<b>SQL State</b>	QDA43

## Errors and Warnings

<b>Warning 1000043</b>	"Number of files in backup: %1"
<b>SQL Code</b>	1000043L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	number of files in backup
<b>Probable Cause</b>	This message displays the number of files in the backup.
<b>Error 1000044</b>	<b>"The join for table "%2" does not have enough columns defined (%3). %1"</b>
<b>Constant</b>	EMSG_CAT_JINDEXNOFIELDS
<b>SAP Sybase Error Number</b>	20704
<b>SQL State</b>	QDA44
<b>SQL Code</b>	-1000044L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	table name
<b>Parameter 3</b>	number of columns
<b>Probable Cause</b>	Cannot define a join with zero columns. If this error occurs, it should be reported to Sybase.
<b>Error 1000045</b>	<b>"Index %2 does not exist. %1"</b>
<b>Constant</b>	EMSG.utility_indexnotfound
<b>SAP Sybase Error Number</b>	20705
<b>SQL State</b>	QDA45
<b>SQL Code</b>	-1000045L
<b>ODBC 2 State</b>	ERROR

<b>Error 1000045</b>	<b>"Index %2 does not exist. %1"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	index name given by the user
<b>Probable Cause</b>	User has specified an index which does not exist in any table within the current database.
<b>Error 1000046</b>	<b>"No Field passed to PutMCIField. %1"</b>
<b>Constant</b>	EMSG_CAT_NOFIELDPUTMCI
<b>SAP Sybase Error Number</b>	20706
<b>SQL State</b>	QDA46
<b>SQL Code</b>	-1000046L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	This error should not occur during normal operation and should be reported to Sybase. See the iqmsg file for additional diagnostic information.
<b>Error 1000047</b>	<b>"For table pair %2, table '%3' has a precision mismatch in column %4. %1"</b>
<b>Constant</b>	EMSG_CAT_JINDEXPRECISION
<b>SAP Sybase Error Number</b>	20707
<b>SQL State</b>	QDA47
<b>SQL Code</b>	-1000047L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2

## Errors and Warnings

<b>Error 1000047</b>	<b>"For table pair %2, table '%3' has a precision mismatch in column %4. %1"</b>
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	table pair
<b>Parameter 3</b>	table name
<b>Parameter 4</b>	column number
<b>Probable Cause</b>	Corresponding columns in the join must have equal precision.
<b>Error 1000048</b>	<b>"For table pair %2, table '%3' has a scale mismatch in column %4. %1"</b>
<b>Constant</b>	EMSG_CAT_JINDEXSCALE
<b>SAP Sybase Error Number</b>	20708
<b>SQL State</b>	QDA48
<b>SQL Code</b>	-1000048L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	table pair
<b>Parameter 3</b>	table name
<b>Parameter 4</b>	column number
<b>Probable Cause</b>	Corresponding columns in the join must have equal scale.
<b>Error 1000049</b>	<b>"'%2' is being used in a self join. Self joins are not allowed. %1"</b>
<b>Constant</b>	EMSG_CAT_JINDEXSELFJOIN
<b>SAP Sybase Error Number</b>	20709
<b>SQL State</b>	QDA49
<b>SQL Code</b>	-1000049L
<b>ODBC 2 State</b>	ERROR

<b>Error 1000049</b>	<b>"'%2' is being used in a self join. Self joins are not allowed. %1"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	table name
<b>Probable Cause</b>	Self joins are not allowed.

<b>Error 1000050</b>	<b>"Table '%2' is used in the join twice. %1"</b>
<b>Constant</b>	EMSG_CAT_JINDEXTABLETWICE
<b>SAP Sybase Error Number</b>	20710
<b>SQL State</b>	QDA50
<b>SQL Code</b>	-1000050L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	tablename
<b>Probable Cause</b>	A table cannot be used twice in a join.

<b>Error 1000051</b>	<b>"Cannot retrieve a row from the SYSIQJOINIXTABLE system table. %1"</b>
<b>Constant</b>	EMSG_CAT_JIXTABLEFIND
<b>SAP Sybase Error Number</b>	20711
<b>SQL State</b>	QDA51
<b>SQL Code</b>	-1000051L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2

## Errors and Warnings

<b>Error 1000051</b>	<b>"Cannot retrieve a row from the SYSIQJOINIXTABLE system table. %1"</b>
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	This is an internal error. Cannot retrieve a row from the SYSIQJOINIXTABLE system table. If this error occurs, it should be reported to Sybase.
<b>Error 1000052</b>	<b>"Cannot delete a row from the SYSIQJOINIXTABLE system table. %1"</b>
<b>Constant</b>	EMSG_CAT_JIXTABLEDELETE
<b>SAP Sybase Error Number</b>	20712
<b>SQL State</b>	QDA52
<b>SQL Code</b>	-1000052L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	This is an internal error. Cannot delete a row from the SYSIQJOINIXTABLE system table. If this error occurs, it should be reported to Sybase.
<b>Error 1000053</b>	<b>"Cannot commit changes to the SYSIQJOINIXTABLE system table. %1"</b>
<b>Constant</b>	EMSG_CAT_JIXTABLEFLUSH
<b>SAP Sybase Error Number</b>	20713
<b>SQL State</b>	QDA53
<b>SQL Code</b>	-1000053L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception

<b>Error 1000053</b>	<b>"Cannot commit changes to the SYSIQJOINIXTABLE system table. %1"</b>
<b>Probable Cause</b>	This is an internal error. Cannot commit changes to the SYSIQJOINIXTABLE system table. If this error occurs, it should be reported to Sybase.
<b>Error 1000054</b>	<b>"Cannot open %2 in Meta (exclusive) mode. Object is already open. %1"</b>
<b>Constant</b>	EMSG_CAT_METAACCESS
<b>SAP Sybase Error Number</b>	20714
<b>SQL State</b>	QDA54
<b>SQL Code</b>	-1000054L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	object name
<b>Probable Cause</b>	The object cannot be opened for exclusive access; it is already open.
<b>Warning 1000055</b>	<b>"Warning: %1"</b>
<b>Constant</b>	EMSG_CLBK_WARNING
<b>SAP Sybase Error Number</b>	20715
<b>SQL State</b>	01A55
<b>SQL Code</b>	1000055L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	explanation of %1
<b>Probable Cause</b>	This message appears in context with other messages.

## Errors and Warnings

<b>Error 1000056</b>	<b>"Cannot convert from datatype '%2' to '%3' for column '%4'. %1"</b>
<b>Constant</b>	EMSG_CAT_NOCONVERSIONPOSSIBLE
<b>SAP Sybase Error Number</b>	20716
<b>SQL State</b>	QDA56
<b>SQL Code</b>	-1000056L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	datatype
<b>Parameter 3</b>	datatype
<b>Parameter 4</b>	column name
<b>Probable Cause</b>	Implicit conversion for this column is not possible.
<b>Error 1000057</b>	<b>"Column '%2' has an unknown datatype: '%3'. %1"</b>
<b>Constant</b>	EMSG_CAT_NODATATYPE
<b>SAP Sybase Error Number</b>	20717
<b>SQL State</b>	QDA57
<b>SQL Code</b>	-1000057L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column number
<b>Parameter 3</b>	the unknown datatype
<b>Probable Cause</b>	The column is of a datatype that is unknown to ASIQ. This is an internal error. If this error occurs, it should be reported to Sybase.

<b>Warning 1000058</b>	"Platform: %1"
<b>Constant</b>	EMSG_DB_HEADER_MSG9
<b>SAP Sybase Error Number</b>	20718
<b>SQL State</b>	QDA58
<b>SQL Code</b>	1000058L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	platform
<b>Probable Cause</b>	This is an informational message reporting the platform type.
<b>Error 1000060</b>	"Column '%2', PRECISION (%3) cannot be greater than %4. %1"
<b>Constant</b>	EMSG_CAT_PRECISIONTOOBIG
<b>SAP Sybase Error Number</b>	20720
<b>SQL State</b>	QDA60
<b>SQL Code</b>	-1000060L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column number
<b>Parameter 3</b>	requested precision
<b>Parameter 4</b>	maximum allowed precision
<b>Probable Cause</b>	The precision requested by the user is larger than what is allowed for the datatype.
<b>Error 1000061</b>	"Column %2, PRECISION (%3) cannot be less than 0. %1"
<b>Constant</b>	EMSG_CAT_PRECISIONTOOSMALL

<b>Error 1000061</b>	"Column %2, PRECISION (%3) cannot be less than 0. %1"
<b>SAP Sybase Error Number</b>	20721
<b>SQL State</b>	QDA61
<b>SQL Code</b>	-1000061L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column name
<b>Parameter 3</b>	column precision
<b>Probable Cause</b>	The precision specified by the user is less than zero.

## Messages 1000062 through 1000084

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1000062</b>	"Cannot add column '%3' with 'not null' constraint on table %2 with data. %1"
<b>Constant</b>	EMSG_TABLEHASDATA
<b>SAP Sybase Error Number</b>	20722
<b>SQL State</b>	QDC35
<b>SQL Code</b>	-1000062L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	table name
<b>Parameter 3</b>	column name

<b>Error 1000062</b>	<b>"Cannot add column '%3' with 'not null' constraint on table %2 with data. %1"</b>
<b>Probable Cause</b>	The user tried to ALTER ADD a NOT NULL column to a table that has data. The newly added column would violate the NOT NULL constraint as it would have null data.
<b>Error 1000063</b>	<b>"Cannot enforce the NOT NULL constraint. Column %2 has NULL data. %1"</b>
<b>Constant</b>	EMSG_COLUMNHASNULLDATA
<b>SAP Sybase Error Number</b>	20723
<b>SQL State</b>	QDC34
<b>SQL Code</b>	-1000063L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column name
<b>Probable Cause</b>	The user tried ALTER MODIFY column NOT NULL on a column that used to allow nulls and has null data. The user has to first delete the null rows before altering the column to enforce the NOT NULL constraint.
<b>Error 1000064</b>	<b>"Column %2 can not be altered because it participates in join %3. %1"</b>
<b>Constant</b>	EMSG_CAT_JOINFIELDINPREJOIN
<b>SAP Sybase Error Number</b>	20724
<b>SQL State</b>	QDA64
<b>SQL Code</b>	-1000064L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the error

## Errors and Warnings

<b>Error 1000064</b>	<b>"Column %2 can not be altered because it participates in join %3. %1"</b>
<b>Parameter 2</b>	columns
<b>Parameter 3</b>	join
<b>Probable Cause</b>	A column/field that participates in a join cannot be altered. Joins on this field must be deleted before an ALTER can be performed.
<b>Error 1000065</b>	<b>"Table %2 must be owned by the creator of the join. %1"</b>
<b>Constant</b>	EMSG_CAT_TABLEOWNERDIFF
<b>SAP Sybase Error Number</b>	20725
<b>SQL State</b>	QDA65
<b>SQL Code</b>	-1000065L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the error
<b>Parameter 2</b>	tablename
<b>Probable Cause</b>	This error message is given during CREATE JOIN when one of the tables specified is not owned by the owner of the join. Joins can only be created from tables of the same owner.
<b>Error 1000066</b>	<b>"ALTER on the column would interfere with the natural join to table %2 in join %3. %1"</b>
<b>Constant</b>	EMSG_CAT_JOINFIELDNATMAT
<b>SAP Sybase Error Number</b>	20726
<b>SQL State</b>	QDA66
<b>SQL Code</b>	-1000066L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the error

<b>Error 1000066</b>	"ALTER on the column would interfere with the natural join to table %2 in join %3. %1"
<b>Parameter 2</b>	tablename
<b>Parameter 3</b>	join
<b>Probable Cause</b>	This message is displayed when using the ALTER command or adding columns to a table that participates in a join.

<b>Error 1000067</b>	"Table '%2' is not defined in the catalog. %1"
<b>Constant</b>	EMSG_CAT_TABLENOTINCAT
<b>SAP Sybase Error Number</b>	20727
<b>SQL State</b>	QDA67
<b>SQL Code</b>	-1000067L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> 4 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	tablename
<b>Probable Cause</b>	This is an internal error. The table does not exist in the catalog. If this error occurs, it should be reported to Sybase.

<b>Warning 1000069</b>	" %1; %2 blocks; %3"
<b>Constant</b>	EMSG_DB_HEADER_MSG10
<b>SAP Sybase Error Number</b>	20729
<b>SQL State</b>	QDA69
<b>SQL Code</b>	1000069L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	argument 1 comment
<b>Parameter 2</b>	argument 2 comment

## Errors and Warnings

<b>Warning 1000069</b>	" %1; %2 blocks; %3"
<b>Parameter 3</b>	argument 3 comment
<b>Probable Cause</b>	This message is an informational message displayed in context with other messages.
<b>Warning 1000070</b>	"File listing:"
<b>Constant</b>	EMSG_DB_HEADER_MSG11
<b>SAP Sybase Error Number</b>	20730
<b>SQL State</b>	QDA70
<b>SQL Code</b>	1000070L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> on page 2
<b>Probable Cause</b>	This message is an informational message displayed in context with other messages.
<b>Warning 1000071</b>	" %1"
<b>Constant</b>	EMSG_DB_HEADER_MSG14
<b>SAP Sybase Error Number</b>	20731
<b>SQL State</b>	QDA71
<b>SQL Code</b>	1000071L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	argument 1 comment
<b>Probable Cause</b>	This message is an informational message displayed in context with other messages.
<b>Warning 1000072</b>	"Hole listing (%1):"
<b>Constant</b>	EMSG_DB_HEADER_MSG20

<b>Warning 1000072</b>	"Hole listing (%1):"
<b>SAP Sybase Error Number</b>	20732
<b>SQL State</b>	QDA72
<b>SQL Code</b>	1000072L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	argument 1 comment
<b>Probable Cause</b>	This message is an informational message displayed in context with other messages.
<b>Warning 1000073</b>	" start: %1; size: %2"
<b>Constant</b>	EMSG_DB_HEADER_MSG21
<b>SAP Sybase Error Number</b>	20733
<b>SQL State</b>	QDA73
<b>SQL Code</b>	1000073L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	Parameter 1 description
<b>Parameter 2</b>	Parameter 2 description
<b>Probable Cause</b>	This message is displayed in context with other messages.
<b>Warning 1000074</b>	"Offset %1 Length %2, %3%4%5"
<b>Constant</b>	EMSG_PREVIEWFILLER
<b>SAP Sybase Error Number</b>	20734
<b>SQL State</b>	QDA74
<b>SQL Code</b>	1000074L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Warning 1000074</b>	"Offset %1 Length %2, %3%4%5"
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	Parameter 1 description
<b>Parameter 2</b>	Parameter 2 description
<b>Parameter 3</b>	Parameter 3 description
<b>Parameter 4</b>	Parameter 4 description
<b>Parameter 5</b>	Parameter 5 description
<b>Probable Cause</b>	This message is displayed in context with other messages.
<b>Warning 1000075</b>	"%1, %2%3%4"
<b>Constant</b>	EMSG_PREVIEWFILLER1
<b>SAP Sybase Error Number</b>	20735
<b>SQL State</b>	QDA75
<b>SQL Code</b>	1000075L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	Parameter 1 description
<b>Parameter 2</b>	Parameter 2 description
<b>Parameter 3</b>	Parameter 3 description
<b>Parameter 4</b>	Parameter 4 description
<b>Probable Cause</b>	This message is displayed in context with other messages.
<b>Warning 1000076</b>	"%1, %2%3%4"
<b>Constant</b>	EMSG_PREVIEWFILLER2
<b>SAP Sybase Error Number</b>	20736
<b>SQL State</b>	QDA76
<b>SQL Code</b>	1000076L

<b>Warning 1000076</b>	"%1, %2%3%4"
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	Parameter 1 description
<b>Parameter 2</b>	Parameter 2 description
<b>Parameter 3</b>	Parameter 3 description
<b>Parameter 4</b>	Parameter 4 description
<b>Probable Cause</b>	This message is displayed in context with other messages.
<b>Warning 1000077</b>	"%1, %2%3%4"
<b>Constant</b>	EMSG_PREVIEWFILLER4
<b>SAP Sybase Error Number</b>	20737
<b>SQL State</b>	QDA77
<b>SQL Code</b>	1000077L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	Parameter 1 description
<b>Parameter 2</b>	Parameter 2 description
<b>Parameter 3</b>	Parameter 3 description
<b>Parameter 4</b>	Parameter 4 description
<b>Probable Cause</b>	This message is displayed in context with other messages.
<b>Error 1000078</b>	<b>"IQ PAGE SIZE of '%2' for database '%3' is not valid. %1"</b>
<b>Constant</b>	EMSG_HDB_INVALIDPAGESIZE
<b>SAP Sybase Error Number</b>	20738
<b>SQL State</b>	QDA78
<b>SQL Code</b>	-1000078L

## Errors and Warnings

<b>Error 1000078</b>	<b>"IQ PAGE SIZE of '%2' for database '%3' is not valid. %1"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	requested PAGE SIZE
<b>Parameter 3</b>	database name
<b>Probable Cause</b>	An invalid IQ PAGE SIZE was specified. IQ PAGE SIZE must be one of 1024, 2048, 4096, 8192, 16384, 32768, 65536, 131072, 262144, 524288. See the Reference Manual and Admin and Performance Guide for IQ PAGE SIZE recommendations.

<b>Error 1000079</b>	<b>"IQ SIZE of '%2' for database '%3' is not valid. %1"</b>
<b>Constant</b>	EMSG_HDB_INVALIDDATABASESIZE
<b>SAP Sybase Error Number</b>	20739
<b>SQL State</b>	QDA79
<b>SQL Code</b>	-1000079L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	requested IQ SIZE
<b>Parameter 3</b>	database name
<b>Probable Cause</b>	The maximum IQ SIZE is 128GB.

<b>Error 1000082</b>	<b>"The insert must contain all of the table %2 columns because it participates in one or more joins. %1"</b>
<b>Constant</b>	EMSG_INSRT_MUSTBE_FULLWIDTH
<b>SAP Sybase Error Number</b>	20742
<b>SQL State</b>	QDA82

<b>Error 1000082</b>	<b>"The insert must contain all of the table %2 columns because it participates in one or more joins. %1"</b>
<b>SQL Code</b>	-1000082L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	table name
<b>Probable Cause</b>	If a table participates in a join, then the user cannot load data into that table using a partial width insert.
<b>Error 1000083</b>	<b>"The field array entry must be given a name. %1"</b>
<b>Constant</b>	EMSG_HDB_FIELDNONAME
<b>SAP Sybase Error Number</b>	20743
<b>SQL State</b>	QDA83
<b>SQL Code</b>	-1000083L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1000084</b>	<b>"The %2th join field array entry for table '%3' must have a name. %1"</b>
<b>Constant</b>	EMSG_HDB_FIELDNOJOINNAME
<b>SAP Sybase Error Number</b>	20744
<b>SQL State</b>	QDA84
<b>SQL Code</b>	-1000084L
<b>ODBC 2 State</b>	ERROR

<b>Error 1000084</b>	"The %2th join field array entry for table "%3' must have a name. %1"
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	field array entry
<b>Parameter 3</b>	tablename
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.

## Messages 1000085 through 1000107

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1000085</b>	"The join field array for table '%2' must have at least one entry. %1"
<b>Constant</b>	EMSG_HDB_FIELDNOJOINNAMES
<b>SAP Sybase Error Number</b>	20745
<b>SQL State</b>	QDA85
<b>SQL Code</b>	-1000085L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	tablename
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.

<b>Warning 1000086</b>	"Length %1 %2%3%4"
<b>Constant</b>	EMSG_PREVIEWFILLERA
<b>SAP Sybase Error Number</b>	20746

<b>Warning 1000086</b>	"Length %1 %2%3%4"
<b>SQL State</b>	QDA86
<b>SQL Code</b>	1000086L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	Parameter 1 description
<b>Parameter 2</b>	Parameter 2 description
<b>Parameter 3</b>	Parameter 3 description
<b>Parameter 4</b>	Parameter 4 description
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.

<b>Warning 1000087</b>	"Delimiter %1 %2%3%4"
<b>Constant</b>	EMSG_PREVIEWFILLERCD
<b>SAP Sybase Error Number</b>	20747
<b>SQL State</b>	QDA87
<b>SQL Code</b>	1000087L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	delimiter name
<b>Parameter 2</b>	Parameter 2 description
<b>Parameter 3</b>	Parameter 3 description
<b>Parameter 4</b>	Parameter 4 description
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.

## Errors and Warnings

<b>Warning 1000088</b>	"Offset %1, Length %2, %3 nulls, %4%5%6 %7"
<b>Constant</b>	EMSG_PREVIEWOFFSET
<b>SAP Sybase Error Number</b>	20748
<b>SQL State</b>	QDA88
<b>SQL Code</b>	1000088L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	offset
<b>Parameter 2</b>	length
<b>Parameter 3</b>	nulls
<b>Parameter 4</b>	parameter 4 description
<b>Parameter 5</b>	parameter 5 description
<b>Parameter 6</b>	parameter 6 description
<b>Parameter 7</b>	parameter 7 description
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.
<b>Warning 1000089</b>	"Length %1, %2 nulls, %3%4%5 %6"
<b>Constant</b>	EMSG_PREVIEWLENGTH
<b>SAP Sybase Error Number</b>	20749
<b>SQL State</b>	QDA89
<b>SQL Code</b>	1000089L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	length
<b>Parameter 2</b>	nulls

<b>Warning 1000089</b>	"Length %1, %2 nulls, %3%4%5 %6"
<b>Parameter 3</b>	parameter 3 description
<b>Parameter 4</b>	parameter 4 description
<b>Parameter 5</b>	parameter 5 description
<b>Parameter 6</b>	parameter 6 description
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.
<b>Warning 1000090</b>	"%1, %2 nulls, %3%4%5 %6"
<b>Constant</b>	EMSG_PREVIEWPREFIX1
<b>SAP Sybase Error Number</b>	20750
<b>SQL State</b>	QDA90
<b>SQL Code</b>	1000090L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	length
<b>Parameter 2</b>	nulls
<b>Parameter 3</b>	parameter 3 description
<b>Parameter 4</b>	parameter 4 description
<b>Parameter 5</b>	parameter 5 description
<b>Parameter 6</b>	parameter 6 description
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.
<b>Warning 1000091</b>	"%1, %2 nulls, %3%4%5 %6"
<b>Constant</b>	EMSG_PREVIEWPREFIX2
<b>SAP Sybase Error Number</b>	20751
<b>SQL State</b>	QDA91

## Errors and Warnings

<b>Warning 1000091</b>	"%1, %2 nulls, %3%4%5 %6"
<b>SQL Code</b>	1000091L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	length
<b>Parameter 2</b>	nulls
<b>Parameter 3</b>	parameter 3 description
<b>Parameter 4</b>	parameter 4 description
<b>Parameter 5</b>	parameter 5 description
<b>Parameter 6</b>	parameter 6 description
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.
<b>Error 1000092</b>	<b>"Table %2 must have a name for the join field array. %1"</b>
<b>Constant</b>	EMSG_HDB_TABLENOJOINNAME
<b>SAP Sybase Error Number</b>	20752
<b>SQL State</b>	QDA92
<b>SQL Code</b>	-1000092L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for %2
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Warning 1000093</b>	"%1, %2 nulls, %3%4%5 %6"
<b>Constant</b>	EMSG_PREVIEWPREFIX4

<b>Warning 1000093</b>	"%1, %2 nulls, %3%4%5 %6"
<b>SAP Sybase Error Number</b>	20753
<b>SQL State</b>	QDA93
<b>SQL Code</b>	1000093L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	Parameter 1 description
<b>Parameter 2</b>	Parameter 2 description
<b>Parameter 3</b>	Parameter 3 description
<b>Parameter 4</b>	Parameter 4 description
<b>Parameter 5</b>	Parameter 5 description
<b>Parameter 6</b>	Parameter 6 description
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.
<b>Error 1000094</b>	<b>"Sufficient memory cannot be found for the LOAD. Increasing the Load_Memory_MB or decreasing the BLOCK FACTOR or BLOCK SIZE will allow the LOAD to proceed. %1"</b>
<b>Constant</b>	EMSG_BLOCK_FACTOR_SIZE_LOAD_MEMORY
<b>SAP Sybase Error Number</b>	20754
<b>SQL State</b>	QDA94
<b>SQL Code</b>	-1000094L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.

## Errors and Warnings

<b>Error 1000094</b>	<b>"Sufficient memory cannot be found for the LOAD. Increasing the Load_Memory_MB or decreasing the BLOCK FACTOR or BLOCK SIZE will allow the LOAD to proceed. %1"</b>
<b>Probable Cause</b>	When the user explicitly sets Load_Memory_MB, the LOAD process applies various heuristics for load parameters in an attempt to find a combination such that the memory required is not more than what the user specified. For a fixed width LOAD, BLOCK FACTOR indicates the minimal number of rows that must be read into memory for each read. The default BLOCK FACTOR is 10,000. Decreasing the BLOCK FACTOR will make the LOAD's internal memory requirements smaller. For a variable length input LOAD, BLOCK SIZE represents the size in bytes in which input data should be read. The default BLOCK SIZE is 500,000 bytes. Decreasing the BLOCK SIZE for a variable width input load will reduce LOAD's memory requirements. Alternatively, the Load_Memory_MB option setting could be raised.

<b>Warning 1000096</b>	<b>"Delimiter %1 %2 nulls, %3%4%5 %6"</b>
<b>Constant</b>	EMSG_PREVIEWCD
<b>SAP Sybase Error Number</b>	20756
<b>SQL State</b>	QDA96
<b>SQL Code</b>	1000096L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	delimiter
<b>Parameter 2</b>	nulls
<b>Parameter 3</b>	parameter 3 description
<b>Parameter 4</b>	parameter 4 description
<b>Parameter 5</b>	parameter 5 description
<b>Parameter 6</b>	parameter 6 description
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.

<b>Error 1000097</b>	<b>"Parse Error in Command String at '%2'. %1"</b>
<b>Constant</b>	EMSG_PARSEERROR
<b>SAP Sybase Error Number</b>	20757
<b>SQL State</b>	QDA97
<b>SQL Code</b>	-1000097L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Start of the parse error
<b>Probable Cause</b>	Consult the IQ reference manual for the DBCC grammar
<b>Error 1000099</b>	<b>"The PAGE SIZE divided by the BLOCK SIZE must be equal to 2, 4, 8, or 16. DATABASE: %2 PAGE SIZE: %3 BLOCK SIZE: %4 %1"</b>
<b>Constant</b>	EMSG_HDB_INVALIDCHUNKSIZE
<b>SAP Sybase Error Number</b>	20759
<b>SQL State</b>	QDA99
<b>SQL Code</b>	-1000099L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	database name
<b>Parameter 3</b>	page size
<b>Parameter 4</b>	block size
<b>Probable Cause</b>	(PAGE SIZE)/(BLOCK SIZE) must be one of 2, 4, 8, 16. Adjust the PAGE SIZE or the BLOCK SIZE in the CREATE DATABASE statement.

## Errors and Warnings

<b>Error 1000100</b>	" <b>Cannot INSERT, LOAD, or UPDATE a join virtual table. %1</b> "
<b>Constant</b>	EMSG_SQL_NOINSERTJVT
<b>SAP Sybase Error Number</b>	20760
<b>SQL State</b>	QDB00
<b>SQL Code</b>	-1000100L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	The user is not allowed to INSERT to or LOAD a join virtual table. Instead you must INSERT to or LOAD the tables which participate in the join and execute the SYNCHRONIZE command.
<b>Error 1000101</b>	" <b>%2 not supported by Sybase IQ. %1</b> "
<b>Constant</b>	EMSG_SQL_STMT_NOTSUPPORTED
<b>SAP Sybase Error Number</b>	20761
<b>SQL State</b>	QDB01
<b>SQL Code</b>	-1000101L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	sql statement type
<b>Parameter 2</b>	location of the exception
<b>Probable Cause</b>	The statement in question is not supported by Sybase IQ.
<b>Error 1000103</b>	" <b>Cannot find an index for field '%2'. Every field must have at least one index. Current IndexCount = %3. %1</b> "
<b>Constant</b>	EMSG_CAT_FIELD_HAS_NOINDEX
<b>SAP Sybase Error Number</b>	20763

<b>Error 1000103</b>	<b>"Cannot find an index for field '%2'. Every field must have at least one index. Current IndexCount = %3. %1"</b>
<b>SQL State</b>	QDB03
<b>SQL Code</b>	-1000103L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Field name
<b>Parameter 2</b>	Number of indexes found for the named field.
<b>Parameter 3</b>	location of the exception
<b>Probable Cause</b>	This error should not occur during normal operation. Every field in ASIQ will have at least one index (the automatically generated FP index). This error occurs, the operation should be retried. If the error persists, it should be reported to Sybase. Extra information may have been output to the iqmsg file.

<b>Warning 1000104</b>	<b>"in join virtual table '%1'%2"</b>
<b>Constant</b>	EMSG_DELETE_CBTNAMEJOIN
<b>SAP Sybase Error Number</b>	20764
<b>SQL State</b>	01B04
<b>SQL Code</b>	1000104L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	Parameter 1 description
<b>Parameter 2</b>	Parameter 2 description
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.

<b>Warning 1000105</b>	<b>"%1"</b>
<b>Constant</b>	EMSG_DELETE_CBTNAME1TABLE

## Errors and Warnings

<b>Warning 1000105</b>	"%1"
<b>SAP Sybase Error Number</b>	20765
<b>SQL State</b>	01B05
<b>SQL Code</b>	1000105L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	Parameter 1 description
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.
<b>Error 1000106</b>	<b>"Local temporary table, %2, must be committed in order to create an index. %1"</b>
<b>Constant</b>	EMSG_CAT_CANNOT_CREATEIDX_ONLTT
<b>SAP Sybase Error Number</b>	20766
<b>SQL State</b>	QDB06
<b>SQL Code</b>	-1000106L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception.
<b>Parameter 2</b>	Tablename
<b>Probable Cause</b>	To be able to create an index for a local temporary table, the table must be in a committed state. If this message occurs, the user has tried to execute a CREATE INDEX on a local temporary table that has had data inserted, deleted, or updated that has not yet been committed.
<b>Warning 1000107</b>	<b>"For table '%1' in join virtual table '%2', \n%3 left outer rows with %4 columns will be moved (inserted/deleted).\n"</b>
<b>Constant</b>	EMSG_DELETE_CBTLOUTERROWSMOVED

<b>Warning 1000107</b>	"For table '%1' in join virtual table '%2', \n%3 left outer rows with %4 columns will be moved (inserted/deleted).\n"
<b>SAP Sybase Error Number</b>	20767
<b>SQL State</b>	01B07
<b>SQL Code</b>	1000107L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	tablename
<b>Parameter 2</b>	join virtual table
<b>Parameter 3</b>	number of rows moved
<b>Parameter 4</b>	number of columns
<b>Probable Cause</b>	This is an informational message displayed in context with other messages. The message displays the number of rows moved during an insert to or delete from a join.

## Messages 1000108 through 1000133

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Warning 1000108</b>	"The DELETE where clause yielded %1 rows, but table '%2' has no data."
<b>Constant</b>	EMSG_DELETE_TABLENODATA
<b>SAP Sybase Error Number</b>	20768
<b>SQL State</b>	01B08
<b>SQL Code</b>	1000108L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	number of rows
<b>Parameter 2</b>	tablename

## Errors and Warnings

<b>Warning 1000108</b>	"The DELETE where clause yielded %1 rows, but table "%2' has no data."
<b>Probable Cause</b>	This is an internal error. This warning should not occur during normal use. If this error occurs, it should be reported to Sybase.
<b>Error 1000110</b>	"The wrong SIndex has been opened for a fast projection index. %1"
<b>Constant</b>	EMSG_CAT_WRONGSINDEX
<b>SAP Sybase Error Number</b>	20770
<b>SQL State</b>	QDB10
<b>SQL Code</b>	-1000110L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	This is an internal error and should not occur. Diagnostic information has been output to the iqmsg file. If the error occurs, it should be reported to Sybase. The operation that caused the error may be tried again.
<b>Error 1000111</b>	"The wrong FP Index has been opened for a field. %1"
<b>Constant</b>	EMSG_CAT_WRONGFPOPENED
<b>SAP Sybase Error Number</b>	20771
<b>SQL State</b>	QDB11
<b>SQL Code</b>	-1000111L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.

<b>Error 1000111</b>	"The wrong FP Index has been opened for a field. %1"
<b>Probable Cause</b>	This is an internal error and should not occur. Diagnostic information has been output to the iqmsg file. If the error occurs, it should be reported to Sybase. The operation that caused the error may be tried again.

<b>Error 1000112</b>	"The EBM on the field's columnDescriptor does not match the column EBM on the FPIIndex. %1"
<b>Constant</b>	EMSG_CAT_EBMSDONTMATCH
<b>SAP Sybase Error Number</b>	20772
<b>SQL State</b>	QDB12
<b>SQL Code</b>	-1000112L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	This is an internal error and should not occur. Diagnostic information has been output to the iqmsg file. If the error occurs, it should be reported to Sybase. The operation that caused the error may be tried again.

<b>Error 1000113</b>	"Field %2 does not have an FP index. %1"
<b>Constant</b>	EMSG_CAT_FIELD_HAS_NOFPINDEX
<b>SAP Sybase Error Number</b>	20773
<b>SQL State</b>	QDB13
<b>SQL Code</b>	-1000113L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	Field name.

## Errors and Warnings

<b>Error 1000113</b>	<b>"Field %2 does not have an FP index. %1"</b>
<b>Probable Cause</b>	This error should not occur during normal operation. Every field has an FP index which is created automatically when the field is created. If the error occurs, diagnostic information will be output to the iqmsg file and the operation that caused it may be tried again. If the problem persists, the server should be shutdown and restarted. An occurrence of this error should be reported to Sybase.
<b>Error 1000114</b>	<b>"CMP index can only be created on two distinct columns having identical datatypes. %1"</b>
<b>Constant</b>	EMSG_CMP_NOT_ON_TWOCOLUMNS
<b>SAP Sybase Error Number</b>	20774
<b>SQL State</b>	QDB14
<b>SQL Code</b>	-1000114L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	A CMP index is an index that can be only created on two columns. You cannot create a single column CMP index; nor can you create a CMP index on three or more columns. Furthermore, when specifying two columns, the two columns must have identical datatypes.
<b>Warning 1000117</b>	<b>"The data to be inserted into table '%2', column '%1' cannot be converted to the datatype of the column. NULL will be inserted if the column allows NULLs."</b>
<b>Constant</b>	EMSG_CANNOT_CONVERT_FOR_INSERT
<b>SAP Sybase Error Number</b>	20777
<b>SQL State</b>	00B17
<b>SQL Code</b>	1000117L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK

<b>Warning 1000117</b>	<b>"The data to be inserted into table '%2', column '%1' cannot be converted to the datatype of the column. NULL will be inserted if the column allows NULLs."</b>
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	The table that is being inserted to.
<b>Parameter 2</b>	The column that is being inserted to.
<b>Probable Cause</b>	The database option CONVERSION_ERROR has been set to 'OFF' for this INSERT. The data to be inserted to the named column cannot be converted to the datatype of that column. If the column allows NULL, then NULL will be inserted instead.
<b>Warning 1000119</b>	<b>"The data to be inserted into table '%2', column `'%1' from row %3 of the select results cannot be converted to the datatype of the destination column. NULL will be inserted if the column allows NULLs."</b>
<b>Constant</b>	EMSG_CANNOT_CONVERT_FOR_INSERT_SELECT
<b>SAP Sybase Error Number</b>	20779
<b>SQL State</b>	00B19
<b>SQL Code</b>	1000119L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	The table being inserted to.
<b>Parameter 2</b>	The column being inserted to.
<b>Parameter 3</b>	The row number in the SELECT results that contains the data that cannot be converted.
<b>Probable Cause</b>	The database option CONVERSION_ERROR has been set to 'OFF' for this INSERT...SELECT. During INSERT...SELECT, the data to be inserted to one of the columns cannot be converted to the datatype of that column. If the column allows NULL, then NULL will be inserted instead.
<b>Error 1000120</b>	<b>"Join %2 was not found in the catalog. %1"</b>
<b>Constant</b>	EMSG_DELETE_NOJOINTABLE

## Errors and Warnings

<b>Error 1000120</b>	"Join %2 was not found in the catalog. %1"
<b>SAP Sybase Error Number</b>	20780
<b>SQL State</b>	QDB20
<b>SQL Code</b>	-1000120L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	join virtual table name
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1000121</b>	"binary data not supported on data longer than 32767 %2, %1"
<b>Constant</b>	EMSG_BINARYINPUTTOOLARGE
<b>SAP Sybase Error Number</b>	20781
<b>SQL State</b>	QDB21
<b>SQL Code</b>	-1000121L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	SA parse source code line
<b>Probable Cause</b>	The user has input a binary string that is too wide
<b>Warning 1000122</b>	"The data to update table '%2', column `%1' cannot be converted to the datatype of the destination column for update number %3 to the table. NULL will be inserted if the column allows NULLs."
<b>Constant</b>	EMSG_CANNOT_CONVERT_FOR_UPDATE

<b>Warning 1000122</b>	"The data to update table '%2', column `%1' cannot be converted to the datatype of the destination column for update number %3 to the table. NULL will be inserted if the column allows NULLs."
<b>SAP Sybase Error Number</b>	20782
<b>SQL State</b>	00B22
<b>SQL Code</b>	1000122L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	The table being updated.
<b>Parameter 2</b>	The column being updated.
<b>Parameter 3</b>	The n'th update to the table.
<b>Probable Cause</b>	The database option CONVERSION_ERROR has been set to 'OFF' for this UPDATE. During UPDATE, the data to update one of the columns cannot be converted to the datatype of the column. The update number represents the number of updates made to the table which is not necessarily the row number of the table being updated. The column will be updated with NULL if the column definition allows NULLs.

<b>Error 1000123</b>	"Index '%2' cannot be created. Multicolumn indexes must be created using distinct columns. %1"
<b>Constant</b>	EMSG_MCINDEX_NEEDS_DISTINCT_COLS
<b>SAP Sybase Error Number</b>	20783
<b>SQL State</b>	QDB23
<b>SQL Code</b>	-1000123L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	The name of the index being created.
<b>Parameter 2</b>	Location of the exception.

## Errors and Warnings

<b>Error 1000123</b>	<b>"Index '%2' cannot be created. Multicolumn indexes must be created using distinct columns. %1"</b>
<b>Probable Cause</b>	Multicolumn indexes must be created using distinct columns. That is, you cannot use the same column more than once when creating a multicolumn index.
<b>Error 1000124</b>	<b>"Function or Operator not supported on data longer than %2 bytes. %1"</b>
<b>Constant</b>	EMSG_BINARYINPUTFIELDTOOLARGE
<b>SAP Sybase Error Number</b>	20784
<b>SQL State</b>	QDB24
<b>SQL Code</b>	-1000124L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	number of bytes
<b>Probable Cause</b>	The user has entered a binary string that is too wide.
<b>Error 1000126</b>	<b>"This database must be upgraded. %1"</b>
<b>Constant</b>	EMSG_VERSION_2OLD
<b>SAP Sybase Error Number</b>	20786
<b>SQL State</b>	QDB26
<b>SQL Code</b>	-1000126L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	This database must be upgraded with the ALTER DATABASE UPGRADE command in order to continue.

<b>Error 1000127</b>	<b>"The LIMIT specified, "%2", is too large. %1"</b>
<b>Constant</b>	EMSG_SQL_LIMIT_INVALIDSIZE
<b>SAP Sybase Error Number</b>	20787
<b>SQL State</b>	QDB27
<b>SQL Code</b>	-1000127L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	The LIMIT that was entered.
<b>Probable Cause</b>	The LIMIT entered is too large. The LIMIT entered on the command line must be between 0 and 4294967295. However, this limitation is only for the LIMIT clause in the sql command. See the ASIQ Reference Manual for the actual, valid LIMIT size.
<b>Warning 1000129</b>	<b>"%1 row(s) deleted from index "%2' in %3 seconds."</b>
<b>Constant</b>	EMSG_DELETE_1INDEX_A
<b>SAP Sybase Error Number</b>	20789
<b>SQL State</b>	QDB29
<b>SQL Code</b>	1000129L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	Number of rows
<b>Parameter 2</b>	index name
<b>Parameter 3</b>	number of seconds to complete the operation
<b>Probable Cause</b>	This is an informational message displayed after a delete.

## Errors and Warnings

<b>Warning 1000130</b>	<b>"%1 row(s) deleted from index '%2' on field '%3', %4 seconds."</b>
<b>Constant</b>	EMSG_DELETE_1INDEX
<b>SAP Sybase Error Number</b>	20790
<b>SQL State</b>	01B30
<b>SQL Code</b>	1000130L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	Number of rows
<b>Parameter 2</b>	index name
<b>Parameter 3</b>	field name
<b>Parameter 4</b>	number of seconds to complete the operation
<b>Probable Cause</b>	This is an informational message displayed after a delete.
<b>Error 1000131</b>	<b>"The DELIMITED BY and LIMIT options are valid for WD indexes only. %1"</b>
<b>Constant</b>	EMSG_OPTION_FOR_WDINDEX_ONLY
<b>SAP Sybase Error Number</b>	20791
<b>SQL State</b>	QDB31
<b>SQL Code</b>	-1000131L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	The DELIMITED BY and LIMIT options may be used only when creating a WD (WORD) index.

<b>Error 1000132</b>	<b>"In table '%2', the START ROW ID value (%3) must be greater than %4. Data has already been inserted at this location. %1"</b>
<b>Constant</b>	EMSG_INSRT_BADSTARTRECID
<b>SAP Sybase Error Number</b>	20792
<b>SQL State</b>	QDB32
<b>SQL Code</b>	-1000132L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	tablename
<b>Parameter 3</b>	requested START ROW ID value
<b>Parameter 4</b>	row id value
<b>Probable Cause</b>	You have entered an incorrect START ROW ID and are trying to insert into a column that already contains data. See the Administration and Performance Guide's chapter Moving Data in and out of Databases. The section on partial width inserts contains information regarding the START ROW ID option.
<b>Error 1000133</b>	<b>"During the LOAD into table '%2', the LOAD statement's column count (%3) must be between 1 and %4. Check the LOAD statement's 'load-specification'. %1"</b>
<b>Constant</b>	EMSG_INSRT_COLUMNCOUNT
<b>SAP Sybase Error Number</b>	20793
<b>SQL State</b>	QDB33
<b>SQL Code</b>	-1000133L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2

<b>Error 1000133</b>	"During the LOAD into table '%2', the LOAD statement's column count (%3) must be between 1 and %4. Check the LOAD statement's 'load-specification'. %1"
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	tablename
<b>Parameter 3</b>	number of columns attempting to insert to
<b>Parameter 4</b>	number of columns in the table.
<b>Probable Cause</b>	The number of columns you are trying to insert to is not consistent with the number of columns specified in the LOAD statement's 'load-specification'. You must specify by name each column you are attempting to insert to via the LOAD statement.

## 1000134 - 1000328

---

### Messages 1000134 through 1000154

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1000134</b>	"Column '%2' is being inserted into twice by this INSERT command. %1"
<b>Constant</b>	EMSG_INSRT_DUPFIELD
<b>SAP Sybase Error Number</b>	20794
<b>SQL State</b>	QDB34
<b>SQL Code</b>	-1000134L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column name
<b>Probable Cause</b>	The specified column was listed twice in the insert command.

<b>Error 1000135</b>	<b>"Cannot open the existence list for table "%2'. %1"</b>
<b>Constant</b>	EMSG_INSRT_EXISTENCEBM
<b>SAP Sybase Error Number</b>	20795
<b>SQL State</b>	QDB35
<b>SQL Code</b>	-1000135L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	tablename
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1000136</b>	<b>"A mismatch exists between the existence bitmaps in the insert object. %1"</b>
<b>Constant</b>	EMSG_INSRT_EXISTENCEMISMATCH
<b>SAP Sybase Error Number</b>	20796
<b>SQL State</b>	QDB36
<b>SQL Code</b>	-1000136L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1000137</b>	<b>"While inserting, table "%2' already had a Complete started. %1"</b>
<b>Constant</b>	EMSG_INSRT_HADDONE
<b>SAP Sybase Error Number</b>	20797

## Errors and Warnings

<b>Error 1000137</b>	<b>"While inserting, table '%2' already had a Complete started. %1"</b>
<b>SQL State</b>	QDB37
<b>SQL Code</b>	-1000137L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	tablename
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1000138</b>	<b>"A data conversion error has occurred while loading record %2. This error should be reported to Sybase. %1"</b>
<b>Constant</b>	EMSG_INSRT_CONVERTDATA
<b>SAP Sybase Error Number</b>	20798
<b>SQL State</b>	QDB38
<b>SQL Code</b>	-1000138L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	The input record number when the error occurred.
<b>Probable Cause</b>	A data conversion error occurred during an insert. The input datatype cannot converted to the datatype of the data's destination field. This error should be reported to Sybase. Diagnostic information has been output to the iqmsg file.

<b>Error 1000139</b>	<b>"You cannot insert into table '%2' past the original end of the table while there are %3 join virtual tables based on it. %1"</b>
<b>Constant</b>	EMSG_INSRT_HASJOINPASTEND
<b>SAP Sybase Error Number</b>	20799
<b>SQL State</b>	QDB39
<b>SQL Code</b>	-1000139L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	tablename
<b>Parameter 3</b>	number of join virtual tables
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1000140</b>	<b>"You cannot change column '%2' because it is a 'link' column. %1"</b>
<b>Constant</b>	EMSG_INSRT_HASLINK
<b>SAP Sybase Error Number</b>	20800
<b>SQL State</b>	QDB40
<b>SQL Code</b>	-1000140L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column name
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.

## Errors and Warnings

<b>Warning 1000142</b>	"Insert into '%1', \n%2 Inners added, %3 Left Outers converted to Inners, %4 Right Outers added."
<b>Constant</b>	EMSG_INSRT_JOINTABLEDONE
<b>SAP Sybase Error Number</b>	20802
<b>SQL State</b>	01B42
<b>SQL Code</b>	1000142L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	Join name
<b>Parameter 2</b>	number of inners added
<b>Parameter 3</b>	number of left outers converted to inners
<b>Parameter 4</b>	number of right outers added
<b>Probable Cause</b>	This is an informational message displayed upon completion of an insert to a join.
<b>Error 1000143</b>	"While inserting, table '%2' must be Complete(d) before it can be (re)Prepare(d). %1"
<b>Constant</b>	EMSG_INSRT_NODONE
<b>SAP Sybase Error Number</b>	20803
<b>SQL State</b>	QDB43
<b>SQL Code</b>	-1000143L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	tablename
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.

<b>Error 1000144</b>	<b>"Cannot insert into table '%2'. Column %3 does not have a name. %1"</b>
<b>Constant</b>	EMSG_INSRT_NOFIELDNAME
<b>SAP Sybase Error Number</b>	20804
<b>SQL State</b>	QDB44
<b>SQL Code</b>	-1000144L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	tablename
<b>Parameter 3</b>	column number
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1000145</b>	<b>"The insert for table '%2' has no insertable columns in the column list. %1"</b>
<b>Constant</b>	EMSG_INSRT_NOINSERTABLEFIELDS
<b>SAP Sybase Error Number</b>	20805
<b>SQL State</b>	QDB45
<b>SQL Code</b>	-1000145L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	table to insert into
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.

## Errors and Warnings

<b>Error 1000146</b>	<b>"Cannot get the index buffer for the column '%2'. %1"</b>
<b>Constant</b>	EMSG_INSRT_NOSINDEX
<b>SAP Sybase Error Number</b>	20806
<b>SQL State</b>	QDB46
<b>SQL Code</b>	-1000146L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column name
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1000147</b>	<b>"Table '%2' must be Prepare(d) before inserting. %1"</b>
<b>Constant</b>	EMSG_INSRT_NOPREPARE
<b>SAP Sybase Error Number</b>	20807
<b>SQL State</b>	QDB47
<b>SQL Code</b>	-1000147L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	tablename
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1000148</b>	<b>"The table being inserted to does not have a name. %1"</b>
<b>Constant</b>	EMSG_INSRT_NOTABLENAME
<b>SAP Sybase Error Number</b>	20808

<b>Error 1000148</b>	<b>"The table being inserted to does not have a name. %1"</b>
<b>SQL State</b>	QDB48
<b>SQL Code</b>	-1000148L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1000149</b>	<b>"Unable to open table "%2" with Read/Write access for insert. %1"</b>
<b>Constant</b>	EMSG_INSRT_NOTABLE
<b>SAP Sybase Error Number</b>	20809
<b>SQL State</b>	QDB49
<b>SQL Code</b>	-1000149L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	tablename
<b>Probable Cause</b>	The table cannot be opened for write access. The insert cannot proceed. Another user has this table open with write access.
<b>Error 1000150</b>	<b>"Cannot insert into the table. Column "%2" has no index. %1"</b>
<b>Constant</b>	EMSG_INSRT_NOTNULLNIDX
<b>SAP Sybase Error Number</b>	20810
<b>SQL State</b>	QDB50
<b>SQL Code</b>	-1000150L

## Errors and Warnings

<b>Error 1000150</b>	<b>"Cannot insert into the table. Column "%2' has no index. %1"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column name
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1000151</b>	<b>"NOT NULL column '%2' was not included in this insert. Data is needed at row %3. %1"</b>
<b>Constant</b>	EMSG_INSRT_NOTNULLFIELDNOTINC
<b>SAP Sybase Error Number</b>	20811
<b>SQL State</b>	QDB51
<b>SQL Code</b>	-1000151L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column name
<b>Parameter 3</b>	row number
<b>Probable Cause</b>	Data must be provided for insertion into columns defined as "NOT NULL".
<b>Error 1000152</b>	<b>"The NOT NULL column '%2' was not included in this insert. %1"</b>
<b>Constant</b>	EMSG_INSRT_NOTNULLNOTINC
<b>SAP Sybase Error Number</b>	20812
<b>SQL State</b>	QDB52
<b>SQL Code</b>	-1000152L

<b>Error 1000152</b>	<b>"The NOT NULL column '%2' was not included in this insert. %1"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column name
<b>Probable Cause</b>	Data must be provided for insertion into columns defined as "NOT NULL".
<b>Error 1000153</b>	<b>"Table '%2', pass-x index count mismatch (%3/%4). %1"</b>
<b>Constant</b>	EMSG_INSRT_PXCOUNT
<b>SAP Sybase Error Number</b>	20813
<b>SQL State</b>	QDB53
<b>SQL Code</b>	-1000153L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	tablename
<b>Parameter 3</b>	number used for comparison
<b>Parameter 4</b>	number used for comparison
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1000154</b>	<b>"While inserting into table '%2', the record number recycled (%3). %1"</b>
<b>Constant</b>	EMSG_INSRT_RECNUMRECYCLED
<b>SAP Sybase Error Number</b>	20814
<b>SQL State</b>	QDB54

<b>Error 1000154</b>	"While inserting into table '%2', the record number recycled (%3). %1"
<b>SQL Code</b>	-1000154L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	tablename
<b>Parameter 3</b>	record number
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.

## Messages 1000155 through 1000174

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1000155</b>	"The attempted insert length (%3) for column %2 is longer than the maximum allowed (%4). %1"
<b>Constant</b>	EMSG_INSRT_TOOLONG
<b>SAP Sybase Error Number</b>	20815
<b>SQL State</b>	QDB55
<b>SQL Code</b>	-1000155L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column name
<b>Parameter 3</b>	requested insert length
<b>Parameter 4</b>	maximum insert length allowed.
<b>Probable Cause</b>	The attempted insert length is too long. The maximum length allowed is 65535.

<b>Error 1000156</b>	<b>"Tried to insert into too many (%2) LOW FAST indexes at one time in table '%3'. %1"</b>
<b>Constant</b>	EMSG_INSRT_TOOMANYINDICES
<b>SAP Sybase Error Number</b>	20816
<b>SQL State</b>	QDB56
<b>SQL Code</b>	-1000156L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	requested number of indexes to insert to
<b>Parameter 3</b>	tablename
<b>Probable Cause</b>	The maximum number allowed is 32727.
<b>Error 1000157</b>	<b>"Columns for the index must be in ascending sort order. %1"</b>
<b>Constant</b>	EMSG_ASCENDING_SORT_ONLY
<b>SAP Sybase Error Number</b>	20817
<b>SQL State</b>	QDB57
<b>SQL Code</b>	-1000157L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	It is required that ASC (ascending) sort order be used for the columns in the indexes.
<b>Error 1000158</b>	<b>"An Identity size mismatch has occurred. The current transaction will rollback. %1"</b>
<b>Constant</b>	EMSG_CAT_IDSIZE_MISMATCH

## Errors and Warnings

<b>Error 1000158</b>	"An Identity size mismatch has occurred. The current transaction will rollback. %1"
<b>SAP Sybase Error Number</b>	20818
<b>SQL State</b>	QDB58
<b>SQL Code</b>	-1000158L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> 4 on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	IQ has encountered an Identity size mismatch. The current command will be rolled back. If this error occurs, the operation that caused it may be tried again. If the error occurs again, the server should be stopped and restarted. If the problem persists, Sybase should be notified of the error.

<b>Warning 1000159</b>	"\nIn table \"%1\", the %2 width insert of %3 columns will begin at record %4."
<b>Constant</b>	EMSG_INSRT_STARTRECID
<b>SAP Sybase Error Number</b>	20819
<b>SQL State</b>	00B59
<b>SQL Code</b>	1000159L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	tablename
<b>Parameter 2</b>	partial/fixed
<b>Parameter 3</b>	number of columns
<b>Parameter 4</b>	row number
<b>Probable Cause</b>	Informational message displayed during insert.

<b>Warning 1000160</b>	"Option %1 has an invalid setting: %2."
<b>Constant</b>	EMSG_INVALID_OPTION_SETTING
<b>SAP Sybase Error Number</b>	20820
<b>SQL State</b>	00B60
<b>SQL Code</b>	1000160L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	Name of the option with the invalid setting.
<b>Parameter 2</b>	The current value of the option.
<b>Probable Cause</b>	The named OPTION is set to an invalid value. See the documentation for the valid values for the option.

<b>Warning 1000161</b>	"You have %1 and %2 available, respectively."
<b>Constant</b>	EMSG_INSRT_MEMNEEDEDWARN
<b>SAP Sybase Error Number</b>	20821
<b>SQL State</b>	01B61
<b>SQL Code</b>	1000161L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	amount of memory
<b>Parameter 2</b>	amount of memory
<b>Probable Cause</b>	Informational message displayed with other messages regarding available memory.

<b>Error 1000162</b>	"Unable to create the requested object. %1"
<b>Constant</b>	EMSG_CAT_CANNOT_CREATE_OBJECT
<b>SAP Sybase Error Number</b>	20822

## Errors and Warnings

<b>Error 1000162</b>	"Unable to create the requested object. %1"
<b>SQL State</b>	QDB62
<b>SQL Code</b>	-1000162L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	IQ is not able to create the object that was requested. This object may be an FP index that is being created during a CREATE TABLE. This error will occur if IQ finds that the index already exists in the table for which it is being created. This can happen if you FORCE DROP a table and then try to recreate the table that was dropped. If this error occurs after a FORCE DROP, the server needs to be rebooted before continuing. If this error occurs for some other reason, Sybase should be notified. Extra diagnostic information will have output to the iqmsg file.

<b>Error 1000163</b>	"%1 not supported."
<b>Constant</b>	EMSG_NOT_SUPPORTED
<b>SAP Sybase Error Number</b>	20823
<b>SQL State</b>	QNA32
<b>SQL Code</b>	-1000163L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	operation name
<b>Probable Cause</b>	The named operation is not supported.

<b>Error 1000164</b>	"Only %1 supported."
<b>Constant</b>	EMSG_RESTRICT_ONLY
<b>SAP Sybase Error Number</b>	20824
<b>SQL State</b>	QNA33

<b>Error 1000164</b>	"Only %1 supported."
<b>SQL Code</b>	-1000164L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	type of RESTRICT supported
<b>Probable Cause</b>	Only UPDATE RESTRICT and DELETE RESTRICT supported
<b>Error 1000165</b>	<b>"Only a single foreign key constraint can be created on the same foreign key column(s) and same candidate key column(s)."</b>
<b>Constant</b>	EMSG_SINGLE_FKEY_CONSTRAINT
<b>SAP Sybase Error Number</b>	20825
<b>SQL State</b>	QNA34
<b>SQL Code</b>	-1000165L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	For a given set of foreign key columns and candidate key columns,
<b>Error 1000166</b>	<b>"Cannot specify IGNORE CONSTRAINT ALL or DATA VALUE when option CONVERSION_ERROR is on. %1"</b>
<b>Constant</b>	EMSG_DATAVALUE_CONVERSION_ON
<b>SAP Sybase Error Number</b>	20826
<b>SQL State</b>	QDB66
<b>SQL Code</b>	-1000166L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of exception

## Errors and Warnings

<b>Error 1000166</b>	<b>"Cannot specify IGNORE CONSTRAINT ALL or DATA VALUE when option CONVERSION_ERROR is on. %1"</b>
<b>Probable Cause</b>	When choosing to ignore DATA TYPE or ALL integrity constraint violations on LOAD command, you must also have option CONVERSION_ERROR set to 'off'.
<b>Error 1000167</b>	<b>"Cannot %3 table %2 because of RI concurrency conflict. %1"</b>
<b>Constant</b>	EMSG_RI_CONCURRENCY_CONFLICT
<b>SAP Sybase Error Number</b>	20827
<b>SQL State</b>	QDB67
<b>SQL Code</b>	-1000167L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of exception
<b>Parameter 2</b>	name of table undergoing the given operation
<b>Parameter 3</b>	operation being performed on specified table
<b>Probable Cause</b>	The named table cannot be modified in the manner specified because of an RI concurrency conflict. Such a conflict arises under the following conditions. delete/truncate/update candidate key at the same time its corresponding foreign key is being loaded/inserted/updated
<b>Error 1000168</b>	<b>"Cannot create %1 HG index because one already exists on the given columns."</b>
<b>Constant</b>	EMSG_CANNOT_CREATE_HG
<b>SAP Sybase Error Number</b>	20828
<b>SQL State</b>	QNA35
<b>SQL Code</b>	-1000168L
<b>ODBC 2 State</b>	ERROR

<b>Error 1000168</b>	<b>"Cannot create %1 HG index because one already exists on the given columns."</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	type of HG index to be created (non-unique vs. unique)
<b>Probable Cause</b>	Only a single HG index of a given type can be created on the same column set. For example, you cannot have two unique HG indexes on the same column set, but you are allowed to have a unique HG and a non-unique HG index on the same set of columns.
<b>Error 1000169</b>	<b>"Cannot create unique HG index because primary key or unique constraint already exists on the given columns."</b>
<b>Constant</b>	EMSG_CANNOT_CREATE_UNIQUE_HG
<b>SAP Sybase Error Number</b>	20829
<b>SQL State</b>	QNA36
<b>SQL Code</b>	-1000169L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	When you create a primary key or unique constraint, IQ automatically creates a unique HG index as the mechanism for enforcing the 'uniqueness' attribute of a primary key or unique constraint. Consequently, a user cannot create another unique HG on the same columns on which the primary key or unique constraint is defined.
<b>Error 1000170</b>	<b>"Cannot create a duplicate '%1' index '%2'."</b>
<b>Constant</b>	EMSG_DUPLICATE_INDEX
<b>SAP Sybase Error Number</b>	20830
<b>SQL State</b>	QNA37
<b>SQL Code</b>	-1000170L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1000170</b>	"Cannot create a duplicate "%1' index "%2'."
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> 4 on page 2
<b>Parameter 1</b>	indextype
<b>Parameter 2</b>	indexname
<b>Probable Cause</b>	Cannot create duplicate indexes of the same type on a set of columns.
<b>Warning 1000171</b>	"Insert Pass IP2.2 started."
<b>Constant</b>	EMSG_INSRT_SORTPASS22_STARTED
<b>SAP Sybase Error Number</b>	20831
<b>SQL State</b>	00B71
<b>SQL Code</b>	1000171L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Probable Cause</b>	Informational message.
<b>Warning 1000172</b>	"Insert Pass %1 (%2 of %3) started."
<b>Constant</b>	EMSG_INSRT_SORTPASS234_STARTED
<b>SAP Sybase Error Number</b>	20832
<b>SQL State</b>	00B72
<b>SQL Code</b>	1000172L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	pass number
<b>Parameter 2</b>	pass number
<b>Parameter 3</b>	number
<b>Probable Cause</b>	This is an informational message.

<b>Error 1000173</b>	"Index '%1' cannot be created. Multicolumn indexes must be created using distinct columns."
<b>Constant</b>	EMSG_NEED_DISTINCT_COLUMNS
<b>SAP Sybase Error Number</b>	20833
<b>SQL State</b>	QNA38
<b>SQL Code</b>	-1000173L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	The name of the index being created.
<b>Probable Cause</b>	Multicolumn indexes must be created using distinct columns. That is, you cannot use the same column more than once when creating a multicolumn index.

<b>Warning 1000174</b>	"\n\t%1 records were inserted into '%2'.\n"
<b>Constant</b>	EMSG_INSRT_COMPLETE
<b>SAP Sybase Error Number</b>	20834
<b>SQL State</b>	01B74
<b>SQL Code</b>	1000174L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I0</i> on page 2
<b>Parameter 1</b>	number of insertions
<b>Parameter 2</b>	tablename
<b>Probable Cause</b>	Informational message displayed after insert.

**Messages 1000175 through 1000197**

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Warning 1000175</b>	<b>"%1 records were inserted into %2 join virtual tables (%3 sections)\n for \"%4".\n"</b>
<b>Constant</b>	EMSG_INSRT_COMPLETEJOINS
<b>SAP Sybase Error Number</b>	20835
<b>SQL State</b>	01B75
<b>SQL Code</b>	1000175L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	number of records
<b>Parameter 2</b>	number of join virtual tables
<b>Parameter 3</b>	number of join sorts
<b>Parameter 4</b>	join virtual table name
<b>Probable Cause</b>	This is an informational message displayed at the end of insert.
<b>Error 1000176</b>	<b>"Cannot perform foreign key create/alter operation because one is already in progress. %1"</b>
<b>Constant</b>	EMSG_FK_INPROGRESS
<b>SAP Sybase Error Number</b>	20836
<b>SQL State</b>	QDB76
<b>SQL Code</b>	-1000176L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of exception

<b>Error 1000176</b>	<b>"Cannot perform foreign key create/alter operation because one is already in progress. %1"</b>
<b>Probable Cause</b>	Concurrent foreign key create/alter operations are not supported. This error means that there is such an operation already in progress. Consequently, this new operation will be denied.
<b>Warning 1000177</b>	<b>"Only the catalog entry for the "%1" index was created, no data was available to populate the index."</b>
<b>Constant</b>	EMSG_APICREATEINDEXNODATA
<b>SAP Sybase Error Number</b>	20837
<b>SQL State</b>	QDB77
<b>SQL Code</b>	1000177L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	The index name
<b>Probable Cause</b>	This is an internal error. The new index was to be populated from another, existing index but a source index could not be found. If this error occurs, it should be reported to Sybase.
<b>Error 1000178</b>	<b>"The DATA parameter must have a non-NULL value. %1"</b>
<b>Constant</b>	EMSG_APIDATAMUSTHAVEVALUE
<b>SAP Sybase Error Number</b>	20838
<b>SQL State</b>	QDB78
<b>SQL Code</b>	-1000178L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.

## Errors and Warnings

<b>Error 1000179</b>	"The column length (%2) must be [if variable sized, between 0 and] %3. %1"
<b>Constant</b>	EMSG_APISETACTUALFIELDLENGTH
<b>SAP Sybase Error Number</b>	20839
<b>SQL State</b>	QDB79
<b>SQL Code</b>	-1000179L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column length
<b>Parameter 3</b>	column length
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1000180</b>	"The maximum column length (%2) must be between 0 and %3. %1"
<b>Constant</b>	EMSG_APISETMAXFIELDLENGTH
<b>SAP Sybase Error Number</b>	20840
<b>SQL State</b>	QDB80
<b>SQL Code</b>	-1000180L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column length
<b>Parameter 3</b>	column length
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.

<b>Error 1000181</b>	<b>"The maximum column length (%2) is less than the actual length (%3). %1"</b>
<b>Constant</b>	EMSG_APIMAXACTUALFLEN
<b>SAP Sybase Error Number</b>	20841
<b>SQL State</b>	QDB81
<b>SQL Code</b>	-1000181L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column length
<b>Parameter 3</b>	column length
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1000182</b>	<b>"Table %2 cannot be opened because it is currently involved in a foreign key create/alter operation. %1"</b>
<b>Constant</b>	EMSG_CANNOT_OPEN_FK_INPROGRESS
<b>SAP Sybase Error Number</b>	20842
<b>SQL State</b>	QDB82
<b>SQL Code</b>	-1000182L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of exception
<b>Parameter 2</b>	The name of the table being opened.
<b>Probable Cause</b>	The named table cannot be opened for read or write access because it is currently undergoing a create/alter foreign operation.

## Errors and Warnings

<b>Error 1000183</b>	<b>"Attempt to insert data into column '%2' with a non-insertable datatype (%3) ignored. %1"</b>
<b>Constant</b>	EMSG_APIINSERTDATATYPEIGNORED
<b>SAP Sybase Error Number</b>	20843
<b>SQL State</b>	QDB83
<b>SQL Code</b>	-1000183L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for %2
<b>Parameter 3</b>	explanation for %3
<b>Probable Cause</b>	This is an internal error. The datatype IQ is inserting to is unknown. If this error occurs, it should be reported to Sybase.
<b>Error 1000185</b>	<b>"Cannot drop table %1 because foreign keys still reference it."</b>
<b>Constant</b>	EMSG_FKEY_STILL_EXISTS_TO_TABLE
<b>SAP Sybase Error Number</b>	20845
<b>SQL State</b>	QNA39
<b>SQL Code</b>	-1000185L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	name of the table
<b>Probable Cause</b>	The named table cannot be dropped until all foreign keys referencing it have first been dropped.
<b>Error 1000186</b>	<b>"Cannot create foreign key constraint on a candidate key that is also a foreign key."</b>
<b>Constant</b>	EMSG_CKEY_IS_ALSO_FKEY

<b>Error 1000186</b>	<b>"Cannot create foreign key constraint on a candidate key that is also a foreign key."</b>
<b>SAP Sybase Error Number</b>	20846
<b>SQL State</b>	QNA40
<b>SQL Code</b>	-1000186L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	A candidate key cannot also be a foreign key. Here's an example illustrating what is meant by this exception. (1) A [pk] <---- B [fk] [pk] <-- ADD THIS ONE -- C[fk] (2) A [pk] <-- ADD THIS ONE -- B[fk] [pk] <----- C[fk] In case (1), adding foreign key C[fk] is disallowed. In case (2), adding foreign key B[fk] is disallowed.

<b>Error 1000187</b>	<b>"Unable to implicitly convert column '%2' to datatype (%3) from datatype (%4). %1"</b>
<b>Constant</b>	EMSG_SQL_IMPLICITCONVERSION
<b>SAP Sybase Error Number</b>	20847
<b>SQL State</b>	QCB87
<b>SQL Code</b>	-1000187L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column converting
<b>Parameter 3</b>	datatype being converted to
<b>Parameter 4</b>	datatype being converted from

## Errors and Warnings

<b>Error 1000187</b>	<b>"Unable to implicitly convert column '%2' to datatype (%3) from datatype (%4). %1"</b>
<b>Probable Cause</b>	The attempted implicit conversion is not possible. The conversion must be done explicitly. If implicit conversion is being attempted to or from a NUMERIC and this error results, the datatype displayed in the error for the NUMERIC will be SMALLINT, INT, or INT64 depending on the precision of the NUMERIC. This is because NUMERICs are treated internally as multiple precision signed integers.
<b>Error 1000188</b>	<b>"Only ASCII, BCP and BINARY are supported LOAD formats. %1"</b>
<b>Constant</b>	EMSG_LOAD_FORMAT_NOT_SUPPORTED
<b>SAP Sybase Error Number</b>	20848
<b>SQL State</b>	QDB88
<b>SQL Code</b>	-1000188L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	The user specified a LOAD format that is not supported.
<b>Error 1000189</b>	<b>"DDL statements cannot proceed while the %2 is in an out of space condition. %1"</b>
<b>Constant</b>	EMSG_CAT_NODDL_WHILE_OUTOFSpace
<b>SAP Sybase Error Number</b>	20849
<b>SQL State</b>	QDB89
<b>SQL Code</b>	-1000189L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	The store that is out of space.

<b>Error 1000189</b>	<b>"DDL statements cannot proceed while the %2 is in an out of space condition. %1"</b>
<b>Parameter 2</b>	Location of the exception.
<b>Probable Cause</b>	The DDL statement cannot proceed until the named db store is no longer in an out of space condition. The out of space condition had been previously reported. The only course of action available is to stop and restart the server. The database is in an out-of-space condition. Space needs to be added to the database.
<b>Error 1000190</b>	<b>"The index '%2' cannot be opened in the current transaction (%3). %1"</b>
<b>Constant</b>	EMSG_CANNOTFINDINDEX
<b>SAP Sybase Error Number</b>	20850
<b>SQL State</b>	QDB90
<b>SQL Code</b>	-1000190L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	Name of the index.
<b>Parameter 3</b>	The current transaction.
<b>Probable Cause</b>	The procedure cannot open the named index. It is likely that the index was created by a transaction that began after the one that is trying to open it. In order to proceed, COMMIT the current transaction and try again.
<b>Error 1000192</b>	<b>"The cursor for table '%2' has no data to fetch. %1"</b>
<b>Constant</b>	EMSG_JOIN_CURSORNOFETCH
<b>SAP Sybase Error Number</b>	20852
<b>SQL State</b>	QDB92
<b>SQL Code</b>	-1000192L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1000192</b>	<b>"The cursor for table '%2' has no data to fetch. %1"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	tablename
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1000193</b>	<b>"The table '%2' is either not part of the join virtual table or has had its data loaded through linked indices. %1"</b>
<b>Constant</b>	EMSG_JOIN_CURSORNOTUSED
<b>SAP Sybase Error Number</b>	20853
<b>SQL State</b>	QDB93
<b>SQL Code</b>	-1000193L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	tablename
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1000194</b>	<b>"You must supply either a cursor count (%2) and a cursor array, or neither. %1"</b>
<b>Constant</b>	EMSG_JOIN_CURSORS
<b>SAP Sybase Error Number</b>	20854
<b>SQL State</b>	QDB94
<b>SQL Code</b>	-1000194L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1000194</b>	<b>"You must supply either a cursor count (%2) and a cursor array, or neither. %1"</b>
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	cursor count
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1000195</b>	<b>"Load specification '%2' only valid for column(s) having datatype '%3'. %1"</b>
<b>Constant</b>	EMSG_BINARYFILE
<b>SAP Sybase Error Number</b>	20855
<b>SQL State</b>	QDB95
<b>SQL Code</b>	-1000195L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	type of load specification
<b>Parameter 3</b>	datatype of column
<b>Probable Cause</b>	The named load specification is only valid for columns that have the given datatype.
<b>Error 1000197</b>	<b>"Table '%2' has no columns in the cursor that don't already have data, \nor the join field(s) are not part of the cursor. %1"</b>
<b>Constant</b>	EMSG_JOIN_NOCOLUMNSTOINSERTINTO
<b>SAP Sybase Error Number</b>	20857
<b>SQL State</b>	QDB97
<b>SQL Code</b>	-1000197L
<b>ODBC 2 State</b>	ERROR

<b>Error 1000197</b>	"Table '%2' has no columns in the cursor that don't already have data, \nor the join field(s) are not part of the cursor. %1"
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	tablename
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.

## Messages 1000199 through 1000218

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Warning 1000199</b>	"Table '%1' has no data."
<b>Constant</b>	EMSG_JOIN_NODATAINBASESRC
<b>SAP Sybase Error Number</b>	20859
<b>SQL State</b>	01B99
<b>SQL Code</b>	1000199L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	the name of the table that has no data %1
<b>Probable Cause</b>	This is a warning that there is no data in a base table.

<b>Error 1000200</b>	"Table '%2' has no data with which to join the other tables. %1"
<b>Constant</b>	EMSG_JOIN_NODATAINSRC
<b>SAP Sybase Error Number</b>	20860
<b>SQL State</b>	QDC00
<b>SQL Code</b>	-1000200L

<b>Error 1000200</b>	"Table '%2' has no data with which to join the other tables. %1"
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	tablename
<b>Probable Cause</b>	There is no data in a table which participates in a join.
<b>Error 1000201</b>	<b>"JOIN cannot be created or updated because the thread's stack space has been exceeded. %1"</b>
<b>Constant</b>	EMSG_CAT_NEAR_END_OF_STACK
<b>SAP Sybase Error Number</b>	20861
<b>SQL State</b>	QDC01
<b>SQL Code</b>	-1000201L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Creation or update of this JOIN has exceeded the thread's stack space. Create or update the JOIN after restarting the engine with a larger value for the -iqtss startup parameter. See the ASIQ Reference Manual for information on setting iqtss.
<b>Error 1000202</b>	<b>"In join virtual table '%2', there is no table cursor at index %3. %1"</b>
<b>Constant</b>	EMSG_JOIN_NOTABLECURSOR
<b>SAP Sybase Error Number</b>	20862
<b>SQL State</b>	QDC02
<b>SQL Code</b>	-1000202L

## Errors and Warnings

<b>Error 1000202</b>	<b>"In join virtual table '%2', there is no table cursor at index %3. %1"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	jvt name
<b>Parameter 3</b>	index
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1000203</b>	<b>"In join virtual table '%2', there is no tablename at index %3. %1"</b>
<b>Constant</b>	EMSG_JOIN_NOTABLENAME
<b>SAP Sybase Error Number</b>	20863
<b>SQL State</b>	QDC03
<b>SQL Code</b>	-1000203L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	join virtual table name
<b>Parameter 3</b>	index
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1000204</b>	<b>"Within the join, the portion for table '%2' already has data. %1"</b>
<b>Constant</b>	EMSG_JOIN_TABLEHASDATA
<b>SAP Sybase Error Number</b>	20864
<b>SQL State</b>	QDC04

<b>Error 1000204</b>	"Within the join, the portion for table '%2' already has data. %1"
<b>SQL Code</b>	-1000204L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	tablename
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1000205</b>	"Within the join, the cursor for table '%2' yielded no data. %1"
<b>Constant</b>	EMSG_JOIN_TABLEHASNODATA
<b>SAP Sybase Error Number</b>	20865
<b>SQL State</b>	QDC05
<b>SQL Code</b>	-1000205L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	tablename
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1000206</b>	"Within the join, there remain no rows to insert into table '%2' \n after processing the INNER and OUTER rows. %1"
<b>Constant</b>	EMSG_JOIN_TABLEHASNOROWS
<b>SAP Sybase Error Number</b>	20866
<b>SQL State</b>	QDC06
<b>SQL Code</b>	-1000206L

## Errors and Warnings

<b>Error 1000206</b>	"Within the join, there remain no rows to insert into table "%2' \n after processing the INNER and OUTER rows. %1"
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	tablename
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1000207</b>	"Within the join, the portion for table "%2' has no data. \n INSERT INTO or LOAD this table first. %1"
<b>Constant</b>	EMSG_JOIN_TABLENEEDSDATA
<b>SAP Sybase Error Number</b>	20867
<b>SQL State</b>	QDC07
<b>SQL Code</b>	-1000207L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	tablename
<b>Probable Cause</b>	The named table must be populated with data.
<b>Error 1000208</b>	"Within the non-appending partial width insert into the join virtual table "%2', \n there must be at least one other column besides the join field(s). %1"
<b>Constant</b>	EMSG_JOIN_VINSETNEEDSDATACOL
<b>SAP Sybase Error Number</b>	20868
<b>SQL State</b>	QDC08
<b>SQL Code</b>	-1000208L
<b>ODBC 2 State</b>	ERROR

<b>Error 1000208</b>	"Within the non-appending partial width insert into the join virtual table '%2', \nthere must be at least one other column besides the join field(s). %1"
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	join virtual table name
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1000209</b>	"Within the partial width insert into the join virtual table '%2', \nrow %3 is no longer an inner join. %1"
<b>Constant</b>	EMSG_JOIN_VINSERTNOTINNER
<b>SAP Sybase Error Number</b>	20869
<b>SQL State</b>	QDC09
<b>SQL Code</b>	-1000209L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	join virtual table name
<b>Parameter 3</b>	row number
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1000210</b>	"For the partial width insert into the join virtual table '%2', \nrow %3 is no longer a left outer. %1"
<b>Constant</b>	EMSG_JOIN_VINSERTNOTLOUTER
<b>SAP Sybase Error Number</b>	20870
<b>SQL State</b>	QDC10
<b>SQL Code</b>	-1000210L

## Errors and Warnings

<b>Error 1000210</b>	<b>"For the partial width insert into the join virtual table '%2', \nrow %3 is no longer a left outer. %1"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	join virtual table name
<b>Parameter 3</b>	row
<b>Probable Cause</b>	This is an internal error. If this error occurs, then it should be reported to Sybase.
<b>Error 1000211</b>	<b>"For the partial width insert into the join virtual table '%2', \nrow %3 is no longer a right outer. %1"</b>
<b>Constant</b>	EMSG_JOIN_VINSERTNOTROUTER
<b>SAP Sybase Error Number</b>	20871
<b>SQL State</b>	QDC11
<b>SQL Code</b>	-1000211L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	join virtual table name
<b>Parameter 3</b>	row
<b>Probable Cause</b>	This is an internal error. If this error occurs, then it should be reported to Sybase.
<b>Error 1000212</b>	<b>"For the partial width insert into join virtual table '%2', \nrow %3 is now a duplicate row (but was not before or vice-versa). %1"</b>
<b>Constant</b>	EMSG_JOIN_VINSERTNOTT1TRUE
<b>SAP Sybase Error Number</b>	20872

<b>Error 1000212</b>	"For the partial width insert into join virtual table "%2', \nrow %3 is now a duplicate row (but was not before or vice-versa). %1"
<b>SQL State</b>	QDC12
<b>SQL Code</b>	-1000212L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	join virtual table name
<b>Parameter 3</b>	row
<b>Probable Cause</b>	This is an internal error. If this error occurs, then it should be reported to Sybase.
<b>Warning 1000213</b>	<b>No message</b>
<b>Constant</b>	EMSG_JOIN_WARNNOCURSORS_EMPTY_SLOT
<b>SAP Sybase Error Number</b>	20873
<b>SQL State</b>	01C13
<b>SQL Code</b>	1000213L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1000214</b>	<b>"Duplicate records seen in table %2. The SYNCHRONIZE operation will rollback. %1"</b>
<b>Constant</b>	EMSG_JOIN_DUPLICATE_ROWS
<b>SAP Sybase Error Number</b>	20874
<b>SQL State</b>	QDC14
<b>SQL Code</b>	-1000214L

## Errors and Warnings

<b>Error 1000214</b>	"Duplicate records seen in table %2. The SYNCHRONIZE operation will rollback. %1"
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	table containing duplicate records
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.

<b>Error 1000215</b>	"An invalid filler option (e.g., filler()) was specified in the load statement. %1"
<b>Constant</b>	EMSG_INVALID_FILLER_OPTION
<b>SAP Sybase Error Number</b>	20875
<b>SQL State</b>	QDC15
<b>SQL Code</b>	-1000215L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	An invalid filler option was specified on the load statement.

<b>Warning 1000216</b>	<b>No message</b>
<b>Constant</b>	EMSG_JOIN_EJP1ADD_EMPTY_SLOT
<b>SAP Sybase Error Number</b>	20876
<b>SQL State</b>	01C16
<b>SQL Code</b>	1000216L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2

<b>Warning 1000216</b>	<b>No message</b>
<b>Probable Cause</b>	No additional information available.
<b>Warning 1000217</b>	<b>No message</b>
<b>Constant</b>	EMSG_JOIN_EJP1STARTRECID_EMPTY_SLOT
<b>SAP Sybase Error Number</b>	20877
<b>SQL State</b>	01C17
<b>SQL Code</b>	1000217L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Warning 1000218</b>	<b>"Join virtual table fetches (JP1%1) complete for '%2'."</b>
<b>Constant</b>	EMSG_JOIN_EJP12DONE
<b>SAP Sybase Error Number</b>	20878
<b>SQL State</b>	01C18
<b>SQL Code</b>	1000218L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	Parameter 1 description
<b>Parameter 2</b>	Parameter 2 description
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.

**Messages 1000219 through 1000235**

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1000219</b>	"The specified indextype does not exist in the given target.%1"
<b>Constant</b>	EMSG_DBCC_INDEXTYPE_NOT_FOUND
<b>SAP Sybase Error Number</b>	20879
<b>SQL State</b>	QDC19
<b>SQL Code</b>	-1000219L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	The indextype the user requested to check with sp_iqcheckdb does not exist in the given table or database.
<b>Warning 1000220</b>	" Left Rows: %1, Right Rows: %2, Ratio: %3 to %4\n"
<b>Constant</b>	EMSG_JOIN_EJP12CNTS
<b>SAP Sybase Error Number</b>	20880
<b>SQL State</b>	01C20
<b>SQL Code</b>	1000220L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I0</i> on page 2
<b>Parameter 1</b>	Parameter 1 description
<b>Parameter 2</b>	Parameter 2 description
<b>Parameter 3</b>	Parameter 3 description
<b>Parameter 4</b>	Parameter 4 description

<b>Warning 1000220</b>	" <b>Left Rows: %1, Right Rows: %2, Ratio: %3 to %4</b> \n"
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.
<b>Warning 1000221</b>	" <b>Right Rows Skipped: %1 (former leftouters)</b> . \n"
<b>Constant</b>	EMSG_JOIN_EJP12SKIPS
<b>SAP Sybase Error Number</b>	20881
<b>SQL State</b>	01C21
<b>SQL Code</b>	1000221L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	Parameter 1 description
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.
<b>Error 1000222</b>	" <b>JP3&amp;4</b> "
<b>Constant</b>	EMSG_JOIN_ESORT34
<b>SAP Sybase Error Number</b>	20882
<b>SQL State</b>	QDC22
<b>SQL Code</b>	-1000222L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.
<b>Error 1000223</b>	<b>"Column name '%2' is invalid. The column name must follow the format [OWNER.]TABLE.COLUMN. %1"</b>
<b>Constant</b>	EMSG_INVALID_COLUMN_NAME
<b>SAP Sybase Error Number</b>	20883

## Errors and Warnings

<b>Error 1000223</b>	"Column name '%2' is invalid. The column name must follow the format [OWNER.]TABLE.COLUMN. %1"
<b>SQL State</b>	QDC23
<b>SQL Code</b>	-1000223L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	The name of the column typed by the user.
<b>Probable Cause</b>	The column name must follow the format [OWNER.]TABLE.COL-UMN.
<b>Warning 1000224</b>	<b>"Join record rejected: '%1', duplicate rows in 1st indexset. \nRow# %2 &amp; %3X, row %4 rejected."</b>
<b>Constant</b>	EMSG_CLBK_JOINIDXRECORDREJECTEDDX
<b>SAP Sybase Error Number</b>	20884
<b>SQL State</b>	01C24
<b>SQL Code</b>	1000224L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I0</i> on page 2
<b>Parameter 1</b>	Parameter 1 description
<b>Parameter 2</b>	Parameter 2 description
<b>Parameter 3</b>	Parameter 3 description
<b>Parameter 4</b>	Parameter 4 description
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.
<b>Error 1000225</b>	<b>"Cannot open table %2. The table has already been opened by a cursor declared FOR UPDATE in transaction %3. %1"</b>
<b>Constant</b>	EMSG_CAT_CANNOT_OPEN_TABLE

<b>Error 1000225</b>	<b>"Cannot open table %2. The table has already been opened by a cursor declared FOR UPDATE in transaction %3. %1"</b>
<b>SAP Sybase Error Number</b>	20885
<b>SQL State</b>	QDC25
<b>SQL Code</b>	-1000225L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	Tablename.
<b>Parameter 3</b>	The id of the transaction during which the cursor was opened.
<b>Probable Cause</b>	A table opened by a CURSOR that has been declared FOR UPDATE cannot be opened again by another operation.
<b>Warning 1000226</b>	<b>"\n Inner Rows: %1, Left Outer Rows: %2, Right Outer Rows: %3"</b>
<b>Constant</b>	EMSG_JOIN_EJP3CNT1
<b>SAP Sybase Error Number</b>	20886
<b>SQL State</b>	01C26
<b>SQL Code</b>	1000226L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	Parameter 1 description
<b>Parameter 2</b>	Parameter 2 description
<b>Parameter 3</b>	Parameter 3 description
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.

## Errors and Warnings

<b>Error 1000226</b>	"The LOCATION string passed to the attached database insert is invalid. %1"
<b>Constant</b>	EMSG_INVALIDLOCATION
<b>SAP Sybase Error Number</b>	20996
<b>SQL State</b>	QDC36
<b>SQL Code</b>	-1000226L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	The user passed an invalid LOCATION string in an attached database insert. Check the format of the string. It must be of the form "servername.dbname".
<b>Warning 1000227</b>	" Join Rows: %1, Left m2m Rows: %2, Right m2m Rows: %3\n"
<b>Constant</b>	EMSG_JOIN_EJP3CNT2
<b>SAP Sybase Error Number</b>	20887
<b>SQL State</b>	01C27
<b>SQL Code</b>	1000227L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I0</i> on page 2
<b>Parameter 1</b>	Parameter 1 description
<b>Parameter 2</b>	Parameter 2 description
<b>Parameter 3</b>	Parameter 3 description
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.

<b>Error 1000227</b>	" <b>Cannot load data with both BINARY and delimited columns. %1</b> "
<b>Constant</b>	EMSG_LOADBINARYDELIMITED
<b>SAP Sybase Error Number</b>	20997
<b>SQL State</b>	QDC37
<b>SQL Code</b>	-1000227L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	You cannot load data with both BINARY and delimited columns in the same LOAD command.
<b>Error 1000228</b>	" <b>JP4&amp;5</b> "
<b>Constant</b>	EMSG_JOIN_ESORT45
<b>SAP Sybase Error Number</b>	20888
<b>SQL State</b>	QDC28
<b>SQL Code</b>	-1000228L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.
<b>Warning 1000229</b>	" <b>%1 records were inserted and %2 records were rejected for %3 tables \nfor join index "%4".\n</b> "
<b>Constant</b>	EMSG_JOIN_COMPLETE
<b>SAP Sybase Error Number</b>	20889
<b>SQL State</b>	01C29
<b>SQL Code</b>	1000229L

## Errors and Warnings

<b>Warning 1000229</b>	<b>"%1 records were inserted and %2 records were rejected for %3 tables \nfor join index "%4'.\n"</b>
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	Parameter 1 description
<b>Parameter 2</b>	Parameter 2 description
<b>Parameter 3</b>	Parameter 3 description
<b>Parameter 4</b>	Parameter 4 description
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.
<b>Error 1000229</b>	<b>"Only BINARY [WITH NULL BYTE] can be used as a column specification when using UNLOAD FORMAT. %1"</b>
<b>Constant</b>	EMSG_CANTUSEINLOAD
<b>SAP Sybase Error Number</b>	20998
<b>SQL State</b>	QDC38
<b>SQL Code</b>	-1000229L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	When using UNLOAD FORMAT, you cannot specify any column specification other than BINARY. If need to load null values for a column using the BINARY column spec, you must specify the WITH NULL BYTE option. You cannot use the [ROW] DELIMITED BY options with UNLOAD FORMAT.
<b>Warning 1000230</b>	<b>"\nInsert for "%1",\n completed in %2 seconds."</b>
<b>Constant</b>	EMSG_DELETE_INSERTDONE
<b>SAP Sybase Error Number</b>	20890

<b>Warning 1000230</b>	"\nInsert for \"%1\",\n completed in %2 seconds."
<b>SQL State</b>	01C30
<b>SQL Code</b>	1000230L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	Parameter 1 description
<b>Parameter 2</b>	Parameter 2 description
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.
<b>Error 1000230</b>	<b>"Columns that allow nulls must use the WITH NULL BYTE option. %1"</b>
<b>Constant</b>	EMSG_MUSTUSENULLBYTE
<b>SAP Sybase Error Number</b>	20999
<b>SQL State</b>	QDC39
<b>SQL Code</b>	-1000230L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	The user must use the WITH NULL BYTE option for a BINARY column spec for columns that allow nulls.
<b>Error 1000232</b>	<b>"Partial input record skipped at EOF. %1"</b>
<b>Constant</b>	EMSG_PARTIAL_INPUT_ROW
<b>SAP Sybase Error Number</b>	20892
<b>SQL State</b>	QDC32
<b>SQL Code</b>	-1000232L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1000232</b>	"Partial input record skipped at EOF. %1"
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	A partial input record was detected during a 'load' operation. This can occur as a result of an OS/hardware error or simply because the input data file was missing values for one or more columns in the table.
<b>Warning 1000234</b>	"\nInsert into table '%1', %2 rows rejected (in all)."
<b>Constant</b>	EMSG_CLBK_INSERTREJECTTOTAL
<b>SAP Sybase Error Number</b>	20894
<b>SQL State</b>	01C34
<b>SQL Code</b>	1000234L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I0</i> on page 2
<b>Parameter 1</b>	table name
<b>Parameter 2</b>	number of rows rejected.
<b>Probable Cause</b>	This is an informational message displayed in context with other messages. During the LOAD, some records were rejected.
<b>Error 1000234</b>	"The record size of the unloaded data: %2, does not match the record size of the load: %3. %1"
<b>Constant</b>	EMSG_RECSIZEWRONG
<b>SAP Sybase Error Number</b>	21000
<b>SQL State</b>	QDC40
<b>SQL Code</b>	-1000234L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2

<b>Error 1000234</b>	"The record size of the unloaded data: %2, does not match the record size of the load: %3. %1"
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	record size in the tape being read
<b>Parameter 3</b>	record size of the load command.
<b>Probable Cause</b>	The record size of the unloaded data does not match the size of the record described by the LOAD command.
<b>Warning 1000235</b>	"%3 Pass %1 completed in %2 seconds."
<b>Constant</b>	EMSG_CLBK_INSERTPASSDONE
<b>SAP Sybase Error Number</b>	20895
<b>SQL State</b>	00C35
<b>SQL Code</b>	1000235L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	Parameter 1 description
<b>Parameter 2</b>	Parameter 2 description
<b>Parameter 3</b>	Parameter 3 description
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.

## Messages 1000235 through 1000245

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1000235</b>	"The total number of columns of unloaded data: %2, does not match the total number of columns in the load: %3. %1"
<b>Constant</b>	EMSG_NUMCOLSWRON
<b>SAP Sybase Error Number</b>	21001
<b>SQL State</b>	QDC42

## Errors and Warnings

<b>Error 1000235</b>	"The total number of columns of unloaded data: %2, does not match the total number of columns in the load: %3. %1"
<b>SQL Code</b>	-1000235L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	number of columns in the tape being read
<b>Parameter 3</b>	number of columns in the load command.
<b>Probable Cause</b>	The total number of columns in the unloaded data does not match the number of columns in the LOAD command.
<b>Warning 1000236</b>	"%4 for '%1' completed in %2 seconds. %3 rows %5."
<b>Constant</b>	EMSG_CLBK_INSERTDONE
<b>SAP Sybase Error Number</b>	20896
<b>SQL State</b>	01C36
<b>SQL Code</b>	1000236L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I0</i> on page 2
<b>Parameter 1</b>	table name
<b>Parameter 2</b>	number of seconds
<b>Parameter 3</b>	number of rows inserted
<b>Parameter 4</b>	operation performed
<b>Parameter 5</b>	operation performed
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.

<b>Error 1000236</b>	"The total number of null columns in the unloaded data, %2, does not match the total number of null columns in the LOAD command, %3. %1"
<b>Constant</b>	EMSG_NUMNULLCOLSWRONG
<b>SAP Sybase Error Number</b>	21002
<b>SQL State</b>	QDC43
<b>SQL Code</b>	-1000236L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> 4 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	number of null columns in the tape being read
<b>Parameter 3</b>	number of null columns in the load command.
<b>Probable Cause</b>	The total number of null columns in the unloaded data does not match the number of null columns in the LOAD command.
<b>Warning 1000237</b>	"\t%1 Rows, %2 Seconds"
<b>Constant</b>	EMSG_CLBK_INSERTNRECS
<b>SAP Sybase Error Number</b>	20897
<b>SQL State</b>	00C37
<b>SQL Code</b>	1000237L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	Parameter 1 description
<b>Parameter 2</b>	Parameter 2 description
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.

## Errors and Warnings

<b>Error 1000237</b>	"The total number of variable width columns in the unloaded data, %2, does not match the total number of variable width columns in the LOAD command, %3. %1"
<b>Constant</b>	EMSG_NUMVARCOLSWRONG
<b>SAP Sybase Error Number</b>	21003
<b>SQL State</b>	QDC44
<b>SQL Code</b>	-1000237L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	number of variable width columns in the tape being read
<b>Parameter 3</b>	number of variable width columns in the load command.
<b>Probable Cause</b>	The total number of variable width columns in the unloaded data does not match the number of variable width columns in the LOAD command.
<b>Warning 1000238</b>	"\t%1 Rows, %2 Seconds, "%3"
<b>Constant</b>	EMSG_CLBK_INSERTNRECSINDEX
<b>SAP Sybase Error Number</b>	20898
<b>SQL State</b>	01C38
<b>SQL Code</b>	1000238L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I0</i> on page 2
<b>Parameter 1</b>	Parameter 1 description
<b>Parameter 2</b>	Parameter 2 description
<b>Parameter 3</b>	Parameter 3 description
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.

<b>Error 1000238</b>	"The platform type of the unloaded data, %2, does not match the platform type on the load, %3. %1"
<b>Constant</b>	EMSG_PLATIDWRONG
<b>SAP Sybase Error Number</b>	21009
<b>SQL State</b>	QDC45
<b>SQL Code</b>	-1000238L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Platform ID in the tape being read
<b>Parameter 3</b>	Platform ID the load command command is executing in.
<b>Probable Cause</b>	The Platform ID of unloaded data does not match the Platform ID of load. The LOAD command detected that the platform on which the UNLOAD was performed, is not the same platform on which the LOAD is being attempted. Cross platform UNLOAD-LOAD cannot be done.
<b>Warning 1000239</b>	"Inserting into table '%1',\ncolumn '%2'.\nInput record %3 was rejected."
<b>Constant</b>	EMSG_CLBK_INSERTRECORDREJECTED
<b>SAP Sybase Error Number</b>	20899
<b>SQL State</b>	01C39
<b>SQL Code</b>	1000239L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	The name of the table being inserted to.
<b>Parameter 2</b>	The column being inserted to.
<b>Parameter 3</b>	The data Being inserted to the column.

## Errors and Warnings

<b>Warning 1000239</b>	<b>"Inserting into table '%1',\ncolumn '%2'.\nInput record %3 was rejected."</b>
<b>Probable Cause</b>	Some data cannot be inserted. Examine the data and column definition to determine why.
<b>Error 1000239</b>	<b>"UNLOAD version number: %2, does not match the LOAD version number: %3. %1"</b>
<b>Constant</b>	EMSG_VERSIONWRONG
<b>SAP Sybase Error Number</b>	21010
<b>SQL State</b>	QDC46
<b>SQL Code</b>	-1000239L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	version number of data in the tape being read
<b>Parameter 3</b>	version number of the load command.
<b>Probable Cause</b>	The UNLOAD version number does not match the LOAD version number. The version number of the data on the tape being read does not match the version number of the LOAD command. The version numbers must match before the data on the tape can be loaded.
<b>Warning 1000240</b>	<b>"Inserting into table '%1',\nColumn '%2'.\nOn input record %3, the value was rejected."</b>
<b>Constant</b>	EMSG_CLBK_INSERTVALUEREJECTED
<b>SAP Sybase Error Number</b>	20900
<b>SQL State</b>	01C40
<b>SQL Code</b>	1000240L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2

<b>Warning 1000240</b>	<b>"Inserting into table '%1',\nColumn '%2'.\nOn input record %3, the value was rejected."</b>
<b>Parameter 1</b>	The name of the table being inserted to.
<b>Parameter 2</b>	The column being inserted to.
<b>Parameter 3</b>	This is the nth record being inserted.
<b>Probable Cause</b>	Some data was rejected on insert. Examine the input data and column definition to determine why.
<b>Error 1000240</b>	<b>"The total number of blocks of unloaded data: %2, does not match the total number of blocks loaded: %3. %1"</b>
<b>Constant</b>	EMSG_BLOCKCOUNTWRONG
<b>SAP Sybase Error Number</b>	21011
<b>SQL State</b>	QDC47
<b>SQL Code</b>	-1000240L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	number of blocks on the tape being read
<b>Parameter 3</b>	number of blocks in the load command.
<b>Probable Cause</b>	Total number of blocks of unloaded data on the tape does not match the number of blocks of data that were just loaded.
<b>Warning 1000241</b>	<b>"The insert to the table will be single threaded."</b>
<b>Constant</b>	EMSG_CLBK_INSERT_SINGLE_THREADED
<b>SAP Sybase Error Number</b>	20901
<b>SQL State</b>	QDC41
<b>SQL Code</b>	1000241L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK

## Errors and Warnings

<b>Warning 1000241</b>	<b>"The insert to the table will be single threaded."</b>
<b>Severity Code</b>	<i>10</i> on page 2
<b>Probable Cause</b>	There are not enough threads available to do a multithreaded insert or load. The number of users doing parallel processing has limited the number of threads available for your insert/load. The insert/load will proceed, but will be done serially.
<b>Warning 1000242</b>	<b>"Insert completed. Index '%1',\n in %2 seconds."</b>
<b>Constant</b>	EMSG_CLBK_INSERTINDEXDONE
<b>SAP Sybase Error Number</b>	20902
<b>SQL State</b>	01C42
<b>SQL Code</b>	1000242L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	index name
<b>Parameter 2</b>	number of seconds
<b>Probable Cause</b>	This is an informational message that is displayed after an insert to an index.
<b>Error 1000242</b>	<b>"Total number of rows of unloaded data: %2, does not match the total number of rows in the load: %3. %1"</b>
<b>Constant</b>	EMSG_ROWCOUNTWRONG
<b>SAP Sybase Error Number</b>	21012
<b>SQL State</b>	QDC48
<b>SQL Code</b>	-1000242L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	number of rows on the tape being read

<b>Error 1000242</b>	<b>"Total number of rows of unloaded data: %2, does not match the total number of rows in the load: %3. %1"</b>
<b>Parameter 3</b>	number of rows in the load command.
<b>Probable Cause</b>	The total number of rows of unloaded data on the tape does not match the numbers of rows of data just loaded.
<b>Warning 1000243</b>	<b>"\nInsert into join virtual table '%1' started.\n\n%2 tables will be modified (in all)."</b>
<b>Constant</b>	EMSG_CLBK_INSERTJOINSTART
<b>SAP Sybase Error Number</b>	20903
<b>SQL State</b>	01C43
<b>SQL Code</b>	1000243L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	join virtual table name
<b>Parameter 2</b>	number of tables
<b>Probable Cause</b>	This is an informational message.
<b>Error 1000243</b>	<b>"The unload format number: %2, does not match the load format number: %3. %1"</b>
<b>Constant</b>	EMSG_FORMATWRONG
<b>SAP Sybase Error Number</b>	21013
<b>SQL State</b>	QDC49
<b>SQL Code</b>	-1000243L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	format number of data in the tape being read.

## Errors and Warnings

<b>Error 1000243</b>	"The unload format number: %2, does not match the load format number: %3. %1"
<b>Parameter 3</b>	format number of the load command.
<b>Probable Cause</b>	The unload format number does not match the load format number. The data on the tape being read contains a format number. This number does not match the format number of the LOAD command. In order to load the data, the numbers must match.
<b>Warning 1000244</b>	"\nInsert into join virtual table '%1' completed\n in %2 seconds.\n\n%3 tables modified (in all).\n"
<b>Constant</b>	EMSG_CLBK_INSERTJOINDONE
<b>SAP Sybase Error Number</b>	20904
<b>SQL State</b>	01C44
<b>SQL Code</b>	1000244L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	join virtual table name
<b>Parameter 2</b>	number of seconds
<b>Parameter 3</b>	number of tables
<b>Probable Cause</b>	This is an informational message.
<b>Error 1000244</b>	"The BLOCK FACTOR of unloaded data: %2 does not match the BLOCK FACTOR of the LOAD: %3. %1"
<b>Constant</b>	EMSG_BLOCKFACTORWRONG
<b>SAP Sybase Error Number</b>	21014
<b>SQL State</b>	QDC50
<b>SQL Code</b>	-1000244L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2

<b>Error 1000244</b>	<b>"The BLOCK FACTOR of unloaded data: %2 does not match the BLOCK FACTOR of the LOAD: %3. %1"</b>
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Block Factor of data in the tape being read.
<b>Parameter 3</b>	Block Factor specified in the load command.
<b>Probable Cause</b>	The BLOCK FACTOR used in the LOAD command must be the same as the BLOCK FACTOR that was used in the LOAD command to unload the data.
<b>Warning 1000245</b>	<b>"Insert into join virtual table "%1' started.\n%2 rows will be inserted (in all)."</b>
<b>Constant</b>	EMSG_CLBK_INSERTJOINTABLESTART
<b>SAP Sybase Error Number</b>	20905
<b>SQL State</b>	01C45
<b>SQL Code</b>	1000245L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	join virtual table name
<b>Parameter 2</b>	number of rows to be inserted
<b>Probable Cause</b>	This is an informational message.
<b>Error 1000245</b>	<b>"Tape / File already loaded. Block number %2 repeats. %1"</b>
<b>Constant</b>	EMSG_FILEALREADYLOADED
<b>SAP Sybase Error Number</b>	21015
<b>SQL State</b>	QDC51
<b>SQL Code</b>	-1000245L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2

<b>Error 1000245</b>	"Tape / File already loaded. Block number %2 repeats. %1"
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	block number that was already loaded.
<b>Probable Cause</b>	LOAD has encountered a block that has already been loaded. This tape (or file) has already been loaded.

## Messages 1000246 through 1000264

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Warning 1000246</b>	"%1 Rows, %2 Seconds"
<b>Constant</b>	EMSG_CLBK_INSERTJOINNRECS
<b>SAP Sybase Error Number</b>	20906
<b>SQL State</b>	01C46
<b>SQL Code</b>	1000246L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	rows
<b>Parameter 2</b>	seconds
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.

<b>Error 1000246</b>	"The number of rows loaded: %3, does not match the number of rows unloaded: %2. %1"
<b>Constant</b>	EMSG_ROWCOUNTMISMATCH
<b>SAP Sybase Error Number</b>	21016
<b>SQL State</b>	QDC52
<b>SQL Code</b>	-1000246L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1000246</b>	"The number of rows loaded: %3, does not match the number of rows unloaded: %2. %1"
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Number of rows of data in all tapes that were read.
<b>Parameter 3</b>	Number of rows of data actually loaded by the load command.
<b>Probable Cause</b>	The number of rows of data on all of the tapes that were loaded does not match the number of rows of data that were unloaded by the LOAD command.
<b>Warning 1000247</b>	"Insert into join virtual table "%1' completed in %2 seconds.\n%3 rows inserted (in all)."
<b>Constant</b>	EMSG_CLBK_INSERTJOINTABLEDONE
<b>SAP Sybase Error Number</b>	20907
<b>SQL State</b>	01C47
<b>SQL Code</b>	1000247L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	join virtual table name
<b>Parameter 2</b>	number of seconds
<b>Parameter 3</b>	number of rows inserted
<b>Probable Cause</b>	This is an informational message.
<b>Error 1000247</b>	"The number of blocks loaded: %3, does not match the number of blocks unloaded: %2. %1"
<b>Constant</b>	EMSG_BLOCKCOUNTMISMATCH
<b>SAP Sybase Error Number</b>	21017
<b>SQL State</b>	QDC54
<b>SQL Code</b>	-1000247L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1000247</b>	"The number of blocks loaded: %3, does not match the number of blocks unloaded: %2. %1"
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Number of blocks of data in all tapes that were read.
<b>Parameter 3</b>	Number of blocks of data actually loaded by the load command.
<b>Probable Cause</b>	The number of blocks of data on all of the tapes that were loaded does not match the number of blocks of data that were unloaded by the LOAD command.

<b>Warning 1000248</b>	"\nJoin virtual table passes started for "%1'. \n"
<b>Constant</b>	EMSG_CLBK_JOINIDXPASSESSTART
<b>SAP Sybase Error Number</b>	20908
<b>SQL State</b>	01C48
<b>SQL Code</b>	1000248L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	index name
<b>Probable Cause</b>	This is an informational message.

<b>Warning 1000249</b>	"\nJoin Virtual Table Pass 1 started for "%1'. \n"
<b>Constant</b>	EMSG_CLBK_JOINIDXPASS1START
<b>SAP Sybase Error Number</b>	20909
<b>SQL State</b>	01C49
<b>SQL Code</b>	1000249L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2

<b>Warning 1000249</b>	"\nJoin Virtual Table Pass 1 started for "%1".\n"
<b>Parameter 1</b>	index name
<b>Probable Cause</b>	This is an informational message.
<b>Warning 1000250</b>	"\nJoin virtual table Pass %1 completed for '%2', %3 seconds.\n\n%4 rows processed.\n"
<b>Constant</b>	EMSG_CLBK_JOINIDXPASSCOMPLETE
<b>SAP Sybase Error Number</b>	20910
<b>SQL State</b>	01C50
<b>SQL Code</b>	1000250L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	pass
<b>Parameter 2</b>	index
<b>Parameter 3</b>	seconds
<b>Parameter 4</b>	rows
<b>Probable Cause</b>	This is an informational message.
<b>Warning 1000251</b>	"\nJoin virtual table passes 1 and 2 complete for "%1' in %2 seconds.\n%3 rows processed.\n"
<b>Constant</b>	EMSG_CLBK_JOINIDXPASS1AND2COMPLETE
<b>SAP Sybase Error Number</b>	20911
<b>SQL State</b>	01C51
<b>SQL Code</b>	1000251L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	index name

## Errors and Warnings

<b>Warning 1000251</b>	"\nJoin virtual table passes 1 and 2 complete for '%1' in %2 seconds.\n%3 rows processed.\n"
<b>Parameter 2</b>	number of seconds
<b>Parameter 3</b>	number of rows processed
<b>Probable Cause</b>	This is an informational message.
<b>Error 1000253</b>	<b>"Cannot drop the constraint "%1"."</b>
<b>Constant</b>	EMSG_ALTER_DROP_CONSTRAINT
<b>SAP Sybase Error Number</b>	20913
<b>SQL State</b>	QDC53
<b>SQL Code</b>	-1000253L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Constraint name.
<b>Probable Cause</b>	IQ is unable to drop the named constraint because the index associated with the constraint could not be found or opened.
<b>Warning 1000254</b>	<b>"\t%1 Rows, JP%2, %3 Seconds"</b>
<b>Constant</b>	EMSG_CLBK_JOINIDXNRECS
<b>SAP Sybase Error Number</b>	20914
<b>SQL State</b>	01C54
<b>SQL Code</b>	1000254L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I0</i> on page 2
<b>Parameter 1</b>	rows
<b>Parameter 2</b>	explanation of %2
<b>Parameter 3</b>	seconds

<b>Warning 1000254</b>	"\t%1 Rows, JP%2, %3 Seconds"
<b>Probable Cause</b>	This is an informational message displayed in the context of other messages.
<b>Warning 1000255</b>	<b>"Join Record Rejected: '%1', duplicate rows in 1st table. \nRow# %2 &amp; %3, row %4 rejected."</b>
<b>Constant</b>	EMSG_CLBK_JOINIDXRECORDREJECTED
<b>SAP Sybase Error Number</b>	20915
<b>SQL State</b>	01C55
<b>SQL Code</b>	1000255L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	rejected record
<b>Parameter 2</b>	duplicate row number
<b>Parameter 3</b>	duplicate row number
<b>Parameter 4</b>	rejected row
<b>Probable Cause</b>	This is an informational message describing duplicate rows encountered.
<b>Warning 1000256</b>	<b>"Join virtual table '%1'. \nTotal rows rejected: %2"</b>
<b>Constant</b>	EMSG_CLBK_JOINIDXREJECTEDTOTAL
<b>SAP Sybase Error Number</b>	20916
<b>SQL State</b>	01C56
<b>SQL Code</b>	1000256L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	Join virtual table name
<b>Parameter 2</b>	number of records rejected

## Errors and Warnings

<b>Warning 1000256</b>	<b>"Join virtual table "%1". \nTotal rows rejected: %2"</b>
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.
<b>Warning 1000257</b>	<b>"Delete of %1 rows started for table: "</b>
<b>Constant</b>	EMSG_CLBK_DELETESTART
<b>SAP Sybase Error Number</b>	20917
<b>SQL State</b>	00C57
<b>SQL Code</b>	1000257L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	number of rows
<b>Probable Cause</b>	This is an informational message foretelling the number of rows to be deleted from a table.
<b>Warning 1000258</b>	<b>"Portions of the insert/load will be single threaded."</b>
<b>Constant</b>	EMSG_CLBK_INSERT_SINGLE_THREADED1
<b>SAP Sybase Error Number</b>	20918
<b>SQL State</b>	QDC58
<b>SQL Code</b>	1000258L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Probable Cause</b>	The load will proceed, but portions of it will be done serially. This can be caused by constraining the amount of memory available to the load with the LOAD_MEMORY_MB option; executing a variable length load without row delimiters; or executing a partial width, variable length load.

<b>Warning 1000259</b>	"\nDelete of %1 rows completed for table: %2, %3 seconds."
<b>Constant</b>	EMSG_CLBK_DELETEDONE
<b>SAP Sybase Error Number</b>	20919
<b>SQL State</b>	01C59
<b>SQL Code</b>	1000259L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	number of rows deleted
<b>Parameter 2</b>	table name
<b>Parameter 3</b>	number of seconds to do the delete
<b>Probable Cause</b>	This is an informational message displayed at the end of a delete.
<b>Error 1000260</b>	"ALTER DBSPACE <dbspace-name> ADD <number> is not supported. %1"
<b>Constant</b>	EMSG_ALTER_ADD_NOTSUPPORTED
<b>SAP Sybase Error Number</b>	20920
<b>SQL State</b>	QDC60
<b>SQL Code</b>	-1000260L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	For a Sybase IQ database, one can add space to a database only using the CREATE DBSPACE command. The size of existing dbspaces cannot be changed.
<b>Error 1000261</b>	"A Sybase IQ system dbspace, '%2', cannot be renamed. %1"
<b>Constant</b>	EMSG_ALTER_CANT_RENAME_DBSPACE

## Errors and Warnings

<b>Error 1000261</b>	<b>"A Sybase IQ system dbspace, "%2', cannot be renamed. %1"</b>
<b>SAP Sybase Error Number</b>	20921
<b>SQL State</b>	QDC61
<b>SQL Code</b>	-1000261L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	dbspace name
<b>Probable Cause</b>	You cannot rename a dbspace in a Sybase IQ database.
<b>Error 1000262</b>	<b>"You cannot specify BLANK PADDING OFF for CREATE DATABASE. %1"</b>
<b>Constant</b>	EMSG_BLANKPADDINGOFF
<b>SAP Sybase Error Number</b>	20922
<b>SQL State</b>	QDC62
<b>SQL Code</b>	-1000262L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	The BLANK PADDING OFF clause is not valid while creating a Sybase IQ database.
<b>Error 1000263</b>	<b>"Undo failure for row %2. Statement will rollback to statement before the first insert..values. %1"</b>
<b>Constant</b>	EMSG_UNDO_UNDO_FAILED
<b>SAP Sybase Error Number</b>	20973
<b>SQL State</b>	QDC63

<b>Error 1000263</b>	<b>"Undo failure for row %2. Statement will rollback to statement before the first insert..values. %1"</b>
<b>SQL Code</b>	-1000263L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	14 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	row for which the 'undo' operation failed
<b>Probable Cause</b>	There was a unrecoverable error encountered while attempting to undo an 'insert' operation for the specified row. Consequently, the statement now rolls back to the first insert..values statement that occurred since the most recent commit, rollback, or non-insert..values command.
<b>Error 1000264</b>	<b>"Ambiguous index name '%2'. Please specify owner. %1"</b>
<b>Constant</b>	EMSG_INDEXAMBIGUOUS
<b>SAP Sybase Error Number</b>	21077
<b>SQL State</b>	QDB04
<b>SQL Code</b>	-1000264L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Name of ambiguous index
<b>Probable Cause</b>	The specified index name is shared by more than one owner. The owner can be specified as OWNER.TABLE.INDEX

## **Messages 1000265 through 1000284**

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1000265</b>	<b>"Index '%2' not found. %1"</b>
<b>Constant</b>	EMSG_INDEX_NOTFOUND

## Errors and Warnings

<b>Error 1000265</b>	<b>"Index '%2' not found. %1"</b>
<b>SAP Sybase Error Number</b>	21078
<b>SQL State</b>	QDB05
<b>SQL Code</b>	-1000265L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Name of user specified index
<b>Probable Cause</b>	The specified index could not be opened. Either the index does not exist or the name format is incorrect. The index name must follow the format [OWNER.]TABLE.INDEX
<b>Error 1000266</b>	<b>"Table '%2' not found. %1"</b>
<b>Constant</b>	EMSG_TABLE_NOTFOUND
<b>SAP Sybase Error Number</b>	21079
<b>SQL State</b>	QDB09
<b>SQL Code</b>	-1000266L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Name of user specified table
<b>Probable Cause</b>	The specified table could not be opened. Either the table does not exist or the name format is incorrect. The table name must follow the format [OWNER.]TABLE
<b>Error 1000267</b>	<b>"Cannot convert '%2' to an integer percent. %1"</b>
<b>Constant</b>	EMSG_RESOURCE_CONVERROR
<b>SAP Sybase Error Number</b>	21080

<b>Error 1000267</b>	<b>"Cannot convert '%2' to an integer percent. %1"</b>
<b>SQL State</b>	QDB07
<b>SQL Code</b>	-1000267L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Percent specified for RESOURCES
<b>Probable Cause</b>	The percent must be an integer value
<b>Error 1000268</b>	<b>"The target '%2' overlaps an earlier target. %1"</b>
<b>Constant</b>	EMSG_TARGETS_OVERLAP
<b>SAP Sybase Error Number</b>	21081
<b>SQL State</b>	QDB08
<b>SQL Code</b>	-1000268L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Name of table or index
<b>Probable Cause</b>	The user cannot specify an index or table multiple times. This also applies to an index that was already included by specifying its table.
<b>Error 1000269</b>	<b>"DBCC: Multiple modes specified with a write mode. %1"</b>
<b>Constant</b>	EMSG_DBCC_MULTI_WRITE_MODES
<b>SAP Sybase Error Number</b>	21082
<b>SQL State</b>	QDB59
<b>SQL Code</b>	-1000269L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1000269</b>	<b>"DBCC: Multiple modes specified with a write mode. %1"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	The user can only specify one mode if a mode that updates the database is present. Update modes are dbcc command REPAIR, server switch -iqdrplks, database options Convert_HG_To_1242 and Convert_Varchar_To_1242
<b>Error 1000270</b>	<b>"DBCC: FP Recreate failed for index "%2". %1"</b>
<b>Constant</b>	EMSG_DBCC_FP_RECREATE_FAILED
<b>SAP Sybase Error Number</b>	21083
<b>SQL State</b>	QDB60
<b>SQL Code</b>	-1000270L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Name of index
<b>Probable Cause</b>	If an FP re-create fails, the command must rollback
<b>Error 1000271</b>	<b>"Table '%2' is a temporary table, a view, or not an IQ table. %1"</b>
<b>Constant</b>	EMSG_NOT_IQ_TABLE
<b>SAP Sybase Error Number</b>	21084
<b>SQL State</b>	QDB61
<b>SQL Code</b>	-1000271L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2

<b>Error 1000271</b>	"Table '%2' is a temporary table, a view, or not an IQ table. %1"
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Name of user specified table
<b>Probable Cause</b>	The specified table was opened, but it was a non-IQ or temporary table or a view. Only non-temporary IQ tables can be processed.

<b>Error 1000272</b>	"Invalid table name "%2'. %1"
<b>Constant</b>	EMSG_INVALID_TABLE_NAME
<b>SAP Sybase Error Number</b>	21085
<b>SQL State</b>	QDB63
<b>SQL Code</b>	-1000272L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Name of user specified table
<b>Probable Cause</b>	The table name must follow the format [OWNER.]TABLE

<b>Error 1000273</b>	"Invalid index name "%2'. %1"
<b>Constant</b>	EMSG_INVALID_INDEX_NAME
<b>SAP Sybase Error Number</b>	21086
<b>SQL State</b>	QDB64
<b>SQL Code</b>	-1000273L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Name of user specified index

## Errors and Warnings

<b>Error 1000273</b>	<b>"Invalid index name '%2'. %1"</b>
<b>Probable Cause</b>	The index name must follow the format [OWNER.]TABLE.INDEX
<b>Error 1000274</b>	<b>"DBCC: Upgrade options can be used only with CHECK or REPAIR mode. %1"</b>
<b>Constant</b>	EMSG_DBCC_UPGRADE_OPTIONS
<b>SAP Sybase Error Number</b>	21087
<b>SQL State</b>	QDB65
<b>SQL Code</b>	-1000274L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	Upgrade options (such as Convert_HG_To_1242) can be used only with CHECK or REPAIR. They cannot be used with ALLOCATION.
<b>Error 1000275</b>	<b>"Cannot process object '%2' at the current transaction level. %1"</b>
<b>Constant</b>	EMSG_FUTUREVERSION
<b>SAP Sybase Error Number</b>	21088
<b>SQL State</b>	QDB68
<b>SQL Code</b>	-1000275L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	Name of the object that cannot be processed.
<b>Probable Cause</b>	The requested object cannot be opened because it was created by a future transaction. A COMMIT or ROLLBACK must be issued before the object can be opened

<b>Error 1000276</b>	<b>"At least one mode and target must be specified. %1"</b>
<b>Constant</b>	EMSG_NOTHING_TO_DO
<b>SAP Sybase Error Number</b>	21094
<b>SQL State</b>	QDB69
<b>SQL Code</b>	-1000276L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	DBCC has no default target or mode. The user must explicitly specify both a mode and target.
<b>Error 1000277</b>	<b>"\"dropleaks {database dbspace dbspace-name}\\" is the only command allowed in drop leaks mode. %1"</b>
<b>Constant</b>	EMSG_DBCC_DROPLEAKS_COMMAND
<b>SAP Sybase Error Number</b>	21095
<b>SQL State</b>	QDB70
<b>SQL Code</b>	-1000277L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	Modes are restricted to avoid long DBCC sessions during forced recovery
<b>Error 1000278</b>	<b>"\"resetclks\\" must be run in single-node mode with \"allocation database\\". %1"</b>
<b>Constant</b>	EMSG_DBCC_RESETCLKS_COMMAND
<b>SAP Sybase Error Number</b>	21096
<b>SQL State</b>	QDB71

## Errors and Warnings

<b>Error 1000278</b>	<b>"\"resetclks\" must be run in single-node mode with \"allocation database\". %1"</b>
<b>SQL Code</b>	-1000278L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	resetclks is restricted to allocation mode and single-node mode, and requires checking entire DB
<b>Error 1000279</b>	<b>"Column '%2' must be included in the insert. It is part of a multicolumn index. %1"</b>
<b>Constant</b>	EMSG_INSRT_MISSING_COLUMN_ON_INSERT
<b>SAP Sybase Error Number</b>	21108
<b>SQL State</b>	QDB99
<b>SQL Code</b>	-1000279L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	14 on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	The name of the column missing in the insert.
<b>Probable Cause</b>	All columns of a multicolumn index must be included in an insert.
<b>Error 1000280</b>	<b>"Secondary server version information has not changed"</b>
<b>Constant</b>	EMSG_IQ_QUERY_NOTCHANGED
<b>SAP Sybase Error Number</b>	21109
<b>SQL State</b>	QDC64
<b>SQL Code</b>	-1000280L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1000280</b>	<b>"Secondary server version information has not changed"</b>
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	ev_iqmpxstatus has run the query event but there is nothing for it to do.
<b>Error 1000281</b>	<b>"Column %2 has unsupported data type for index rebuild. %1"</b>
<b>Constant</b>	EMSG_FPSTYLE_UNSUPPORTED
<b>SAP Sybase Error Number</b>	21110
<b>SQL State</b>	QDC56
<b>SQL Code</b>	-1000281L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Index name
<b>Probable Cause</b>	You have tried to rebuild an FP index of unsupported index style.
<b>Error 1000282</b>	<b>"DBCC must be restricted to the MAIN or LOCAL store only. %1"</b>
<b>Constant</b>	EMSG_DBCC_ONEMPXSTORE
<b>SAP Sybase Error Number</b>	21116
<b>SQL State</b>	QDB72
<b>SQL Code</b>	-1000282L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	DBCC is restricted to either the main or the local store only. It may not combine checking of tables in both main and local in the same dbcc run.

## Errors and Warnings

<b>Error 1000283</b>	"Identity/Autoincrement Column value range exceeded for column %2. %1"
<b>Constant</b>	EMSG_IDENTITY_EXCEEDS_RANGE
<b>SAP Sybase Error Number</b>	20030
<b>SQL State</b>	QDC65
<b>SQL Code</b>	-1000283L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column name
<b>Probable Cause</b>	Data overflow: An Identity/Autoincrement Column has reached its maximum value. To correct this create a new table in which the datatype of the new Identity/Autoincrement Column is larger and copy this table into the new table. Alternatively add a new Identity/Autoincrement Column to the table with a larger datatype and delete the old one.
<b>Error 1000284</b>	"Identity/Autoincrement Column value for column %2 must be positive. %1"
<b>Constant</b>	EMSG_IDENTITY_VALUE_MUST_BE_POSITIVE
<b>SAP Sybase Error Number</b>	20032
<b>SQL State</b>	QDC66
<b>SQL Code</b>	-1000284L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column name

<b>Error 1000284</b>	<b>"Identity/Autoincrement Column value for column %2 must be positive. %1"</b>
<b>Probable Cause</b>	All values in Identity/Autoincrement Columns must be positive. To correct this, only use positive values when manually inserting into Identity/Autoincrement Columns.

## Messages 1000285 through 1000306

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1000285</b>	<b>"The value specified for the Identity/Autoincrement Column %2 exceeds the range of its datatype. %1"</b>
<b>Constant</b>	EMSG_VALUE_TOO_LARGE
<b>SAP Sybase Error Number</b>	20034
<b>SQL State</b>	QDC67
<b>SQL Code</b>	-1000285L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column name
<b>Probable Cause</b>	The value specified does not fit in the Identity/Autoincrement Column. To correct this, choose a smaller value

<b>Error 1000286</b>	<b>"Invalid table argument %2 to sp_iq_reset_identity, Table has no Identity/Autoincrement Column. %1"</b>
<b>Constant</b>	EMSG_TABLE_HAS_NO_IDENTITY
<b>SAP Sybase Error Number</b>	20035
<b>SQL State</b>	QDC68
<b>SQL Code</b>	-1000286L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 1000286</b>	<b>"Invalid table argument %2 to sp_iq_reset_identity, Table has no Identity/Autoincrement Column. %1"</b>
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	name of table
<b>Probable Cause</b>	Table's without Identity/Autoincrement Columns cannot be used in calls to stored procedure sp_iq_reset_identity.
<b>Error 1000287</b>	<b>"Invalid table argument %2 to sp_iq_reset_identity, Table cannot be a JVT. %1"</b>
<b>Constant</b>	EMSG_NO_JVT_RESET_IDENTITY
<b>SAP Sybase Error Number</b>	20036
<b>SQL State</b>	QDC69
<b>SQL Code</b>	-1000287L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	table name
<b>Probable Cause</b>	Tables of type JVT are not allowed as arguments to the stored procedure sp_iq_reset_identity
<b>Error 1000288</b>	<b>"Invalid table argument %2 for set option 'identity_insert', Table cannot be a JVT. %1"</b>
<b>Constant</b>	EMSG_TABLE_CANNOT_BE_JVT
<b>SAP Sybase Error Number</b>	20037
<b>SQL State</b>	QDC70
<b>SQL Code</b>	-1000288L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2

<b>Error 1000288</b>	<b>"Invalid table argument %2 for set option 'identity_insert', Table cannot be a JVT. %1"</b>
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	table name
<b>Probable Cause</b>	Tables of type JVT are not allowed as a value for the set option 'identity_insert'
<b>Error 1000289</b>	<b>"Invalid table argument %2 for set option 'identity_insert', Table must be an IQ table. %1"</b>
<b>Constant</b>	EMSG_TABLE_MUST_BE_IQ_IDENTITY_INSERT
<b>SAP Sybase Error Number</b>	20038
<b>SQL State</b>	QDC71
<b>SQL Code</b>	-1000289L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	table name
<b>Probable Cause</b>	Only IQ tables are allowed as an argument value to the set option 'identity_insert'
<b>Error 1000290</b>	<b>"Invalid table argument %2 for stored procedure sp_iq_reset_identity, Table must be an IQ Table. %1"</b>
<b>Constant</b>	EMSG_TABLE_MUST_BE_IQ_RESET_IDENTITY
<b>SAP Sybase Error Number</b>	20039
<b>SQL State</b>	QDC72
<b>SQL Code</b>	-1000290L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception

## Errors and Warnings

<b>Error 1000290</b>	<b>"Invalid table argument %2 for stored procedure sp_iq_reset_identity, Table must be an IQ Table. %1"</b>
<b>Parameter 2</b>	table name
<b>Probable Cause</b>	Only IQ tables are allowed as a table argument to the stored procedure sp_iq_reset_identity
<b>Error 1000291</b>	<b>"You do not have insert permission on table %2. %1"</b>
<b>Constant</b>	EMSG_NO_PERM_IDENTITY_INSERT
<b>SAP Sybase Error Number</b>	20041
<b>SQL State</b>	QDC73
<b>SQL Code</b>	-1000291L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	table name
<b>Probable Cause</b>	You cannot set the option 'identity_insert' to a table for which you do not have insert permission
<b>Error 1000292</b>	<b>"Invalid use of set option 'identity insert'. Table %2 does not have an Identity/Autoincrement Column. %1"</b>
<b>Constant</b>	EMSG_PARAM_TABLE_HAS_NO_IDENTITY
<b>SAP Sybase Error Number</b>	20474
<b>SQL State</b>	QDC74
<b>SQL Code</b>	-1000292L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of exception
<b>Parameter 2</b>	table name

<b>Error 1000292</b>	<b>"Invalid use of set option 'identity insert'. Table %2 does not have an Identity/Autoincrement Column. %1"</b>
<b>Probable Cause</b>	the set option 'identity insert' cannot be used on a table without an Identity/Autoincrement Column.
<b>Error 1000293</b>	<b>"Cannot insert or update Column %2: set option 'identity_insert' to the specific table name containing the identity column to be modified. %1"</b>
<b>Constant</b>	EMSG_IDENTITY_INSERT_IS_OFF
<b>SAP Sybase Error Number</b>	20644
<b>SQL State</b>	QDC75
<b>SQL Code</b>	-1000293L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of exception
<b>Parameter 2</b>	column name
<b>Probable Cause</b>	set option 'identity_insert' must be set to the specific table for which you want to insert or update an Identity column. To turn it on use set identity_insert <table_name>
<b>Error 1000294</b>	<b>"Cannot set 'identity_insert', it is already on for a different table. %1"</b>
<b>Constant</b>	EMSG_IDENTITY_INSERT_ON_FOR_OTHER
<b>SAP Sybase Error Number</b>	20645
<b>SQL State</b>	QDC76
<b>SQL Code</b>	-1000294L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of exception

## Errors and Warnings

<b>Error 1000294</b>	<b>"Cannot set 'identity_insert', it is already on for a different table. %1"</b>
<b>Probable Cause</b>	the set option 'identity_insert' can only be set for one table at a time. To set it for a different table, first turn it off using 'set identity_insert '' then set it to the desired table.
<b>Error 1000295</b>	<b>"Invalid table name %2 specified for option 'identity_insert'. %1"</b>
<b>Constant</b>	EMSG_INVALID_TAB_NAME
<b>SAP Sybase Error Number</b>	20646
<b>SQL State</b>	QDC77
<b>SQL Code</b>	-1000295L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of exception
<b>Parameter 2</b>	table name
<b>Probable Cause</b>	The table associated with the table name specified for the 'identity_insert' option could not be found.
<b>Error 1000296</b>	<b>" Invalid load specification for LOAD ... FORMAT BCP. %1"</b>
<b>Constant</b>	EMSG_INVALIDLOADSPECFORBCPLOAD
<b>SAP Sybase Error Number</b>	21124
<b>SQL State</b>	QDC78
<b>SQL Code</b>	-1000296L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of exception
<b>Probable Cause</b>	The user specified a load specification that is not supported with FORMAT BCP option.

<b>Warning 1000297</b>	"%1. Message logging stopped."
<b>Constant</b>	EMSG_SQL_IQMSG_MANAGEMENT_ERROR
<b>SAP Sybase Error Number</b>	21149
<b>SQL State</b>	QCB17
<b>SQL Code</b>	1000297L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	Reason behind stopping of message logging. Can be either due to disk error, or due to message log management error.
<b>Probable Cause</b>	Message log management operation failed due to error in file renaming / deletion / creation. Or log could not be written in the IQMSG file because some DISK IO error occurred.

<b>Warning 1000298</b>	" Message logging resumed."
<b>Constant</b>	EMSG_MESSAGE_LOGGING_RESUMED
<b>SAP Sybase Error Number</b>	21150
<b>SQL State</b>	QCB18
<b>SQL Code</b>	1000298L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Probable Cause</b>	Engine has detected that reason behind message log management / message logging failure has been resolved. Message logging is resumed now.

<b>Error 1000299</b>	" Partition key of %2 is unsupported. %1"
<b>Constant</b>	EMSG_CAT_UNSUPPORTED_PARTITION_KEY
<b>SAP Sybase Error Number</b>	21152
<b>SQL State</b>	QDC79

## Errors and Warnings

<b>Error 1000299</b>	<b>" Partition key of %2 is unsupported. %1"</b>
<b>SQL Code</b>	-1000299L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	datatype
<b>Parameter 2</b>	location of exception
<b>Probable Cause</b>	Partition key of LOB/CLOB/char/varchar/binary/varbinary over 255 is not supported.
<b>Error 1000302</b>	<b>" Exceed maximum number of partitions. %1"</b>
<b>Constant</b>	EMSG_CAT_EXCEED_MAX_NUM_PARTITIONS
<b>SAP Sybase Error Number</b>	21155
<b>SQL State</b>	QDC82
<b>SQL Code</b>	-1000302L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of exception
<b>Probable Cause</b>	Exceed maximum number of partitions.
<b>Error 1000303</b>	<b>" Object %2 not usable in current context. %1"</b>
<b>Constant</b>	EMSG_CAT_OBJECT_NOT_USABLE
<b>SAP Sybase Error Number</b>	21156
<b>SQL State</b>	QDC83
<b>SQL Code</b>	-1000303L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2

<b>Error 1000303</b>	<b>" Object %2 not usable in current context. %1"</b>
<b>Parameter 1</b>	location of exception
<b>Parameter 2</b>	object name
<b>Probable Cause</b>	Table of TBLTYP_PARTITION type cannot be used.
<b>Error 1000304</b>	<b>" Cannot drop a partition key column. %1"</b>
<b>Constant</b>	EMSG_CAT_CANNOT_DROP_PARTITION_KEY
<b>SAP Sybase Error Number</b>	21157
<b>SQL State</b>	QDC84
<b>SQL Code</b>	-1000304L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of exception
<b>Probable Cause</b>	Can not drop a partition key column.
<b>Error 1000305</b>	<b>" Allocation failure. %1"</b>
<b>Constant</b>	EMSG_DBCC_ALLOCATION_FAILURE
<b>SAP Sybase Error Number</b>	21158
<b>SQL State</b>	QDC85
<b>SQL Code</b>	-1000305L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	DBCC allocation failure
<b>Error 1000306</b>	<b>" Different DB space, cannot merge partition %2 into %3. %1"</b>
<b>Constant</b>	EMSG_CAT_PARTITION_MERGE_ERROR

<b>Error 1000306</b>	" Different DB space, cannot merge partition %2 into %3. %1"
<b>SAP Sybase Error Number</b>	21164
<b>SQL State</b>	QDC86
<b>SQL Code</b>	-1000306L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of exception
<b>Parameter 2</b>	partition1
<b>Parameter 3</b>	partition2
<b>Probable Cause</b>	Cannot merge Partition partition name 1 into Partition partition name2 in different dbspaces

## **Messages 1000307 through 1000328**

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1000307</b>	" No data move is allowed, cannot split partition %2. %1"
<b>Constant</b>	EMSG_CAT_PARTITION_SPLIT_ERROR
<b>SAP Sybase Error Number</b>	21165
<b>SQL State</b>	QDC87
<b>SQL Code</b>	-1000307L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of exception
<b>Parameter 2</b>	partition1
<b>Probable Cause</b>	Cannot split Partition partition name 1 into Partition partition name2 and Partition name3 as the split requires to move data.

<b>Error 1000308</b>	<b>" Boundary value for the partition %2 cannot be changed.%1"</b>
<b>Constant</b>	EMSG_CAT_PARTITION_SPLIT_BOUNDARY_ERROR
<b>SAP Sybase Error Number</b>	21166
<b>SQL State</b>	QDC88
<b>SQL Code</b>	-1000308L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of exception
<b>Parameter 2</b>	partition name1
<b>Probable Cause</b>	Cannot change boundary value for split Partition partition name 1 into (partition-decl-1, partition-decl-2). Boundary value for partition-decl-2 must be the same as partition name 1.
<b>Error 1000309</b>	<b>" Not all partitions in each column are in same dbspace, cannot unpartition %2. %1"</b>
<b>Constant</b>	EMSG_CAT_UNPARTITION_ERROR
<b>SAP Sybase Error Number</b>	21167
<b>SQL State</b>	QDC89
<b>SQL Code</b>	-1000309L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of exception
<b>Parameter 2</b>	tablename
<b>Probable Cause</b>	Cannot alter partitioned table to an unpartitioned table as not all partitions in each column are in the same dbspace.

## Errors and Warnings

<b>Error 1000310</b>	" Cannot truncate table partition on a non-partitioned table %2. %1"
<b>Constant</b>	EMSG_TABLE_NOT_PARTITIONED
<b>SAP Sybase Error Number</b>	21168
<b>SQL State</b>	QDC90
<b>SQL Code</b>	-1000310L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of exception
<b>Parameter 2</b>	tablename
<b>Probable Cause</b>	Cannot truncate table partition on a non-partitioned table.

<b>Error 1000311</b>	" '%2' is not an IQ DBSPACE. %1"
<b>Constant</b>	EMSG_NO_SUCH_IQ_DBSPACE
<b>SAP Sybase Error Number</b>	21169
<b>SQL State</b>	QDC91
<b>SQL Code</b>	-1000311L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of exception
<b>Parameter 2</b>	supplied dbspace name
<b>Probable Cause</b>	Specified dbspace does not exist or is a catalog dbspace.

<b>Error 1000312</b>	" ALTER INDEX MOVE can not move FP indexes. Command failed for %2. Use ALTER TABLE MOVE COLUMN instead. %1"
<b>Constant</b>	EMSG_CANNOT_MOVE_FP_INDEX
<b>SAP Sybase Error Number</b>	21170

<b>Error 1000312</b>	<b>" ALTER INDEX MOVE can not move FP indexes. Command failed for %2. Use ALTER TABLE MOVE COLUMN instead. %1"</b>
<b>SQL State</b>	QDC92
<b>SQL Code</b>	-1000312L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of exception
<b>Parameter 2</b>	Index name
<b>Probable Cause</b>	ALTER INDEX MOVE command does not move FP indexes. Use ALTER TABLE MOVE COLUMN instead.
<b>Error 1000314</b>	<b>" All rows must be in the first partition. %1 "</b>
<b>Constant</b>	EMSG_CAT_PARTITION_ERROR
<b>SAP Sybase Error Number</b>	21173
<b>SQL State</b>	QDC94
<b>SQL Code</b>	-1000314L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of exception
<b>Probable Cause</b>	Cannot alter unpartitioned table to a partitioned table as not all rows in the first partition.
<b>Error 1000315</b>	<b>" Cannot drop the last partition of a partitioned table. %1 "</b>
<b>Constant</b>	EMSG_CAT_CANNOT_DROP_LAST_PARTITION_ERROR
<b>SAP Sybase Error Number</b>	21174
<b>SQL State</b>	QDC95
<b>SQL Code</b>	-1000315L

## Errors and Warnings

<b>Error 1000315</b>	<b>" Cannot drop the last partition of a partitioned table. %1"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of exception
<b>Probable Cause</b>	Cannot drop the last partition of a partitioned table.
<b>Error 1000316</b>	<b>"The NoExec option is set. The current operation will be rolled back. %1"</b>
<b>Constant</b>	EMSG_NOEXEC_OP_PROHIBITED
<b>SAP Sybase Error Number</b>	21175
<b>SQL State</b>	QDC96
<b>SQL Code</b>	-1000316L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	Certain operations will not be allowed whenever the NoExec option is set. They are: Alter table Split Partition & Alter Table Partition
<b>Error 1000317</b>	<b>"The current operation is not allowed on RO partition. %1"</b>
<b>Constant</b>	EMSG_ROPARTITION_OP_PROHIBITED
<b>SAP Sybase Error Number</b>	21181
<b>SQL State</b>	QDC97
<b>SQL Code</b>	-1000317L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.

<b>Error 1000317</b>	<b>"The current operation is not allowed on RO partition. %1"</b>
<b>Probable Cause</b>	Alter table drop/split/merge on a RO partition is not allowed.
<b>Error 1000318</b>	<b>"Unexpected type encountered for column '%2'. %1"</b>
<b>Constant</b>	EMSG_UNEXPECTED_COLUMN_TYPE
<b>SAP Sybase Error Number</b>	21182
<b>SQL State</b>	QDC98
<b>SQL Code</b>	-1000318L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Exception Location
<b>Parameter 2</b>	Column Name
<b>Probable Cause</b>	Parse tree contains an expected column type.
<b>Error 1000319</b>	<b>"Server (%2) is no longer a Multiplex coordinator. %1"</b>
<b>Constant</b>	EMSG_MPX_NODE_NOT_COORDINATOR
<b>SAP Sybase Error Number</b>	21185
<b>SQL State</b>	QDC99
<b>SQL Code</b>	-1000319L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Parameter 1 description
<b>Parameter 2</b>	Parameter 2 description
<b>Probable Cause</b>	Specified server is no longer a Multiplex coordinator.
<b>Error 1000320</b>	<b>"Table with table id %2 no longer exists. %1"</b>
<b>Constant</b>	EMSG_INVALID_TABLE_ID

## Errors and Warnings

<b>Error 1000320</b>	"Table with table id %2 no longer exists. %1"
<b>SAP Sybase Error Number</b>	21189
<b>SQL State</b>	QDD00
<b>SQL Code</b>	-1000320L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Table identifier
<b>Probable Cause</b>	There is no table with the given table id. It would have been dropped.
<b>Error 1000321</b>	"dropleaks is not allowed in multiplex mode. %1"
<b>Constant</b>	EMSG_DBCC_DROPLEAKS_NEED_SIMPLEX
<b>SAP Sybase Error Number</b>	22006
<b>SQL State</b>	QDB85
<b>SQL Code</b>	-1000321L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	Dropleaks require server to be started in simplex configuration
<b>Error 1000322</b>	"Use CREATE DBSPACE USING FILE syntax for creating IQ dbspaces. %1"
<b>Constant</b>	EMSG_CREATE_DBSPACE_FILE_SYNTAX_NOT_USED
<b>SAP Sybase Error Number</b>	22007
<b>SQL State</b>	QDB86
<b>SQL Code</b>	-1000322L

<b>Error 1000322</b>	<b>"Use CREATE DBSPACE USING FILE syntax for creating IQ dbspaces. %1"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	In Atomic IQ dbspaces can be created using the FILE Syntax for create dbspace. Old pre-atomic syntax can be used to create catalog store dbspaces only.
<b>Error 1000324</b>	<b>"Maximum secondary node license limit reached. Cannot add new secondary node. %1"</b>
<b>Constant</b>	EMSG_MPX_MAX_SECONDARY_LICENSE_EXCEEDED
<b>SAP Sybase Error Number</b>	21193
<b>SQL State</b>	QDD03
<b>SQL Code</b>	-1000324L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	New secondary node cannot be added since the license limit for adding a new secondary node has been reached.
<b>Error 1000325</b>	<b>"%2 node cannot be made a failover node. %1"</b>
<b>Constant</b>	EMSG_MPX_CANNOT_BE_FAILOVER
<b>SAP Sybase Error Number</b>	21194
<b>SQL State</b>	QDD04
<b>SQL Code</b>	-1000325L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2

## Errors and Warnings

<b>Error 1000325</b>	<b>"%2 node cannot be made a failover node. %1"</b>
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Could be either Excluded or Coordinator
<b>Probable Cause</b>	An excluded or coordinator node cannot be made a failover node.
<b>Error 1000326</b>	<b>"%2 of Coordinator node cannot be changed. %1"</b>
<b>Constant</b>	EMSG_MPX_COORD_ATTR_CANNOT_CHANGE
<b>SAP Sybase Error Number</b>	21195
<b>SQL State</b>	QDD05
<b>SQL Code</b>	-1000326L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Could be either ROLE or STATUS
<b>Probable Cause</b>	ROLE or STATUS of Coordinator node cannot be changed.
<b>Error 1000327</b>	<b>"Failover node cannot be Excluded. %1"</b>
<b>Constant</b>	EMSG_MPX_CANNOT_EXCLUDE_FAILOVER
<b>SAP Sybase Error Number</b>	21196
<b>SQL State</b>	QDD06
<b>SQL Code</b>	-1000327L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	A designated failover node cannot be Excluded.

<b>Error 1000328</b>	"%2 node cannot be dropped. %1"
<b>Constant</b>	EMSG_MPX_CANNOT_BE_DROPPED
<b>SAP Sybase Error Number</b>	21197
<b>SQL State</b>	QDD07
<b>SQL Code</b>	-1000328L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Could be either COORDINATOR or FAILOVER
<b>Probable Cause</b>	A Coordinator or a Failover node cannot be dropped from the multiplex configuration.

## 1000329 - 1006035

---

### Messages 1000329 through 1001010

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1000329</b>	<b>"The move target %2 is already in the specified dbspace. %1"</b>
<b>Constant</b>	EMSG_MOVE_TARGET_DBSPACE_UNCHANGED
<b>SAP Sybase Error Number</b>	21198
<b>SQL State</b>	QDD02
<b>SQL Code</b>	-1000329L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Target name to be moved.
<b>Parameter 2</b>	Location of the exception.

## Errors and Warnings

<b>Error 1000329</b>	<b>"The move target %2 is already in the specified dbspace. %1"</b>
<b>Probable Cause</b>	The move target for alter table or alter index is already in the specified dbspace.
<b>Error 1000330</b>	<b>"Default value %2 cannot be used as a LOAD default value. %1"</b>
<b>Constant</b>	EMSG_INVALIDLOADDEFAULTVALUE
<b>SAP Sybase Error Number</b>	21199
<b>SQL State</b>	QDD17
<b>SQL Code</b>	-1000330L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of exception
<b>Parameter 2</b>	load default value
<b>Probable Cause</b>	Specified default value cannot be used as a LOAD default value.
<b>Error 1000331</b>	<b>"The requested FP style (%1) for %2 cannot be rebuilt. It will be rebuilt as %3."</b>
<b>Constant</b>	EMSG_CANNOT_REBUILD_FP
<b>SAP Sybase Error Number</b>	21204
<b>SQL State</b>	QDD19
<b>SQL Code</b>	-1000331L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Requested FP style
<b>Parameter 2</b>	FP index
<b>Parameter 3</b>	Actual Rebuilt FP style

<b>Error 1000331</b>	"The requested FP style (%1) for %2 cannot be rebuilt. It will be rebuilt as %3."
<b>Probable Cause</b>	The requested FP style cannot be rebuilt. Increase main cache or set FP_Lookup_Size_PPM to a higher percentage for 3-byte FP.
<b>Error 1000332</b>	"Odd length of binary data value detected on column %2 - %1"
<b>Constant</b>	EMSG_ODDNUMBER_NIBBLES
<b>SAP Sybase Error Number</b>	21206
<b>SQL State</b>	QDD20
<b>SQL Code</b>	-1000332L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	the column where the error occurs
<b>Probable Cause</b>	When loading hexadeciml data into BLOB, the total number of nibbles has to be an even number. If an odd number is detected, the load engine will rollback. This restriction does not apply to binary and varbinary data type.
<b>Error 1000333</b>	"DBCC IQ_SHARED_TEMP dbspace target not allowed with other targets. %1"
<b>Constant</b>	EMSG_DBCC_SHTEMP_MODE
<b>SAP Sybase Error Number</b>	22021
<b>SQL State</b>	QDD22
<b>SQL Code</b>	-1000333L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	Location of the exception.

## Errors and Warnings

<b>Error 1000333</b>	<b>"DBCC IQ_SHARED_TEMP dbspace target not allowed with other targets. %1"</b>
<b>Probable Cause</b>	When specifying the IQ_SHARED_TEMP dbspace as a DBCC mode target, no other targets may be specified.
<b>Error 1000334</b>	<b>"Unsupported DBCC dbspace target \"&gt;%2\%. %1"</b>
<b>Constant</b>	EMSG_DBCC_UNSUPPORTED_DBSPACE
<b>SAP Sybase Error Number</b>	22022
<b>SQL State</b>	QDD23
<b>SQL Code</b>	-1000334L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	Dbspace name.
<b>Probable Cause</b>	DBCC Does not support checking modes on this dbspace target.
<b>Error 1000335</b>	<b>"Cannot add writer when coordinator started with -iqmpx_nowr %1"</b>
<b>Constant</b>	EMSG_MPX_NO_WRITER_ALLOWED
<b>SAP Sybase Error Number</b>	21214
<b>SQL State</b>	QDD25
<b>SQL Code</b>	-1000335L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	14 on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Please restart coordinator without -iqmpx_nowr switch to add writer node

<b>Error 1000336</b>	"Cannot convert to writer when coordinator started with -iqmpx_nowr %1"
<b>Constant</b>	EMSG_MPX_ROLE_CHANGE_DENIED_NOWR
<b>SAP Sybase Error Number</b>	21215
<b>SQL State</b>	QDD26
<b>SQL Code</b>	-1000336L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Please restart coordinator without -iqmpx_nowr switch to change role to writer
<b>Error 1000337</b>	" Number of columns in Hash Partition key cannot be greater than %2. %1"
<b>Constant</b>	EMSG_CAT_NUM_HASH_PARTITION_KEY_COL_EXCEEDED
<b>SAP Sybase Error Number</b>	21216
<b>SQL State</b>	QDD27
<b>SQL Code</b>	-1000337L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of exception
<b>Parameter 2</b>	Maximum number of allowed columns in hash key
<b>Probable Cause</b>	Hash partition key columns cannot be greater than the allowed value.
<b>Error 1001000</b>	"DFE Sum or Average overflow - try CASTing the argument to a larger datatype. %1"
<b>Constant</b>	EMSG_SUMAVGOVERFLOW

## Errors and Warnings

<b>Error 1001000</b>	"DFE Sum or Average overflow - try CASTing the argument to a larger datatype. %1"
<b>SAP Sybase Error Number</b>	20509
<b>SQL State</b>	QFA00
<b>SQL Code</b>	-1001000L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1001001</b>	"DFE Typechecking error %1"
<b>Constant</b>	EMSG_TCHECKERROR
<b>SAP Sybase Error Number</b>	20510
<b>SQL State</b>	QFA01
<b>SQL Code</b>	-1001001L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1001002</b>	"Feature is not yet implemented %1"
<b>Constant</b>	EMSG_NOTIMPLEMENTED
<b>SAP Sybase Error Number</b>	20511
<b>SQL State</b>	QFA02
<b>SQL Code</b>	-1001002L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1001002</b>	"Feature is not yet implemented %1"
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1001003</b>	"Internal error: subclass responsibility %1"
<b>Constant</b>	EMSG_SUBCLASSRESPONSIBILITY
<b>SAP Sybase Error Number</b>	20512
<b>SQL State</b>	QFA03
<b>SQL Code</b>	-1001003L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>18</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1001004</b>	"Data exception - substring error. %1"
<b>Constant</b>	EMSG_SUBSTRINGERROR
<b>SAP Sybase Error Number</b>	20513
<b>SQL State</b>	QFA04
<b>SQL Code</b>	-1001004L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1001005</b>	"Data exception - string length error. %1"
<b>Constant</b>	EMSG_STRINGLENERROR

## Errors and Warnings

<b>Error 1001005</b>	<b>"Data exception - string length error. %1"</b>
<b>SAP Sybase Error Number</b>	20514
<b>SQL State</b>	QFA05
<b>SQL Code</b>	-1001005L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1001006</b>	<b>"Data exception - data type conversion is not possible. %1"</b>
<b>Constant</b>	EMSG_TYPECONVERSION
<b>SAP Sybase Error Number</b>	20515
<b>SQL State</b>	QFA06
<b>SQL Code</b>	-1001006L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1001007</b>	<b>"Data exception - operation resulted in division by zero. %1"</b>
<b>Constant</b>	EMSG_DIVIDEBYZERO
<b>SAP Sybase Error Number</b>	20516
<b>SQL State</b>	QFA07
<b>SQL Code</b>	-1001007L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1001007</b>	<b>"Data exception - operation resulted in division by zero. %1"</b>
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1001008</b>	<b>"Data exception - invalid character data for cast. %1"</b>
<b>Constant</b>	EMSG_BADCASTVALUE
<b>SAP Sybase Error Number</b>	20517
<b>SQL State</b>	QFA08
<b>SQL Code</b>	-1001008L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1001009</b>	<b>"Data exception - string data, right truncation. %1"</b>
<b>Constant</b>	EMSG_TRUNCATEDSTRING
<b>SAP Sybase Error Number</b>	20518
<b>SQL State</b>	QFA09
<b>SQL Code</b>	-1001009L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1001010</b>	<b>"Data exception - numeric value out of range. %1"</b>
<b>Constant</b>	EMSG_NUMERICOUTOFRANGE

<b>Error 1001010</b>	"Data exception - numeric value out of range. %1"
<b>SAP Sybase Error Number</b>	20519
<b>SQL State</b>	QFA10
<b>SQL Code</b>	-1001010L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

## Messages 1001011 through 1001030

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1001011</b>	"Data exception - argument must be DATE or DATETIME %1"
<b>Constant</b>	EMSG_ARGMUSTBEDATETIME
<b>SAP Sybase Error Number</b>	20520
<b>SQL State</b>	QFA11
<b>SQL Code</b>	-1001011L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1001012</b>	"Internal state violation, please contact Sybase IQ support %1"
<b>Constant</b>	EMSG_INTERNALERROR
<b>SAP Sybase Error Number</b>	20521
<b>SQL State</b>	QFA12

<b>Error 1001012</b>	"Internal state violation, please contact Sybase IQ support %1"
<b>SQL Code</b>	-1001012L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I8</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1001013</b>	"Invalid data type comparison %2, %1"
<b>Constant</b>	EMSG_TYPECOMPAREERROR
<b>SAP Sybase Error Number</b>	20522
<b>SQL State</b>	QFA13
<b>SQL Code</b>	-1001013L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	SA parse source code line
<b>Probable Cause</b>	No additional information available.

<b>Error 1001014</b>	"Data conversion failed %1"
<b>Constant</b>	EMSG_DATACONVERSIONERROR
<b>SAP Sybase Error Number</b>	20523
<b>SQL State</b>	QFA14
<b>SQL Code</b>	-1001014L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2

## Errors and Warnings

<b>Error 1001014</b>	<b>"Data conversion failed %1"</b>
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1001015</b>	<b>"QUARTER, WEEK and MILLISECOND dateparts are not currently supported %1"</b>
<b>Constant</b>	EMSG_DATEPARTNOTSUPPORTED
<b>SAP Sybase Error Number</b>	20524
<b>SQL State</b>	QFA15
<b>SQL Code</b>	-1001015L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1001016</b>	<b>"Invalid datepart"</b>
<b>Constant</b>	EMSG_INVALIDDATEPARTTYPE
<b>SAP Sybase Error Number</b>	20525
<b>SQL State</b>	QFA16
<b>SQL Code</b>	-1001016L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1001017</b>	<b>"IQ Internal error in exception code. %1 "</b>
<b>Constant</b>	EMSG_PROGERRORINEXCEPTION
<b>SAP Sybase Error Number</b>	20526
<b>SQL State</b>	QFA17

<b>Error 1001017</b>	<b>"IQ Internal error in exception code. %1 "</b>
<b>SQL Code</b>	-1001017L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>18</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1001018</b>	<b>"INSERT ... VALUES ... accepts only constant expressions as values %2, %1"</b>
<b>Constant</b>	EMSG_BADINSERTVALUES
<b>SAP Sybase Error Number</b>	20527
<b>SQL State</b>	QFA18
<b>SQL Code</b>	-1001018L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	SA parse source code line
<b>Probable Cause</b>	No additional information available.
<b>Error 1001019</b>	<b>"Function not supported on varchars longer than 32767 %2, %1"</b>
<b>Constant</b>	EMSG_FUNCNOTSUPONLVCHAR
<b>SAP Sybase Error Number</b>	20528
<b>SQL State</b>	QFA19
<b>SQL Code</b>	-1001019L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 1001019</b>	"Function not supported on varchars longer than 32767 %2, %1"
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	SA parse source code line
<b>Probable Cause</b>	No additional information available.

<b>Error 1001020</b>	"Incompatible data types %2, %1"
<b>Constant</b>	EMSG_UNIONNOTCOMPATIBLE
<b>SAP Sybase Error Number</b>	20529
<b>SQL State</b>	QFA20
<b>SQL Code</b>	-1001020L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	SA parse source code line
<b>Probable Cause</b>	No additional information available.

<b>Error 1001021</b>	"DFO State machine error %1"
<b>Constant</b>	EMSG_DFOSTATE
<b>SAP Sybase Error Number</b>	20530
<b>SQL State</b>	QFA21
<b>SQL Code</b>	-1001021L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>18</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1001022</b>	<b>"Subquery cardinality violation, &gt; 1 row returned from a subquery %1"</b>
<b>Constant</b>	EMSG_SUBQCARDVIOLATION
<b>SAP Sybase Error Number</b>	20531
<b>SQL State</b>	QFA22
<b>SQL Code</b>	-1001022L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>18</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1001023</b>	<b>"Query rejected because it exceeds resource: Query_Temp_Space_Limit %1"</b>
<b>Constant</b>	EMSG_QUERY_EXCEEDS_SPACE_LIMIT
<b>SAP Sybase Error Number</b>	20532
<b>SQL State</b>	QFA23
<b>SQL Code</b>	-1001023L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>17</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1001024</b>	<b>"Metadata for column %2 is internally inconsistent (%3): database may be corrupted %1"</b>
<b>Constant</b>	EMSG_INCONSISTENT_INDEX_INFO
<b>SAP Sybase Error Number</b>	20533
<b>SQL State</b>	QFA24
<b>SQL Code</b>	-1001024L

## Errors and Warnings

<b>Error 1001024</b>	"Metadata for column %2 is internally inconsistent (%3): database may be corrupted %1"
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column name
<b>Parameter 3</b>	what was apparently corrupted
<b>Probable Cause</b>	No additional information available.

<b>Error 1001025</b>	"Function not currently supported. %2 %1"
<b>Constant</b>	EMSG_DFFUNCNOTSUPPORTED
<b>SAP Sybase Error Number</b>	20534
<b>SQL State</b>	QFA25
<b>SQL Code</b>	-1001025L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	14 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	The SA code line
<b>Probable Cause</b>	No additional information available.

<b>Warning 1001026</b>	"%1"
<b>Constant</b>	EMSG_DF_ONEPLANLINE
<b>SAP Sybase Error Number</b>	20535
<b>SQL State</b>	QFA26
<b>SQL Code</b>	1001026L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK

<b>Warning 1001026</b>	"%1"
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	prefix and detail string
<b>Probable Cause</b>	No additional information available.
<b>Error 1001027</b>	<b>"Query rejected because plan exceeds stack space %1"</b>
<b>Constant</b>	EMSG_QUERY_NEAR_END_OF_STACK
<b>SAP Sybase Error Number</b>	20536
<b>SQL State</b>	QFA27
<b>SQL Code</b>	-1001027L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1001028</b>	<b>"Query rejected because it exceeds resource: Query_Rows_Returned_Limit %1"</b>
<b>Constant</b>	EMSG_QUERY_EXCEEDS_ROW_LIMIT
<b>SAP Sybase Error Number</b>	20537
<b>SQL State</b>	QFA28
<b>SQL Code</b>	-1001028L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I7</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

## Errors and Warnings

<b>Error 1001029</b>	<b>"Index metadata for %2 is internally inconsistent: database may be corrupted %1"</b>
<b>Constant</b>	EMSG_INCONSISTENT_COLUMN_INFO
<b>SAP Sybase Error Number</b>	20538
<b>SQL State</b>	QFA29
<b>SQL Code</b>	-1001029L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column name
<b>Probable Cause</b>	No additional information available.

<b>Error 1001030</b>	<b>"Feature, %2, is not supported. %1"</b>
<b>Constant</b>	EMSG_NOTIMPLEMENTED_W_ARG
<b>SAP Sybase Error Number</b>	20539
<b>SQL State</b>	QFA2A
<b>SQL Code</b>	-1001030L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	feature name
<b>Parameter 2</b>	SA parse source code line
<b>Probable Cause</b>	No additional information available.

## Messages 1001031 through 1001050

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1001031</b>	<b>"Non-aggregate select/having (%2) must appear in the group by %1"</b>
<b>Constant</b>	EMSG_INVALIDGROUPINGEXPR
<b>SAP Sybase Error Number</b>	20540
<b>SQL State</b>	QFA2B
<b>SQL Code</b>	-1001031L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	name of illegal expression
<b>Parameter 2</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1001032</b>	<b>"Thread stack ran past the end of its allocated stack space %1"</b>
<b>Constant</b>	EMSG_THREAD_PAST_END_OF_STACK
<b>SAP Sybase Error Number</b>	20541
<b>SQL State</b>	QFA2C
<b>SQL Code</b>	-1001032L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

## Errors and Warnings

<b>Error 1001033</b>	<b>"Internal state violation, please contact Sybase IQ support %2, %1"</b>
<b>Constant</b>	EMSG_INTERNALERROR_W_ARG
<b>SAP Sybase Error Number</b>	20542
<b>SQL State</b>	QFA2D
<b>SQL Code</b>	-1001033L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Exception line number
<b>Parameter 2</b>	SA parse source code line
<b>Probable Cause</b>	No additional information available.

<b>Error 1001034</b>	<b>"Invalid argument to the rowid function."</b>
<b>Constant</b>	EMSG_INVALID_ROWID_ARG
<b>SAP Sybase Error Number</b>	20543
<b>SQL State</b>	QFA30
<b>SQL Code</b>	-1001034L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	No additional information available.

<b>Error 1001035</b>	<b>"Global variable '%2' in SELECT...FROM... statement is not supported by Sybase IQ, %1"</b>
<b>Constant</b>	EMSG_GLOBVARNOTSUPPORTED
<b>SAP Sybase Error Number</b>	20544
<b>SQL State</b>	QFA31
<b>SQL Code</b>	-1001035L

<b>Error 1001035</b>	<b>"Global variable '%2' in SELECT...FROM... statement is not supported by Sybase IQ, %1"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	variable name
<b>Probable Cause</b>	No additional information available.

<b>Error 1001036</b>	<b>"Host variable '%2' is not initialized, %1"</b>
<b>Constant</b>	EMSG_HOSTVARNOTINIT
<b>SAP Sybase Error Number</b>	20545
<b>SQL State</b>	QFA32
<b>SQL Code</b>	-1001036L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	variable name
<b>Probable Cause</b>	No additional information available.

<b>Error 1001037</b>	<b>"Text-style CONTAINS left-hand arg must be a character type column from a base table. %1"</b>
<b>Constant</b>	EMSG_CONTAINS_LHS
<b>SAP Sybase Error Number</b>	20546
<b>SQL State</b>	QFA33
<b>SQL Code</b>	-1001037L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 1001037</b>	<b>"Text-style CONTAINS left-hand arg must be a character type column from a base table. %1"</b>
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1001038</b>	<b>"Text-style CONTAINS right-hand arglist must be string constants each containing exactly one word. %1"</b>
<b>Constant</b>	EMSG_CONTAINS_RHS
<b>SAP Sybase Error Number</b>	20547
<b>SQL State</b>	QFA34
<b>SQL Code</b>	-1001038L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1001039</b>	<b>"CONTAINS right-hand arglist too large. %1"</b>
<b>Constant</b>	EMSG_CONTAINS_RHS2LARGE
<b>SAP Sybase Error Number</b>	20548
<b>SQL State</b>	QFA35
<b>SQL Code</b>	-1001039L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1001040</b>	<b>"String contains a multi-byte character fragment. %1"</b>
<b>Constant</b>	EMSG_CHARFRAG
<b>SAP Sybase Error Number</b>	20549
<b>SQL State</b>	QFA36
<b>SQL Code</b>	-1001040L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1001041</b>	<b>"Word-style CONTAINS left-hand arg must have a WD index. %1"</b>
<b>Constant</b>	EMSG_CONTAINS_NOINDEX
<b>SAP Sybase Error Number</b>	20550
<b>SQL State</b>	QFA37
<b>SQL Code</b>	-1001041L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1001042</b>	<b>"Table, '%2', is not accessible in this context. %1"</b>
<b>Constant</b>	EMSG_TABLEACCESS_ERR_WARG
<b>SAP Sybase Error Number</b>	20551
<b>SQL State</b>	QFA38
<b>SQL Code</b>	-1001042L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1001042</b>	"Table, '%2', is not accessible in this context. %1"
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	table name
<b>Probable Cause</b>	No additional information available.
<b>Error 1001043</b>	"Report to Sybase IQ Support. Query "%2', %1"
<b>Constant</b>	EMSG_REWRITE_QUERY_WARG
<b>SAP Sybase Error Number</b>	20552
<b>SQL State</b>	QFA39
<b>SQL Code</b>	-1001043L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	error message
<b>Probable Cause</b>	No additional information available.
<b>Error 1001044</b>	"Incompatible datatypes in ARGN. %1"
<b>Constant</b>	EMSG_BAD_ARGN
<b>SAP Sybase Error Number</b>	20553
<b>SQL State</b>	QFA40
<b>SQL Code</b>	-1001044L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1001045</b>	"Invalid argument in Extract option: %2. %1"
<b>Constant</b>	EMSG_BAD_EXTRACT_WARG
<b>SAP Sybase Error Number</b>	20554
<b>SQL State</b>	QFA41
<b>SQL Code</b>	-1001045L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Invalid option
<b>Probable Cause</b>	No additional information available.

<b>Error 1001046</b>	"Extract exceeds maximum supported row width of %2 (width %3). %1"
<b>Constant</b>	EMSG_EXTRACT_TOO_WIDE_WARG
<b>SAP Sybase Error Number</b>	20555
<b>SQL State</b>	QFA42
<b>SQL Code</b>	-1001046L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	maximum width supported
<b>Parameter 3</b>	current width
<b>Probable Cause</b>	No additional information available.

<b>Error 1001047</b>	"%2. %1"
<b>Constant</b>	EMSG_QUERY_GENERIC_WARG
<b>SAP Sybase Error Number</b>	20556

## Errors and Warnings

<b>Error 1001047</b>	"%2. %1"
<b>SQL State</b>	QFA43
<b>SQL Code</b>	-1001047L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	error message
<b>Probable Cause</b>	No additional information available.

<b>Error 1001048</b>	<b>"To display a varbinary column &gt; 32k you must set the parameter Ase_Binary_Display to off. %1"</b>
<b>Constant</b>	EMSG_VARBIN_TOOBIG
<b>SAP Sybase Error Number</b>	20557
<b>SQL State</b>	QFA44
<b>SQL Code</b>	-1001048L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	cannot convert any varbinary > 32k to varchar.

<b>Error 1001049</b>	<b>"Expression, \ "%2\ " changed datatypes between CURSOR DESCRIBE and CURSOR OPEN from %3. The CURSOR DESCRIBE needs to be rerun %1"</b>
<b>Constant</b>	EMSG_DATATYPE_CHANGE
<b>SAP Sybase Error Number</b>	20558
<b>SQL State</b>	QFA45
<b>SQL Code</b>	-1001049L
<b>ODBC 2 State</b>	ERROR

<b>Error 1001049</b>	<b>"Expression, \%"2\  changed datatypes between CURSOR DESCRIBE and CURSOR OPEN from %3. The CURSOR DESCRIBE needs to be rerun %1"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column number
<b>Parameter 3</b>	datatype info
<b>Probable Cause</b>	Given a database's BLOCK SIZE and the number of blocks specified by the user for the dbspace, the dbspace size (in bytes) would exceed the OS's limit of bytes per file.
<b>Error 1001050</b>	<b>"this row is too wide to extract. Reduce the row width to less than %2 (iq page size) %1"</b>
<b>Constant</b>	EMSG_EXTRACT_ROW_TOO_WIDE
<b>SAP Sybase Error Number</b>	20559
<b>SQL State</b>	QFA46
<b>SQL Code</b>	-1001050L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	this row width
<b>Probable Cause</b>	An attempt was made to extract a row that is larger than this database's pagesize.

## Messages 1001051 through 1001071

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1001051</b>	<b>"Query returns %2 data &gt; 2GB. Use %3 %1"</b>
<b>Constant</b>	EMSG_LOB_OVER_2G_W_ARG

## Errors and Warnings

<b>Error 1001051</b>	"Query returns %2 data > 2GB. Use %3 %1"
<b>SAP Sybase Error Number</b>	21097
<b>SQL State</b>	QFA47
<b>SQL Code</b>	-1001051L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	long binary or long varchar data type
<b>Parameter 2</b>	function recommended
<b>Parameter 3</b>	SA parse source code line
<b>Probable Cause</b>	No additional information available.
<b>Error 1001052</b>	"Parameter %2 must be long binary/varchar type. %3 %1"
<b>Constant</b>	EMSG_ONLY_SUPPORT_LOB_W_ARG
<b>SAP Sybase Error Number</b>	21098
<b>SQL State</b>	QFA48
<b>SQL Code</b>	-1001052L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	lob argument name
<b>Parameter 2</b>	recommended function name
<b>Parameter 3</b>	SA parse source code line
<b>Probable Cause</b>	No additional information available.
<b>Error 1001053</b>	"Wrong number of parameters to function %2 %1"
<b>Constant</b>	EMSG_WRONG_NUM_PARAMS_W_ARG
<b>SAP Sybase Error Number</b>	21099
<b>SQL State</b>	QFA49

<b>Error 1001053</b>	"Wrong number of parameters to function %2 %1"
<b>SQL Code</b>	-1001053L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	function name
<b>Parameter 2</b>	SA parse source code line
<b>Probable Cause</b>	No additional information available.
<b>Error 1001054</b>	"You cannot specify long binary/varchar column in the ORDER/GROUP by clause or in an aggregate function. %1"
<b>Constant</b>	EMSG_LOB_NOT_ALLOWED_GROUP
<b>SAP Sybase Error Number</b>	21100
<b>SQL State</b>	QFA50
<b>SQL Code</b>	-1001054L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Warning 1001055</b>	"An error occurred loading %1 column, %2, for %3, rowid %4. "
<b>Constant</b>	EMSG_LOB_LOAD_ERROR_WARN
<b>SAP Sybase Error Number</b>	21101
<b>SQL State</b>	QFA51
<b>SQL Code</b>	1001055L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK

## Errors and Warnings

<b>Warning 1001055</b>	"An error occurred loading %1 column, %2, for %3, rowid %4. "
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	long binary or long varchar data type
<b>Parameter 2</b>	FP index name
<b>Parameter 3</b>	secondary file name
<b>Parameter 4</b>	rowid
<b>Probable Cause</b>	No additional information available.
<b>Warning 1001056</b>	"An error occurred extracting %1 column, %2, for %3. "
<b>Constant</b>	EMSG_LOB_EXTRACT_ERROR_WARN
<b>SAP Sybase Error Number</b>	21102
<b>SQL State</b>	QFA52
<b>SQL Code</b>	1001056L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	long binary or long varchar data type
<b>Parameter 2</b>	FP index name
<b>Parameter 3</b>	secondary file name
<b>Probable Cause</b>	No additional information available.
<b>Error 1001057</b>	"You must use BFILE() to extract %2 column. %1"
<b>Constant</b>	EMSG_LOB_EXTRACT_USE_BFILE
<b>SAP Sybase Error Number</b>	21103
<b>SQL State</b>	QFA53
<b>SQL Code</b>	-1001057L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1001057</b>	" <b>You must use BFILE() to extract %2 column. %1</b> "
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	long binary or long varchar data type
<b>Parameter 2</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1001058</b>	" <b>The secondary file name, %2, is too long. %1</b> "
<b>Constant</b>	EMSG_LOB_SECONDARY_FILE_TOOLONG
<b>SAP Sybase Error Number</b>	21104
<b>SQL State</b>	QFA54
<b>SQL Code</b>	-1001058L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	secondary file name
<b>Parameter 2</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1001059</b>	" <b>IQ does not support ASE extended group by syntax (%2) with join tables %1</b> "
<b>Constant</b>	EMSG_EXTGROUPINGWITHJOIN
<b>SAP Sybase Error Number</b>	21106
<b>SQL State</b>	QFA2F
<b>SQL Code</b>	-1001059L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	name of illegal expression
<b>Parameter 2</b>	location of the exception

## Errors and Warnings

<b>Error 1001059</b>	<b>"IQ does not support ASE extended group by syntax (%2) with join tables %1"</b>
<b>Probable Cause</b>	No additional information available.
<b>Error 1001060</b>	<b>"IQ does not support ASE extended group by columns (%2) from view/derived table with distinct/group by/aggregations %1"</b>
<b>Constant</b>	EMSG_EXTGROUPINGFROMVIEW
<b>SAP Sybase Error Number</b>	21107
<b>SQL State</b>	QFA2G
<b>SQL Code</b>	-1001060L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	name of illegal expression
<b>Parameter 2</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1001061</b>	<b>"extract error: incorrect \"%2\" size: valid sizes \"0 to %3\" %1"</b>
<b>Constant</b>	EMSG_EXTRACT_ERROR
<b>SAP Sybase Error Number</b>	20560
<b>SQL State</b>	QFA55
<b>SQL Code</b>	-1001061L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	type of extract delimiter error
<b>Parameter 3</b>	max size

<b>Error 1001061</b>	"extract error: incorrect \"%2\" size: valid sizes \"0 to %3\" %1"
<b>Probable Cause</b>	either a column delimiter or a row delimiter is of incorrect length
<b>Error 1001062</b>	<b>"IQ does not support ASE extended group by syntax (%2) with OLAP function %1"</b>
<b>Constant</b>	EMSG_EXTGROUPINGWITHOLAP
<b>SAP Sybase Error Number</b>	21120
<b>SQL State</b>	QFA2H
<b>SQL Code</b>	-1001062L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	name of illegal expression
<b>Parameter 2</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1001063</b>	<b>"Encrypt/Decrypt: Currently only AES algorithm is supported."</b>
<b>Constant</b>	EMSG_ENCRYPT_ALGO_ERROR
<b>SAP Sybase Error Number</b>	20561
<b>SQL State</b>	QFA56
<b>SQL Code</b>	-1001063L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	when the algorithm string is other than AES.
<b>Error 1001064</b>	<b>"Decryption error: %2. %1"</b>
<b>Constant</b>	EMSG_DECRYPTION_ERROR

## Errors and Warnings

<b>Error 1001064</b>	"Decryption error: %2. %1"
<b>SAP Sybase Error Number</b>	20562
<b>SQL State</b>	QFA57
<b>SQL Code</b>	-1001064L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	error message
<b>Probable Cause</b>	An error occurred during decryption.
<b>Error 1001065</b>	"Encryption/Decryption for %2 datatype is not supported. %1"
<b>Constant</b>	EMSG_ENCRYPT_UNSUPPORTED_DATATYPE
<b>SAP Sybase Error Number</b>	20563
<b>SQL State</b>	QFA58
<b>SQL Code</b>	-1001065L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	datatype value which is not supported like float.
<b>Probable Cause</b>	An error occurred during encryption/decryption.
<b>Error 1001066</b>	"Encrypt/Decrypt Error: %2. %1"
<b>Constant</b>	EMSG_ENCRYPT_SIZE_ERROR
<b>SAP Sybase Error Number</b>	20564
<b>SQL State</b>	QFA59
<b>SQL Code</b>	-1001066L

<b>Error 1001066</b>	"Encrypt/Decrypt Error: %2. %1"
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	large input and key size not supported.
<b>Probable Cause</b>	An error occurred during encryption/decryption.

<b>Error 1001067</b>	"Encrypt/Decrypt Error: %2. %1"
<b>Constant</b>	EMSG_ENCRYPT_NULL_ERROR
<b>SAP Sybase Error Number</b>	20565
<b>SQL State</b>	QFA60
<b>SQL Code</b>	-1001067L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	key and algorithm string as null are not supported.
<b>Probable Cause</b>	An error occurred during encryption/decryption.

<b>Error 1001068</b>	"Datatype, %2 is not supported for this operation. %1"
<b>Constant</b>	EMSG_DATATYPE_NOT_SUPPORTED_ERROR
<b>SAP Sybase Error Number</b>	20567
<b>SQL State</b>	QFA61
<b>SQL Code</b>	-1001068L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception

## Errors and Warnings

<b>Error 1001068</b>	<b>"Datatype, %2 is not supported for this operation. %1"</b>
<b>Parameter 2</b>	datatype.
<b>Probable Cause</b>	The reported datatype is not supported by Sybase IQ.
<b>Error 1001070</b>	<b>"Unable to load shared library for user-defined function. %1"</b>
<b>Constant</b>	EMSG_UDF_LIBRARY_ERROR
<b>SAP Sybase Error Number</b>	20569
<b>SQL State</b>	QFA63
<b>SQL Code</b>	-1001070L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Shared library for the UDF could not be loaded.
<b>Error 1001071</b>	<b>"No valid license found for user-defined function. Feature: %2 %1"</b>
<b>Constant</b>	EMSG_UDF_LICENSE_ERROR
<b>SAP Sybase Error Number</b>	20572
<b>SQL State</b>	QFA64
<b>SQL Code</b>	-1001071L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	licensed feature
<b>Parameter 2</b>	location of the exception
<b>Probable Cause</b>	No valid license found for UDF feature.

## Messages 1001072 through 1003001

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1001072</b>	<b>"User-defined function %2 internal programming error. %3 . %1"</b>
<b>Constant</b>	EMSG_UDF_PROGRAMMING_ERROR
<b>SAP Sybase Error Number</b>	20573
<b>SQL State</b>	QFA65
<b>SQL Code</b>	-1001072L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	function name
<b>Parameter 3</b>	specific UDF programming error
<b>Probable Cause</b>	User-defined function has an internal programming error.
<b>Error 1001073</b>	<b>"The result datatype for function '%2' exceeds the maximum supported numeric precision of 255. Please set the proper value for precision in numeric function, %1"</b>
<b>Constant</b>	EMSG_PRECISIONOVERFLOW
<b>SAP Sybase Error Number</b>	20574
<b>SQL State</b>	QFA66
<b>SQL Code</b>	-1001073L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Field Name

## Errors and Warnings

<b>Error 1001073</b>	<b>"The result datatype for function '%2' exceeds the maximum supported numeric precision of 255. Please set the proper value for precision in numeric function, %1"</b>
<b>Probable Cause</b>	Precision requested for numeric function is larger than what is allowed. Please set the proper value for precision if not set.
<b>Error 1001074</b>	<b>"The number of select list columns do not match the required for the input table parameter %2, %1"</b>
<b>Constant</b>	EMSG_TPF_INBL_INSEL_COLNUM_MISMATCH
<b>SAP Sybase Error Number</b>	20575
<b>SQL State</b>	QFA67
<b>SQL Code</b>	-1001074L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	input table parameter name
<b>Probable Cause</b>	MARKNEW Please check your input query or definition of the UDF.
<b>Error 1001100</b>	<b>"Load/insert/update/delete/RLV are not supported for 15.x char/varchar/varbinary columns of width greater than 255 and LOB datatypes. Please execute sp_iqrebuildindex first to convert the index to IQ version 16. %1"</b>
<b>Constant</b>	EMSG_15_LVC_LOB_UPDATE_NOT_SUPPORTED
<b>SAP Sybase Error Number</b>	22150
<b>SQL State</b>	QSB92
<b>SQL Code</b>	-1001100L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception

<b>Error 1001100</b>	<b>"Load/insert/update/delete/RLV are not supported for 15.x char/varchar/varbinary columns of width greater than 255 and LOB datatypes. Please execute sp_iqrebuildindex first to convert the index to IQ version 16. %1"</b>
<b>Probable Cause</b>	When IQ 16.x engine attempts to load/insert/update data into a 15.x char/varchar/varbinary greater than 255 or LOB FP index, this exception is thrown to indicate that the operation is not allowed. It is required to run sp_iqrebuildindex first so as to convert the index to IQ version 16.

<b>Error 1001102</b>	<b>"RLV store merge already in progress for table %2. %1"</b>
<b>Constant</b>	EMSG_RV_MERGE_IN_PROGRESS
<b>SAP Sybase Error Number</b>	22038
<b>SQL State</b>	QRA02
<b>SQL Code</b>	-1001102L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	The illegal merge string
<b>Probable Cause</b>	There is already an RLV store merge in progress for this table. Only one RLV merge is allowed at a time for an RLV table.

<b>Error 1001103</b>	<b>"Table %2 is not RLV enabled. %1"</b>
<b>Constant</b>	EMSG_RV_MERGE_NOT_RLV_ENABLED
<b>SAP Sybase Error Number</b>	22039
<b>SQL State</b>	QRA03
<b>SQL Code</b>	-1001103L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception

## Errors and Warnings

<b>Error 1001103</b>	<b>"Table %2 is not RLV enabled. %1"</b>
<b>Parameter 2</b>	The table name
<b>Probable Cause</b>	An RLV store merge was attempted on a table which was not RLV enabled. Only tables which are RLV enabled may be merged.
<b>Error 1001104</b>	<b>"Unable to perform merge, table %2 has too many fragments. %1"</b>
<b>Constant</b>	EMSG_RV_MERGE_TOO_MANY_FRAGMENTS
<b>SAP Sybase Error Number</b>	22040
<b>SQL State</b>	QRA04
<b>SQL Code</b>	-1001104L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	table name
<b>Probable Cause</b>	Long running transactions are keeping too many old fragments of the table in memory. Table cannot be merged until the long running transactions terminate.
<b>Error 1001105</b>	<b>"Table %2 requires an RLV store merge before table-level modification. %1"</b>
<b>Constant</b>	EMSG_RV_MERGE_NEEDED
<b>SAP Sybase Error Number</b>	22041
<b>SQL State</b>	QRA05
<b>SQL Code</b>	-1001105L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2

<b>Error 1001105</b>	<b>"Table %2 requires an RLV store merge before table-level modification. %1"</b>
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	The table name
<b>Probable Cause</b>	An table-level RW operation was attempted on an RLV table requiring merge of the RLV store. This merge cannot be done automatically because the current transaction has already established a snapshot version for this table. Either run a manual merge first using sp_iqmergerlvstore or modify the transaction such that blocking is enabled and the the first statement in the transaction is a table-level RW command.

<b>Error 1001106</b>	<b>"Transaction attempted to delete or update a row in "%2" already deleted or updated by another transaction. %1"</b>
<b>Constant</b>	EMSG_RV_FUTUREVERSION
<b>SAP Sybase Error Number</b>	22042
<b>SQL State</b>	QRA06
<b>SQL Code</b>	-1001106L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	The table name
<b>Probable Cause</b>	A transaction attempted to delete or update a row that has already been deleted or updated by another transaction. Row Level Versioning does not allow access to future versions of the row.

<b>Error 1001107</b>	<b>"PARALLEL IQ is not supported for RLV enabled tables."</b>
<b>Constant</b>	EMSG_RV_NO_PARALLEL_IQ
<b>SAP Sybase Error Number</b>	22043
<b>SQL State</b>	QRA07
<b>SQL Code</b>	-1001107L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1001107</b>	<b>"PARALLEL IQ is not supported for RLV enabled tables."</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	BEGIN .. END PARALLEL IQ is not supported if any of the tables on which (parallel) index is to be created is RLV enabled.
<b>Error 1001108</b>	<b>"The option 'Revert_To_V15_Optimizer' is not supported for queries involving RLV enabled tables"</b>
<b>Constant</b>	EMSG_RV_V15_CONFLICT
<b>SAP Sybase Error Number</b>	22044
<b>SQL State</b>	QRA08
<b>SQL Code</b>	-1001108L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	Pre-Elan optimization is used with revert_to_v15_optimizer option, query tree creation itself does not allow it if table is RLV enabled.
<b>Error 1002000</b>	<b>"Unknown error: %1"</b>
<b>Constant</b>	EMSG_DATA_UNKNOWN
<b>SAP Sybase Error Number</b>	20502
<b>SQL State</b>	QGA00
<b>SQL Code</b>	-1002000L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1002001</b>	"Data has already been inserted into index %2 for row %3. %1"
<b>Constant</b>	EMSG_DATA_ALREADYINSERTED
<b>SAP Sybase Error Number</b>	20503
<b>SQL State</b>	QGA01
<b>SQL Code</b>	-1002001L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Parameter 3</b>	explanation for arg %3 delete if no %3
<b>Probable Cause</b>	No additional information available.

<b>Error 1002002</b>	" for IQ_ROWID row "
<b>Constant</b>	EMSG_NOT_USED
<b>SAP Sybase Error Number</b>	20504
<b>SQL State</b>	QGA02
<b>SQL Code</b>	-1002002L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	No additional information available.

<b>Error 1002003</b>	"Tried to insert a duplicate value into a unique index %2 on row %3. %1"
<b>Constant</b>	EMSG_DATA_DUPLICATEVALUE
<b>SAP Sybase Error Number</b>	20505
<b>SQL State</b>	QGA03

## Errors and Warnings

<b>Error 1002003</b>	"Tried to insert a duplicate value into a unique index %2 on row %3. %1"
<b>SQL Code</b>	-1002003L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Parameter 3</b>	explanation for arg %3 delete if no %3
<b>Probable Cause</b>	No additional information available.
<b>Error 1002004</b>	<b>No message</b>
<b>Constant</b>	EMSG_DATA_DUPLICATEVALUE2_EMPTY_SLOT
<b>SAP Sybase Error Number</b>	20506
<b>SQL State</b>	QGA04
<b>SQL Code</b>	-1002004L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1002005</b>	"Tried to insert a null value into a non-null field %2 on row %3. %1"
<b>Constant</b>	EMSG_DATA_NONULLSALLOWED
<b>SAP Sybase Error Number</b>	20507
<b>SQL State</b>	QGA05
<b>SQL Code</b>	-1002005L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1002005</b>	"Tried to insert a null value into a non-null field %2 on row %3. %1"
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Parameter 3</b>	explanation for arg %3 delete if no %3
<b>Probable Cause</b>	No additional information available.

<b>Error 1002006</b>	<b>No message</b>
<b>Constant</b>	EMSG_DATA_NONULLSALLOWED2_EMPTY_SLOT
<b>SAP Sybase Error Number</b>	20508
<b>SQL State</b>	QGA06
<b>SQL Code</b>	-1002006L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.

<b>Error 1003000</b>	"Datatype %2, returned by Client Library, is not valid in Sybase IQ. %1"
<b>Constant</b>	EMSG_HQM_BAD_DATATYPE
<b>SAP Sybase Error Number</b>	20172
<b>SQL State</b>	QHA00
<b>SQL Code</b>	-1003000L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	name of the CTLib datatype

<b>Error 1003000</b>	<b>"Datatype %2, returned by Client Library, is not valid in Sybase IQ. %1"</b>
<b>Probable Cause</b>	Sybase IQ doesn't support a number of datatypes that ASE does (text or image, for example). Refer to documentation for the respective products to see what datatypes are supported.
<b>Error 1003001</b>	<b>"Cannot convert to Sybase IQ datatype: %2 from Client Library datatype %3. %1"</b>
<b>Constant</b>	EMSG_HQM_CANT_CONVERT
<b>SAP Sybase Error Number</b>	20173
<b>SQL State</b>	QHA01
<b>SQL Code</b>	-1003001L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	name of the IQ datatype
<b>Parameter 3</b>	name of the CTLib datatype
<b>Probable Cause</b>	Error converting CSLIB datatype to IQ datatype.

## Messages 1003002 through 1004007

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1003002</b>	<b>"CtLibrary Error: %2, Severity: %3, Origin: %4, Layer: %5\nError Message: %6\nOS Error: %7, OS Message: %8. %1"</b>
<b>Constant</b>	EMSG_HQM_CTLIB_ERROR
<b>SAP Sybase Error Number</b>	20174
<b>SQL State</b>	QHA02
<b>SQL Code</b>	-1003002L
<b>ODBC 2 State</b>	ERROR

<b>Error 1003002</b>	"CtLibrary Error: %2, Severity: %3, Origin: %4, Layer: %5\nError Message: %6\nOS Error: %7, OS Message: %8.\n%1"
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	CtLib error number
<b>Parameter 3</b>	CtLib severity number
<b>Parameter 4</b>	CtLib origin number
<b>Parameter 5</b>	CtLib layer number
<b>Parameter 6</b>	CtLib error message
<b>Parameter 7</b>	OS error number (optional)
<b>Parameter 8</b>	OS error message (optional)
<b>Probable Cause</b>	General CTLIB/CSLIB error message. Refer to the CTLibrary/CSLibrary for error information.
<b>Error 1003003</b>	"Adaptive Server Error: %2, Severity: %3, State: %4, Line: %5\nServer Name: %6, Procedure Name: %7\nError Message: %8. %1"
<b>Constant</b>	EMSG_HQM_SERVER_ERROR
<b>SAP Sybase Error Number</b>	20175
<b>SQL State</b>	QHA03
<b>SQL Code</b>	-1003003L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Server error number
<b>Parameter 3</b>	Server severity number
<b>Parameter 4</b>	Server state number

## Errors and Warnings

<b>Error 1003003</b>	"Adaptive Server Error: %2, Severity: %3, State: %4, Line: %5\nServer Name: %6, Procedure Name: %7\nError Message: %8. %1"
<b>Parameter 5</b>	Server line number
<b>Parameter 6</b>	Server name (optional)
<b>Parameter 7</b>	Server stored procedure name (optional)
<b>Parameter 8</b>	Server error message
<b>Probable Cause</b>	ASE error. Refer to the ASE error documentation for information regarding the error.
<b>Error 1003004</b>	"COMPUTE values cannot be used in attached database queries. %1"
<b>Constant</b>	EMSG_HQM_NOCOMPUTES
<b>SAP Sybase Error Number</b>	20176
<b>SQL State</b>	QHA04
<b>SQL Code</b>	-1003004L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Sybase IQ doesn't process COMPUTE clauses.
<b>Error 1003005</b>	"Connectivity libraries cannot be found (check your dynamic library search path). Selects from attached databases are not possible without these libraries. %1"
<b>Constant</b>	EMSG_HQM_CTSTUB
<b>SAP Sybase Error Number</b>	20177
<b>SQL State</b>	QHA05
<b>SQL Code</b>	-1003005L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1003005</b>	<b>"Connectivity libraries cannot be found (check your dynamic library search path). Selects from attached databases are not possible without these libraries. %1"</b>
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Cannot process attached DB request without the connectivity libraries. Check your dynamic library search path to make sure it is correct.

<b>Error 1003006</b>	<b>"A call to ct_con_props failed trying to get the msglist from the connection. %1"</b>
<b>Constant</b>	EMSG_HQM_GET_MSG
<b>SAP Sybase Error Number</b>	20178
<b>SQL State</b>	QHA06
<b>SQL Code</b>	-1003006L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	While trying to report an error condition, another error occurred trying to retrieve the original error from the connection in order to report it to the user. If this error occurs, retry the operation that caused it.

<b>Error 1003007</b>	<b>"%2 functionality is not licensed on this server. %1"</b>
<b>Constant</b>	EMSG_NO_LICENSE
<b>SAP Sybase Error Number</b>	20179
<b>SQL State</b>	QHA07
<b>SQL Code</b>	-1003007L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2

## Errors and Warnings

<b>Error 1003007</b>	<b>"%2 functionality is not licensed on this server. %1"</b>
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	Product or feature that is not licensed on the server.
<b>Probable Cause</b>	The named feature is not licensed on the server.
<b>Error 1003008</b>	<b>"Licensing error. Code = %2. %1"</b>
<b>Constant</b>	EMSG_CAT_LICENSE_ERROR
<b>SAP Sybase Error Number</b>	20180
<b>SQL State</b>	QHA08
<b>SQL Code</b>	-1003008L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	Error code returned from the license checking.
<b>Probable Cause</b>	An error occurred while verifying the license. Refer to the documentation for information about the Code reported in the error.
<b>Error 1003009</b>	<b>"The specified target contains no indexes on which to report. %1"</b>
<b>Constant</b>	EMSG_NOTHING_TO_REPORT
<b>SAP Sybase Error Number</b>	20181
<b>SQL State</b>	QHA09
<b>SQL Code</b>	-1003009L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	sp_iqindexfragmentation will report this error if it is run on a table that contains only FP indexes.

<b>Error 1003010</b>	<b>No message</b>
<b>Constant</b>	EMSG_HQM_EMPTY_SLOT6
<b>SAP Sybase Error Number</b>	20182
<b>SQL State</b>	QHA10
<b>SQL Code</b>	-1003010
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1003011</b>	<b>No message</b>
<b>Constant</b>	EMSG_HQM_EMPTY_SLOT7
<b>SAP Sybase Error Number</b>	20183
<b>SQL State</b>	QHA11
<b>SQL Code</b>	-1003011L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1003012</b>	<b>No message</b>
<b>Constant</b>	EMSG_HQM_EMPTY_SLOT8
<b>SAP Sybase Error Number</b>	20184
<b>SQL State</b>	QHA12
<b>SQL Code</b>	-1003012L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.

## Errors and Warnings

<b>Error 1003013</b>	<b>No message</b>
<b>Constant</b>	EMSG_HQM_EMPTY_SLOT9
<b>SAP Sybase Error Number</b>	20185
<b>SQL State</b>	QHA13
<b>SQL Code</b>	-1003013L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1003014</b>	<b>No message</b>
<b>Constant</b>	EMSG_HQM_EMPTY_SLOT10
<b>SAP Sybase Error Number</b>	20186
<b>SQL State</b>	QHA14
<b>SQL Code</b>	-1003014L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1004000</b>	<b>"The number of connections in the connection pool have exceeded the upper limit"</b>
<b>Constant</b>	EMSG_INC_MAXCONNEXCEEDED
<b>SAP Sybase Error Number</b>	20209
<b>SQL State</b>	QIA00
<b>SQL Code</b>	-1004000L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1004000</b>	"The number of connections in the connection pool have exceeded the upper limit"
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	The number of connections in the connection pool have exceeded the total number of connections allowed in the connection pool. No more connections can be allocated.
<b>Error 1004001</b>	"Number of unused connections exceeded the maximum number of unused connections in the connection pool"
<b>Constant</b>	EMSG_INC_MAXUNUSED_EXCEEDED
<b>SAP Sybase Error Number</b>	20210
<b>SQL State</b>	QIA01
<b>SQL Code</b>	-1004001L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	The number of unused connections in the connection pool has exceeded the maximum number of unused connections in the connection pool.
<b>Error 1004003</b>	"Timeout period should be greater than or equal to the heartbeat frequency"
<b>Constant</b>	EMSG_INVALIDTIMEOUTPERIOD1
<b>SAP Sybase Error Number</b>	20212
<b>SQL State</b>	QIA03
<b>SQL Code</b>	-1004003L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	All the timeout periods should be greater than or equal to the heartbeat frequency.

## Errors and Warnings

<b>Error 1004004</b>	<b>"No connection found for the server id %1 on the coordinator"</b>
<b>Constant</b>	EMSG_CONNECTIONNOTFOUND
<b>SAP Sybase Error Number</b>	20215
<b>SQL State</b>	QIA04
<b>SQL Code</b>	-1004004L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Parameter 1 description
<b>Probable Cause</b>	A secondary node with the given server id does not exist on the coordinator connection list
<b>Error 1004005</b>	<b>"Timeout period should be multiple of the Heartbeat Frequency"</b>
<b>Constant</b>	EMSG_INVALIDTIMEOUTPERIOD2
<b>SAP Sybase Error Number</b>	20216
<b>SQL State</b>	QIA05
<b>SQL Code</b>	-1004005L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	All the timeout periods of INC(e.g.,AUTOEXCLUDE,LIVENESS,IDLE_CONNECTION) requires to be multiple of the Heartbeat Frequency.
<b>Error 1004006</b>	<b>"Unused Connection Pool size should be always less than the Maximum Connection Pool size"</b>
<b>Constant</b>	EMSG_INVALIDUNUSEDPOOLSIZE
<b>SAP Sybase Error Number</b>	20217
<b>SQL State</b>	QIA06

<b>Error 1004006</b>	"Unused Connection Pool size should be always less than the Maximum Connection Pool size"
<b>SQL Code</b>	-1004006L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	Unused Connection pool size can not be greater than the maximum allowable size of the Connection pool
<b>Error 1004007</b>	"Unable to acquire a pooled connection to the coordinator node"
<b>Constant</b>	EMSG_INC_NOPOOLEDCONNECTION
<b>SAP Sybase Error Number</b>	20218
<b>SQL State</b>	QIA07
<b>SQL Code</b>	-1004007L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	There are no empty pooled connections on the secondary node and also no new connections can be established because the total number of connections has exceeded the maximum capacity of the connection pool

## Messages 1004008 through 1005010

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1004008</b>	"Coordinator node is offline"
<b>Constant</b>	EMSG_INC_NODE_OFFLINE
<b>SAP Sybase Error Number</b>	20219
<b>SQL State</b>	QIA08
<b>SQL Code</b>	-1004008L

## Errors and Warnings

<b>Error 1004008</b>	"Coordinator node is offline"
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	Coordinator node is offline and hence, all the suspended commands on the suspended connections will be terminated
<b>Error 1004009</b>	"INC communication failure %1"
<b>Constant</b>	EMSG_INC_CONN_INTERNAL_ERROR
<b>SAP Sybase Error Number</b>	20220
<b>SQL State</b>	QIA09
<b>SQL Code</b>	-1004009L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of exception
<b>Probable Cause</b>	INC communication failure. This can happen if either the coordinator or the secondary node is restarted or shutdown down when the other node is trying to connect to it
<b>Error 1004010</b>	"Error in getting current user information"
<b>Constant</b>	EMSG_INC_NOUSERFOUND
<b>SAP Sybase Error Number</b>	20221
<b>SQL State</b>	QIA10
<b>SQL Code</b>	-1004010L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	Error returned while trying to find out the current user connected to the given node

<b>Error 1004011</b>	<b>"Coordinator node not responding"</b>
<b>Constant</b>	EMSG_INC_NODE_NOT_ALIVE
<b>SAP Sybase Error Number</b>	21222
<b>SQL State</b>	QIA11
<b>SQL Code</b>	-1004011L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	Coordinator node is not responding. Check to see if the Coordinator is running
<b>Error 1004012</b>	<b>"INC communication between coordinator and secondary failed due to : %2 %1"</b>
<b>Constant</b>	EMSG_INC_CONN_ERROR
<b>SAP Sybase Error Number</b>	21223
<b>SQL State</b>	QIA12
<b>SQL Code</b>	-1004012L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of exception
<b>Parameter 2</b>	Error message returned from target server
<b>Probable Cause</b>	INC communication failed between coordinator and secondary nodes. The error returned from target node is also displayed. This connection is similar to a client connection.
<b>Error 1004013</b>	<b>"Cannot drop multiplex server %2 as it holds freelist. %1"</b>
<b>Constant</b>	EMSG_MPX_CANNOT_DROP HOLDS_FREELIST
<b>SAP Sybase Error Number</b>	21224

## Errors and Warnings

<b>Error 1004013</b>	<b>"Cannot drop multiplex server %2 as it holds freelist. %1"</b>
<b>SQL State</b>	QDD08
<b>SQL Code</b>	-1004013L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception
<b>Parameter 2</b>	Multiplex Server Name
<b>Probable Cause</b>	If a writer holds a freelist, it cannot be dropped. If the writer can be started, start it. This is because a startup or a clean shutdown will clear the freelist. If the writer cannot be restarted, restart the coordinator with -iqmpx_reclaim-writerfreelist <server name> server switch to force the coordinator to reset the writer freelist.
<b>Error 1004014</b>	<b>"Trying to execute an unknown SQL type over the INC connection"</b>
<b>Constant</b>	EMSG_INC_CONN_UNKNOWN_STMT
<b>SAP Sybase Error Number</b>	20225
<b>SQL State</b>	QIA14
<b>SQL Code</b>	-1004014L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	The node is trying to execute an unknown SQL over the dblib connections
<b>Error 1004015</b>	<b>"Permission denied: Command not allowed on Multiplex %2 servers. %1"</b>
<b>Constant</b>	EMSG_MPX_CMD_PERMISSION_LEVEL_DENIED
<b>SAP Sybase Error Number</b>	21225
<b>SQL State</b>	QIA15

<b>Error 1004015</b>	<b>"Permission denied: Command not allowed on Multiplex %2 servers. %1"</b>
<b>SQL Code</b>	-1004015L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception
<b>Parameter 2</b>	Role of current node
<b>Probable Cause</b>	The command is not permitted on current multiplex node
<b>Warning 1004060</b>	<b>"Warning: Heartbeat frequency should be less than or equal to other timeout periods"</b>
<b>Constant</b>	EMSG_INVALIDHEARTBEATFREQUENCY1
<b>SAP Sybase Error Number</b>	20211
<b>SQL State</b>	01A60
<b>SQL Code</b>	1004060L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>O1</i> on page 2
<b>Probable Cause</b>	The heartbeat frequency should always be less than or equal to other timeout period. This is to make sure that the time lag between the timeout occurring and the time when it is detected is minimal.
<b>Warning 1004061</b>	<b>"Warning: All INC timeout periods should be multiple of Heartbeat frequency"</b>
<b>Constant</b>	EMSG_INVALIDHEARTBEATFREQUENCY2
<b>SAP Sybase Error Number</b>	20213
<b>SQL State</b>	QIA61
<b>SQL Code</b>	1004061L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK

## Errors and Warnings

<b>Warning 1004061</b>	<b>"Warning: All INC timeout periods should be multiple of Heartbeat frequency"</b>
<b>Severity Code</b>	<i>01</i> on page 2
<b>Probable Cause</b>	All the timeout periods of INC(e.g.,AUTOEXCLUDE,LIVENESS,IDLE_CONNECTION) requires to be multiple of the Heartbeat Frequency.
<b>Error 1005000</b>	<b>"Bind parameters are not supported in data flow query processing"</b>
<b>Constant</b>	EMSG_BINDPARAMETERS_UNSUPPORTED
<b>SAP Sybase Error Number</b>	20154
<b>SQL State</b>	QTA00
<b>SQL Code</b>	-1005000L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1005001</b>	<b>"Query has exceeded the supported maximum number of tables that can be joined. %1"</b>
<b>Constant</b>	EMSG_TOO_MANY_TABLES_TO_JOIN
<b>SAP Sybase Error Number</b>	20155
<b>SQL State</b>	QTA01
<b>SQL Code</b>	-1005001L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1005002</b>	<b>"Subquery predicates are not supported in the ON clause of outer joins in this release. %1"</b>
<b>Constant</b>	EMSG_NO_SUBQ_PRED_S_IN_OUTER_JOINS
<b>SAP Sybase Error Number</b>	20156
<b>SQL State</b>	QTA02
<b>SQL Code</b>	-1005002L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1005003</b>	<b>"A maximum of one subquery predicate per conjunct is supported in this release. %1"</b>
<b>Constant</b>	EMSG_ONLY_ONE_SUBQ_PER_CONJUNCT
<b>SAP Sybase Error Number</b>	20157
<b>SQL State</b>	QTA03
<b>SQL Code</b>	-1005003L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1005004</b>	<b>"Subqueries are allowed only as arguments of comparisons, IN, and EXISTS %2, %1"</b>
<b>Constant</b>	EMSG_ILLEGAL_SUBQUERY_USAGE
<b>SAP Sybase Error Number</b>	20158
<b>SQL State</b>	QTA04
<b>SQL Code</b>	-1005004L

## Errors and Warnings

<b>Error 1005004</b>	<b>"Subqueries are allowed only as arguments of comparisons, IN, and EXISTS %2, %1"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	SA code line
<b>Probable Cause</b>	No additional information available.
<b>Error 1005005</b>	<b>"Deleting from views is not supported. %1"</b>
<b>Constant</b>	EMSG_NO_UPDATABLE_VIEWS
<b>SAP Sybase Error Number</b>	20159
<b>SQL State</b>	QTA05
<b>SQL Code</b>	-1005005L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1005006</b>	<b>"The target DELETE table must also appear in FROM. %1"</b>
<b>Constant</b>	EMSG_ILLEGAL_FROMCLAUSE_FOR_DELETE
<b>SAP Sybase Error Number</b>	20160
<b>SQL State</b>	QTA06
<b>SQL Code</b>	-1005006L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception

<b>Error 1005006</b>	<b>"The target DELETE table must also appear in FROM. %1"</b>
<b>Probable Cause</b>	No additional information available.
<b>Error 1005008</b>	<b>"Sybase IQ does not support nested aggregations. %1"</b>
<b>Constant</b>	EMSG_UNSUPPORTEDNESTEDAGG
<b>SAP Sybase Error Number</b>	20162
<b>SQL State</b>	QTA08
<b>SQL Code</b>	-1005008L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1005009</b>	<b>"Cannot perform an aggregate function on a column from a table not declared in the same query. %2, %1"</b>
<b>Constant</b>	EMSG_OUTERSINAGG
<b>SAP Sybase Error Number</b>	20163
<b>SQL State</b>	QTA09
<b>SQL Code</b>	-1005009L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	SQL Commandline line
<b>Probable Cause</b>	No additional information available.
<b>Error 1005010</b>	<b>"The field "%2' is not unique and needs to be qualified, %1"</b>
<b>Constant</b>	EMSG_FIELDNOTUNIQUE
<b>SAP Sybase Error Number</b>	20164

<b>Error 1005010</b>	"The field '%2' is not unique and needs to be qualified, %1"
<b>SQL State</b>	QTA10
<b>SQL Code</b>	-1005010L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

## Messages 1005011 through 1005030

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1005011</b>	"There are two tables named '%2'. Please specify an alias for one of them. %1"
<b>Constant</b>	EMSG_TABLENOTUNIQUE
<b>SAP Sybase Error Number</b>	20165
<b>SQL State</b>	QTA11
<b>SQL Code</b>	-1005011L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	table name which is not unique
<b>Probable Cause</b>	No additional information available.
<b>Error 1005012</b>	"The field '%2' specified in the query cannot be found, %1"
<b>Constant</b>	EMSG_FIELDNOTDEFINED
<b>SAP Sybase Error Number</b>	20166

<b>Error 1005012</b>	<b>"The field '%2' specified in the query cannot be found, %1"</b>
<b>SQL State</b>	QTA12
<b>SQL Code</b>	-1005012L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1005013</b>	<b>"The FROM clause must have at least one table identifier %1"</b>
<b>Constant</b>	EMSG_SEMANTIC_NO_TABLES_IN_FROM_CLAUSE
<b>SAP Sybase Error Number</b>	20167
<b>SQL State</b>	QTA13
<b>SQL Code</b>	-1005013L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1005014</b>	<b>"Non-space text found after ending quote character for an enclosed field. %1"</b>
<b>Constant</b>	EMSG_NONSPACE_AFTER_QUOTE
<b>SAP Sybase Error Number</b>	20168
<b>SQL State</b>	QTA14
<b>SQL Code</b>	-1005014L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1005014</b>	<b>"Non-space text found after ending quote character for an enclosed field. %1"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Non-space text found after ending quote character for an enclosed field.
<b>Error 1005015</b>	<b>"The optimizer was unable to find a query plan that avoided cartesian product joins larger than the Max_Cartesian_Result setting %1"</b>
<b>Constant</b>	EMSG_CARTESION_RESULT_TOO_BIG
<b>SAP Sybase Error Number</b>	20169
<b>SQL State</b>	QTA15
<b>SQL Code</b>	-1005015L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1005016</b>	<b>"Aggregate functions are not allowed in a GROUP BY clause %1"</b>
<b>Constant</b>	EMSG_ILLEGAL_SET_FUNCTION_USAGE
<b>SAP Sybase Error Number</b>	20170
<b>SQL State</b>	QTA16
<b>SQL Code</b>	-1005016L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception

<b>Error 1005016</b>	"Aggregate functions are not allowed in a GROUP BY clause %1"
<b>Probable Cause</b>	No additional information available.
<b>Error 1005017</b>	"You cannot DELETE from a join virtual table. (%2) %1"
<b>Constant</b>	EMSG_CANNOT_DELETE_FROM_JVT
<b>SAP Sybase Error Number</b>	20171
<b>SQL State</b>	QTA17
<b>SQL Code</b>	-1005017L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Tablename
<b>Probable Cause</b>	If this message occurs, it means that the user has tried to DELETE from a join virtual table. This is not permitted.
<b>Error 1005018</b>	"Illegal ORDER BY item %2, %1"
<b>Constant</b>	EMSG_BAD_ORDERBY_ITEM
<b>SAP Sybase Error Number</b>	20989
<b>SQL State</b>	QTA18
<b>SQL Code</b>	-1005018L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	argument
<b>Probable Cause</b>	No additional information available.

## Errors and Warnings

<b>Error 1005019</b>	<b>"The update FROM list must match the table-clause exactly"</b>
<b>Constant</b>	EMSG_BAD_UPDATE_FROM_LIST
<b>SAP Sybase Error Number</b>	21060
<b>SQL State</b>	QTA19
<b>SQL Code</b>	-1005019L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1005020</b>	<b>"Only single-table updates are supported by Sybase IQ"</b>
<b>Constant</b>	EMSG_SINGLE_TABLE_UPDATE_ONLY
<b>SAP Sybase Error Number</b>	21062
<b>SQL State</b>	QTA20
<b>SQL Code</b>	-1005020L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1005021</b>	<b>"Sybase IQ does not allow subqueries in update set-items"</b>
<b>Constant</b>	EMSG_SUBQ_NOT_ALLOWED_IN_SETITEM
<b>SAP Sybase Error Number</b>	21063
<b>SQL State</b>	QTA21
<b>SQL Code</b>	-1005021L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2

<b>Error 1005021</b>	<b>"Sybase IQ does not allow subqueries in update set-items"</b>
<b>Probable Cause</b>	No additional information available.
<b>Error 1005022</b>	<b>"Aggregate not valid in update set-item expression."</b>
<b>Constant</b>	EMSG_AGG_NOT_ALLOWED_IN_SETITEM
<b>SAP Sybase Error Number</b>	21066
<b>SQL State</b>	QTA22
<b>SQL Code</b>	-1005022L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1005023</b>	<b>"Unmatched number of select list items in union"</b>
<b>Constant</b>	EMSG_UNMATCHED_SELECT_LISTS_IN_UNION
<b>SAP Sybase Error Number</b>	21073
<b>SQL State</b>	QTA23
<b>SQL Code</b>	-1005023L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	Cube message here
<b>Error 1005024</b>	<b>"Estimate number: %2 exceed the MAX_CUBE_RESULT of GROUP BY CUBE or ROLLUP %1"</b>
<b>Constant</b>	EMSG_EXCEED_MAX_CUBE_RESULT
<b>SAP Sybase Error Number</b>	21074
<b>SQL State</b>	QTA24
<b>SQL Code</b>	-1005024L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1005024</b>	<b>"Estimate number: %2 exceed the MAX_CUBE_RESULT of GROUP BY CUBE or ROLLUP %1"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location
<b>Parameter 2</b>	the estimated total result of hash base cube
<b>Probable Cause</b>	location of the exception the estimated total result of hash base cube or rollup
<b>Error 1005025</b>	<b>"Query rejected as too complex. After join simplifications there were still %2 tables to be joined, which exceeds the current setting of Max_Join_Enumeration. %1"</b>
<b>Constant</b>	EMSG_JOINS_TOO_COMPLEX
<b>SAP Sybase Error Number</b>	21089
<b>SQL State</b>	QTA25
<b>SQL Code</b>	-1005025L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	the user name specified
<b>Probable Cause</b>	The query will take too long to optimize, so it is being rejected
<b>Error 1005026</b>	<b>"Update not supported on null supplying side of outer join."</b>
<b>Constant</b>	EMSG_UPDATE_NOT_ALLOWED_NULL_OUTER
<b>SAP Sybase Error Number</b>	21090
<b>SQL State</b>	QTA26
<b>SQL Code</b>	-1005026L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1005026</b>	"Update not supported on null supplying side of outer join."
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1005027</b>	<b>"An error occurs during unistring conversion - %2. %1"</b>
<b>Constant</b>	EMSG_UNILIB_ERR
<b>SAP Sybase Error Number</b>	21091
<b>SQL State</b>	QTA27
<b>SQL Code</b>	-1005027L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	the details of unilib error
<b>Probable Cause</b>	No additional information available.
<b>Error 1005028</b>	<b>"Syntax error - %2. %1"</b>
<b>Constant</b>	EMSG_SYNTAX_ERROR
<b>SAP Sybase Error Number</b>	21092
<b>SQL State</b>	QTA28
<b>SQL Code</b>	-1005028L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	the details of syntax error
<b>Probable Cause</b>	No additional information available.

## Errors and Warnings

<b>Error 1005029</b>	" <b>You cannot SELECT from a join virtual table. (%2) %1</b> "
<b>Constant</b>	EMSG_CANNOT_SELECT_FROM_JVT
<b>SAP Sybase Error Number</b>	21143
<b>SQL State</b>	QTA29
<b>SQL Code</b>	-1005029L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	the details of the syntax error
<b>Probable Cause</b>	No additional information available.
<b>Error 1005030</b>	" <b>Query has an ambiguous table reference between prepare and open cursor (%2). %1</b> "
<b>Constant</b>	EMSG_INCONSISTENT_TABLES
<b>SAP Sybase Error Number</b>	21145
<b>SQL State</b>	QTA30
<b>SQL Code</b>	-1005030L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	table name
<b>Probable Cause</b>	SA allows a base and temp table to both have the same table name. In some places, such as when a temp table is created in a stored procedure between the describe and open, IQ can find the base table in the describe and the temp table in the open, giving inconsistent results.

## Messages 1005031 through 1006015

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1005031</b>	"Illegal PARTITION BY item %2, %1"
<b>Constant</b>	EMSG_BAD_PARTITIONBY_ITEM
<b>SAP Sybase Error Number</b>	21217
<b>SQL State</b>	QTA31
<b>SQL Code</b>	-1005031L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column name or ordinal number
<b>Probable Cause</b>	MARKNEW The specified column name or ordinal number is not present within the select list.
<b>Error 1005032</b>	"Conflicting partitioning requirements were detected in UDF '%2' and SQL '%3', %1"
<b>Constant</b>	EMSG_PARTITIONBY_SPECS_CONFLICT
<b>SAP Sybase Error Number</b>	21218
<b>SQL State</b>	QTA32
<b>SQL Code</b>	-1005032L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	specification described by the UDF
<b>Parameter 3</b>	specification contained within SQL select

## Errors and Warnings

<b>Error 1005032</b>	<b>"Conflicting partitioning requirements were detected in UDF '%2' and SQL '%3', %1"</b>
<b>Probable Cause</b>	MARKNEW The partition by specification described by the UDF and contained within the SQL select conflict.
<b>Error 1005033</b>	<b>"Conflicting ordering requirements were detected: %2, %1"</b>
<b>Constant</b>	EMSG_ORDERBY_SPECS_CONFLICT
<b>SAP Sybase Error Number</b>	21219
<b>SQL State</b>	QTA33
<b>SQL Code</b>	-1005033L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	conflict message
<b>Probable Cause</b>	MARKNEW The order by specification described by the UDF and contained within the SQL select conflict.
<b>Error 1005034</b>	<b>"column is not present in the projection list, %1"</b>
<b>Constant</b>	EMSG_COLUMN_NOT_PRESENT_IN_PROJECTION_LIST
<b>SAP Sybase Error Number</b>	21220
<b>SQL State</b>	QTA34
<b>SQL Code</b>	-1005034L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available..

<b>Error 1006000</b>	"IQ Internal error. Please report this to Sybase IQ support. %1"
<b>Constant</b>	EMSG_PROGERROR
<b>SAP Sybase Error Number</b>	20238
<b>SQL State</b>	QBA00
<b>SQL Code</b>	-1006000L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006001</b>	"IQ Internal error. Please report this to Sybase IQ support. %2 %1"
<b>Constant</b>	EMSG_PROGERROR2
<b>SAP Sybase Error Number</b>	20239
<b>SQL State</b>	QBA01
<b>SQL Code</b>	-1006001L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006002</b>	"IQ Internal error. Please report this to Sybase IQ support. %2 %3 %1"
<b>Constant</b>	EMSG_PROGERROR3
<b>SAP Sybase Error Number</b>	20240
<b>SQL State</b>	QBA02

## Errors and Warnings

<b>Error 1006002</b>	"IQ Internal error. Please report this to Sybase IQ support. %2 %3 %1"
<b>SQL Code</b>	-1006002L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Parameter 3</b>	explanation for arg %3 delete if no %3
<b>Probable Cause</b>	No additional information available.
<b>Error 1006003</b>	"IQ Internal error. Please report this to Sybase IQ support. %2 %3 %4 %1"
<b>Constant</b>	EMSG_PROGERRO4
<b>SAP Sybase Error Number</b>	20241
<b>SQL State</b>	QBA03
<b>SQL Code</b>	-1006003L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Parameter 3</b>	explanation for arg %3 delete if no %3
<b>Parameter 4</b>	explanation for arg %4 delete if no %4
<b>Probable Cause</b>	No additional information available.
<b>Error 1006004</b>	"IQ Internal error. Please report this to Sybase IQ support. %2 %3 %4 %5 %1"
<b>Constant</b>	EMSG_PROGERRO5
<b>SAP Sybase Error Number</b>	20242

<b>Error 1006004</b>	"IQ Internal error. Please report this to Sybase IQ support. %2 %3 %4 %5 %1"
<b>SQL State</b>	QBA04
<b>SQL Code</b>	-1006004L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Parameter 3</b>	explanation for arg %3 delete if no %3
<b>Parameter 4</b>	explanation for arg %4 delete if no %4
<b>Parameter 5</b>	explanation for arg %5 delete if no %5
<b>Probable Cause</b>	No additional information available.
<b>Error 1006005</b>	"IQ Internal error. Please report this to Sybase IQ support. %2 %3 %4 %5 %6 %1"
<b>Constant</b>	EMSG_PROGERROR6
<b>SAP Sybase Error Number</b>	20243
<b>SQL State</b>	QBA05
<b>SQL Code</b>	-1006005L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Parameter 3</b>	explanation for arg %3 delete if no %3
<b>Parameter 4</b>	explanation for arg %4 delete if no %4
<b>Parameter 5</b>	explanation for arg %5 delete if no %5
<b>Parameter 6</b>	explanation for arg %6 delete if no %6

## Errors and Warnings

<b>Error 1006005</b>	"IQ Internal error. Please report this to Sybase IQ support. %2 %3 %4 %5 %6 %1"
<b>Probable Cause</b>	No additional information available.
<b>Error 1006006</b>	"IQ Internal error. Please report this to Sybase IQ support. %2 %3 %4 %5 %6 %7 %1"
<b>Constant</b>	EMSG_PROGERROR7
<b>SAP Sybase Error Number</b>	20244
<b>SQL State</b>	QBA06
<b>SQL Code</b>	-1006006L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Parameter 3</b>	explanation for arg %3 delete if no %3
<b>Parameter 4</b>	explanation for arg %4 delete if no %4
<b>Parameter 5</b>	explanation for arg %5 delete if no %5
<b>Parameter 6</b>	explanation for arg %6 delete if no %6
<b>Parameter 7</b>	explanation for arg %7 delete if no %7
<b>Probable Cause</b>	No additional information available.
<b>Error 1006007</b>	"IQ Internal error. Please report this to Sybase IQ support. %2 %3 %4 %5 %6 %7 %8 %1"
<b>Constant</b>	EMSG_PROGERROR8
<b>SAP Sybase Error Number</b>	20245
<b>SQL State</b>	QBA07
<b>SQL Code</b>	-1006007L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1006007</b>	"IQ Internal error. Please report this to Sybase IQ support. %2 %3 %4 %5 %6 %7 %8 %1"
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Parameter 3</b>	explanation for arg %3 delete if no %3
<b>Parameter 4</b>	explanation for arg %4 delete if no %4
<b>Parameter 5</b>	explanation for arg %5 delete if no %5
<b>Parameter 6</b>	explanation for arg %6 delete if no %6
<b>Parameter 7</b>	explanation for arg %7 delete if no %7
<b>Parameter 8</b>	explanation for arg %8 delete if no %8
<b>Probable Cause</b>	No additional information available.
<b>Error 1006008</b>	"IQ Internal error. Please report this to Sybase IQ support. %2 %3 %4 %5 %6 %7 %8 %9 %1"
<b>Constant</b>	EMSG_PROGERROR9
<b>SAP Sybase Error Number</b>	20246
<b>SQL State</b>	QBA08
<b>SQL Code</b>	-1006008L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Parameter 3</b>	explanation for arg %3 delete if no %3
<b>Parameter 4</b>	explanation for arg %4 delete if no %4
<b>Parameter 5</b>	explanation for arg %5 delete if no %5
<b>Parameter 6</b>	explanation for arg %6 delete if no %6
<b>Parameter 7</b>	explanation for arg %7 delete if no %7

## Errors and Warnings

<b>Error 1006008</b>	"IQ Internal error. Please report this to Sybase IQ support. %2 %3 %4 %5 %6 %7 %8 %9 %1"
<b>Parameter 8</b>	explanation for arg %8 delete if no %8
<b>Parameter 9</b>	explanation for arg %9 delete if no %9
<b>Probable Cause</b>	No additional information available.
<b>Error 1006009</b>	<b>"Exception Stack Full %1"</b>
<b>Constant</b>	EMSG_ERRORSTACKFULL
<b>SAP Sybase Error Number</b>	20247
<b>SQL State</b>	QBA09
<b>SQL Code</b>	-1006009L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006010</b>	<b>"No TRY Found %1"</b>
<b>Constant</b>	EMSG_ERRORNOTTRYFOUND
<b>SAP Sybase Error Number</b>	20248
<b>SQL State</b>	QBA10
<b>SQL Code</b>	-1006010L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006011</b>	<b>"No Exception object found"</b>
<b>Constant</b>	EMSG_ERRORTHROWNOEXCEPT

<b>Error 1006011</b>	<b>"No Exception object found"</b>
<b>SAP Sybase Error Number</b>	20249
<b>SQL State</b>	QBA11
<b>SQL Code</b>	-1006011L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006012</b>	<b>"No Top Of Stack Set %1"</b>
<b>Constant</b>	EMSG_ERRORNOTOPOFSTACK
<b>SAP Sybase Error Number</b>	20250
<b>SQL State</b>	QBA12
<b>SQL Code</b>	-1006012L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006013</b>	<b>"Try Stack Corrupt %1"</b>
<b>Constant</b>	EMSG_ERRORTRYSTACKCORRUPT
<b>SAP Sybase Error Number</b>	20251
<b>SQL State</b>	QBA13
<b>SQL Code</b>	-1006013L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception

## Errors and Warnings

<b>Error 1006013</b>	"Try Stack Corrupt %1"
<b>Probable Cause</b>	No additional information available.
<b>Error 1006014</b>	<b>"Object Not Found"</b>
<b>Constant</b>	EMSG_ERRORNOOBJECTFOUND
<b>SAP Sybase Error Number</b>	20252
<b>SQL State</b>	QBA14
<b>SQL Code</b>	-1006014L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006015</b>	<b>"Invalid Object size on stack"</b>
<b>Constant</b>	EMSG_ERRORSTACKOBJSIZE
<b>SAP Sybase Error Number</b>	20253
<b>SQL State</b>	QBA15
<b>SQL Code</b>	-1006015L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.

## Messages 1006016 through 1006035

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1006016</b>	<b>"hdb_sqlcode thrown: "</b>
<b>Constant</b>	EMSG_ERRORHDBSQLCODETHROWN
<b>SAP Sybase Error Number</b>	20254
<b>SQL State</b>	QBA16

<b>Error 1006016</b>	" <b>hdb_sqlcode thrown:</b> "
<b>SQL Code</b>	-1006016L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006017</b>	" <b>Number of REGISTER()/UNREGISTER() calls do not match</b> "
<b>Constant</b>	EMSG_ERRORREGUNREG
<b>SAP Sybase Error Number</b>	20255
<b>SQL State</b>	QBA17
<b>SQL Code</b>	-1006017L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006018</b>	" <b>Exception Stack could not malloc more memory</b> "
<b>Constant</b>	EMSG_ERRORBADMALLOC
<b>SAP Sybase Error Number</b>	20256
<b>SQL State</b>	QBA18
<b>SQL Code</b>	-1006018L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006019</b>	" <b>Exception Stack overflow during grow</b> "
<b>Constant</b>	EMSG_ERRORGROWOVFL

## Errors and Warnings

<b>Error 1006019</b>	<b>"Exception Stack overflow during grow"</b>
<b>SAP Sybase Error Number</b>	20257
<b>SQL State</b>	QBA19
<b>SQL Code</b>	-1006019L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006020</b>	<b>"Group Object Not Found"</b>
<b>Constant</b>	EMSG_ERRORGROUPOBJECTNOTFOUND
<b>SAP Sybase Error Number</b>	20258
<b>SQL State</b>	QBA20
<b>SQL Code</b>	-1006020L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006021</b>	<b>"objects still registered on hos_ObjectStack when -hos_ObjectStack() called"</b>
<b>Constant</b>	EMSG_ERRORSTILLREGISTERED
<b>SAP Sybase Error Number</b>	20259
<b>SQL State</b>	QBA21
<b>SQL Code</b>	-1006021L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006022</b>	"*** Aborting because AbortOnErrorNumber Matched ***"
<b>Constant</b>	EMSG_ERRORTHROW_ABORTONNUMBER
<b>SAP Sybase Error Number</b>	20260
<b>SQL State</b>	QBA22
<b>SQL Code</b>	-1006022L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006023</b>	"*** Aborting because AbortOnErrorFile&Line Matched ***"
<b>Constant</b>	EMSG_ERRORTHROW_ABORTONFILELINE
<b>SAP Sybase Error Number</b>	20261
<b>SQL State</b>	QBA23
<b>SQL Code</b>	-1006023L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006024</b>	"Memory Corruption Found %1"
<b>Constant</b>	EMSG_MEMORY_CORRUPTED
<b>SAP Sybase Error Number</b>	20262
<b>SQL State</b>	QBA24
<b>SQL Code</b>	-1006024L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2

## Errors and Warnings

<b>Error 1006024</b>	<b>"Memory Corruption Found %1"</b>
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006025</b>	<b>"No Shared Memory Manager %1"</b>
<b>Constant</b>	EMSG_MEMORY_NOSHAREDMEMMGR
<b>SAP Sybase Error Number</b>	20263
<b>SQL State</b>	QBA25
<b>SQL Code</b>	-1006025L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006026</b>	<b>"Zero Pointer Passed to hos_free %1"</b>
<b>Constant</b>	EMSG_MEMORY_BADPTR
<b>SAP Sybase Error Number</b>	20264
<b>SQL State</b>	QBA26
<b>SQL Code</b>	-1006026L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006027</b>	<b>"Mark Stack Invalid %1"</b>
<b>Constant</b>	EMSG_MEMORY_INVALIDMARKSTACK
<b>SAP Sybase Error Number</b>	20265

<b>Error 1006027</b>	<b>"Mark Stack Invalid %1"</b>
<b>SQL State</b>	QBA27
<b>SQL Code</b>	-1006027L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006028</b>	<b>"Memory Type Invalid\nFound Object %2. Size %3 Type %4\n\nAllocated from %5 : %6 %1"</b>
<b>Constant</b>	EMSG_MEMORY_BADTYPE
<b>SAP Sybase Error Number</b>	20266
<b>SQL State</b>	QBA28
<b>SQL Code</b>	-1006028L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Parameter 3</b>	explanation for arg %3 delete if no %3
<b>Parameter 4</b>	explanation for arg %4 delete if no %4
<b>Parameter 5</b>	explanation for arg %5 delete if no %5
<b>Parameter 6</b>	explanation for arg %6 delete if no %6
<b>Probable Cause</b>	No additional information available.
<b>Error 1006029</b>	<b>"Memory Manager Leak Found\nCurrent Allocated Memory %2 \nFound object %3 Size %4 Type %5 \nAllocated from %6 : %7 %1 "</b>
<b>Constant</b>	EMSG_MEMORY_LEAK

## Errors and Warnings

<b>Error 1006029</b>	<b>"Memory Manager Leak Found\nCurrent Allocated Memory %2 \nFound object %3 Size %4 Type %5 \nAllocated from %6 : %7 %1 "</b>
<b>SAP Sybase Error Number</b>	20267
<b>SQL State</b>	QBA29
<b>SQL Code</b>	-1006029L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Parameter 3</b>	explanation for arg %3 delete if no %3
<b>Parameter 4</b>	explanation for arg %4 delete if no %4
<b>Parameter 5</b>	explanation for arg %5 delete if no %5
<b>Parameter 6</b>	explanation for arg %6 delete if no %6
<b>Parameter 7</b>	explanation for arg %7 delete if no %7
<b>Probable Cause</b>	No additional information available.
<b>Error 1006030</b>	<b>"Command line error. Invalid command line variable name or value. %1"</b>
<b>Constant</b>	EMSG_CMDERROR
<b>SAP Sybase Error Number</b>	20268
<b>SQL State</b>	QBA30
<b>SQL Code</b>	-1006030L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of failure
<b>Probable Cause</b>	No additional information available.

<b>Error 1006031</b>	"Invalid SQL code %1"
<b>Constant</b>	EMSG_INCORRECT_SQLCODE
<b>SAP Sybase Error Number</b>	20269
<b>SQL State</b>	QBA31
<b>SQL Code</b>	-1006031L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> 4 on page 2
<b>Parameter 1</b>	invalid SQL code
<b>Probable Cause</b>	No additional information available.
<b>Warning 1006032</b>	"\n=n*** File: %1\n\n"
<b>Constant</b>	EMSG_MVION_INFO
<b>SAP Sybase Error Number</b>	20270
<b>SQL State</b>	QBA32
<b>SQL Code</b>	1006032L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> 1 on page 2
<b>Parameter 1</b>	file
<b>Probable Cause</b>	No additional information available.
<b>Warning 1006033</b>	"team id %1 : # threads = %2"
<b>Constant</b>	EMSG_THREAD_TEAM_INFO
<b>SAP Sybase Error Number</b>	20271
<b>SQL State</b>	QBA33
<b>SQL Code</b>	1006033L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Warning 1006033</b>	"team id %1 : # threads = %2"
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	team id
<b>Parameter 2</b>	thread id
<b>Probable Cause</b>	No additional information available.

<b>Error 1006034</b>	<b>No message</b>
<b>Constant</b>	EMSG_MEMORY_LEAK6_EMPTY_SLOT
<b>SAP Sybase Error Number</b>	20272
<b>SQL State</b>	QBA34
<b>SQL Code</b>	-1006034L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006035</b>	<b>No message</b>
<b>Constant</b>	EMSG_MEMORY_LEAKSHORTFORMHDRTRAILER_EMP-TY_SLOT
<b>SAP Sybase Error Number</b>	20273
<b>SQL State</b>	QBA35
<b>SQL Code</b>	-1006035L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	No additional information available.

## 1006036 - 1006238

---

## Messages 1006036 through 1006055

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1006036</b>	<b>No message</b>
<b>Constant</b>	EMSG_MEMORY_LEAKSHORTFORMTRAILER_EMP-TY_SLOT
<b>SAP Sybase Error Number</b>	20274
<b>SQL State</b>	QBA36
<b>SQL Code</b>	-1006036L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006037</b>	<b>No message</b>
<b>Constant</b>	EMSG_MEMORY_LEAKSHORTFORMHDR0_EMPTY_SLOT
<b>SAP Sybase Error Number</b>	20275
<b>SQL State</b>	QBA37
<b>SQL Code</b>	-1006037L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006038</b>	<b>No message</b>
<b>Constant</b>	EMSG_MEMORY_LEAKSHORTFORMHDR1_EMPTY_SLOT
<b>SAP Sybase Error Number</b>	20276
<b>SQL State</b>	QBA38
<b>SQL Code</b>	-1006038L

## Errors and Warnings

<b>Error 1006038</b>	<b>No message</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006039</b>	<b>No message</b>
<b>Constant</b>	EMSG_MEMORY_LEAKSHORTFORMHDR2_EMPTY_SLOT
<b>SAP Sybase Error Number</b>	20277
<b>SQL State</b>	QBA39
<b>SQL Code</b>	-1006039L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006040</b>	<b>No message</b>
<b>Constant</b>	EMSG_MEMORY_LEAKSHORTFORM_EMPTY_SLOT
<b>SAP Sybase Error Number</b>	20278
<b>SQL State</b>	QBA40
<b>SQL Code</b>	-1006040L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006041</b>	<b>"No Mark Pointer Found %1"</b>
<b>Constant</b>	EMSG_MEMORY_NOMARK
<b>SAP Sybase Error Number</b>	20279

<b>Error 1006041</b>	<b>"No Mark Pointer Found %1"</b>
<b>SQL State</b>	QBA41
<b>SQL Code</b>	-1006041L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006042</b>	<b>"All available virtual memory has been used; allocation cancelled: [Extra info: %2] %1"</b>
<b>Constant</b>	EMSG_MEMORY_NOMEMORY
<b>SAP Sybase Error Number</b>	20280
<b>SQL State</b>	QBA42
<b>SQL Code</b>	-1006042L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006043</b>	<b>"No more event handlers %1"</b>
<b>Constant</b>	EMSG_MEMORY_NOMOREEVENTHANDLERS
<b>SAP Sybase Error Number</b>	20281
<b>SQL State</b>	QBA43
<b>SQL Code</b>	-1006043L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 1006043</b>	<b>"No more event handlers %1"</b>
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006044</b>	<b>"No more Mark Stack slots available %1"</b>
<b>Constant</b>	EMSG_MEMORY_NOMOREMARKSTACKSLOTS
<b>SAP Sybase Error Number</b>	20282
<b>SQL State</b>	QBA44
<b>SQL Code</b>	-1006044L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006045</b>	<b>"Not a Vector: delete[] was called on an object that is not a vector %1"</b>
<b>Constant</b>	EMSG_MEMORY_NOTAVECTOR
<b>SAP Sybase Error Number</b>	20283
<b>SQL State</b>	QBA45
<b>SQL Code</b>	-1006045L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1006046</b>	"Is a Vector: delete was called on an object that is a vector; use delete[] %1"
<b>Constant</b>	EMSG_MEMORY_ISAVECTOR
<b>SAP Sybase Error Number</b>	20284
<b>SQL State</b>	QBA46
<b>SQL Code</b>	-1006046L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1006047</b>	"Error Memory Object errnum %2 %1"
<b>Constant</b>	EMSG_MEMORY_DEFAULT
<b>SAP Sybase Error Number</b>	20285
<b>SQL State</b>	QBA47
<b>SQL Code</b>	-1006047L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006048</b>	"hos_memArena: memory corrupt %1"
<b>Constant</b>	EMSG_MEMARENA_CORRUPT
<b>SAP Sybase Error Number</b>	20286
<b>SQL State</b>	QBA48
<b>SQL Code</b>	-1006048L

## Errors and Warnings

<b>Error 1006048</b>	"hos_memArena: memory corrupt %1"
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1006049</b>	"hos_memArena: not all memory returned %1"
<b>Constant</b>	EMSG_MEMARENA_MEMLEAK
<b>SAP Sybase Error Number</b>	20287
<b>SQL State</b>	QBA49
<b>SQL Code</b>	-1006049L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1006050</b>	"hos_memArena: out of memory %1"
<b>Constant</b>	EMSG_MEMARENA_OUTOFMEM
<b>SAP Sybase Error Number</b>	20288
<b>SQL State</b>	QBA50
<b>SQL Code</b>	-1006050L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1006051</b>	<b>"hos_memArena: could not get memory during initialization %1"</b>
<b>Constant</b>	EMSG_MEMARENA_COULDNOTINIT
<b>SAP Sybase Error Number</b>	20289
<b>SQL State</b>	QBA51
<b>SQL Code</b>	-1006051L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1006052</b>	<b>"hos_memArena: unknown error %1"</b>
<b>Constant</b>	EMSG_MEMARENA_DEFAULT
<b>SAP Sybase Error Number</b>	20290
<b>SQL State</b>	QBA52
<b>SQL Code</b>	-1006052L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1006053</b>	<b>"Vector index out of bounds %1"</b>
<b>Constant</b>	EMSG_VECTOR_OUTOFBOUNDS
<b>SAP Sybase Error Number</b>	20291
<b>SQL State</b>	QBA53
<b>SQL Code</b>	-1006053L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1006053</b>	"Vector index out of bounds %1"
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006054</b>	"Error processing hos_vector_exception. _errnum: %2 %1"
<b>Constant</b>	EMSG_VECTOR_DEFAULT
<b>SAP Sybase Error Number</b>	20292
<b>SQL State</b>	QBA54
<b>SQL Code</b>	-1006054L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006055</b>	<b>No message</b>
<b>Constant</b>	EMSG_BIO_FILESTR_EMPTY_SLOT
<b>SAP Sybase Error Number</b>	20293
<b>SQL State</b>	QBA55
<b>SQL Code</b>	-1006055L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.

## **Messages 1006056 through 1006075**

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1006056</b>	<b>"Invalid File Access argument. File: %2 %1"</b>
<b>Constant</b>	EMSG_BIO_BADACCESS
<b>SAP Sybase Error Number</b>	20294
<b>SQL State</b>	QBA56
<b>SQL Code</b>	-1006056L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006057</b>	<b>"Bad seek in Allocate. File: %2 %1"</b>
<b>Constant</b>	EMSG_BIO_BADALLOCATE
<b>SAP Sybase Error Number</b>	20295
<b>SQL State</b>	QBA57
<b>SQL Code</b>	-1006057L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006058</b>	<b>"Partial read on hos_bio object. File: %2 %1"</b>
<b>Constant</b>	EMSG_BIO_PARTBLK

## Errors and Warnings

<b>Error 1006058</b>	"Partial read on hos_bio object. File: %2 %1"
<b>SAP Sybase Error Number</b>	20296
<b>SQL State</b>	QBA58
<b>SQL Code</b>	-1006058L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006059</b>	"An I/O error has occurred on this object. File: %2 %1"
<b>Constant</b>	EMSG_BIO_IOERRORSET
<b>SAP Sybase Error Number</b>	20297
<b>SQL State</b>	QBA59
<b>SQL Code</b>	-1006059L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006060</b>	"Object not open for file %2 %1"
<b>Constant</b>	EMSG_BIO_NOTOPEN
<b>SAP Sybase Error Number</b>	20298
<b>SQL State</b>	QBA60
<b>SQL Code</b>	-1006060L
<b>ODBC 2 State</b>	ERROR

<b>Error 1006060</b>	"Object not open for file %2 %1"
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006061</b>	"Invalid Blocksize %2 %3 %1"
<b>Constant</b>	EMSG_BIO_INVBLKSIZE
<b>SAP Sybase Error Number</b>	20299
<b>SQL State</b>	QBA61
<b>SQL Code</b>	-1006061L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Parameter 3</b>	explanation for arg %3 delete if no %3
<b>Probable Cause</b>	No additional information available.
<b>Error 1006062</b>	"OS error %2 reported on file %3. %1"
<b>Constant</b>	EMSG_BIO_OSERROR
<b>SAP Sybase Error Number</b>	20300
<b>SQL State</b>	QBA62
<b>SQL Code</b>	-1006062L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception

## Errors and Warnings

<b>Error 1006062</b>	"OS error %2 reported on file %3. %1"
<b>Parameter 2</b>	The OS has returned Errno.
<b>Parameter 3</b>	The file on which the error occurred.
<b>Probable Cause</b>	No additional information available.
<b>Error 1006063</b>	"Invalid block %2. File: %3 %1"
<b>Constant</b>	EMSG_BIO_BADBLKNO
<b>SAP Sybase Error Number</b>	20301
<b>SQL State</b>	QBA63
<b>SQL Code</b>	-1006063L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Parameter 3</b>	explanation for arg %3 delete if no %3
<b>Probable Cause</b>	No additional information available.
<b>Error 1006064</b>	<b>No message</b>
<b>Constant</b>	EMSG_BIO_BLKNOTOOBIG_EMPTY_SLOT
<b>SAP Sybase Error Number</b>	20302
<b>SQL State</b>	QBA64
<b>SQL Code</b>	-1006064L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006065</b>	<b>No message</b>
<b>Constant</b>	EMSG_BIO_BLKNOTOOBIG2_EMPTY_SLOT
<b>SAP Sybase Error Number</b>	20303
<b>SQL State</b>	QBA65
<b>SQL Code</b>	-1006065L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006066</b>	<b>"Invalid number of blocks File: %2 %1"</b>
<b>Constant</b>	EMSG_BIO_BADNBLKS
<b>SAP Sybase Error Number</b>	20304
<b>SQL State</b>	QBA66
<b>SQL Code</b>	-1006066L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006067</b>	<b>"Filename does not exist. File: %2 %1"</b>
<b>Constant</b>	EMSG_BIO_NOSUCHOBJECT
<b>SAP Sybase Error Number</b>	20305
<b>SQL State</b>	QBA67
<b>SQL Code</b>	-1006067L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 1006067</b>	"Filename does not exist. File: %2 %1"
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006068</b>	<b>No message</b>
<b>Constant</b>	EMSG_BIO_NOMESSAGE_EMPTY_SLOT
<b>SAP Sybase Error Number</b>	20306
<b>SQL State</b>	QBA68
<b>SQL Code</b>	-1006068L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006069</b>	<b>"No more system record locks available %1"</b>
<b>Constant</b>	EMSG_BIO_NOMORELOCKS
<b>SAP Sybase Error Number</b>	20307
<b>SQL State</b>	QBA69
<b>SQL Code</b>	-1006069L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006070</b>	<b>"Attempt to use object after EOF on file %2 %1"</b>
<b>Constant</b>	EMSG_BIO_IOEOF

<b>Error 1006070</b>	<b>"Attempt to use object after EOF on file %2 %1"</b>
<b>SAP Sybase Error Number</b>	20308
<b>SQL State</b>	QBA70
<b>SQL Code</b>	-1006070L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006071</b>	<b>"Handle must be greater than 0 File: %2 %1"</b>
<b>Constant</b>	EMSG_BIO_INVHANDLE
<b>SAP Sybase Error Number</b>	20309
<b>SQL State</b>	QBA71
<b>SQL Code</b>	-1006071L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006072</b>	<b>"The file is/will be too big. File: %2 %1"</b>
<b>Constant</b>	EMSG_BIO_FILETOOBIG
<b>SAP Sybase Error Number</b>	20310
<b>SQL State</b>	QBA72
<b>SQL Code</b>	-1006072L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1006072</b>	"The file is/will be too big. File: %2 %1"
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006073</b>	"Operation failed, user not owner. File: %2 %1"
<b>Constant</b>	EMSG_BIO_NOTOWNER
<b>SAP Sybase Error Number</b>	20311
<b>SQL State</b>	QBA73
<b>SQL Code</b>	-1006073L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006074</b>	"No such process %2 %1"
<b>Constant</b>	EMSG_BIO_NOSUCHPROCESS
<b>SAP Sybase Error Number</b>	20312
<b>SQL State</b>	QBA74
<b>SQL Code</b>	-1006074L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2

<b>Error 1006074</b>	"No such process %2 %1"
<b>Probable Cause</b>	No additional information available.
<b>Error 1006075</b>	"Operation on file interrupted by user. File: %2 %1"
<b>Constant</b>	EMSG_BIO_INTERRUPT
<b>SAP Sybase Error Number</b>	20313
<b>SQL State</b>	QBA75
<b>SQL Code</b>	-1006075L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

## Messages 1006076 through 1006095

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1006076</b>	"I/O Error on file %2 %1"
<b>Constant</b>	EMSG_BIO_IOERROR
<b>SAP Sybase Error Number</b>	20314
<b>SQL State</b>	QBA76
<b>SQL Code</b>	-1006076L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

## Errors and Warnings

<b>Error 1006077</b>	<b>"No such device or address %2 %1"</b>
<b>Constant</b>	EMSG_BIO_NOSUCHDEVADDR
<b>SAP Sybase Error Number</b>	20315
<b>SQL State</b>	QBA77
<b>SQL Code</b>	-1006077L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006078</b>	<b>"Argument list too big %2 %1"</b>
<b>Constant</b>	EMSG_BIO_ARGTTOBIG
<b>SAP Sybase Error Number</b>	20316
<b>SQL State</b>	QBA78
<b>SQL Code</b>	-1006078L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006079</b>	<b>"Exec format error %2 %1"</b>
<b>Constant</b>	EMSG_BIO_EXECFORMAT
<b>SAP Sybase Error Number</b>	20317
<b>SQL State</b>	QBA79
<b>SQL Code</b>	-1006079L

<b>Error 1006079</b>	"Exec format error %2 %1"
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006080</b>	"Bad file handle passed to OS on file %2 %1"
<b>Constant</b>	EMSG_BIO_BADFILEHANDLE
<b>SAP Sybase Error Number</b>	20318
<b>SQL State</b>	QBA80
<b>SQL Code</b>	-1006080L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006081</b>	"No children %2 %1"
<b>Constant</b>	EMSG_BIO_NOCHILDREN
<b>SAP Sybase Error Number</b>	20319
<b>SQL State</b>	QBA81
<b>SQL Code</b>	-1006081L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception

## Errors and Warnings

<b>Error 1006081</b>	"No children %2 %1"
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006082</b>	"No more processes %2 %1"
<b>Constant</b>	EMSG_BIO_NMOREPROCESSES
<b>SAP Sybase Error Number</b>	20320
<b>SQL State</b>	QBA82
<b>SQL Code</b>	-1006082L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006083</b>	"No more memory %2 %1"
<b>Constant</b>	EMSG_BIO_NMOREMEMORY
<b>SAP Sybase Error Number</b>	20321
<b>SQL State</b>	QBA83
<b>SQL Code</b>	-1006083L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006084</b>	"Operation failed on file due to file permissions. File: %2 %1"
<b>Constant</b>	EMSG_BIO_PERMISSION
<b>SAP Sybase Error Number</b>	20322
<b>SQL State</b>	QBA84
<b>SQL Code</b>	-1006084L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006085</b>	"Bad address %2 %1"
<b>Constant</b>	EMSG_BIO_BADADDRESS
<b>SAP Sybase Error Number</b>	20323
<b>SQL State</b>	QBA85
<b>SQL Code</b>	-1006085L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006086</b>	"File already exists. File: %2 %1"
<b>Constant</b>	EMSG_BIO_FILEEXISTS
<b>SAP Sybase Error Number</b>	20324
<b>SQL State</b>	QBA86

## Errors and Warnings

<b>Error 1006086</b>	<b>"File already exists. File: %2 %1"</b>
<b>SQL Code</b>	-1006086L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006087</b>	<b>"%2 is not a directory %1"</b>
<b>Constant</b>	EMSG_BIO_NOTDIR
<b>SAP Sybase Error Number</b>	20325
<b>SQL State</b>	QBA87
<b>SQL Code</b>	-1006087L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006088</b>	<b>"%2 is a directory %1"</b>
<b>Constant</b>	EMSG_BIO_ISDIR
<b>SAP Sybase Error Number</b>	20326
<b>SQL State</b>	QBA88
<b>SQL Code</b>	-1006088L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2

<b>Error 1006088</b>	"%2 is a directory %1"
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006089</b>	<b>"Invalid Block I/O argument, maybe %2 is a directory, or it exceeds maximum file size limit for the platform, or trying to use Direct IO on unsupported OS %1"</b>
<b>Constant</b>	EMSG_BIO_INVARG
<b>SAP Sybase Error Number</b>	20327
<b>SQL State</b>	QBA89
<b>SQL Code</b>	-1006089L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006090</b>	<b>No message</b>
<b>Constant</b>	EMSG_BIO_INVARG2_EMPTY_SLOT
<b>SAP Sybase Error Number</b>	20328
<b>SQL State</b>	QBA90
<b>SQL Code</b>	-1006090L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	No additional information available.

## Errors and Warnings

<b>Error 1006091</b>	"File table is full %2 %1"
<b>Constant</b>	EMSG_BIO_FILETABLEFULL
<b>SAP Sybase Error Number</b>	20329
<b>SQL State</b>	QBA91
<b>SQL Code</b>	-1006091L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006092</b>	"Too many files %2 %1"
<b>Constant</b>	EMSG_BIO_TOMANYFILES
<b>SAP Sybase Error Number</b>	20330
<b>SQL State</b>	QBA92
<b>SQL Code</b>	-1006092L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006093</b>	"File is too large. File: %2 %1"
<b>Constant</b>	EMSG_BIO_FILETOLARGE
<b>SAP Sybase Error Number</b>	20331
<b>SQL State</b>	QBA93
<b>SQL Code</b>	-1006093L

<b>Error 1006093</b>	"File is too large. File: %2 %1"
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006094</b>	"Disk is or will be full on I/O to or allocation of file %2 %1"
<b>Constant</b>	EMSG_BIO_DISKFULL
<b>SAP Sybase Error Number</b>	20332
<b>SQL State</b>	QBA94
<b>SQL Code</b>	-1006094L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006095</b>	"Read only filesystem on file %2 %1"
<b>Constant</b>	EMSG_BIO_READONLYFS
<b>SAP Sybase Error Number</b>	20333
<b>SQL State</b>	QBA95
<b>SQL Code</b>	-1006095L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception

<b>Error 1006095</b>	"Read only filesystem on file %2 %1"
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

## Messages 1006096 through 1006116

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1006096</b>	"Backup device is busy %2 %1"
<b>Constant</b>	EMSG_IO_DEVICEBUSY
<b>SAP Sybase Error Number</b>	20334
<b>SQL State</b>	QBA96
<b>SQL Code</b>	-1006096L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	file that caused the problem
<b>Probable Cause</b>	No additional information available.

<b>Error 1006097</b>	"The database is locked by another user File: "
<b>Constant</b>	EMSG_BIO_FILELOCKED
<b>SAP Sybase Error Number</b>	20335
<b>SQL State</b>	QBA97
<b>SQL Code</b>	-1006097L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006098</b>	<b>"Blockmap Bufman For "</b>
<b>Constant</b>	EMSG_BUFCMAN_BMID
<b>SAP Sybase Error Number</b>	20336
<b>SQL State</b>	QBA98
<b>SQL Code</b>	-1006098L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006099</b>	<b>"Shared Bufman For "</b>
<b>Constant</b>	EMSG_BUFCMAN_SHRBUFCMANID
<b>SAP Sybase Error Number</b>	20337
<b>SQL State</b>	QBA99
<b>SQL Code</b>	-1006099L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006100</b>	<b>"Shared Temp Bufman For "</b>
<b>Constant</b>	EMSG_BUFCMAN_SHRTEMPCMANID
<b>SAP Sybase Error Number</b>	20338
<b>SQL State</b>	QBB00
<b>SQL Code</b>	-1006100L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.

## Errors and Warnings

<b>Error 1006101</b>	"Buffer too small %1"
<b>Constant</b>	EMSG_CMPRS_BUFFTOOSMALL
<b>SAP Sybase Error Number</b>	20339
<b>SQL State</b>	QBB01
<b>SQL Code</b>	-1006101L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006102</b>	"Unknown error"
<b>Constant</b>	EMSG_LZSTACK_UNKNOWN
<b>SAP Sybase Error Number</b>	20340
<b>SQL State</b>	QBB02
<b>SQL Code</b>	-1006102L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006103</b>	"Stack underflow during expansion"
<b>Constant</b>	EMSG_LZSTACK_UNDERFLOW
<b>SAP Sybase Error Number</b>	20341
<b>SQL State</b>	QBB03
<b>SQL Code</b>	-1006103L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2

<b>Error 1006103</b>	"Stack underflow during expansion"
<b>Probable Cause</b>	No additional information available.
<b>Error 1006104</b>	"Stack overflow during expansion"
<b>Constant</b>	EMSG_LZSTACK_OVERFLOW
<b>SAP Sybase Error Number</b>	20342
<b>SQL State</b>	QBB04
<b>SQL Code</b>	-1006104L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006106</b>	"Invalid file path: %2 %1"
<b>Constant</b>	EMSG_FN_BAD_PATH
<b>SAP Sybase Error Number</b>	20344
<b>SQL State</b>	QBB06
<b>SQL Code</b>	-1006106L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006107</b>	"Invalid disk name: %2 %1"
<b>Constant</b>	EMSG_FN_BAD_DISK
<b>SAP Sybase Error Number</b>	20345
<b>SQL State</b>	QBB07

## Errors and Warnings

<b>Error 1006107</b>	" <b>Invalid disk name: %2 %1</b> "
<b>SQL Code</b>	-1006107L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006108</b>	" <b>Invalid directory name(s): %2 %1</b> "
<b>Constant</b>	EMSG_FN_BAD_DIRS
<b>SAP Sybase Error Number</b>	20346
<b>SQL State</b>	QBB08
<b>SQL Code</b>	-1006108L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006109</b>	" <b>Invalid file name: %2 %1</b> "
<b>Constant</b>	EMSG_FN_BAD_NAME
<b>SAP Sybase Error Number</b>	20347
<b>SQL State</b>	QBB09
<b>SQL Code</b>	-1006109L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2

<b>Error 1006109</b>	" <b>Invalid file name: %2 %1</b> "
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006110</b>	" <b>Invalid file extension : %2 %1</b> "
<b>Constant</b>	EMSG_FN_BAD_EXT
<b>SAP Sybase Error Number</b>	20348
<b>SQL State</b>	QBB10
<b>SQL Code</b>	-1006110L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006111</b>	" <b>Invalid file version : %2 %1</b> "
<b>Constant</b>	EMSG_FN_BAD_VERS
<b>SAP Sybase Error Number</b>	20349
<b>SQL State</b>	QBB11
<b>SQL Code</b>	-1006111L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

## Errors and Warnings

<b>Error 1006112</b>	"Unknown file error : %2 %1"
<b>Constant</b>	EMSG_FN_UNKNOWN
<b>SAP Sybase Error Number</b>	20350
<b>SQL State</b>	QBB12
<b>SQL Code</b>	-1006112L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006113</b>	"Unknown error %1"
<b>Constant</b>	EMSG_BITVEC_UNKNOWN
<b>SAP Sybase Error Number</b>	20351
<b>SQL State</b>	QBB13
<b>SQL Code</b>	-1006113L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006114</b>	"Operation on two hos_bitvec objects that are not the same size %1"
<b>Constant</b>	EMSG_BITVEC_SIZEERROR
<b>SAP Sybase Error Number</b>	20352
<b>SQL State</b>	QBB14
<b>SQL Code</b>	-1006114L

<b>Error 1006114</b>	<b>"Operation on two hos_bitvec objects that are not the same size %1"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006115</b>	<b>"Operation on hos_bitvec object is out of range. %1"</b>
<b>Constant</b>	EMSG_BITVEC_INDEXERROR
<b>SAP Sybase Error Number</b>	20353
<b>SQL State</b>	QBB15
<b>SQL Code</b>	-1006115L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006116</b>	<b>"Attempting to set/unset an already set/unset bit. %1"</b>
<b>Constant</b>	EMSG_BITVEC_SETERROR
<b>SAP Sybase Error Number</b>	20354
<b>SQL State</b>	QBB16
<b>SQL Code</b>	-1006116L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

**Messages 1006117 through 1006137**

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1006117</b>	"Record Size Invalid"
<b>Constant</b>	EMSG_OS_SORT_INVALIDRECSIZE
<b>SAP Sybase Error Number</b>	20355
<b>SQL State</b>	QBB17
<b>SQL Code</b>	-1006117L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006118</b>	"This class does not support multiple instances"
<b>Constant</b>	EMSG_SORT_MULTIPLEINSTANCES
<b>SAP Sybase Error Number</b>	20356
<b>SQL State</b>	QBB18
<b>SQL Code</b>	-1006118L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006119</b>	"SORT Error: %s"
<b>Constant</b>	EMSG_SORT_COSORTERROR
<b>SAP Sybase Error Number</b>	20357
<b>SQL State</b>	QBB19
<b>SQL Code</b>	-1006119L
<b>ODBC 2 State</b>	ERROR

<b>Error 1006119</b>	"SORT Error: %s"
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006120</b>	<b>"The operation has been cancelled - Max_Query_Time exceeded"</b>
<b>Constant</b>	EMSG_ATTN_OUTOFTIME
<b>SAP Sybase Error Number</b>	20358
<b>SQL State</b>	QBB20
<b>SQL Code</b>	-1006120L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006121</b>	<b>"Unknown error message"</b>
<b>Constant</b>	EMSG_SORT_UNKNOWN
<b>SAP Sybase Error Number</b>	20359
<b>SQL State</b>	QBB21
<b>SQL Code</b>	-1006121L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006123</b>	<b>"Attempt to add an invalid extent %1"</b>
<b>Constant</b>	EMSG_MVBIO_EXTENTSIZE
<b>SAP Sybase Error Number</b>	20361
<b>SQL State</b>	QBB23

## Errors and Warnings

<b>Error 1006123</b>	<b>"Attempt to add an invalid extent %1"</b>
<b>SQL Code</b>	-1006123L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1006124</b>	<b>"Attempt to operate on object before being opened %1"</b>
<b>Constant</b>	EMSG_MVBIO_NOTOPEN
<b>SAP Sybase Error Number</b>	20362
<b>SQL State</b>	QBB24
<b>SQL Code</b>	-1006124L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1006125</b>	<b>"Bad block number %2 passed to object %1"</b>
<b>Constant</b>	EMSG_MVBIO_BADBLK
<b>SAP Sybase Error Number</b>	20363
<b>SQL State</b>	QBB25
<b>SQL Code</b>	-1006125L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) bad block number

<b>Error 1006125</b>	<b>"Bad block number %2 passed to object %1"</b>
<b>Probable Cause</b>	No additional information available.
<b>Error 1006126</b>	<b>"The File access and MV BIO access do not match %1"</b>
<b>Constant</b>	EMSG_MVBIO_BADACCESS
<b>SAP Sybase Error Number</b>	20364
<b>SQL State</b>	QBB26
<b>SQL Code</b>	-1006126L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006127</b>	<b>"The File is out of space. File: %2 %1"</b>
<b>Constant</b>	EMSG_MVBIO_DBFULL
<b>SAP Sybase Error Number</b>	20365
<b>SQL State</b>	QBB27
<b>SQL Code</b>	-1006127L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006128</b>	<b>"Invalid File Access argument. %1"</b>
<b>Constant</b>	EMSG_IO_BADACCESS
<b>SAP Sybase Error Number</b>	20366

## Errors and Warnings

<b>Error 1006128</b>	"Invalid File Access argument. %1"
<b>SQL State</b>	QBB28
<b>SQL Code</b>	-1006128L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006129</b>	"An I/O error has occurred on this object."
<b>Constant</b>	EMSG_IO_IOERRORSET
<b>SAP Sybase Error Number</b>	20367
<b>SQL State</b>	QBB29
<b>SQL Code</b>	-1006129L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006130</b>	"Object not open for file %2 %1"
<b>Constant</b>	EMSG_IO_NOTOPEN
<b>SAP Sybase Error Number</b>	20368
<b>SQL State</b>	QBB30
<b>SQL Code</b>	-1006130L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	file that could not be opened.

<b>Error 1006130</b>	"Object not open for file %2 %1"
<b>Probable Cause</b>	Unable to open file.
<b>Error 1006131</b>	"OS error reported on file: %2 . OS error: %3 %1"
<b>Constant</b>	EMSG_IO_OSERROR
<b>SAP Sybase Error Number</b>	20369
<b>SQL State</b>	QBB31
<b>SQL Code</b>	-1006131L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	file that reports error
<b>Parameter 3</b>	system error IO operation reported (errno)
<b>Probable Cause</b>	No additional information available.
<b>Error 1006132</b>	". OS error: "
<b>Constant</b>	EMSG_IO_OSERROR2_NOT_USED
<b>SAP Sybase Error Number</b>	20370
<b>SQL State</b>	QBB32
<b>SQL Code</b>	-1006132L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006133</b>	"File does not exist. File: %2 %1"
<b>Constant</b>	EMSG_IO_NOSUCHOBJECT
<b>SAP Sybase Error Number</b>	20371

## Errors and Warnings

<b>Error 1006133</b>	<b>"File does not exist. File: %2 %1"</b>
<b>SQL State</b>	QBB33
<b>SQL Code</b>	-1006133L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	file that does not exist
<b>Probable Cause</b>	No additional information available.
<b>Error 1006134</b>	<b>"Invalid filename: %2. '::' is not allowed in the filename for this statement. %1"</b>
<b>Constant</b>	EMSG_IO_INVALID_FILE
<b>SAP Sybase Error Number</b>	20372
<b>SQL State</b>	QBB34
<b>SQL Code</b>	-1006134L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	File or device name that is invalid.
<b>Probable Cause</b>	A "::" (colon-colon) is not allowed in the filename by Sybase IQ for the statement being executed."
<b>Error 1006135</b>	<b>"Attempt to use object after EOF on file %2 %1"</b>
<b>Constant</b>	EMSG_IO_IOEOF
<b>SAP Sybase Error Number</b>	20373
<b>SQL State</b>	QBB35
<b>SQL Code</b>	-1006135L

<b>Error 1006135</b>	<b>"Attempt to use object after EOF on file %2 %1"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	file we have read past EOF on
<b>Probable Cause</b>	No additional information available.
<b>Error 1006136</b>	<b>"The file is/will be too big "</b>
<b>Constant</b>	EMSG_IO_FILETOOBIG
<b>SAP Sybase Error Number</b>	20374
<b>SQL State</b>	QBB36
<b>SQL Code</b>	-1006136L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006137</b>	<b>"Operation failed on file, user not owner. File: %2 %1"</b>
<b>Constant</b>	EMSG_IO_NOTOWNER
<b>SAP Sybase Error Number</b>	20375
<b>SQL State</b>	QBB37
<b>SQL Code</b>	-1006137L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	file that cannot be accessed
<b>Probable Cause</b>	No additional information available.

**Messages 1006138 through 1006157**

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1006138</b>	" <b>No such process %2 %1</b> "
<b>Constant</b>	EMSG_IO_NOSUCHPROCESS
<b>SAP Sybase Error Number</b>	20376
<b>SQL State</b>	QBB38
<b>SQL Code</b>	-1006138L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006139</b>	" <b>Operation on file interrupted by user. File: %2 %1</b> "
<b>Constant</b>	EMSG_IO_INTERRUPT
<b>SAP Sybase Error Number</b>	20377
<b>SQL State</b>	QBB39
<b>SQL Code</b>	-1006139L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	file being used when the interrupt occurred
<b>Probable Cause</b>	No additional information available.

<b>Error 1006140</b>	" <b>I/O Error on file %2 %1</b> "
<b>Constant</b>	EMSG_IO_IOERROR

<b>Error 1006140</b>	"I/O Error on file %2 %1"
<b>SAP Sybase Error Number</b>	20378
<b>SQL State</b>	QBB40
<b>SQL Code</b>	-1006140L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	file the I/O operation failed on
<b>Probable Cause</b>	No additional information available.

<b>Error 1006141</b>	"No such device or address %2 %1"
<b>Constant</b>	EMSG_IO_NOSUCHDEVADDR
<b>SAP Sybase Error Number</b>	20379
<b>SQL State</b>	QBB41
<b>SQL Code</b>	-1006141L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006142</b>	"Argument list too big %2 %1"
<b>Constant</b>	EMSG_IO_ARGTTOBIG
<b>SAP Sybase Error Number</b>	20380
<b>SQL State</b>	QBB42
<b>SQL Code</b>	-1006142L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1006142</b>	"Argument list too big %2 %1"
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	file the I/O operation failed on
<b>Probable Cause</b>	No additional information available.
<b>Error 1006143</b>	"Exec format error %2 %1"
<b>Constant</b>	EMSG_IO_EXECFORMAT
<b>SAP Sybase Error Number</b>	20381
<b>SQL State</b>	QBB43
<b>SQL Code</b>	-1006143L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006144</b>	"Bad file handle passed to OS on file %2 %1"
<b>Constant</b>	EMSG_IO_BADFILEHANDLE
<b>SAP Sybase Error Number</b>	20382
<b>SQL State</b>	QBB44
<b>SQL Code</b>	-1006144L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2

<b>Error 1006144</b>	<b>"Bad file handle passed to OS on file %2 %1"</b>
<b>Probable Cause</b>	No additional information available.
<b>Error 1006145</b>	<b>"No children %2 %1"</b>
<b>Constant</b>	EMSG_IO_NOCHILDREN
<b>SAP Sybase Error Number</b>	20383
<b>SQL State</b>	QBB45
<b>SQL Code</b>	-1006145L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006146</b>	<b>"No more processes %2 %1"</b>
<b>Constant</b>	EMSG_IO_NOMOREPROCESSES
<b>SAP Sybase Error Number</b>	20384
<b>SQL State</b>	QBB46
<b>SQL Code</b>	-1006146L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006147</b>	<b>"No more memory %2 %1 "</b>
<b>Constant</b>	EMSG_IO_NOMOREMEMORY

## Errors and Warnings

<b>Error 1006147</b>	"No more memory %2 %1 "
<b>SAP Sybase Error Number</b>	20385
<b>SQL State</b>	QBB47
<b>SQL Code</b>	-1006147L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006148</b>	"Operation failed on file due to file permissions. File: %2 %1"
<b>Constant</b>	EMSG_IO_PERMISSION
<b>SAP Sybase Error Number</b>	20386
<b>SQL State</b>	QBB48
<b>SQL Code</b>	-1006148L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	file that the operation failed on.
<b>Probable Cause</b>	No additional information available.
<b>Error 1006149</b>	"Bad address %2 %1"
<b>Constant</b>	EMSG_IO_BADADDRESS
<b>SAP Sybase Error Number</b>	20387
<b>SQL State</b>	QBB49
<b>SQL Code</b>	-1006149L

<b>Error 1006149</b>	"Bad address %2 %1"
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006150</b>	"File already exists. File: %2 %1"
<b>Constant</b>	EMSG_IO_FILEEXISTS
<b>SAP Sybase Error Number</b>	20388
<b>SQL State</b>	QBB50
<b>SQL Code</b>	-1006150L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006151</b>	"%2 is not a directory %1"
<b>Constant</b>	EMSG_IO_NOTDIR
<b>SAP Sybase Error Number</b>	20389
<b>SQL State</b>	QBB51
<b>SQL Code</b>	-1006151L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception

## Errors and Warnings

<b>Error 1006151</b>	"%2 is not a directory %1"
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006152</b>	"%2'is a directory %1"
<b>Constant</b>	EMSG_IO_ISDIR
<b>SAP Sybase Error Number</b>	20390
<b>SQL State</b>	QBB52
<b>SQL Code</b>	-1006152L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006153</b>	<b>"Invalid stream I/O argument, maybe %2 is a directory, or it contains more than 2,147,483,647 bytes, %1"</b>
<b>Constant</b>	EMSG_IO_INVARG
<b>SAP Sybase Error Number</b>	20391
<b>SQL State</b>	QBB53
<b>SQL Code</b>	-1006153L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006154</b>	"Perhaps the device (%2) is not in variable block mode? %1"
<b>Constant</b>	EMSG_IO_NOTVARBLOCKMODE
<b>SAP Sybase Error Number</b>	20392
<b>SQL State</b>	QBB54
<b>SQL Code</b>	-1006154L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006155</b>	"File table is full %2 %1"
<b>Constant</b>	EMSG_IO_FILETABLEFULL
<b>SAP Sybase Error Number</b>	20393
<b>SQL State</b>	QBB55
<b>SQL Code</b>	-1006155L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006156</b>	"Too many files %2 %1"
<b>Constant</b>	EMSG_IO_TOMANYFILES
<b>SAP Sybase Error Number</b>	20394
<b>SQL State</b>	QBB56

## Errors and Warnings

<b>Error 1006156</b>	"Too many files %2 %1"
<b>SQL Code</b>	-1006156L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006157</b>	"File is too large. File: %2 %1"
<b>Constant</b>	EMSG_IO_FILETOLARGE
<b>SAP Sybase Error Number</b>	20395
<b>SQL State</b>	QBB57
<b>SQL Code</b>	-1006157L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

## Messages 1006158 through 1006177

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1006158</b>	"Disk is full on I/O to file %2 %1"
<b>Constant</b>	EMSG_IO_DISKFULL
<b>SAP Sybase Error Number</b>	20396
<b>SQL State</b>	QBB58
<b>SQL Code</b>	-1006158L

<b>Error 1006158</b>	"Disk is full on I/O to file %2 %1"
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	file that grew to fill the disk.
<b>Probable Cause</b>	No additional information available.

<b>Error 1006159</b>	"Read only filesystem on file %2 %1"
<b>Constant</b>	EMSG_IO_READONLYFS
<b>SAP Sybase Error Number</b>	20397
<b>SQL State</b>	QBB59
<b>SQL Code</b>	-1006159L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	file invalid operation was tried on
<b>Probable Cause</b>	No additional information available.

<b>Error 1006160</b>	"Bad tape blocksize %2 %1"
<b>Constant</b>	EMSG_IO_BADBLOCKSIZE
<b>SAP Sybase Error Number</b>	20398
<b>SQL State</b>	QBB60
<b>SQL Code</b>	-1006160L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception

## Errors and Warnings

<b>Error 1006160</b>	"Bad tape blocksize %2 %1"
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006161</b>	"Operation Canceled %2 %1"
<b>Constant</b>	EMSG_IO_OPCANCELED
<b>SAP Sybase Error Number</b>	20399
<b>SQL State</b>	QBB61
<b>SQL Code</b>	-1006161L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	file that had an I/O operation cancelled
<b>Probable Cause</b>	No additional information available.
<b>Error 1006162</b>	"Tape IO Error %2 %1 "
<b>Constant</b>	EMSG_IO_TAPEIOERROR
<b>SAP Sybase Error Number</b>	20400
<b>SQL State</b>	QBB62
<b>SQL Code</b>	-1006162L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006163</b>	"Operating system error : %2 %1"
<b>Constant</b>	EMSG_LS_OSERROR
<b>SAP Sybase Error Number</b>	20401
<b>SQL State</b>	QBB63
<b>SQL Code</b>	-1006163L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006164</b>	"The text in the DateString for Day is not a valid number. Day: "
<b>Constant</b>	EMSG_DATE_FORMATSTRINGDAY
<b>SAP Sybase Error Number</b>	20402
<b>SQL State</b>	QBB64
<b>SQL Code</b>	-1006164L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006165</b>	"The text in the DateString for Month is not a valid number. Month: "
<b>Constant</b>	EMSG_DATE_FORMATSTRINGMONTH
<b>SAP Sybase Error Number</b>	20403
<b>SQL State</b>	QBB65
<b>SQL Code</b>	-1006165L

## Errors and Warnings

<b>Error 1006165</b>	"The text in the DateString for Month is not a valid number. Month: "
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006166</b>	"The text in the DateString for Year is not a valid number. Year: "
<b>Constant</b>	EMSG_DATE_FORMATSTRINGYEAR
<b>SAP Sybase Error Number</b>	20404
<b>SQL State</b>	QBB66
<b>SQL Code</b>	-1006166L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006167</b>	"DateTime is invalid (%2) %1"
<b>Constant</b>	EMSG_DATE_INVALIDDATETIME
<b>SAP Sybase Error Number</b>	20405
<b>SQL State</b>	QBB67
<b>SQL Code</b>	-1006167L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006168</b>	<b>"Date is invalid (%2) %1"</b>
<b>Constant</b>	EMSG_DATE_INVALIDDATE
<b>SAP Sybase Error Number</b>	20406
<b>SQL State</b>	QBB68
<b>SQL Code</b>	-1006168L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006169</b>	<b>"Time is invalid (%2) %1"</b>
<b>Constant</b>	EMSG_DATE_INVALIDTIME
<b>SAP Sybase Error Number</b>	20407
<b>SQL State</b>	QBB69
<b>SQL Code</b>	-1006169L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006170</b>	<b>"Date is invalid because of the year (%2) %1"</b>
<b>Constant</b>	EMSG_DATE_INVALIDYEAR
<b>SAP Sybase Error Number</b>	20408
<b>SQL State</b>	QBB70
<b>SQL Code</b>	-1006170L

## Errors and Warnings

<b>Error 1006170</b>	"Date is invalid because of the year (%2) %1"
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006171</b>	"Date is invalid because of the day of the year (%2) %1"
<b>Constant</b>	EMSG_DATE_INVALIDJDAY
<b>SAP Sybase Error Number</b>	20409
<b>SQL State</b>	QBB71
<b>SQL Code</b>	-1006171L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006172</b>	"Date is invalid because of the Month (%2) %1"
<b>Constant</b>	EMSG_DATE_INVALIDMONTH
<b>SAP Sybase Error Number</b>	20410
<b>SQL State</b>	QBB72
<b>SQL Code</b>	-1006172L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception

<b>Error 1006172</b>	<b>"Date is invalid because of the Month (%2) %1"</b>
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006173</b>	<b>"Date is invalid because of the day the Month (%2) %1"</b>
<b>Constant</b>	EMSG_DATE_INVALIDMDAY
<b>SAP Sybase Error Number</b>	20411
<b>SQL State</b>	QBB73
<b>SQL Code</b>	-1006173L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006174</b>	<b>"Date is invalid (Year:%2 Month:%3 Day:%4) %1"</b>
<b>Constant</b>	EMSG_DATE_INVALIDYMD
<b>SAP Sybase Error Number</b>	20412
<b>SQL State</b>	QBB74
<b>SQL Code</b>	-1006174L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Parameter 3</b>	explanation for arg %3 delete if no %3
<b>Parameter 4</b>	explanation for arg %4 delete if no %4
<b>Probable Cause</b>	No additional information available.

## Errors and Warnings

<b>Error 1006175</b>	"Time is invalid (Hour:%2 Minute:%3 Second:%4 MicroSecond:%5) %1"
<b>Constant</b>	EMSG_DATE_INVALIDHMS
<b>SAP Sybase Error Number</b>	20413
<b>SQL State</b>	QBB75
<b>SQL Code</b>	-1006175L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Parameter 3</b>	explanation for arg %3 delete if no %3
<b>Parameter 4</b>	explanation for arg %4 delete if no %4
<b>Parameter 5</b>	explanation for arg %5 delete if no %5
<b>Probable Cause</b>	No additional information available.

<b>Error 1006176</b>	<b>No message</b>
<b>Constant</b>	EMSG_DATE_INVALIDDAYS_EMPTY_SLOT
<b>SAP Sybase Error Number</b>	20414
<b>SQL State</b>	QBB76
<b>SQL Code</b>	-1006176L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006177</b>	<b>"Time is invalid because of the MicroSeconds (%2) %1"</b>
<b>Constant</b>	EMSG_DATE_INVALIDUSECONDS
<b>SAP Sybase Error Number</b>	20415

<b>Error 1006177</b>	<b>"Time is invalid because of the MicroSeconds (%2) %1"</b>
<b>SQL State</b>	QBB77
<b>SQL Code</b>	-1006177L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

## Messages 1006178 through 1006197

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1006178</b>	<b>"DateTime is invalid because of the MicroSeconds from 1/1/0000 (%2) %1"</b>
<b>Constant</b>	EMSG_DATE_INVALIDUSECONDSBOE
<b>SAP Sybase Error Number</b>	20416
<b>SQL State</b>	QBB78
<b>SQL Code</b>	-1006178L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006179</b>	<b>"Cannot allocate space for CS context %1 "</b>
<b>Constant</b>	EMSG_DATE_INVALIDDCSCONTEXTALLOC
<b>SAP Sybase Error Number</b>	20417

## Errors and Warnings

<b>Error 1006179</b>	<b>"Cannot allocate space for CS context %1 "</b>
<b>SQL State</b>	QBB79
<b>SQL Code</b>	-1006179L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006180</b>	<b>"Cannot allocate space for CS locale %1 "</b>
<b>Constant</b>	EMSG_DATE_INVALIDCSLOCALEALLOC
<b>SAP Sybase Error Number</b>	20418
<b>SQL State</b>	QBB80
<b>SQL Code</b>	-1006180L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006181</b>	<b>"Cannot set CS locale %1 "</b>
<b>Constant</b>	EMSG_DATE_INVALIDCSLOCALE
<b>SAP Sybase Error Number</b>	20419
<b>SQL State</b>	QBB81
<b>SQL Code</b>	-1006181L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception

<b>Error 1006181</b>	<b>"Cannot set CS locale %1 "</b>
<b>Probable Cause</b>	No additional information available.
<b>Error 1006182</b>	<b>"Cannot configure CS context %1 "</b>
<b>Constant</b>	EMSG_DATE_INVALIDDCS CONFIG
<b>SAP Sybase Error Number</b>	20420
<b>SQL State</b>	QBB82
<b>SQL Code</b>	-1006182L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006183</b>	<b>"Raw device is not open %1"</b>
<b>Constant</b>	EMSG_RAWIO_NO_FD
<b>SAP Sybase Error Number</b>	20421
<b>SQL State</b>	QBB83
<b>SQL Code</b>	-1006183L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006184</b>	<b>"Unable to query raw device %1"</b>
<b>Constant</b>	EMSG_RAWIO_BAD_IOCTL
<b>SAP Sybase Error Number</b>	20422
<b>SQL State</b>	QBB84

## Errors and Warnings

<b>Error 1006184</b>	<b>"Unable to query raw device %1"</b>
<b>SQL Code</b>	-1006184L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006185</b>	<b>"Unsupported raw device type %1"</b>
<b>Constant</b>	EMSG_RAWIO_UNSUPP
<b>SAP Sybase Error Number</b>	20423
<b>SQL State</b>	QBB85
<b>SQL Code</b>	-1006185L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006186</b>	<b>"Program error on raw device %1"</b>
<b>Constant</b>	EMSG_RAWIO_PROGERROR
<b>SAP Sybase Error Number</b>	20424
<b>SQL State</b>	QBB86
<b>SQL Code</b>	-1006186L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1006187</b>	<b>"OS error was found on a lock (mutex,condvar,etc) Call: error = %2 %1"</b>
<b>Constant</b>	EMSG_LOCK_OSERROR
<b>SAP Sybase Error Number</b>	20425
<b>SQL State</b>	QBB87
<b>SQL Code</b>	-1006187L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006188</b>	<b>"USEAGE error was found on a lock (mutex,condvar,etc) Call %1"</b>
<b>Constant</b>	EMSG_LOCK_USEERROR
<b>SAP Sybase Error Number</b>	20426
<b>SQL State</b>	QBB88
<b>SQL Code</b>	-1006188L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006189</b>	<b>"The condition variable was killed %1"</b>
<b>Constant</b>	EMSG_LOCK_KILLED
<b>SAP Sybase Error Number</b>	20427
<b>SQL State</b>	QBB89

## Errors and Warnings

<b>Error 1006189</b>	<b>"The condition variable was killed %1"</b>
<b>SQL Code</b>	-1006189L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1006190</b>	<b>"The semaphore variable was canceled %1"</b>
<b>Constant</b>	EMSG_SEMA_KILLED
<b>SAP Sybase Error Number</b>	20428
<b>SQL State</b>	QBB90
<b>SQL Code</b>	-1006190L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1006191</b>	<b>"Unknown error was found on a lock (mutex,condvar,etc) Call %1"</b>
<b>Constant</b>	EMSG_LOCK_DEFAULT
<b>SAP Sybase Error Number</b>	20429
<b>SQL State</b>	QBB91
<b>SQL Code</b>	-1006191L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception

<b>Error 1006191</b>	"Unknown error was found on a lock (mutex,condvar,etc) Call %1"
<b>Probable Cause</b>	No additional information available.
<b>Error 1006192</b>	"OS error was found on Thread Call: error = %2, %1"
<b>Constant</b>	EMSG_THREAD_OSERROR
<b>SAP Sybase Error Number</b>	20430
<b>SQL State</b>	QBB92
<b>SQL Code</b>	-1006192L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006193</b>	"Unknown error was found on Thread Call %1"
<b>Constant</b>	EMSG_THREAD_DEFAULT
<b>SAP Sybase Error Number</b>	20431
<b>SQL State</b>	QBB93
<b>SQL Code</b>	-1006193L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006194</b>	"Could not get a thread %1"
<b>Constant</b>	EMSG_THREAD_COULDNT_GET_THREAD
<b>SAP Sybase Error Number</b>	20432

## Errors and Warnings

<b>Error 1006194</b>	<b>"Could not get a thread %1"</b>
<b>SQL State</b>	QBB94
<b>SQL Code</b>	-1006194L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006195</b>	<b>"OS error was found on hos_threadman Call: error = %2 %1"</b>
<b>Constant</b>	EMSG_THREADMAN_OSERROR
<b>SAP Sybase Error Number</b>	20433
<b>SQL State</b>	QBB95
<b>SQL Code</b>	-1006195L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006196</b>	<b>"hos_threadman: the environment variable HOS_NUM_OF_CPUS does not exist %1"</b>
<b>Constant</b>	EMSG_THREADMAN_NOENVVAR
<b>SAP Sybase Error Number</b>	20434
<b>SQL State</b>	QBB96
<b>SQL Code</b>	-1006196L
<b>ODBC 2 State</b>	ERROR

<b>Error 1006196</b>	"hos_threadman: the environment variable HOS_NUM_OF_CPUS does not exist %1"
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006197</b>	"Unknown error was found during hos_threadman Constructor %1"
<b>Constant</b>	EMSG_THREADMAN_CSTRFAILED
<b>SAP Sybase Error Number</b>	20435
<b>SQL State</b>	QBB97
<b>SQL Code</b>	-1006197L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

## Messages 1006198 through 1006217

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1006198</b>	"Unknown error was found during hos_threadman Destructor %1"
<b>Constant</b>	EMSG_THREADMAN_DSTRFAILED
<b>SAP Sybase Error Number</b>	20436
<b>SQL State</b>	QBB98
<b>SQL Code</b>	-1006198L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 1006198</b>	<b>"Unknown error was found during hos_threadman Destructor %1"</b>
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006199</b>	<b>"Unknown error was found on hos_threadman Call %1"</b>
<b>Constant</b>	EMSG_THREADMAN_DEFAULT
<b>SAP Sybase Error Number</b>	20437
<b>SQL State</b>	QBB99
<b>SQL Code</b>	-1006199L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006200</b>	<b>" and last packet was "</b>
<b>Constant</b>	EMSG_IPCC_BAD_SEQ_PACKET2
<b>SAP Sybase Error Number</b>	20438
<b>SQL State</b>	QBC00
<b>SQL Code</b>	-1006200L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006201</b>	<b>" and last packet was "</b>
<b>Constant</b>	EMSG_IPCS_BAD_SEQ_PACKET2
<b>SAP Sybase Error Number</b>	20439

<b>Error 1006201</b>	" and last packet was "
<b>SQL State</b>	QBC01
<b>SQL Code</b>	-1006201L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006202</b>	<b>"Syntax error in conversion of string to DATETIME value."</b>
<b>Constant</b>	EMSG_INVALID_DATETIMESYNTAX
<b>SAP Sybase Error Number</b>	20440
<b>SQL State</b>	QBC02
<b>SQL Code</b>	-1006202L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006203</b>	<b>"Syntax error in conversion of string to DATE value."</b>
<b>Constant</b>	EMSG_INVALID_DATESYNTAX
<b>SAP Sybase Error Number</b>	20441
<b>SQL State</b>	QBC03
<b>SQL Code</b>	-1006203L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.

## Errors and Warnings

<b>Error 1006204</b>	"Syntax error in conversion of string to TIME value."
<b>Constant</b>	EMSG_INVALID_TIMESYNTAX
<b>SAP Sybase Error Number</b>	20442
<b>SQL State</b>	QBC04
<b>SQL Code</b>	-1006204L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006205</b>	<b>"A lock was acquired on an object which has inconsistent state"</b>
<b>Constant</b>	EMSG_CATCHLOCK_STATE_INCONSISTENT
<b>SAP Sybase Error Number</b>	20443
<b>SQL State</b>	QBC05
<b>SQL Code</b>	-1006205L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006206</b>	<b>No message</b>
<b>Constant</b>	EMSG_ASSERT_DEFAULT_EMPTY_SLOT
<b>SAP Sybase Error Number</b>	20444
<b>SQL State</b>	QBC06
<b>SQL Code</b>	-1006206L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2

<b>Error 1006206</b>	<b>No message</b>
<b>Probable Cause</b>	No additional information available.
<b>Error 1006207</b>	<b>"ACCESS exception: OS error %1"</b>
<b>Constant</b>	EMSG_ACCESS_OSERROR
<b>SAP Sybase Error Number</b>	20445
<b>SQL State</b>	QBC07
<b>SQL Code</b>	-1006207L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006208</b>	<b>"CONSTRAINT exception: OS error %2 %1"</b>
<b>Constant</b>	EMSG_CONSTRAINT_OSERROR
<b>SAP Sybase Error Number</b>	20446
<b>SQL State</b>	QBC08
<b>SQL Code</b>	-1006208L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	error number
<b>Probable Cause</b>	No additional information available.
<b>Error 1006209</b>	<b>"The exception handler's memory manager could not get memory during initialization"</b>
<b>Constant</b>	EMSG_EXMEM_COULDNOTINIT
<b>SAP Sybase Error Number</b>	20447

## Errors and Warnings

<b>Error 1006209</b>	"The exception handler's memory manager could not get memory during initialization"
<b>SQL State</b>	QBC09
<b>SQL Code</b>	-1006209L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006210</b>	"The exception handler's memory manager has run out of memory"
<b>Constant</b>	EMSG_EXMEM_OUTOFMEM
<b>SAP Sybase Error Number</b>	20448
<b>SQL State</b>	QBC10
<b>SQL Code</b>	-1006210L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006211</b>	"Not all memory was returned to the exception handler's memory manager"
<b>Constant</b>	EMSG_EXMEM_MEMLEAK
<b>SAP Sybase Error Number</b>	20449
<b>SQL State</b>	QBC11
<b>SQL Code</b>	-1006211L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006212</b>	"The exception handler's memory manager has been corrupted"
<b>Constant</b>	EMSG_EXMEM_MEMCORRUPT
<b>SAP Sybase Error Number</b>	20450
<b>SQL State</b>	QBC12
<b>SQL Code</b>	-1006212L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006213</b>	"Unable to use shared memory because "
<b>Constant</b>	EMSG_SHRMEM_BECAUSE
<b>SAP Sybase Error Number</b>	20451
<b>SQL State</b>	QBC13
<b>SQL Code</b>	-1006213L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006214</b>	"the semaphore for shared memory did not exist"
<b>Constant</b>	EMSG_SHRMEM_NO_SUCH_SEMAPHORE
<b>SAP Sybase Error Number</b>	20452
<b>SQL State</b>	QBC14
<b>SQL Code</b>	-1006214L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2

## Errors and Warnings

<b>Error 1006214</b>	"the semaphore for shared memory did not exist"
<b>Probable Cause</b>	No additional information available.
<b>Error 1006215</b>	"the semaphore for shared memory was deleted"
<b>Constant</b>	EMSG_SHRMEM_SEMAPHORE_DELETED
<b>SAP Sybase Error Number</b>	20453
<b>SQL State</b>	QBC15
<b>SQL Code</b>	-1006215L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006216</b>	"of insufficient system semaphore resources"
<b>Constant</b>	EMSG_SHRMEM_INSUF_SEM_RESOURCES
<b>SAP Sybase Error Number</b>	20454
<b>SQL State</b>	QBC16
<b>SQL Code</b>	-1006216L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006217</b>	"the system limit on the number of processes allowed to request semaphore undos would be exceeded"
<b>Constant</b>	EMSG_SHRMEM_SEM_UNDOS_ENOSPC
<b>SAP Sybase Error Number</b>	20455
<b>SQL State</b>	QBC17
<b>SQL Code</b>	-1006217L
<b>ODBC 2 State</b>	ERROR

<b>Error 1006217</b>	"the system limit on the number of processes allowed to request semaphore undos would be exceeded"
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.

## Messages 1006218 through 1006238

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1006218</b>	"the system limit on the number of semaphore undo requests allowed per process (semume) would be exceeded"
<b>Constant</b>	EMSG_SHRMEM_SEM_UNDOS_EINVAL
<b>SAP Sybase Error Number</b>	20456
<b>SQL State</b>	QBC18
<b>SQL Code</b>	-1006218L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006219</b>	"the creation of a new semaphore would exceed the system limit on either the maximum number of semaphores allowed or the maximum number of semaphore identifiers allowed"
<b>Constant</b>	EMSG_SHRMEM_SEMGET_CREATE_ENOSPC
<b>SAP Sybase Error Number</b>	20457
<b>SQL State</b>	QBC19
<b>SQL Code</b>	-1006219L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 1006219</b>	"the creation of a new semaphore would exceed the system limit on either the maximum number of semaphores allowed or the maximum number of semaphore identifiers allowed"
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006220</b>	"of insufficient system shared memory resources"
<b>Constant</b>	EMSG_SHRMEM_INSUF_SHM_RESOURCES
<b>SAP Sybase Error Number</b>	20458
<b>SQL State</b>	QBC20
<b>SQL Code</b>	-1006220L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006221</b>	"the creation of a new shared memory segment would exceed the system limit on the maximum number of shared segments allowed"
<b>Constant</b>	EMSG_SHRMEM_SHMGET_CREATE_ENOSPC
<b>SAP Sybase Error Number</b>	20459
<b>SQL State</b>	QBC21
<b>SQL Code</b>	-1006221L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006222</b>	"the requested shared memory segment size is less than the system-imposed minimum (shmin) or greater than the system-imposed maximum (shmax)"
<b>Constant</b>	EMSG_SHRMEM_SHMGET_CREATE_EINVAL
<b>SAP Sybase Error Number</b>	20460
<b>SQL State</b>	QBC22
<b>SQL Code</b>	-1006222L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006223</b>	"of insufficient available physical memory to create a new shared memory segment"
<b>Constant</b>	EMSG_SHRMEM_SHMGET_CREATE_ENOMEM
<b>SAP Sybase Error Number</b>	20461
<b>SQL State</b>	QBC23
<b>SQL Code</b>	-1006223L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006224</b>	"the system limit of shared memory segments attached per process (shmseg) would be exceeded"
<b>Constant</b>	EMSG_SHRMEM_SHMAT_EMFILE
<b>SAP Sybase Error Number</b>	20462
<b>SQL State</b>	QBC24
<b>SQL Code</b>	-1006224L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1006224</b>	<b>"the system limit of shared memory segments attached per process (shmseg) would be exceeded"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006225</b>	<b>"the available data space is not large enough to accommodate the shared memory segment"</b>
<b>Constant</b>	EMSG_SHRMEM_SHMAT_ENOMEM
<b>SAP Sybase Error Number</b>	20463
<b>SQL State</b>	QBC25
<b>SQL Code</b>	-1006225L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006226</b>	<b>"you have no permission to access the shared memory semaphore"</b>
<b>Constant</b>	EMSG_SHRMEM_SEM_NO_ACCESS
<b>SAP Sybase Error Number</b>	20464
<b>SQL State</b>	QBC26
<b>SQL Code</b>	-1006226L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006227</b>	<b>"you have no permission to access the shared memory segment"</b>
<b>Constant</b>	EMSG_SHRMEM_SHM_NO_ACCESS

<b>Error 1006227</b>	"you have no permission to access the shared memory segment"
<b>SAP Sybase Error Number</b>	20465
<b>SQL State</b>	QBC27
<b>SQL Code</b>	-1006227L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006228</b>	<b>"the attach failed because the shared memory segment was created by a process with significantly different settings (e.g. max threads)"</b>
<b>Constant</b>	EMSG_SHRMEM_SHM_ATTACH_FAILED
<b>SAP Sybase Error Number</b>	20466
<b>SQL State</b>	QBC28
<b>SQL Code</b>	-1006228L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006229</b>	<b>"the attach failed because the shared memory segment was created by a process running a different version of sybase_iq"</b>
<b>Constant</b>	EMSG_SHRMEM_SHM_IMAGE_MISMATCH
<b>SAP Sybase Error Number</b>	20467
<b>SQL State</b>	QBC29
<b>SQL Code</b>	-1006229L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 1006229</b>	"the attach failed because the shared memory segment was created by a process running a different version of <b>sybase_iq</b> "
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006230</b>	<b>"lock request was interrupted"</b>
<b>Constant</b>	EMSG_SHRMEM_SHM_INTERRUPTED
<b>SAP Sybase Error Number</b>	20468
<b>SQL State</b>	QBC30
<b>SQL Code</b>	-1006230L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006231</b>	<b>"ACCESS exception: OS error %2: %3 %1"</b>
<b>Constant</b>	EMSG_ACCESS_OSERROR2
<b>SAP Sybase Error Number</b>	20469
<b>SQL State</b>	QBC31
<b>SQL Code</b>	-1006231L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	error number
<b>Parameter 3</b>	working directory
<b>Probable Cause</b>	No additional information available.

<b>Error 1006232</b>	"Unknown ParamSet error %1"
<b>Constant</b>	EMSG_PARAM_UNKNOWN
<b>SAP Sybase Error Number</b>	20470
<b>SQL State</b>	QBC32
<b>SQL Code</b>	-1006232L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006233</b>	<b>"CONSTRAINT exception: OS error %2: pathname len is %3, your buffer size is %4. Pathname is %5 %1"</b>
<b>Constant</b>	EMSG_CONSTRAINT_OSERROR2
<b>SAP Sybase Error Number</b>	20471
<b>SQL State</b>	QBC33
<b>SQL Code</b>	-1006233L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	error number
<b>Parameter 3</b>	pathname length
<b>Parameter 4</b>	buffer size
<b>Parameter 5</b>	pathname
<b>Probable Cause</b>	No additional information available.
<b>Error 1006234</b>	<b>"The IQ SET command has no option named '%2' %1"</b>
<b>Constant</b>	EMSG_PARAM_UNKNOPARAM

## Errors and Warnings

<b>Error 1006234</b>	<b>"The IQ SET command has no option named '%2' %1"</b>
<b>SAP Sybase Error Number</b>	20472
<b>SQL State</b>	QBC34
<b>SQL Code</b>	-1006234L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006235</b>	<b>"The IQ SET SERVERDEFAULT command requires the SA_ROLE %1"</b>
<b>Constant</b>	EMSG_PARAM_SERVER_ONLY_SA
<b>SAP Sybase Error Number</b>	20473
<b>SQL State</b>	QBC35
<b>SQL Code</b>	-1006235L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1006237</b>	<b>"The IQ SET option, "%2", can not be set server-wide %1"</b>
<b>Constant</b>	EMSG_PARAM_NOT_SET_SERV2
<b>SAP Sybase Error Number</b>	20475
<b>SQL State</b>	QBC37
<b>SQL Code</b>	-1006237L
<b>ODBC 2 State</b>	ERROR

<b>Error 1006237</b>	"The IQ SET option, "%2', can not be set server-wide %1"
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006238</b>	"The IQ SET option, "%2', can only be set server-wide and not for a session %1"
<b>Constant</b>	EMSG_PARAM_NOT_SESSION2
<b>SAP Sybase Error Number</b>	20476
<b>SQL State</b>	QBC38
<b>SQL Code</b>	-1006238L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

## 1006239 - 1009145

---

### Messages 1006239 through 1006258

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1006239</b>	"The IQ SET option, "%2', can only be changed by users with SA_ROLE or DBO_ROLE %1"
<b>Constant</b>	EMSG_PARAM_NEEDS_DBO_OR_SA2
<b>SAP Sybase Error Number</b>	20477

## Errors and Warnings

<b>Error 1006239</b>	<b>"The IQ SET option, "%2', can only be changed by users with SA_ROLE or DBO_ROLE %1"</b>
<b>SQL State</b>	QBC39
<b>SQL Code</b>	-1006239L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006240</b>	<b>"The value, %2, is not valid for the SQL Anywhere option, '%3' %1"</b>
<b>Constant</b>	EMSG_PARAM_BADPARAMVALUESA
<b>SAP Sybase Error Number</b>	20478
<b>SQL State</b>	QBC40
<b>SQL Code</b>	-1006240L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Parameter 3</b>	explanation for arg %3 delete if no %3
<b>Probable Cause</b>	No additional information available.
<b>Error 1006241</b>	<b>"The value, %2, is not valid for the integer option, "%3' %1"</b>
<b>Constant</b>	EMSG_PARAM_BADPARAMVALUEINT
<b>SAP Sybase Error Number</b>	20479
<b>SQL State</b>	QBC41

<b>Error 1006241</b>	<b>"The value, %2, is not valid for the integer option, "%3' %1"</b>
<b>SQL Code</b>	-1006241L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Parameter 3</b>	explanation for arg %3 delete if no %3
<b>Probable Cause</b>	No additional information available.
<b>Error 1006242</b>	<b>"The value, %2, is not valid for the unsigned integer option, "%3' %1"</b>
<b>Constant</b>	EMSG_PARAM_BADPARAMVALUEUINT
<b>SAP Sybase Error Number</b>	20480
<b>SQL State</b>	QBC42
<b>SQL Code</b>	-1006242L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Parameter 3</b>	explanation for arg %3 delete if no %3
<b>Probable Cause</b>	No additional information available.
<b>Error 1006243</b>	<b>"The value, %2, is not valid for the boolean option, "%3' %1"</b>
<b>Constant</b>	EMSG_PARAM_BADPARAMVALUEBOOL
<b>SAP Sybase Error Number</b>	20481
<b>SQL State</b>	QBC43
<b>SQL Code</b>	-1006243L

## Errors and Warnings

<b>Error 1006243</b>	<b>"The value, %2, is not valid for the boolean option, "%3' %1"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Parameter 3</b>	explanation for arg %3 delete if no %3
<b>Probable Cause</b>	No additional information available.
<b>Error 1006244</b>	<b>"The value, %2, is not valid for the unsigned 64bit integer option, "%3' %1"</b>
<b>Constant</b>	EMSG_PARAM_BADPARAMVALUEUINT64
<b>SAP Sybase Error Number</b>	20482
<b>SQL State</b>	QBC44
<b>SQL Code</b>	-1006244L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Parameter 3</b>	explanation for arg %3 delete if no %3
<b>Probable Cause</b>	No additional information available.
<b>Error 1006245</b>	<b>"The value, %2, is not valid for the string option, "%3' %1"</b>
<b>Constant</b>	EMSG_PARAM_BADPARAMVALUESTRING
<b>SAP Sybase Error Number</b>	20483
<b>SQL State</b>	QBC45
<b>SQL Code</b>	-1006245L
<b>ODBC 2 State</b>	ERROR

<b>Error 1006245</b>	"The value, %2, is not valid for the string option, "%3' %1"
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Parameter 3</b>	explanation for arg %3 delete if no %3
<b>Probable Cause</b>	No additional information available.

<b>Error 1006246</b>	<b>No message</b>
<b>Constant</b>	EMSG_PARAM_UNKNOWNDATATYPE_EMPTY_SLOT
<b>SAP Sybase Error Number</b>	20484
<b>SQL State</b>	QBC46
<b>SQL Code</b>	-1006246L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006247</b>	<b>"shared segment: os error"</b>
<b>Constant</b>	EMSG_SHAREDSEG_OSERR
<b>SAP Sybase Error Number</b>	20485
<b>SQL State</b>	QBC47
<b>SQL Code</b>	-1006247L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	No additional information available.

## Errors and Warnings

<b>Error 1006248</b>	<b>"shared segment: virtual addr does not match"</b>
<b>Constant</b>	EMSG_SHAREDSEG_VADDRERR
<b>SAP Sybase Error Number</b>	20486
<b>SQL State</b>	QBC48
<b>SQL Code</b>	-1006248L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006249</b>	<b>"Shared segment attach failed because the shared memory segment was created by a process running a different version of sybase_iq."</b>
<b>Constant</b>	EMSG_SHAREDSEG_IMG_MISMATCH
<b>SAP Sybase Error Number</b>	20487
<b>SQL State</b>	QBC49
<b>SQL Code</b>	-1006249L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006250</b>	<b>"Requested shared memory size, SHMEMMB &amp; TEMPSHMEMMB, too big for available shared memory segments, SYSTEMSHMMAX &amp; SYSTEMSHMSEG"</b>
<b>Constant</b>	EMSG_SHAREDSEG_TOO_BIG
<b>SAP Sybase Error Number</b>	20488
<b>SQL State</b>	QBC50
<b>SQL Code</b>	-1006250L
<b>ODBC 2 State</b>	ERROR

<b>Error 1006250</b>	"Requested shared memory size, SHMEMMB & TEMPSHMEMMB, too big for available shared memory segments, SYSTEMSHMAX & SYSTEMSHMSEG"
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006251</b>	"Requested shared memory size, SHMEMMB & TEMPSHMEMMB, greater than system limit (max 4GB)"
<b>Constant</b>	EMSG_SHAREDSEG_SHMEMMB_TOO_BIG
<b>SAP Sybase Error Number</b>	20489
<b>SQL State</b>	QBC51
<b>SQL Code</b>	-1006251L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006252</b>	"Requested shared memory size, SHMEMMB or TEMPSHMEMMB, too small (min 1MB)"
<b>Constant</b>	EMSG_SHAREDSEG_SHMEMMB_TOO_SMALL
<b>SAP Sybase Error Number</b>	20490
<b>SQL State</b>	QBC52
<b>SQL Code</b>	-1006252L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.

## Errors and Warnings

<b>Error 1006253</b>	"Requested shared memory size, SYSTEMSHMMAX, greater than system limit"
<b>Constant</b>	EMSG_SHAREDSEG_SYSTEMSHMMAX_TOO_BIG
<b>SAP Sybase Error Number</b>	20491
<b>SQL State</b>	QBC53
<b>SQL Code</b>	-1006253L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006254</b>	"Data overflow %2 %1"
<b>Constant</b>	EMSG_ERROR_OVERFLOW
<b>SAP Sybase Error Number</b>	20492
<b>SQL State</b>	QBC54
<b>SQL Code</b>	-1006254L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006255</b>	"Maximum exceeded %2 %1"
<b>Constant</b>	EMSG_ERROR_EXCEEDMAX
<b>SAP Sybase Error Number</b>	20493
<b>SQL State</b>	QBC55
<b>SQL Code</b>	-1006255L
<b>ODBC 2 State</b>	ERROR

<b>Error 1006255</b>	<b>"Maximum exceeded %2 %1"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006256</b>	<b>"Invalid arithmetic construction %2 %1"</b>
<b>Constant</b>	EMSG_NUMERIC_CONSTRUCTOR
<b>SAP Sybase Error Number</b>	20494
<b>SQL State</b>	QBC56
<b>SQL Code</b>	-1006256L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006257</b>	<b>"Invalid arithmetic conversion %2 %1"</b>
<b>Constant</b>	EMSG_NUMERIC_CONVERSION
<b>SAP Sybase Error Number</b>	20495
<b>SQL State</b>	QBC57
<b>SQL Code</b>	-1006257L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2

## Errors and Warnings

<b>Error 1006257</b>	" <b>Invalid arithmetic conversion %2 %1</b> "
<b>Probable Cause</b>	No additional information available.
<b>Error 1006258</b>	" <b>Invalid arithmetic operation %2 %1</b> "
<b>Constant</b>	EMSG_NUMERIC_OPERATOR
<b>SAP Sybase Error Number</b>	20496
<b>SQL State</b>	QBC58
<b>SQL Code</b>	-1006258L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

## Messages 1006259 through 1008005

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1006259</b>	" <b>Invalid arithmetic function arguments %2 %1</b> "
<b>Constant</b>	EMSG_NUMERIC_FUNCTION
<b>SAP Sybase Error Number</b>	20497
<b>SQL State</b>	QBC59
<b>SQL Code</b>	-1006259L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1006260</b>	" Could not open file: "
<b>Constant</b>	EMSG_FILEINFO_OPENERR
<b>SAP Sybase Error Number</b>	20498
<b>SQL State</b>	QBC60
<b>SQL Code</b>	-1006260L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006261</b>	"\n\n*** File: %s\n\n"
<b>Constant</b>	EMSG_FILENAME
<b>SAP Sybase Error Number</b>	20499
<b>SQL State</b>	QBC61
<b>SQL Code</b>	-1006261L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006262</b>	" This new operator should never be called "
<b>Constant</b>	EMSG_SHOULDNOTCALLNEW
<b>SAP Sybase Error Number</b>	20500
<b>SQL State</b>	QBC62
<b>SQL Code</b>	-1006262L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.

## Errors and Warnings

<b>Error 1006263</b>	" This delete operator should never be called "
<b>Constant</b>	EMSG_SHOULDNOTCALLDELETE
<b>SAP Sybase Error Number</b>	20501
<b>SQL State</b>	QBC63
<b>SQL Code</b>	-1006263L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1006264</b>	<b>"Invalid Blocksize %2 less than the Device Sectorsize %3 %4 %1"</b>
<b>Constant</b>	EMSG_BIO_INVBLKSZFORDEV
<b>SAP Sybase Error Number</b>	21072
<b>SQL State</b>	QBC64
<b>SQL Code</b>	-1006264L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	%2 Invalid block size
<b>Parameter 3</b>	%3 Device Sector Size
<b>Parameter 4</b>	%4 Name of Raw device
<b>Probable Cause</b>	No additional information available.
<b>Error 1006265</b>	<b>"Invalid Filename: %2. %1"</b>
<b>Constant</b>	EMSG_IO_INVALID_FILENAME
<b>SAP Sybase Error Number</b>	21093
<b>SQL State</b>	QBC65

<b>Error 1006265</b>	<b>"Invalid Filename: %2. %1"</b>
<b>SQL Code</b>	-1006265L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	%2 Invalid filename
<b>Probable Cause</b>	A bad filename (perhaps zero-length) was specified.
<b>Error 1006266</b>	<b>"Found bad sector on raw device: %1"</b>
<b>Constant</b>	EMSG_RAWIO_BAD_SECTOR
<b>SAP Sybase Error Number</b>	21105
<b>SQL State</b>	QBC66
<b>SQL Code</b>	-1006266L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	A bad sector was detected on the given raw device.
<b>Error 1006267</b>	<b>"%2 blocks is greater than the partition size of %3 blocks %1"</b>
<b>Constant</b>	EMSG_BIO_RESIZETOOBIG
<b>SAP Sybase Error Number</b>	21119
<b>SQL State</b>	QBC67
<b>SQL Code</b>	-1006267L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2

## Errors and Warnings

<b>Error 1006267</b>	<b>"%2 blocks is greater than the partition size of %3 blocks %1"</b>
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	user specified size
<b>Parameter 3</b>	partition size
<b>Probable Cause</b>	No additional information available.
<b>Error 1006268</b>	<b>"The current operation has been cancelled: Max_Temp_Space_Per_Connection exceeded"</b>
<b>Constant</b>	EMSG_ATTN_MAXTEMPSPACE
<b>SAP Sybase Error Number</b>	21151
<b>SQL State</b>	QBC68
<b>SQL Code</b>	-1006268L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	User has exhausted maximum temp dbspace limit for this connection
<b>Error 1006269</b>	<b>"No SYSAM License Available"</b>
<b>Constant</b>	EMSG_NO_SYSAMLICENSE
<b>SAP Sybase Error Number</b>	21161
<b>SQL State</b>	QBC69
<b>SQL Code</b>	-1006269L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	SYSAM license for the product is either not available or not configured.

<b>Error 1006270</b>	"SYSAM Failure while doing: %1"
<b>Constant</b>	EMSG_SYLAPI_FAILURE
<b>SAP Sybase Error Number</b>	21162
<b>SQL State</b>	QBC70
<b>SQL Code</b>	-1006270L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Parameter 1 description
<b>Probable Cause</b>	SYSAM internal failure.

<b>Error 1006271</b>	"IQ_CORE License has expired"
<b>Constant</b>	EMSG_IQCORE_EXPIRED
<b>SAP Sybase Error Number</b>	21163
<b>SQL State</b>	QBC71
<b>SQL Code</b>	-1006271L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	SYSAM IQ_CORE license has expired leading to server shutdown

<b>Error 1006272</b>	"IQ Main store cannot be larger than licensed limit"
<b>Constant</b>	EMSG_IQSTORE_LIMIT
<b>SAP Sybase Error Number</b>	21172
<b>SQL State</b>	QBC72
<b>SQL Code</b>	-1006272L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2

## Errors and Warnings

<b>Error 1006272</b>	<b>"IQ Main store cannot be larger than licensed limit"</b>
<b>Probable Cause</b>	SYSAM IQ Main store is larger than the limit specified in product license leading to server shutdown
<b>Error 1006273</b>	<b>"License limit for dbspaces reached. Cannot create new dbspace"</b>
<b>Constant</b>	EMSG_VLDBMGMT_LIMIT
<b>SAP Sybase Error Number</b>	21203
<b>SQL State</b>	QBC73
<b>SQL Code</b>	-1006273L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	SYSAM Number of IQ Main DBSpaces higher than the licensed limit
<b>Error 1006274</b>	<b>"Transaction cannot continue due to unrecoverable INC failure. Roll back current transaction. %1"</b>
<b>Constant</b>	EMSG_INC_FAILURE_ROLLBACKTXN
<b>SAP Sybase Error Number</b>	22036
<b>SQL State</b>	QBC74
<b>SQL Code</b>	-1006274L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	The underlying INC for current transaction has failed to connect to coordinator in Mpx_Liveness_Timeout seconds or coordinator side state of transaction is unknown.
<b>Error 1008000</b>	<b>"Users are not allowed to create an FP index. FP indexes are created automatically when the table is created."</b>
<b>Constant</b>	EMSG_IQ_NOCREATEFP

<b>Error 1008000</b>	<b>"Users are not allowed to create an FP index. FP indexes are created automatically when the table is created."</b>
<b>SAP Sybase Error Number</b>	20596
<b>SQL State</b>	QNA00
<b>SQL Code</b>	-1008000L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	Users are not able to create Fast Projection indexes on columns. They are created automatically when the table is created.
<b>Error 1008001</b>	<b>"The user cannot create indexes on a join virtual table."</b>
<b>Constant</b>	EMSG_IQ_NOCREATEINDEXJVT
<b>SAP Sybase Error Number</b>	20621
<b>SQL State</b>	QNA01
<b>SQL Code</b>	-1008001L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	Users cannot create indexes on a join virtual table. They are automatically created.
<b>Error 1008004</b>	<b>"Cannot DROP index '%1'."</b>
<b>Constant</b>	EMSG_IQ_NODROPIQINDEX
<b>SAP Sybase Error Number</b>	20673
<b>SQL State</b>	QNA04
<b>SQL Code</b>	-1008004L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2

## Errors and Warnings

<b>Error 1008004</b>	" <b>Cannot DROP index "%1".</b> "
<b>Parameter 1</b>	Name of the index the user is attempting to drop.
<b>Probable Cause</b>	Users cannot drop internally created indexes except by dropping the table, join index, or alter-dropping the table or join index. Fast Projection indexes are internally created indexes.
<b>Error 1008005</b>	" <b>Cannot ALTER join virtual table "%1".</b> "
<b>Constant</b>	EMSG_IQ_NOALTERJVT
<b>SAP Sybase Error Number</b>	20675
<b>SQL State</b>	QNA05
<b>SQL Code</b>	-1008005L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	The join virtual table the user is attempting to alter.
<b>Probable Cause</b>	The user cannot alter a join virtual table.

## Messages 1008006 through 1008027

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1008006</b>	" <b>You cannot specify a DEFAULT value for a column.</b> "
<b>Constant</b>	EMSG_IQ_INVALIDDEFAULT
<b>SAP Sybase Error Number</b>	20676
<b>SQL State</b>	QNA06
<b>SQL Code</b>	-1008006L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	The user cannot specify a DEFAULT value for a column during CREATE TABLE or ALTER TABLE ADD COLUMN.

<b>Error 1008007</b>	"The ALTER TABLE option '%2' is not supported by Sybase IQ. %1"
<b>Constant</b>	EMSG_IQ_NOSUPPORT
<b>SAP Sybase Error Number</b>	20677
<b>SQL State</b>	QNA07
<b>SQL Code</b>	-1008007L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	The ALTER TABLE option the user is attempting to use.
<b>Probable Cause</b>	The user entered an option that is not supported by Sybase IQ but is supported by ASA (like REPLICATION ON).
<b>Error 1008008</b>	"You cannot TRUNCATE a join virtual table."
<b>Constant</b>	EMSG_IQ_NOTRUNCATEJVT
<b>SAP Sybase Error Number</b>	20679
<b>SQL State</b>	QNA08
<b>SQL Code</b>	-1008008L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	The user is not allowed to TRUNCATE a join virtual table.
<b>Error 1008009</b>	"This statement is not supported by Sybase IQ."
<b>Constant</b>	EMSG_IQ_STMTNOTSUPPORTED
<b>SAP Sybase Error Number</b>	20680
<b>SQL State</b>	QNA09
<b>SQL Code</b>	-1008009L

## Errors and Warnings

<b>Error 1008009</b>	<b>"This statement is not supported by Sybase IQ."</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	The statement entered is supported by Adaptive Server Anywhere, but not by Sybase IQ.
<b>Error 1008010</b>	<b>"A request was made to delete the primary key constraint, but the primary key cannot be found."</b>
<b>Constant</b>	EMSG_IQ_NOPRIMARYKEY
<b>SAP Sybase Error Number</b>	20681
<b>SQL State</b>	QNA10
<b>SQL Code</b>	-1008010L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	The user wanted to delete the primary key constraint on the table but the primary key could not be found.
<b>Error 1008012</b>	<b>"This unique index/constraint must be ENFORCED."</b>
<b>Constant</b>	EMSG_IQ_NEEDENFORCED
<b>SAP Sybase Error Number</b>	20990
<b>SQL State</b>	QNA12
<b>SQL Code</b>	-1008012L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	This unique index/constraint must be ENFORCED (The UNENFORCED keyword not allowed for this index/constraint).

<b>Error 1008013</b>	"This multi-column unique index/constraint must be UNENFORCED."
<b>Constant</b>	EMSG_IQ_NEEDUNENFORCED
<b>SAP Sybase Error Number</b>	20991
<b>SQL State</b>	QNA13
<b>SQL Code</b>	-1008013L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	This multi-column unique index/constraint must be UNENFORCED (The UNENFORCED keyword is required for this index/constraint).
<b>Error 1008014</b>	"This foreign key must be UNENFORCED."
<b>Constant</b>	EMSG_IQ_FKEYNOSUPP
<b>SAP Sybase Error Number</b>	20992
<b>SQL State</b>	QNA14
<b>SQL Code</b>	-1008014L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	This foreign key must be UNENFORCED (The UNENFORCED keyword is required for this foreign key).
<b>Error 1008015</b>	"This check constraint must be ENFORCED."
<b>Constant</b>	EMSG_IQ_CHCKENFORCED
<b>SAP Sybase Error Number</b>	20993
<b>SQL State</b>	QNA15
<b>SQL Code</b>	-1008015L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 1008015</b>	"This check constraint must be ENFORCED."
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	The keyword UNENFORCED is not supported.
<b>Error 1008016</b>	"Cannot ALTER DELETE a column that has a unique or primary key constraint."
<b>Constant</b>	EMSG_IQ_CONSTRAINTONCOL
<b>SAP Sybase Error Number</b>	20994
<b>SQL State</b>	QNA16
<b>SQL Code</b>	-1008016L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	Cannot ALTER DELETE a column that has a unique or primary key constraint. This is a duplicate of an SA error code.
<b>Error 1008017</b>	"Cannot ALTER DELETE a column that has multi-column index."
<b>Constant</b>	EMSG_IQ_MULTICOLONINDEX
<b>SAP Sybase Error Number</b>	20995
<b>SQL State</b>	QNA17
<b>SQL Code</b>	-1008017L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	Cannot ALTER DELETE a column that has multi-column index. This is a duplicate of an SA error code.
<b>Error 1008019</b>	"Multiplex is currently inactive."
<b>Constant</b>	EMSG_IQMPX_INACTIVE
<b>SAP Sybase Error Number</b>	21041

<b>Error 1008019</b>	<b>"Multiplex is currently inactive."</b>
<b>SQL State</b>	QNA19
<b>SQL Code</b>	-1008019L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	The user has either requested a multiplex function or has asked for multiplex status.
<b>Error 1008020</b>	<b>"Multiplex command or request is unimplemented."</b>
<b>Constant</b>	EMSG_IQMPX_NOTIMPL
<b>SAP Sybase Error Number</b>	21042
<b>SQL State</b>	QNA20
<b>SQL Code</b>	-1008020L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	The user has requested an unimplemented multiplex feature. This would typically be a status request which doesn't exist.
<b>Error 1008021</b>	<b>"The SYSIQFILE table is not configured for this server to run in a multiplex."</b>
<b>Constant</b>	EMSG_IQMPX_BADCONFIG
<b>SAP Sybase Error Number</b>	21043
<b>SQL State</b>	QNA21
<b>SQL Code</b>	-1008021L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2

## Errors and Warnings

<b>Error 1008021</b>	<b>"The SYSIQFILE table is not configured for this server to run in a multiplex."</b>
<b>Probable Cause</b>	SYSIQFILE identifies all files which make up the given stores that the IQ server requires (main, temp, and message). For multiplex, each entry in SYSIQFILE must be associated with a particular multiplex server before that server can access the particular file. This message indicates that some these rows are missing for the active server.
<b>Error 1008022</b>	<b>"Bad commit identity block. The server may be out of synchronization. %1"</b>
<b>Constant</b>	EMSG_IQMPX_BADCMID
<b>SAP Sybase Error Number</b>	21044
<b>SQL State</b>	QNA22
<b>SQL Code</b>	-1008022L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Multiplex servers cannot start this database. Start the coordinator in single server mode.
<b>Error 1008023</b>	<b>"Cannot start multiplex secondary server while the coordinator is in single server mode"</b>
<b>Constant</b>	EMSG_IQMPX_SPXDB
<b>SAP Sybase Error Number</b>	21045
<b>SQL State</b>	QNA23
<b>SQL Code</b>	-1008023L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	Restart the secondary server after the coordinator has restarted in normal mode.

<b>Error 1008024</b>	<b>"Multiplex coordinator must start as server@host: %2, on file: %3; to start with different settings, you must use the override switch. %1"</b>
<b>Constant</b>	EMSG_IQMPX_TWOWRITERS
<b>SAP Sybase Error Number</b>	21046
<b>SQL State</b>	QNA24
<b>SQL Code</b>	-1008024L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	server@host names for coordinator
<b>Parameter 3</b>	catalog db filename for coordinator
<b>Probable Cause</b>	Only the configured coordinator can start the database. Start with the override switch (-iqmpx_ov 1) to bypass this check.
<b>Error 1008025</b>	<b>"Multiplex secondary server cannot continue while the coordinator is in single server mode. %1"</b>
<b>Constant</b>	EMSG_IQMPX_SPXONLY
<b>SAP Sybase Error Number</b>	21047
<b>SQL State</b>	QNA25
<b>SQL Code</b>	-1008025L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Resynchronize and restart the secondary server after the coordinator has restarted in normal mode.

## Errors and Warnings

<b>Error 1008026</b>	<b>"Multiplex secondary server out of synchronization with the coordinator. %1"</b>
<b>Constant</b>	EMSG_IQMPX_CATSYNC
<b>SAP Sybase Error Number</b>	21048
<b>SQL State</b>	QNA26
<b>SQL Code</b>	-1008026L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	The secondary server's IQ catalog cannot be brought up to date with the coordinator's IQ catalog. This server must be synchronized.
<b>Error 1008027</b>	<b>"Multiplex secondary node shutting down due to a file added to the IQ_SYSTEM_MAIN dbspace.\nThis node must be synchronized and restarted. %1"</b>
<b>Constant</b>	EMSG_IQMPX_SEGCOUNT
<b>SAP Sybase Error Number</b>	21057
<b>SQL State</b>	QNA28
<b>SQL Code</b>	-1008027L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	The user has added a dbspace file to IQ_SYSTEM_MAIN on the coordinator. This causes secondary nodes to shut down. All secondary nodes must be synchronized and restarted after this operation.

## Messages 1008029 through 1009023

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1008029</b>	<b>"Cannot create foreign key to an unenforced primary key or unenforced unique constraint."</b>
<b>Constant</b>	EMSG_NOFKKEY_TO_UNENFORCED
<b>SAP Sybase Error Number</b>	21059
<b>SQL State</b>	QNA29
<b>SQL Code</b>	-1008029L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	Existing unenforced primary keys or unique constraints cannot be used to create an referential integrity relationship to a foreign table.
<b>Error 1008030</b>	<b>"Only IQ index types can be created on IQ tables within a Parallel IQ block."</b>
<b>Constant</b>	EMSG_SQL_PLBEGINONLYCI
<b>SAP Sybase Error Number</b>	21064
<b>SQL State</b>	QNA30
<b>SQL Code</b>	-1008030L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	Parallel IQ Begin/End blocks allow users to create multiple indexes simultaneously. At this time, only Create Index statements for HG, HNG, LF, LD, DATE, TIME, WD, and CMP index types on IQ tables are allowed within Parallel IQ Begin and End statements.

## Errors and Warnings

<b>Error 1008031</b>	" <b>Cannot do Create Index commands on global or local temporary tables or catalog server tables in a Parallel IQ block.</b> "
<b>Constant</b>	EMSG_SQL_NOTEMPINPLB
<b>SAP Sybase Error Number</b>	21065
<b>SQL State</b>	QNA31
<b>SQL Code</b>	-1008031L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	Cannot do Create Index commands on global or local temporary tables in a Parallel IQ block.
<b>Error 1008032</b>	" <b>Foreign keys disallowed on Identity/Autoincrement Columns when set option identity_enforce_uniqueness is on</b> "
<b>Constant</b>	EMSG_FOREIGN_KEY_DISALLOWED
<b>SAP Sybase Error Number</b>	20026
<b>SQL State</b>	QNA41
<b>SQL Code</b>	-1008032L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	An Identity/Autoincrement Column cannot be a foreign key when the set option <code>identity_enforce_uniqueness</code> is on. Either turn the option off, or chose a different column for the foreign key.
<b>Error 1008033</b>	" <b>Identity/Autoincrement Column %2 has Invalid datatype: scale must be 0. %1</b> "
<b>Constant</b>	EMSG_NON_ZERO_SCALE
<b>SAP Sybase Error Number</b>	20027
<b>SQL State</b>	QNA42

<b>Error 1008033</b>	"Identity/Autoincrement Column %2 has Invalid datatype: scale must be 0. %1"
<b>SQL Code</b>	-1008033L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column name
<b>Probable Cause</b>	Identity/Autoincrement Columns defined as datatype numeric must have scale 0
<b>Error 1008035</b>	"Invalid datatype for Identity/Autoincrement Column %2. %1"
<b>Constant</b>	EMSG_INVALID_DATATYPE
<b>SAP Sybase Error Number</b>	20029
<b>SQL State</b>	QNA44
<b>SQL Code</b>	-1008035L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I3</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column name
<b>Probable Cause</b>	The datatype used is not supported by Identity/Autoincrement column. Valid datatypes are bigint, unsigned bigint, integer, unsigned integer, smallint, tinyint, numeric scale 0 and decimal scale 0
<b>Error 1008036</b>	"Table %2 already has an Identity/Autoincrement Column. %1 "
<b>Constant</b>	EMSG_ALREADY_HAS_IDENTITY_COLUMN
<b>SAP Sybase Error Number</b>	20642
<b>SQL State</b>	QNA45

## Errors and Warnings

<b>Error 1008036</b>	"Table %2 already has an Identity/Autoincrement Column. %1 "
<b>SQL Code</b>	-1008036L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Table name
<b>Probable Cause</b>	An Identity/Autoincrement Column cannot be added to this table because it already has one.
<b>Error 1008037</b>	"Cannot drop %1 %2: set option 'identity_insert' must be off. "
<b>Constant</b>	EMSG_IDENTITY_INSERT_IS_ON
<b>SAP Sybase Error Number</b>	20643
<b>SQL State</b>	QNA46
<b>SQL Code</b>	-1008037L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	string literal 'Table' or 'Column'
<b>Parameter 2</b>	column name
<b>Probable Cause</b>	option 'identity insert' must not be set to any table name to drop an Identity Column. To turn it off use 'set identity_insert ''
<b>Error 1008038</b>	"create schema command not allowed on an active multiplex server. "
<b>Constant</b>	EMSG_NOSCHEMACMD_MULTIPLEX
<b>SAP Sybase Error Number</b>	21123
<b>SQL State</b>	QNA47
<b>SQL Code</b>	-1008038L

<b>Error 1008038</b>	"create schema command not allowed on an active multiplex server. "
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	the create schema command is not allowed on an active multiplex server
<b>Error 1008039</b>	<b>"Permission denied: The current multiplex server is not a writer server"</b>
<b>Constant</b>	EMSG_MPX_GLOBAL_CMD_PERMISSION_DENIED
<b>SAP Sybase Error Number</b>	22005
<b>SQL State</b>	QNA48
<b>SQL Code</b>	-1008039L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	The global command is not permitted on current multiplex node
<b>Error 1009000</b>	<b>"Bit %2 is unexpectedly on in bitmap. If the error persists, you may have a damaged index; please run sp_iqcheckdb. %1"</b>
<b>Constant</b>	EMSG_BM_BITON
<b>SAP Sybase Error Number</b>	20021
<b>SQL State</b>	QSA00
<b>SQL Code</b>	-1009000L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Bit that is on.

## Errors and Warnings

<b>Error 1009000</b>	<b>"Bit %2 is unexpectedly on in bitmap. If the error persists, you may have a damaged index; please run sp_iqcheckdb. %1"</b>
<b>Probable Cause</b>	This is either an internal calling error (some component called bitmap SET with a duplicate bit), a corrupt bitmap (and dbcc needs be run), or a bitmap operator that has gone awry and mis-computed a result.
<b>Error 1009001</b>	<b>"Bit %2 is unexpectedly off in bitmap. If the error persists, you may have a damaged index; please run sp_iqcheckdb. %1"</b>
<b>Constant</b>	EMSG_BM_BITOFF
<b>SAP Sybase Error Number</b>	20022
<b>SQL State</b>	QSA01
<b>SQL Code</b>	-1009001L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Bit that is off.
<b>Probable Cause</b>	This is either an internal calling error (some component called bitmap CLEAR with a duplicate bit), a corrupt bitmap (and dbcc needs be run), or a bitmap operator that has gone awry and mis-computed a result.
<b>Warning 1009002</b>	<b>" Index %2: Starting Insert Pass 2. %1 "</b>
<b>Constant</b>	EMSG_HG_STARTING_PASS2
<b>SAP Sybase Error Number</b>	20023
<b>SQL State</b>	00002
<b>SQL Code</b>	1009002L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	1 on page 2

<b>Warning 1009002</b>	" Index %2: Starting Insert Pass 2. %1"
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Index name
<b>Probable Cause</b>	No additional information available.
<b>Warning 1009003</b>	" Index %1: Thread %2 Inserting %3 Recs, %4 Secs."
<b>Constant</b>	EMSG_HG_INSERTED
<b>SAP Sybase Error Number</b>	20024
<b>SQL State</b>	00003
<b>SQL Code</b>	1009003L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	Index name
<b>Parameter 2</b>	Thread index
<b>Parameter 3</b>	Number of records
<b>Parameter 4</b>	Time
<b>Probable Cause</b>	No additional information available.
<b>Error 1009004</b>	"Statistics context = %2 %3\n %1"
<b>Constant</b>	EMSG_STATS_CONTEXT
<b>SAP Sybase Error Number</b>	20025
<b>SQL State</b>	QSA04
<b>SQL Code</b>	-1009004L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	majContext

## Errors and Warnings

<b>Error 1009004</b>	<b>"Statistics context = %2 %3\n %1"</b>
<b>Parameter 3</b>	minContext
<b>Probable Cause</b>	No additional information available.
<b>Error 1009012</b>	<b>"Cannot create %2 index on a column having a datatype %3. %1"</b>
<b>Constant</b>	EMSG_ERROR_INDEX_NOTALLOWED
<b>SAP Sybase Error Number</b>	20033
<b>SQL State</b>	QSA12
<b>SQL Code</b>	-1009012L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	the index type (e.g., LF, HG)
<b>Parameter 3</b>	textual name of the column's datatype
<b>Probable Cause</b>	A named index type index cannot be created on named datatype
<b>Error 1009019</b>	<b>"An internal server component, a bitmap, was given invalid input. %1"</b>
<b>Constant</b>	EMSG_BM_BADINPUT
<b>SAP Sybase Error Number</b>	20040
<b>SQL State</b>	QSA19
<b>SQL Code</b>	-1009019L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	location of the exception

<b>Error 1009019</b>	<b>"An internal server component, a bitmap, was given invalid input. %1"</b>
<b>Probable Cause</b>	Some non-bitmap component has called a bitmap with an illegal argument. This is an internal programming error and not the (direct) result of customer error.
<b>Error 1009021</b>	<b>"This server must first be started in Multiplex single-node mode (-iqmpx_sn 1) %1"</b>
<b>Constant</b>	EMSG_DATABASE_MPX_BADTLVFORMAT_START_SINGLE
<b>SAP Sybase Error Number</b>	20042
<b>SQL State</b>	QSA21
<b>SQL Code</b>	-1009021L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	The tlv log has an incorrect format
<b>Error 1009022</b>	<b>"Cannot create a WD index on a column narrower than 3 bytes. %1"</b>
<b>Constant</b>	EMSG_ERROR_WD_NOTALLOWED_CW2SMALL
<b>SAP Sybase Error Number</b>	20043
<b>SQL State</b>	QSA22
<b>SQL Code</b>	-1009022L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1009023</b>	<b>"Cannot create a WD index on a column wider than 32767 bytes. %1"</b>
<b>Constant</b>	EMSG_ERROR_WD_NOTALLOWED_CW2LARGE
<b>SAP Sybase Error Number</b>	20044
<b>SQL State</b>	QSA23
<b>SQL Code</b>	-1009023L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

## Messages 1009024 through 1009043

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1009024</b>	<b>"Cannot create a WD index with a max permitted word size less than 1 byte. %1"</b>
<b>Constant</b>	EMSG_ERROR_WD_NOTALLOWED_WL2SMALL
<b>SAP Sybase Error Number</b>	20045
<b>SQL State</b>	QSA24
<b>SQL Code</b>	-1009024L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1009025</b>	<b>"Cannot create a WD index with a max permitted word size greater than 255 bytes. %1"</b>
<b>Constant</b>	EMSG_ERROR_WD_NOTALLOWED_WL2LARGE

<b>Error 1009025</b>	<b>"Cannot create a WD index with a max permitted word size greater than 255 bytes. %1"</b>
<b>SAP Sybase Error Number</b>	20046
<b>SQL State</b>	QSA25
<b>SQL Code</b>	-1009025L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1009026</b>	<b>"Cannot create a WD index with a separator string this long. %1"</b>
<b>Constant</b>	EMSG_ERROR_WD_NOTALLOWED_SS2LARGE
<b>SAP Sybase Error Number</b>	20047
<b>SQL State</b>	QSA26
<b>SQL Code</b>	-1009026L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1009027</b>	<b>"Cannot create a WD index with a separator string containing a character fragment. %1"</b>
<b>Constant</b>	EMSG_ERROR_WD_NOTALLOWED_SSFRAG
<b>SAP Sybase Error Number</b>	20048
<b>SQL State</b>	QSA27
<b>SQL Code</b>	-1009027L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1009027</b>	<b>"Cannot create a WD index with a separator string containing a character fragment. %1"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1009028</b>	<b>"Cannot create a WD index with more than 256 separators. %1"</b>
<b>Constant</b>	EMSG_ERROR_WD_NOTALLOWED_NS2LARGE
<b>SAP Sybase Error Number</b>	20049
<b>SQL State</b>	QSA28
<b>SQL Code</b>	-1009028L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1009029</b>	<b>"Words exceeding the maximum permitted word length not supported. %1"</b>
<b>Constant</b>	EMSG_ERROR_WD_TRUNCWORD_NOT_SUPPORTED
<b>SAP Sybase Error Number</b>	20050
<b>SQL State</b>	QSA29
<b>SQL Code</b>	-1009029L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1009030</b>	<b>"Cannot create a WD index with the database IQ pagesize less than 4KB. %1"</b>
<b>Constant</b>	EMSG_ERROR_WD_NOTALLOWED_PS2SMALL
<b>SAP Sybase Error Number</b>	20051
<b>SQL State</b>	QSA30
<b>SQL Code</b>	-1009030L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1009031</b>	<b>"%2: All buffer cache pages are in use, ask your DBA to increase the size of the buffer cache. %1"</b>
<b>Constant</b>	EMSG_BUFLIST_ALLSLOTSLOCKED
<b>SAP Sybase Error Number</b>	20052
<b>SQL State</b>	QSA31
<b>SQL Code</b>	-1009031L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) The particular buffer cache throwing the exception.
<b>Probable Cause</b>	No additional information available.
<b>Error 1009032</b>	<b>"%2: Bio ptr must be non-null; buffer=%3} page=%4}. %1"</b>
<b>Constant</b>	EMSG_BUFLIST_BADBIOP
<b>SAP Sybase Error Number</b>	20053
<b>SQL State</b>	QSA32

## Errors and Warnings

<b>Error 1009032</b>	"%2: Bio ptr must be non-null; buffer=%3 page=%4%. %1"
<b>SQL Code</b>	-1009032L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) The particular buffer cache throwing the exception.
<b>Parameter 3</b>	3) Information about the sbuf involved, if any.
<b>Parameter 4</b>	4) Information about the disk block header involved, if any.
<b>Probable Cause</b>	No additional information available.
<b>Error 1009033</b>	"%2: Blocksize must be a multiple of sizeof(hos_mrdtype & hos_uint) and > 0; buffer=%3 page=%4%. %1"
<b>Constant</b>	EMSG_BUFLMAN_BADBLOCKSIZE
<b>SAP Sybase Error Number</b>	20054
<b>SQL State</b>	QSA33
<b>SQL Code</b>	-1009033L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) The particular buffer cache throwing the exception.
<b>Parameter 3</b>	3) Information about the sbuf involved, if any.
<b>Parameter 4</b>	4) Information about the disk block header involved, if any.
<b>Probable Cause</b>	No additional information available.
<b>Error 1009034</b>	"%2: The number of blocks must be > 0; buffer=%3 page=%4%. %1"
<b>Constant</b>	EMSG_BUFLMAN_BADNUMOFBLKS

<b>Error 1009034</b>	<b>"%2: The number of blocks must be &gt; 0; buffer=%3} page=%4}. %1"</b>
<b>SAP Sybase Error Number</b>	20055
<b>SQL State</b>	QSA34
<b>SQL Code</b>	-1009034L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) The particular buffer cache throwing the exception.
<b>Parameter 3</b>	3) Information about the sbuf involved, if any.
<b>Parameter 4</b>	4) Information about the disk block header involved, if any.
<b>Probable Cause</b>	No additional information available.
<b>Error 1009035</b>	<b>"%2: The logical or physical block number must be &gt; 0; buffer=%3} page=%4}. %1"</b>
<b>Constant</b>	EMSG_BUFLIST_BADBLOCKNUMBER
<b>SAP Sybase Error Number</b>	20056
<b>SQL State</b>	QSA35
<b>SQL Code</b>	-1009035L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) The particular buffer cache throwing the exception.
<b>Parameter 3</b>	3) Information about the sbuf involved, if any.
<b>Parameter 4</b>	4) Information about the disk block header involved, if any.

## Errors and Warnings

<b>Error 1009035</b>	<b>"%2: The logical or physical block number must be &gt; 0; buffer=%3} page=%4}. %1"</b>
<b>Probable Cause</b>	Typically, production builds will abort here if trying to Find() a page that does not exist (non-existent pages have a 0 pbn in the blockmap entry).
<b>Error 1009036</b>	<b>"%2: Invalid compression type; buffer=%3} page=%4}. %1"</b>
<b>Constant</b>	EMSG_BUFSIZE_TYPE
<b>SAP Sybase Error Number</b>	20057
<b>SQL State</b>	QSA36
<b>SQL Code</b>	-1009036L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) The particular buffer cache throwing the exception.
<b>Parameter 3</b>	3) Information about the sbuf involved, if any.
<b>Parameter 4</b>	4) Information about the disk block header involved, if any.
<b>Probable Cause</b>	No additional information available.
<b>Error 1009037</b>	<b>"%2: Buffer was not locked when it should have been; buffer=%3} page=%4}. %1"</b>
<b>Constant</b>	EMSG_BUFSIZE_TYPE
<b>SAP Sybase Error Number</b>	20058
<b>SQL State</b>	QSA37
<b>SQL Code</b>	-1009037L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	1) location of the exception

<b>Error 1009037</b>	<b>"%2: Buffer was not locked when it should have been; buffer={%3} page={%4}. %1"</b>
<b>Parameter 2</b>	2) The particular buffer cache throwing the exception.
<b>Parameter 3</b>	3) Information about the sbuf involved, if any.
<b>Parameter 4</b>	4) Information about the disk block header involved, if any.
<b>Probable Cause</b>	No additional information available.
<b>Error 1009038</b>	<b>"%2: Tried to write to a readonly database; buffer={%3} page={%4}. %1"</b>
<b>Constant</b>	EMSG_BUFLMAN_MUSTHAVEWACCESS
<b>SAP Sybase Error Number</b>	20059
<b>SQL State</b>	QSA38
<b>SQL Code</b>	-1009038L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) The particular buffer cache throwing the exception.
<b>Parameter 3</b>	3) Information about the sbuf involved, if any.
<b>Parameter 4</b>	4) Information about the disk block header involved, if any.
<b>Probable Cause</b>	No additional information available.
<b>Error 1009039</b>	<b>"%2: An error was detected on a database page. You may have a damaged index. For additional information, please check your IQ message file or run sp_iqcheckdb. %1"</b>
<b>Constant</b>	EMSG_BUFLMAN_INCORRECT_DISKBLOCKHEADER
<b>SAP Sybase Error Number</b>	20060
<b>SQL State</b>	QSA39
<b>SQL Code</b>	-1009039L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1009039</b>	"%2: An error was detected on a database page. You may have a damaged index. For additional information, please check your IQ message file or run sp_iqcheckdb. %1"
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) The particular buffer cache throwing the exception.
<b>Probable Cause</b>	When we read a page from the database, we detected that its header was either corrupt or that the header did not correspond to the page we thought we were reading. This is normally a fatal error; the database itself is likely to be corrupt.
<b>Error 1009040</b>	"%2: Memory & disk block number mismatch; buffer=%3 page=%4. %1"
<b>Constant</b>	EMSG_BUFSMAN_BIO_MISMATCH_BLOCK
<b>SAP Sybase Error Number</b>	20061
<b>SQL State</b>	QSA40
<b>SQL Code</b>	-1009040L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) The particular buffer cache throwing the exception.
<b>Parameter 3</b>	3) Information about the sbuf involved, if any.
<b>Parameter 4</b>	4) Information about the disk block header involved, if any.
<b>Probable Cause</b>	No additional information available.
<b>Error 1009041</b>	"%2: Memory & disk block type mismatch; buffer=%3 page=%4. %1"
<b>Constant</b>	EMSG_BUFSMAN_BIO_MISMATCH_BTYP
<b>SAP Sybase Error Number</b>	20062

<b>Error 1009041</b>	<b>"%2: Memory &amp; disk block type mismatch; buffer=%3 page=%4}. %1"</b>
<b>SQL State</b>	QSA41
<b>SQL Code</b>	-1009041L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) The particular buffer cache throwing the exception.
<b>Parameter 3</b>	3) Information about the sbuf involved, if any.
<b>Parameter 4</b>	4) Information about the disk block header involved, if any.
<b>Probable Cause</b>	No additional information available.
<b>Error 1009042</b>	<b>"%2: Attempted to write a page that was not dirty; buffer=%3 page=%4}. %1"</b>
<b>Constant</b>	EMSG_BUFSMAN_BIO_NOTDIRTY
<b>SAP Sybase Error Number</b>	20063
<b>SQL State</b>	QSA42
<b>SQL Code</b>	-1009042L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) The particular buffer cache throwing the exception.
<b>Parameter 3</b>	3) Information about the sbuf involved, if any.
<b>Parameter 4</b>	4) Information about the disk block header involved, if any.
<b>Probable Cause</b>	No additional information available.

## Errors and Warnings

<b>Error 1009043</b>	"%2: Memory & disk number of blocks mismatch. %1"
<b>Constant</b>	EMSG_BUFSMAN_BIO_MISMATCH_NBLKS
<b>SAP Sybase Error Number</b>	20064
<b>SQL State</b>	QSA43
<b>SQL Code</b>	-1009043L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) The particular buffer cache throwing the exception.
<b>Probable Cause</b>	No additional information available.

## Messages 1009044 through 1009064

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1009044</b>	"An IO error was encountered while reading a database page in %2 DBSpace. %1"
<b>Constant</b>	EMSG_BUFSMAN_BIO_READ_ERROR
<b>SAP Sybase Error Number</b>	20065
<b>SQL State</b>	QSA44
<b>SQL Code</b>	-1009044L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) dbspace name
<b>Probable Cause</b>	No additional information available.

<b>Error 1009045</b>	"Bitmap failed internal checks. You may have a damaged index. Please check your IQ message file for additional information. %1"
<b>Constant</b>	EMSG_BM_VERIFY
<b>SAP Sybase Error Number</b>	20066
<b>SQL State</b>	QSA45
<b>SQL Code</b>	-1009045L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1009046</b>	"%2: An error was detected on a database page. You may have a damaged index. For additional information, please check your IQ message file or run sp_iqcheckdb. %1"
<b>Constant</b>	EMSG_BUFLMAN_DECOMPRESSION_ERROR
<b>SAP Sybase Error Number</b>	20067
<b>SQL State</b>	QSA46
<b>SQL Code</b>	-1009046L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) The particular buffer cache throwing the exception.
<b>Probable Cause</b>	No additional information available.
<b>Error 1009047</b>	"%2: Blockmap info error; bmp=%3. %1"
<b>Constant</b>	EMSG_BUFLMAN_BLOCKMAP_INFO_ERROR
<b>SAP Sybase Error Number</b>	20068

## Errors and Warnings

<b>Error 1009047</b>	"%2: Blockmap info error; bmp=%3. %1"
<b>SQL State</b>	QSA47
<b>SQL Code</b>	-1009047L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	14 on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) The particular buffer cache throwing the exception.
<b>Parameter 3</b>	3) Information about the blockmap
<b>Probable Cause</b>	No additional information available.
<b>Error 1009048</b>	"%2: Tried to destroy a userlocked buffer; buffer=%3 page=%4. %1"
<b>Constant</b>	EMSG_BUFLMAN_LOCK_DURINGDESTROY
<b>SAP Sybase Error Number</b>	20069
<b>SQL State</b>	QSA48
<b>SQL Code</b>	-1009048L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) The particular buffer cache throwing the exception.
<b>Parameter 3</b>	3) Information about the sbuf involved, if any.
<b>Parameter 4</b>	4) Information about the disk block header involved, if any.
<b>Probable Cause</b>	No additional information available.
<b>Error 1009049</b>	"%2: The buffer manager is in an inconsistent state; buffer=%3 page=%4. %1"
<b>Constant</b>	EMSG_BUFLMAN_CORRUPT

<b>Error 1009049</b>	<b>"%2: The buffer manager is in an inconsistent state; buffer=%3} page=%4}. %1"</b>
<b>SAP Sybase Error Number</b>	20070
<b>SQL State</b>	QSA49
<b>SQL Code</b>	-1009049L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) The particular buffer cache throwing the exception.
<b>Parameter 3</b>	3) Information about the sbuf involved, if any.
<b>Parameter 4</b>	4) Information about the disk block header involved, if any.
<b>Probable Cause</b>	No additional information available.
<b>Error 1009050</b>	<b>"%2: Btype specific truncation method returned invalid size for btype. %1"</b>
<b>Constant</b>	EMSG_BUFLIST_TRUNC_BAD
<b>SAP Sybase Error Number</b>	20071
<b>SQL State</b>	QSA50
<b>SQL Code</b>	-1009050L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) The particular buffer cache throwing the exception.
<b>Probable Cause</b>	No additional information available.
<b>Error 1009051</b>	<b>"An index cannot be created on a char, varchar or varbinary column greater than 255 characters. %1"</b>
<b>Constant</b>	EMSG_VARCHAR_INDEX_NOT_SUPPORTED

## Errors and Warnings

<b>Error 1009051</b>	"An index cannot be created on a char, varchar or varbinary column greater than 255 characters. %1"
<b>SAP Sybase Error Number</b>	20072
<b>SQL State</b>	QSA51
<b>SQL Code</b>	-1009051L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1009052</b>	"Internal error. Index %2 does not yet support the requested operation. %1"
<b>Constant</b>	EMSG_INDEX_OPERATION_NOT_IMPLEMENTED
<b>SAP Sybase Error Number</b>	20073
<b>SQL State</b>	QSA52
<b>SQL Code</b>	-1009052L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	name of the index
<b>Probable Cause</b>	An operation, for example SUM, was forwarded to an index, for example HG, that does not directly implement the operation. Normally, this should not be possible, but can be forced by setting command options.
<b>Error 1009053</b>	"%2: s_dbmvbio WriteCheck failed; buffer=%3 page=%4. %1"
<b>Constant</b>	EMSG_BUFSMAN_BIO_WRITECHECK
<b>SAP Sybase Error Number</b>	20074

<b>Error 1009053</b>	<b>"%2: s_dbmvbio WriteCheck failed; buffer=%3 page=%4}. %1"</b>
<b>SQL State</b>	QSA53
<b>SQL Code</b>	-1009053L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) The particular buffer cache throwing the exception.
<b>Parameter 3</b>	3) Information about the sbuf involved, if any.
<b>Parameter 4</b>	4) Information about the disk block header involved, if any.
<b>Probable Cause</b>	No additional information available.
<b>Error 1009054</b>	<b>"Command prohibited on a multiplex coordinator, %1"</b>
<b>Constant</b>	EMSG_NOCMD_MPX_WRITE
<b>SAP Sybase Error Number</b>	20075
<b>SQL State</b>	QSA54
<b>SQL Code</b>	-1009054L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Command not allowed on a multiplex coordinator
<b>Error 1009055</b>	<b>"Command prohibited on a multiplex query server, %1"</b>
<b>Constant</b>	EMSG_NOCMD_MPX_QUERY
<b>SAP Sybase Error Number</b>	20076
<b>SQL State</b>	QSA55
<b>SQL Code</b>	-1009055L

## Errors and Warnings

<b>Error 1009055</b>	<b>"Command prohibited on a multiplex query server, %1"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Command not allowed on a multiplex query server
<b>Error 1009056</b>	<b>"Command prohibited on a multiplex server, %1"</b>
<b>Constant</b>	EMSG_NOCMD_MPX_SERVER
<b>SAP Sybase Error Number</b>	20077
<b>SQL State</b>	QSA56
<b>SQL Code</b>	-1009056L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Command not allowed on a multiplex server
<b>Error 1009057</b>	<b>"Cannot make all dbspaces readonly while there are active or uncheckpointed readwrite transactions, %1"</b>
<b>Constant</b>	EMSG_CANNOT_ALTER_TOALLRO
<b>SAP Sybase Error Number</b>	20078
<b>SQL State</b>	QSA57
<b>SQL Code</b>	-1009057L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Cannot make the last rw dbspace ro while there is rw activity.

<b>Error 1009058</b>	<b>"There are no dbspaces open in readwrite mode for this RW operation, %1"</b>
<b>Constant</b>	EMSG_NO_RWDBSPACE
<b>SAP Sybase Error Number</b>	20079
<b>SQL State</b>	QSA58
<b>SQL Code</b>	-1009058L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1009059</b>	<b>"Alter dbspace relocate requires at least one other readwrite dbspace (%2). %1"</b>
<b>Constant</b>	EMSG_SDBEXT_NEEDRWFORRR
<b>SAP Sybase Error Number</b>	20080
<b>SQL State</b>	QSA59
<b>SQL Code</b>	-1009059L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	dbspace name
<b>Probable Cause</b>	Cannot alter the only readwrite dbspace to relocate mode.
<b>Error 1009060</b>	<b>"Cannot alter this dbspace to relocate mode without a readwrite dbspace (%2). %1"</b>
<b>Constant</b>	EMSG_SDBEXT_CANNOT_ALTER_RR
<b>SAP Sybase Error Number</b>	20081
<b>SQL State</b>	QSA60

## Errors and Warnings

<b>Error 1009060</b>	<b>"Cannot alter this dbspace to relocate mode without a readwrite dbspace (%2). %1"</b>
<b>SQL Code</b>	-1009060L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	dbspace name
<b>Probable Cause</b>	Cannot alter the readonly segment that contains the db identity to relocate mode.
<b>Error 1009061</b>	<b>"There must be at least one readwrite dbspace and one relocate dbspace to relocate data. %1"</b>
<b>Constant</b>	EMSG_NOT_OK_TO_RELOCATE
<b>SAP Sybase Error Number</b>	20082
<b>SQL State</b>	QSA61
<b>SQL Code</b>	-1009061L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Must have at least one RW dbspace and one RR dbspace for sp_iq-relocate
<b>Error 1009063</b>	<b>"Cannot alter this dbspace from relocate mode to readonly mode while there are active readwrite transactions that may be using it. %1"</b>
<b>Constant</b>	EMSG_CANNOT_ALTER_RRTORO
<b>SAP Sybase Error Number</b>	20084
<b>SQL State</b>	QSA63
<b>SQL Code</b>	-1009063L

<b>Error 1009063</b>	"Cannot alter this dbspace from relocate mode to readonly mode while there are active readwrite transactions that may be using it. %1"
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1009064</b>	"Cannot create or add file %2 for dbspace %3 until new readwrite space is added to dbspace %4 to hold the new freelist. %1"
<b>Constant</b>	EMSG_SDBEXT_NO_FREELIST_SPACE
<b>SAP Sybase Error Number</b>	20085
<b>SQL State</b>	QSA64
<b>SQL Code</b>	-1009064L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	pathname of file being created
<b>Parameter 3</b>	name of dbspace for which file is being created
<b>Parameter 4</b>	name of IQ_SYSTEM_MAIN dbspace
<b>Probable Cause</b>	When creating a new dbspace in the IQ MAIN STORE, or creating a new file for a dbspace other than IQ_SYSTEM_MAIN in the IQ MAIN STORE, there must be sufficient freelist space available to describe the physical blocks we are adding to the database. If this is not the case, the above error occurs. (The space for the freelist can only be allocated in readwrite IQ_SYSTEM_MAIN files.) The corrective action is to first add a new file to the IQ_SYSTEM_MAIN dbspace so that new freelist space becomes available.

**Messages 1009065 through 1009084**

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1009065</b>	<b>"Operation '%2' not allowed in forced recovery. %1"</b>
<b>Constant</b>	EMSG_DBSPACE_NOT_IN_FORCEDRECOVERY
<b>SAP Sybase Error Number</b>	20086
<b>SQL State</b>	QSA65
<b>SQL Code</b>	-1009065L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Dbspace name
<b>Probable Cause</b>	Certain operations are not permitted in forced recovery
<b>Error 1009066</b>	<b>"Cannot execute '%2' yet since previous alter command is not yet propagated through the multiplex. Try again. %1"</b>
<b>Constant</b>	EMSG_CMD_NOT_REPLAYED
<b>SAP Sybase Error Number</b>	20087
<b>SQL State</b>	QSA66
<b>SQL Code</b>	-1009066L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Dbspace name
<b>Probable Cause</b>	The command cannot be executed since the previous alter/create command has not propagated through multiplex yet.

<b>Error 1009067</b>	"%1"
<b>Constant</b>	EMSG_RFU_QSA67
<b>SAP Sybase Error Number</b>	20088
<b>SQL State</b>	QSA67
<b>SQL Code</b>	-1009067L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1009068</b>	"Tried to insert a duplicate entry. %1"
<b>Constant</b>	EMSG_HASHTB_DUPENTRY
<b>SAP Sybase Error Number</b>	20089
<b>SQL State</b>	QSA68
<b>SQL Code</b>	-1009068L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1009069</b>	"Could not find key in hashtable"
<b>Constant</b>	EMSG_HASHTB_KEYNOTFOUND
<b>SAP Sybase Error Number</b>	20090
<b>SQL State</b>	QSA69
<b>SQL Code</b>	-1009069L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 1009069</b>	"Could not find key in hashtable"
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1009070</b>	"Hashtable is full"
<b>Constant</b>	EMSG_HASHTB_FULL
<b>SAP Sybase Error Number</b>	20091
<b>SQL State</b>	QSA70
<b>SQL Code</b>	-1009070L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1009071</b>	"Hash input key descriptor has zero fields (%2, %3). %1"
<b>Constant</b>	EMSG_PHASH_NOKEY
<b>SAP Sybase Error Number</b>	20092
<b>SQL State</b>	QSA71
<b>SQL Code</b>	-1009071L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) major context (hos_StatsObj::SubStatementId, usually dfo number)
<b>Parameter 3</b>	3) minor context (s_phash::StatMinorContext, see s_phash.h for enum)
<b>Probable Cause</b>	No additional information available.

<b>Error 1009072</b>	"Insufficient buffers for hash. (%2, %3). %1"
<b>Constant</b>	EMSG_PHASH_MAXBUFFERS
<b>SAP Sybase Error Number</b>	20093
<b>SQL State</b>	QSA72
<b>SQL Code</b>	-1009072L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) major context (hos_StatsObj::SubStatementId, usually dfo number)
<b>Parameter 3</b>	3) minor context (s_phash::StatMinorContext, see s_phash.h for enum)
<b>Probable Cause</b>	Specifically, the number of estimated buffers given to the hash object exceeds the size of the buffer cache.

<b>Error 1009073</b>	"Hash function can't handle this datatype (%2, %3). %1"
<b>Constant</b>	EMSG_PHASH_HASHDT
<b>SAP Sybase Error Number</b>	20094
<b>SQL State</b>	QSA73
<b>SQL Code</b>	-1009073L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) major context (hos_StatsObj::SubStatementId, usually dfo number)
<b>Parameter 3</b>	3) minor context (s_phash::StatMinorContext, see s_phash.h for enum)
<b>Probable Cause</b>	No additional information available.

## Errors and Warnings

<b>Error 1009074</b>	<b>"Key length in hash equality function is zero (%2, %3). %1"</b>
<b>Constant</b>	EMSG_PHASH_EQUALKEYLEN
<b>SAP Sybase Error Number</b>	20095
<b>SQL State</b>	QSA74
<b>SQL Code</b>	-1009074L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) major context (hos_StatsObj::SubStatementId, usually dfo number)
<b>Parameter 3</b>	3) minor context (s_phash::StatMinorContext, see s_phash.h for enum)
<b>Probable Cause</b>	No additional information available.
<b>Error 1009075</b>	<b>"Buffer mapper init incorrect (%2, %3). %1"</b>
<b>Constant</b>	EMSG_PHASH_BUFMAPINIT
<b>SAP Sybase Error Number</b>	20096
<b>SQL State</b>	QSA75
<b>SQL Code</b>	-1009075L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) major context (hos_StatsObj::SubStatementId, usually dfo number)
<b>Parameter 3</b>	3) minor context (s_phash::StatMinorContext, see s_phash.h for enum)
<b>Probable Cause</b>	No additional information available.

<b>Error 1009076</b>	<b>"Internal hash error; buffer was previously created: %2 (%3, %4). %1"</b>
<b>Constant</b>	EMSG_PHASH_BUFDDOUBLECREATE
<b>SAP Sybase Error Number</b>	20097
<b>SQL State</b>	QSA76
<b>SQL Code</b>	-1009076L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) Buffer Number.
<b>Parameter 3</b>	3) major context (hos_StatsObj::SubStatementId, usually dfo number)
<b>Parameter 4</b>	4) minor context (s_phash::StatMinorContext, see s_phash.h for enum)
<b>Probable Cause</b>	No additional information available.
<b>Error 1009077</b>	<b>"Internal hash error; next data entry should be valid (%2, %3). %1"</b>
<b>Constant</b>	EMSG_PHASH_INVALID_NEXTENTRY
<b>SAP Sybase Error Number</b>	20098
<b>SQL State</b>	QSA77
<b>SQL Code</b>	-1009077L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) major context (hos_StatsObj::SubStatementId, usually dfo number)

## Errors and Warnings

<b>Error 1009077</b>	<b>"Internal hash error; next data entry should be valid (%2, %3). %1"</b>
<b>Parameter 3</b>	3) minor context (s_phash::StatMinorContext, see s_phash.h for enum)
<b>Probable Cause</b>	No additional information available.
<b>Error 1009078</b>	<b>"Internal hash error; buffer not pinned (%2, %3). %1"</b>
<b>Constant</b>	EMSG_PHASH_NOT_PINNED
<b>SAP Sybase Error Number</b>	20099
<b>SQL State</b>	QSA78
<b>SQL Code</b>	-1009078L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) major context (hos_StatsObj::SubStatementId, usually dfo number)
<b>Parameter 3</b>	3) minor context (s_phash::StatMinorContext, see s_phash.h for enum)
<b>Probable Cause</b>	No additional information available.
<b>Error 1009079</b>	<b>"Internal hash error; too many buffers left in use: %2 (%3, %4). %1"</b>
<b>Constant</b>	EMSG_PHASH_INUSE_HIGH
<b>SAP Sybase Error Number</b>	20100
<b>SQL State</b>	QSA79
<b>SQL Code</b>	-1009079L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	1) location of the exception

<b>Error 1009079</b>	<b>"Internal hash error; too many buffers left in use: %2 (%3, %4). %1"</b>
<b>Parameter 2</b>	2) Number of buffers.
<b>Parameter 3</b>	3) major context (hos_StatsObj::SubStatementId, usually dfo number)
<b>Parameter 4</b>	4) minor context (s_phash::StatMinorContext, see s_phash.h for enum)
<b>Probable Cause</b>	No additional information available.
<b>Error 1009080</b>	<b>"Key doesn't fit on a single database page: %2 (%3, %4). %1"</b>
<b>Constant</b>	EMSG_PHASH_KEY_TOO_LARGE
<b>SAP Sybase Error Number</b>	20101
<b>SQL State</b>	QSA80
<b>SQL Code</b>	-1009080L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) Key size.
<b>Parameter 3</b>	3) major context (hos_StatsObj::SubStatementId, usually dfo number)
<b>Parameter 4</b>	4) minor context (s_phash::StatMinorContext, see s_phash.h for enum)
<b>Probable Cause</b>	No additional information available.
<b>Error 1009081</b>	<b>"Data doesn't fit on a single database page: %2 (%3, %4). %1"</b>
<b>Constant</b>	EMSG_PHASH_DATA_TOO_LARGE
<b>SAP Sybase Error Number</b>	20102
<b>SQL State</b>	QSA81

## Errors and Warnings

<b>Error 1009081</b>	<b>"Data doesn't fit on a single database page: %2 (%3, %4).%1"</b>
<b>SQL Code</b>	-1009081L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) Data size.
<b>Parameter 3</b>	3) major context (hos_StatsObj::SubStatementId, usually dfo number)
<b>Parameter 4</b>	4) minor context (s_phash::StatMinorContext, see s_phash.h for enum)
<b>Probable Cause</b>	No additional information available.
<b>Error 1009082</b>	<b>"Hash object has no data to retrieve, only keys (%2, %3).%1"</b>
<b>Constant</b>	EMSG_PHASH_NO_DATA
<b>SAP Sybase Error Number</b>	20103
<b>SQL State</b>	QSA82
<b>SQL Code</b>	-1009082L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) major context (hos_StatsObj::SubStatementId, usually dfo number)
<b>Parameter 3</b>	3) minor context (s_phash::StatMinorContext, see s_phash.h for enum)
<b>Probable Cause</b>	No additional information available.

<b>Error 1009083</b>	"DBSpace '%2' must be OFFLINE for ALTER PATH. %1"
<b>Constant</b>	EMSG_ALTER_PATH_REQUIRES_OFFLINE_DBSPACE
<b>SAP Sybase Error Number</b>	20104
<b>SQL State</b>	QSA83
<b>SQL Code</b>	-1009083L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	dbspace name
<b>Probable Cause</b>	No additional information available.

<b>Error 1009084</b>	"Error opening DBSPACE '%2'. %1"
<b>Constant</b>	EMSG_DBSPACE_OPEN_ERROR
<b>SAP Sybase Error Number</b>	20105
<b>SQL State</b>	QSA84
<b>SQL Code</b>	-1009084L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	dbspace name
<b>Probable Cause</b>	No additional information available.

## Messages 1009085 through 1009104

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1009085</b>	"DBFILE '%2' is not valid. The catalog DBSpaceID is incorrect. DBSpaceID found: %3 DBSpaceID expected: %4. This segment cannot be used. %1"
<b>Constant</b>	EMSG_BAD_CAT_DBSPACEID
<b>SAP Sybase Error Number</b>	20106
<b>SQL State</b>	QSA85
<b>SQL Code</b>	-1009085L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	file path
<b>Parameter 3</b>	dbspace_id found
<b>Parameter 4</b>	dbspace_id expected
<b>Probable Cause</b>	No additional information available.

<b>Error 1009086</b>	"Error opening DBFILE '%2'. %1"
<b>Constant</b>	EMSG_DBFILE_OPEN_ERROR
<b>SAP Sybase Error Number</b>	20107
<b>SQL State</b>	QSA86
<b>SQL Code</b>	-1009086L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	file path

<b>Error 1009086</b>	"Error opening DBFILE '%2'. %1"
<b>Probable Cause</b>	No additional information available.
<b>Error 1009087</b>	<b>"The dbfile '%2' must be in READONLY mode for this operation. %1"</b>
<b>Constant</b>	EMSG_DBFILE_MUST_BE_RO
<b>SAP Sybase Error Number</b>	20108
<b>SQL State</b>	QSA87
<b>SQL Code</b>	-1009087L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	file path
<b>Probable Cause</b>	No additional information available.
<b>Error 1009088</b>	<b>"Attempted to add a duplicate key. %1"</b>
<b>Constant</b>	EMSG_BT_DUPLICATE
<b>SAP Sybase Error Number</b>	20109
<b>SQL State</b>	QSA88
<b>SQL Code</b>	-1009088L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1009089</b>	<b>"The size of the value is more than the maximum allowed for the field. Value: %2 %1"</b>
<b>Constant</b>	EMSG_BT_KEYTOOBIG

## Errors and Warnings

<b>Error 1009089</b>	<b>"The size of the value is more than the maximum allowed for the field. Value: %2 %1"</b>
<b>SAP Sybase Error Number</b>	20110
<b>SQL State</b>	QSA89
<b>SQL Code</b>	-1009089L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Key value.
<b>Probable Cause</b>	No additional information available.
<b>Error 1009090</b>	<b>"Page size selected is too small for this datatype. %1"</b>
<b>Constant</b>	EMSG_BT_LARGERPAGE
<b>SAP Sybase Error Number</b>	20111
<b>SQL State</b>	QSA90
<b>SQL Code</b>	-1009090L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Parameter 1 description
<b>Probable Cause</b>	No additional information available.
<b>Error 1009091</b>	<b>"Attempt to create a B-Tree with RecordSize+KeySize too large. %1"</b>
<b>Constant</b>	EMSG_BT_SIZEERROR
<b>SAP Sybase Error Number</b>	20112
<b>SQL State</b>	QSA91
<b>SQL Code</b>	-1009091L

<b>Error 1009091</b>	<b>"Attempt to create a B-Tree with RecordSize+KeySize too large. %1"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1009092</b>	<b>"Must provide a key comparison routine on object creation. %1"</b>
<b>Constant</b>	EMSG_BT_NOKEYCOMPARE
<b>SAP Sybase Error Number</b>	20113
<b>SQL State</b>	QSA92
<b>SQL Code</b>	-1009092L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1009093</b>	<b>"The maximum key size must be between 1 and 5300. Key size: %2 %1"</b>
<b>Constant</b>	EMSG_BT_MAXKEYSIZEWRONG
<b>SAP Sybase Error Number</b>	20114
<b>SQL State</b>	QSA93
<b>SQL Code</b>	-1009093L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception

## Errors and Warnings

<b>Error 1009093</b>	<b>"The maximum key size must be between 1 and 5300. Key size: %2 %1"</b>
<b>Parameter 2</b>	Key Size in error.
<b>Probable Cause</b>	No additional information available.
<b>Error 1009094</b>	<b>"Cannot use raw partition for MESSAGE LOG or ROW LOG. %1"</b>
<b>Constant</b>	EMSG_SVIOLATION_LOG_ON_RAW
<b>SAP Sybase Error Number</b>	20115
<b>SQL State</b>	QSA94
<b>SQL Code</b>	-1009094L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	The MESSAGE LOG and ROW LOG files for load integrity constraint handling must be regular files. They cannot be raw partitions.
<b>Error 1009095</b>	<b>"MESSAGE LOG and ROW LOG cannot be the same on-disk file. %1"</b>
<b>Constant</b>	EMSG_SVIOLATION_LOGS_SAMEFILE
<b>SAP Sybase Error Number</b>	20116
<b>SQL State</b>	QSA95
<b>SQL Code</b>	-1009095L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	The MESSAGE LOG and ROW LOG files cannot be the same on-disk files.

<b>Error 1009096</b>	<b>"%3 integrity constraint limit (%2) exceeded. %1"</b>
<b>Constant</b>	EMSG_SVIOLATION_IGNORE_LIMIT_EXCEEDED
<b>SAP Sybase Error Number</b>	20117
<b>SQL State</b>	QSA96
<b>SQL Code</b>	-1009096L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	user specified integrity constraint limit
<b>Parameter 3</b>	type of integrity constraint violation specified by the user
<b>Probable Cause</b>	The number of integrity constraint violations for the given type has been exceeded during the LOAD. The LOAD will rollback.
<b>Error 1009097</b>	<b>"Cumulative total (%2) for all integrity constraint violations exceeded. %1"</b>
<b>Constant</b>	EMSG_SVIOLATION_ALL_LIMIT_EXCEEDED
<b>SAP Sybase Error Number</b>	20118
<b>SQL State</b>	QSA97
<b>SQL Code</b>	-1009097L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of exception
<b>Parameter 2</b>	maximum number of constraint violations to ignore
<b>Probable Cause</b>	The total number of NULL, UNIQUE, DATA VALUE, and FOREIGN KEY integrity constraint violations has exceeded the user specified limit.

## Errors and Warnings

<b>Error 1009098</b>	"Invalid MESSAGE LOG or ROW LOG filename. %1"
<b>Constant</b>	EMSG_SVIOLATION_INVALID_FILENAME
<b>SAP Sybase Error Number</b>	20119
<b>SQL State</b>	QSA98
<b>SQL Code</b>	-1009098L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of exception
<b>Probable Cause</b>	A bad filename (perhaps zero-length) was specified for either the MESSAGE LOG or ROW LOG files on the LOAD statement.
<b>Error 1009099</b>	"%1"
<b>Constant</b>	EMSG_RFU_QSA99
<b>SAP Sybase Error Number</b>	20120
<b>SQL State</b>	QSA99
<b>SQL Code</b>	-1009099L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1009100</b>	<b>"Database segment '%2' is not valid. It is of type '%3'. Type BTYPE_DBEXT was expected. This segment cannot be used. %1"</b>
<b>Constant</b>	EMSG_SDBEXT_BAD_BTYP
<b>SAP Sybase Error Number</b>	20121
<b>SQL State</b>	QSB00

<b>Error 1009100</b>	<b>"Database segment '%2' is not valid. It is of type '%3'. Type BTTYPE_DBEXT was expected. This segment cannot be used. %1"</b>
<b>SQL Code</b>	-1009100L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	Name of the segment.
<b>Parameter 3</b>	Internal segment type found.
<b>Probable Cause</b>	The segment type written to the segment header was found not to be of the expected type. You will need to restore your database from backup.
<b>Error 1009101</b>	<b>"Database segment '%2' is not valid. PhysicalNBlocks Found: %3 PhysicalNBlocks Expected: 1. This segment cannot be used. %1"</b>
<b>Constant</b>	EMSG_SDBEXT_BAD_NUMPHYSBLOCKS
<b>SAP Sybase Error Number</b>	20122
<b>SQL State</b>	QSB01
<b>SQL Code</b>	-1009101L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	Name of the segment.
<b>Parameter 3</b>	Number of Physical Blocks found.
<b>Probable Cause</b>	The number of physical blocks read from the segment header is incorrect. You will need to restore your database from backup.

## Errors and Warnings

<b>Error 1009102</b>	<b>"Incorrect HG Index Version (%2): Index must be dropped by previous version of Sybase IQ and recreated. %1"</b>
<b>Constant</b>	EMSG_ERROR_VERSION
<b>SAP Sybase Error Number</b>	20123
<b>SQL State</b>	QSB02
<b>SQL Code</b>	-1009102L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Incorrect version of index.
<b>Probable Cause</b>	No additional information available.
<b>Error 1009103</b>	<b>"Number of unique values exceeded for index. %2 %3 %1"</b>
<b>Constant</b>	EMSG_ERROR_KVTMAX
<b>SAP Sybase Error Number</b>	20124
<b>SQL State</b>	QSB03
<b>SQL Code</b>	-1009103L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Index.
<b>Parameter 3</b>	Number of values.
<b>Probable Cause</b>	No additional information available.
<b>Error 1009104</b>	<b>"Bad args, both values must be &gt;= 1 (%2 %3). %1"</b>
<b>Constant</b>	EMSG_VDO_BADARGS
<b>SAP Sybase Error Number</b>	20125

<b>Error 1009104</b>	"Bad args, both values must be >= 1 (%2 %3). %1"
<b>SQL State</b>	QSB04
<b>SQL Code</b>	-1009104L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Value 1
<b>Parameter 3</b>	Value 2
<b>Probable Cause</b>	No additional information available.

## Messages 1009105 through 1009124

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1009105</b>	"Could not find block: %2. %1"
<b>Constant</b>	EMSG_VDO_BLKNOTFOUND
<b>SAP Sybase Error Number</b>	20126
<b>SQL State</b>	QSB05
<b>SQL Code</b>	-1009105L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Block Number
<b>Probable Cause</b>	No additional information available.

<b>Error 1009106</b>	"DBFILE '%2' is not valid. The catalog file id is incorrect. FileID found: %3 FileID expected: %4. This segment cannot be used. %1"
<b>Constant</b>	EMSG_SDBEXT_BAD_CATFILEID

## Errors and Warnings

<b>Error 1009106</b>	<b>"DBFILE '%2' is not valid. The catalog file id is incorrect. FileID found: %3 FileID expected: %4. This segment cannot be used. %1"</b>
<b>SAP Sybase Error Number</b>	20127
<b>SQL State</b>	QSB06
<b>SQL Code</b>	-1009106L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	Segment name.
<b>Parameter 3</b>	FileID found on the disk segment header.
<b>Parameter 4</b>	FileID expected to be found on the disk segment header.
<b>Probable Cause</b>	The FileID information stored on the disk segment's header is not correct. The disk segment cannot be used.

<b>Error 1009107</b>	<b>"Duplicate entry for block: %2, record %3. %1"</b>
<b>Constant</b>	EMSG_VDO_DUPENTRY
<b>SAP Sybase Error Number</b>	20128
<b>SQL State</b>	QSB07
<b>SQL Code</b>	-1009107L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Block with duplication entry.
<b>Parameter 3</b>	Duplicate entry.
<b>Probable Cause</b>	No additional information available.

<b>Error 1009108</b>	"Database segment '%2' is not valid. Startblock found in the header: %3 Startblock expected: %4. This segment cannot be used. %1"
<b>Constant</b>	EMSG_SDBEXT_BAD_STARTBLOCK
<b>SAP Sybase Error Number</b>	20129
<b>SQL State</b>	QSB08
<b>SQL Code</b>	-1009108L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	Name of the segment.
<b>Parameter 3</b>	Starting block found in the disk header.
<b>Parameter 4</b>	Starting block expected.
<b>Probable Cause</b>	The start block of the disk segment that was found in the disk segment header is not the same as what was expected. The disk segment cannot be used.

<b>Error 1009109</b>	"Key size %2 is more than the maximum %3. %1"
<b>Constant</b>	EMSG_VDO_KEYTOOBIG
<b>SAP Sybase Error Number</b>	20130
<b>SQL State</b>	QSB09
<b>SQL Code</b>	-1009109L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Key size.
<b>Parameter 3</b>	Max key size.

## Errors and Warnings

<b>Error 1009109</b>	"Key size %2 is more than the maximum %3. %1"
<b>Probable Cause</b>	No additional information available.
<b>Error 1009110</b>	"%1"
<b>Constant</b>	EMSG_RFU_QSB10
<b>SAP Sybase Error Number</b>	20131
<b>SQL State</b>	QSB10
<b>SQL Code</b>	-1009110L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1009111</b>	"Could not find record %2 within block %3. %1"
<b>Constant</b>	EMSG_VDO_RECNOTFOUND
<b>SAP Sybase Error Number</b>	20132
<b>SQL State</b>	QSB11
<b>SQL Code</b>	-1009111L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Record that could not be found.
<b>Parameter 3</b>	Block being searched.
<b>Probable Cause</b>	No additional information available.
<b>Error 1009112</b>	"%1"
<b>Constant</b>	EMSG_RFU_QSB12

<b>Error 1009112</b>	"%1"
<b>SAP Sybase Error Number</b>	20133
<b>SQL State</b>	QSB12
<b>SQL Code</b>	-1009112L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1009113</b>	<b>"Secondary error noted. Semi-Join not ready %2. %1"</b>
<b>Constant</b>	EMSG_SECONDARY_ERR
<b>SAP Sybase Error Number</b>	20134
<b>SQL State</b>	QSB13
<b>SQL Code</b>	-1009113L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	more information about join node for which semi-join is not ready.
<b>Probable Cause</b>	No additional information available.

<b>Error 1009114</b>	<b>"Tried to put too many records %2 into block %3. %1"</b>
<b>Constant</b>	EMSG_VDO_TOOMANYRECS
<b>SAP Sybase Error Number</b>	20135
<b>SQL State</b>	QSB14
<b>SQL Code</b>	-1009114L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 1009114</b>	"Tried to put too many records %2 into block %3. %1"
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Number of records.
<b>Parameter 3</b>	Block being inserted into.
<b>Probable Cause</b>	No additional information available.
<b>Error 1009115</b>	<b>"Database segment '%2' is not valid. %3 imaginary freelist blocks were found, but %4 imaginary freelist blocks were expected. This segment cannot be used. %1"</b>
<b>Constant</b>	EMSG_SDBEXT_DIF_NIBLOCKS
<b>SAP Sybase Error Number</b>	20136
<b>SQL State</b>	QSB15
<b>SQL Code</b>	-1009115L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	14 on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	Name of the segment.
<b>Parameter 3</b>	Number of imaginary freelist blocks recorded in the segment header.
<b>Parameter 4</b>	Number of freelist blocks that were expected to be recorded in the header.
<b>Probable Cause</b>	When a database segment is opened, the segment header is read and the number of freelist blocks read from the header is compared with the number of freelist blocks that are expected to be read from the segment header. If the numbers do not match, the segment cannot be used and the database must be restored from backup.
<b>Error 1009116</b>	<b>"Wrong new() was called. %1"</b>
<b>Constant</b>	EMSG_VDO_WRONGNEW
<b>SAP Sybase Error Number</b>	20137

<b>Error 1009116</b>	"Wrong new() was called. %1"
<b>SQL State</b>	QSB16
<b>SQL Code</b>	-1009116L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1009117</b>	"Update can not do different sized values yet. New size = %2, old size = %3. %1"
<b>Constant</b>	EMSG_VDO_UPDATESIZE
<b>SAP Sybase Error Number</b>	20138
<b>SQL State</b>	QSB17
<b>SQL Code</b>	-1009117L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	New size.
<b>Parameter 3</b>	Old size.
<b>Probable Cause</b>	No additional information available.
<b>Error 1009118</b>	"Database segment '%2' is not valid. %3 freelist blocks were found, but %4 freelist blocks were expected. This segment cannot be used. %1"
<b>Constant</b>	EMSG_SDBEXT_DIF_NFLBLOCKS
<b>SAP Sybase Error Number</b>	20139
<b>SQL State</b>	QSB18

## Errors and Warnings

<b>Error 1009118</b>	"Database segment '%2' is not valid. %3 freelist blocks were found, but %4 freelist blocks were expected. This segment cannot be used. %1"
<b>SQL Code</b>	-1009118L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	Name of the segment.
<b>Parameter 3</b>	Number of freelist blocks recorded in the segment header.
<b>Parameter 4</b>	Number of freelist blocks that were expected to be recorded in the header.
<b>Probable Cause</b>	When a database segment is opened, the segment header is read and the number of freelist blocks read from the header is compared with the number of freelist blocks that are expected to be read from the segment header. If the numbers do not match, the segment cannot be used and the database must be restored from backup.
<b>Error 1009119</b>	"Record size too large for database page size. %1"
<b>Constant</b>	EMSG_SORT_INVALIDRECSIZE
<b>SAP Sybase Error Number</b>	20140
<b>SQL State</b>	QSB19
<b>SQL Code</b>	-1009119L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Warning 1009120</b>	" %1 Sort: Sorted %#2, %3 Recs, %4 Secs"
<b>Constant</b>	EMSG_SORT_INFOSORTED
<b>SAP Sybase Error Number</b>	20141

<b>Warning 1009120</b>	" %1 Sort: Sorted #%2, %3 Recs, %4 Secs"
<b>SQL State</b>	QSB20
<b>SQL Code</b>	1009120L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	What is being sorted.
<b>Parameter 2</b>	Which particular run of the sort.
<b>Parameter 3</b>	How many records were sorted.
<b>Parameter 4</b>	How long the sort took.
<b>Probable Cause</b>	No additional information available.

<b>Warning 1009121</b>	" %1 Sort: Saved #%2, %3 Recs, %4 Secs"
<b>Constant</b>	EMSG_SORT_INFOSAVED
<b>SAP Sybase Error Number</b>	20142
<b>SQL State</b>	QSB21
<b>SQL Code</b>	1009121L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	What is being sorted.
<b>Parameter 2</b>	Which particular run of the sort.
<b>Parameter 3</b>	How many records were sorted.
<b>Parameter 4</b>	How long the sort took.
<b>Probable Cause</b>	No additional information available.

<b>Warning 1009122</b>	" %1 Sort: Merged %2 runs, %3 Secs, %4 runs remaining"
<b>Constant</b>	EMSG_SORT_INFOMERGED
<b>SAP Sybase Error Number</b>	20143

## Errors and Warnings

<b>Warning 1009122</b>	" %1 Sort: Merged %2 runs, %3 Secs, %4 runs remaining"
<b>SQL State</b>	QSB22
<b>SQL Code</b>	1009122L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	What is being sorted.
<b>Parameter 2</b>	How many merged.
<b>Parameter 3</b>	Time taken.
<b>Parameter 4</b>	How many runs still requiring to be merged.
<b>Probable Cause</b>	No additional information available.
<b>Error 1009123</b>	<b>"Database Segment %2 is not valid. Missing DBSignature. This Segment can not be used. %1"</b>
<b>Constant</b>	EMSG_SDBEXT_BAD_DB SIGNATURE
<b>SAP Sybase Error Number</b>	20144
<b>SQL State</b>	QSB23
<b>SQL Code</b>	-1009123L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> 4 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Database segment.
<b>Probable Cause</b>	No additional information available.
<b>Error 1009124</b>	<b>"Database Segment %2, blocksize %3 does not match catalog blocksize of %4. This Segment can not be used. %1"</b>
<b>Constant</b>	EMSG_SDBEXT_DIF_BLOCKSIZE
<b>SAP Sybase Error Number</b>	20145

<b>Error 1009124</b>	"Database Segment %2, blocksize %3 does not match catalog blocksize of %4. This Segment can not be used. %1"
<b>SQL State</b>	QSB24
<b>SQL Code</b>	-1009124L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Database segment.
<b>Parameter 3</b>	Block size.
<b>Parameter 4</b>	Catalog Block size.
<b>Probable Cause</b>	No additional information available.

## Messages 1009125 through 1009145

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1009125</b>	"Database Segment %2, maxcompression %3 does not match catalog maxcompression of %4. This Segment can not be used. %1"
<b>Constant</b>	EMSG_SDBEXT_DIF_MAXCOMPRESSION
<b>SAP Sybase Error Number</b>	20146
<b>SQL State</b>	QSB25
<b>SQL Code</b>	-1009125L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Database segment.
<b>Parameter 3</b>	Max compression

## Errors and Warnings

<b>Error 1009125</b>	<b>"Database Segment %2, maxcompression %3 does not match catalog maxcompression of %4. This Segment can not be used. %1"</b>
<b>Parameter 4</b>	Catalog max compression.
<b>Probable Cause</b>	No additional information available.
<b>Error 1009126</b>	<b>"Database Segment %2, createtime does not match catalog. This Segment can not be used. %1"</b>
<b>Constant</b>	EMSG_SDBEXT_DIF_CREATETIME
<b>SAP Sybase Error Number</b>	20147
<b>SQL State</b>	QSB26
<b>SQL Code</b>	-1009126L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Database segment.
<b>Probable Cause</b>	No additional information available.
<b>Error 1009127</b>	<b>"Database Segment %2, %3 size does not match catalog size of %4. This Segment can not be used. %1"</b>
<b>Constant</b>	EMSG_SDBEXT_DIF_NBLOCKS
<b>SAP Sybase Error Number</b>	20148
<b>SQL State</b>	QSB27
<b>SQL Code</b>	-1009127L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Database segment.

<b>Error 1009127</b>	<b>"Database Segment %2, %3 size does not match catalog size of %4. This Segment can not be used. %1"</b>
<b>Parameter 3</b>	Size of segment.
<b>Parameter 4</b>	Catalog size of segment.
<b>Probable Cause</b>	No additional information available.
<b>Error 1009128</b>	<b>"The IQ_SYSTEM_TEMP dbspace does not have dbfiles for this server. %1"</b>
<b>Constant</b>	EMSG_SDBEXT_NOFREELIST
<b>SAP Sybase Error Number</b>	20149
<b>SQL State</b>	QSB28
<b>SQL Code</b>	-1009128L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1009129</b>	<b>"Database Segment %2, secondary server can not find a valid header. This segment can not be used. %1"</b>
<b>Constant</b>	EMSG_SDBEXT_QSERVER_FAIL
<b>SAP Sybase Error Number</b>	20150
<b>SQL State</b>	QSB29
<b>SQL Code</b>	-1009129L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	14 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Database segment.
<b>Probable Cause</b>	No additional information available.

## Errors and Warnings

<b>Error 1009130</b>	<b>"Database %2, does not have a segment for catalogfileid %3. %1"</b>
<b>Constant</b>	EMSG_SDBEXT_MISSING_CATALOGFILEID
<b>SAP Sybase Error Number</b>	20151
<b>SQL State</b>	QSB30
<b>SQL Code</b>	-1009130L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Database segment.
<b>Parameter 2</b>	Max compression
<b>Parameter 3</b>	Catalog max compression.
<b>Probable Cause</b>	No additional information available.
<b>Warning 1009131</b>	<b>"You have run out of %1 dbspace in database %2. In another session, please issue a CREATE DBSPACE ... %3 command and add a dbspace of at least %4 MB."</b>
<b>Constant</b>	EMSG_IQSTORE_OUTOFDISK_HEADER
<b>SAP Sybase Error Number</b>	20152
<b>SQL State</b>	QSB31
<b>SQL Code</b>	1009131L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I0</i> on page 2
<b>Parameter 1</b>	string IQ STORE or IQ TEMPORARY STORE
<b>Parameter 2</b>	database name
<b>Parameter 3</b>	string IQ STORE or IQ TEMPORARY STORE
<b>Parameter 4</b>	the minimum number of megabytes to add

<b>Warning 1009131</b>	<b>"You have run out of %1 dbspace in database %2. In another session, please issue a CREATE DBSPACE ... %3 command and add a dbspace of at least %4 MB."</b>
<b>Probable Cause</b>	You have run out of DBSPACE in the named database. In order to continue, you must add another DBSPACE to the database unless space becomes available from another connection.
<b>Warning 1009132</b>	<b>"The DBA has added %1 %2 dbspaces to database %3. Sybase IQ (TM) is no longer waiting for more dbspace."</b>
<b>Constant</b>	EMSG_IQSTORE_OUTOFDISK_TRAILER
<b>SAP Sybase Error Number</b>	20153
<b>SQL State</b>	QSB32
<b>SQL Code</b>	1009132L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> 0 on page 2
<b>Parameter 1</b>	explanation for arg %2 delete if no %1
<b>Parameter 2</b>	explanation for arg %3 delete if no %2
<b>Parameter 3</b>	explanation for %3
<b>Probable Cause</b>	No additional information available.
<b>Error 1009133</b>	<b>"You have run out of space during the CHECKPOINT operation. %1"</b>
<b>Constant</b>	EMSG_IQSTORE_OUTOFSPACE_CHECKPOINT
<b>SAP Sybase Error Number</b>	20982
<b>SQL State</b>	QSB33
<b>SQL Code</b>	-1009133L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> 4 on page 2

## Errors and Warnings

<b>Error 1009133</b>	<b>"You have run out of space during the CHECKPOINT operation. %1"</b>
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	The checkpoint operation in progress needs to allocate blocks so that it can construct and save required checkpoint information. When space is exhausted during a checkpoint operation, it is not possible to add more space via a CREATE DBSPACE command. Consequently, the checkpoint operation will fail.

<b>Error 1009134</b>	<b>"Insufficient buffers for '%2'. %1"</b>
<b>Constant</b>	EMSG_SORT_MINBUFSAVAIL
<b>SAP Sybase Error Number</b>	21023
<b>SQL State</b>	QSB34
<b>SQL Code</b>	-1009134L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	clientType
<b>Probable Cause</b>	No additional information available.

<b>Error 1009135</b>	<b>"Cannot perform requested command as there is a CREATE DBSPACE command in progress. %1"</b>
<b>Constant</b>	EMSG_IQSTORE_INCREASEDBSPACE
<b>SAP Sybase Error Number</b>	21034
<b>SQL State</b>	QSB36
<b>SQL Code</b>	-1009135L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception

<b>Error 1009135</b>	<b>"Cannot perform requested command as there is a CREATE DBSPACE command in progress. %1"</b>
<b>Probable Cause</b>	A CREATE DBSPACE or a DROP DBSPACE command was issued when there was already a DROP DBSPACE command in progress.
<b>Error 1009136</b>	<b>"Cannot perform requested command as there is a DROP DBSPACE command in progress. %1"</b>
<b>Constant</b>	EMSG_IQSTORE_INDROPDBSPACE
<b>SAP Sybase Error Number</b>	21035
<b>SQL State</b>	QSB37
<b>SQL Code</b>	-1009136L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	A CREATE DBSPACE or a DROP DBSPACE command was issued when there was already an ALTER DBSPACE command in progress.
<b>Error 1009137</b>	<b>"Cannot perform DDL command now on table %2 as a DDL command is already in progress on that table. %1"</b>
<b>Constant</b>	EMSG_DDLINPROGRESS
<b>SAP Sybase Error Number</b>	21036
<b>SQL State</b>	QDC55
<b>SQL Code</b>	-1009137L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Parameter 1 description
<b>Parameter 2</b>	location of the exception

## Errors and Warnings

<b>Error 1009137</b>	<b>"Cannot perform DDL command now on table %2 as a DDL command is already in progress on that table. %1"</b>
<b>Probable Cause</b>	There is already a DDL command in progress at the moment on the table specified and you must wait until it is finished before starting another DDL command on that table.
<b>Error 1009139</b>	<b>"Cannot perform requested command as there is a CHECKPOINT command in progress. %1"</b>
<b>Constant</b>	EMSG_IQSTORE_INCHECKPOINT
<b>SAP Sybase Error Number</b>	21038
<b>SQL State</b>	QSB38
<b>SQL Code</b>	-1009139L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	A CREATE DBSPACE or a DROP DBSPACE command was issued when there was already a CHECKPOINT command in progress.
<b>Error 1009140</b>	<b>"Cannot restore dbspace "%2' to raw partition "%3' because its size is smaller than the size of the original raw partition (%4 vs. %5 blocks). %1"</b>
<b>Constant</b>	EMSG_RESTORE_RAW_PARTITION_SIZE_MISMATCH
<b>SAP Sybase Error Number</b>	21039
<b>SQL State</b>	QCA49
<b>SQL Code</b>	-1009140L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	name of the IQ dbspace being restored

<b>Error 1009140</b>	<b>"Cannot restore dbspace '%2' to raw partition '%3' because its size is smaller than the size of the original raw partition (%4 vs. %5 blocks). %1"</b>
<b>Parameter 3</b>	raw partition to which the IQ dbspace is being restored
<b>Parameter 4</b>	size of the new raw partition
<b>Parameter 5</b>	size of the old raw partition
<b>Probable Cause</b>	This error means that the user is attempting to restore an IQ dbspace on a raw partition that is not the same size as the original raw partition on which the IQ dbspace existed at the time of the backup. The user must resize the raw partition and then retry the restore operation.

<b>Error 1009141</b>	<b>"Table '%2' cannot be found in the IQ store. %1"</b>
<b>Constant</b>	EMSG_SQL_IQTABLENOTFOUND
<b>SAP Sybase Error Number</b>	21061
<b>SQL State</b>	QCA51
<b>SQL Code</b>	-1009141L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	table name
<b>Probable Cause</b>	The stored procedure sp_iqtablesize cannot find the table. This stored procedure is for IQ tables only. It cannot be run against system tables or ASA tables.

<b>Warning 1009142</b>	<b>" %1 SortMerge0: %2 records, Phasel=%3 Secs, %4 runs total, %5 pgs=%6 M, runlen=%7, %8 est. phases"</b>
<b>Constant</b>	EMSG_SORT_INFOMERGED0
<b>SAP Sybase Error Number</b>	21067
<b>SQL State</b>	QSB39
<b>SQL Code</b>	1009142L
<b>ODBC 2 State</b>	OK

## Errors and Warnings

<b>Warning 1009142</b>	" %1 SortMerge0: %2 records, Phasel=%3 Secs, %4 runs total, %5 pgs=%6 M, runlen=%7, %8 est. phases"
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	What is being sorted.
<b>Parameter 2</b>	How many records are being sorted.
<b>Parameter 3</b>	Time taken in Phase I.
<b>Parameter 4</b>	How many runs to be merged.
<b>Parameter 5</b>	How many pages of data to be sorted.
<b>Parameter 6</b>	How many Mbytes of data to be sorted.
<b>Parameter 7</b>	Average number of pages in a run.
<b>Parameter 8</b>	Estimated number of merge phases.
<b>Probable Cause</b>	This information is provided after the Phase I radix sorting is complete and the Phase II merge-sorting is about to begin. Each run consists of a sequence of pages that have been radix sorted in Phase I. These runs are merged together in Phase II to finish the sort.
<b>Warning 1009143</b>	" %1 SortMergePass: Merged %2 runs, %3 Secs, %4 runs remaining, %5 reads = %6 M, runlen=%7, phase %8, %9 M on disk"
<b>Constant</b>	EMSG_SORT_INFOMERGED1
<b>SAP Sybase Error Number</b>	21068
<b>SQL State</b>	QSB40
<b>SQL Code</b>	1009143L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	What is being sorted.
<b>Parameter 2</b>	How many runs were merged in this merge pass..
<b>Parameter 3</b>	Time taken in this merge pass.

<b>Warning 1009143</b>	" %1 SortMergePass: Merged %2 runs, %3 Secs, %4 runs remaining, %5 reads = %6 M, runlen=%7, phase %8, %9 M on disk"
<b>Parameter 4</b>	How many runs still to be merged.
<b>Parameter 5</b>	How many page reads done in this pass.
<b>Parameter 6</b>	How many Mbytes of data read in this pass.
<b>Parameter 7</b>	Average length of runs in pages, this pass.
<b>Parameter 8</b>	Fractional phase number reached.
<b>Parameter 9</b>	How many Mbytes of data physically read in this pass.
<b>Probable Cause</b>	This information is provided after each merge pass. One merge pass merges a certain number of runs, using one pinned buffer page per run plus one pinned buffer for the output run. Note that there can be several passes in a merge phase. One merge phase reads all the sort data and produces a new set of runs that provide input to the next phase.
<b>Warning 1009144</b>	" %1 SortMergeDone: Ave mem %2 M, %3 Secs, %4 passes, %5 reads, %6 M data= %7 pgs, %8 phases, %9 M on disk"
<b>Constant</b>	EMSG_SORT_INFOMERGED2
<b>SAP Sybase Error Number</b>	21069
<b>SQL State</b>	QSB41
<b>SQL Code</b>	1009144L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	What is being sorted.
<b>Parameter 2</b>	Time-average number of pinned page buffers used by Phase II of the sort.
<b>Parameter 3</b>	Time taken for Phase II of the sort.
<b>Parameter 4</b>	Total number of passes in Phase II.
<b>Parameter 5</b>	Total number of page reads in Phase II.

## Errors and Warnings

<b>Warning 1009144</b>	" %1 SortMergeDone: Ave mem %2 M, %3 Secs, %4 passes, %5 reads, %6 M data= %7 pgs, %8 phases, %9 M on disk"
<b>Parameter 6</b>	Total Mbytes of data sorted.
<b>Parameter 7</b>	Total number of pages of data sorted.
<b>Parameter 8</b>	Number of merge phases in the merge sort of Phase II.
<b>Parameter 9</b>	Total Mbytes of physical reads in Phase II.
<b>Probable Cause</b>	This information is provided at the end of Phase II to summarize the resource usage of the whole merge sort. The last pass of the sort is separately reported on by an EMSG_SORT_INFOMERGED1 message.
<b>Error 1009145</b>	<b>"Data exception - data type conversion is not possible. %2, %1"</b>
<b>Constant</b>	EMSG_TYPECONVERSION_W_ARG
<b>SAP Sybase Error Number</b>	21070
<b>SQL State</b>	QFA2E
<b>SQL Code</b>	-1009145L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Exception line number
<b>Parameter 2</b>	SA parse source code line
<b>Probable Cause</b>	No additional information available.

## **1009146 - 1013018**

---

## Messages 1009146 through 1009165

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1009146</b>	<b>"Cannot perform requested command as there is a DBCC command in progress. %1"</b>
<b>Constant</b>	EMSG_IQSTORE_INDBCC
<b>SAP Sybase Error Number</b>	21071
<b>SQL State</b>	QSB42
<b>SQL Code</b>	-1009146L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	A CHECKPOINT command was issued when there was already a DBCC command in progress.
<b>Warning 1009147</b>	<b>"Space has become available in the %1 store of database %2. Sybase IQ (TM) is no longer waiting for more dbspace."</b>
<b>Constant</b>	EMSG_IQSTORE_OUTOFDISK_SPACEAVAILABLE
<b>SAP Sybase Error Number</b>	20188
<b>SQL State</b>	QSB43
<b>SQL Code</b>	1009147L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	string IQ STORE or IQ TEMPORARY STORE
<b>Parameter 2</b>	Database Name
<b>Probable Cause</b>	No additional information available.

## Errors and Warnings

<b>Error 1009148</b>	" <b>Cannot use -iqfrec to start a multiplex secondary server. %1</b> "
<b>Constant</b>	EMSG_IQSTORE_NOFREC
<b>SAP Sybase Error Number</b>	21049
<b>SQL State</b>	QSB44
<b>SQL Code</b>	-1009148L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	A sp_iqcheckdb procedure call was issued on an IQ multiplex secondary server, or it was started in drop-leaks or forced recovery mode. These operations are only allowed on the coordinator

<b>Error 1009149</b>	" <b>%2 Internal Inconsistency: %1 (%3,%4,%5)</b> "
<b>Constant</b>	EMSG_INDEXCONTAINER_CORRUPT
<b>SAP Sybase Error Number</b>	20189
<b>SQL State</b>	QSB45
<b>SQL Code</b>	-1009149L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Container type
<b>Parameter 3</b>	Internal Error Code
<b>Parameter 4</b>	Internal Error Info 1
<b>Parameter 5</b>	Internal Error Info 2
<b>Probable Cause</b>	A corrupt index container was found. DBCC cannot repair the container. The database object using the container must be re-created.

<b>Error 1009150</b>	"Cannot delete/truncate CK %2 because of RI violation - FK has non-nulls. %1"
<b>Constant</b>	EMSG_RI_VIOLATION_FKNOTNULL
<b>SAP Sybase Error Number</b>	20190
<b>SQL State</b>	QSB46
<b>SQL Code</b>	-1009150L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of exception
<b>Parameter 2</b>	index name of candidate key
<b>Probable Cause</b>	No additional information available. Cannot truncate or delete all from candidate table if there exists any associated foreign key which has any all non-null data.

<b>Error 1009151</b>	"Cannot %2 CK %3 row %4 because of RI violation. %1"
<b>Constant</b>	EMSG_RI_VIOLATION_CK
<b>SAP Sybase Error Number</b>	20191
<b>SQL State</b>	QSB47
<b>SQL Code</b>	-1009151L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of exception
<b>Parameter 2</b>	operation: update or delete
<b>Parameter 3</b>	index name for CK
<b>Parameter 4</b>	row id that violated RI
<b>Probable Cause</b>	No additional information available. Cannot delete/update CK if there exists same value in associated FK. any associated foreign key which has any all non-null data.

## Errors and Warnings

<b>Error 1009152</b>	"Cannot %2 FK %3 row %4 because of RI violation. %1"
<b>Constant</b>	EMSG_RI_VIOLATION_FK
<b>SAP Sybase Error Number</b>	20192
<b>SQL State</b>	QSB48
<b>SQL Code</b>	-1009152L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of exception
<b>Parameter 2</b>	operation: update or insert/load
<b>Parameter 3</b>	role name for FK
<b>Parameter 4</b>	row id that violated RI
<b>Probable Cause</b>	No additional information available. Cannot insert/update FK if there does not exist same value in associated CK any associated foreign key which has any all non-null data.

<b>Error 1009153</b>	"Cannot remove row %3 from CK %2 during LOAD cleanup because of RI violation. %1"
<b>Constant</b>	EMSG_RI_VIOLATION_LOADCLEANUP
<b>SAP Sybase Error Number</b>	20193
<b>SQL State</b>	QSB49
<b>SQL Code</b>	-1009153L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of exception
<b>Parameter 2</b>	index name for CK
<b>Parameter 3</b>	row id that violated RI

<b>Error 1009153</b>	<b>"Cannot remove row %3 from CK %2 during LOAD cleanup because of RI violation. %1"</b>
<b>Probable Cause</b>	No additional information available. If removing self-referential CK during LOAD cleanup phase and there exists a FK of removed value, we roll back the whole operation.
<b>Error 1009154</b>	<b>"Cannot alter dbspace when a backup is in progress"</b>
<b>Constant</b>	EMSG_IQSTORE_CANNOT_ALTERDBSPACE
<b>SAP Sybase Error Number</b>	21118
<b>SQL State</b>	QSB50
<b>SQL Code</b>	-1009154L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	An alter dbspace operation was attempted while a backup was running. The alter dbspace operation cannot proceed since it may modify internal database structures that are being backed up.
<b>Error 1009155</b>	<b>"Cannot perform requested command as there is an ALTER DBSPACE command in progress. %1"</b>
<b>Constant</b>	EMSG_IQSTORE_INALTERDBSPACE
<b>SAP Sybase Error Number</b>	22000
<b>SQL State</b>	QSB55
<b>SQL Code</b>	-1009155L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	A CREATE DBSPACE or a DROP DBSPACE command was issued when there was already an ALTER DBSPACE command in progress.

## Errors and Warnings

<b>Error 1009156</b>	<b>"Drop disallowed for dbspace %2. One or more of the file(s) are in use by the database. %1"</b>
<b>Constant</b>	EMSG_SDBEXT_DROPSEGMENTINUSE
<b>SAP Sybase Error Number</b>	20194
<b>SQL State</b>	QSB51
<b>SQL Code</b>	-1009156L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Database segment.
<b>Probable Cause</b>	A segment must contain no user data and no database structures to drop
<b>Error 1009157</b>	<b>"There is insufficient reserve space to add %3 blocks to segment %2. Only %4 blocks or less may be added. %1"</b>
<b>Constant</b>	EMSG_SDBEXT_SEGMENTNORESERVE
<b>SAP Sybase Error Number</b>	20195
<b>SQL State</b>	QSB52
<b>SQL Code</b>	-1009157L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Database segment.
<b>Parameter 3</b>	Number of blocks user attempted to add
<b>Parameter 4</b>	Maximum blocks that may be added
<b>Probable Cause</b>	Since a segment must use a contiguous range of block numbers, it can only be resized larger when the blocks following it are not in use by the next segment.

<b>Error 1009158</b>	"Cannot resize segment %2 since the truncated region is in use. %1"
<b>Constant</b>	EMSG_SDBEXT_RESIZESEGMENTINUSE
<b>SAP Sybase Error Number</b>	20196
<b>SQL State</b>	QSB53
<b>SQL Code</b>	-1009158L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Database segment.
<b>Probable Cause</b>	A segment can only be resized smaller when no blocks in the truncated are in use.
<b>Error 1009159</b>	"The status specified for segment %2 is unchanged. %1"
<b>Constant</b>	EMSG_SDBEXT_SEGMENTSAMERWMODE
<b>SAP Sybase Error Number</b>	20197
<b>SQL State</b>	QSB54
<b>SQL Code</b>	-1009159L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Database segment.
<b>Probable Cause</b>	The "alter dbspace status" syntax requires the new status to be different than the original status.
<b>Error 1009160</b>	"There must be at least one readwrite dbspace (%2). %1"
<b>Constant</b>	EMSG_SDBEXT_MUST_HAVE_RW
<b>SAP Sybase Error Number</b>	20198

## Errors and Warnings

<b>Error 1009160</b>	<b>"There must be at least one readwrite dbspace (%2). %1"</b>
<b>SQL State</b>	QSB56
<b>SQL Code</b>	-1009160L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Database segment.
<b>Probable Cause</b>	There must at least one readwrite segment
<b>Error 1009161</b>	<b>"Cannot resize segment %2 since it is readonly. %1"</b>
<b>Constant</b>	EMSG_SDBEXT_RO_RESIZE
<b>SAP Sybase Error Number</b>	20199
<b>SQL State</b>	QSB57
<b>SQL Code</b>	-1009161L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Database segment.
<b>Probable Cause</b>	A readonly segment cannot be resized
<b>Error 1009162</b>	<b>"Insufficient space to relocate structures on %2. %1"</b>
<b>Constant</b>	EMSG_SDBEXT_NO_RELOCATE_SPACE
<b>SAP Sybase Error Number</b>	20200
<b>SQL State</b>	QSB58
<b>SQL Code</b>	-1009162L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1009162</b>	<b>"Insufficient space to relocate structures on %2. %1"</b>
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Database segment.
<b>Probable Cause</b>	Database structures may need to be relocated in order to drop a segment or make it readonly. This space must be available on other segments.
<b>Error 1009163</b>	<b>"Segment %2 cannot be smaller than %3 blocks. %1"</b>
<b>Constant</b>	EMSG_SDBEXT_SEGMENTTOOSMALL
<b>SAP Sybase Error Number</b>	20201
<b>SQL State</b>	QSB59
<b>SQL Code</b>	-1009163L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Database segment.
<b>Parameter 3</b>	Minimum size in blocks
<b>Probable Cause</b>	Database structures may need to be relocated in order to drop a segment or make it readonly. This space must be available on other segments.
<b>Error 1009164</b>	<b>"You cannot drop the last dbspace. %1"</b>
<b>Constant</b>	EMSG_DATABASE_LASTDBSPACE
<b>SAP Sybase Error Number</b>	20202
<b>SQL State</b>	QSB60
<b>SQL Code</b>	-1009164L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 1009164</b>	<b>"You cannot drop the last dbspace. %1"</b>
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	You can drop the last dbspace only if it is a temp dbspace
<b>Error 1009165</b>	<b>"Cannot perform requested command as the SYSIQFILE table is locked by another transaction. %1"</b>
<b>Constant</b>	EMSG_IQSTORE_INREADSYSFILE
<b>SAP Sybase Error Number</b>	20203
<b>SQL State</b>	QSB61
<b>SQL Code</b>	-1009165L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	A CREATE DBSPACE, ALTER DPSACE or DROP DBSPACE command was issued when there was another command or stored procedure accessing the system table SYSIQFILE.

## Messages 1009166 through 1009185

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1009166</b>	<b>"%3 %4 is in use by dropped dbspace %2 on a secondary server. The drop dbspace command has not yet propagated through the multiplex. %1"</b>
<b>Constant</b>	EMSG_SDBEXT_IN_USE_BY_QUERY_SERVER
<b>SAP Sybase Error Number</b>	20204
<b>SQL State</b>	QSB62
<b>SQL Code</b>	-1009166L
<b>ODBC 2 State</b>	ERROR

<b>Error 1009166</b>	<b>"%3 %4 is in use by dropped dbspace %2 on a secondary server. The drop dbspace command has not yet propagated through the multiplex. %1"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	DBSpace name
<b>Parameter 3</b>	Description of field in use (i.e. File, Name, File ID)
<b>Parameter 4</b>	Value of field in use
<b>Probable Cause</b>	Fields for dropped dbspaces cannot be re-used until the drop dbspace commands have propagated through the multiplex
<b>Error 1009167</b>	<b>"dbspace %2 failed to open since it's definition conflicts with dbspace %3. Secondary server may need to be synchronized. %1"</b>
<b>Constant</b>	EMSG_SDBEXT_DBSPACE_BLOCK_RANGE
<b>SAP Sybase Error Number</b>	20207
<b>SQL State</b>	QSB63
<b>SQL Code</b>	-1009167L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Name of DBSpace that was already open
<b>Parameter 3</b>	Name of DBSpace that failed to open
<b>Probable Cause</b>	The server has an invalid dbspace configuration. New dbspaces may fail to open or the server may fail to start until this is corrected.
<b>Error 1009168</b>	<b>"The WORD SKIP limit (%2) has been exceeded. %1"</b>
<b>Constant</b>	EMSG_SVIOLATION_WORDS_SKIP_LIMIT_EXCEEDED

## Errors and Warnings

<b>Error 1009168</b>	"The WORD SKIP limit (%2) has been exceeded. %1"
<b>SAP Sybase Error Number</b>	20208
<b>SQL State</b>	QSB64
<b>SQL Code</b>	-1009168L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	The WORD SKIP limit specified in the LOAD TABLE statement.
<b>Probable Cause</b>	The number of words encountered that are longer than the limit specified when the word index was created has been exceeded for the load. The load will rollback.

<b>Error 1009169</b>	"Cannot write to RO DBSpace %2. %1"
<b>Constant</b>	EMSG_RODBSPACE_ILLEGAL_ACCESS
<b>SAP Sybase Error Number</b>	20222
<b>SQL State</b>	QSB65
<b>SQL Code</b>	-1009169L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	dbspace name
<b>Probable Cause</b>	No additional information available..

<b>Error 1009170</b>	"You have run out of space in %2 DBSpace. %1"
<b>Constant</b>	EMSG_OUT_OF_DBSPACE
<b>SAP Sybase Error Number</b>	20223
<b>SQL State</b>	QSB66

<b>Error 1009170</b>	"You have run out of space in %2 DBSpace. %1"
<b>SQL Code</b>	-1009170L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	name of dbspace
<b>Probable Cause</b>	No additional information available..

<b>Error 1009171</b>	"An IO error was encountered while writing a database page in %2 DBSpace. %1"
<b>Constant</b>	EMSG_BUFSMAN_BIO_WRITE_ERROR
<b>SAP Sybase Error Number</b>	20224
<b>SQL State</b>	QSB67
<b>SQL Code</b>	-1009171L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	dbspace name
<b>Probable Cause</b>	No additional information available..

<b>Error 1009172</b>	"%2 is in use by another sp_iqemptyfile or ALTER DBSPACE command. %1"
<b>Constant</b>	EMSG_DBSPACE_FILE_IN_USE_BY_ALTER_OR_EMPTY
<b>SAP Sybase Error Number</b>	20226
<b>SQL State</b>	QSB68
<b>SQL Code</b>	-1009172L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1009172</b>	<b>"%2 is in use by another sp_iqemptyfile or ALTER DBSPACE command. %1"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Name of the FILE or DBSPACE locked.
<b>Probable Cause</b>	sp_iqemptyfile or ALTER DBSPACE commands disallow status change for the FILE(s) or DBSPACE. No other ALTER DBSPACE or sp_iqemptyfile command can run on those FILE(s) or DBSPACE.
<b>Error 1009173</b>	<b>"Operation not permitted on an OFFLINE DBSpace %2. %1"</b>
<b>Constant</b>	EMSG_OFFLINE_DBSPACE_ILLEGAL_ACCESS
<b>SAP Sybase Error Number</b>	20227
<b>SQL State</b>	QSB69
<b>SQL Code</b>	-1009173L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	dbspace name
<b>Probable Cause</b>	No additional information available..
<b>Error 1009174</b>	<b>"Operation not yet supported. Sort metadata sources have incompatible record descriptors. %1"</b>
<b>Constant</b>	EMSG_SORT_METADATADESC_MISMATCH
<b>SAP Sybase Error Number</b>	20228
<b>SQL State</b>	QSB70
<b>SQL Code</b>	-1009174L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1009174</b>	<b>"Operation not yet supported. Sort metadata sources have incompatible record descriptors. %1"</b>
<b>Severity Code</b>	<i>14 on page 2</i>
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available..
<b>Error 1009175</b>	<b>"Database segment '%2' is not valid. Reserve Blocks found in the header: %3 Reserve Blocks expected: %4. This segment cannot be used. %1"</b>
<b>Constant</b>	EMSG_SDBEXT_BAD_RESERVE
<b>SAP Sybase Error Number</b>	20229
<b>SQL State</b>	QSB71
<b>SQL Code</b>	-1009175L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14 on page 2</i>
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	Name of the segment.
<b>Parameter 3</b>	Reserve blocks found in the disk header.
<b>Parameter 4</b>	Reserve blocks expected.
<b>Probable Cause</b>	The start block of the disk segment that was found in the disk segment header is not the same as what was expected. The disk segment cannot be used. You will need to restore your database from backup.
<b>Error 1009176</b>	<b>"Create temporary dbspace not allowed. %1"</b>
<b>Constant</b>	EMSG_DBSPACE_TEMP_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	20230
<b>SQL State</b>	QSB72
<b>SQL Code</b>	-1009176L

## Errors and Warnings

<b>Error 1009176</b>	"Create temporary dbspace not allowed. %1"
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Additional dbspaces may not be created in temp store. Temp space may only be added to IQ_SYSTEM_TEMP.
<b>Error 1009177</b>	"%2 is already %3. %1"
<b>Constant</b>	EMSG_DBSPACE_ATTRIB_UNCHANGED
<b>SAP Sybase Error Number</b>	20231
<b>SQL State</b>	QSB73
<b>SQL Code</b>	-1009177L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	dbspace name
<b>Parameter 3</b>	READONLY, READWRITE, ONLINE, OFFLINE
<b>Probable Cause</b>	The dbspace being altered already had the requested attributes
<b>Error 1009178</b>	"Operation not allowed on dbspaces that contain multiple files. %1"
<b>Constant</b>	EMSG_DBSPACE_NOT_FOR_MULTI_DBSPACE
<b>SAP Sybase Error Number</b>	20232
<b>SQL State</b>	QSB74
<b>SQL Code</b>	-1009178L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1009178</b>	<b>"Operation not allowed on dbspaces that contain multiple files. %1"</b>
<b>Severity Code</b>	<i>14 on page 2</i>
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	The specified operation cannot be applied to a file the contains multiple files

<b>Error 1009179</b>	<b>"The last file in a dbspace may only be removed by DROP DBSPACE. %1"</b>
<b>Constant</b>	EMSG_DBSPACE_CANT_DROP_LAST_FILE
<b>SAP Sybase Error Number</b>	20233
<b>SQL State</b>	QSB75
<b>SQL Code</b>	-1009179L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14 on page 2</i>
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	A dbspace must contain at least one file. The last file can only be removed by dropping the dbspace that contains it.

<b>Error 1009180</b>	<b>"%2 is not allowed on system dbspace %3. %1"</b>
<b>Constant</b>	EMSG_DBSPACE_NOT_ALLOWED_SYSTEM
<b>SAP Sybase Error Number</b>	20234
<b>SQL State</b>	QSB76
<b>SQL Code</b>	-1009180L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14 on page 2</i>
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	disallowed command

## Errors and Warnings

<b>Error 1009180</b>	<b>"%2 is not allowed on system dbspace %3. %1"</b>
<b>Parameter 3</b>	dbspace name
<b>Probable Cause</b>	The requested DDL operation is not allowed on system dbspaces
<b>Error 1009181</b>	<b>"Multiple FILE clauses are not allowed for this command. %1"</b>
<b>Constant</b>	EMSG_DBSPACE_SINGLE_FILE_CLAUSE
<b>SAP Sybase Error Number</b>	20235
<b>SQL State</b>	QSB77
<b>SQL Code</b>	-1009181L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Some alter dbspace commands do not allow multiple files to be specified
<b>Error 1009182</b>	<b>"DBFile name %2 is already in use. %1"</b>
<b>Constant</b>	EMSG_DBSPACE_DBFILE_NAME_IN_USE
<b>SAP Sybase Error Number</b>	20236
<b>SQL State</b>	QSB78
<b>SQL Code</b>	-1009182L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	logical filename
<b>Probable Cause</b>	logical filenames must be unique for dbfiles

<b>Error 1009183</b>	<b>"A readwrite dbspace may not be placed offline. %1"</b>
<b>Constant</b>	EMSG_DBSPACE_NO_OFFLINE_RW_DBSPACE
<b>SAP Sybase Error Number</b>	20237
<b>SQL State</b>	QSB79
<b>SQL Code</b>	-1009183L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	A dbspace must be readonly before it can be placed offline
<b>Error 1009184</b>	<b>"Operation not permitted on a READONLY DBSpace. %1"</b>
<b>Constant</b>	EMSG_READONLY_DBSPACE_ILLEGAL_ACCESS
<b>SAP Sybase Error Number</b>	21190
<b>SQL State</b>	QSB80
<b>SQL Code</b>	-1009184L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available..
<b>Error 1009185</b>	<b>"An IO error was encountered while writing a database page in %2 DBSpace. %1. File is readonly."</b>
<b>Constant</b>	EMSG_READONLY_FILE_ILLEGAL_ACCESS
<b>SAP Sybase Error Number</b>	21191
<b>SQL State</b>	QSB81
<b>SQL Code</b>	-1009185L
<b>ODBC 2 State</b>	ERROR

<b>Error 1009185</b>	"An IO error was encountered while writing a database page in %2 DBSpace. %1. File is readonly."
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	dbspace name
<b>Probable Cause</b>	No additional information available..

## Messages 1009186 through 1009420

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1009186</b>	"Global Request for freelist failed. %1"
<b>Constant</b>	EMSG_GLOBAL_FL_REQUEST_FAILED
<b>SAP Sybase Error Number</b>	21200
<b>SQL State</b>	QSB82
<b>SQL Code</b>	-1009186L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Global request for freelist failed.

<b>Error 1009187</b>	"Textindex External Error: Error Code: %2: Error Message: %3. %1"
<b>Constant</b>	EMSG_EXTLIB_ERROR
<b>SAP Sybase Error Number</b>	21205
<b>SQL State</b>	QSB83
<b>SQL Code</b>	-1009187L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1009187</b>	<b>"Textindex External Error: Error Code: %2: Error Message: %3. %1"</b>
<b>Severity Code</b>	<i>14 on page 2</i>
<b>Parameter 1</b>	Error code set by the external library
<b>Parameter 2</b>	Error message from the external library
<b>Parameter 3</b>	location of the exception
<b>Probable Cause</b>	Error from external prefilter or term breaker library.

<b>Error 1009188</b>	<b>"Create shared temporary dbspace not allowed. %1"</b>
<b>Constant</b>	EMSG_DBSPACE_SHARED_TEMP_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	22019
<b>SQL State</b>	QDD1A
<b>SQL Code</b>	-1009188L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14 on page 2</i>
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Additional dbspaces may not be created in shared temp store. Shared Temp space may only be added to IQ_SHARED_TEMP.

<b>Error 1009189</b>	<b>"Text document exceeds maximum number of terms. Support up to 4294967295 terms per document. %1"</b>
<b>Constant</b>	EMSG_MAXTERM_ERROR
<b>SAP Sybase Error Number</b>	21210
<b>SQL State</b>	QSB84
<b>SQL Code</b>	-1009189L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14 on page 2</i>

## Errors and Warnings

<b>Error 1009189</b>	<b>"Text document exceeds maximum number of terms. Support up to 4294967295 terms per document. %1"</b>
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Error from external prefilter or term breaker library.
<b>Error 1009190</b>	<b>"Incorrect %3 Index Version (%2): Index must be dropped and recreated. %1"</b>
<b>Constant</b>	EMSG_TEXTVERSION_ERROR
<b>SAP Sybase Error Number</b>	21211
<b>SQL State</b>	QSB85
<b>SQL Code</b>	-1009190L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Incorrect version of index.
<b>Parameter 3</b>	index type.
<b>Probable Cause</b>	Error from text index.
<b>Error 1009191</b>	<b>"The FORCE READWRITE clause is not allowed on this dbspace. It can be specified for the dbspace IQ_SHARED_TEMP only. %1"</b>
<b>Constant</b>	EMSG_DBSPACE_FORCE_READWRITE_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	22025
<b>SQL State</b>	QSB86
<b>SQL Code</b>	-1009191L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception

<b>Error 1009191</b>	<b>"The FORCE READWRITE clause is not allowed on this dbspace. It can be specified for the dbspace IQ_SHARED_TEMP only. %1"</b>
<b>Probable Cause</b>	The FORCE READWRITE clause can be used with IQ_SHARED_TEMP only.
<b>Error 1009192</b>	<b>"File may not be accessible from one or more multiplex servers. Use sp_iqmpxfilestatus for further diagnosis. %1"</b>
<b>Constant</b>	EMSG_DBSPACE_GLOBAL_FILE_STATUS_INVALID
<b>SAP Sybase Error Number</b>	22026
<b>SQL State</b>	QSB87
<b>SQL Code</b>	-1009192L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	The file must be accessible from all multiplex servers (except those that are excluded) before its mode can be changed to READWRITE. The global file status maintained at the coordinator indicates that file may not be accessible from one or more multiplex servers. Use sp_iqmpxfilestatus for further diagnosis.
<b>Error 1009193</b>	<b>"Insufficient space to accommodate Freelist blocks. Please use a file with at least %2 MB space and turn that file READWRITE. %1"</b>
<b>Constant</b>	EMSG_DBSPACE_INSUFFICIENT_SPACE_FOR_RW
<b>SAP Sybase Error Number</b>	22027
<b>SQL State</b>	QSB88
<b>SQL Code</b>	-1009193L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 1009193</b>	<b>"Insufficient space to accommodate Freelist blocks. Please use a file with at least %2 MB space and turn that file READWRITE. %1"</b>
<b>Severity Code</b>	<i>14 on page 2</i>
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Size of the file needed
<b>Probable Cause</b>	There is no READWRITE file in IQ_SHARED_TEMP dbspace at this point in time. While trying to turn the first file READWRITE, the file needs to have enough space to accommodate freelist blocks for all the existing files.
<b>Error 1009194</b>	<b>"Please drop the rest of the files in this dbspace before trying to drop this file. \nThis was the first file to be made READWRITE and can only be dropped if it is the last remaining file. %1"</b>
<b>Constant</b>	EMSG_DBSPACE_LAST_FILE_DROPPED
<b>SAP Sybase Error Number</b>	22028
<b>SQL State</b>	QSB89
<b>SQL Code</b>	-1009194L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14 on page 2</i>
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	This was the first file to be made READWRITE in IQ_SHARED_TEMP dbspace. This file should be the last file in IQ_SHARED_TEMP to be dropped. Please drop rest of the files before trying to drop this file.
<b>Error 1009195</b>	<b>"Cannot open file %2, alter file ReadWrite operation failed. %1"</b>
<b>Constant</b>	EMSG_SDBEXT_SHTEMP_RW_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	22030
<b>SQL State</b>	QSB90

<b>Error 1009195</b>	"Cannot open file %2, alter file ReadWrite operation failed. %1"
<b>SQL Code</b>	-1009195L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	logical filename
<b>Probable Cause</b>	Secondary node cannot make a file in IQ_SHARED_TEMP dbspace READWRITE if it is not accessible.
<b>Error 1009196</b>	"%2: Cannot convert blockmap; bmp=%3}. %1"
<b>Constant</b>	EMSG_BLOCKMAP_CONVERSION_FAILED
<b>SAP Sybase Error Number</b>	22033
<b>SQL State</b>	QSB91
<b>SQL Code</b>	-1009196L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	1) location of the exception
<b>Parameter 2</b>	2) The particular buffer cache throwing the exception.
<b>Parameter 3</b>	3) Information about the blockmap
<b>Probable Cause</b>	Blockmap conversion failed. Blockmap remains unconverted and in read only mode.
<b>Error 1009412</b>	"The INSERT ... LOCATION statement must use a SELECT statement. %1"
<b>Constant</b>	EMSG_SQL_INS_LOC_SEL
<b>SAP Sybase Error Number</b>	21050
<b>SQL State</b>	QCB10

## Errors and Warnings

<b>Error 1009412</b>	<b>"The INSERT ... LOCATION statement must use a SELECT statement. %1"</b>
<b>SQL Code</b>	-1009412L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	The INSERT ... LOCATION statement must use a SELECT statement. No other SQL statement is supported here.
<b>Error 1009413</b>	<b>"Secondary server cannot maintain catalog sync. %1"</b>
<b>Constant</b>	EMSG_CAT_MPX_REPLAY_FAIL
<b>SAP Sybase Error Number</b>	21051
<b>SQL State</b>	QCB11
<b>SQL Code</b>	-1009413L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	An error has occurred while applying catalog updates from the coordinator. The secondary server must be restarted or synchronized.
<b>Error 1009414</b>	<b>"Secondary server cannot recover catalog during post-synchronization. %1"</b>
<b>Constant</b>	EMSG_CAT_MPX_POSTSYNC_FAIL
<b>SAP Sybase Error Number</b>	21052
<b>SQL State</b>	QCB12
<b>SQL Code</b>	-1009414L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1009414</b>	<b>"Secondary server cannot recover catalog during post-synchronization. %1"</b>
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	An error has occurred while reconstituting catalog entries for the IQ Local store. Manual repair is required.
<b>Error 1009415</b>	<b>"CREATE TABLE cannot use IN clause for IQ Local store. %1"</b>
<b>Constant</b>	EMSG_CAT_MPX_NO_LOCAL_INCLAUSE
<b>SAP Sybase Error Number</b>	21053
<b>SQL State</b>	QCB13
<b>SQL Code</b>	-1009415L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	14 on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	You may not specify the IN clause to create tables in IQ Local store. Without an IN clause, the secondary server create tables in Local store by default.
<b>Error 1009416</b>	<b>"Option '%2' not allowed on a partitioned table. %1"</b>
<b>Constant</b>	EMSG_UNSUPPORTED_PARTITIONED_TABLE_LOAD_OPTION
<b>SAP Sybase Error Number</b>	21054
<b>SQL State</b>	QCB14
<b>SQL Code</b>	-1009416L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	14 on page 2

## Errors and Warnings

<b>Error 1009416</b>	<b>"Option '%2' not allowed on a partitioned table. %1"</b>
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	option name
<b>Probable Cause</b>	Certain 'load table' options are not supported on a partitioned table.
<b>Error 1009417</b>	<b>"Updating partition key column on a partitioned table is not allowed. %1"</b>
<b>Constant</b>	EMSG_CANNOT_UPDATE_PARTITION_COLUMN
<b>SAP Sybase Error Number</b>	21055
<b>SQL State</b>	QCB15
<b>SQL Code</b>	-1009417L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	A partition key column cannot be updated.
<b>Error 1009418</b>	<b>"Operation not allowed - partition key column %2 not specified. %1"</b>
<b>Constant</b>	EMSG_PARTITIONING_COLUMN OMITTED
<b>SAP Sybase Error Number</b>	21056
<b>SQL State</b>	QCB16
<b>SQL Code</b>	-1009418L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column name
<b>Probable Cause</b>	A partial width insert on a partitioned table is not permitted when at least one of the table's partition key columns is omitted.

<b>Error 1009419</b>	"The width of one or more columns are too large to fit into database's page."
<b>Constant</b>	EMSG_PAGESIZE_TOO_SMALL_FOR_QCP
<b>SAP Sybase Error Number</b>	21159
<b>SQL State</b>	QCB19
<b>SQL Code</b>	-1009419L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	The LOAD Engine cannot fit a column into the page.
<b>Error 1009420</b>	"Value of row's partition-key columns do not fit into any of the table's partitions."
<b>Constant</b>	EMSG_VALUE_DOES_NOT_FIT
<b>SAP Sybase Error Number</b>	21160
<b>SQL State</b>	QCB20
<b>SQL Code</b>	-1009420L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	The value for the partition key columns for a specific row do not fit within any of the table's partitions.

## Messages 1010000 through 1010019

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1010000</b>	"The file '%2' already exists. %1"
<b>Constant</b>	EMSG_DATABASE_FILEALREADYEXISTS
<b>SAP Sybase Error Number</b>	20014
<b>SQL State</b>	QXA00

## Errors and Warnings

<b>Error 1010000</b>	"The file '%2' already exists. %1"
<b>SQL Code</b>	-1010000L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	dbspace name
<b>Probable Cause</b>	The named dbspace already exists (and it is a raw partition). To proceed, you must first remove it by hand.
<b>Error 1010001</b>	"Cannot use raw partition for dbspace file '%2'. %1"
<b>Constant</b>	EMSG_DATABASE_FILEISRAW
<b>SAP Sybase Error Number</b>	20015
<b>SQL State</b>	QXA01
<b>SQL Code</b>	-1010001L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	dbspace name
<b>Probable Cause</b>	The named dbspace cannot exist on a raw partition.
<b>Error 1010002</b>	"File format mismatch; database %2; Sybase IQ: %3. %1"
<b>Constant</b>	EMSG_DATABASE_FILEFORMAT
<b>SAP Sybase Error Number</b>	20016
<b>SQL State</b>	QXA02
<b>SQL Code</b>	-1010002L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1010002</b>	<b>"File format mismatch; database %2; Sybase IQ: %3. %1"</b>
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	file format of database as found in SYSIQINFO
<b>Parameter 3</b>	file format as known by IQ DLL
<b>Probable Cause</b>	The file format of the database doesn't match the file format as expected by the IQ DLL. The IQ DLL and the database each have a format version. They must match.
<b>Error 1010003</b>	<b>"Catalog format mismatch: database %2; Sybase IQ: %3. %1"</b>
<b>Constant</b>	EMSG_DATABASE_CATALOGFORMAT
<b>SAP Sybase Error Number</b>	20017
<b>SQL State</b>	QXA03
<b>SQL Code</b>	-1010003L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	catalog format of database as found in SYSIQINFO
<b>Parameter 3</b>	catalog format as known by IQ DLL
<b>Probable Cause</b>	The catalog format of the database doesn't match the catalog format as expected by the IQ DLL. The IQ DLL and the ASA catalog each have a format version. They must match.
<b>Error 1010004</b>	<b>"Stored procedure format mismatch: database %2; Sybase IQ: %3. %1"</b>
<b>Constant</b>	EMSG_DATABASE_SPFORMAT
<b>SAP Sybase Error Number</b>	20018
<b>SQL State</b>	QXA04
<b>SQL Code</b>	-1010004L

## Errors and Warnings

<b>Error 1010004</b>	<b>"Stored procedure format mismatch: database %2; Sybase IQ: %3. %1"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	stored procedure of database as found in SYSIQINFO
<b>Parameter 3</b>	stored procedure format as known by IQ DLL
<b>Probable Cause</b>	The stored procedure format of the database doesn't match the stored procedure format as expected by the IQ DLL. The IQ DLL and the database each contain a stored procedure format version. They must match.
<b>Error 1010005</b>	<b>"File format date mismatch: database %2; Sybase IQ: %3. %1"</b>
<b>Constant</b>	EMSG_DATABASE_TIMESTAMP
<b>SAP Sybase Error Number</b>	20019
<b>SQL State</b>	QXA05
<b>SQL Code</b>	-1010005L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	file format date of database as found in SYSIQINFO
<b>Parameter 3</b>	file format as known by IQ DLL
<b>Probable Cause</b>	The file format date of the database doesn't match the file format date as expected by the IQ DLL.
<b>Error 1010006</b>	<b>"Maximum blocks for dbspace '%2' is %3 blocks. %4 blocks were specified. (Database blocksize is %5.) %1"</b>
<b>Constant</b>	EMSG_DATABASE_BLOCKRANGE

<b>Error 1010006</b>	"Maximum blocks for dbspace '%2' is %3 blocks. %4 blocks were specified. (Database blocksize is %5.) %1"
<b>SAP Sybase Error Number</b>	20020
<b>SQL State</b>	QXA06
<b>SQL Code</b>	-1010006L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	dbspace name
<b>Parameter 3</b>	maximum number of blocks for a dbspace given the database's blocksize
<b>Parameter 4</b>	maximum blocks the user specified
<b>Parameter 5</b>	The blocksize of the database.
<b>Probable Cause</b>	Given a database's BLOCK SIZE and the number of blocks specified by the user for the dbspace, the dbspace size (in bytes) would exceed the OS's limit of bytes per file.
<b>Error 1010007</b>	"The number of blocks (%3) for dbspace '%2' must be less than or equal to the number of blocks in the raw partition (%4). %1"
<b>Constant</b>	EMSG_DATABASE_INVALIDNBLOCKS
<b>SAP Sybase Error Number</b>	20980
<b>SQL State</b>	QXA07
<b>SQL Code</b>	-1010007L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	dbspace name

## Errors and Warnings

<b>Error 1010007</b>	<b>"The number of blocks (%3) for dbspace '%2' must be less than or equal to the number of blocks in the raw partition (%4). %1"</b>
<b>Parameter 3</b>	user's number of blocks in dbspace
<b>Parameter 4</b>	number of blocks in raw partition
<b>Probable Cause</b>	When creating a dbspace on a raw partition, if the user specifies the dbspace's size, then it must exactly match the size of the raw partition.
<b>Error 1010008</b>	<b>"For an IQ PAGE SIZE of %2, the dbspace '%3' must have at least %4 MB. %1"</b>
<b>Constant</b>	EMSG_DATABASE_DBNBLOCKS
<b>SAP Sybase Error Number</b>	20981
<b>SQL State</b>	QXA08
<b>SQL Code</b>	-1010008L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	page size
<b>Parameter 3</b>	dbspace name
<b>Parameter 4</b>	required minimum size in mega-bytes
<b>Probable Cause</b>	The named dbspace must have the stated minimum size in megabytes.
<b>Error 1010009</b>	<b>"Improper use of cursor - programmer error %1"</b>
<b>Constant</b>	EMSG_CURSOR_PROG_ERROR
<b>SAP Sybase Error Number</b>	21005
<b>SQL State</b>	QXA09
<b>SQL Code</b>	-1010009L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1010009</b>	<b>"Improper use of cursor - programmer error %1"</b>
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	The programmer has misused the internal cursor class(es)
<b>Error 1010010</b>	<b>"An invalid attribute flag was passed to the cursor"</b>
<b>Constant</b>	EMSG_CURSOR_INVALID_ATTRIBUTE
<b>SAP Sybase Error Number</b>	21006
<b>SQL State</b>	QXA10
<b>SQL Code</b>	-1010010L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	A state violation was detected in the cursor
<b>Error 1010011</b>	<b>"Not enough server threads available for this query."</b>
<b>Constant</b>	EMSG_CURSOR_NO_THREADS
<b>SAP Sybase Error Number</b>	21007
<b>SQL State</b>	QXA11
<b>SQL Code</b>	-1010011L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No thread could be allocated to allow this query to be executed
<b>Error 1010012</b>	<b>"The cursor is in an invalid state %1"</b>
<b>Constant</b>	EMSG_CURSOR_INVALID_STATE
<b>SAP Sybase Error Number</b>	21008
<b>SQL State</b>	QXA12

## Errors and Warnings

<b>Error 1010012</b>	"The cursor is in an invalid state %1"
<b>SQL Code</b>	-1010012L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	A state violation was detected in the cursor
<b>Warning 1010013</b>	<b>"IQ cannot support the %1 connections requested by the server.\nRestart the server with -gm %2 on the command line."</b>
<b>Constant</b>	EMSG_CONN_INFO
<b>SAP Sybase Error Number</b>	21024
<b>SQL State</b>	00A13
<b>SQL Code</b>	1010013L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	the number of connections
<b>Parameter 2</b>	the number of supported connections
<b>Probable Cause</b>	Inform the DBA about the number of connection
<b>Error 1010013</b>	<b>"Raw partition %2 is already in use. %1"</b>
<b>Constant</b>	EMSG_RAW_PARTITION_INUSE
<b>SAP Sybase Error Number</b>	21025
<b>SQL State</b>	QXA13
<b>SQL Code</b>	-1010013L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1010013</b>	<b>"Raw partition %2 is already in use. %1"</b>
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	name of the raw partition
<b>Probable Cause</b>	User attempted to create dbspace on a raw partition which is currently in use by the database.
<b>Warning 1010014</b>	<b>"Default cache size is used for command %1."</b>
<b>Constant</b>	EMSG_DEFAULTCACHESIZEUSED
<b>SAP Sybase Error Number</b>	21058
<b>SQL State</b>	QXA14
<b>SQL Code</b>	1010014L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	command type
<b>Probable Cause</b>	warning is issued for the command that uses the default cache size
<b>Error 1010015</b>	<b>"The MAIN store is out of space. Space must be added to the MAIN store first. %1"</b>
<b>Constant</b>	EMSG_DATABASE_MSNOSPACE
<b>SAP Sybase Error Number</b>	21075
<b>SQL State</b>	QXA15
<b>SQL Code</b>	-1010015L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	The MAIN store is out of space. Space must be added to the MAIN store before space can be added to any other store.

## Errors and Warnings

<b>Error 1010016</b>	"The TEMPORARY store is out of space. Space must be added to the TEMPORARY store first. %1"
<b>Constant</b>	EMSG_DATABASE_TSNOSPACE
<b>SAP Sybase Error Number</b>	21076
<b>SQL State</b>	QXA16
<b>SQL Code</b>	-1010016L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	The TEMPORARY store is out of space. Space must be added to the TEMPORARY store before space can be added to any other store.

<b>Error 1010017</b>	"You cannot create tables on a secondary server without a readwrite local IQ Store. %1"
<b>Constant</b>	EMSG_DATABASE_MPX_NOLOCAL
<b>SAP Sybase Error Number</b>	21111
<b>SQL State</b>	QXA17
<b>SQL Code</b>	-1010017L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	MPX secondary servers can only create IQ objects in a local store.

<b>Error 1010019</b>	"Cannot modify object %2 on dbspace %3. %1"
<b>Constant</b>	EMSG_DATABASE_MPX_NOROMAIN
<b>SAP Sybase Error Number</b>	21113
<b>SQL State</b>	QXA19
<b>SQL Code</b>	-1010019L

<b>Error 1010019</b>	"Cannot modify object %2 on dbspace %3. %1"
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	object name
<b>Parameter 3</b>	dbspace name
<b>Probable Cause</b>	A generic error indicating error in modifying an object.

## Messages 1010020 through 1010040

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1010020</b>	"Backup not allowed on secondary servers. %1"
<b>Constant</b>	EMSG_DATABASE_MPX_NOLOCALFORBU
<b>SAP Sybase Error Number</b>	21114
<b>SQL State</b>	QXA20
<b>SQL Code</b>	-1010020L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	The backup command is not allowed to be executed on a secondary server. Execute the command on the coordinator.

<b>Error 1010021</b>	"Foreign key constraint on a local table cannot reference a shared table. %1"
<b>Constant</b>	EMSG_DATABASE_MPX_NOXKEYS
<b>SAP Sybase Error Number</b>	21115
<b>SQL State</b>	QXA21
<b>SQL Code</b>	-1010021L

## Errors and Warnings

<b>Error 1010021</b>	<b>"Foreign key constraint on a local table cannot reference a shared table. %1"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	Cannot combine main and local tables in a foreign key relationship.
<b>Error 1010022</b>	<b>"Cannot modify main store from a multiplex query server. %1"</b>
<b>Constant</b>	EMSG_DATABASE_MPX_NOMAINRWACCESS
<b>SAP Sybase Error Number</b>	21117
<b>SQL State</b>	QXA22
<b>SQL Code</b>	-1010022L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	The general error when a query server tries to modify the shared main store. There are other more detailed messages for specific cases.
<b>Error 1010023</b>	<b>"Cursor is not updatable: %2. %1"</b>
<b>Constant</b>	EMSG_CURSOR_NOT_UPDATABLE
<b>SAP Sybase Error Number</b>	21121
<b>SQL State</b>	QXA23
<b>SQL Code</b>	-1010023L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of exception.

<b>Error 1010023</b>	<b>"Cursor is not updatable: %2. %1"</b>
<b>Parameter 2</b>	Reason why the cursor is not updatable.
<b>Probable Cause</b>	Cursor is not updatable: there are join/group by/distinct/set, union, olap function, or no updatable columns.
<b>Error 1010024</b>	<b>"Column '%2' is not updatable. %1"</b>
<b>Constant</b>	EMSG_COLUMN_NOT_UPDATABLE
<b>SAP Sybase Error Number</b>	21122
<b>SQL State</b>	QXA24
<b>SQL Code</b>	-1010024L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of exception.
<b>Parameter 2</b>	Column name.
<b>Probable Cause</b>	Column is not updatable if it is long binary/varchar, rowid, (var)binary when ASE_Binary_Display is ON, referenced by other expressions in the select list, identity column, or not in FOR UPDATE of list.
<b>Error 1010025</b>	<b>"Cannot restore to multiplex secondary server. %1"</b>
<b>Constant</b>	EMSG_DATABASE_MPX_NOLOCALFORRESTORE
<b>SAP Sybase Error Number</b>	21125
<b>SQL State</b>	QXA25
<b>SQL Code</b>	-1010025L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	Multiplex secondary server cannot be restored. Only the coordinator can be restored.

## Errors and Warnings

<b>Error 1010026</b>	<b>"Only a server in single_node mode can become a coordinator %1"</b>
<b>Constant</b>	EMSG_DATABASE_MPX_CANTBECOMEWRITER
<b>SAP Sybase Error Number</b>	21126
<b>SQL State</b>	QXA26
<b>SQL Code</b>	-1010026L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	Must be in simplex mode to convert to coordinator mode.
<b>Error 1010027</b>	<b>"Only a server in coordinator mode can become a single_node server %1"</b>
<b>Constant</b>	EMSG_DATABASE_MPX_CANTBECOMESPX
<b>SAP Sybase Error Number</b>	21127
<b>SQL State</b>	QXA27
<b>SQL Code</b>	-1010027L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	Must be in coordinator mode to convert to simplex.
<b>Error 1010028</b>	<b>"A secondary server may not drop or alter a domain owned by the coordinator. %1"</b>
<b>Constant</b>	EMSG_DATABASE_MPX_QNODEDOESNOTOWNDOMAIN
<b>SAP Sybase Error Number</b>	21128
<b>SQL State</b>	QXA28
<b>SQL Code</b>	-1010028L

<b>Error 1010028</b>	<b>"A secondary server may not drop or alter a domain owned by the coordinator. %1"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	Cannot drop a domain on a secondary server unless the secondary server owns the domain.

<b>Error 1010030</b>	<b>"Wrong multiplex mode for this restore. %1"</b>
<b>Constant</b>	EMSG_DATABASE_MPX_WRONGMODEFORRESTORE
<b>SAP Sybase Error Number</b>	21130
<b>SQL State</b>	QXA30
<b>SQL Code</b>	-1010030L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	The mpx mode does not match the restore type.

<b>Error 1010031</b>	<b>"Cannot modify object %2 on dbspace %3. A query server may not modify objects in the main IQ store. %1"</b>
<b>Constant</b>	EMSG_DATABASE_MPX_QUERY_NOWRITE
<b>SAP Sybase Error Number</b>	21131
<b>SQL State</b>	QXA31
<b>SQL Code</b>	-1010031L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.

## Errors and Warnings

<b>Error 1010031</b>	<b>"Cannot modify object %2 on dbspace %3. A query server may not modify objects in the main IQ store. %1"</b>
<b>Parameter 2</b>	object name
<b>Parameter 3</b>	dbspace name
<b>Probable Cause</b>	A query server may not modify objects in the main store.
<b>Error 1010032</b>	<b>"Bad Database Identity block. %1"</b>
<b>Constant</b>	EMSG_DATABASE_MPX_BADDIBID
<b>SAP Sybase Error Number</b>	21132
<b>SQL State</b>	QXA32
<b>SQL Code</b>	-1010032L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	The secondary server has too many or too few shared main dbspaces defined.
<b>Error 1010033</b>	<b>"This secondary server was not shut down cleanly before synchronize. Must start with -iqfrec %1"</b>
<b>Constant</b>	EMSG_DATABASE_MPX_READERNOTSHUTDOWNCLEANLY
<b>SAP Sybase Error Number</b>	21133
<b>SQL State</b>	QXA33
<b>SQL Code</b>	-1010033L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	Must start with iqfrec to rebuild freelist.

<b>Error 1010034</b>	<b>"Modifications of the iq main store not allowed in readonly mode. %1"</b>
<b>Constant</b>	EMSG_DATABASE_MPX_NOWRITEIFREADONLY
<b>SAP Sybase Error Number</b>	21134
<b>SQL State</b>	QXA34
<b>SQL Code</b>	-1010034L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	The mpx mode does not match the restore type.
<b>Error 1010035</b>	<b>"The transaction log does not match the mpx mode of this server. %1"</b>
<b>Constant</b>	EMSG_DATABASE_MPX_LOGDBMODEISMISMATCH
<b>SAP Sybase Error Number</b>	21135
<b>SQL State</b>	QXA35
<b>SQL Code</b>	-1010035L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	The mpx mode does not match the transaction log.
<b>Error 1010036</b>	<b>"MPX: invalid file_id. Single_node or coordinator using a local or bad fileId. %1"</b>
<b>Constant</b>	EMSG_DATABASE_MPX_BADFILEID
<b>SAP Sybase Error Number</b>	21136
<b>SQL State</b>	QXA36
<b>SQL Code</b>	-1010036L

## Errors and Warnings

<b>Error 1010036</b>	"MPX: invalid file_id. Single_node or coordinator using a local or bad fileId. %1"
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	The fileid is not valid for this mpx mode.
<b>Error 1010037</b>	"MPX: invalid local file_id. Secondary server using a bad local fileId. %1"
<b>Constant</b>	EMSG_DATABASE_MPX_BADLOCALFILEID
<b>SAP Sybase Error Number</b>	21137
<b>SQL State</b>	QXA37
<b>SQL Code</b>	-1010037L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	The local fileid is not valid for this mpx mode.
<b>Error 1010038</b>	"MPX: Local stores are not supported. %1"
<b>Constant</b>	EMSG_DATABASE_MPX_NOLOCALFILEID
<b>SAP Sybase Error Number</b>	21138
<b>SQL State</b>	QXA38
<b>SQL Code</b>	-1010038L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.

<b>Error 1010038</b>	<b>"MPX: Local stores are not supported. %1"</b>
<b>Probable Cause</b>	The local fileid is not valid for this mpx mode.
<b>Error 1010039</b>	<b>"MPX: Inconsistent Transaction Manager Data. %1"</b>
<b>Constant</b>	EMSG_DATABASE_MPX_TXNMGRCHECK
<b>SAP Sybase Error Number</b>	21139
<b>SQL State</b>	QXA39
<b>SQL Code</b>	-1010039L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	The local fileid is not valid for this mpx mode.
<b>Error 1010040</b>	<b>"Cannot restore to multiplex secondary server without a local store. %1"</b>
<b>Constant</b>	EMSG_DATABASE_UNDEFINEDUTILITYCMD
<b>SAP Sybase Error Number</b>	21140
<b>SQL State</b>	QXA40
<b>SQL Code</b>	-1010040L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	A secondary server must have local store dbspaces defined in order to do a restore.

**Messages 1010041 through 1010060**

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1010041</b>	<b>"Inconsistent data during OpenDatabase. %1"</b>
<b>Constant</b>	EMSG_DATABASE_OPENDBCHECK
<b>SAP Sybase Error Number</b>	21141
<b>SQL State</b>	QXA41
<b>SQL Code</b>	-1010041L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	Open database check failure.
<b>Error 1010042</b>	<b>"\"drop leaks\" is not allowed without executing post-sync secondary server replay. %1"</b>
<b>Constant</b>	EMSG_DBCC_DROPLEAKS_NEED_LOCAL_REPLY
<b>SAP Sybase Error Number</b>	21142
<b>SQL State</b>	QDB73
<b>SQL Code</b>	-1010042L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	Disallow DBCC to drop leaked blocks on a MPX secondary server without executing post-sync local TLV replay.
<b>Error 1010043</b>	<b>"dbspace %2 is currently not open. %1"</b>
<b>Constant</b>	EMSG_DATABASE_DBSPACE_NOT_OPENED

<b>Error 1010043</b>	" <b>dbspace %2 is currently not open. %1</b> "
<b>SAP Sybase Error Number</b>	21144
<b>SQL State</b>	QXA42
<b>SQL Code</b>	-1010043L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Name of dbspace
<b>Parameter 2</b>	Location of the exception.
<b>Probable Cause</b>	The specified dbspace exists but is not currently open.

<b>Error 1010044</b>	" <b>Plan not available.</b> "
<b>Constant</b>	EMSG_QPTCACHE_NOPLAN
<b>SAP Sybase Error Number</b>	21146
<b>SQL State</b>	QXA43
<b>SQL Code</b>	-1010044L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	"User request for the plan and there is no plan in the cache to be returned. cases when this error will be returned :1. User makes a connection and executes select graphical_plan() or select html_plan(). 2. When the the SQL function graphical_plan and html_plan is used to get the plan for an IQ query for which IQ does not generate plan. "

<b>Error 1010045</b>	" <b>Plan not available. Plan type is not supported for Sybase IQ queries.</b> "
<b>Constant</b>	EMSG_QPTCACHE_INVALID_PLANTYPE
<b>SAP Sybase Error Number</b>	21147
<b>SQL State</b>	QXA44

## Errors and Warnings

<b>Error 1010045</b>	"Plan not available. Plan type is not supported for Sybase IQ queries."
<b>SQL Code</b>	-1010045L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	"IQ supports only graphical_plan and html_plan SQL functions. Other SA plan functions (plan, explanation etc.) are not supported for Sybase IQ."
<b>Error 1010046</b>	"Plan not available. The database option QUERY_PLAN_TEXT_ACCESS is off."
<b>Constant</b>	EMSG_QPTCACHE_ACCESS_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	21148
<b>SQL State</b>	QXA45
<b>SQL Code</b>	-1010046L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	"The plan can be accessed on the client by the user only when DBA sets option QUERY_PLAN_TEXT_ACCESS to ON for the user."
<b>Error 1010047</b>	"%1 is not designated as failover server"
<b>Constant</b>	EMSG_IQMPX_NOT_FAILOVER
<b>SAP Sybase Error Number</b>	21176
<b>SQL State</b>	QXA46
<b>SQL Code</b>	-1010047L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2

<b>Error 1010047</b>	<b>"%1 is not designated as failover server"</b>
<b>Parameter 1</b>	server name
<b>Probable Cause</b>	Failover process is started on a server which is not designated as failover server
<b>Error 1010048</b>	<b>"iqmpx_failover and iqmpx_sn switches cannot be enabled simultaneously"</b>
<b>Constant</b>	EMSG_IQMPX_CANNOT_MIX_FAILOVER_SN
<b>SAP Sybase Error Number</b>	21177
<b>SQL State</b>	QXA47
<b>SQL Code</b>	-1010048L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	While starting an IQ server, both iqmpx_failover and iqmpx_sn command line server switches are ON.
<b>Error 1010049</b>	<b>"Transaction log recovery not allowed during failover. Please restart the server without the failover switch, do a clean shutdown, restart failover"</b>
<b>Constant</b>	EMSG_IQMPX_NO_RECOVERY_IN_FAILOVER
<b>SAP Sybase Error Number</b>	21178
<b>SQL State</b>	QXA48
<b>SQL Code</b>	-1010049L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	The failover process should be started only after clean shutdown of the server. If recovery process is initiated during failover then the server was not shut down cleanly and failover should be restarted after the server is restarted and shut down without the failover switch.

## Errors and Warnings

<b>Error 1010050</b>	<b>"Recovery required to complete the last failover process. Please restart the server with failover switch"</b>
<b>Constant</b>	EMSG_IQMPX_START_IN_FAILOVER
<b>SAP Sybase Error Number</b>	21179
<b>SQL State</b>	QXA49
<b>SQL Code</b>	-1010050L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	A previous failover attempt did not finish cleanly. The failover changes must be recovered and to do that restart the server with failover switch.
<b>Error 1010051</b>	<b>"Failover node catalog is not in sync with TLV log. Please restart server without failover switch, run BEGIN TRANSACTION, do a clean shutdown, then restart failover "</b>
<b>Constant</b>	EMSG_IQMPX_FAILOVER_CAT_OUT_OF_SYNC
<b>SAP Sybase Error Number</b>	21180
<b>SQL State</b>	QXA50
<b>SQL Code</b>	-1010051L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	The failover process can be started only if the failover node's catalog is up to date with the TLV log. To fix this, restart the server without the failover switch, run BEGIN TRANSACTION, do a clean shutdown, then restart the server with the failover switch.
<b>Error 1010052</b>	<b>"Only one dbspace file may be added at a time for multiplex servers"</b>
<b>Constant</b>	EMSG_IQMPX_ALTERADD_MULTIPLE_FILES

<b>Error 1010052</b>	<b>"Only one dbspace file may be added at a time for multiplex servers"</b>
<b>SAP Sybase Error Number</b>	21183
<b>SQL State</b>	QXA51
<b>SQL Code</b>	-1010052L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	When using ALTER DBSPACE to add a file to a multiplex server, only one file may be added at a time. Specifying a list of files to add is not supported.
<b>Error 1010053</b>	<b>"DBSPACE command extended syntax not permitted"</b>
<b>Constant</b>	EMSG_DBSPACE_EXTENDED_SYNTAX
<b>SAP Sybase Error Number</b>	21184
<b>SQL State</b>	QXA52
<b>SQL Code</b>	-1010053L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	When using ALTER DBSPACE command, extended syntax is not allowed on a user connection
<b>Error 1010054</b>	<b>"Server option '-iqmpx_ov' only valid when used with '-iqmpx_sn' or '-iqmpx_failover'. %1"</b>
<b>Constant</b>	EMSG_MPX_OV_INVALID_USE
<b>SAP Sybase Error Number</b>	21186
<b>SQL State</b>	QXA53
<b>SQL Code</b>	-1010054L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 1010054</b>	<b>"Server option '-iqmpx_ov' only valid when used with '-iqmpx_sn' or '-iqmpx_failover'. %1"</b>
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Server option '-iqmpx_ov' is permitted on an Multiplex coordinator node or in combination with either '-iqmpx_sn' or '-iqmpx_failover' on any other Multiplex node type.
<b>Error 1010055</b>	<b>"iqmpx_reclaimwriterfreelist server switch can not be used in Simplex or Secondary nodes"</b>
<b>Constant</b>	EMSG_MPX_SWITCH_INVALID_FOR_SPX_OR_SECONDARY
<b>SAP Sybase Error Number</b>	21187
<b>SQL State</b>	QXA54
<b>SQL Code</b>	-1010055L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	iqmpx_reclaimwriterfreelist server switch can only be used on a Coordinator node.
<b>Error 1010056</b>	<b>"Recovery switch '-iqfrec' is allowed on a multiplex server only in single-node operating mode. %1"</b>
<b>Constant</b>	EMSG_MPX_FREC_INVALID_USE
<b>SAP Sybase Error Number</b>	21188
<b>SQL State</b>	QXA55
<b>SQL Code</b>	-1010056L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception

<b>Error 1010056</b>	<b>"Recovery switch '-iqfrec' is allowed on a multiplex server only in single-node operating mode. %1"</b>
<b>Probable Cause</b>	Recovery switch '-iqfrec' is allowed on a multiplex server only in single-node operating mode.
<b>Error 1010057</b>	<b>"'%2' command is not allowed on temp store files, when server started with -iqnotemp switch. %1"</b>
<b>Constant</b>	EMSG_ILLEGAL_ALTER_DBSPACE_NOTEMP
<b>SAP Sybase Error Number</b>	21201
<b>SQL State</b>	QXA56
<b>SQL Code</b>	-1010057L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	alter dbspace command type string
<b>Probable Cause</b>	When the server is running with -iqnotemp switch, certain alter dbspace operations are not allowed. For e.g. alter dbspace add file.
<b>Error 1010058</b>	<b>"Unable to perform forced recovery when database is in read only mode. %1"</b>
<b>Constant</b>	EMSG_FREC_IN_READ_ONLY
<b>SAP Sybase Error Number</b>	21202
<b>SQL State</b>	QXA57
<b>SQL Code</b>	-1010058L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Recovery switch '-iqfrec' is allowed on read/write databases only

## Errors and Warnings

<b>Error 1010059</b>	<b>"Unable to open the multiplex database. The database can only be opened by starting the Coordinator server using single node mode switch '-iqmpx_sn 1'. %1"</b>
<b>Constant</b>	EMSG_MPX_OPEN_OLDDB_NEED_SINGLE
<b>SAP Sybase Error Number</b>	22023
<b>SQL State</b>	QXA58
<b>SQL Code</b>	-1010059L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	An older version of multiplex database can only be opened by starting the server in single node mode. If you get this error after upgrading the database when the server was started using '-iqro 1', then the database still needs to be opened by starting the coordinator server in single node mode but without '-iqro 1'. This is because the internal IQ on-disk structures could not be upgraded earlier. To complete the upgrade, open the database by starting the coordinator server using single node mode switch '-iqmpx_sn 1', but without '-iqro 1'. After a clean shutdown, the database can then be started normally.
<b>Error 1010060</b>	<b>"Server option -iqmpx_nowr only allowed when there are no writers in multiplex %1"</b>
<b>Constant</b>	EMSG_MPX_NOWR_INVALID_USE
<b>SAP Sybase Error Number</b>	21212
<b>SQL State</b>	QXA60
<b>SQL Code</b>	-1010060L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	location of the exception

<b>Error 1010060</b>	<b>"Server option -iqmpx_nowr only allowed when there are no writers in multiplex %1"</b>
<b>Probable Cause</b>	Please restart coordinator without -iqmpx_nowr switch to add a writer

## Messages 1010061 through 1012005

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1010061</b>	<b>"Server switch -iqmpx_nowr only allowed on coordinator node %1"</b>
<b>Constant</b>	EMSG_MPX_NOWR_INVALID_USE_NOTCNODE
<b>SAP Sybase Error Number</b>	21213
<b>SQL State</b>	QXA61
<b>SQL Code</b>	-1010061L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Please restart the server without -iqmpx_nowr switch

<b>Error 1010062</b>	<b>"Unable to open the database. Start the coordinator server first, without server option -iqro, to complete the Database Upgrade. %1"</b>
<b>Constant</b>	EMSG_MPX_START_COORD_FIRST
<b>SAP Sybase Error Number</b>	22029
<b>SQL State</b>	QXA62
<b>SQL Code</b>	-1010062L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2

## Errors and Warnings

<b>Error 1010062</b>	<b>"Unable to open the database. Start the coordinator server first, without server option -iqro, to complete the Database Upgrade. %1"</b>
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	As IQ store was opened in RO mode when you upgraded the database, some of its internal meta-data information could not be upgraded to new format. Please start the coordinator server first, without server option -iqro, to complete the IQ side upgrade and continue.

<b>Error 1011000</b>	<b>"Vertical Projection Cursor state error %1"</b>
<b>Constant</b>	EMSG_CURSORSTATEERROR
<b>SAP Sybase Error Number</b>	20000
<b>SQL State</b>	QVA00
<b>SQL Code</b>	-1011000L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1011001</b>	<b>"Cannot find index for a given dfe %1"</b>
<b>Constant</b>	EMSG_INDEXNOTFOUND
<b>SAP Sybase Error Number</b>	20001
<b>SQL State</b>	QVA01
<b>SQL Code</b>	-1011001L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>18</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1011002</b>	"The number of existing indexes exceeds the current maximum number of indexes. %1"
<b>Constant</b>	EMSG_EXCEEDEDMAXINDEXES
<b>SAP Sybase Error Number</b>	20002
<b>SQL State</b>	QVA02
<b>SQL Code</b>	-1011002L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1011003</b>	"Vertical Projection Cursor does not support AD-HOC joins. %1"
<b>Constant</b>	EMSG_ADHOCJOINREQUIRED
<b>SAP Sybase Error Number</b>	20003
<b>SQL State</b>	QVA03
<b>SQL Code</b>	-1011003L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	14 on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1011004</b>	"Cannot drop primary key or unique constraint because a foreign key still references it."
<b>Constant</b>	EMSG_FKEY_STILL_EXISTS_TO_CKEY
<b>SAP Sybase Error Number</b>	20004
<b>SQL State</b>	QNA27

## Errors and Warnings

<b>Error 1011004</b>	<b>"Cannot drop primary key or unique constraint because a foreign key still references it."</b>
<b>SQL Code</b>	-1011004L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	A primary key or unique constraint involved in a referential integrity relationship cannot be dropped until its corresponding foreign key is first dropped.
<b>Error 1011006</b>	<b>"the pattern argument in a like predicate must have string datatype."</b>
<b>Constant</b>	EMSG_INVALIDDATATYPE
<b>SAP Sybase Error Number</b>	20006
<b>SQL State</b>	QVA06
<b>SQL Code</b>	-1011006L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1011007</b>	<b>"the escape argument in a like predicate must be a one byte character."</b>
<b>Constant</b>	EMSG_INVALIDESCAPE
<b>SAP Sybase Error Number</b>	20007
<b>SQL State</b>	QVA07
<b>SQL Code</b>	-1011007L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.

<b>Error 1011009</b>	"Group (L)"
<b>Constant</b>	EMSG_VPGP_GB_COL_LFS
<b>SAP Sybase Error Number</b>	20009
<b>SQL State</b>	QVA09
<b>SQL Code</b>	-1011009L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1011010</b>	"Group (S)"
<b>Constant</b>	EMSG_VPGP_GB_COL_SFS
<b>SAP Sybase Error Number</b>	20010
<b>SQL State</b>	QVA10
<b>SQL Code</b>	-1011010L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1011011</b>	"Aggregate (L)"
<b>Constant</b>	EMSG_VPGP_AGG_LFS
<b>SAP Sybase Error Number</b>	20011
<b>SQL State</b>	QVA11
<b>SQL Code</b>	-1011011L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.

## Errors and Warnings

<b>Error 1011012</b>	"Aggregate (S)"
<b>Constant</b>	EMSG_VPGP_AGG_SFS
<b>SAP Sybase Error Number</b>	20012
<b>SQL State</b>	QVA12
<b>SQL Code</b>	-1011012L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1011013</b>	"Projection"
<b>Constant</b>	EMSG_VPGP_PROJ
<b>SAP Sybase Error Number</b>	20013
<b>SQL State</b>	QVA13
<b>SQL Code</b>	-1011013L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1012000</b>	<b>"You cannot do a partial restore for database '%2' because it has been updated (%3) since its last backup (%4). %1"</b>
<b>Constant</b>	EMSG_RESTORE_MORE_RECENT_UPDATETIME
<b>SAP Sybase Error Number</b>	20923
<b>SQL State</b>	QUA00
<b>SQL Code</b>	-1012000L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2

<b>Error 1012000</b>	<b>"You cannot do a partial restore for database '%2' because it has been updated (%3) since its last backup (%4). %1"</b>
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	database
<b>Parameter 3</b>	last update
<b>Parameter 4</b>	last backup
<b>Probable Cause</b>	No additional information available.
<b>Error 1012001</b>	<b>"There is already a backup or selective restore in progress. %1"</b>
<b>Constant</b>	EMSG_BACKUP_MULTIPLE_IN_PROGRESS
<b>SAP Sybase Error Number</b>	20924
<b>SQL State</b>	QUA01
<b>SQL Code</b>	-1012001L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1012002</b>	<b>"Unable to write to archive. ('%2') %1"</b>
<b>Constant</b>	EMSG_BACKUP_DEVICE_WRITEERROR
<b>SAP Sybase Error Number</b>	20925
<b>SQL State</b>	QUA02
<b>SQL Code</b>	-1012002L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception

## Errors and Warnings

<b>Error 1012002</b>	<b>"Unable to write to archive. ('%2') %1"</b>
<b>Parameter 2</b>	explanation for %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1012003</b>	<b>"You must do a full backup before doing an incremental backup. %1"</b>
<b>Constant</b>	EMSG_BACKUP_NEED_FULL_FIRST
<b>SAP Sybase Error Number</b>	20926
<b>SQL State</b>	QUA03
<b>SQL Code</b>	-1012003L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1012004</b>	<b>"You cannot do incremental backups with this release. %1"</b>
<b>Constant</b>	EMSG_BACKUP_INC_NOT_IMPLEMENTED
<b>SAP Sybase Error Number</b>	20927
<b>SQL State</b>	QUA04
<b>SQL Code</b>	-1012004L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1012005</b>	<b>"Server is reporting no files in the database. %1"</b>
<b>Constant</b>	EMSG_BACKUP_SA_NUMFILES_ZERO
<b>SAP Sybase Error Number</b>	20928

<b>Error 1012005</b>	<b>"Server is reporting no files in the database. %1"</b>
<b>SQL State</b>	QUA05
<b>SQL Code</b>	-1012005L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

## **Messages 1012006 through 1012025**

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1012006</b>	<b>"Server reports '%2' files in IQ store, IQ reports '%3'. %1"</b>
<b>Constant</b>	EMSG_BACKUP_SA_IQ_NUMFILES_DISAGREE
<b>SAP Sybase Error Number</b>	20929
<b>SQL State</b>	QUA06
<b>SQL Code</b>	-1012006L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for %2
<b>Parameter 3</b>	explanation for %3
<b>Probable Cause</b>	No additional information available.

<b>Error 1012007</b>	<b>"IQ unable to find all files to back up. %1"</b>
<b>Constant</b>	EMSG_BACKUP_NO_FILES
<b>SAP Sybase Error Number</b>	20930
<b>SQL State</b>	QUA07

## Errors and Warnings

<b>Error 1012007</b>	<b>"IQ unable to find all files to back up. %1"</b>
<b>SQL Code</b>	-1012007L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1012008</b>	<b>"Database has changed since last restore. %1"</b>
<b>Constant</b>	EMSG_RESTORE_DBCHANGED
<b>SAP Sybase Error Number</b>	20931
<b>SQL State</b>	QUA08
<b>SQL Code</b>	-1012008L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1012009</b>	<b>"This restore cannot immediately follow the previous restore. %1"</b>
<b>Constant</b>	EMSG_RESTORE_BAD_PREVRESTORE
<b>SAP Sybase Error Number</b>	20932
<b>SQL State</b>	QUA09
<b>SQL Code</b>	-1012009L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception

<b>Error 1012009</b>	<b>"This restore cannot immediately follow the previous restore. %1"</b>
<b>Probable Cause</b>	No additional information available.
<b>Error 1012010</b>	<b>"Unable to read from archive ('%2'). %1"</b>
<b>Constant</b>	EMSG_RESTORE_READ_IOERROR
<b>SAP Sybase Error Number</b>	20933
<b>SQL State</b>	QUA10
<b>SQL Code</b>	-1012010L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1012011</b>	<b>"Header of block to be restored appears to be corrupted. %1"</b>
<b>Constant</b>	EMSG_RESTORE_BAD_BLOCK_HEADER
<b>SAP Sybase Error Number</b>	20934
<b>SQL State</b>	QUA11
<b>SQL Code</b>	-1012011L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1012012</b>	<b>"Media data appears corrupted (bad checksum). %1"</b>
<b>Constant</b>	EMSG_RESTORE_BAD_CRC

## Errors and Warnings

<b>Error 1012012</b>	<b>"Media data appears corrupted (bad checksum). %1"</b>
<b>SAP Sybase Error Number</b>	20935
<b>SQL State</b>	QUA12
<b>SQL Code</b>	-1012012L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1012013</b>	<b>"Media meta data appears corrupted (boundary record). %1"</b>
<b>Constant</b>	EMSG_RESTORE_BAD_BOUNDARY_RECORD
<b>SAP Sybase Error Number</b>	20936
<b>SQL State</b>	QUA13
<b>SQL Code</b>	-1012013L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1012014</b>	<b>"Media meta data appear corrupted (multiple begin boundary records). %1"</b>
<b>Constant</b>	EMSG_RESTORE_MULTIPLE_BEGIN_BOUNDARY_RECORDS
<b>SAP Sybase Error Number</b>	20937
<b>SQL State</b>	QUA14
<b>SQL Code</b>	-1012014L
<b>ODBC 2 State</b>	ERROR

<b>Error 1012014</b>	"Media meta data appear corrupted (multiple begin boundary records). %1"
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1012015</b>	"Media meta data appears corrupted (missing begin boundary record). %1"
<b>Constant</b>	EMSG_RESTORE_MISSING_BEGIN_BOUNDARY_RECORD
<b>SAP Sybase Error Number</b>	20938
<b>SQL State</b>	QUA15
<b>SQL Code</b>	-1012015L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1012016</b>	"Restoring database "%2" has failed because not all media required for restoring "%3" were supplied. %1"
<b>Constant</b>	EMSG_RESTORE_INCOMPLETE
<b>SAP Sybase Error Number</b>	20939
<b>SQL State</b>	QUA16
<b>SQL Code</b>	-1012016L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for %2

## Errors and Warnings

<b>Error 1012016</b>	<b>"Restoring database "%2' has failed because not all media required for restoring "%3' were supplied. %1"</b>
<b>Parameter 3</b>	explanation for %3
<b>Probable Cause</b>	No additional information available.
<b>Error 1012017</b>	<b>"An I/O write error has occurred on '%2'. The restore query has failed. %1"</b>
<b>Constant</b>	EMSG_RESTORE_WRITE_IOERROR
<b>SAP Sybase Error Number</b>	20940
<b>SQL State</b>	QUA17
<b>SQL Code</b>	-1012017L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for %2
<b>Probable Cause</b>	No additional information available.
<b>Error 1012018</b>	<b>"An I/O read error has occurred on "%2'. The backup query has failed. %1"</b>
<b>Constant</b>	EMSG_BACKUP_READ_IOERROR
<b>SAP Sybase Error Number</b>	20941
<b>SQL State</b>	QUA18
<b>SQL Code</b>	-1012018L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1012019</b>	<b>".db or .log file does not exist. Incremental restore not possible. %1"</b>
<b>Constant</b>	EMSG_RESTORE_SADB_FILE_DOES_NOT_EXIST
<b>SAP Sybase Error Number</b>	20942
<b>SQL State</b>	QUA19
<b>SQL Code</b>	-1012019L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1012020</b>	<b>"Wrong IQ backup tape or file. %1"</b>
<b>Constant</b>	EMSG_RESTORE_WRONG_ARCHIVE
<b>SAP Sybase Error Number</b>	20943
<b>SQL State</b>	QUA20
<b>SQL Code</b>	-1012020L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1012021</b>	<b>"Backup Internal Error. %1"</b>
<b>Constant</b>	EMSG_BACKUP_INTERNAL_ERROR
<b>SAP Sybase Error Number</b>	20944
<b>SQL State</b>	QUA21
<b>SQL Code</b>	-1012021L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1012021</b>	<b>"Backup Internal Error. %1"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1012022</b>	<b>"Restore Internal Error. %1"</b>
<b>Constant</b>	EMSG_RESTORE_INTERNAL_ERROR
<b>SAP Sybase Error Number</b>	20945
<b>SQL State</b>	QUA22
<b>SQL Code</b>	-1012022L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1012023</b>	<b>"Not an IQ backup tape or file. %1"</b>
<b>Constant</b>	EMSG_RESTORE_NOT_IQ_ARCHIVE
<b>SAP Sybase Error Number</b>	20946
<b>SQL State</b>	QUA23
<b>SQL Code</b>	-1012023L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1012024</b>	"Ran out of threads. Start up server with more threads. %1"
<b>Constant</b>	EMSG_RESTORE_OUT_OF_THREADS
<b>SAP Sybase Error Number</b>	20947
<b>SQL State</b>	QUA24
<b>SQL Code</b>	-1012024L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1012025</b>	".db or .log file exists. Full restore will not be done. %1"
<b>Constant</b>	EMSG_RESTORE_SADB_FILE_EXISTS
<b>SAP Sybase Error Number</b>	20948
<b>SQL State</b>	QUA25
<b>SQL Code</b>	-1012025L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

## Messages 1012026 through 1012045

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Warning 1012026</b>	"Number of IQ blocks backed up: %1"
<b>Constant</b>	EMSG_BACKUP_BLOCK_COUNT
<b>SAP Sybase Error Number</b>	20949

## Errors and Warnings

<b>Warning 1012026</b>	"Number of IQ blocks backed up: %1"
<b>SQL State</b>	QUA26
<b>SQL Code</b>	1012026L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	number of blocks
<b>Probable Cause</b>	No additional information available.
<b>Warning 1012027</b>	<b>"Total number of IQ blocks backed Up: %1\n at %2\n\tIQ Blocksize %3\n\tbackup Blocksize %4\n\tblocking factor %5\n\tbuffer size %6"</b>
<b>Constant</b>	EMSG_BACKUP_STATS
<b>SAP Sybase Error Number</b>	20950
<b>SQL State</b>	QUA27
<b>SQL Code</b>	1012027L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	number of blocks
<b>Parameter 2</b>	time of backup
<b>Parameter 3</b>	IQ Blocksize
<b>Parameter 4</b>	Backup BlockSize
<b>Parameter 5</b>	Blocking Factor
<b>Parameter 6</b>	BufferSize
<b>Probable Cause</b>	No additional information available.
<b>Warning 1012028</b>	<b>"Total number of IQ blocks to be backed up: %1"</b>
<b>Constant</b>	EMSG_TOTAL_BACKUP_BLOCK_COUNT

<b>Warning 1012028</b>	<b>"Total number of IQ blocks to be backed up: %1"</b>
SAP Sybase Error Number	20951
SQL State	QUA28
SQL Code	1012028L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>I</i> on page 2
Parameter 1	number of blocks
Probable Cause	No additional information available.
<b>Error 1012029</b>	<b>"Incremental backups disabled, perhaps due to forced recovery. To enable,\n do a full backup"</b>
Constant	EMSG_BACKUP_INCS_DISABLED
SAP Sybase Error Number	20952
SQL State	QUA29
SQL Code	-1012029L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>I4</i> on page 2
Probable Cause	No additional information available.
<b>Error 1012030</b>	<b>"for long binary/varchar Column '%2', database page size of (%3) must be greater than %4. %1"</b>
Constant	EMSG_CAT_PAGESIZETOOSMALL
SAP Sybase Error Number	20953
SQL State	QUA30
SQL Code	-1012030L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

## Errors and Warnings

<b>Error 1012030</b>	<b>"for long binary/varchar Column '%2', database page size of (%3) must be greater than %4. %1"</b>
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column number
<b>Parameter 3</b>	requested page size
<b>Parameter 4</b>	minimum allowed page size
<b>Probable Cause</b>	The database page size requested by the user for a long binary column is too small.
<b>Error 1012031</b>	<b>"A readonly dbspace does not match this backup. Found: AlterID %2 startBlock %3 numBlocks %4 fileID %5 %1"</b>
<b>Constant</b>	EMSG_RESTORE_BAD_RO_FILE
<b>SAP Sybase Error Number</b>	20954
<b>SQL State</b>	QUA31
<b>SQL Code</b>	-1012031L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	alterID found in the RO dbspace header
<b>Parameter 3</b>	startBlock found in the RO dbspace header
<b>Parameter 4</b>	number of blocks found in the RO dbspace header
<b>Parameter 5</b>	fileID found in the RO dbspace header
<b>Probable Cause</b>	There is a readonly dbspace that does not match the RO dbspaces that existed at the time of the backup.
<b>Error 1012032</b>	<b>"You may either do selective backup of readonly dbspaces or readonly dbfiles with backup type 'full' alone, or do an all-inclusive backup"</b>
<b>Constant</b>	EMSG_BACKUP_RO_WITH_FULL_ALONE

<b>Error 1012032</b>	"You may either do selective backup of readonly dbspaces or readonly dbfiles with backup type 'full' alone, or do an all-inclusive backup"
<b>SAP Sybase Error Number</b>	20955
<b>SQL State</b>	QUA32
<b>SQL Code</b>	-1012032L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1012033</b>	"IQ store dbfile %2 must be either readonly or belong to an RO dbspace. %1"
<b>Constant</b>	EMSG_BACKUP_RO_ILLEGAL
<b>SAP Sybase Error Number</b>	20956
<b>SQL State</b>	QUA33
<b>SQL Code</b>	-1012033L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	dbfile to backup
<b>Probable Cause</b>	Dbfile or the dbspace specified in RO selective backup found to be RW
<b>Error 1012034</b>	"IQ store dbspace or dbfile %2 is unavailable. Backup will not be done. %1"
<b>Constant</b>	EMSG_BACKUP_DBSPACE_OFFLINE
<b>SAP Sybase Error Number</b>	20957
<b>SQL State</b>	QUA34
<b>SQL Code</b>	-1012034L

## Errors and Warnings

<b>Error 1012034</b>	<b>"IQ store dbspace or dbfile %2 is unavailable. Backup will not be done. %1"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	dbspace to backup
<b>Probable Cause</b>	dbspace to backup must be online, both in catalog and dynamically
<b>Error 1012035</b>	<b>"You may either do selective restore of readonly dbspaces or readonly dbfiles from a 'full' backup archive, or restore from an all-inclusive backup."</b>
<b>Constant</b>	EMSG_RESTORE_RO_WITH_FULL_ALONE
<b>SAP Sybase Error Number</b>	20958
<b>SQL State</b>	QUA35
<b>SQL Code</b>	-1012035L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.
<b>Error 1012036</b>	<b>"IQ unable to find any file to restore. %1"</b>
<b>Constant</b>	EMSG_RESTORE_NO_FILES
<b>SAP Sybase Error Number</b>	20959
<b>SQL State</b>	QUA36
<b>SQL Code</b>	-1012036L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2

<b>Error 1012036</b>	<b>"IQ unable to find any file to restore. %1"</b>
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Error 1012037</b>	<b>"IQ store dbfile %2 exists. Restore will not be done. %1"</b>
<b>Constant</b>	EMSG_RESTORE_IQDB_FILE_EXISTS
<b>SAP Sybase Error Number</b>	20960
<b>SQL State</b>	QUA37
<b>SQL Code</b>	-1012037L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	dbfile to restore
<b>Probable Cause</b>	File must not exist when restoring from a full backup, unless restore is RO selective or restoring from virtual backup, or the file was created after the dependent backup when restoring from inc backup.

<b>Error 1012038</b>	<b>"IQ store dbfile %2 does not exist. Restore will not be done. %1"</b>
<b>Constant</b>	EMSG_RESTORE_IQDB_FILE_DOES_NOT_EXIST
<b>SAP Sybase Error Number</b>	20961
<b>SQL State</b>	QUA38
<b>SQL Code</b>	-1012038L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	dbfile to restore

## Errors and Warnings

<b>Error 1012038</b>	<b>"IQ store dbfile %2 does not exist. Restore will not be done. %1"</b>
<b>Probable Cause</b>	File must exist when restoring from inc backup, unless it was created after the dependant backup, or when restoring from virtual backup.
<b>Error 1012039</b>	<b>"The maximum number of backup devices allowed is %2. %1"</b>
<b>Constant</b>	EMSG_BACKUP_MAX_DEVICES_EXCEEDED
<b>SAP Sybase Error Number</b>	20962
<b>SQL State</b>	QUA39
<b>SQL Code</b>	-1012039L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	the maximum number of backup devices permitted.
<b>Probable Cause</b>	A database can be backed up to a maximum of the stated number of devices.
<b>Error 1012040</b>	<b>"IQ store dbspace %2 is online. Restore will not be done. %1"</b>
<b>Constant</b>	EMSG_RESTORE_DBSPACE_ONLINE
<b>SAP Sybase Error Number</b>	20963
<b>SQL State</b>	QUA40
<b>SQL Code</b>	-1012040L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	dbspace to restore
<b>Probable Cause</b>	dbspace to restore must be offline, both in catalog and dynamically

<b>Error 1012041</b>	"The backup no longer matches the version of the dbspace/dbfile in the database and, therefore, cannot be restored. %1"
<b>Constant</b>	EMSG_RESTORE_VERSIONCHANGED
<b>SAP Sybase Error Number</b>	20964
<b>SQL State</b>	QUA41
<b>SQL Code</b>	-1012041L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.

<b>Warning 1012042</b>	"(%1) Please mount archive media on "%2"."
<b>Constant</b>	EMSG_RESTORE_MOUNT_NONMASTERMEDIA
<b>SAP Sybase Error Number</b>	20965
<b>SQL State</b>	01A42
<b>SQL Code</b>	1012042L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I0</i> on page 2
<b>Parameter 1</b>	explanation of %1
<b>Parameter 2</b>	explanation of %2
<b>Probable Cause</b>	No additional information available.

<b>Warning 1012043</b>	"(%1) Please mount IQ MASTER archive media for database '%2' on '%3'."
<b>Constant</b>	EMSG_RESTORE_MOUNT_MASTERMEDIA
<b>SAP Sybase Error Number</b>	20966
<b>SQL State</b>	01A43

## Errors and Warnings

<b>Warning 1012043</b>	<b>"(%1) Please mount IQ MASTER archive media for database '%2' on '%3'."</b>
<b>SQL Code</b>	1012043L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	explanation of %1
<b>Parameter 2</b>	explanation of %2
<b>Parameter 3</b>	explanation of %3
<b>Probable Cause</b>	No additional information available.
<b>Warning 1012044</b>	<b>"(%1) Please mount Backup Server archive media for database '%2' on '%3'."</b>
<b>Constant</b>	EMSG_RESTORE_MOUNT_BACKUPSERVERMEDIA
<b>SAP Sybase Error Number</b>	20967
<b>SQL State</b>	01A44
<b>SQL Code</b>	1012044L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	explanation of %1
<b>Parameter 2</b>	explanation of %2
<b>Parameter 3</b>	explanation of %3
<b>Probable Cause</b>	No additional information available.
<b>Warning 1012045</b>	<b>"(%1) Please mount archive media on '%2'."</b>
<b>Constant</b>	EMSG_BACKUP_MOUNT_NONMASTERMEDIA
<b>SAP Sybase Error Number</b>	20968
<b>SQL State</b>	01A45

<b>Warning 1012045</b>	"(%1) Please mount archive media on "%2'."
<b>SQL Code</b>	1012045L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	explanation of %1
<b>Parameter 2</b>	explanation of %2
<b>Probable Cause</b>	No additional information available.

## Messages 1012046 through 1013018

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Warning 1012046</b>	<b>"(%1) Please mount archive media on "%2'. It will be the IQ MASTER archive for database "%3'."</b>
<b>Constant</b>	EMSG_BACKUP_MOUNT_MASTERMEDIA
<b>SAP Sybase Error Number</b>	20969
<b>SQL State</b>	01A46
<b>SQL Code</b>	1012046L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	explanation of %1
<b>Parameter 2</b>	explanation of %2
<b>Parameter 3</b>	explanation of %3
<b>Probable Cause</b>	No additional information available.
<b>Warning 1012047</b>	<b>"(%1) Please mount archive media on "%2'. It will be the Backup Server archive for database "%3'."</b>
<b>Constant</b>	EMSG_BACKUP_MOUNT_BACKUPSERVERMEDIA
<b>SAP Sybase Error Number</b>	20970

## Errors and Warnings

<b>Warning 1012047</b>	<b>"(%1) Please mount archive media on '%2'. It will be the Backup Server archive for database '%3'."</b>
<b>SQL State</b>	01A47
<b>SQL Code</b>	1012047L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	explanation of %1
<b>Parameter 2</b>	explanation of %2
<b>Parameter 3</b>	explanation of %3
<b>Probable Cause</b>	No additional information available.
<b>Warning 1012048</b>	<b>"(%1) Archive media mounted on '%2'."</b>
<b>Constant</b>	EMSG_BACKUP_ARCHIVEMEDIA_MOUNTED
<b>SAP Sybase Error Number</b>	20971
<b>SQL State</b>	01U48
<b>SQL Code</b>	1012048L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	explanation of %1
<b>Parameter 2</b>	explanation of %2
<b>Probable Cause</b>	No additional information available.
<b>Warning 1012049</b>	<b>"(%1) Done with archive media on '%2'."</b>
<b>Constant</b>	EMSG_BACKUP_ARCHIVEMEDIA_CLOSED
<b>SAP Sybase Error Number</b>	20972
<b>SQL State</b>	01U49
<b>SQL Code</b>	1012049L

<b>Warning 1012049</b>	"(%1) Done with archive media on '%2'."
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	10 on page 2
<b>Parameter 1</b>	explanation of %1
<b>Parameter 2</b>	explanation of %2
<b>Probable Cause</b>	No additional information available.

<b>Error 1012050</b>	<b>"Bad opcode detected during restore. Expected opcode is '%2', but '%3' was seen. %1"</b>
<b>Constant</b>	EMSG_HEADER_BADOPCODE
<b>SAP Sybase Error Number</b>	20974
<b>SQL State</b>	QUA50
<b>SQL Code</b>	-1012050L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation of %2
<b>Parameter 3</b>	explanation of %3
<b>Probable Cause</b>	This is an internal error. If this error occurs it should be reported to Sybase.

<b>Error 1012051</b>	<b>"An invalid database segment number (%2, %3) has been detected. %1"</b>
<b>Constant</b>	EMSG_HEADER_BAD_SEGMENTNUMBER
<b>SAP Sybase Error Number</b>	20975
<b>SQL State</b>	QUA51
<b>SQL Code</b>	-1012051L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1012051</b>	<b>"An invalid database segment number (%2, %3) has been detected. %1"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation of %2
<b>Parameter 3</b>	explanation of %3
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1012052</b>	<b>"Programming error: looking for hole '%2', but only have '%3'. %1"</b>
<b>Constant</b>	EMSG_HEADER_HOLE_ERROR
<b>SAP Sybase Error Number</b>	20976
<b>SQL State</b>	QUA52
<b>SQL Code</b>	-1012052L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation of %2
<b>Parameter 3</b>	explanation of %3
<b>Probable Cause</b>	This is an internal error. If this error occurs it should be reported to Sybase.
<b>Error 1012053</b>	<b>"Fatal internal error: looking for segment containing hole {%,%,%}, but none was found. %1"</b>
<b>Constant</b>	EMSG_HEADER_HOLE_LOOKUP_ERROR
<b>SAP Sybase Error Number</b>	20977
<b>SQL State</b>	QUA53
<b>SQL Code</b>	-1012053L

<b>Error 1012053</b>	<b>"Fatal internal error: looking for segment containing hole {%,%,%}, but none was found. %1"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation of %2
<b>Parameter 3</b>	explanation of %3
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1012054</b>	<b>"Fatal internal error: looking for segment containing block '%2', but none was found. %1"</b>
<b>Constant</b>	EMSG_BACKUP_SEGMENT_NUMBER_ERROR
<b>SAP Sybase Error Number</b>	20978
<b>SQL State</b>	QUA54
<b>SQL Code</b>	-1012054L
<b>ODBC 2 State</b>	ERRORi
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation of %2
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1012055</b>	<b>"RESTORE VERIFY has found errors with the archive. %1"</b>
<b>Constant</b>	EMSG_RESTORE_VERIFY_FAILED_WITH_ERRORS
<b>SAP Sybase Error Number</b>	21207
<b>SQL State</b>	QUA55
<b>SQL Code</b>	-1012055L

## Errors and Warnings

<b>Error 1012055</b>	"RESTORE VERIFY has found errors with the archive. %1"
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> 4 on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	The verification of the provided archive has failed. Please check the server log for details of errors which were thrown during the verification process.
<b>Warning 1012056</b>	"Total number of IQ blocks verified: %1/%2 ( %3% )"
<b>Constant</b>	EMSG_RESTORE_VERIFY_PROGRESS
<b>SAP Sybase Error Number</b>	21208
<b>SQL State</b>	QUA56
<b>SQL Code</b>	1012056L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	Parameter 1 description
<b>Parameter 2</b>	Parameter 2 description
<b>Parameter 3</b>	Parameter 3 description
<b>Probable Cause</b>	This is an informational message displayed in context with other messages.
<b>Error 1012057</b>	"Command specified for virtual backup failed. %1"
<b>Constant</b>	EMSG_BACKUP_VIRTUAL_CMD_FAILED
<b>SAP Sybase Error Number</b>	21209
<b>SQL State</b>	QUA57
<b>SQL Code</b>	-1012057L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1012057</b>	"Command specified for virtual backup failed. %1"
<b>Severity Code</b>	<i>I</i> 4 on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	No additional information available.
<b>Error 1012058</b>	"IQ cache dbspace %2 is readonly. Backup will not be done. %1"
<b>Constant</b>	EMSG_BACKUP_DBSPACE_READONLY
<b>SAP Sybase Error Number</b>	22167
<b>SQL State</b>	QUA42
<b>SQL Code</b>	-1012058L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> 4 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	dbspace to backup
<b>Probable Cause</b>	cache dbspace to backup must be readwrite.
<b>Warning 1013000</b>	"*** BlockSize: %2, Block size: Record size: %1"
<b>Constant</b>	EMSG_ISQL_RECORDBLOCKING
<b>SAP Sybase Error Number</b>	20570
<b>SQL State</b>	00A00
<b>SQL Code</b>	1013000L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	record size
<b>Parameter 2</b>	block size
<b>Probable Cause</b>	No additional information available.

## Errors and Warnings

<b>Warning 1013001</b>	"*** Record size: variable, Block size: %1"
<b>Constant</b>	EMSG_ISQL_RECORDBLOCKSIZE
<b>SAP Sybase Error Number</b>	20571
<b>SQL State</b>	00A01
<b>SQL Code</b>	1013001L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	block size
<b>Probable Cause</b>	No additional information available.
<b>Warning 1013015</b>	"Row Delimiter: %1"
<b>Constant</b>	EMSG_ISQL_PREVIEWROWD
<b>SAP Sybase Error Number</b>	20585
<b>SQL State</b>	00A15
<b>SQL Code</b>	1013015L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	row delimiter
<b>Probable Cause</b>	This is the ROW DELIMITER used for the LOAD.
<b>Error 1013015</b>	<b>"Multi-column indexes that are non unique or of more than 5300 bytes in total width are not supported. %1"</b>
<b>Constant</b>	EMSG_SQL_MULTICOLWIDTH
<b>SAP Sybase Error Number</b>	20584
<b>SQL State</b>	QCA15
<b>SQL Code</b>	-1013015L

<b>Error 1013015</b>	"Multi-column indexes that are non unique or of more than 5300 bytes in total width are not supported. %1"
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Multicolumn indexes that are non unique or of more than 1024 bytes in total width are not supported. The total width is obtained by summing the individual widths of the various columns involved in the multicolumn index.

<b>Error 1013016</b>	"FILLER"
<b>Constant</b>	EMSG_ISQL_FILLERNAME
<b>SAP Sybase Error Number</b>	20586
<b>SQL State</b>	QCA16
<b>SQL Code</b>	-1013016L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	No additional information available.

<b>Error 1013017</b>	"An internal error occurred while calling a method on a db_sql_*_identifier. Object does not have an Index Handle. %1"
<b>Constant</b>	EMSG_SQL_NOINDEX
<b>SAP Sybase Error Number</b>	20587
<b>SQL State</b>	QCA17
<b>SQL Code</b>	-1013017L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2

<b>Error 1013017</b>	<b>"An internal error occurred while calling a method on a db_sql_*_identifier. Object does not have an IIndex Handle. %1"</b>
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	This error should not occur during normal operation. It is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1013018</b>	<b>"An internal error occurred while calling a method on db_sql_*_identifier. Object does not have an IColumn Handle. %1"</b>
<b>Constant</b>	EMSG_SQL_NOCOLUMN
<b>SAP Sybase Error Number</b>	20588
<b>SQL State</b>	QCA18
<b>SQL Code</b>	-1013018L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<a href="#">23 on page 2</a>
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	This error should not occur during normal operation. It is an internal error. If this error occurs, it should be reported to Sybase.

## **1013019 - 1013136**

---

### **Messages 1013019 through 1013040**

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1013019</b>	<b>"CHECK constraint has unsupported component %2. %1"</b>
<b>Constant</b>	EMSG_SQL_IQ_UNSUPPORTED_CONSTRAINT
<b>SAP Sybase Error Number</b>	20589
<b>SQL State</b>	QCA19
<b>SQL Code</b>	-1013019L

<b>Error 1013019</b>	<b>"CHECK constraint has unsupported component %2. %1"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	details of the constraint
<b>Probable Cause</b>	the CHECK constraints contains either a subquery, a aggregate function, a user defined function, or other components that are not supported by IQ. CHECK constraints are not supported by Sybase IQ.

<b>Error 1013020</b>	<b>"User defined default values are not supported. %1"</b>
<b>Constant</b>	EMSG_SQL_NODEFAULT
<b>SAP Sybase Error Number</b>	20590
<b>SQL State</b>	QCA20
<b>SQL Code</b>	-1013020L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	User defined default values are not supported by Sybase IQ.

<b>Error 1013021</b>	<b>"Multi-column indexes of the specified type are not supported. %1"</b>
<b>Constant</b>	EMSG_SQL_NOCLUSTEREDINDEX
<b>SAP Sybase Error Number</b>	20591
<b>SQL State</b>	QCA21
<b>SQL Code</b>	-1013021L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2

## Errors and Warnings

<b>Error 1013021</b>	<b>"Multi-column indexes of the specified type are not supported. %1"</b>
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Multi-column indexes of the user specified type are not supported by Sybase IQ.
<b>Error 1013022</b>	<b>"Cannot create a duplicate "%2' index "%3'. %1"</b>
<b>Constant</b>	EMSG_SQL_INDEXFOUND
<b>SAP Sybase Error Number</b>	20592
<b>SQL State</b>	QCA22
<b>SQL Code</b>	-1013022L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	indextype
<b>Parameter 3</b>	indexname
<b>Probable Cause</b>	Cannot create duplicate indexes of the same type on a set of columns.
<b>Error 1013023</b>	<b>"Cannot create a unique "%2' index. %1"</b>
<b>Constant</b>	EMSG_SQL_INDEXNOUNIQUE
<b>SAP Sybase Error Number</b>	20593
<b>SQL State</b>	QCA23
<b>SQL Code</b>	-1013023L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column name

<b>Error 1013023</b>	<b>"Cannot create a unique "%2' index. %1"</b>
<b>Probable Cause</b>	Fast Projection, Low Disk, and High Non Group index types cannot be created as unique.
<b>Error 1013024</b>	<b>"ALTER TABLE MODIFY &lt;column&gt; &lt;datatype&gt; is not supported. %1"</b>
<b>Constant</b>	EMSG_SQL_NOSUPPMODDTYPE
<b>SAP Sybase Error Number</b>	20594
<b>SQL State</b>	QCA24
<b>SQL Code</b>	-1013024L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Cannot modify the datatype of a column.
<b>Error 1013025</b>	<b>"ALTER TABLE MODIFY &lt;default-value&gt; is not supported. %1"</b>
<b>Constant</b>	EMSG_SQL_NOSUPPMODDEF
<b>SAP Sybase Error Number</b>	20595
<b>SQL State</b>	QCA25
<b>SQL Code</b>	-1013025L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Cannot modify the default value of a column as defaults are not supported.

## Errors and Warnings

<b>Error 1013027</b>	<b>"Number of bytes (%2) for a column from an input file has exceeded the maximum allowed (%3). %1"</b>
<b>Constant</b>	EMSG_DB_RECSCANNER_E_EXCEEDMAX
<b>SAP Sybase Error Number</b>	20597
<b>SQL State</b>	QCA27
<b>SQL Code</b>	-1013027L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	# of bytes.
<b>Parameter 3</b>	maximum number of bytes allowed.
<b>Probable Cause</b>	The number of bytes you are trying to load into a column from an input file has exceeded the maximum number of bytes allowed.
<b>Error 1013028</b>	<b>"An invalid size (too large) was specified for a LOAD option. %1"</b>
<b>Constant</b>	EMSG_SQL_INVALIDSIZE
<b>SAP Sybase Error Number</b>	20598
<b>SQL State</b>	QCA28
<b>SQL Code</b>	-1013028L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I3</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	A size too large was specified for a LOAD option. Check the options specified for the LOAD statement.
<b>Error 1013029</b>	<b>"The INSERT...LOCATION statement must have a SELECT statement. %1"</b>
<b>Constant</b>	EMSG_SQL_INS_LOC_SELECT

<b>Error 1013029</b>	"The INSERT...LOCATION statement must have a SELECT statement. %1"
<b>SAP Sybase Error Number</b>	20599
<b>SQL State</b>	QCA29
<b>SQL Code</b>	-1013029L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	The INSERT...LOCATION statement must use a SELECT statement to provide the data for insertion. No other SQL statement type is supported here.
<b>Error 1013031</b>	"An error occurred while calling a method on db_sql_*_identifier. Object does not have an ITable handle. %1"
<b>Constant</b>	EMSG_SQL_NOTABLE
<b>SAP Sybase Error Number</b>	20601
<b>SQL State</b>	QCA31
<b>SQL Code</b>	-1013031L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	This error should not occur during normal operation. It is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1013032</b>	"No database is currently in use. %1"
<b>Constant</b>	EMSG_SQL_NODATABASE
<b>SAP Sybase Error Number</b>	20602
<b>SQL State</b>	QCA32

## Errors and Warnings

<b>Error 1013032</b>	<b>"No database is currently in use. %1"</b>
<b>SQL Code</b>	-1013032L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1013033</b>	<b>"An error occurred while calling a method on db_sql_*_identifier. Object does not have an IJoinIndex handle. %1"</b>
<b>Constant</b>	EMSG_SQL_NOJOININDEX
<b>SAP Sybase Error Number</b>	20603
<b>SQL State</b>	QCA33
<b>SQL Code</b>	-1013033L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	This is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1013034</b>	<b>"Cannot create an index with no columns. %1"</b>
<b>Constant</b>	EMSG_SQL_INDEXNOFIELDS
<b>SAP Sybase Error Number</b>	20604
<b>SQL State</b>	QCA34
<b>SQL Code</b>	-1013034L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1013034</b>	<b>"Cannot create an index with no columns. %1"</b>
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	You cannot create an index with no columns.
<b>Error 1013035</b>	<b>"The number of insert VALUES does not match the column list. %1"</b>
<b>Constant</b>	EMSG_SQL_INSERTNOVALUE
<b>SAP Sybase Error Number</b>	20605
<b>SQL State</b>	QCA35
<b>SQL Code</b>	-1013035L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	The number of columns in the INSERT does not match the number of of VALUES provided.
<b>Error 1013036</b>	<b>"The keyword 'FILLER' is not valid in this context. %1"</b>
<b>Constant</b>	EMSG_SQL_NOFILLER
<b>SAP Sybase Error Number</b>	20606
<b>SQL State</b>	QCA36
<b>SQL Code</b>	-1013036L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	You cannot use the 'FILLER' keyword here. No column can be of type 'FILLER' for a VALUES insert.

## Errors and Warnings

<b>Error 1013037</b>	"The datatype of column '%2' is not valid. %1"
<b>Constant</b>	EMSG_SQL_DATATYPE NOT VALID FOR OP
<b>SAP Sybase Error Number</b>	20607
<b>SQL State</b>	QCA37
<b>SQL Code</b>	-1013037L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column
<b>Probable Cause</b>	The named column has an invalid datatype. If subsequent examination of the column definition reveals a datatype that is valid, then this error should be reported to Sybase.
<b>Error 1013038</b>	"The number of columns given does not match. %1"
<b>Constant</b>	EMSG_SQL_INSERTNUMBERFIELDS
<b>SAP Sybase Error Number</b>	20608
<b>SQL State</b>	QCA38
<b>SQL Code</b>	-1013038L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	The number of columns to be inserted does not match the number of columns in the insert. If this error persists, it should be reported to Sybase.
<b>Error 1013039</b>	"An internal error occurred while constructing a db_sql_*_identifier. The IColumn handle does not belong to the ITable. %1"
<b>Constant</b>	EMSG_SQL_COLUMNMISMATCH

<b>Error 1013039</b>	"An internal error occurred while constructing a db_sql_*_identifier. The IColumn handle does not belong to the ITable. %1"
<b>SAP Sybase Error Number</b>	20609
<b>SQL State</b>	QCA39
<b>SQL Code</b>	-1013039L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	This error should not occur during normal operation. It is an internal error. If this error occurs, it should be reported to Sybase.
<b>Error 1013040</b>	"Column '%2' in the INSERT list has no matching column in the SELECT list. %1"
<b>Constant</b>	EMSG_SQL_INSERTNOMATCHILIST
<b>SAP Sybase Error Number</b>	20610
<b>SQL State</b>	QCA40
<b>SQL Code</b>	-1013040L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column
<b>Probable Cause</b>	The named column in the INSERT list does not have a matching column in the SELECT list.

**Messages 1013041 through 1013062**

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1013041</b>	<b>"Column '%2' in the SELECT list has no matching column in the INSERT list. %1"</b>
<b>Constant</b>	EMSG_SQL_INSERTNOMATCHCLIST
<b>SAP Sybase Error Number</b>	20611
<b>SQL State</b>	QCA41
<b>SQL Code</b>	-1013041L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column
<b>Probable Cause</b>	The named column in the SELECT list does not have a matching column in the INSERT list.
<b>Error 1013042</b>	<b>"An internal error occurred while constructing a db_sql_*_identifier. The lIndex handle does not belong to the ITable. %1"</b>
<b>Constant</b>	EMSG_SQL_INDEXMISMATCH
<b>SAP Sybase Error Number</b>	20612
<b>SQL State</b>	QCA42
<b>SQL Code</b>	-1013042L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	This error should not occur during normal operation. It is an internal error. If this error occurs it should be reported to Sybase.

<b>Error 1013043</b>	<b>"Unable to convert column "%2' to the requested datatype (%3) from datatype (%4). %1"</b>
<b>Constant</b>	EMSG_SQL_INVALIDCONVERSION
<b>SAP Sybase Error Number</b>	20613
<b>SQL State</b>	QCA43
<b>SQL Code</b>	-1013043L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column
<b>Parameter 3</b>	requested datatype
<b>Parameter 4</b>	current datatype
<b>Probable Cause</b>	This column cannot be converted to the requested datatype.
<b>Error 1013044</b>	<b>"An internal error occurred. An invalid table type was encountered. %1"</b>
<b>Constant</b>	EMSG_SQL_INVALID_TBL_TYPE
<b>SAP Sybase Error Number</b>	20614
<b>SQL State</b>	QCA44
<b>SQL Code</b>	-1013044L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	This is an internal programming error. The table type was not correctly set to BASE, VIEW, JVT, TMP, LOCAL TMP for its context. If this error occurs it should be reported to Sybase.

## Errors and Warnings

<b>Error 1013045</b>	"An invalid file name ('%2') was specified for a LOAD TABLE. The file name has zero length. %1"
<b>Constant</b>	EMSG_SQL_INVALIDFILENAME
<b>SAP Sybase Error Number</b>	20615
<b>SQL State</b>	QCA45
<b>SQL Code</b>	-1013045L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	file name
<b>Probable Cause</b>	A file name of zero length was specified for LOAD TABLE.
<b>Error 1013046</b>	"An internal error occurred. An invalid index type was encountered. %1"
<b>Constant</b>	EMSG_SQL_INVALIDINDEXTYPE
<b>SAP Sybase Error Number</b>	20616
<b>SQL State</b>	QCA46
<b>SQL Code</b>	-1013046L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	This error should not occur during normal operation. It is an internal error and should be reported to Sybase.
<b>Error 1013047</b>	"Cannot alter index '%2'. Only indexes in base tables or global temporary tables can be altered. %1"
<b>Constant</b>	EMSG_SQL_CANNOT_ALTER_INDEX
<b>SAP Sybase Error Number</b>	20617

<b>Error 1013047</b>	<b>"Cannot alter index '%2'. Only indexes in base tables or global temporary tables can be altered. %1"</b>
<b>SQL State</b>	QCA47
<b>SQL Code</b>	-1013047L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	Indexname.
<b>Probable Cause</b>	Only indexes in base tables and global temporary tables listed in SYS.SYSINDEX can be altered.
<b>Warning 1013048</b>	<b>"Warning: Partial input record (%1 bytes) skipped at EOF (O/S %2). %3 rows read."</b>
<b>Constant</b>	EMSG_SQL_INSERTPARTIALRECORD
<b>SAP Sybase Error Number</b>	20618
<b>SQL State</b>	01A48
<b>SQL Code</b>	1013048L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I0</i> on page 2
<b>Parameter 1</b>	number of bytes at end of file that were skipped
<b>Parameter 2</b>	operating system error
<b>Parameter 3</b>	number of rows read from the input file
<b>Probable Cause</b>	An incomplete input record was found at the end of the flat file. If the operating system error returned is not zero, you may need to take action as dictated by the error and try the LOAD again.
<b>Warning 1013049</b>	<b>"***** Possible Tape/File Error *****\n\n Bytes Read: %1, O/S errno: %2\n %3 rows read. Input suspended."</b>
<b>Constant</b>	EMSG_SQL_INSERTTAPEERROR

## Errors and Warnings

<b>Warning 1013049</b>	"***** Possible Tape/File Error *****\n\n Bytes Read: %1, O/S errno: %2\n %3 rows read. Input suspended."
<b>SAP Sybase Error Number</b>	20619
<b>SQL State</b>	01A49
<b>SQL Code</b>	1013049L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	number of bytes read
<b>Parameter 2</b>	operating system error number
<b>Parameter 3</b>	number of rows read
<b>Probable Cause</b>	Take action as dictated by the operating system error and retry the operation.
<b>Error 1013050</b>	<b>"The Temp_Extract_Name1 option is set. The current operation will be rolled back. %1"</b>
<b>Constant</b>	EMSG_SQL_OP_PROHIBITED
<b>SAP Sybase Error Number</b>	20620
<b>SQL State</b>	QCA50
<b>SQL Code</b>	-1013050L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Probable Cause</b>	Certain operations will not be allowed whenever the Temp_Extract_Name1 option is set. They are: INSERT...VALUES, LOAD, DELETE, and INSERT...LOCATION if the table being inserted, SYNCHRONIZE join index. (Which also may be executed as part of CREATE JOIN INDEX.) loaded or deleted from is the top table in a join. INSERT...SELECT. For example, 'insert t1 select * from t2'.

<b>Error 1013052</b>	<b>"The BLOCK FACTOR for LOAD cannot be zero. %1"</b>
<b>Constant</b>	EMSG_SQL_BLOCKFACTOR_IS_ZERO
<b>SAP Sybase Error Number</b>	20622
<b>SQL State</b>	QCA52
<b>SQL Code</b>	-1013052L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	The BLOCK FACTOR for LOAD cannot be zero.
<b>Error 1013054</b>	<b>"Delimiter '%2' must be 1 to %3 characters in length. %1"</b>
<b>Constant</b>	EMSG_SQL_INVALIDDELIMITERSIZE
<b>SAP Sybase Error Number</b>	20624
<b>SQL State</b>	QCA54
<b>SQL Code</b>	-1013054L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	delimiter
<b>Parameter 3</b>	maximum allowable length of column delimiter or row terminator
<b>Probable Cause</b>	The row or column delimiter in a LOAD statement must be 1-4 characters.
<b>Error 1013055</b>	<b>"ON_ERROR = 'CONTINUE' is valid only for a full-width INSERT. %1"</b>
<b>Constant</b>	EMSG_SQL_INVALIDCONTINUE
<b>SAP Sybase Error Number</b>	20625

## Errors and Warnings

<b>Error 1013055</b>	<b>"ON_ERROR = 'CONTINUE' is valid only for a full-width INSERT. %1"</b>
<b>SQL State</b>	QCA55
<b>SQL Code</b>	-1013055L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	ON_ERROR = 'CONTINUE' is valid only for a full width insert.
<b>Error 1013056</b>	<b>"FILLER width must be greater than zero. %1"</b>
<b>Constant</b>	EMSG_SQL_INVALIDFILLERWIDTH
<b>SAP Sybase Error Number</b>	20626
<b>SQL State</b>	QCA56
<b>SQL Code</b>	-1013056L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	FILLER width must be greater than zero.
<b>Error 1013057</b>	<b>"ASCII input column width must be greater than zero. %1"</b>
<b>Constant</b>	EMSG_SQL_INVALIDASCIIWIDTH
<b>SAP Sybase Error Number</b>	20627
<b>SQL State</b>	QCA57
<b>SQL Code</b>	-1013057L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2

<b>Error 1013057</b>	<b>"ASCII input column width must be greater than zero. %1"</b>
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	ASCII input column width must be greater than zero.
<b>Error 1013058</b>	<b>"The row delimiter must be distinct from all column delimiters. %1"</b>
<b>Constant</b>	EMSG_SQL_IDENTICALDELIMITERANDROWTERMINATOR
<b>SAP Sybase Error Number</b>	20628
<b>SQL State</b>	QCA58
<b>SQL Code</b>	-1013058L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	The row delimiter cannot be the same as any column delimiter.
<b>Error 1013059</b>	<b>"The BLOCK SIZE option is not valid for a fixed-width input insert. %1"</b>
<b>Constant</b>	EMSG_SQL_INVALIDBLOCKSIZEOPTION
<b>SAP Sybase Error Number</b>	20629
<b>SQL State</b>	QCA59
<b>SQL Code</b>	-1013059L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	You cannot specify BLOCK SIZE for a fixed-width input insert.

## Errors and Warnings

<b>Error 1013060</b>	<b>"The BLOCK FACTOR option is not valid for a variable width input insert. %1"</b>
<b>Constant</b>	EMSG_SQL_INVALIDBLOCKFACTOREOPTION
<b>SAP Sybase Error Number</b>	20630
<b>SQL State</b>	QCA60
<b>SQL Code</b>	-1013060L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	You cannot specify BLOCK FACTOR for a variable width input insert.
<b>Error 1013061</b>	<b>"Missing row delimiter detected during a row delimited insert. %1"</b>
<b>Constant</b>	EMSG_SQL_MISSINGROWTERMINATOR
<b>SAP Sybase Error Number</b>	20631
<b>SQL State</b>	QCA61
<b>SQL Code</b>	-1013061L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	The input data is missing a row delimiter.
<b>Error 1013062</b>	<b>"Expected '%2' delimited column type on input, but encountered a row delimiter instead. Probable cause is a mismatch between the specified column delimiter and the column delimiter used in the input file. %1"</b>
<b>Constant</b>	EMSG_SQL_EXPECTEDFIELDTYPENOTSEEN

<b>Error 1013062</b>	<b>"Expected '%2' delimited column type on input, but encountered a row delimiter instead. Probable cause is a mismatch between the specified column delimiter and the column delimiter used in the input file. %1"</b>
<b>SAP Sybase Error Number</b>	20632
<b>SQL State</b>	QCA62
<b>SQL Code</b>	-1013062L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	expected datatype of column
<b>Probable Cause</b>	A row delimiter, rather than a column, was encountered during a LOAD. Probable cause is a mismatch between the specified column delimiter and the column delimiter used in the input file.

## **Messages 1013063 through 1013088**

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1013063</b>	<b>"Expected raw-data column type '%2' on input, but no input data exists. %1"</b>
<b>Constant</b>	EMSG_SQL_EXPECTEDRAWFIELDTYPENOTSEEN
<b>SAP Sybase Error Number</b>	20633
<b>SQL State</b>	QCA63
<b>SQL Code</b>	-1013063L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column datatype

## Errors and Warnings

<b>Error 1013063</b>	<b>"Expected raw-data column type '%2' on input, but no input data exists. %1"</b>
<b>Probable Cause</b>	No data was found during a scan of an input file during insert.
<b>Error 1013064</b>	<b>"Row delimiter not seen during scan of input file. At least one of the input rows is missing a terminator. %1"</b>
<b>Constant</b>	EMSG_SQL_ROWTERMINATORNOTSEEN
<b>SAP Sybase Error Number</b>	20634
<b>SQL State</b>	QCA64
<b>SQL Code</b>	-1013064L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	A row delimiter has been omitted from an input file.
<b>Error 1013065</b>	<b>"Row delimiter '%2' and column delimiter '%3' cannot be substrings of each other. %1"</b>
<b>Constant</b>	EMSG_SQL_CANTBESUBSTRING
<b>SAP Sybase Error Number</b>	20635
<b>SQL State</b>	QCA65
<b>SQL Code</b>	-1013065L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	the row delimiter
<b>Parameter 3</b>	the column delimiter
<b>Probable Cause</b>	Row and column delimiters cannot be substrings of each other.

<b>Error 1013066</b>	"The %2 load option can be specified only once. %1"
<b>Constant</b>	EMSG_SQL_MULTIPLE_LOAD_OPTION
<b>SAP Sybase Error Number</b>	20636
<b>SQL State</b>	QCA66
<b>SQL Code</b>	-1013066L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	name of the load option
<b>Probable Cause</b>	The named load option can be specified only once per LOAD statement.
<b>Error 1013067</b>	"Option CONVERSION ERROR must be OFF when IGNORE CONSTRAINT DATA VALUE or ALL is specified. %1"
<b>Constant</b>	EMSG_SQL_DATAVALUE_CVTERROR
<b>SAP Sybase Error Number</b>	20637
<b>SQL State</b>	QCA67
<b>SQL Code</b>	-1013067L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	When IGNORE CONSTRAINT DATA VALUE or ALL is given on a load statement, the database option CONVERSION ERROR must be off.
<b>Error 1013068</b>	"Constraint '%2' violated: Invalid value for column '%3' in table '%4'. %1"
<b>Constant</b>	EMSG_SQL_COLUMN_CHECK_CONSTRAINT_VIOLATED

## Errors and Warnings

<b>Error 1013068</b>	<b>"Constraint '%2' violated: Invalid value for column '%3' in table '%4'. %1"</b>
<b>SAP Sybase Error Number</b>	20638
<b>SQL State</b>	QCA68
<b>SQL Code</b>	-1013068L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	constraint name
<b>Parameter 3</b>	column name for which the violation occurred
<b>Parameter 4</b>	table name
<b>Probable Cause</b>	The Data being inserted or updated is invalid due to a column check constraint violation.
<b>Error 1013070</b>	<b>"Cannot specify check constraints off and ignore all, ignore check, log all or log check during load. %1"</b>
<b>Constant</b>	EMSG_SQL_IQ_LOAD_CONFLICT
<b>SAP Sybase Error Number</b>	20640
<b>SQL State</b>	QCA70
<b>SQL Code</b>	-1013070L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	when check constraints off is specified during load ignore all, ignore check, log all, log check are not available.
<b>Error 1013071</b>	<b>"Constraint '%2' violated: Invalid value in table '%3'. %1"</b>
<b>Constant</b>	EMSG_SQL_TABLE_CHECK_CONSTRAINT_VIOLATED

<b>Error 1013071</b>	<b>"Constraint '%2' violated: Invalid value in table '%3'. %1"</b>
<b>SAP Sybase Error Number</b>	20641
<b>SQL State</b>	QCA71
<b>SQL Code</b>	-1013071L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	constraint name
<b>Parameter 3</b>	table name on which the table check violation occurred
<b>Probable Cause</b>	The Data being inserted or updated is invalid due to a table check constraint violation.
<b>Error 1013077</b>	<b>"ROW DELIMITED BY is valid only when all columns are delimited or ASCII fixed-width. %1"</b>
<b>Constant</b>	EMSG_SQL_INVALIDUSEOFROWTERMINATOR
<b>SAP Sybase Error Number</b>	20647
<b>SQL State</b>	QCA77
<b>SQL Code</b>	-1013077L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	ROW DELIMITED BY is valid only when all columns are delimited or ASCII fixed-width. You cannot use a row delimiter with PREFIX or BINARY columns.
<b>Error 1013078</b>	<b>"Insert Pass 1 CPU utilization"</b>
<b>Constant</b>	EMSG_FFININSERT_1
<b>SAP Sybase Error Number</b>	20648

## Errors and Warnings

<b>Error 1013078</b>	"Insert Pass 1 CPU utilization"
<b>SQL State</b>	QCA78
<b>SQL Code</b>	-1013078L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	This is displayed as part of an informational message during insert.
<b>Error 1013079</b>	"Insert Pass 1 user (%)"
<b>Constant</b>	EMSG_FFINSTRT_1U
<b>SAP Sybase Error Number</b>	20649
<b>SQL State</b>	QCA79
<b>SQL Code</b>	-1013079L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	This is displayed as part of an informational message during insert.
<b>Error 1013080</b>	"Insert Pass 1 system (%)"
<b>Constant</b>	EMSG_FFINSTRT_1S
<b>SAP Sybase Error Number</b>	20650
<b>SQL State</b>	QCA80
<b>SQL Code</b>	-1013080L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	This is displayed as part of an informational message during insert.

<b>Error 1013081</b>	"Insert Pass 2 CPU utilization"
<b>Constant</b>	EMSG_FFINST_2
<b>SAP Sybase Error Number</b>	20651
<b>SQL State</b>	QCA81
<b>SQL Code</b>	-1013081L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	This is displayed as part of an informational message during insert.
<b>Error 1013082</b>	"Insert Pass 2 user (%)"
<b>Constant</b>	EMSG_FFINST_2U
<b>SAP Sybase Error Number</b>	20652
<b>SQL State</b>	QCA82
<b>SQL Code</b>	-1013082L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	This is displayed as part of an informational message during insert.
<b>Error 1013083</b>	"Insert Pass 2 system (%)"
<b>Constant</b>	EMSG_FFINST_2S
<b>SAP Sybase Error Number</b>	20653
<b>SQL State</b>	QCA83
<b>SQL Code</b>	-1013083L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	This is displayed as part of an informational message during insert.

## Errors and Warnings

<b>Error 1013084</b>	"Insert Commit CPU utilization"
<b>Constant</b>	EMSG_FFINSTERT_COMMIT
<b>SAP Sybase Error Number</b>	20654
<b>SQL State</b>	QCA84
<b>SQL Code</b>	-1013084L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	This is displayed as part of an informational message during insert.
<b>Error 1013085</b>	"Insert Commit user (%)"
<b>Constant</b>	EMSG_FFINSTERT_COMMITU
<b>SAP Sybase Error Number</b>	20655
<b>SQL State</b>	QCA85
<b>SQL Code</b>	-1013085L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	This is displayed as part of an informational message during insert.
<b>Error 1013086</b>	"Insert Commit system (%)"
<b>Constant</b>	EMSG_FFINSTERT_COMMITS
<b>SAP Sybase Error Number</b>	20656
<b>SQL State</b>	QCA86
<b>SQL Code</b>	-1013086L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	This is displayed as part of an informational message during insert.

<b>Error 1013087</b>	"Total Insert CPU utilization"
<b>Constant</b>	EMSG_FFINSTANT_TOTAL
<b>SAP Sybase Error Number</b>	20657
<b>SQL State</b>	QCA87
<b>SQL Code</b>	-1013087L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	This is displayed as part of an informational message during insert.
<b>Error 1013088</b>	"Insert Total user (%)"
<b>Constant</b>	EMSG_FFINSTANT_TOTALU
<b>SAP Sybase Error Number</b>	20658
<b>SQL State</b>	QCA88
<b>SQL Code</b>	-1013088L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	This is displayed as part of an informational message during insert.

## Messages 1013089 through 1013111

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1013089</b>	"Insert Total system (%)"
<b>Constant</b>	EMSG_FFINSTANT_TOTALS
<b>SAP Sybase Error Number</b>	20659
<b>SQL State</b>	QCA89
<b>SQL Code</b>	-1013089L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1013089</b>	"Insert Total system (%)"
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	This is displayed as part of an informational message during insert.
<b>Error 1013090</b>	<b>"Single or double quote mark cannot be the first character of column delimiter or row terminator with QUOTES option ON. %1"</b>
<b>Constant</b>	EMSG_INVALID_COLUMN_DELIM
<b>SAP Sybase Error Number</b>	20979
<b>SQL State</b>	QCA90
<b>SQL Code</b>	-1013090L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Cannot use single or double quote mark for column/row delimiter with QUOTES option ON.
<b>Error 1013091</b>	<b>"Column pairs %2=%3 could not be matched. %1"</b>
<b>Constant</b>	EMSG_SQL_COLUMNPAIRSNOTFOUND
<b>SAP Sybase Error Number</b>	20983
<b>SQL State</b>	QCA91
<b>SQL Code</b>	-1013091L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	column name
<b>Parameter 3</b>	column name

<b>Error 1013091</b>	<b>"Column pairs %2=%3 could not be matched. %1"</b>
<b>Probable Cause</b>	The columns specified in CREATE JOIN could not be matched in the tables specified.
<b>Error 1013092</b>	<b>"The MONITOR for this database, connection and buffer cache already exists. %1"</b>
<b>Constant</b>	EMSG_SQL_MONITOREXISTS
<b>SAP Sybase Error Number</b>	20984
<b>SQL State</b>	QCA92
<b>SQL Code</b>	-1013092L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I</i> 4 on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	A monitor has already been started for this database, connection and buffer cache.
<b>Warning 1013093</b>	<b>"Insert started: %1\n"</b>
<b>Constant</b>	EMSG_SQL_INSERTSTARTED
<b>SAP Sybase Error Number</b>	20985
<b>SQL State</b>	00A93
<b>SQL Code</b>	1013093L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>I</i> on page 2
<b>Parameter 1</b>	The table being inserted to.
<b>Probable Cause</b>	This is an informational message displayed during insert.
<b>Error 1013096</b>	<b>"Index %2 could not be created. The datatype does not support an index of %3. %1"</b>
<b>Constant</b>	EMSG_SQL_INDEXTYPEUNSUPPORTED

## Errors and Warnings

<b>Error 1013096</b>	<b>"Index %2 could not be created. The datatype does not support an index of %3. %1"</b>
<b>SAP Sybase Error Number</b>	20988
<b>SQL State</b>	QCA96
<b>SQL Code</b>	-1013096L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	indexname
<b>Parameter 3</b>	indextype
<b>Probable Cause</b>	You cannot create an index of the type specified for the column's datatype.
<b>Error 1013098</b>	<b>" The foreign key %2 participates in join %3 and can not be ALTERed. %1"</b>
<b>Constant</b>	EMSG_CAT_JOINFIELDKEYMAT
<b>SAP Sybase Error Number</b>	21004
<b>SQL State</b>	QCA98
<b>SQL Code</b>	-1013098L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	the column of the foreign key
<b>Parameter 3</b>	the name of the join index
<b>Probable Cause</b>	This message is returned during ALTER when a foreign key that is about to be altered, participates in the join of two tables.

<b>Error 1013100</b>	"The ON keyword cannot be used in a NATURAL join. %1"
<b>Constant</b>	EMSG_SQL_JOININVALIDONWITHNATURAL
<b>SAP Sybase Error Number</b>	21020
<b>SQL State</b>	QCB00
<b>SQL Code</b>	-1013100L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	The ON keyword cannot be used in a NATURAL join.

<b>Error 1013102</b>	"User name '%2' does not exist. %1"
<b>Constant</b>	EMSG_SQL_FINDUSERBYNAME
<b>SAP Sybase Error Number</b>	21022
<b>SQL State</b>	QCB02
<b>SQL Code</b>	-1013102L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	the user name specified
<b>Probable Cause</b>	The specified user does not exist.

<b>Error 1013103</b>	"%2 not implemented %1"
<b>Constant</b>	EMSG_SQL_IQMSG_NOT_YET_IMPLEMENTED_IN_ATOMIC
<b>SAP Sybase Error Number</b>	22001
<b>SQL State</b>	QCC00
<b>SQL Code</b>	-1013103L

## Errors and Warnings

<b>Error 1013103</b>	<b>"%2 not implemented %1"</b>
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	Name of the feature
<b>Probable Cause</b>	This feature has not been implemented
<b>Error 1013104</b>	<b>"This operation is not allowed on the dbspace IQ_SYSTEM_TEMP. %1"</b>
<b>Constant</b>	EMSG_DBSPACE_ILLEGAL_TEMP_OP
<b>SAP Sybase Error Number</b>	22012
<b>SQL State</b>	QDD13
<b>SQL Code</b>	-1013104L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Illegal op for iq_system_temp
<b>Error 1013105</b>	<b>"Use ALTER DBSPACE ALTER FILE for this operation. %1"</b>
<b>Constant</b>	EMSG_DBSPACE_USE_ALTER_FILE
<b>SAP Sybase Error Number</b>	22013
<b>SQL State</b>	QDD14
<b>SQL Code</b>	-1013105L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception

<b>Error 1013105</b>	<b>"Use ALTER DBSPACE ALTER FILE for this operation. %1"</b>
<b>Probable Cause</b>	Must use alter dbspace alter file

<b>Error 1013106</b>	<b>"logical file %2 not part of dbspace %3. %1"</b>
<b>Constant</b>	EMSG_NON_EXISTENT_LOGICAL_FILENAME
<b>SAP Sybase Error Number</b>	22004
<b>SQL State</b>	QDC59
<b>SQL Code</b>	-1013106L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	logical filename that is to be altered
<b>Parameter 3</b>	dbspace named in sql command
<b>Probable Cause</b>	this logical filename is not part of this dbspace

<b>Error 1013107</b>	<b>"MPX: server %2 is not part of the Multiplex configuration. %1"</b>
<b>Constant</b>	EMSG_MPX_BADSERVER_NAME
<b>SAP Sybase Error Number</b>	22008
<b>SQL State</b>	QDD09
<b>SQL Code</b>	-1013107L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	Server name
<b>Probable Cause</b>	This is a multiplex and this server is not part of it.

## Errors and Warnings

<b>Error 1013108</b>	<b>"MPX: startup failure message: server '%2' was started on an incorrect host '%3': this server was created with this connection string '%4'. %1"</b>
<b>Constant</b>	EMSG_MPX_START_WRONG_HOST
<b>SAP Sybase Error Number</b>	22009
<b>SQL State</b>	QDD10
<b>SQL Code</b>	-1013108L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	server name
<b>Parameter 3</b>	host server was started on
<b>Parameter 4</b>	this server connection information
<b>Probable Cause</b>	This server cannot be started on this host
<b>Error 1013109</b>	<b>"MPX: coordinator has been started with an incorrect catalog. %1"</b>
<b>Constant</b>	EMSG_MPX_INCORRECT_CATALOG
<b>SAP Sybase Error Number</b>	22010
<b>SQL State</b>	QDD11
<b>SQL Code</b>	-1013109L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	The coordinator has been started with an incorrect catalog

<b>Warning 1013110</b>	"IQ had insufficient memory to create the buffer cache with the size specified with the Main_Cache_Memory_MB or Temp_Cache_Memory_MB options. Instead, the cache will be created using the default size."
<b>Constant</b>	EMSG_IQSTORE_OUTOFMEM_ONOPENDB
<b>SAP Sybase Error Number</b>	21033
<b>SQL State</b>	QSB35
<b>SQL Code</b>	1013110L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Probable Cause</b>	If we catch an OUTOFMEMORY exception when creating the MAIN or the TEMP buffer cache, we report this warning of our failure and retry to create the cache with the default settings (and NOT the settings in the hos_paramset). This will allow the DBA to re-open a database even if the Main_Cache_Memory_MB or Temp_Cache_Memory_MB options are set so high as to otherwise prevent the re-opening of the database. (QTS 183253.)

<b>Error 1013110</b>	"MPX: server %2 has been started with an incorrect catalog path (expected path: %3). %1"
<b>Constant</b>	EMSG_MPX_INCORRECT_CATALOG_PATH
<b>SAP Sybase Error Number</b>	22011
<b>SQL State</b>	QDD12
<b>SQL Code</b>	-1013110L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	server name
<b>Parameter 3</b>	expected catalog path
<b>Probable Cause</b>	The coordinator has been started with the incorrect catalog

## Errors and Warnings

<b>Warning 1013111</b>	<b>"WARNING***** File '%1' has a length of 0"</b>
<b>Constant</b>	EMSG_SQL_LOAD0LENGTHFILE
<b>SAP Sybase Error Number</b>	22162
<b>SQL State</b>	01A50
<b>SQL Code</b>	1013111L
<b>ODBC 2 State</b>	OK
<b>ODBC 3 State</b>	OK
<b>Severity Code</b>	<i>10</i> on page 2
<b>Parameter 1</b>	Filename
<b>Probable Cause</b>	An attempt was made to load a file of length 0
<b>Error 1013111</b>	<b>"MPX: This operation is not supported on a MPX secondary node. %1"</b>
<b>Constant</b>	EMSG_MPX_DBSPACE_ILLEGAL_ON_SN
<b>SAP Sybase Error Number</b>	22014
<b>SQL State</b>	QDD15
<b>SQL Code</b>	-1013111L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Not supported on a mpx secondary node

## Messages 1013112 through 1013131

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1013112</b>	<b>"MPX: Striping parameters for IQ_SYSTEM_TEMP are global and may only be altered on the coordinator node. %1"</b>
<b>Constant</b>	EMSG_MPX_DBSPACE_STRIPING_ILLEGAL_ON_SN

<b>Error 1013112</b>	"MPX: Striping parameters for IQ_SYSTEM_TEMP are global and may only be altered on the coordinator node.%1"
<b>SAP Sybase Error Number</b>	22015
<b>SQL State</b>	QDD116
<b>SQL Code</b>	-1013112L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Change striping for IQ_SYSTEM_TEMP on coordinator only.
<b>Error 1013113</b>	"The multiplex server '%2' is not included in the multiplex.%1"
<b>Constant</b>	EMSG_MPX_SERVER_NOT_INCLUDED
<b>SAP Sybase Error Number</b>	22016
<b>SQL State</b>	QNA49
<b>SQL Code</b>	-1013113L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Exception Location
<b>Parameter 2</b>	server name
<b>Probable Cause</b>	This multiplex server has been excluded
<b>Error 1013114</b>	"To start a Secondary node in single-node mode (-iqmpx_sn 1) the override switch (-iqmpx_ov 1) should be used %1"
<b>Constant</b>	EMSG_MPX_SECONDARY_NEED_OV_START_SINGLE
<b>SAP Sybase Error Number</b>	22017
<b>SQL State</b>	QNA50

## Errors and Warnings

<b>Error 1013114</b>	<b>"To start a Secondary node in single-node mode (-iqmpx_sn 1) the override switch (-iqmpx_ov 1) should be used %1"</b>
<b>SQL Code</b>	-1013114L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	Secondary servers are not allowed to start with -iqmpx_sn 1. As the use of -iqmpx_sn 1 makes the server the owner of the IQ database it should not be used unless coordinator restore and failover operations have failed. If it becomes necessary to re-establish ownership of the database by a secondary server you can start the secondary server with -iqmpx_sn 1 only with override (-iqmpx_ov 1)
<b>Error 1013115</b>	<b>"IQ Internal multiplex error. Please report this to Sybase IQ support. %1"</b>
<b>Constant</b>	EMSG_MPX_FATAL_PROGERROR
<b>SAP Sybase Error Number</b>	22018
<b>SQL State</b>	QDD18
<b>SQL Code</b>	-1013115L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>23</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	A fatal programming error encountered, server will be aborted.
<b>Error 1013116</b>	<b>"The operation has been cancelled - Mpx_Work_Unit_Timeout exceeded. %2 %1"</b>
<b>Constant</b>	EMSG_MPX_WU_TIMEOUT
<b>SAP Sybase Error Number</b>	22020
<b>SQL State</b>	QDD21
<b>SQL Code</b>	-1013116L

<b>Error 1013116</b>	"The operation has been cancelled - Mpx_Work_Unit_Timeout exceeded. %2 %1"
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	explanation for arg %2 delete if no %2
<b>Probable Cause</b>	The elapsed time to complete a distributed work unit exceed the timeout value.
<b>Error 1013117</b>	"Worker rejected query fragment - %2. %1"
<b>Constant</b>	EMSG_WORKER_REJECTED_QUERY_FRAGMENT
<b>SAP Sybase Error Number</b>	22024
<b>SQL State</b>	QDD24
<b>SQL Code</b>	-1013117L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of exception
<b>Parameter 2</b>	reason for rejecting the fragment.
<b>Probable Cause</b>	Worker node could not execute a remote procedure call.
<b>Error 1013118</b>	"Login denied to logical server '%2', Either the server is not part of the logical server or does not match the node type or login redirection is disabled. %1"
<b>Constant</b>	EMSG_LOGIN_REDIRECTION_ERROR
<b>SAP Sybase Error Number</b>	22031
<b>SQL State</b>	QXA63
<b>SQL Code</b>	-1013118L
<b>ODBC 2 State</b>	ERROR

## Errors and Warnings

<b>Error 1013118</b>	<b>"Login denied to logical server '%2', Either the server is not part of the logical server or does not match the node type or login redirection is disabled. %1"</b>
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	logical server id
<b>Probable Cause</b>	This connection attempt failed because the logical server did not match the connection criteria
<b>Error 1013119</b>	<b>"To redirect to the COORDINATOR logical server the connection parameter nodetype should be a 'writer'. %1"</b>
<b>Constant</b>	EMSG_NODETYPE_MUST_BE_WRITER
<b>SAP Sybase Error Number</b>	22032
<b>SQL State</b>	QXA64
<b>SQL Code</b>	-1013119L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	23 on page 2
<b>Parameter 1</b>	location of the exception
<b>Probable Cause</b>	The connection parameter logicalserver = coordinator must ask for a writer node
<b>Error 1013120</b>	<b>"Worker unable to send remote procedure call to leader. - %2. %1"</b>
<b>Constant</b>	EMSG_WORKER_RPC_FAILURE
<b>SAP Sybase Error Number</b>	22035
<b>SQL State</b>	QDD28
<b>SQL Code</b>	-1013120L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

<b>Error 1013120</b>	"Worker unable to send remote procedure call to leader. - %2. %1"
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of exception
<b>Parameter 2</b>	reason for rejecting the fragment.
<b>Probable Cause</b>	The worker node is trying to send a message to the leader node but the leader is no longer available.
<b>Error 1013121</b>	<b>"Cannot truncate partition "%2' of table '%3' - table partitioned incorrectly. %1"</b>
<b>Constant</b>	EMSG_CANNOT_TRUNCATE_PARTITION
<b>SAP Sybase Error Number</b>	22151
<b>SQL State</b>	QDD29
<b>SQL Code</b>	-1013121L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	partition name.
<b>Parameter 3</b>	table name.
<b>Probable Cause</b>	Table must be range partitioned for truncate partition and hash-range partitioned for truncate subpartition
<b>Error 1013122</b>	<b>"Cannot add a partition or subpartition to table %2 %1"</b>
<b>Constant</b>	EMSG_TABLE_CONTAINS_DATA_CANNOT_HASH_PARTITION
<b>SAP Sybase Error Number</b>	22152
<b>SQL State</b>	QDD30
<b>SQL Code</b>	-1013122L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR

## Errors and Warnings

<b>Error 1013122</b>	<b>"Cannot add a partition or subpartition to table %2 %1"</b>
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	table name.
<b>Probable Cause</b>	Alter table add partition hash - not allowed on table that contains data
<b>Error 1013123</b>	<b>"Invalid value for IQ UNIQUE on column %2 %1"</b>
<b>Constant</b>	EMSG_INVALID_IQ_UNIQUE
<b>SAP Sybase Error Number</b>	22153
<b>SQL State</b>	QDD31
<b>SQL Code</b>	-1013123L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	column name.
<b>Probable Cause</b>	Value out of range or datatype does not allow dictionary compression
<b>Error 1013124</b>	<b>"NBIT Column %2 exceeded token limit of %3 %1"</b>
<b>Constant</b>	EMSG_NBIT_LIMIT_EXCEEDED
<b>SAP Sybase Error Number</b>	22154
<b>SQL State</b>	QDD32
<b>SQL Code</b>	-1013124L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	column name.
<b>Parameter 3</b>	token limit.

<b>Error 1013124</b>	"NBIT Column %2 exceeded token limit of %3 %1"
<b>Probable Cause</b>	Exceeded the IQ UNIQUE(N) limit defined for this column.
<b>Error 1013125</b>	<b>"The optimizer hint ESTIMATED IQ UNIQUE is only allowed on flat FP columns %2 %1"</b>
<b>Constant</b>	EMSG_INVALID_EST_IQ_UNIQUE
<b>SAP Sybase Error Number</b>	22155
<b>SQL State</b>	QDD33
<b>SQL Code</b>	-1013125L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	column name.
<b>Probable Cause</b>	Estimated unique is only allowed on flat columns.
<b>Error 1013126</b>	<b>"Value %3 is less than the current maximum token %4 for column %2 %1"</b>
<b>Constant</b>	EMSG_NBIT_VALUE_TOO_LOW
<b>SAP Sybase Error Number</b>	22156
<b>SQL State</b>	QDD34
<b>SQL Code</b>	-1013126L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	column name.
<b>Parameter 3</b>	new value.
<b>Parameter 4</b>	current number of tokens.

## Errors and Warnings

<b>Error 1013126</b>	"Value %3 is less than the current maximum token %4 for column %2 %1"
<b>Probable Cause</b>	The Value is lower than the current number of tokens in the column
<b>Error 1013127</b>	<b>"Create RLV dbspace not allowed in multiplex."</b>
<b>Constant</b>	EMSG_DBSPACE_RLV_MPX_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	22157
<b>SQL State</b>	QRLV1A
<b>SQL Code</b>	-1013127L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	RLV dbspace may not be created in multiplex nodes.
<b>Error 1013128</b>	<b>"The RLV freelist is corrupted."</b>
<b>Constant</b>	EMSG_RLV_FREELIST_CORRUPT
<b>SAP Sybase Error Number</b>	22158
<b>SQL State</b>	QRLV1B
<b>SQL Code</b>	-1013128L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Probable Cause</b>	The RLV freelist is corrupted.
<b>Error 1013129</b>	<b>"RLV Store has run out of memory"</b>
<b>Constant</b>	EMSG_RLV_HEAP_MEMORY_EXHAUSTED
<b>SAP Sybase Error Number</b>	22159
<b>SQL State</b>	QRLV1C
<b>SQL Code</b>	-1013129L
<b>ODBC 2 State</b>	ERROR

<b>Error 1013129</b>	"RLV Store has run out of memory"
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Probable Cause</b>	RLV store has exceeded the configured memory limit.
<b>Error 1013130</b>	<b>"All IQ large memory has been used, allocation canceled [size: %2] %1"</b>
<b>Constant</b>	EMSG_LMA_OUTOFMEMORY
<b>SAP Sybase Error Number</b>	22160
<b>SQL State</b>	QBC75
<b>SQL Code</b>	-1013130L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	The size of unable to allocate memory
<b>Probable Cause</b>	iqlm large memory manager reprot error
<b>Error 1013131</b>	<b>"Cannot unpartition a non-empty hash or hash-range partitioned table %2 %1"</b>
<b>Constant</b>	EMSG_TABLE_CONTAINS_DATA_CANNOT_UNPARTITION_HASH_PARTITION
<b>SAP Sybase Error Number</b>	22161
<b>SQL State</b>	QDD35
<b>SQL Code</b>	-1013131L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	Location of the exception.
<b>Parameter 2</b>	table name.

<b>Error 1013131</b>	<b>"Cannot unpartition a non-empty hash or hash-range partitioned table %2 %1"</b>
<b>Probable Cause</b>	Alter table unpartition hash partition hash - not allowed on table that contains data

## Messages 1013132 through 1013136

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

<b>Error 1013132</b>	<b>"A local main cache already exists for the node %2. %1"</b>
<b>Constant</b>	EMSG_DBSPACE_CACHE_CREATION_NOT_ALLOWED
<b>SAP Sybase Error Number</b>	22163
<b>SQL State</b>	QDD36
<b>SQL Code</b>	-1013132L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	server name
<b>Probable Cause</b>	Creation of more than one user defined CACHE dbspace is not allowed per node.

<b>Error 1013133</b>	<b>"%2 is not allowed on cache dbspace %3. %1"</b>
<b>Constant</b>	EMSG_DBSPACE_NOT_ALLOWED_CACHE
<b>SAP Sybase Error Number</b>	22164
<b>SQL State</b>	QDD37
<b>SQL Code</b>	-1013133L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception

<b>Error 1013133</b>	<b>"%2 is not allowed on cache dbspace %3. %1"</b>
<b>Parameter 2</b>	disallowed command
<b>Parameter 3</b>	dbspace name
<b>Probable Cause</b>	The requested DDL operation is not allowed on cache dbspaces
<b>Error 1013134</b>	<b>"Error accessing server '%2': %3 %1"</b>
<b>Constant</b>	EMSG_XT_ACCESS_ERROR
<b>SAP Sybase Error Number</b>	22165
<b>SQL State</b>	QCB88
<b>SQL Code</b>	-1013134L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	server name
<b>Parameter 3</b>	server specific error message
<b>Probable Cause</b>	An error occurred while accessing an external server.
<b>Error 1013135</b>	<b>"Error converting %2 to %3 %1"</b>
<b>Constant</b>	EMSG_XT_CONVERSION_ERROR
<b>SAP Sybase Error Number</b>	22166
<b>SQL State</b>	QCB89
<b>SQL Code</b>	-1013135L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>I4</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	value
<b>Parameter 3</b>	datatype

## Errors and Warnings

<b>Error 1013135</b>	<b>"Error converting %2 to %3 %1"</b>
<b>Probable Cause</b>	Error converting value returned from an external server to target datatype
<b>Error 1013136</b>	<b>"Cannot acquire agent info from server %2. %1"</b>
<b>Constant</b>	EMSG_MPX_AGENT_INFO_NOT_FOUND
<b>SAP Sybase Error Number</b>	21192
<b>SQL State</b>	QDD01
<b>SQL Code</b>	-1013136L
<b>ODBC 2 State</b>	ERROR
<b>ODBC 3 State</b>	ERROR
<b>Severity Code</b>	<i>14</i> on page 2
<b>Parameter 1</b>	location of the exception
<b>Parameter 2</b>	server id
<b>Probable Cause</b>	Agent for this server appears to running but failed to get needed info

# SQL Preprocessor Errors

## Messages 2601 through 2621

Messages on this page are sorted by error number. Locate the appropriate error code in the table below.

Error Code	Type	Message	Possible Cause
2601	Error	Subscript value %1 too large	You have attempted to index a host variable that is an array with a value too large for the array.
2602	Error	Combined pointer and arrays not supported for host types	You have used an array of pointers as a host variable. This is not legal.
2603	Error	Only one-dimensional arrays supported for CHAR type	You have attempted to declare a host variable as an array of character arrays. This is not a legal host variable type
2604	Error	VARCHAR type must have a length	You have attempted to declare a VARCHAR or BINARY host variable using the DECL_VARCHAR or DECL_BINARY macro but have not specified a size for the array.
2605	Error	Arrays of VARCHAR not supported	You have attempted to declare a host variable as an array of VARCHAR or BINARY. This is not a legal host variable type.
2606	Error	VARCHAR host variables cannot be pointers	You have attempted to declare a host variable as a pointer to a VARCHAR or BINARY. This is not a legal host variable type.
2607	Error	Initializer not allowed on VARCHAR host variable	You can not specify a C variable initializer for a host variable of type VARCHAR or BINARY. You must initialize this variable in regular C executable code.

## SQL Preprocessor Errors

Error Code	Type	Message	Possible Cause
2608	Error	FIXCHAR type must have a length	You have used the DECL_FIXCHAR macro to declare a host variable of type FIXCHAR but have not specified a length.
2609	Error	Arrays of FIXCHAR not supported	You have attempted to declare a host variable as an array of FIXCHAR arrays. This is not a legal host variable type.
2610	Error	Arrays of this type not supported	You have attempted to declare a host variable array of a type that is not supported.
2611	Error	Precision must be specified for decimal type	You must specify the precision when declaring a packed decimal host variable using the DECL_DECIMAL macro. The scale is optional.
2612	Error	Arrays of decimal not allowed	You have attempted to declare a host variable as an array of DECIMAL. This is not a legal host variable type
2613	Error	Unknown host variable type	You declared a host variable of a type not understood by the SQL preprocessor.
2614	Error	Invalid integer	An integer was required in an Embedded SQL statement (for a fetch offset, or a host variable array index, etc.) and the preprocessor was unable to convert what was supplied into an integer.
2615	Error	'%1' host variable must be a C string type	A C string was required in an Embedded SQL statement (for a cursor name, option name, etc.) and the value supplied was not a C string.
2617	Error	'%1' symbol already defined	You defined a host variable twice.
2618	Error	Invalid type for SQL statement variable	A host variable used as a statement identifier should be of type a_sql_statement_number. You attempted to use a host variable of some other type as a statement identifier.

Error Code	Type	Message	Possible Cause
2619	Error	Cannot find include file '%1'	The specified include file was not found. Note that the preprocessor will use the INCLUDE environment variable to search for include files.
2620	Error	Host variable '%1' is unknown	You have used a host variable in a statement and that host variable has not been declared in a declare section.
2621	Error	Indicator variable '%1' is unknown	You have used a indicator variable in a statement and that indicator variable has not been declared in a declare section

## Messages 2622 through 2649

Messages on this page are sorted by error number. Locate the appropriate error code in the table below.

Error Code	Type	Message	Possible Cause
2622	Error	Invalid type for indicator variable '%1'	Indicator variables must be of type short int. You have used a variable of a different type as an indicator variable.
2623	Error	Invalid host variable type on '%1'	You have used a host variable that is not a string type in a place where the preprocessor was expecting a host variable of a string type.
2625	Error	Host variable '%1' has two different definitions	The same host variable name was defined with two different types within the same module. Note that host variable names are global to a C module.
2626	Error	Statement '%1' not previously prepared	An Embedded SQL statement name has been used (EXECUTE) without first being prepared.

## SQL Preprocessor Errors

Error Code	Type	Message	Possible Cause
2627	Error	Cursor '%1' not previously declared	An Embedded SQL cursor name has been used (in a FETCH, OPEN, CLOSE, etc.) without first being declared.
2628	Error	Unknown statement '%1'	You attempted to drop an embedded SQL statement that doesn't exist.
2629	Error	Host variables not allowed for this cursor	Host variables are not allowed on the declare statement for the specified cursor. If the cursor name is provided through a host variable, then you should use full dynamic SQL and prepare the statement. A prepared statement may have host variables in it.
2630	Error	Host variables specified twice - on declare and open	You have specified host variables for a cursor on both the declare and the open statements. In the static case, you should specify the host variables on the declare statement. In the dynamic case, specify them on the open.
2631	Error	Must specify a host list or using clause on %1	The specified statement requires host variables to be specified either in a host variable list or from an SQLDA.
2633	Error	No INTO clause on SELECT statement	You specified an embedded static SELECT statement, but you did not specify an INTO clause for the results.
2636	Error	Incorrect Embedded SQL syntax	An Embedded SQL specific statement (OPEN, DECLARE, FETCH, etc.) has a syntax error.
2637	Error	Missing ending quote of string	You have specified a string constant in an Embedded SQL statement, but there is no ending quote before the end of line or end of file.

Error Code	Type	Message	Possible Cause
2639	Error	Token too long	The SQL preprocessor has a maximum token length of 2K. Any token longer than 2K will produce this error. For constant strings in Embedded SQL commands (the main place this error shows up) use string concatenation to make a longer string.
2640	Error	'%1' host variable must be an integer type	You have used a host variable that is not of integer type in a statement where only an integer type host variable is allowed.
2641	Error	Must specify an SQLDA on a DESCRIBE	No additional information available.
2642	Error	Two SQLDAs specified of the same type (INTO or USING)	You have specified two INTO DESCRIPTOR or two USING DESCRIPTOR clauses for this statement.
2646	Error	Cannot describe static cursors	You have described a static cursor. When describing a cursor, the cursor name must be specified in a host variable
2647	Error	Macros cannot be redefined	A preprocessor macro has been defined twice, possibly in a header file.
2648	Error	Invalid array dimension	The array dimension of the variable is negative
2649	Error	Invalid descriptor index	You have allocated less than one variable with the ALLOCATE DESCRIPTOR statement.

## Messages 2650 through 2692

---

Messages on this page are sorted by error number. Locate the appropriate error code in the table below.

Error Code	Type	Message	Possible Cause
2650	Error	Invalid field for SET DESCRIPTOR	An invalid or unknown keyword is present in a SET DESCRIPTOR statement. The keywords can only be TYPE, PRECISION, SCALE, LENGTH, INDICATOR, or DATA.
2651	Error	Field used more than once in SET DESCRIPTOR statement	The same keyword has been used more than once inside a single SET DESCRIPTOR statement.
2652	Error	Data value must be a host variable	The variable used in the SET DESCRIPTOR statement hasn't been declared as a host variable.
2660	Warning	Into clause not allowed on declare cursor - ignored	You have specified an INTO clause on a SELECT statement in a DECLARE CURSOR. Note that the INTO clause will be ignored.
2661	Warning	Unrecognized SQL syntax	You have used a SQL statement that will probably cause a syntax error when the statement is sent to the database server.
2662	Warning	Unknown SQL function '%1'	You have used a SQL function that is unknown to the preprocessor and will probably cause an error when the statement is sent to the database engine.
2663	Warning	Wrong number of arguments to SQL function '%1'	You have used a SQL function with the wrong number of parameters. This will likely cause an error when the statement is sent to the database server.

Error Code	Type	Message	Possible Cause
2664	Warning	Static statement names will not work properly if used by 2 threads	You have used a static statement name and preprocessed with the -r reentrancy switch. Static statement names cause static variables to be generated that are filled in by the database. If two threads use the same statement, contention arises over this var
2665	Warning	Host variable '%1' has been redefined	You have redefined the same host variable with a different host type. As far as the preprocessor is concerned, host variables are global; two host variables with different types cannot have the same name.
2666	Flag (warning or error)	Disallowed language extension detected in syntax	You have used a feature that is not defined by SQL/92 and preprocessed with the -ee, -ei, -ef, -we, -wi or -wf flagging switch.
2667	Flag (warning or error)	Language extension detected in syntax	You have used a SQL Anywhere feature that is not supported by the current flagging level (set using the -w option).
2668	Flag (warning or error)	Full SQL feature	You have used a full-SQL/92 feature and preprocessed with the -ee, -ei, -we or -wi flagging switch.
2669	Flag (warning or error)	Transact SQL extension	You have used a Sybase Transact SQL feature that is not defined by SQL/92 and preprocessed with the -ee, -ei, -ef, -we, -wi or -wf flagging switch.
2680	Error	No DECLARE SECTION and no INCLUDE SQLCA statement	The EXEC SQL INCLUDE SQLCA statement is missing from the source file.
2681	Error	Unable to open temporary file	An error occurred while attempting to open a temporary file.
2682	Error	Error reading temporary file	An error occurred while reading from a temporary file.
2683	Error	Error writing output file	An error occurred while writing to the output file.

Error Code	Type	Message	Possible Cause
2690	Error	Inconsistent number of host variables for this cursor	You have used a different number of host variables than the number previously used with the cursor. The number of host variables must be consistent for the cursor.
2691	Error	Inconsistent host variable types for this cursor	You have used a host variable with a different type or length than the type or length previously used with the cursor. Host variable types must be consistent for the cursor.
2692	Error	Inconsistent indicator variables for this cursor	You have used an indicator variable when one was not previously used with the cursor, or you have not used an indicator variable when one was previously used with the cursor. Indicator variable usage must be consistent for the cursor.

## Messages 2694 through 2701

Messages on this page are sorted by error number. Locate the appropriate error code in the table below.

Error Code	Type	Message	Possible Cause
2694	Error	No OPEN for cursor '%1'	A cursor is declared, and possibly used, but is never opened.
2695	Error	No FETCH or PUT for cursor '%1'	A cursor is declared and opened, but is never used.
2696	Error	Host variable '%1' is in use more than once with different indicators	You have used the same host variable multiple times with different indicator variables in the same statement. This is not supported.
2698	Error	WCHAR and TCHAR host variable types are not supported	You have attempted to declare a host variable as a WCHAR or TCHAR string. These are only supported by UltraLite on Windows platforms.

Error Code	Type	Message	Possible Cause
2699	Error	char, WCHAR, and TCHAR string parameters cannot be mixed	You have attempted to use parameters to one statement that are not all char strings, WCHAR strings or TCHAR strings. String parameters (other than INTO and USING parameters) for one statement must all be the same type of string. Note that literal strings are treated as char strings.
2701	Error	FOR UPDATE or FOR READ ONLY clause must be specified on PREPARE (not on DECLARE CURSOR)	You specified the FOR UPDATE or FOR READ ONLY clause on a DECLARE CURSOR statement. The FOR UPDATE or FOR READ ONLY clause must be specified on the PREPARE statement and not the DECLARE CURSOR statement. For compatibility with previous versions (but with reduced performance), the sqlpp -m HISTORICAL option can be used to allow the FOR UPDATE or FOR READ ONLY clause on the DECLARE CURSOR statement.

