



SAP Sybase IQ Error Messages

SAP Sybase IQ 16.0 SP03

DOCUMENT ID: DC00462-01-1603-01

LAST REVISED: November 2013

Copyright © 2013 by SAP AG or an SAP affiliate company. All rights reserved.

No part of this publication may be reproduced or transmitted in any form or for any purpose without the express permission of SAP AG. The information contained herein may be changed without prior notice.

Some software products marketed by SAP AG and its distributors contain proprietary software components of other software vendors. National product specifications may vary.

These materials are provided by SAP AG and its affiliated companies ("SAP Group") for informational purposes only, without representation or warranty of any kind, and SAP Group shall not be liable for errors or omissions with respect to the materials. The only warranties for SAP Group products and services are those that are set forth in the express warranty statements accompanying such products and services, if any. Nothing herein should be construed as constituting an additional warranty.

SAP and other SAP products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of SAP AG in Germany and other countries. Please see <http://www.sap.com/corporate-en/legal/copyright/index.epx#trademark> for additional trademark information and notices.

Contents

About this guide	1
Messages	1
Severity Codes	2
SQL Preprocessor Errors	3
Errors and Warnings	5
0 - 262	5
Messages 0 through 91	5
Messages 92 through 105	13
Messages 106 through 116	21
Messages 117 through 128	30
Messages 129 through 140	39
Messages 140 through 150	48
Messages 151 through 180	57
Messages 181 through 200	65
Messages 200 through 218	74
Messages 220 through 262	83
263 - 785	91
Messages 263 through 288	92
Messages 289 through 313	100
Messages 503 through 619	109
Messages 620 through 639	118
Messages 640 through 659	126
Messages 660 through 681	134
Messages 682 through 709	143
Messages 710 through 731	151
Messages 732 through 760	159
Messages 761 through 785	168
786 - 1005	176
Messages 786 through 809	177
Messages 810 through 829	185
Messages 830 through 854	194

Messages 855 through 876	203
Messages 877 through 901	213
Messages 902 through 923	222
Messages 924 through 944	230
Messages 945 through 964	238
Messages 965 through 985	247
Messages 986 through 1005	255
1006 - 1217	264
Messages 1006 through 1028	264
Messages 1029 through 1050	272
Messages 1051 through 1075	281
Messages 1076 through 1096	290
Messages 1097 through 1117	299
Messages 1118 through 1137	308
Messages 1138 through 1157	317
Messages 1158 through 1177	327
Messages 1178 through 1197	336
Messages 1198 through 1217	345
1218 - 1427	353
Messages 1218 through 1237	354
Messages 1239 through 1260	362
Messages 1261 through 1280	371
Messages 1281 through 1301	379
Messages 1302 through 1321	388
Messages 1322 through 1341	397
Messages 1342 through 1363	407
Messages 1366 through 1386	416
Messages 1387 through 1406	424
Messages 1407 through 1427	433
1428 - 1629	441
Messages 1428 through 1448	442
Messages 1449 through 1468	450
Messages 1469 through 1489	458
Messages 1490 through 1509	467
Messages 1510 through 1529	476

Messages 1530 through 1549	486
Messages 1550 through 1569	495
Messages 1570 through 1589	503
Messages 1590 through 1609	512
Messages 1610 through 1629	521
1630 - 1000133	531
Messages 1630 through 1649	531
Messages 1650 through 1669	539
Messages 1670 through 1689	548
Messages 1690 through 1709	557
Messages 1710 through 1000008	566
Messages 1000009 through 1000040	575
Messages 1000041 through 1000061	585
Messages 1000062 through 1000084	594
Messages 1000085 through 1000107	604
Messages 1000108 through 1000133	615
1000134 - 1000328	626
Messages 1000134 through 1000154	626
Messages 1000155 through 1000174	636
Messages 1000175 through 1000197	646
Messages 1000199 through 1000218	656
Messages 1000219 through 1000235	666
Messages 1000235 through 1000245	675
Messages 1000246 through 1000264	686
Messages 1000265 through 1000284	695
Messages 1000285 through 1000306	705
Messages 1000307 through 1000328	714
1000329 - 1006035	723
Messages 1000329 through 1001010	723
Messages 1001011 through 1001030	732
Messages 1001031 through 1001050	741
Messages 1001051 through 1001071	749
Messages 1001072 through 1003001	759
Messages 1003002 through 1004007	768
Messages 1004008 through 1005010	777

Messages 1005011 through 1005030	786
Messages 1005031 through 1006015	795
Messages 1006016 through 1006035	804
1006036 - 1006238	812
Messages 1006036 through 1006055	813
Messages 1006056 through 1006075	821
Messages 1006076 through 1006095	829
Messages 1006096 through 1006116	838
Messages 1006117 through 1006137	846
Messages 1006138 through 1006157	854
Messages 1006158 through 1006177	862
Messages 1006178 through 1006197	871
Messages 1006198 through 1006217	879
Messages 1006218 through 1006238	887
1006239 - 1009145	895
Messages 1006239 through 1006258	895
Messages 1006259 through 1008005	904
Messages 1008006 through 1008027	912
Messages 1008029 through 1009023	921
Messages 1009024 through 1009043	930
Messages 1009044 through 1009064	940
Messages 1009065 through 1009084	950
Messages 1009085 through 1009104	960
Messages 1009105 through 1009124	969
Messages 1009125 through 1009145	979
1009146 - 1013018	990
Messages 1009146 through 1009165	991
Messages 1009166 through 1009185	1000
Messages 1009186 through 1009420	1010
Messages 1010000 through 1010019	1019
Messages 1010020 through 1010040	1029
Messages 1010041 through 1010060	1038
Messages 1010061 through 1012005	1047
Messages 1012006 through 1012025	1055
Messages 1012026 through 1012045	1063

Messages 1012046 through 1013018	1073
1013019 - 1013136	1082
Messages 1013019 through 1013040	1082
Messages 1013041 through 1013062	1092
Messages 1013063 through 1013088	1101
Messages 1013089 through 1013111	1109
Messages 1013112 through 1013131	1118
Messages 1013132 through 1013136	1128
SQL Preprocessor Errors	1131
Messages 2601 through 2621	1131
Messages 2622 through 2649	1133
Messages 2650 through 2692	1136
Messages 2694 through 2701	1138

About this guide

The SAP® Sybase® IQ Error Messages Guide is an reference for SAP Sybase IQ errors and warnings.

Organization

This guide references *SAP Sybase Error Codes* on page 1 and *SQL Preprocessor Errors* on page 3. Messages are organized by error number and include all attributes associated with the message.

Other sources of information

- For additional information about SAP Sybase IQ, see the SAP Sybase IQ documentation set.
- The *SAP Sybase Product Documentation Web site* provides online access to all of the books in the SAP Sybase IQ documentation set. The *SAP Sybase Web site* also includes links to *SAP Sybase Product Download Center*, *Platform Certifications*, and the *SAP Sybase Developer Network*. Create a personal profile on the *MySybase page* to simplify your browsing.

If you need help

Each SAP Sybase installation with a valid support contract should have one or more designated people authorized to contact SAP Sybase Technical Support. If you cannot resolve a problem using the manuals or online help, please have that designated person contact SAP Sybase Technical Support or the SAP Sybase subsidiary in your area.

Messages

Messages are grouped by range and include all attributes associated with the error or warning. To find information about a message, choose the appropriate page.

Row Name	Description
Error or Warning	Error number and full text of the message.
Constant	Unique string constant for each message.
SAP Sybase Error Number	<p>SAP Sybase error numbers are a set of error codes used by all SAP Sybase products.</p> <p>For every error code returned by SAP Sybase IQ, there is a pair of matching SQLCODE and SQLSTATE codes. Some error codes are not unique. Many of the errors contain the characters %1, %2 and so on. These are replaced by the parameters to the error message.</p>

Row Name	Description
SQL State	<p>SQLSTATE error codes are defined by the SQL/92 standard. Each SQLSTATE value is a 5-character string containing a 2-character class followed by a 3-character subclass.</p> <p>Each character can be one of the uppercase letters A through Z or the digits 0 through 9. A class that begins with A through H or 0 through 4 has been defined by the ANSI standard; other classes are implementation defined. Similarly, subclasses of standard classes that start with the same characters (A-H, 0-4) are standard. The subclass 000 always means that no subclass code is defined. The most common SQLSTATE value is 00000, which indicates successful completion.</p>
SQL Code	<p>SQLCODE is a numeric code associated with an exception. Negative codes are considered errors; positive codes are warnings.</p> <p>If a SQLCODE has both a negative and a positive value, the first message listed is 'Warning nnn' (the positive SQLCODE), then 'Error nnn' (the negative SQLCODE). The SQLCODE 0 indicates successful completion.</p>
ODBC 2 State	ODBCSTATE 2 is set to OK or ERROR.
ODBC 3 State	ODBCSTATE 3 is set to OK or ERROR.
Severity Codes	Each numbered error message has an associated severity level that indicates the seriousness of the problem.
Parameters	Many error messages contain the characters %1, %2, and so on. These characters are replaced by the parameters to the error message.
Probable Cause	Probable Cause tells you what the problem is, and may suggest how to fix it.

Severity Codes

Severity codes indicate the degree and source of the error.

Number	Description	Number	Description
0	Comment.	17	Insufficient resources.
1	Information.	18	Non-fatal internal error detected.
10	Status information; warning.	19	Fatal error in resource.
11	Specified database object not found.	20	Fatal error in current process.
12	Wrong data type encountered.	21	Fatal error in database processes.

Number	Description	Number	Description
13	User transaction syntax error.	22	Fatal error: table integrity suspect.
14	Insufficient permission to execute command.	23	Hardware error or system table corruption.
15	Syntax error in SQL statement.	24	Hardware error or system table corruption.
16	Miscellaneous user error (non-fatal).		

SQL Preprocessor Errors

SQL preprocessor errors occur in the C preprocessor.

Embedded SQL is a database programming interface for the C and C++ programming languages. Embedded SQL consists of SQL statements intermixed with (embedded in) C or C++ source code. These SQL statements are translated by a SQL preprocessor into C or C++ source code, which then need to be recompiled by the user. The Sybase IQ SQL preprocessor utility `sqlpp` translates the SQL statements in an input file `sqc` into C language source that is put into an output file `.c`.

SQL preprocessor errors are grouped by range. To find information about a specific error or warning, choose the appropriate page.

Errors and Warnings

0 - 262

Messages 0 through 91

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Warning 0	No message
Constant	NOERROR
SAP Sybase Error Number	2000
SQL State	00000
SQL Code	0L
ODBC 2 State	00000
ODBC 3 State	00000
Severity Code	10 on page 2
Probable Cause	This code indicates that there was no error or warning.

Error 72	"No database file specified"
Constant	NO_DATABASE_FILE
SAP Sybase Error Number	2021
SQL State	08W39
SQL Code	-72L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	11 on page 2
Probable Cause	The database server was started but there was no specified database file. The server is stopped.

Error 74	"The selected database is currently inactive"
Constant	DATABASE_NOT_ACTIVE
SAP Sybase Error Number	2013
SQL State	08W30
SQL Code	-74L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	14 on page 2
Probable Cause	The selected database is in an inactive state. The database may be in the process of being started or shut down.

Error 75	"Request to start/stop database denied"
Constant	START_STOP_DATABASE_DENIED
SAP Sybase Error Number	2014
SQL State	08W29
SQL Code	-75L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	14 on page 2
Probable Cause	You do not have permission to start or stop a database. The required permission is determined on the server command line.

Error 76	"Request denied -- no active databases"
Constant	REQUEST_DENIED_NO_DATABASES
SAP Sybase Error Number	2015
SQL State	08W28
SQL Code	-76L
ODBC 2 State	08004
ODBC 3 State	08004

Error 76	"Request denied -- no active databases"
Severity Code	<i>14</i> on page 2
Probable Cause	The server has denied your request as there are currently no running databases.

Error 77	"Database name not unique"
Constant	ALIAS_CLASH
SAP Sybase Error Number	2016
SQL State	08W27
SQL Code	-77L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	<i>16</i> on page 2
Probable Cause	The database cannot be started as its name conflicts with a previously started database.

Error 78	"Dynamic memory exhausted"
Constant	DYNAMIC_MEMORY_EXHAUSTED
SAP Sybase Error Number	2024
SQL State	08W26
SQL Code	-78L
ODBC 2 State	S1001
ODBC 3 State	HY001
Severity Code	<i>17</i> on page 2
Probable Cause	A failure occurred when the database server was trying to allocate dynamic memory.

Error 79	"Invalid local database option"
Constant	INVALID_LOCAL_OPTION
SAP Sybase Error Number	2017

Error 79	"Invalid local database option"
SQL State	08W25
SQL Code	-79L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	18 on page 2
Probable Cause	An invalid database option was found in the DBS (DatabaseSwitches) connection parameter.

Error 80	"Unable to start database server"
Constant	UNABLE_TO_START_ENGINE
SAP Sybase Error Number	2011
SQL State	08W07
SQL Code	-80L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	17 on page 2
Probable Cause	It was not possible to start the database server. There may not be enough memory to run the database server. It may also be that the executable cannot be found.

Error 81	"Invalid database server command line"
Constant	INVALID_COMMAND_LINE
SAP Sybase Error Number	2012
SQL State	08W08
SQL Code	-81L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	18 on page 2

Error 81	"Invalid database server command line"
Probable Cause	It was not possible to start the database server because the command line was invalid.

Error 82	"Unable to start specified database: %1"
Constant	UNABLE_TO_START_DATABASE
SAP Sybase Error Number	2018
SQL State	08W09
SQL Code	-82L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	11 on page 2
Parameter 1	Reason the database could not be started, if known.
Probable Cause	The database server was unable to start the specified database. Check the database server messages window for more details. If the server was being started automatically, you can use the database server -o option to view messages from the database server or start the server manually to try to obtain more information about why the database cannot be started.

Error 83	"Specified database not found"
Constant	DATABASE_NOT_FOUND
SAP Sybase Error Number	2019
SQL State	08W10
SQL Code	-83L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	16 on page 2

Error 83	"Specified database not found"
Probable Cause	The database server was unable to find the specified database. The database server may be attempting to start a database file that cannot be opened or that cannot be found on the network. You may be attempting to connect to a database name that is not running.

Error 84	"Specified database is invalid"
Constant	INVALID_DATABASE
SAP Sybase Error Number	2020
SQL State	08W11
SQL Code	-84L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	11 on page 2
Probable Cause	The database file you specified is invalid. The database server is stopped.

Error 85	"Communication error"
Constant	COMMUNICATIONS_ERROR
SAP Sybase Error Number	2022
SQL State	08W12
SQL Code	-85L
ODBC 2 State	08S01
ODBC 3 State	08S01
Severity Code	21 on page 2
Probable Cause	There is a communication problem between the application and the server.

Error 86	"Not enough memory to start"
Constant	NO_MEMORY
SAP Sybase Error Number	2025

Error 86	"Not enough memory to start"
SQL State	08W13
SQL Code	-86L
ODBC 2 State	S1001
ODBC 3 State	HY001
Severity Code	17 on page 2
Probable Cause	The database server started, but stopped because there was not enough memory.

Error 87	"Database name required to start server"
Constant	DATABASE_NAME_REQUIRED
SAP Sybase Error Number	2026
SQL State	08W14
SQL Code	-87L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	17 on page 2
Probable Cause	You did not supply a database name. A database name is required to start a database server.

Error 88	"Client/server communications protocol version mismatch"
Constant	PROTOCOL_MISMATCH
SAP Sybase Error Number	2027
SQL State	08W15
SQL Code	-88L
ODBC 2 State	08S01
ODBC 3 State	08S01
Severity Code	21 on page 2

Error 88	"Client/server communications protocol version mismatch"
Probable Cause	The connection failed because the protocol versions of the client and the server do not match. Ensure the client and server software are the same version.

Error 89	"Database server not running in multi-user mode"
Constant	ENGINE_NOT_MULTUSER
SAP Sybase Error Number	2029
SQL State	08W16
SQL Code	-89L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	17 on page 2
Probable Cause	The database server was started for bulk loading (the -b option) and cannot be used as a network server. Stop the database server, and start again without -b.

Error 90	"Argument %1 of procedure '%2' cannot be NULL"
Constant	ARGUMENT_CANNOT_BE_NULL
SAP Sybase Error Number	2267
SQL State	WP000
SQL Code	-90L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The argument number that cannot be NULL.
Parameter 2	The name of the procedure that cannot receive the NULL parameter.
Probable Cause	You passed a NULL value to a procedure expecting a scalar argument. For example, a Java procedure that has an 'int' argument cannot receive a NULL value.

Error 91	"Procedure '%1' terminated with unhandled exception '%2'"
Constant	UNHANDLED_EXTENV_EXCEPTION
SAP Sybase Error Number	2268
SQL State	WP001
SQL Code	-91L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the procedure that returned the unhandled exception.
Parameter 2	The fully qualified Java class name of the unhandled exception.
Probable Cause	A Java procedure terminated with an active exception, and this exception is reflected in SQL as an error status.

Messages 92 through 105

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 92	""%1' is not a valid class file"
Constant	BAD_CLASS_FILE
SAP Sybase Error Number	2269
SQL State	WP002
SQL Code	-92L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the invalid file.
Probable Cause	A file passed to the INSTALL JAVA statement was not a valid Java class file.

Errors and Warnings

Error 93	"Class '%1' has no public field '%2'"
Constant	FIELD_NOT_FOUND
SAP Sybase Error Number	2273
SQL State	WW013
SQL Code	-93L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the class in which the named field could not be found.
Parameter 2	The name of the field that could not be found.
Probable Cause	An expression referenced a field that either does not exist or is not public.

Error 94	"Invalid type for field reference"
Constant	INVALID_FIELD_REFERENCE
SAP Sybase Error Number	2274
SQL State	WW014
SQL Code	-94L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	An expression attempted to reference a field or a method of a non-Java value. Field references via . and >> are only valid when applied to Java objects.

Error 95	"Parse error: %1"
Constant	INVALID_PARSE_PARAMETER
SAP Sybase Error Number	2380
SQL State	08W49
SQL Code	-95L

Error 95	"Parse error: %1"
ODBC 2 State	08004
ODBC 3 State	08004
Severity Code	18 on page 2
Parameter 1	Description of the parsing error.
Probable Cause	An error occurred while parsing a connection string.

Error 96	"Database server already running"
Constant	ENGINE_ALREADY_RUNNING
SAP Sybase Error Number	2028
SQL State	08W23
SQL Code	-96L
ODBC 2 State	S1000
ODBC 3 State	HY000
Severity Code	18 on page 2
Probable Cause	The database server was not able to start because a server with the same name was already running.

Error 97	"Database page size too big: %1"
Constant	PAGE_SIZE_TOO_BIG
SAP Sybase Error Number	2031
SQL State	08W22
SQL Code	-97L
ODBC 2 State	08004
ODBC 3 State	08004
Severity Code	14 on page 2
Parameter 1	Database name.

Error 97	"Database page size too big: %1"
Probable Cause	You attempted to start a database with a page size that exceeds the maximum page size of the running server. Either restart the server and include this database name on the command line, or restart the server with the required page size.

Error 98	"Authentication violation"
Constant	AUTHENTICATION_VIOLATION
SAP Sybase Error Number	2034
SQL State	08W21
SQL Code	-98L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	16 on page 2
Probable Cause	You attempted to connect to a server that has been authenticated for exclusive use with a specific application.

Error 99	"Connections to database have been disabled"
Constant	CONNECTIONS_DISABLED
SAP Sybase Error Number	2035
SQL State	08W04
SQL Code	-99L
ODBC 2 State	08005
ODBC 3 State	08005
Severity Code	16 on page 2
Probable Cause	Connections to the network database server have been disabled. You will receive this error until connections have been enabled.

Warning 100	"Row not found"
Constant	NOTFOUND
SAP Sybase Error Number	2001

Warning 100	"Row not found"
SQL State	02000
SQL Code	100L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>16 on page 2</i>
Probable Cause	You positioned a cursor beyond the beginning or past the end of the query. There is no row at that position.

Error 100	"Database server not found"
Constant	ENGINE_NOT_RUNNING
SAP Sybase Error Number	2036
SQL State	08W01
SQL Code	-100L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	<i>16 on page 2</i>
Probable Cause	The database server is not running, or is in the process of starting up or shutting down, or the interface library is unable to find it.

Warning 101	"Value truncated"
Constant	TRUNCATED
SAP Sybase Error Number	2002
SQL State	01004
SQL Code	101L
ODBC 2 State	01004
ODBC 3 State	01004
Severity Code	<i>10 on page 2</i>
Probable Cause	You may have fetched data into a host variable or SQLDA variable not large enough to receive the value.

Error 101	"Not connected to a database"
Constant	NOT_CONNECTED
SAP Sybase Error Number	2037
SQL State	08003
SQL Code	-101L
ODBC 2 State	08003
ODBC 3 State	08003
Severity Code	<i>16</i> on page 2
Probable Cause	You are not connected to a database, or you executed the DISCONNECT statement and have not connected to a database again.

Warning 102	"Using temporary table"
Constant	TEMPORARY_TABLE
SAP Sybase Error Number	2003
SQL State	01W02
SQL Code	102L
ODBC 2 State	01000
ODBC 3 State	01000
Severity Code	<i>10</i> on page 2
Probable Cause	A temporary table has been created to satisfy the query. This warning can only occur on an OPEN statement.

Error 102	"Database server connection limit exceeded"
Constant	TOO_MANY_CONNECTIONS
SAP Sybase Error Number	2038
SQL State	08W03
SQL Code	-102L
ODBC 2 State	08004
ODBC 3 State	08004

Error 102	"Database server connection limit exceeded"
Severity Code	<i>21 on page 2</i>
Probable Cause	You exceeded the number of computers allowed to connect to the server. If you are running the network database server, the limit is specified in your license agreement. The server may be running low on cache, and as a result it cannot accept any more database connections. The personal database server is restricted to 10 connections.

Warning 103	"Invalid data conversion"
Constant	CANNOT_CONVERT
SAP Sybase Error Number	2004
SQL State	01W03
SQL Code	103L
ODBC 2 State	01S01
ODBC 3 State	01S01
Severity Code	<i>10 on page 2</i>
Probable Cause	The database could not convert a value to the required type. The value being converted was either supplied to the database on an insert, update, or as a host bind variable, or was a value retrieved from the database into a host variable or SQLDA.

Error 103	"Invalid user ID or password"
Constant	INVALID_LOGON
SAP Sybase Error Number	2039
SQL State	28000
SQL Code	-103L
ODBC 2 State	28000
ODBC 3 State	28000
Severity Code	<i>14 on page 2</i>
Probable Cause	You supplied an invalid user ID or an incorrect password.

Warning 104	"Row has been updated since last time read"
Constant	ROW_UPDATED_WARNING
SAP Sybase Error Number	2005
SQL State	01W04
SQL Code	104L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10</i> on page 2
Probable Cause	You fetched a row from a SCROLL cursor. The row was previously fetched from the same cursor, and one or more columns in the row has been updated since the previous fetch. The column(s) updated may or may not be fetched by the cursor; this warning just indicates that the row from the table has been updated. If the cursor involves more than one table, a row from one or more of the tables has been updated.

Error 104	"Invalid user ID or password on preprocessed module"
Constant	INVALID_MODULE_LOGON
SAP Sybase Error Number	2041
SQL State	28W01
SQL Code	-104L
ODBC 2 State	28000
ODBC 3 State	28000
Severity Code	<i>14</i> on page 2
Probable Cause	You specified an invalid user ID or password when a module was preprocessed.

Warning 105	"Procedure has completed"
Constant	PROCEDURE_COMPLETE
SAP Sybase Error Number	2006
SQL State	01W05

Warning 105	"Procedure has completed"
SQL Code	105L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10</i> on page 2
Probable Cause	There are no more result sets available for this procedure. An OPEN or a RESUME statement may have caused the procedure to execute to completion.

Error 105	"Database cannot be started -- %1"
Constant	UNABLE_TO_CONNECT
SAP Sybase Error Number	2042
SQL State	08001
SQL Code	-105L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	<i>11</i> on page 2
Parameter 1	Reason that database cannot be started.
Probable Cause	The specified database cannot be started. Either it does not exist, it is not a database, it is corrupt, or it is an older, unsupported format.

Messages 106 through 116

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Warning 106	"Value for column '%1' in table '%2' has changed"
Constant	COLUMN_VALUE_CHANGED
SAP Sybase Error Number	2007
SQL State	01W06
SQL Code	106L
ODBC 2 State	OK

Warning 106	"Value for column '%1' in table '%2' has changed"
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	Name of the column whose value has changed.
Parameter 2	Name of the table containing the column.
Probable Cause	A replicated UPDATE has found a value in an updated column that does not match the value when the original UPDATE was made.

Error 106	"Cannot open transaction log file -- %1"
Constant	CANNOT_OPEN_LOG
SAP Sybase Error Number	2043
SQL State	08W05
SQL Code	-106L
ODBC 2 State	08003
ODBC 3 State	08003
Severity Code	16 on page 2
Parameter 1	Reason why the transaction log file cannot be opened.
Probable Cause	The database server was unable to open the named transaction log file. The transaction log file name may include an invalid device or directory. If this is the case, you can use the Transaction Log utility (dblog) to find out where the transaction log should be and perhaps change it.

Error 107	"Error writing to transaction log file"
Constant	ERROR_WRITING_LOG
SAP Sybase Error Number	2044
SQL State	08W17
SQL Code	-107L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	17 on page 2

Error 107	"Error writing to transaction log file"
Probable Cause	The database server got an I/O error writing the transaction log file. The disk may be full or the log file name could be invalid.
Warning 107	"Language extension detected in syntax near '%1' on line %2"
Constant	SYNTAX_EXTENSION_WARNING
SAP Sybase Error Number	2238
SQL State	01W07
SQL Code	107L
ODBC 2 State	01000
ODBC 3 State	01000
Severity Code	10 on page 2
Parameter 1	The word or symbol where the syntax has been detected.
Parameter 2	Line number.
Probable Cause	The statement you are executing contains syntax that is not allowed with the current setting of the option SQL_FLAGGER_WARNING_LEVEL. Modify the offending statement or set the SQL_FLAGGER_WARNING_LEVEL option to a different value.
Error 108	"Connection not found"
Constant	CONNECTION_NOT_FOUND
SAP Sybase Error Number	2045
SQL State	08W02
SQL Code	-108L
ODBC 2 State	08003
ODBC 3 State	08003
Severity Code	16 on page 2
Probable Cause	The specified connection name on a DISCONNECT or SET CONNECTION statement is invalid.

Error 109	"There are still active database connections"
Constant	STILL_ACTIVE_CONNECTIONS
SAP Sybase Error Number	2046
SQL State	08W06
SQL Code	-109L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Probable Cause	You attempted to shut down a database that still has active connections.

Warning 109	"Null value eliminated in aggregate function"
Constant	NULL_VALUE_ELIMINATED
SAP Sybase Error Number	2241
SQL State	01003
SQL Code	109L
ODBC 2 State	01000
ODBC 3 State	01003
Severity Code	<i>10</i> on page 2
Probable Cause	The expression argument of the aggregate function evaluated to NULL for one or more rows.

Error 110	"Item '%1' already exists"
Constant	NAME_NOT_UNIQUE
SAP Sybase Error Number	2047
SQL State	52010
SQL Code	-110L
ODBC 2 State	S0001
ODBC 3 State	42S01

Error 110	"Item '%1' already exists"
Severity Code	<i>16</i> on page 2
Parameter 1	Name of the item that already exists.
Probable Cause	You attempted to create a file, table, view, column, constraint, foreign key, or publication with the same name as an existing one.

Warning 110	"Transaction log backup page only partially full"
Constant	BACKUP_PAGE_INCOMPLETE
SAP Sybase Error Number	2249
SQL State	01W10
SQL Code	110L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10</i> on page 2
Probable Cause	A DB_LOG_BACKUP_READ_WAIT was issued against the transaction log and the page returned was not full. The application should reissue the request for the same page.

Warning 111	"Statement cannot be executed"
Constant	CANNOT_EXECUTE_STMT
SAP Sybase Error Number	2008
SQL State	01W08
SQL Code	111L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10</i> on page 2
Probable Cause	You specified a SQL statement for the PREPARE...WITH EXECUTE statement that cannot be executed. If you specified an output SQLDA, it may contain a DESCRIBE of the prepared statement. It is normal for this warning to appear in the request log during the successful execution of a statement.

Error 111	"Index name '%1' not unique"
Constant	INDEX_NAME_NOT_UNIQUE
SAP Sybase Error Number	2048
SQL State	52W04
SQL Code	-111L
ODBC 2 State	S0011
ODBC 3 State	42S11
Severity Code	16 on page 2
Parameter 1	Name of the invalid index.
Probable Cause	You attempted to create an index with the same name as an existing index.

Error 112	"Table already has a primary key"
Constant	EXISTING_PRIMARY_KEY
SAP Sybase Error Number	2049
SQL State	55013
SQL Code	-112L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	You attempted to add a primary key on a table that already has a primary key defined. You must delete the current primary key before adding a new one.

Warning 112	"More information required"
Constant	MORE_INFO
SAP Sybase Error Number	2252
SQL State	01W09
SQL Code	112L
ODBC 2 State	37000

Warning 112	"More information required"
ODBC 3 State	OK
Severity Code	<i>10</i> on page 2
Probable Cause	More information is required to complete the request. This is used internally in the database interface library to process a unified login. It should not be returned to an application.

Error 113	"Column '%1' in foreign key has a different definition than primary key"
Constant	INVALID_FOREIGN_KEY_DEF
SAP Sybase Error Number	2050
SQL State	53030
SQL Code	-113L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	<i>16</i> on page 2
Parameter 1	Name of the problematic column.
Probable Cause	The data type of the column in the foreign key is not the same as the data type of the column in the primary key. Change the definition of one of the columns using ALTER TABLE.

Warning 113	"Database option '%1' for user '%2' has an invalid setting"
Constant	INVALID_OPTION_ON_CONNECT
SAP Sybase Error Number	2255
SQL State	01W11
SQL Code	113L
ODBC 2 State	01000
ODBC 3 State	01000
Severity Code	<i>10</i> on page 2
Parameter 1	Name of the database option that has the invalid value.
Parameter 2	Name of the user attempting to connect.

Warning 113	"Database option '%1' for user '%2' has an invalid setting"
Probable Cause	Upon processing a connection request for a specific user, the server processed a database option that has an invalid setting. The server will use the default option value.

Error 114	"Number of columns defined for the view does not match SELECT statement"
Constant	VIEW_DEFINITION_ERROR
SAP Sybase Error Number	2051
SQL State	53011
SQL Code	-114L
ODBC 2 State	21S02
ODBC 3 State	21S02
Severity Code	20 on page 2
Probable Cause	You attempted to create a view, but the column list specified as part of the CREATE VIEW statement does not correspond to the list of items in the view's SELECT statement.

Warning 114	"Character set conversion to '%1' cannot be performed; '%2' is used instead"
Constant	CANNOT_PERFORM_CHAR_TRANSLATION
SAP Sybase Error Number	2350
SQL State	01W12
SQL Code	114L
ODBC 2 State	01000
ODBC 3 State	01000
Severity Code	10 on page 2
Parameter 1	Name of character set the application requested.
Parameter 2	Name of character set the database will be using.

Warning 114	"Character set conversion to '%1' cannot be performed; '%2' is used instead"
Probable Cause	The server is unable to perform a character conversion from the character set the database is using to the character set the application requested.
Warning 115	"Database server cannot convert data from/to character set '%1', conversion may not be correct"
Constant	UNSUPPORTED_CHARACTER_SET_WARNING
SAP Sybase Error Number	2360
SQL State	01W13
SQL Code	115L
ODBC 2 State	01000
ODBC 3 State	01000
Severity Code	10 on page 2
Parameter 1	Name of the requested character set.
Probable Cause	The database server cannot convert character data from/to the character set requested by the application because the character set is not supported. The connection succeeds, but character conversion may not be correct for all characters.
Error 116	"Table must be empty"
Constant	TABLE_MUST_BE_EMPTY
SAP Sybase Error Number	2053
SQL State	55W02
SQL Code	-116L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You attempted to modify a table, and the database server can only perform the change if there are no rows in the table.

Warning 116	"Language '%1' is not supported, '%2' will be used"
Constant	UNSUPPORTED_LANGUAGE
SAP Sybase Error Number	2375
SQL State	01W14
SQL Code	116L
ODBC 2 State	01000
ODBC 3 State	01000
Severity Code	10 on page 2
Parameter 1	Name of the language that was requested by the client.
Parameter 2	Name of the language that the server will use to send message strings.
Probable Cause	The language that the application requested is not supported by the server to which the application is connecting. Instead, the server will send message strings in the language stated.

Messages 117 through 128

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Warning 117	"Unsupported character set '%1' and unsupported language '%2'; language used is '%3' instead"
Constant	UNSUPPORTED_CHARSET_AND_LANGUAGE
SAP Sybase Error Number	2376
SQL State	01W15
SQL Code	117L
ODBC 2 State	01000
ODBC 3 State	01000
Severity Code	10 on page 2
Parameter 1	Name of the character set that could not be supported.
Parameter 2	Name of the language that could not be supported.
Parameter 3	Name of the language that the server will use to send language strings.

Warning 117	"Unsupported character set '%1' and unsupported language '%2'; language used is '%3' instead"
Probable Cause	The character set that the application requested is not supported by the server to which the application is connecting. The language that the application requested is not supported either. Language strings will be sent in the language specified.

Error 118	"Table '%1' has no primary key"
Constant	NO_PRIMARY_KEY
SAP Sybase Error Number	2055
SQL State	55008
SQL Code	-118L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Name of the table that does not have a primary key.
Probable Cause	You attempted an operation that required the referenced table to have a primary key. Examples of these operations include adding a foreign key, or using the ON EXISTING clause of an INSERT statement, while referring to a table that does not have a primary key. You must add a primary key to the referenced table.

Warning 118	"Illegal user selectivity estimate specified"
Constant	INVALID_USER_ESTIMATE
SAP Sybase Error Number	2381
SQL State	01W16
SQL Code	118L
ODBC 2 State	01000
ODBC 3 State	01000
Severity Code	10 on page 2

Warning 118	"Illegal user selectivity estimate specified"
Probable Cause	You specified a user selectivity estimate that is either not a literal constant or is outside the range 0.0 to 100.0 (estimates are specified as percentages). The estimate has been ignored.

Error 119	"Primary key column '%1' already defined"
Constant	PRIMARY_KEY_COLUMN_DEFINED
SAP Sybase Error Number	2056
SQL State	52009
SQL Code	-119L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Name of the column that is already in the primary key.
Probable Cause	You listed the same column name twice in the definition of a primary key.

Warning 119	"Unable to open backup log '%1'"
Constant	UNABLE_TO_OPEN_BACKUP_LOG
SAP Sybase Error Number	2412
SQL State	WB011
SQL Code	119L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	Backup log file name.
Probable Cause	The server was unable to open the backup log to record the execution of a BACKUP or RESTORE statement. Check the settings of the environment variables used to locate the backup log file. The directory to contain the log must already exist.

Error 120	"User '%1' already has GRANT OPTION"
Constant	ALREADY_HAS_GRANT_PERMS
SAP Sybase Error Number	2065
SQL State	42W01
SQL Code	-120L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Name of the user that already has GRANT OPTION.
Probable Cause	You attempted to give GRANT OPTION to a user that already has it.

Warning 120	"'%1' is an unknown option"
Constant	UNKNOWN_OPTION
SAP Sybase Error Number	2384
SQL State	01W17
SQL Code	120L
ODBC 2 State	01000
ODBC 3 State	01000
Severity Code	10 on page 2
Parameter 1	The option that is unknown to the server.
Probable Cause	You attempted to set the value of an option that is not known to the server.

Error 121	"Permission denied: %1"
Constant	PERMISSION_DENIED
SAP Sybase Error Number	2066
SQL State	42501
SQL Code	-121L
ODBC 2 State	42000

Error 121	"Permission denied: %1"
ODBC 3 State	42000
Severity Code	<i>16</i> on page 2
Parameter 1	Description of the type of permission required.
Probable Cause	You do not have the required permission to perform the specified action. The message specifies the actual permission required and the object being acted upon.

Warning 121	"Cursor option values changed"
Constant	CURSOR_OPTIONS_CHANGED
SAP Sybase Error Number	2500
SQL State	01S02
SQL Code	121L
ODBC 2 State	01S02
ODBC 3 State	01S02
Severity Code	<i>10</i> on page 2
Probable Cause	The database server could not support the requested cursor option values for the associated query. Similar option settings were substituted.

Error 122	"Operation would cause a group cycle"
Constant	GROUP_CYCLE
SAP Sybase Error Number	2067
SQL State	42W02
SQL Code	-122L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	<i>16</i> on page 2
Probable Cause	You attempted to add a member to group that would result in a member belonging to itself. The membership may be direct or indirect.

Warning 122	"The result returned is non-deterministic"
Constant	NONDETERMINISTIC_RESULT
SAP Sybase Error Number	2529
SQL State	01W18
SQL Code	122L
ODBC 2 State	01000
ODBC 3 State	01000
Severity Code	<i>10</i> on page 2
Probable Cause	FIRST or TOP n are used in a SELECT statement to limit the size of a result. The statement must also have an ORDER BY if the result is to be well-defined. If it does not have an ORDER BY, then the server is free to return any subset of the result that has the requested number of rows.

Error 123	"User '%1' is not a user group"
Constant	NOT_A_GROUP
SAP Sybase Error Number	2068
SQL State	42W03
SQL Code	-123L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	<i>16</i> on page 2
Parameter 1	Name of user you thought was a group.
Probable Cause	You attempted to add a member to group, but the user ID specified as a group has not been granted GROUP permission.

Warning 124	"Invalid data conversion: NULL was inserted for column '%1' on row %2"
Constant	CANNOT_CONVERT_LOAD_TABLE
SAP Sybase Error Number	2532

Warning 124	"Invalid data conversion: NULL was inserted for column '%1' on row %2"
SQL State	01W01
SQL Code	124L
ODBC 2 State	07006
ODBC 3 State	07006
Severity Code	10 on page 2
Parameter 1	Name of the column where NULL was inserted.
Parameter 2	Row number in the data file where the invalid data conversion took place.
Probable Cause	The database could not convert a value to the required type. The value being converted was supplied to the database in a data file and inserted using LOAD TABLE. A NULL value has been inserted into the column.

Error 124	"Dropping all columns from table '%1' is not allowed"
Constant	TOO_MANY_COLUMNS_DELETED
SAP Sybase Error Number	2253
SQL State	42W44
SQL Code	-124L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Name of the table from which the columns could not be dropped.
Probable Cause	The number of columns in a table can never fall below one. Your ALTER TABLE has more drop/delete column clauses than the current number of columns in the table.

Error 125	"ALTER clause conflict"
Constant	ALTER_CLAUSE_CONFLICT
SAP Sybase Error Number	2057

Error 125	"ALTER clause conflict"
SQL State	53W01
SQL Code	-125L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	15 on page 2
Probable Cause	A primary key clause, foreign key clause, or a uniqueness clause must be the only clause of an ALTER TABLE statement.

Warning 125	"An invalid multi-byte input character was encountered when converting from %1 to %2"
Constant	ILLEGAL_MULTIBYTE_WARNING
SAP Sybase Error Number	2538
SQL State	01WC1
SQL Code	125L
ODBC 2 State	01000
ODBC 3 State	01000
Severity Code	10 on page 2
Parameter 1	The character set of the input string.
Parameter 2	The character set of the output string.
Probable Cause	While the server was performing character set conversion on an input string, an invalid multi-byte character was encountered. The illegal character was directly copied without conversion. Data following the illegal character may be misinterpreted. See on_charset_conversion_failure option.

Error 126	"Table cannot have two primary keys"
Constant	PRIMARY_KEY_TWICE
SAP Sybase Error Number	2058
SQL State	52W05

Error 126	"Table cannot have two primary keys"
SQL Code	-126L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	You specified the primary key twice in a CREATE TABLE statement.

Error 127	"Cannot alter a column in an index"
Constant	COLUMN_IN_INDEX
SAP Sybase Error Number	2059
SQL State	53W05
SQL Code	-127L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You may have attempted to delete or modify the definition of a column that is part of a primary or foreign key. You may have attempted to delete a column that has an index on it. In this case, DROP the index or key, perform the ALTER statement, and then add the index or key again.

Warning 127	"Character substitution occurred when converting from %1 to %2"
Constant	SIMPLE_SUBSTITUTION_WARNING
SAP Sybase Error Number	2542
SQL State	01WC3
SQL Code	127L
ODBC 2 State	01000
ODBC 3 State	01000
Severity Code	10 on page 2
Parameter 1	The character set of the input string.

Warning 127	"Character substitution occurred when converting from %1 to %2"
Parameter 2	The character set of the output string.
Probable Cause	While the server was performing character set conversion on an input string, some characters could not be represented in the database character set. Those characters were substituted. See on_char-set_conversion_failure option.

Error 128	"Cannot drop a user that owns tables in runtime system"
Constant	USER_OWNS_TABLES
SAP Sybase Error Number	2060
SQL State	55W03
SQL Code	-128L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	You attempted to drop a user that owns tables while running the runtime server. This operation would result in dropping tables. The runtime server cannot drop tables. Use the full server.

Messages 129 through 140

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Warning 129	"Plan may contain virtual indexes"
Constant	USING_VIRTUAL_INDEXES
SAP Sybase Error Number	2549
SQL State	01W20
SQL Code	129L
ODBC 2 State	01S01
ODBC 3 State	01S01
Severity Code	10 on page 2

Warning 129	"Plan may contain virtual indexes"
Probable Cause	Virtual indexes are currently enabled in this connection. Any plans that are generated may contain virtual indexes.

Warning 130	"A row was dropped because it could not be converted to the new schema format"
Constant	ROW_DROPPED_DURING_SCHEMA_UPGRADE
SAP Sybase Error Number	2559
SQL State	01W21
SQL Code	130L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Probable Cause	A row that was valid in the old schema is no longer valid. This could be because a column domain changed and the old value cannot be cast to the new domain. Rows are also dropped if a uniqueness or foreign key constraint cannot be satisfied.

Error 130	"Invalid statement"
Constant	INVALID_STATEMENT
SAP Sybase Error Number	2070
SQL State	07W02
SQL Code	-130L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The prepared statement is invalid. In embedded SQL, an OPEN or EXECUTE failed.

Error 131	"Syntax error near '%1' %2"
Constant	SYNTAX_ERROR

Error 131	"Syntax error near '%1' %2"
SAP Sybase Error Number	2071
SQL State	42W04
SQL Code	-131L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Parameter 1	The word or symbol where the syntax error has been detected.
Parameter 2	Line number.
Probable Cause	The database server cannot understand the statement you are trying to execute. If you used a keyword (such as DATE) for a column name, try enclosing the keyword in quotation marks ("DATE") or brackets ([DATE]).

Error 132	"SQL statement error"
Constant	STATEMENT_ERROR
SAP Sybase Error Number	2073
SQL State	26501
SQL Code	-132L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The prepared statement identifier is invalid. In embedded SQL, an OPEN or EXECUTE failed.

Warning 132	"Cannot output the histogram for string column '%1'"
Constant	CANNOT_DUMP_STRING_HISTOGRAM
SAP Sybase Error Number	2562
SQL State	01W23
SQL Code	132L

Warning 132	"Cannot output the histogram for string column '%1'"
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10 on page 2</i>
Parameter 1	Name of the column containing string data.
Probable Cause	You tried to get the histogram for a column containing strings. Histograms on string information cannot be output in a readable format; as a result, no information was retrieved. Consider using the ESTIMATE function to get information on a specific value or range in the column.

Error 133	"Invalid prepared statement type"
Constant	INVALID_STATEMENT_TYPE
SAP Sybase Error Number	2074
SQL State	07W03
SQL Code	-133L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	This is an internal error. If it can be reproduced, it should be reported to SAP Sybase.

Warning 133	"UltraLite connection was restored"
Constant	CONNECTION_RESTORED
SAP Sybase Error Number	2635
SQL State	WW040
SQL Code	133L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10 on page 2</i>
Probable Cause	The connection attempt completed successfully and the transaction was restored from a suspended state.

Error 134	"Feature '%1' not implemented"
Constant	NOT_IMPLEMENTED
SAP Sybase Error Number	2075
SQL State	0A000
SQL Code	-134L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The unimplemented feature.
Probable Cause	You attempted to carry out an operation or use a feature that is not implemented in this version of SQL Anywhere. In UltraLite, this error often occurs because you attempted to perform an unsupported operation on a LONG VARCHAR or LONG BINARY column. For example, the SUBSTRING function cannot be used with a LONG VARCHAR column. As well, an index cannot be created on a LONG column.

Warning 134	"UltraLite cursor (or result set or table) was restored"
Constant	CURSOR_RESTORED
SAP Sybase Error Number	2636
SQL State	WW041
SQL Code	134L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10</i> on page 2
Probable Cause	The cursor (or result set or table) was opened successfully and the cursor position was restored from the suspended state.

Error 135	"Language extension"
Constant	LANGUAGE_EXTENSION
SAP Sybase Error Number	2077

Error 135	"Language extension"
SQL State	0AW01
SQL Code	-135L
ODBC 2 State	37000
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You used a SQL statement that may be valid in some versions of SQL, but not in SQL Anywhere.

Error 136	"Table '%1' is in an outer join cycle"
Constant	OUTER_JOIN_CYCLE
SAP Sybase Error Number	2088
SQL State	52W14
SQL Code	-136L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Name of a table in the cycle.
Probable Cause	You specified outer joins that create a cycle of tables.

Warning 136	"The database was created"
Constant	DATABASE_CREATED
SAP Sybase Error Number	2666
SQL State	WW061
SQL Code	136L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2

Warning 136	"The database was created"
Probable Cause	The specified UltraLite database was created using the specified schema when the connection was opened.

Error 137	"Table '%1' requires a unique correlation name"
Constant	CORRELATION_NAME_NEEDED
SAP Sybase Error Number	2090
SQL State	52W15
SQL Code	-137L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Name of the table that needs a unique correlation name.
Probable Cause	You specified a join that joins a table to itself. You need to use unique correlation names to have multiple instances of a table.

Warning 137	"Row was dropped from table %1 to maintain referential integrity"
Constant	ROW_DELETED_TO_MAINTAIN_REFERENTIAL_INTEGRITY
SAP Sybase Error Number	2690
SQL State	01W24
SQL Code	137L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	The name of the table.
Probable Cause	A delete of a primary row during a download forced its foreign row(s) to also be deleted to maintain referential integrity.

Error 138	"DbSPACE '%1' not found"
Constant	DBSPACE_NOT_FOUND
SAP Sybase Error Number	2078
SQL State	52W13
SQL Code	-138L
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	<i>11</i> on page 2
Parameter 1	Name of the dbSPACE that could not be found.
Probable Cause	You tried to access a dbSPACE that the database server could not find.

Warning 138	"Publication predicates were not evaluated"
Constant	PUBLICATION_PREDICATE_IGNORED
SAP Sybase Error Number	2761
SQL State	01W25
SQL Code	138L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10</i> on page 2
Probable Cause	Publication predicates were not evaluated because UltraLite was initialized without SQL support. The table will be uploaded as if no publication predicate was specified for the table.

Error 139	"More than one table is identified as '%1'"
Constant	CORRELATION_NAME_AMBIGUOUS
SAP Sybase Error Number	2079
SQL State	52012
SQL Code	-139L
ODBC 2 State	37000

Error 139	"More than one table is identified as '%1'"
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Ambiguous correlation name.
Probable Cause	You identified two tables in the same FROM clause with the same correlation name.

Warning 139	"Option '%1' specified more than once"
Constant	DUPLICATE_OPTION
SAP Sybase Error Number	2770
SQL State	01W26
SQL Code	139L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	The name of the duplicated option.
Probable Cause	A particular option has been specified multiple times. Only the last instance of the option is used; the previous ones are ignored.

Error 140	"User ID '%1' does not exist"
Constant	UNKNOWN_USERID
SAP Sybase Error Number	2080
SQL State	08004
SQL Code	-140L
ODBC 2 State	28000
ODBC 3 State	28000
Severity Code	11 on page 2
Parameter 1	Name of the user that could not be found.
Probable Cause	You used a user ID that does not exist.

Messages 140 through 150

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Warning 140	"Encryption has not been enabled."
Constant	ENCRYPTION_NOT_ENABLED_WARNING
SAP Sybase Error Number	2817
SQL State	01005
SQL Code	140L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Probable Cause	An encryption key was provided, but encryption has not been enabled, nor is the database encrypted.

Error 141	"Table '%1' not found"
Constant	TABLE_NOT_FOUND
SAP Sybase Error Number	2081
SQL State	42W33
SQL Code	-141L
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	11 on page 2
Parameter 1	Name of the table that could not be found.
Probable Cause	You misspelled the name of a table, or you did not qualify a table name with the owner name. For example, you might have referred to "table_name" instead of "owner"."table_name".

Error 142	"Correlation name '%1' not found"
Constant	CORRELATION_NAME_NOT_FOUND
SAP Sybase Error Number	2082

Error 142	"Correlation name '%1' not found"
SQL State	52W02
SQL Code	-142L
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	16 on page 2
Parameter 1	Name of the invalid correlation name.
Probable Cause	You misspelled a correlation name, or you used a table name instead of the correlation name.

Warning 142	"UltraLite database state was restored"
Constant	DATABASE_STATE_RESTORED
SAP Sybase Error Number	2921
SQL State	WW114
SQL Code	142L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Probable Cause	The database state was restored from the temporary file. This includes suspended connections, transactions, and cursors.

Error 143	"Column '%1' not found"
Constant	COLUMN_NOT_FOUND
SAP Sybase Error Number	2481
SQL State	52003
SQL Code	-143L
ODBC 2 State	S0002
ODBC 3 State	42S22
Severity Code	16 on page 2

Error 143	"Column '%1' not found"
Parameter 1	Name of the column that could not be found.
Probable Cause	You misspelled the name of a column, or the column you are looking for is in a different table.

Warning 143	"Retrying read of corrupt page (page '%1')"
Constant	CORRUPT_PAGE_READ_RETRY
SAP Sybase Error Number	2922
SQL State	WW115
SQL Code	143L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	The page ID.
Probable Cause	UltraLite detected a corrupt database page and will attempt the read operation again. If a mirror file is enabled, it is used for the retry. If the retry fails, an error will be signaled.

Error 144	"Column '%1' found in more than one table or it is used more than once in the SELECT list -- it needs a correlation name"
Constant	COLUMN_AMBIGUOUS
SAP Sybase Error Number	2084
SQL State	52002
SQL Code	-144L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Name of the ambiguous column.

Error 144	"Column '%1' found in more than one table or it is used more than once in the SELECT list -- it needs a correlation name"
Probable Cause	You have not specified a correlation name on a column which is found in more than one of the tables referenced in a query block or which appears more than once in the SELECT list of a query block. You need to add a correlation name to the column.

Warning 144	"Mirror file requires higher checksum_level"
Constant	MIRROR_FILE_REQUIRES_CHECKSUMS
SAP Sybase Error Number	2923
SQL State	WW116
SQL Code	144L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Probable Cause	To effectively protect against media failures, page checksums must be enabled when using the mirror file. Specify the checksum_level database creation option.

Error 145	"Foreign key name '%1' not found"
Constant	FOREIGN_KEY_NAME_NOT_FOUND
SAP Sybase Error Number	2085
SQL State	52W07
SQL Code	-145L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Parameter 1	Name of the non-existing foreign key.
Probable Cause	You misspelled the name of a foreign key, or the foreign key does not exist.

Warning 145	"Two rows with the same primary key have been downloaded for table '%1'"
Constant	DUPLICATE_ROW_FOUND_IN_DOWNLOAD
SAP Sybase Error Number	2943
SQL State	01W27
SQL Code	145L
ODBC 2 State	01000
ODBC 3 State	01000
Severity Code	10 on page 2
Parameter 1	Name of the table being downloaded.
Probable Cause	The synchronization scripts are producing duplicate rows with the same primary key in your download. Generally this behavior indicates a problem with the synchronization scripts. No guarantees are made about which of the downloaded rows will be applied to the database.

Error 146	"There is no way to join '%1' to '%2'"
Constant	CANNOT_JOIN
SAP Sybase Error Number	2086
SQL State	53W04
SQL Code	-146L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Name of first table that cannot be joined.
Parameter 2	Name of second table that cannot be joined.
Probable Cause	You may have attempted a KEY JOIN between two tables and there is no foreign key on one of the tables that references the primary key of the other table. You may have attempted a NATURAL JOIN between two tables that have no common column names.

Warning 146	"Event notification queue '%1' is full, notification discarded"
Constant	EVENT_NOTIFICATION_QUEUE_FULL
SAP Sybase Error Number	2947
SQL State	WE011
SQL Code	146L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10</i> on page 2
Parameter 1	The name of the event notification queue.
Probable Cause	The named queue is full and will not receive any event notifications until notifications are read from the queue. The pending notification has been discarded.

Error 147	"There is more than one way to join '%1' to '%2'"
Constant	AMBIGUOUS_JOIN
SAP Sybase Error Number	2087
SQL State	52W08
SQL Code	-147L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	<i>16</i> on page 2
Parameter 1	Name of first table that cannot be joined.
Parameter 2	Name of second table that cannot be joined.
Probable Cause	You are attempting to KEY JOIN two tables, and there are two or more foreign keys relating the two tables. There may be two foreign keys from the first table to the second table. It may be that each table has a foreign key to the other table. You must use a correlation name for the primary key table that is the same as the role name of the desired foreign key relationship.

Warning 147	"Event notifications lost on queue '%1'"
Constant	EVENT_NOTIFICATIONS_LOST
SAP Sybase Error Number	2948
SQL State	WE012
SQL Code	147L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10</i> on page 2
Parameter 1	The name of the event notification queue.
Probable Cause	Event notifications have been lost on the named queue. This behavior occurs if there are pending notifications when the queue is destroyed. The notifications are discarded.

Error 148	"Unknown function '%1'"
Constant	UNKNOWN_FUNC
SAP Sybase Error Number	2091
SQL State	42W05
SQL Code	-148L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	<i>15</i> on page 2
Parameter 1	Function name that is not a database function.
Probable Cause	You misspelled the name of a database function (such as MAXIMUM instead of MAX) in a query definition or in a query column name.

Warning 148	"Event notification queue '%1' not found warning"
Constant	EVENT_NOTIFICATION_QUEUE_NOT_FOUND_WARN
SAP Sybase Error Number	2949
SQL State	WE013
SQL Code	148L

Warning 148	"Event notification queue '%1' not found warning"
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	The name of the event notification queue.
Probable Cause	The named event notification queue was not found. The operation will be skipped.

Error 149	"Function or column reference to '%1' must also appear in a GROUP BY"
Constant	INVALID_GROUP_SELECT
SAP Sybase Error Number	2092
SQL State	53003
SQL Code	-149L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Parameter 1	Name of the column referenced directly, or in an expression, that must be in the GROUP BY clause.
Probable Cause	You used a non-aggregate function or column reference in the SELECT list or in a nested query block that does not appear in the GROUP BY clause. In a query using GROUP BY, SELECT list items that are not aggregate functions must also appear in the GROUP BY clause. If the SELECT list item is a column reference or an alias, you may add the column name or alias to the GROUP BY clause. If the SELECT list item is a scalar function, ensure that the function's arguments in the GROUP BY clause match exactly with those in the SELECT list. You may be able to use the MAX function (or another aggregate function) on the column name instead of adding the column to the GROUP BY clause.

Warning 149	"Automatic database upgrade applied"
Constant	DATABASE_UPGRADE_WARNING
SAP Sybase Error Number	2972

Warning 149	"Automatic database upgrade applied"
SQL State	WW234
SQL Code	149L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10</i> on page 2
Probable Cause	The database is from an older version of the software. An automatic database upgrade occurs during startup. Subsequently the database can no longer be opened with the older version of the software.

Error 150	"Invalid use of an aggregate function"
Constant	AGGREGATES_NOT_ALLOWED
SAP Sybase Error Number	2093
SQL State	42W06
SQL Code	-150L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	<i>15</i> on page 2
Probable Cause	You attempted to use an aggregate function inappropriately. For example, a SELECT statement cannot contain an aggregate function within a predicate in the WHERE clause unless the aggregate function constitutes an outer reference. Other invalid uses include specifying an aggregate function in the SET clause of an UPDATE statement, or using an aggregate function in a CHECK constraint.

Warning 150	"Database contains no tables to synchronize"
Constant	NO_TABLES_TO_SYNCHRONIZE
SAP Sybase Error Number	3173
SQL State	01W28
SQL Code	150L
ODBC 2 State	OK

Warning 150	"Database contains no tables to synchronize"
ODBC 3 State	OK
Severity Code	<i>10 on page 2</i>
Probable Cause	The database has no tables to synchronize. No attempt was made to contact the MobiLink server.

Messages 151 through 180

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 151	"Subquery allowed only one SELECT list item"
Constant	SUBQUERY_SELECT_LIST
SAP Sybase Error Number	2094
SQL State	53023
SQL Code	-151L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	<i>15 on page 2</i>
Probable Cause	You entered a subquery that has more than one column in the SELECT list. Change the SELECT list to have only one column.

Warning 151	"UltraLite performed database recovery on startup"
Constant	DATABASE_RECOVERED
SAP Sybase Error Number	3357
SQL State	WW247
SQL Code	151L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10 on page 2</i>

Warning 151	"UltraLite performed database recovery on startup"
Probable Cause	The database file was not shut down cleanly. Any uncommitted rows have been rolled back. This indicates that not all connections were closed when the application terminated.

Error 152	"Invalid ORDER BY specification"
Constant	INVALID_ORDER
SAP Sybase Error Number	2095
SQL State	53005
SQL Code	-152L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Probable Cause	Either you used an integer in an ORDER BY list and the integer is larger than the number of columns in the SELECT list, or you specified an ORDER BY expression that is semantically invalid. For example, for UNION, EXCEPT, and INTERSECT queries you can only use integers or column names of the first SELECT query block to specify an ordering of the result.

Error 153	"Select lists in UNION, INTERSECT, or EXCEPT do not match in length"
Constant	INVALID_UNION
SAP Sybase Error Number	2096
SQL State	53026
SQL Code	-153L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	You specified a UNION, INTERSECT, or EXCEPT, but the SELECT statements involved in the operation do not have the same number of columns in the SELECT list.

Error 154	"Wrong number of parameters to function '%1'"
Constant	WRONG_PARAMETER_COUNT
SAP Sybase Error Number	2100
SQL State	37505
SQL Code	-154L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Parameter 1	Name of the function.
Probable Cause	You supplied an incorrect number of parameters to a database function.

Error 155	"Invalid host variable"
Constant	VARIABLE_INVALID
SAP Sybase Error Number	2102
SQL State	42W07
SQL Code	-155L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	17 on page 2
Probable Cause	You supplied an invalid host variable to the database using the C language interface. You may have supplied the variable as a host variable or through a SQLDA.

Error 156	"Invalid expression near '%1'"
Constant	EXPRESSION_ERROR
SAP Sybase Error Number	2103
SQL State	42W08
SQL Code	-156L
ODBC 2 State	37000

Error 156	"Invalid expression near '%1'"
ODBC 3 State	42000
Severity Code	<i>16</i> on page 2
Parameter 1	The invalid expression.
Probable Cause	You supplied an expression that the database server cannot understand. For example, you may have tried to add two dates.

Error 157	"Cannot convert %1 to a %2"
Constant	CONVERSION_ERROR
SAP Sybase Error Number	2104
SQL State	53018
SQL Code	-157L
ODBC 2 State	07006
ODBC 3 State	07006
Severity Code	<i>16</i> on page 2
Parameter 1	The value that could not be converted.
Parameter 2	The name of the type for the conversion.
Probable Cause	An error occurred while trying to convert a value to another data type.

Error 158	"Value %1 out of range for destination"
Constant	OVERFLOW_ERROR
SAP Sybase Error Number	2105
SQL State	22003
SQL Code	-158L
ODBC 2 State	22003
ODBC 3 State	22003
Severity Code	<i>16</i> on page 2
Parameter 1	The value that caused the overflow.

Error 158	"Value %1 out of range for destination"
Probable Cause	You supplied to or fetched from the database a value that is out of range for the destination column or host variable. For example, the value 10 may have been supplied for a DECIMAL(3,2) field.

Error 159	"Invalid column number"
Constant	INVALID_COLUMN_NUMBER
SAP Sybase Error Number	2106
SQL State	42W13
SQL Code	-159L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	15 on page 2
Probable Cause	You gave an invalid column number, or the column you are looking for is in a different table.

Error 160	"Can only describe a SELECT statement"
Constant	DESCRIBE_NONSELECT
SAP Sybase Error Number	2107
SQL State	07005
SQL Code	-160L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	16 on page 2
Probable Cause	In the C language interface, you attempted to describe the SELECT list of a statement other than a SELECT statement. In UltraLite this error can result from trying to retrieve the schema of any statement other than a SELECT.

Error 161	"Invalid type on DESCRIBE statement"
Constant	INVALID_DESCRIBE_TYPE

Error 161	"Invalid type on DESCRIBE statement"
SAP Sybase Error Number	2108
SQL State	07W01
SQL Code	-161L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	16 on page 2
Probable Cause	A Java type specified on a DESCRIBE statement has no corresponding SQL type.

Error 162	"Cannot convert %1 to a %2. The bad value was supplied for column '%3' on row %4 of the data file"
Constant	CONVERSION_ERROR_LOAD_TABLE
SAP Sybase Error Number	2533
SQL State	53017
SQL Code	-162L
ODBC 2 State	07006
ODBC 3 State	07006
Severity Code	16 on page 2
Parameter 1	Value that could not be converted.
Parameter 2	Destination data type.
Parameter 3	Name of the column where the value was to be inserted.
Parameter 4	Line number of the data file where the invalid data occurred.
Probable Cause	The data file supplied to LOAD TABLE contains a value that cannot be converted to the required data type.

Error 163	"Derived table '%1' has no name for column %2"
Constant	NO_COLUMN_NAME
SAP Sybase Error Number	2302
SQL State	52004

Error 163	"Derived table '%1' has no name for column %2"
SQL Code	-163L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Name of the derived table.
Parameter 2	Number of the column for which there is no name.
Probable Cause	The specified column of the derived table has no column name. Use a SELECT list alias in the query specification or use a derived columns specifier.

Error 164	"Namespace heap exhausted at internal function: %1"
Constant	NAMESPACE_HEAP_EXHAUSTED
SAP Sybase Error Number	2310
SQL State	WP007
SQL Code	-164L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The internal function is for debugging purposes.
Probable Cause	The amount of space allocated for the Java Namespace is insufficient to continue loading Java classes. Increase the size by using: SET OPTION PUBLIC.java_namespace_size = nnnnnnnn.

Error 165	"Java VM heap exhausted at internal function: %1"
Constant	JAVA_VM_HEAP_EXHAUSTED
SAP Sybase Error Number	2311
SQL State	WP008
SQL Code	-165L
ODBC 2 State	ERROR

Error 165	"Java VM heap exhausted at internal function: %1"
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The internal function is for debugging purposes.
Probable Cause	The amount of space allocated for the Java VM is insufficient to continue allocating new objects. Increase the size by using: SET OPTION PUBLIC.java_heap_size = nnnnnnnn.

Error 170	"Cursor has not been declared"
Constant	CURSOR_NOT_DECLARED
SAP Sybase Error Number	2109
SQL State	24W01
SQL Code	-170L
ODBC 2 State	24000
ODBC 3 State	24000
Severity Code	<i>16</i> on page 2
Probable Cause	You attempted to OPEN a cursor that has not been declared.

Error 171	"Error opening cursor"
Constant	OPEN_CURSOR_ERROR
SAP Sybase Error Number	2110
SQL State	07003
SQL Code	-171L
ODBC 2 State	24000
ODBC 3 State	24000
Severity Code	<i>15</i> on page 2
Probable Cause	You attempted to open a cursor on a statement that is not SELECT, CALL or EXEC.

Error 172	"Cursor already open"
Constant	CURSOR_ALREADY_OPEN
SAP Sybase Error Number	2111
SQL State	24502
SQL Code	-172L
ODBC 2 State	24000
ODBC 3 State	24000
Severity Code	16 on page 2
Probable Cause	You attempted to OPEN a cursor that is already open.

Error 180	"Cursor not open"
Constant	CURSOR_NOT_OPEN
SAP Sybase Error Number	2112
SQL State	24501
SQL Code	-180L
ODBC 2 State	34000
ODBC 3 State	34000
Severity Code	16 on page 2
Probable Cause	You attempted to use a cursor that has not been opened.

Messages 181 through 200

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 181	"No indicator variable provided for NULL result"
Constant	NO_INDICATOR
SAP Sybase Error Number	2113
SQL State	22002
SQL Code	-181L
ODBC 2 State	ERROR

Error 181	"No indicator variable provided for NULL result"
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Probable Cause	You tried to retrieve a value from the database that was NULL, but you did not provide an indicator variable for that value.

Error 182	"Not enough fields allocated in SQLDA"
Constant	SQLDA_TOO_SMALL
SAP Sybase Error Number	2114
SQL State	07002
SQL Code	-182L
ODBC 2 State	07001
ODBC 3 State	07002
Severity Code	<i>16</i> on page 2
Probable Cause	There are not enough fields in the SQLDA to retrieve all of the values requested.

Error 183	"Cannot find index named '%1'"
Constant	INDEX_NOT_FOUND
SAP Sybase Error Number	2063
SQL State	52W03
SQL Code	-183L
ODBC 2 State	S0012
ODBC 3 State	42S12
Severity Code	<i>16</i> on page 2
Parameter 1	Name of the index that cannot be found.
Probable Cause	You attempted to perform an operation using an index that does not exist. Check for spelling errors. Check whether the index name must be qualified with a user ID.

Error 184	"Column '%1' in table '%2' cannot be NULL. The invalid data was supplied to LOAD TABLE in a data file on line %3"
Constant	COLUMN_CANNOT_BE_NULL_LOAD_TABLE
SAP Sybase Error Number	2531
SQL State	23501
SQL Code	-184L
ODBC 2 State	23000
ODBC 3 State	23000
Severity Code	16 on page 2
Parameter 1	Name of the column that cannot be NULL.
Parameter 2	Name of the table containing the column.
Parameter 3	The line number of the data file containing the invalid data.
Probable Cause	You either have not supplied a value where a value is required or a data conversion was necessary that resulted in a NULL value. The column definition prohibits NULL values or the column is part of a NOT NULL foreign key.

Error 185	"SELECT returns more than one row"
Constant	TOO_MANY_RECORDS
SAP Sybase Error Number	2116
SQL State	21000
SQL Code	-185L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You tried to use a SELECT statement without a cursor, but the statement cursor returns more than one row. Only a single row SELECT statement can be used in this context.

Error 186	"Subquery cannot return more than one row"
Constant	SUBQUERY_RESULT_NOT_UNIQUE
SAP Sybase Error Number	2117
SQL State	21W01
SQL Code	-186L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	You used a subquery that returns more than one row, in a context where only a single row can be used. If the subquery is in the WHERE clause, you might be able to use the IN keyword.

Error 187	"Illegal cursor operation attempt"
Constant	CURSOROP_NOT_ALLOWED
SAP Sybase Error Number	2118
SQL State	09W02
SQL Code	-187L
ODBC 2 State	07005
ODBC 3 State	07005
Severity Code	16 on page 2
Probable Cause	You attempted an illegal cursor operation. For example, you may be attempting to OPEN a cursor for a statement that is neither a SELECT nor a BATCH.

Error 188	"Not enough values for host variables"
Constant	NOT_ENOUGH_HOST_VARS
SAP Sybase Error Number	2119
SQL State	07001
SQL Code	-188L
ODBC 2 State	07002

Error 188	"Not enough values for host variables"
ODBC 3 State	07002
Severity Code	16 on page 2
Probable Cause	You have not provided enough host variables for either the number of bind variables, or the statement, or the number of SELECT list items.

Error 189	"Unable to find in index '%1' for table '%2'"
Constant	NOT_FOUND_IN_INDEX
SAP Sybase Error Number	2120
SQL State	WI005
SQL Code	-189L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	11 on page 2
Parameter 1	Name of invalid index.
Parameter 2	Name of table containing the invalid index.
Probable Cause	This is an internal error. If it can be reproduced, it should be reported to SAP Sybase. You should be able to work around the error by dropping and recreating the index.

Error 190	"Cannot update an expression"
Constant	NON_UPDATEABLE_COLUMN
SAP Sybase Error Number	2121
SQL State	53W02
SQL Code	-190L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	14 on page 2
Probable Cause	You tried to update a column in a query that is a database expression rather than a column in a table.

Error 191	"Cannot modify column '%1' in table '%2'"
Constant	CANNOT_MODIFY
SAP Sybase Error Number	2122
SQL State	42W32
SQL Code	-191L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	14 on page 2
Parameter 1	Name of the column that cannot be changed.
Parameter 2	Name of the table containing the column.
Probable Cause	You may have tried to modify a column that you do not have permission to modify. You may have tried to modify a column defined as an expression (such as column1+column2) in a view.

Error 192	"Update operation attempted on non-updatable query"
Constant	NON_UPDATEABLE_VIEW
SAP Sybase Error Number	2123
SQL State	42W31
SQL Code	-192L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	15 on page 2
Probable Cause	You attempted an insert, update, or delete operation on a query that is implicitly read-only. Queries that contain DISTINCT, GROUP BY, HAVING, EXCEPT, INTERSECT or UNION, or that contain aggregate functions, or that involve a join, are implicitly read-only. If the query references a view then the view may be non-updatable.

Error 193	"Primary key for table '%1' is not unique: Primary key value ('%2')"
Constant	PRIMARY_KEY_NOT_UNIQUE

Error 193	"Primary key for table '%1' is not unique: Primary key value ('%2')"
SAP Sybase Error Number	2124
SQL State	23W01
SQL Code	-193L
ODBC 2 State	23000
ODBC 3 State	23000
Severity Code	14 on page 2
Parameter 1	Name of the table where the problem was detected.
Parameter 2	Duplicate primary key values that caused the error.
Probable Cause	You attempted to add a new row to a table, but the new row has the same primary key as an existing row. The database has not added the incorrect row to the database. For example, you might have added a student with student number 86004 and there is already a row for a student with that number.

Error 194	"No primary key value for foreign key '%1' in table '%2'"
Constant	INVALID_FOREIGN_KEY
SAP Sybase Error Number	2125
SQL State	23503
SQL Code	-194L
ODBC 2 State	23000
ODBC 3 State	23000
Severity Code	16 on page 2
Parameter 1	Name of the foreign key.
Parameter 2	Name of the table with the foreign key.
Probable Cause	You attempted to insert or update a row that has a foreign key for another table. The value for the foreign key is not NULL and there is not a corresponding value in the primary key.

Error 195	"Column '%1' in table '%2' cannot be NULL"
Constant	COLUMN_CANNOT_BE_NULL

Error 195	"Column '%1' in table '%2' cannot be NULL "
SAP Sybase Error Number	2126
SQL State	23502
SQL Code	-195L
ODBC 2 State	23000
ODBC 3 State	23000
Severity Code	16 on page 2
Parameter 1	Name of the column that cannot be NULL.
Parameter 2	Name of the table containing the column.
Probable Cause	You have not supplied a value where a value is required. The column definition prohibits NULL values or the column is part of a NOT NULL foreign key.

Error 196	"Index '%1' for table '%2' would not be unique"
Constant	INDEX_NOT_UNIQUE
SAP Sybase Error Number	2127
SQL State	23505
SQL Code	-196L
ODBC 2 State	23000
ODBC 3 State	23000
Severity Code	16 on page 2
Parameter 1	Name of the index that would not be unique.
Parameter 2	Name of the table that contains the index.
Probable Cause	You attempted to insert or update a row that has the same value as another row in some column, and there is a constraint that does not allow two rows to have the same value in that column.

Error 197	"No current row of cursor"
Constant	NO_CURRENT_ROW

Error 197	"No current row of cursor"
SAP Sybase Error Number	2128
SQL State	24503
SQL Code	-197L
ODBC 2 State	24000
ODBC 3 State	24000
Severity Code	16 on page 2
Probable Cause	You attempted to perform an operation on the current row of a cursor, but the cursor is not positioned on a row. The cursor is before the first row of the cursor, after the last row, or is on a row that has since been deleted.

Error 198	"Primary key for row in table '%1' is referenced by foreign key '%2' in table '%3'"
Constant	PRIMARY_KEY_VALUE_REF
SAP Sybase Error Number	2129
SQL State	23W05
SQL Code	-198L
ODBC 2 State	23000
ODBC 3 State	23000
Severity Code	16 on page 2
Parameter 1	The name of the table containing the row being modified.
Parameter 2	The name of the foreign index (or role) of the referencing table.
Parameter 3	The name of the foreign table referencing the primary row.
Probable Cause	You attempted to delete or modify a row whose primary key value is referenced elsewhere in the database.

Error 199	"INSERT/DELETE on cursor can modify only one table"
Constant	ONLY_ONE_TABLE

Error 199	"INSERT/DELETE on cursor can modify only one table"
SAP Sybase Error Number	2130
SQL State	09W04
SQL Code	-199L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Probable Cause	You attempted to insert into a cursor and have specified values for more than one table, or you attempted to delete from a cursor that involves a join. Insert into one table at a time. For DELETE, use the FROM clause to specify the table you want to delete from.

Warning 200	"Warning: %1"
Constant	WARNING
SAP Sybase Error Number	2009
SQL State	01000
SQL Code	200L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	Warning message.
Probable Cause	A warning has occurred. The message indicates the condition that caused the warning.

Messages 200 through 218

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 200	"Invalid option '%1' -- no PUBLIC setting exists"
Constant	INVALID_OPTION
SAP Sybase Error Number	2167

Error 200	"Invalid option '%1' -- no PUBLIC setting exists"
SQL State	42W16
SQL Code	-200L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Parameter 1	Name of the invalid option.
Probable Cause	You may have misspelled the name of an option in the SET OPTION statement. You can only define an option for a user if the database administrator has supplied a PUBLIC value for that option.

Error 201	"Invalid setting for option '%1'"
Constant	INVALID_OPTION_SETTING
SAP Sybase Error Number	2168
SQL State	42W17
SQL Code	-201L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Name of the invalid option.
Probable Cause	You supplied an invalid value for an option in the SET statement. Some options allow only numeric values, while other options allow only the values On and Off.

Warning 201	"The ICU collation '%1' has defaulted to another collation"
Constant	COLLATION_DEFAULT_WARNING
SAP Sybase Error Number	2788
SQL State	01WC4
SQL Code	201L
ODBC 2 State	01000

Warning 201	"The ICU collation '%1' has defaulted to another collation"
ODBC 3 State	01000
Severity Code	10 on page 2
Parameter 1	The ICU collation specifier.
Probable Cause	The specified ICU collation is not available. Another collation was substituted, which may or may not produce suitable results. Due to the structure of ICU, the collation that was used is not known, but was the best alternative to the specified collation. If this database is used on another platform, a different collation may be chosen and the operation may generate different results.

Error 202	"Only PUBLIC settings are allowed for option '%1'"
Constant	NOT_PUBLIC_ID
SAP Sybase Error Number	2251
SQL State	42W43
SQL Code	-202L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Name of the option.
Probable Cause	The option specified in the SET OPTION statement is PUBLIC only. You cannot define this option for any other user.

Error 203	"Cannot set a temporary option for user '%1'"
Constant	TEMPORARY_NOT_ALLOWED
SAP Sybase Error Number	2254
SQL State	42W45
SQL Code	-203L
ODBC 2 State	42000
ODBC 3 State	42000

Error 203	"Cannot set a temporary option for user '%1'"
Severity Code	<i>16</i> on page 2
Parameter 1	User ID whose option was to be changed.
Probable Cause	TEMPORARY options are set on a connection basis, and only for specific options known to the database server. To change an option for another user, do not specify TEMPORARY in the SET OPTION statement.

Error 204	"You do not have '%1' system privilege or authority to set the option '%2'"
Constant	OPTION_REQUIRES_DBA
SAP Sybase Error Number	2256
SQL State	42W46
SQL Code	-204L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	<i>14</i> on page 2
Parameter 1	Name of the system privilege or authority required to set the option.
Parameter 2	Name of the option that could not be set.
Probable Cause	The option specified in the SET OPTION statement can only be set by a user with DBA authority or by a user with SET ANY SYSTEM OPTION / SET ANY SECURITY OPTION / SET ANY PUBLIC OPTION depending on the option.

Error 205	"Integrated logins are not permitted"
Constant	INVALID_STANDARD_LOGON
SAP Sybase Error Number	2257
SQL State	28W02
SQL Code	-205L
ODBC 2 State	28000
ODBC 3 State	28000

Error 205	"Integrated logins are not permitted"
Severity Code	<i>16 on page 2</i>
Probable Cause	The login_mode database option is set to Standard, and you attempted an integrated login. Change the option setting or supply an explicit user ID.

Error 206	"Integrated logins are required, standard logins are not permitted"
Constant	INVALID_INTEGRATED_LOGON
SAP Sybase Error Number	2258
SQL State	28W03
SQL Code	-206L
ODBC 2 State	28000
ODBC 3 State	28000
Severity Code	<i>16 on page 2</i>
Probable Cause	The login_mode database option is set to Integrated, and you attempted a standard login. Change the option setting or use an integrated login.

Error 207	"Wrong number of values for INSERT"
Constant	WRONG_NUM_OF_INSERT_COLS
SAP Sybase Error Number	2133
SQL State	53002
SQL Code	-207L
ODBC 2 State	21S01
ODBC 3 State	21S01
Severity Code	<i>16 on page 2</i>
Probable Cause	The number of values you are trying to insert does not match the number of columns specified in the INSERT statement, or the number of columns in the table if no columns are specified.

Error 208	"Row has changed since last read -- operation canceled"
Constant	ROW_UPDATED_SINCE_READ
SAP Sybase Error Number	2132
SQL State	22W02
SQL Code	-208L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You attempted an UPDATE (positioned) or DELETE (positioned) operation on a cursor declared as a SCROLL cursor, and the row you are changing has been updated since you read it. This error prevents the lost update problem.

Error 209	"Constraint '%1' violated: Invalid value for column '%2' in table '%3'"
Constant	INVALID_COLUMN_VALUE
SAP Sybase Error Number	2131
SQL State	23506
SQL Code	-209L
ODBC 2 State	42000
ODBC 3 State	23000
Severity Code	16 on page 2
Parameter 1	Name of the constraint (if defined) that was violated by an invalid value.
Parameter 2	Name of the column that was assigned an invalid value.
Parameter 3	Name of the table containing the column.
Probable Cause	You attempted an insert or update that violates a CHECK constraint. A CHECK constraint is violated if it evaluates to FALSE; it is deemed to hold if the condition evaluates to TRUE or UNKNOWN.

Error 210	"User '%1' has the row in '%2' locked"
Constant	LOCKED
SAP Sybase Error Number	2169
SQL State	42W18
SQL Code	-210L
ODBC 2 State	40001
ODBC 3 State	40001
Severity Code	21 on page 2
Parameter 1	Name of another user.
Parameter 2	Table that generates the error.
Probable Cause	The operation failed because another connection holds a lock on the same object you are attempting to modify. With INSERT, UPDATE, DELETE, SELECT, or MERGE statements this error is typically caused by attempting to read or write a row that is locked by another user, while the database option 'blocking' is set to Off. With data definition statements, including CREATE, DROP, GRANT, REVOKE, REFRESH, or ALTER, this error can be generated when the connection executing the DDL statement is unable to obtain an exclusive lock on the object to be modified (table, view, materialized view, or index) so that the operation can proceed.

Error 211	"Not allowed while '%1' is using the database"
Constant	MUST_BE_ONLY_CONNECTION
SAP Sybase Error Number	2170
SQL State	42W19
SQL Code	-211L
ODBC 2 State	40001
ODBC 3 State	40001
Severity Code	16 on page 2
Parameter 1	Name of the connection that is using the database.
Probable Cause	You attempted a data definition language operation that cannot be completed while another user is connected.

Error 212	"CHECKPOINT statement requires a rollback log"
Constant	CHECKPOINT_REQUIRES_UNDO
SAP Sybase Error Number	2171
SQL State	42W20
SQL Code	-212L
ODBC 2 State	40001
ODBC 3 State	40001
Severity Code	16 on page 2
Probable Cause	You cannot use a CHECKPOINT statement when the database server is running in bulk mode without a rollback log.

Error 213	"Savepoints require a rollback log"
Constant	SAVEPOINTS_REQUIRE_UNDO
SAP Sybase Error Number	2177
SQL State	3BW01
SQL Code	-213L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You cannot use savepoints when the database server is running in bulk mode without a rollback log.

Error 214	"Table in use"
Constant	TABLE_IN_USE
SAP Sybase Error Number	2172
SQL State	42W21
SQL Code	-214L
ODBC 2 State	40001
ODBC 3 State	40001

Error 214	"Table in use"
Severity Code	<i>16 on page 2</i>
Probable Cause	You attempted to ALTER or DROP a table that is being used by other active users of the database.

Error 215	"Procedure in use by '%1'"
Constant	PROCEDURE_IN_USE
SAP Sybase Error Number	2173
SQL State	42W23
SQL Code	-215L
ODBC 2 State	40001
ODBC 3 State	40001
Severity Code	<i>16 on page 2</i>
Parameter 1	Name of user.
Probable Cause	You attempted to DROP a procedure that is being used by other active users of the database.

Error 216	"The option '%1' can only be set as a temporary option"
Constant	OPTION_IS_TEMP_ONLY
SAP Sybase Error Number	2351
SQL State	42W52
SQL Code	-216L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	<i>14 on page 2</i>
Parameter 1	Name of the option that could not be set.
Probable Cause	The option specified in the SET OPTION statement can only be set as a temporary option.

Error 217	"The option '%1' cannot be set from within a procedure"
Constant	OPTION_IN_PROCEDURE
SAP Sybase Error Number	2352
SQL State	42W53
SQL Code	-217L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	14 on page 2
Parameter 1	Name of the option that could not be set.
Probable Cause	The option specified in the SET OPTION statement cannot be set from within a procedure.

Error 218	"Authentication failed"
Constant	AUTHENTICATION_FAILED
SAP Sybase Error Number	2353
SQL State	08W48
SQL Code	-218L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	16 on page 2
Probable Cause	You set the database_authentication or connection_authentication option incorrectly.

Messages 220 through 262

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 220	"Savepoint '%1' not found"
Constant	SAVEPOINT_NOTFOUND
SAP Sybase Error Number	2174
SQL State	3B001

Error 220	"Savepoint '%1' not found"
SQL Code	-220L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of savepoint.
Probable Cause	You attempted to rollback to a savepoint that does not exist.

Error 221	"ROLLBACK TO SAVEPOINT not allowed"
Constant	ROLLBACK_NOT_ALLOWED
SAP Sybase Error Number	2175
SQL State	3B002
SQL Code	-221L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You attempted a ROLLBACK TO SAVEPOINT within an atomic operation to a savepoint established before the atomic operation.

Error 222	"Result set not allowed from within an atomic compound statement"
Constant	RESULT_NOT_ALLOWED
SAP Sybase Error Number	2176
SQL State	3BW02
SQL Code	-222L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You used a SELECT statement with no INTO clause or a RESULT CURSOR statement within an atomic compound statement.

Error 230	"sqlpp/dblib version mismatch"
Constant	PP_DBLIB_MISMATCH
SAP Sybase Error Number	2178
SQL State	08W18
SQL Code	-230L
ODBC 2 State	08801
ODBC 3 State	08001
Severity Code	21 on page 2
Probable Cause	Your executable has Embedded SQL source files that were preprocessed with a version of sqlpp that does not match the database interface library.

Error 231	"Client/database server version mismatch"
Constant	DBLIB_ENGINE_MISMATCH
SAP Sybase Error Number	2179
SQL State	08W19
SQL Code	-231L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	21 on page 2
Probable Cause	Your executable uses a database interface library that does not match the version number of the database server.

Error 240	"Unknown backup operation"
Constant	UNKNOWN_BACKUP_OPERATION
SAP Sybase Error Number	2181
SQL State	WB001
SQL Code	-240L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 240	"Unknown backup operation"
Severity Code	20 on page 2
Probable Cause	You specified an invalid backup statement operation in a call to db_backup.

Error 241	"Database backup not started"
Constant	BACKUP_NOT_STARTED
SAP Sybase Error Number	2182
SQL State	WB002
SQL Code	-241L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	20 on page 2
Probable Cause	A database backup could not be started. Either a backup is already running, or you do not have the required system privileges or authority (BACKUP, DBA or REMOTE DBA).

Error 242	"Incomplete transactions prevent transaction log renaming"
Constant	BACKUP_CANNOT_RENAME_LOG_YET
SAP Sybase Error Number	2183
SQL State	WB003
SQL Code	-242L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	20 on page 2
Probable Cause	The last page in the transaction log was read by a call to db_backup. One or more currently active connections have partially completed transactions, preventing the transaction log file from being renamed. Reissue the db_backup call.

Error 243	"Unable to delete database file"
Constant	BACKUP_UNABLE_TO_DELETE_FILE
SAP Sybase Error Number	2184
SQL State	WB004
SQL Code	-243L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You attempted to delete a database file, but it could not be deleted. The file name should not be the same as any database file that is currently in use.

Error 244	"Transaction log was truncated"
Constant	LOG_TRUNCATED
SAP Sybase Error Number	2185
SQL State	WB005
SQL Code	-244L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	While an operation was occurring on the transaction log, the transaction log was truncated by another operation.

Error 245	"Integrated login failed"
Constant	INTEGRATED_LOGON_FAILED
SAP Sybase Error Number	2259
SQL State	28W04
SQL Code	-245L
ODBC 2 State	28000
ODBC 3 State	28000

Error 245	"Integrated login failed"
Severity Code	<i>16 on page 2</i>
Probable Cause	The integrated login failed. You may not have a system account on the server computer.

Error 246	"Integrated logins are not supported for this database"
Constant	INTEGRATED_LOGON_UNSUPPORTED
SAP Sybase Error Number	2262
SQL State	28W05
SQL Code	-246L
ODBC 2 State	28000
ODBC 3 State	28000
Severity Code	<i>16 on page 2</i>
Probable Cause	The current database is an older database and does not have the information to map integrated login IDs to database user IDs. You must upgrade your database to use integrated logins.

Error 247	"The integrated login ID guest can only be mapped to the guest database user ID"
Constant	INTEGRATED_LOGON_GUESTMAP
SAP Sybase Error Number	2263
SQL State	28W06
SQL Code	-247L
ODBC 2 State	28000
ODBC 3 State	28000
Severity Code	<i>16 on page 2</i>
Probable Cause	You attempted to map the guest login ID to something other than guest.

Error 248	"Cannot map a login ID to the sys or public user ID"
Constant	LOGON_SYSMAP

Error 248	"Cannot map a login ID to the sys or public user ID"
SAP Sybase Error Number	2264
SQL State	28W07
SQL Code	-248L
ODBC 2 State	28000
ODBC 3 State	28000
Severity Code	16 on page 2
Probable Cause	You attempted to map a login ID to either SYS or PUBLIC.

Error 249	"The login ID '%1' is already mapped to user ID '%2'"
Constant	LOGON_MAPPED
SAP Sybase Error Number	2265
SQL State	28W08
SQL Code	-249L
ODBC 2 State	28000
ODBC 3 State	28000
Severity Code	16 on page 2
Parameter 1	Name of the login ID that is already mapped.
Parameter 2	Name of the user that the login ID is already mapped to.
Probable Cause	You attempted to map a login ID twice.

Error 250	"Identifier '%1' too long"
Constant	IDENTIFIER_TOO_LONG
SAP Sybase Error Number	2061
SQL State	54003
SQL Code	-250L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2

Error 250	"Identifier '%1' too long"
Parameter 1	The identifier that is too long.
Probable Cause	An identifier that was specified is longer than 128 bytes.

Error 251	"Foreign key '%1' for table '%2' duplicates an existing foreign key"
Constant	DUPLICATE_FOREIGN_KEY
SAP Sybase Error Number	2062
SQL State	52W06
SQL Code	-251L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	<i>16 on page 2</i>
Parameter 1	The role name of the new foreign key.
Parameter 2	The table containing the foreign key.
Probable Cause	You attempted to define a foreign key that already exists.

Error 260	"Variable '%1' not found"
Constant	VARIABLE_NOT_FOUND
SAP Sybase Error Number	2139
SQL State	42W14
SQL Code	-260L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	<i>15 on page 2</i>
Parameter 1	Name of the variable that could not be found.
Probable Cause	You attempted to DROP or SET the value of a SQL variable that was not created or was previously dropped.

Error 261	"There is already a variable named '%1'"
Constant	VARIABLE_EXISTS
SAP Sybase Error Number	2140
SQL State	42W15
SQL Code	-261L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Parameter 1	Name of the variable that already exists.
Probable Cause	You attempted to create a variable with the name of another variable that already exists.

Error 262	"Label '%1' not found"
Constant	LABEL_NOT_FOUND
SAP Sybase Error Number	2141
SQL State	42W24
SQL Code	-262L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Parameter 1	Name of the label that could not be found.
Probable Cause	You reference a label in a LEAVE statement, but the label could not be found.

263 - 785

Messages 263 through 288

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 263	"Invalid absolute or relative offset in FETCH"
Constant	INVALID_FETCH_POSITION
SAP Sybase Error Number	2142
SQL State	42W25
SQL Code	-263L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	You specified an offset in a FETCH that was invalid or NULL.

Error 264	"Wrong number of variables in FETCH"
Constant	WRONG_NUM_OF_FETCH_VARIABLES
SAP Sybase Error Number	2143
SQL State	42W26
SQL Code	-264L
ODBC 2 State	S1002
ODBC 3 State	07009
Severity Code	16 on page 2
Probable Cause	You specified a number of variables in a FETCH statement that does not match the number of SELECT list items.

Error 265	"Procedure '%1' not found"
Constant	PROCEDURE_NOT_FOUND
SAP Sybase Error Number	2144
SQL State	52W09

Error 265	"Procedure '%1' not found"
SQL Code	-265L
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	<i>11</i> on page 2
Parameter 1	Name of the procedure that could not be found.
Probable Cause	You misspelled the name of a procedure, or you did not qualify a procedure name with a user name.

Error 267	"COMMIT/ROLLBACK not allowed within atomic operation"
Constant	ATOMIC_OPERATION
SAP Sybase Error Number	2146
SQL State	42W28
SQL Code	-267L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	<i>16</i> on page 2
Probable Cause	You attempted a COMMIT or ROLLBACK statement while executing within an atomic operation.

Error 268	"Trigger '%1' not found"
Constant	TRIGGER_NOT_FOUND
SAP Sybase Error Number	2147
SQL State	52W10
SQL Code	-268L
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	<i>11</i> on page 2
Parameter 1	Name of the trigger that could not be found.

Error 268	"Trigger '%1' not found"
Probable Cause	You misspelled the name of a trigger, or you did not qualify a trigger name with a user name.

Error 269	"Cannot delete or rename a column referenced in a trigger definition"
Constant	COLUMN_IN_TRIGGER
SAP Sybase Error Number	2148
SQL State	53W06
SQL Code	-269L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	15 on page 2
Probable Cause	You attempted to delete or rename a column referenced in a trigger definition. Drop the trigger before performing the ALTER statement.

Error 270	"Cannot drop a user that owns procedures in runtime server"
Constant	USER_OWNS_PROCEDURES
SAP Sybase Error Number	2149
SQL State	55W04
SQL Code	-270L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	You attempted to drop a user that owns procedures while using the runtime server. This operation would result in dropping procedures. The runtime server cannot drop procedures. Use the full server.

Error 271	"Trigger definition conflicts with existing triggers"
Constant	TRIGGER_DEFN_CONFLICT
SAP Sybase Error Number	2150

Error 271	"Trigger definition conflicts with existing triggers"
SQL State	52W11
SQL Code	-271L
ODBC 2 State	S0002
ODBC 3 State	42S01
Severity Code	15 on page 2
Probable Cause	You attempted to create a trigger, but a trigger with the same name already exists.

Error 272	"Invalid REFERENCES clause in trigger definition"
Constant	INVALID_TRIGGER_COL_REFS
SAP Sybase Error Number	2151
SQL State	52W12
SQL Code	-272L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Probable Cause	You supplied an invalid REFERENCES clause in a trigger definition. You may have specified an OLD correlation name in a BEFORE INSERT trigger, or a NEW correlation name in an AFTER DELETE trigger. In both cases, the values do not exist and cannot be referenced.

Error 273	"COMMIT/ROLLBACK not allowed within trigger actions"
Constant	INVALID_TRIGGER_STATEMENT
SAP Sybase Error Number	2152
SQL State	2D501
SQL Code	-273L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2

Error 273	"COMMIT/ROLLBACK not allowed within trigger actions"
Probable Cause	You attempted to execute a statement that is not allowed while performing a trigger action. COMMIT and ROLLBACK statements cannot be executed from a trigger.

Error 274	"Procedure or trigger calls have nested too deeply"
Constant	NESTING_TOO_DEEP
SAP Sybase Error Number	2153
SQL State	42W29
SQL Code	-274L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You may have defined a procedure or trigger that causes unlimited recursion.

Error 280	"Publication '%1' not found"
Constant	PUBLICATION_NOT_FOUND
SAP Sybase Error Number	2155
SQL State	5RW01
SQL Code	-280L
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	16 on page 2
Parameter 1	Name of the publication that could not be found.
Probable Cause	You misspelled the name of a publication, or you did not qualify a publication name with a user name.

Error 281	"Table '%1' has publications"
Constant	TABLE_HAS_PUBLICATIONS
SAP Sybase Error Number	2156

Error 281	"Table '%1' has publications"
SQL State	5RW02
SQL Code	-281L
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	16 on page 2
Parameter 1	Name of the table that has publications.
Probable Cause	You attempted to drop a table that has publications defined.

Error 282	"Subscription to '%1' for '%2' already exists"
Constant	SUBSCRIPTION_NOT_UNIQUE
SAP Sybase Error Number	2157
SQL State	5RW03
SQL Code	-282L
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	16 on page 2
Parameter 1	Name of the publication.
Parameter 2	Name of the user.
Probable Cause	You attempted to create a subscription that already exists.

Error 283	"Subscription to '%1' for '%2' not found"
Constant	SUBSCRIPTION_NOT_FOUND
SAP Sybase Error Number	2158
SQL State	5RW04
SQL Code	-283L
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	16 on page 2

Error 283	"Subscription to '%1' for '%2' not found"
Parameter 1	Name of the publication.
Parameter 2	Name of the user.
Probable Cause	You attempted to drop, start, or synchronize a subscription that does not exist.

Error 284	"User '%1' is already the publisher for this database"
Constant	ONLY_ONE_PUBLISHER
SAP Sybase Error Number	2159
SQL State	5RW05
SQL Code	-284L
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	16 on page 2
Parameter 1	Name of the publisher.
Probable Cause	You attempted to GRANT PUBLISH to a user ID, when a publisher already exists.

Error 285	"User '%1' is not a remote user for this database"
Constant	NOT_REMOTE_USER
SAP Sybase Error Number	2160
SQL State	5RW06
SQL Code	-285L
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	16 on page 2
Parameter 1	Name of user.
Probable Cause	You attempted to execute a CREATE SUBSCRIPTION or PASS-THROUGH for a user that is not a remote user of this database. You must GRANT REMOTE or GRANT CONSOLIDATE for this user before proceeding with this operation.

Error 286	"Remote message type '%1' not found"
Constant	NOT_REMOTE_TYPE
SAP Sybase Error Number	2161
SQL State	5RW07
SQL Code	-286L
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	16 on page 2
Parameter 1	Name of remote message type.
Probable Cause	You referred to a remote message type that is not defined in this database. Use CREATE REMOTE TYPE to define remote message types.

Error 287	"Passthrough statement inconsistent with current passthrough"
Constant	PASSTHROUGH_INCONSISTENT
SAP Sybase Error Number	2162
SQL State	5RW08
SQL Code	-287L
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	16 on page 2
Probable Cause	Passthrough is additive, in that subsequent PASSTHROUGH statements add to the list of users receiving passthrough. The PASSTHROUGH statements must all be PASSTHROUGH ONLY or none should be PASSTHROUGH ONLY.

Error 288	"Remote statement failed"
Constant	REMOTE_STATEMENT_FAILED
SAP Sybase Error Number	2163

Error 288	"Remote statement failed"
SQL State	5RW09
SQL Code	-288L
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	16 on page 2
Probable Cause	This SQLSTATE can be signaled within a trigger to prevent the SQL Remote Message Agent (dbremote) from displaying an error message in the output. This exception will only occur when a trigger or procedure signals it. This is useful for ignoring replication errors that are permitted by design.

Messages 289 through 313

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 289	"Multiple consolidated users cannot be defined"
Constant	CONSOLIDATED_USER_ALREADY_EXISTS
SAP Sybase Error Number	2403
SQL State	5RW10
SQL Code	-289L
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	16 on page 2
Probable Cause	You attempted to grant consolidated permissions when your database already has a consolidated user, or attempted to grant consolidated permissions to multiple users in a single statement.

Error 294	"Format string argument number %1 is invalid"
Constant	INVALID_FORMAT_STRING_ARG_NUM
SAP Sybase Error Number	2166
SQL State	53W08

Error 294	"Format string argument number %1 is invalid"
SQL Code	-294L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Argument number.
Probable Cause	You supplied an invalid argument number in the format string for a PRINT or RAISERROR statement. The number must be between 1 and 20 and must not exceed the number of arguments provided.

Error 295	"Cannot uniquely identify rows in cursor"
Constant	CANNOT_UNIQUELY_IDENTIFY_ROWS
SAP Sybase Error Number	2164
SQL State	09W05
SQL Code	-295L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	You opened a UNIQUE cursor on a SELECT statement for which a set of columns uniquely identifying each row cannot be generated. One of the tables may not be defined with a primary key or uniqueness constraint, or the SELECT statement may involve a UNION, INTERSECT, EXCEPT, or GROUP BY.

Error 296	"Error number %1 for RAISERROR must not be less than 17000"
Constant	ERROR_NUMBER_OUT_OF_RANGE
SAP Sybase Error Number	2165
SQL State	53W07
SQL Code	-296L
ODBC 2 State	37000

Error 296	"Error number %1 for RAISERROR must not be less than 17000"
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Error number.
Probable Cause	You supplied an invalid error number in a RAISERROR statement. The number must be greater than or equal to 17000.

Error 297	"User-defined exception signaled"
Constant	USER_DEFINED_EXCEPTION
SAP Sybase Error Number	2186
SQL State	99999
SQL Code	-297L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	A stored procedure or trigger signaled a user-defined exception. This error state is reserved for use within stored procedures or triggers that contain exception handlers, as a way of signaling an exception that can be guaranteed to not have been caused by the database server. Valid SQLSTATE values range from 99000 to 99999 and are set by the user when executing the signal SQL statement.

Error 298	"Attempted two active database requests"
Constant	DOUBLE_REQUEST
SAP Sybase Error Number	2187
SQL State	42W22
SQL Code	-298L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 298	"Attempted two active database requests"
Severity Code	<i>16 on page 2</i>
Probable Cause	In embedded SQL, you attempted to submit a database request while you have another request in progress. You should either use a separate SQLCA and connection for each thread accessing the database, or use thread synchronization calls to ensure that a SQLCA is only accessed by one thread at a time.

Error 299	"Statement interrupted by user"
Constant	INTERRUPTED
SAP Sybase Error Number	2188
SQL State	57014
SQL Code	-299L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	You canceled a statement during its execution. The database was able to stop the operation without doing a rollback. If the statement is an INSERT, UPDATE, or DELETE, any changes made by the statement will be canceled. If the statement is a data definition statement (for example CREATE TABLE), the statement will be canceled, but the COMMIT that was done as a side effect will not be canceled.

Error 300	"Run time SQL error -- %1"
Constant	ERROR
SAP Sybase Error Number	2189
SQL State	40000
SQL Code	-300L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>18 on page 2</i>

Error 300	"Run time SQL error -- %1"
Parameter 1	Identification of the error.
Probable Cause	An internal database error occurred. If it can be reproduced, it should be reported to SAP Sybase. You may be able to work around this problem by modifying the associated query statement.

Error 301	"Internal database error %1 -- transaction rolled back"
Constant	DATABASE_ERROR
SAP Sybase Error Number	2190
SQL State	40W01
SQL Code	-301L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	18 on page 2
Parameter 1	Identification of the error.
Probable Cause	An internal database error occurred. If it can be reproduced, it should be reported to SAP Sybase. A ROLLBACK statement has been automatically executed.

Error 302	"Terminated by user -- transaction rolled back"
Constant	TERMINATED_BY_USER
SAP Sybase Error Number	2191
SQL State	40W02
SQL Code	-302L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You canceled a statement while the database was executing. A ROLLBACK statement has been automatically executed.

Error 303	"Disk write failure '%1' -- transaction rolled back"
Constant	DISK_WRITE_FAILED
SAP Sybase Error Number	2513
SQL State	40W05
SQL Code	-303L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	21 on page 2
Parameter 1	Name of the file that could not be written.
Probable Cause	A disk write failed. A ROLLBACK statement has been automatically executed.

Error 304	"Disk full '%1' -- transaction rolled back"
Constant	DEVICE_FULL
SAP Sybase Error Number	2192
SQL State	40W03
SQL Code	-304L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	17 on page 2
Parameter 1	Name of the file that could not be written to the disk.
Probable Cause	Your hard disk is out of space. A ROLLBACK statement has been automatically executed.

Error 305	"I/O error %1 -- transaction rolled back"
Constant	DEVICE_ERROR
SAP Sybase Error Number	2193
SQL State	40W04
SQL Code	-305L

Error 305	"I/O error %1 -- transaction rolled back"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	24 on page 2
Parameter 1	A message describing the error that occurred.
Probable Cause	SQL Anywhere has detected a problem with your hard disk. A ROLLBACK statement has been automatically executed.

Error 306	"Deadlock detected"
Constant	DEADLOCK
SAP Sybase Error Number	2194
SQL State	40001
SQL Code	-306L
ODBC 2 State	40001
ODBC 3 State	40001
Severity Code	13 on page 2
Probable Cause	You attempted to read or write a row and it is locked by another user. Also, the other user is blocked directly or indirectly on your own transaction. This is a deadlock situation and your transaction has been chosen as the one to rollback.

Error 307	"All threads are blocked"
Constant	THREAD_DEADLOCK
SAP Sybase Error Number	2195
SQL State	40W06
SQL Code	-307L
ODBC 2 State	40001
ODBC 3 State	40001
Severity Code	13 on page 2

Error 307	"All threads are blocked"
Probable Cause	You attempted to read or write a row and it is locked by another user. Also, all other threads (see the -gn server option) are blocked waiting for a lock to be released. This is a deadlock situation and your transaction has been chosen as the one to rollback.
Error 308	"Connection was terminated"
Constant	CONNECTION_TERMINATED
SAP Sybase Error Number	2196
SQL State	40W07
SQL Code	-308L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	Your database connection has been terminated and your transaction has been rolled back. The connection may have been terminated because a DBA executed a DROP CONNECTION statement, or because the database server was shut down, or because your network connection to the database server was interrupted.
Error 309	"Memory error -- transaction rolled back"
Constant	MEMORY_ERROR
SAP Sybase Error Number	2361
SQL State	40W08
SQL Code	-309L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	24 on page 2

Error 309	"Memory error -- transaction rolled back"
Probable Cause	The UltraLite runtime has received an unexpected error from the system calls being used to store the UltraLite database. For example, a write to persistent memory failed. This is an internal error and indicates faulty or corrupt persistent storage on the device. A ROLLBACK statement has been automatically executed.

Error 311	"Internal rollback log corrupted"
Constant	LOG_CORRUPTED
SAP Sybase Error Number	2208
SQL State	WI004
SQL Code	-311L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	22 on page 2
Probable Cause	While processing a COMMIT or ROLLBACK, corruption was found in the internal rollback log. This is a fatal internal error.

Error 312	"User '%1' already has membership in group '%2'"
Constant	ALREADY_HAS_GROUP_MEMBERSHIP
SAP Sybase Error Number	2069
SQL State	42W34
SQL Code	-312L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Name of the user that already has membership.
Parameter 2	Name of the group.
Probable Cause	You attempted to give a membership in a group to a user that already has such membership.

Error 313	"The login ID '%1' has not been mapped to any database user ID"
Constant	LOGON_UNMAPPED
SAP Sybase Error Number	2266
SQL State	28W09
SQL Code	-313L
ODBC 2 State	28000
ODBC 3 State	28000
Severity Code	16 on page 2
Parameter 1	Name of the login ID that is not mapped.
Probable Cause	You attempted to connect using a login ID that is not mapped to a database user ID and there is no guest database user ID, or you attempted to revoke a login ID that has not been mapped. This can also occur when attempting to connect using an integrated login ID that is a member of more than one mapped group.

Messages 503 through 619

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 503	No message
Constant	PREEMPTED
SAP Sybase Error Number	2260
SQL State	WI006
SQL Code	-503L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	No additional information available.

Errors and Warnings

Error 504	No message
Constant	RETRY
SAP Sybase Error Number	2261
SQL State	WI008
SQL Code	-504L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	No additional information available.

Error 601	""%1' is not a known file format for loading or unloading tables"
Constant	UNSUPPORTED_LOAD_FORMAT
SAP Sybase Error Number	2209
SQL State	WL001
SQL Code	-601L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	19 on page 2
Parameter 1	The specified format.
Probable Cause	An unsupported file format was specified for LOAD TABLE or UNLOAD TABLE.

Error 602	"Cannot access file '%1' -- %2"
Constant	CANNOT_ACCESS_FILE
SAP Sybase Error Number	2210
SQL State	WL002
SQL Code	-602L
ODBC 2 State	ERROR

Error 602	"Cannot access file '%1' -- %2"
ODBC 3 State	ERROR
Severity Code	<i>19 on page 2</i>
Parameter 1	The file name.
Parameter 2	The cause of the error.
Probable Cause	A file cannot be accessed. For example, a file referenced by LOAD TABLE does not exist or cannot be read. The message will contain the reason for the error.

Error 604	"A dbspace has reached its maximum file size"
Constant	DBSPACE_FULL
SAP Sybase Error Number	2213
SQL State	04W07
SQL Code	-604L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	A dbspace has grown to its maximum number of disk pages, which is usually limited by the maximum operating system file size. This is a fatal error.

Error 605	"The server attempted to access a page beyond the end of the maximum allowable dbspace file size"
Constant	ACCESS_BEYOND_END_OF_MAX_DBSPACE
SAP Sybase Error Number	2214
SQL State	04W08
SQL Code	-605L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>

Error 605	"The server attempted to access a page beyond the end of the maximum allowable dbspace file size"
Probable Cause	The database attempted to access a page whose page number is beyond the maximum possible number of disk pages. This is a fatal internal error.

Error 606	"The pattern is too long"
Constant	PATTERN_TOO_LONG
SAP Sybase Error Number	2215
SQL State	WW001
SQL Code	-606L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The pattern for the LIKE operator is too long. All patterns of 126 characters or less are supported. Some patterns as long as 254 characters are supported, depending on their contents. Patterns longer than 254 characters are not supported.

Error 607	"Cannot stop the database server"
Constant	CANNOT_STOP_SERVER
SAP Sybase Error Number	2216
SQL State	WW002
SQL Code	-607L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The server has determined that it cannot be shut down at this time. Normally, this error should not occur.

Error 608	"Invalid TEXTPTR value used with WRITETEXT or READTEXT"
Constant	INVALID_TEXTPTR_VALUE
SAP Sybase Error Number	2217
SQL State	22W03
SQL Code	-608L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You supplied an invalid value as the TEXTPTR for a WRITETEXT or READTEXT statement.

Error 609	"Invalid data type for column in WRITETEXT or READTEXT"
Constant	INVALID_TEXT_IMAGE_DATATYPE
SAP Sybase Error Number	2218
SQL State	53W09
SQL Code	-609L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You referenced a column in a WRITETEXT or READTEXT statement that is not defined for storing text or image data.

Error 610	"User message %1 already exists"
Constant	MESSAGE_ALREADY_EXISTS
SAP Sybase Error Number	2064
SQL State	52W16
SQL Code	-610L
ODBC 2 State	42000

Error 610	"User message %1 already exists"
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Error number of the user message that exists in the database.
Probable Cause	The message with this error number already exists in the database.

Error 611	"Transact-SQL feature not supported"
Constant	TSQL_FEATURE_NOT_SUPPORTED
SAP Sybase Error Number	2076
SQL State	0AW02
SQL Code	-611L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Probable Cause	You attempted to use a Transact-SQL feature that is not supported in SQL Anywhere.

Error 612	"User message %1 not found"
Constant	MESSAGE_NOT_FOUND
SAP Sybase Error Number	2097
SQL State	52W17
SQL Code	-612L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Message number.
Probable Cause	The message with this error number does not exist in the database.

Error 613	"User-defined type '%1' not found"
Constant	USER_TYPE_NOT_FOUND

Error 613	"User-defined type '%1' not found"
SAP Sybase Error Number	2098
SQL State	52W18
SQL Code	-613L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Name of the user-defined type.
Probable Cause	The user-defined type with this name does not exist in the database.

Error 614	"Cannot drop a user that owns messages or data types"
Constant	USER_OWNS_MESSAGES_OR_DATATYPES
SAP Sybase Error Number	2099
SQL State	55W05
SQL Code	-614L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	You attempted to drop a user that is the creator of a message or user-defined data type. The message or user-defined data type must be dropped first.

Error 615	"Parameter '%1' not found in procedure '%2'"
Constant	INVALID_PARAMETER_NAME
SAP Sybase Error Number	2101
SQL State	42W47
SQL Code	-615L
ODBC 2 State	37000
ODBC 3 State	42000

Error 615	"Parameter '%1' not found in procedure '%2'"
Severity Code	<i>16</i> on page 2
Parameter 1	Name of the parameter that was not found.
Parameter 2	Name of the procedure where the parameter was not found.
Probable Cause	You supplied a procedure parameter name that does not match a parameter for this procedure. Check the spelling of the parameter name.

Error 616	"Too many columns in table"
Constant	TOO_MANY_COLUMNS_IN_TABLE
SAP Sybase Error Number	2219
SQL State	52W20
SQL Code	-616L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Probable Cause	You executed a CREATE TABLE or ALTER TABLE statement that attempted to add a column to a table. The resulting number of columns in the table would exceed the limit for the current database page size.

Error 617	"Calling functions outside the database server is not supported"
Constant	EXTERNAL_CALLS_NOT_SUPPORTED
SAP Sybase Error Number	2220
SQL State	WW003
SQL Code	-617L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2

Error 617	"Calling functions outside the database server is not supported"
Probable Cause	You attempted to call a stored procedure that, in turn, calls a function in a dynamically loaded module. The operating system on which this stored procedure was called does not support such an action.

Error 618	"Mismatch between external function platform specifier and current operating system"
Constant	EXTERNAL_PLATFORM_FAILURE
SAP Sybase Error Number	2221
SQL State	WW004
SQL Code	-618L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	A call to an external entry point in a dynamically loaded module was qualified by an operating system that was not the operating system on which the server is currently executing.

Error 619	"Need a dynamic library name"
Constant	REQUIRE_DLL_NAME
SAP Sybase Error Number	2222
SQL State	WW005
SQL Code	-619L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	19 on page 2
Probable Cause	You must provide a library name specifier in the name of the external function to call.

Messages 620 through 639

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 620	"Could not load dynamic library '%1'"
Constant	COULD_NOT_LOAD_LIBRARY
SAP Sybase Error Number	2223
SQL State	WW006
SQL Code	-620L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	19 on page 2
Parameter 1	Name of the dynamic library that could not be loaded.
Probable Cause	This error is usually caused by a failure to load a dynamic library named in an external function call.

Error 621	"Could not find '%1' in dynamic library '%2'"
Constant	COULD_NOT_FIND_FUNCTION
SAP Sybase Error Number	2224
SQL State	WW007
SQL Code	-621L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	19 on page 2
Parameter 1	Name of the function that could not be found.
Parameter 2	Name of the dynamic library in which the function could not be found.
Probable Cause	The external function could not be found in the dynamic library.

Error 622	"Could not allocate resources to call external function"
Constant	ERROR_CALLING_FUNCTION
SAP Sybase Error Number	2225
SQL State	WW008
SQL Code	-622L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	19 on page 2
Probable Cause	The external function could not be called due to a shortage of operating system resources. If the operating system supports threads, the maximum thread count should be increased.

Error 623	"Data definition statements not allowed in procedures or triggers"
Constant	DDL_NOT_ALLOWED_IN_PROCEDURES
SAP Sybase Error Number	2226
SQL State	52W21
SQL Code	-623L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	15 on page 2
Probable Cause	The procedure or trigger definition contains a data definition statement (such as CREATE, DROP, GRANT, REVOKE, or ALTER). These statements are not allowed within procedures or triggers.

Error 624	"Expression has unsupported data type"
Constant	DATATYPE_NOT_ALLOWED
SAP Sybase Error Number	2227
SQL State	WW009

Error 624	"Expression has unsupported data type"
SQL Code	-624L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	Either an external function or Java method was declared with a parameter or result data type that is not supported, or a Java field reference with an unsupported result type was attempted.

Error 625	"Too many parameters to this external procedure call"
Constant	TOO_MANY_PARAMETERS
SAP Sybase Error Number	2228
SQL State	WW010
SQL Code	-625L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	19 on page 2
Probable Cause	There is a maximum of 256 parameters to an external function call in 32-bit Windows.

Error 626	"A thread used internally could not be started"
Constant	THREAD_START_FAILURE
SAP Sybase Error Number	2229
SQL State	WW011
SQL Code	-626L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	19 on page 2
Probable Cause	This is a Windows 95 specific error. An operating system thread could not be started that is required to execute external functions.

Error 627	"Disallowed language extension detected in syntax near '%1' on line %2"
Constant	INVALID_SYNTAX_EXTENSION
SAP Sybase Error Number	2230
SQL State	0AW03
SQL Code	-627L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The word or symbol where the syntax has been detected.
Parameter 2	Line number.
Probable Cause	The statement you are trying to execute contains syntax that is not allowed with the current setting of the option <code>sql_flagger_error_level</code> . Modify the offending statement or set the <code>sql_flagger_error_level</code> option to a different value.

Error 628	"Division by zero"
Constant	DIV_ZERO_ERROR
SAP Sybase Error Number	2231
SQL State	22012
SQL Code	-628L
ODBC 2 State	22012
ODBC 3 State	22012
Severity Code	16 on page 2
Probable Cause	A division by zero operation was detected.

Error 629	"Invalid escape character '%1'"
Constant	INVALID_ESCAPE_CHAR
SAP Sybase Error Number	2232
SQL State	22019

Error 629	"Invalid escape character '%1'"
SQL Code	-629L
ODBC 2 State	S1000
ODBC 3 State	22019
Severity Code	16 on page 2
Parameter 1	The escape character that is invalid.
Probable Cause	The escape character string length must be exactly one.

Error 630	"Invalid escape sequence '%1'"
Constant	INVALID_ESCAPE_SEQ
SAP Sybase Error Number	2233
SQL State	22025
SQL Code	-630L
ODBC 2 State	S1000
ODBC 3 State	22025
Severity Code	16 on page 2
Parameter 1	The escaped character.
Probable Cause	A LIKE pattern contains an invalid use of the escape character. The escape character may only precede the special characters '%', '_', '[', and the escape character itself.

Error 631	"RAISERROR executed: %1"
Constant	RAISERROR_STMT
SAP Sybase Error Number	2234
SQL State	WW012
SQL Code	-631L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2

Error 631	"RAISERROR executed: %1"
Parameter 1	RAISERROR message string.
Probable Cause	A RAISERROR statement has been executed. The string associated with the RAISERROR statement is included in the text of the error message.

Error 632	"WITH CHECK OPTION violated for insert/update on base table '%1'"
Constant	WITH_CHECK_OPTION_VIOLATION
SAP Sybase Error Number	2235
SQL State	44000
SQL Code	-632L
ODBC 2 State	S1000
ODBC 3 State	44000
Severity Code	<i>16 on page 2</i>
Parameter 1	Name of the base table being updated.
Probable Cause	You attempted an insert or update operation on the indicated base table through a view (possibly nested). However, one or more values in the modified row(s) triggered a WITH CHECK OPTION violation. This violation occurs when a modified value causes one or more rows to fall outside the range of the view by making the view's WHERE clause evaluate to FALSE or UNKNOWN for that row.

Error 633	"Update operation attempted on a read-only cursor"
Constant	READ_ONLY_CURSOR
SAP Sybase Error Number	2236
SQL State	42W30
SQL Code	-633L
ODBC 2 State	S1009
ODBC 3 State	HY092
Severity Code	<i>16 on page 2</i>

Error 633	"Update operation attempted on a read-only cursor"
Probable Cause	You attempted an update operation on a cursor that was explicitly declared as read-only.

Error 634	"Unterminated C string"
Constant	UNTERMINATED_C_STR
SAP Sybase Error Number	2237
SQL State	22024
SQL Code	-634L
ODBC 2 State	22024
ODBC 3 State	22024
Severity Code	16 on page 2
Probable Cause	The last byte of a C string host variable must contain the null character.

Error 635	"GRANT of column permission on view not allowed"
Constant	NO_COLUMN_PERMS_FOR_VIEWS
SAP Sybase Error Number	2240
SQL State	52W22
SQL Code	-635L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	15 on page 2
Probable Cause	You cannot grant permissions on columns for views.

Error 636	"Duplicate referencing column"
Constant	DUPLICATE_REFERENCING_COLUMN
SAP Sybase Error Number	2242
SQL State	42W40
SQL Code	-636L

Error 636	"Duplicate referencing column"
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	<i>16</i> on page 2
Probable Cause	You supplied a duplicate column name in the list of referencing columns.

Error 637	"Duplicate insert column"
Constant	DUPLICATE_INSERT_COLUMN
SAP Sybase Error Number	2243
SQL State	42W41
SQL Code	-637L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	<i>16</i> on page 2
Probable Cause	You supplied a duplicate column name in the list of insert columns.

Error 638	"Right truncation of string data"
Constant	STRING_RIGHT_TRUNCATION
SAP Sybase Error Number	2244
SQL State	22001
SQL Code	-638L
ODBC 2 State	22001
ODBC 3 State	22001
Severity Code	<i>16</i> on page 2
Probable Cause	Non-space characters were truncated upon the assignment of string data.

Error 639	"Parameter name missing in call to procedure '%1'"
Constant	PARAMETER_NAME_MISSING

Error 639	"Parameter name missing in call to procedure '%1'"
SAP Sybase Error Number	2245
SQL State	42W42
SQL Code	-639L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	The name of the procedure.
Probable Cause	Positional parameters were specified after named parameters in a call to this procedure.

Messages 640 through 659

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 640	"Invalid descriptor index"
Constant	INVALID_DESCRIPTOR_INDEX
SAP Sybase Error Number	2246
SQL State	07009
SQL Code	-640L
ODBC 2 State	S1002
ODBC 3 State	07009
Severity Code	26 on page 2
Probable Cause	The index number used with respect to a descriptor area is out of range.

Error 641	"Error in assignment"
Constant	ERROR_IN_ASSIGNMENT
SAP Sybase Error Number	2247
SQL State	22005
SQL Code	-641L

Error 641	"Error in assignment"
ODBC 2 State	22005
ODBC 3 State	22018
Severity Code	<i>20</i> on page 2
Probable Cause	In a GET DESCRIPTOR statement, the data type of the host variable must correspond to the data type of the descriptor item.

Error 642	"Invalid SQL descriptor name"
Constant	INVALID_DESCRIPTOR_NAME
SAP Sybase Error Number	2248
SQL State	33000
SQL Code	-642L
ODBC 2 State	33000
ODBC 3 State	33000
Severity Code	<i>21</i> on page 2
Probable Cause	You attempted to deallocate a descriptor that has not been allocated.

Error 643	"UNLOAD TABLE cannot be used to unload a view"
Constant	CANNOT_UNLOAD_A_VIEW
SAP Sybase Error Number	2212
SQL State	WL004
SQL Code	-643L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Probable Cause	UNLOAD TABLE was specified with the name of a view. UNLOAD TABLE may only be used to unload tables.

Error 644	"Invalid database page size"
Constant	PAGE_SIZE_INVALID

Error 644	"Invalid database page size"
SAP Sybase Error Number	2032
SQL State	08W32
SQL Code	-644L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	14 on page 2
Probable Cause	You attempted to create a database with an invalid page size. The page size for a SQL Anywhere database must be either 2048, 4096, 8192, 16384, or 32768 bytes. The page size for an UltraLite database must be either 1024, 2048, 4096, 8192, or 16384 bytes.

Error 645	"Database creation failed: %1"
Constant	DATABASE_NOT_CREATED
SAP Sybase Error Number	2033
SQL State	08W33
SQL Code	-645L
ODBC 2 State	08004
ODBC 3 State	08004
Severity Code	14 on page 2
Parameter 1	Reason that the database was not created.
Probable Cause	Your attempt to initialize a file for a database failed.

Error 646	"Could not load the store DLL \"%1\No message"
Constant	STORE_NOT_LOADED
SAP Sybase Error Number	2270
SQL State	08W34
SQL Code	-646L
ODBC 2 State	ERROR

Error 646	"Could not load the store DLL \"%1\"No message"
ODBC 3 State	ERROR
Severity Code	<i>19 on page 2</i>
Parameter 1	Name of the store DLL that could not be loaded.
Probable Cause	An attempt to load the store DLL failed.

Error 647	"Could not execute store DLL (%1) entry point"
Constant	STORE_ENTRY_NOT_FOUND
SAP Sybase Error Number	2271
SQL State	08W35
SQL Code	-647L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>19 on page 2</i>
Parameter 1	Name of the store DLL where the entry point failed.
Probable Cause	An attempt to locate or execute the store DLL entry point failed.

Error 648	"Cannot create item (%1) in the specified dbspace"
Constant	INVALID_DBSPACE_FOR_CREATE
SAP Sybase Error Number	2272
SQL State	08W36
SQL Code	-648L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	Name of the item that could not be created.
Probable Cause	The specified dbspace is invalid. For example, an index must be created in a dbspace of the same type as the underlying table.

Error 649	"Field '%1' of class '%2' cannot be NULL"
Constant	FIELD_CANNOT_BE_NULL
SAP Sybase Error Number	2275
SQL State	WW015
SQL Code	-649L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the field that cannot be NULL.
Parameter 2	The name of the class that has the field.
Probable Cause	An attempt was made to store a SQL NULL value in a Java object field that has a Java type that cannot be NULL. For example, the Java 'int' type cannot be NULL.

Error 650	"Index type specification of '%1' is invalid"
Constant	INVALID_INDEX_TYPE
SAP Sybase Error Number	2276
SQL State	WW016
SQL Code	-650L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The index type specification that is invalid.
Probable Cause	In UltraLite, you cannot specify indexes on LONG column types. Sybase IQ index types can be specified for SAP Sybase IQ indexes only.

Error 651	"An attempt to delete database '%1' failed"
Constant	DROP_DATABASE_FAILED
SAP Sybase Error Number	2277

Error 651	"An attempt to delete database '%1' failed"
SQL State	WW017
SQL Code	-651L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The name of the database that could not be deleted.
Probable Cause	Your attempt to delete a database file failed. You may have attempted to delete a running database. Some parts of the database may have been deleted before failure.

Error 652	"Could not decompress class '%1' from JAR"
Constant	CANNOT_DECOMPRESS_CLASS
SAP Sybase Error Number	2278
SQL State	WP003
SQL Code	-652L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The name of the class file in the JAR.
Probable Cause	The Java runtime library must be installed to extract class files from ZIP or JAR files.

Error 653	"Cannot remove class '%1': member of JAR"
Constant	CLASS_MEMBER_OF_JAR
SAP Sybase Error Number	2279
SQL State	WP004
SQL Code	-653L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 653	"Cannot remove class '%1': member of JAR"
Severity Code	<i>16</i> on page 2
Parameter 1	The name of the class file that cannot be removed.
Probable Cause	You attempted to remove a class file that is still part of a JAR. It must be removed with the JAR.

Error 654	"The connection parameters file could not be found"
Constant	NO_PROFILE_FILE
SAP Sybase Error Number	2280
SQL State	08W37
SQL Code	-654L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	<i>16</i> on page 2
Probable Cause	An attempt was made to parse a connection string containing a connection profile but the connection parameters file could not be found.

Error 655	"Error parsing connection parameter string"
Constant	GEN_PARSE_ERROR
SAP Sybase Error Number	2281
SQL State	08W38
SQL Code	-655L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	<i>16</i> on page 2
Probable Cause	The connection string could not be parsed. The string or connection parameter file contains a syntax error.

Error 656	"Unable to connect to server '%1': %2"
Constant	OMNI_CONNECT_ERROR

Error 656	"Unable to connect to server '%1': %2"
SAP Sybase Error Number	2282
SQL State	WO001
SQL Code	-656L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The name of the server that could not be connected to.
Parameter 2	A more specific reason returned from the server class driver.
Probable Cause	You attempted to connect to a remote server. Check that the remote server is running.

Error 657	"Unable to connect, server definition is circular"
Constant	OMNI_CIRCULAR_CONNECT
SAP Sybase Error Number	2552
SQL State	WO002
SQL Code	-657L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	You attempted to connect to a remote server that maps to the local database.

Error 658	"Remote server '%1' is currently configured as read-only"
Constant	OMNI_READONLY
SAP Sybase Error Number	2284
SQL State	WO003
SQL Code	-658L
ODBC 2 State	ERROR

Error 658	"Remote server '%1' is currently configured as read-only"
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the remote server.
Probable Cause	You attempted to perform an update on an object located on a server that is configured as read-only. Use ALTER SERVER to reconfigure the remote server to be updatable.

Error 659	"Remote server '%1' could not be found"
Constant	OMNI_SERVER_NOT_FOUND
SAP Sybase Error Number	2285
SQL State	WO004
SQL Code	-659L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	11 on page 2
Parameter 1	Name of the remote server.
Probable Cause	You attempted to define an object on a server that has not been added. Use CREATE SERVER to add the remote server definition.

Messages 660 through 681

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 660	"Server '%1': %2"
Constant	OMNI_REMOTE_ERROR
SAP Sybase Error Number	2286
SQL State	WO005
SQL Code	-660L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 660	"Server '%1': %2"
Severity Code	<i>16 on page 2</i>
Parameter 1	The name of the remote server.
Parameter 2	The message from the remote server.
Probable Cause	A message was generated by a remote server. The message text is included.

Error 661	"Backward scrolling cursors are not supported for remote objects"
Constant	OMNI_BACKWARDS_CURSOR
SAP Sybase Error Number	2287
SQL State	WO006
SQL Code	-661L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	Backward scrolling cursors are not supported for remote objects. Use forward scrolling cursors only.

Error 662	"Cannot serialize Java object with class '%1'"
Constant	JAVA_SERIALIZATION_ERROR
SAP Sybase Error Number	2288
SQL State	WI009
SQL Code	-662L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The class of the value that cannot be serialized.
Probable Cause	The Java object cannot be serialized as a persistent database column.

Error 663	"Cannot deserialize Java object"
Constant	JAVA_DESERIALIZATION_ERROR
SAP Sybase Error Number	2289
SQL State	WW018
SQL Code	-663L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The persistent Java object cannot be read from the database column. Possibly, the class of the object has been removed or modified.

Error 664	"Database is active"
Constant	DATABASE_ACTIVE
SAP Sybase Error Number	2290
SQL State	08W40
SQL Code	-664L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The attempted operation (CREATE ENCRYPTED, CREATE DECRYPTED, ALTER DATABASE) cannot be performed while the database is running. Stop the database to perform the operation.

Error 665	"Database \"%1\" needs recovery"
Constant	DATABASE_NEEDS_RECOVERY
SAP Sybase Error Number	2291
SQL State	08W41
SQL Code	-665L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 665	"Database \"%1\" needs recovery"
Severity Code	21 on page 2
Parameter 1	The file name of the database that needs recovery.
Probable Cause	The database quit abnormally the last time it was used. Database recovery must be performed before proceeding.

Error 666	"The remote table '%1' could not be found"
Constant	OMNI_RMT_TABLE_NOTFOUND
SAP Sybase Error Number	2292
SQL State	WO007
SQL Code	-666L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	11 on page 2
Parameter 1	The complete name of the remote table.
Probable Cause	The table could not be found on the remote server. Check the remote table name and the user privileges on that table.

Error 667	"Could not access column information for the table '%1'"
Constant	OMNI_RMT_COLUMNS_NOTFOUND
SAP Sybase Error Number	2293
SQL State	WO008
SQL Code	-667L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	11 on page 2
Parameter 1	The complete name of the remote table.
Probable Cause	Column information for the table could not be accessed. Check permissions for the table.

Error 668	"Cursor is restricted to FETCH NEXT operations"
Constant	NO_SCROLL_CURSOR
SAP Sybase Error Number	2294
SQL State	09W06
SQL Code	-668L
ODBC 2 State	S1106
ODBC 3 State	HY106
Severity Code	16 on page 2
Probable Cause	An illegal FETCH operation has been detected for a NO SCROLL cursor. For a forward-only cursor the only permitted FETCH operations are FETCH RELATIVE 0 and FETCH NEXT (FETCH RELATIVE 1).

Error 669	"Method '%1' cannot be called at this time"
Constant	METHOD_CANNOT_BE_CALLED
SAP Sybase Error Number	2295
SQL State	WJ001
SQL Code	-669L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the method.
Probable Cause	The method cannot be called at this time. Check that the method is not being called out of order.

Error 670	"Invalid class byte code"
Constant	BAD_CLASS_BYTE_CODE
SAP Sybase Error Number	2296
SQL State	WP005
SQL Code	-670L

Error 670	"Invalid class byte code"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	A binary expression passed to the INSTALL JAVA statement was not a valid Java class.

Error 672	"Database upgrade failed"
Constant	DATABASE_UPGRADE_FAILED
SAP Sybase Error Number	2298
SQL State	08W42
SQL Code	-672L
ODBC 2 State	08004
ODBC 3 State	08004
Severity Code	<i>20 on page 2</i>
Probable Cause	Your attempt to upgrade a database failed. This could be caused by a failure to locate one of the SQL script files used to define the system table changes.

Error 673	"Database upgrade not possible"
Constant	DATABASE_UPGRADE_NOT_POSSIBLE
SAP Sybase Error Number	2299
SQL State	08W43
SQL Code	-673L
ODBC 2 State	08004
ODBC 3 State	08004
Severity Code	<i>21 on page 2</i>
Probable Cause	An attempt to upgrade a database failed. The database is too old to be upgraded.

Error 674	"Statement's size limit is invalid"
Constant	INVALID_CURSOR_RANGE
SAP Sybase Error Number	2300
SQL State	09W07
SQL Code	-674L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	15 on page 2
Probable Cause	FIRST or TOP n are used in a SELECT statement to limit the size of a result. The size limit must be a constant integer greater than 0 and less than 32767.

Error 675	"External environment could not be started, '%1' could not be found"
Constant	EXTENV_NOT_STARTED
SAP Sybase Error Number	2301
SQL State	WP006
SQL Code	-675L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The component (executable or file) that could not be found and is needed to run the VM.
Probable Cause	A problem was encountered starting the External Environment. A component that is needed to run the environment could not be found.

Error 676	"The specified transaction isolation is invalid"
Constant	INVALID_TRANSACTION_ISOLATION
SAP Sybase Error Number	2303
SQL State	WJ003

Error 676	"The specified transaction isolation is invalid"
SQL Code	-676L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	15 on page 2
Probable Cause	The specified transaction isolation is invalid.

Error 677	"Table '%1' has a foreign key with a referential action"
Constant	TABLE_HAS_REFACTION
SAP Sybase Error Number	2304
SQL State	56001
SQL Code	-677L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the table with the referential action.
Probable Cause	The table could not be renamed as it has a foreign key with a referential action. To rename the table, first drop the foreign key constraints.

Error 678	"Index name '%1' is ambiguous"
Constant	AMBIGUOUS_INDEX_NAME
SAP Sybase Error Number	2305
SQL State	52W40
SQL Code	-678L
ODBC 2 State	S0011
ODBC 3 State	42S11
Severity Code	16 on page 2
Parameter 1	Name of the ambiguous index.

Error 678	"Index name '%1' is ambiguous"
Probable Cause	A statement has referred to an index name that is not unique. Preface the index name with the table and/or owner name.

Error 680	"Invalid expression in WHERE clause of Transact-SQL outer join"
Constant	INVALID_TSQL_OJ_EXPRESSION
SAP Sybase Error Number	2307
SQL State	52W23
SQL Code	-680L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	An expression in the WHERE clause of a query that uses Transact-SQL syntax contains a comparison of a column from the NULL-supplying table with a subquery or an expression that references a column from another table.

Error 681	"Invalid join type used with Transact-SQL outer join"
Constant	INVALID_TSQL_JOIN_TYPE
SAP Sybase Error Number	2308
SQL State	52W24
SQL Code	-681L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	An invalid join type was used with a query that contains Transact-SQL outer join comparison operators.

Messages 682 through 709

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 682	"%1"
Constant	OMNI_DEBUG
SAP Sybase Error Number	2309
SQL State	WO010
SQL Code	-682L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	16 on page 2
Parameter 1	The debug message for the console.
Probable Cause	This message is used for displaying component integration services debug messages in the messages window.

Error 683	"The cursor name '%1' already exists"
Constant	DUPLICATE_CURSOR_NAME
SAP Sybase Error Number	2312
SQL State	WJ004
SQL Code	-683L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the cursor.
Probable Cause	You attempted to declare a cursor with a name that already exists. Cursor names must be unique within a connection.

Error 684	"Rollback occurred due to deadlock during prefetch"
Constant	ROLLBACK_ON_PREFETCH

Error 684	"Rollback occurred due to deadlock during prefetch"
SAP Sybase Error Number	2313
SQL State	WW019
SQL Code	-684L
ODBC 2 State	40001
ODBC 3 State	40001
Severity Code	13 on page 2
Probable Cause	One of the cursors that was opened with prefetch enabled was performing fetch operations, and a deadlock occurred during a prefetch. This is a deadlock situation and your transaction has been chosen as the one to rollback. The request that received this error was not executed, unless the request was to close the cursor, in which case the cursor was closed.

Error 685	"Resource governor for '%1' exceeded"
Constant	RESOURCE_GOVORNOR_EXCEEDED
SAP Sybase Error Number	2314
SQL State	WP009
SQL Code	-685L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	19 on page 2
Parameter 1	The resource whose limit has been exceeded.
Probable Cause	The resource governor for the stated resource has determined that the usage of the resource has exceeded its limit.

Error 686	"Insufficient cache to start Java VM"
Constant	JAVA_VM_INSUFFICIENT_CACHE
SAP Sybase Error Number	2524
SQL State	WP015
SQL Code	-686L

Error 686	"Insufficient cache to start Java VM"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	Insufficient cache was available to start the Java VM. Restart the database server with a larger cache size.

Error 687	"Syntax error, cannot specify SAP Sybase IQ specific options without specifying IQ PATH"
Constant	IQ_PATH_SYNTAX_ERROR
SAP Sybase Error Number	2072
SQL State	42W48
SQL Code	-687L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	<i>15 on page 2</i>
Probable Cause	The IQ PATH clause must be specified when one or more options specified in the CREATE DATABASE statement are SAP Sybase IQ specific.

Error 689	"Input parameter index out of range"
Constant	BAD_PARAM_INDEX
SAP Sybase Error Number	2317
SQL State	WJ005
SQL Code	-689L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	The range for valid parameters is from 1 up to the number of host variables specified in the prepared/callable statement.

Error 691	"Could not load the backup/restore DLL \"%1\"No message"
Constant	BACKUP_NOT_LOADED
SAP Sybase Error Number	2319
SQL State	08W44
SQL Code	-691L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	19 on page 2
Parameter 1	The name of the DLL that could not be loaded.
Probable Cause	An attempt to load the backup/restore DLL failed.

Error 692	"Could not execute backup/restore DLL (%1) entry point"
Constant	BACKUP_ENTRY_NOT_FOUND
SAP Sybase Error Number	2320
SQL State	08W45
SQL Code	-692L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	19 on page 2
Parameter 1	The name of the entry point that could not be found.
Probable Cause	An attempt to locate or execute the backup/restore DLL entry point failed.

Error 697	"Error during backup/restore: %1"
Constant	BACKUP_ERROR
SAP Sybase Error Number	2325
SQL State	08W46
SQL Code	-697L
ODBC 2 State	ERROR

Error 697	"Error during backup/restore: %1"
ODBC 3 State	ERROR
Severity Code	21 on page 2
Parameter 1	A message describing the error that occurred.
Probable Cause	An error occurred during a BACKUP or RESTORE statement.

Error 698	"The remote server does not support an auto-incrementing data type"
Constant	OMNI_AUTOINC_NOT_SUPPORTED
SAP Sybase Error Number	2329
SQL State	WO011
SQL Code	-698L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	12 on page 2
Probable Cause	Auto-incrementing data types can only be supported in a proxy table when the remote server supports this feature.

Error 700	"SQLDA fields inconsistent for a multi-row SQLDA"
Constant	SQLDA_INCONSISTENT
SAP Sybase Error Number	2328
SQL State	07W04
SQL Code	-700L
ODBC 2 State	07001
ODBC 3 State	07W04
Severity Code	16 on page 2
Probable Cause	Not all of the rows in a multi-row SQLDA have been defined identically for an array operation (insert, fetch, or execute). A given column must be defined the same (type and length) in each row.

Error 702	"TRUNCATE TABLE statement cannot be used on a view"
Constant	CANNOT_TRUNCATE_VIEW
SAP Sybase Error Number	2330
SQL State	42W49
SQL Code	-702L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	You attempted to use TRUNCATE TABLE on a view, which is not permitted.

Error 703	"Cannot insert or update computed column '%1'"
Constant	COMPUTED_COLUMN_WRITE_ATTEMPTED
SAP Sybase Error Number	2331
SQL State	WW023
SQL Code	-703L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the column.
Probable Cause	Computed column values cannot be modified explicitly. Their value is determined implicitly from the computed expression value.

Error 704	"Cannot create an index on Java class '%1'"
Constant	CANNOT_INDEX_ON_JAVA_CLASS
SAP Sybase Error Number	2332
SQL State	WW022
SQL Code	-704L
ODBC 2 State	ERROR

Error 704	"Cannot create an index on Java class '%1'"
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The name of the class.
Probable Cause	An operation requiring an index was attempted in which an attempt was made to create an index on a Java class type.

Error 705	"Return type of void from procedure '%1' cannot be used in any expression"
Constant	PROCEDURE_RETURNS_VOID
SAP Sybase Error Number	2333
SQL State	53019
SQL Code	-705L
ODBC 2 State	07006
ODBC 3 State	07006
Severity Code	<i>16 on page 2</i>
Parameter 1	Name of the procedure.
Probable Cause	The Java type void does not map onto any SQL type, hence a procedure returning void cannot be used in any SQL expression.

Error 706	"Remote server does not have the ability to support this statement"
Constant	OMNI_SERVER_NOT_CAPABLE
SAP Sybase Error Number	2334
SQL State	WO012
SQL Code	-706L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	You attempted to execute a statement that requires a capability that is not supported by a remote server.

Error 707	"Statement is not allowed in passthrough mode"
Constant	STMT_NOT_ALLOWED_IN_PASSTHROUGH
SAP Sybase Error Number	2335
SQL State	0AW05
SQL Code	-707L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	You tried to execute a statement that cannot be executed while in passthrough mode. For example, you may have executed a batch statement.

Error 708	"READTEXT or WRITETEXT statement cannot refer to a view"
Constant	TEXT_OPERATION_ON_VIEW
SAP Sybase Error Number	2336
SQL State	42W50
SQL Code	-708L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	A Transact-SQL READTEXT or WRITETEXT statement cannot refer to text columns in a view. Replace the view reference with the name of a base table.

Error 709	"Computed columns are not supported in this database"
Constant	COMPUTED_COLUMNS_NOT_SUPPORTED
SAP Sybase Error Number	2337
SQL State	0AW06
SQL Code	-709L

Error 709	"Computed columns are not supported in this database"
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	The current database is an older database and does not have catalog support for computed (materialized) columns. To use this feature, upgrade your database to the most recent version.

Messages 710 through 731

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 710	"Invalid comparison"
Constant	INVALID_COMPARISON
SAP Sybase Error Number	2338
SQL State	52W25
SQL Code	-710L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	An attempt was made to compare two arguments that do not support comparison. For example, it is not valid to compare a Java object with another Java object, unless the class of the object supports a valid compareTo method.

Error 711	"Incorrect database store DLL (%1) version"
Constant	STORE_VERSION_MISMATCH
SAP Sybase Error Number	2340
SQL State	08W47
SQL Code	-711L
ODBC 2 State	ERROR

Error 711	"Incorrect database store DLL (%1) version"
ODBC 3 State	ERROR
Severity Code	19 on page 2
Parameter 1	The name of the database store DLL.
Probable Cause	The database store DLL and server DLL versions do not match.

Error 712	"External login for server '%1' could not be found"
Constant	OMNI_EXTLOGIN_NOT_FOUND
SAP Sybase Error Number	2339
SQL State	WO013
SQL Code	-712L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	11 on page 2
Parameter 1	The name of the remote server.
Probable Cause	An external login for the server and user does not exist.

Error 715	"Contents of backup files are inconsistent"
Constant	RESTORE_INCONSISTENT
SAP Sybase Error Number	2344
SQL State	WB006
SQL Code	-715L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Probable Cause	During a RESTORE, the contents of a backup that was done to two or more disk or tape devices were found to be inconsistent.

Error 716	"Backup file format is invalid"
Constant	RESTORE_INVALID_FORMAT

Error 716	"Backup file format is invalid"
SAP Sybase Error Number	2345
SQL State	WB007
SQL Code	-716L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	21 on page 2
Probable Cause	The format of an archive file to be used during a RESTORE is invalid.

Error 717	"RESTORE unable to open file '%1'"
Constant	RESTORE_UNABLE_TO_OPEN
SAP Sybase Error Number	2346
SQL State	WB008
SQL Code	-717L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	21 on page 2
Parameter 1	File name of database file.
Probable Cause	RESTORE was unable to open one of the database files.

Error 718	"RESTORE unable to write to file '%1'"
Constant	RESTORE_UNABLE_TO_WRITE
SAP Sybase Error Number	2347
SQL State	WB009
SQL Code	-718L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	21 on page 2
Parameter 1	File name of database file.

Error 718	"RESTORE unable to write to file '%1'"
Probable Cause	RESTORE was unable to write to one of the database files.

Error 719	"RESTORE unable to start database '%1'"
Constant	RESTORE_UNABLE_TO_START
SAP Sybase Error Number	2348
SQL State	WB010
SQL Code	-719L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	21 on page 2
Parameter 1	File name of database file.
Probable Cause	After a RESTORE, the resulting database could not be started.

Error 720	"VALIDATE statement must refer to a base table"
Constant	CANNOT_VALIDATE_OBJECT
SAP Sybase Error Number	2349
SQL State	42W51
SQL Code	-720L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	The VALIDATE statement must refer to a local base table; it cannot refer to a view, an SAP Sybase IQ table, or an object on a remote server.

Error 721	"The data type specified for column '%1' is not compatible with the actual data type"
Constant	OMNI_DATATYPE_MISMATCH
SAP Sybase Error Number	2354

Error 721	"The data type specified for column '%1' is not compatible with the actual data type"
SQL State	WO015
SQL Code	-721L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	12 on page 2
Parameter 1	The name of the column.
Probable Cause	The data type of the column specified in the CREATE EXISTING statement is not compatible with the actual data type of the column in the remote table.

Error 722	"The column '%1' does not exist in the remote table"
Constant	OMNI_NOSUCH_COLUMN
SAP Sybase Error Number	2355
SQL State	WO016
SQL Code	-722L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	11 on page 2
Parameter 1	The name of the column.
Probable Cause	The column specified in the CREATE EXISTING statement does not exist in the remote table.

Error 723	"The length specified for column '%1' is different than the actual length"
Constant	OMNI_LENGTH_MISMATCH
SAP Sybase Error Number	2356
SQL State	WO017
SQL Code	-723L
ODBC 2 State	OK

Error 723	"The length specified for column '%1' is different than the actual length"
ODBC 3 State	OK
Severity Code	16 on page 2
Parameter 1	The name of the column.
Probable Cause	The length of the column specified in the CREATE EXISTING statement is different than the length of the column in the remote table.

Error 724	"NULL attribute mismatch for column '%1'"
Constant	OMNI_NULL_MISMATCH
SAP Sybase Error Number	2357
SQL State	WO018
SQL Code	-724L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	16 on page 2
Parameter 1	The name of the column.
Probable Cause	The NULL attribute of the column specified in the CREATE EXISTING statement differs from the NULL attribute of the actual column.

Error 725	"Identity attribute mismatch for column '%1'"
Constant	OMNI_IDENTITY_MISMATCH
SAP Sybase Error Number	2358
SQL State	WO019
SQL Code	-725L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	16 on page 2
Parameter 1	The name of the column.

Error 725	"Identity attribute mismatch for column '%1'"
Probable Cause	The identity attribute of the column specified in the CREATE EXISTING statement differs from the identity attribute of the actual column.

Error 726	"The table specification '%1' identifies more than one remote table"
Constant	OMNI_RMT_TABLE_NOTUNIQUE
SAP Sybase Error Number	2359
SQL State	WO020
SQL Code	-726L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	11 on page 2
Parameter 1	The complete name of the remote table.
Probable Cause	More than one table was found on the remote server for the given table specification. Add a database or owner name to the specification.

Error 727	"The optimizer was unable to construct a valid access plan"
Constant	CANNOT_OPTIMIZE_QUERY
SAP Sybase Error Number	2362
SQL State	WI010
SQL Code	-727L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	18 on page 2
Probable Cause	The database server was unable to construct a valid access plan for the given request. This is a SQL Anywhere internal error. If it can be reproduced, it should be reported to SAP Sybase. You may be able to work around this problem by modifying the query statement.

Error 728	"Update operation attempted on non-updatable remote query"
Constant	NON_UPDATEABLE_EXT_TAB
SAP Sybase Error Number	2372
SQL State	42W35
SQL Code	-728L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	15 on page 2
Probable Cause	You attempted an update or delete operation on a remote table that is currently not supported. Examples of such operations include positioned updates or deletes and updates or deletes that involve a join between local and proxy tables. Updates or deletes that involve a join between proxy tables on different remote servers will also give this error.

Error 729	"The specified foreign key (%1) cannot be enforced"
Constant	UNENFORCEABLE_FOREIGN_KEY
SAP Sybase Error Number	2373
SQL State	23507
SQL Code	-729L
ODBC 2 State	23000
ODBC 3 State	23000
Severity Code	16 on page 2
Parameter 1	Name of the foreign key.
Probable Cause	You attempted to create a foreign key that cannot be enforced. To be enforceable, the primary and foreign table for the specified key must exist on the same server. You can use the UNENFORCED keyword to create a foreign key specification that is not to be enforced.

Error 730	"Invalid JAR file"
Constant	BAD_JAR_FILE

Error 730	"Invalid JAR file"
SAP Sybase Error Number	2374
SQL State	WP010
SQL Code	-730L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	A file passed to the INSTALL JAVA statement was not a valid JAR file.

Error 731	"Cannot drop a user that owns objects involved in replication"
Constant	USER_OWNS_REPLICATED_OBJECTS
SAP Sybase Error Number	2377
SQL State	55W06
SQL Code	-731L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	You attempted to drop a user that is the creator of a database object involved in replication. For example, the user may own a table that is part of a publication.

Messages 732 through 760

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 732	"Creating remote tables with computed columns is not supported"
Constant	OMNI_COMPUTED_NOT_SUPPORTED
SAP Sybase Error Number	2366

Error 732	"Creating remote tables with computed columns is not supported"
SQL State	WO021
SQL Code	-732L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	12 on page 2
Probable Cause	Computed columns are not supported in CREATE TABLE statements that specify a remote location.

Error 733	"Number of columns allowing NULLs exceeds limit"
Constant	TOO_MANY_NULL_COLUMNS
SAP Sybase Error Number	2378
SQL State	23504
SQL Code	-733L
ODBC 2 State	23000
ODBC 3 State	23000
Severity Code	16 on page 2
Probable Cause	You attempted to create or modify a table definition such that the number of columns that allow NULLS is now more than the limit on such columns. The limit is a function of database page size and is approximately 8*(page-size - 30).

Error 734	"Cannot update or delete an all-NULL row from table '%1'"
Constant	CANNOT_UPDATE_NULL_ROW
SAP Sybase Error Number	2379
SQL State	09W08
SQL Code	-734L
ODBC 2 State	42000

Error 734	"Cannot update or delete an all-NULL row from table '%1'"
ODBC 3 State	42000
Severity Code	<i>16 on page 2</i>
Parameter 1	The name of the table that cannot be modified.
Probable Cause	You attempted to modify or delete a row in the specified table, which is part of the NULL-supplying side of an outer join. However, the cursor is currently positioned on a derived row that contains an all-NULL row for this table, which is the result of the failure of one or more ON conditions to evaluate to TRUE. Verify that the UPDATE or DELETE statement is correct.

Error 735	"Invalid parameter"
Constant	INVALID_PARAMETER
SAP Sybase Error Number	2030
SQL State	08W24
SQL Code	-735L
ODBC 2 State	08004
ODBC 3 State	08004
Severity Code	<i>18 on page 2</i>
Probable Cause	An error occurred while evaluating a parameter.

Error 736	"The data type of column or variable '%1' is not supported"
Constant	OMNI_UNSUPPORTED_DATATYPE
SAP Sybase Error Number	2367
SQL State	WO022
SQL Code	-736L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>12 on page 2</i>
Parameter 1	The name of the column or variable.

Error 736	"The data type of column or variable '%1' is not supported"
Probable Cause	The column is defined with a data type that is not supported for remote tables or the variable is defined with a datatype that is not supported for using and location clauses.

Error 737	"Signature '%1' does not match procedure parameters"
Constant	SIGNATURE_MISMATCH
SAP Sybase Error Number	2382
SQL State	42W54
SQL Code	-737L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	The value of the signature.
Probable Cause	The number of types in the signature must match the number of procedure parameters. If a DYNAMIC RESULT SETS clause was specified, the number of dynamic result sets must match the quantity found in the signature.

Error 738	"Password must be at least %1 characters"
Constant	PASSWORD_TOO_SHORT
SAP Sybase Error Number	2383
SQL State	54W07
SQL Code	-738L
ODBC 2 State	37000
ODBC 3 State	54000
Severity Code	14 on page 2
Probable Cause	The password is shorter than that allowed by the current min_password_length option setting.

Error 739	"db_init has not been called or the call to db_init failed"
Constant	DB_INIT_NOT_CALLED

Error 739	"db_init has not been called or the call to db_init failed"
SAP Sybase Error Number	2386
SQL State	55W07
SQL Code	-739L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The SQLCA passed to a dblink entry point has not been initialized by a call to db_init or the call to db_init failed.

Error 740	"The communications environment could not be created"
Constant	FAILED_TO_CREATE_STREAMS_ENV
SAP Sybase Error Number	2385
SQL State	WW024
SQL Code	-740L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The communications environment could not be created. Either there are insufficient resources to create the environment or the language resource file cannot be found.

Error 744	"Invalid SAP Sybase IQ database command line option or parameter value: %1"
Constant	IQ_INVALID_COMMAND_LINE
SAP Sybase Error Number	2390
SQL State	08W51
SQL Code	-744L
ODBC 2 State	08001
ODBC 3 State	08001

Error 744	"Invalid SAP Sybase IQ database command line option or parameter value: %1"
Severity Code	<i>18</i> on page 2
Parameter 1	The command line option that is invalid.
Probable Cause	An invalid command line option was used. The option began with -iq, but is either invalid or contained a bad parameter.

Error 745	"Cannot initialize SAP Sybase IQ memory manager: %1"
Constant	IQ_MEMORY_MANAGER_FAILED
SAP Sybase Error Number	2391
SQL State	08W52
SQL Code	-745L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	<i>18</i> on page 2
Parameter 1	A message describing the error that occurred.
Probable Cause	System V shared memory was requested but could not be allocated.

Error 746	"Cannot allocate System V resources"
Constant	IQ_SYSTEM_V_FAILURE
SAP Sybase Error Number	2392
SQL State	08W53
SQL Code	-746L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	<i>18</i> on page 2
Probable Cause	SAP Sybase IQ was unable to allocate System V resources. Delete unused System V semaphores and shared memory segments or increase operating system configuration values for these resources.

Error 749	"Feature not available with UltraLite"
Constant	NOT_SUPPORTED_IN_ULTRALITE
SAP Sybase Error Number	2395
SQL State	0AW07
SQL Code	-749L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	You attempted to execute a statement or use a feature that is not supported in an UltraLite database.

Error 750	"User owns procedures in use"
Constant	USER_OWNS_PROCEDURES_IN_USE
SAP Sybase Error Number	2396
SQL State	42W55
SQL Code	-750L
ODBC 2 State	40001
ODBC 3 State	40001
Severity Code	16 on page 2
Probable Cause	You attempted to drop a user that owns a procedure being used by other active users of the database.

Error 751	"User owns tables in use"
Constant	USER_OWNS_TABLES_IN_USE
SAP Sybase Error Number	2397
SQL State	42W56
SQL Code	-751L
ODBC 2 State	40001
ODBC 3 State	40001

Error 751	"User owns tables in use"
Severity Code	<i>16</i> on page 2
Probable Cause	You attempted to REVOKE CONNECT from a user that owns a table being used by other active users of the database.

Error 754	"Parse error: %1"
Constant	INVALID_DSN_NAME
SAP Sybase Error Number	2400
SQL State	08W54
SQL Code	-754L
ODBC 2 State	08004
ODBC 3 State	08004
Severity Code	<i>18</i> on page 2
Parameter 1	The invalid data source name.
Probable Cause	An invalid data source name was used in the connection string.

Error 755	"You cannot synchronize or upgrade with uncommitted transactions"
Constant	UNCOMMITTED_TRANSACTIONS
SAP Sybase Error Number	2401
SQL State	0AW08
SQL Code	-755L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	<i>16</i> on page 2
Probable Cause	You attempted to synchronize or upgrade the schema of an UltraLite database and there are changes in the UltraLite database that have not been committed.

Error 757	"Modifications not permitted for read-only database"
Constant	READ_ONLY_DATABASE

Error 757	"Modifications not permitted for read-only database"
SAP Sybase Error Number	2404
SQL State	55W08
SQL Code	-757L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	14 on page 2
Probable Cause	You attempted an update operation on a database that was declared as read-only.

Error 759	"SQLDA data type invalid"
Constant	SQLDA_INVALID_DATATYPE
SAP Sybase Error Number	2406
SQL State	07W05
SQL Code	-759L
ODBC 2 State	07001
ODBC 3 State	07W05
Severity Code	16 on page 2
Probable Cause	The data type specified for a SQLDA variable is invalid.

Error 760	"Invalid SQL identifier"
Constant	INVALID_SQL_IDENTIFIER
SAP Sybase Error Number	2407
SQL State	07W06
SQL Code	-760L
ODBC 2 State	07001
ODBC 3 State	07W06
Severity Code	16 on page 2

Error 760	"Invalid SQL identifier"
Probable Cause	An invalid identifier was supplied through the C language interface. For example, you may have supplied a NULL string for a cursor name.

Messages 761 through 785

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 761	"Server capability name '%1' could not be found in the database."
Constant	CAPABILITY_NOT_FOUND
SAP Sybase Error Number	2343
SQL State	WO014
SQL Code	-761L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The name of server capability.
Probable Cause	An ALTER SERVER statement was attempted on a capability that was not defined.

Error 764	"Server not found and unable to automatically start"
Constant	UNABLE_TO_CONNECT_OR_START
SAP Sybase Error Number	2410
SQL State	08W55
SQL Code	-764L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	<i>11 on page 2</i>

Error 764	"Server not found and unable to automatically start"
Probable Cause	The client could not connect to a server, and was unable to automatically start a server. The automatic start may have failed because no database file was specified.

Error 765	"Synchronization message type '%1' not found"
Constant	NOT_SYNC_TYPE
SAP Sybase Error Number	2411
SQL State	5RW11
SQL Code	-765L
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	16 on page 2
Parameter 1	Name of synchronization message type.
Probable Cause	You referred to a synchronization message type that is not defined in this database.

Error 766	"View references '%1', which is a temporary object. Views can only refer to permanent objects"
Constant	VIEW_OVER_TEMP_OBJECT
SAP Sybase Error Number	2413
SQL State	42U00
SQL Code	-766L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Temporary object name.
Probable Cause	Views must refer only to permanent objects, not to temporary objects such as local temporary tables.

Error 767	"Cannot find synchronization subscription with the name '%1'"
Constant	SYNCHRONIZATION_NOT_FOUND
SAP Sybase Error Number	2414
SQL State	5RW12
SQL Code	-767L
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	16 on page 2
Parameter 1	Name of the subscription.
Probable Cause	You misspelled the name of a synchronization subscription or you did not qualify it correctly with a user name.

Error 768	"Cannot subscribe to '%1'"
Constant	CANNOT_SUBSCRIBE
SAP Sybase Error Number	2415
SQL State	5RW13
SQL Code	-768L
ODBC 2 State	42000
ODBC 3 State	42S02
Severity Code	16 on page 2
Parameter 1	Name of the publication.
Probable Cause	Some publications cannot be subscribed to, such as a synchronization publication.

Error 769	"Cannot modify synchronization entry using ALTER PUBLICATION"
Constant	CANNOT_MODIFY_SYNC_AS_PUB
SAP Sybase Error Number	2416
SQL State	5RW14

Error 769	"Cannot modify synchronization entry using ALTER PUBLICATION"
SQL Code	-769L
ODBC 2 State	42000
ODBC 3 State	42S02
Severity Code	16 on page 2
Probable Cause	You attempted to modify a synchronization entry using an ALTER PUBLICATION statement.

Error 770	"Cannot modify publication entry using ALTER SYNCHRONIZATION"
Constant	CANNOT_MODIFY_PUB_AS_SYNC
SAP Sybase Error Number	2417
SQL State	5RW15
SQL Code	-770L
ODBC 2 State	42000
ODBC 3 State	42S02
Severity Code	16 on page 2
Probable Cause	You attempted to modify a publication entry using an ALTER SYNCHRONIZATION statement.

Error 771	"Event '%1' not found"
Constant	EVENT_NOT_FOUND
SAP Sybase Error Number	2418
SQL State	WE001
SQL Code	-771L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	11 on page 2
Parameter 1	Name of the event that could not be found.

Error 771	"Event '%1' not found"
Probable Cause	You have attempted to reference an event with a name that does not exist in the database.

Error 772	"Event '%1' already exists"
Constant	EVENT_ALREADY_EXISTS
SAP Sybase Error Number	2419
SQL State	WE002
SQL Code	-772L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the event that already exists.
Probable Cause	You have attempted to create an event with a name that already exists in the database.

Error 773	"Schedule '%1' for event '%2' not found"
Constant	SCHEDULE_NOT_FOUND
SAP Sybase Error Number	2420
SQL State	WE003
SQL Code	-773L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	11 on page 2
Parameter 1	Name of the schedule that could not be found.
Parameter 2	Name of the event being scheduled.
Probable Cause	You have attempted to reference a schedule with a name that does not exist in the database for the named event.

Error 774	"Schedule '%1' for event '%2' already exists"
Constant	SCHEDULE_ALREADY_EXISTS
SAP Sybase Error Number	2421
SQL State	WE004
SQL Code	-774L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the schedule that already exists.
Parameter 2	Name of the event being scheduled.
Probable Cause	You have attempted to create a schedule with a name that already exists in the database for the named event.

Error 777	"Cannot synchronize table '%1' since it does not have a primary key"
Constant	CANNOT_SYNC_TABLE_WITHOUT_PK
SAP Sybase Error Number	2424
SQL State	5RW16
SQL Code	-777L
ODBC 2 State	42000
ODBC 3 State	42S02
Severity Code	16 on page 2
Parameter 1	Name of the table.
Probable Cause	Tables being synchronized must contain a primary key.

Error 778	"Must include primary key for table '%1' in the synchronization"
Constant	PK_NOT_IN_SYNC_ARTICLE
SAP Sybase Error Number	2425
SQL State	5RW17

Error 778	"Must include primary key for table '%1' in the synchronization"
SQL Code	-778L
ODBC 2 State	42000
ODBC 3 State	42S02
Severity Code	16 on page 2
Parameter 1	Name of the table.
Probable Cause	The primary key of the table must be included in the synchronization entry.

Error 779	"Cannot create synchronization entry for table '%1' with BLOB primary key"
Constant	BLOB_IN_SYNC_TABLE_PK
SAP Sybase Error Number	2426
SQL State	5RW18
SQL Code	-779L
ODBC 2 State	42000
ODBC 3 State	42S02
Severity Code	16 on page 2
Parameter 1	Name of the table.
Probable Cause	You attempted to create a synchronization entry on a table with a BLOB primary key.

Error 780	"Cannot update primary key for table '%1' involved in a publication"
Constant	ARTICLE_PK_CANNOT_BE_UPDATED
SAP Sybase Error Number	2427
SQL State	5RW19
SQL Code	-780L
ODBC 2 State	42000

Error 780	"Cannot update primary key for table '%1' involved in a publication"
ODBC 3 State	42S02
Severity Code	<i>16</i> on page 2
Parameter 1	Name of the table.
Probable Cause	The primary key of a table involved in a publication cannot be updated. The prevent_article_pkey_update database option can be set to Off to allow updates to the primary key of the table involved in the publication.

Error 782	"Cannot register '%1' since another exclusive instance is running"
Constant	SAME_EXCLUSIVE_APP_RUNNING
SAP Sybase Error Number	2429
SQL State	5RW21
SQL Code	-782L
ODBC 2 State	42000
ODBC 3 State	42S02
Severity Code	<i>16</i> on page 2
Parameter 1	Name of the application.
Probable Cause	You attempted to start an application, but another exclusive instance of the same application is already registered.

Error 783	"Cannot register another '%1' as an exclusive application"
Constant	SAME_APP_RUNNING
SAP Sybase Error Number	2430
SQL State	5RW22
SQL Code	-783L
ODBC 2 State	42000
ODBC 3 State	42S02
Severity Code	<i>16</i> on page 2

Error 783	"Cannot register another '%1' as an exclusive application"
Parameter 1	Name of the application.
Probable Cause	You attempted to register an exclusive application but another instance of the same application is already registered.

Error 784	"Cannot register connection because of invalid application cookie"
Constant	CANNOT_REG_CONN
SAP Sybase Error Number	2431
SQL State	5RW23
SQL Code	-784L
ODBC 2 State	42000
ODBC 3 State	42S02
Severity Code	16 on page 2
Probable Cause	Application registration cannot be found for the given cookie.

Error 785	"Cannot deregister application because of invalid cookie"
Constant	DEREG_APP_NOT_FOUND
SAP Sybase Error Number	2432
SQL State	5RW24
SQL Code	-785L
ODBC 2 State	42000
ODBC 3 State	42S02
Severity Code	16 on page 2
Probable Cause	The application has not been registered successfully or it was previously deregistered.

786 - 1005

Messages 786 through 809

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 786	"Cannot deregister '%1' since active registered connection exists"
Constant	DEREG_APP_IN_USE
SAP Sybase Error Number	2433
SQL State	5RW25
SQL Code	-786L
ODBC 2 State	42000
ODBC 3 State	42S02
Severity Code	16 on page 2
Parameter 1	Name of the application.
Probable Cause	You attempted to deregister an application while there are still active connections registered to that application.

Error 787	"Current connection is already registered to '%1' as '%2'"
Constant	CONN_ALREADY_REGISTERED
SAP Sybase Error Number	2434
SQL State	5RW26
SQL Code	-787L
ODBC 2 State	42000
ODBC 3 State	42S02
Severity Code	16 on page 2
Parameter 1	Name of the application.
Parameter 2	Registered connection label.
Probable Cause	You attempted to register this connection more than once.

Error 788	"Another connection has already registered as '%1'"
Constant	NOT_UNIQUE_CONN_REG_LABEL
SAP Sybase Error Number	2435
SQL State	5RW27
SQL Code	-788L
ODBC 2 State	42000
ODBC 3 State	42S02
Severity Code	16 on page 2
Parameter 1	Registered connection label.
Probable Cause	You attempted to register a connection with a label already in use for the same application.

Error 789	"Cannot register '%1' since registration cookie exhausted"
Constant	APP_REG_COOKIE_EXHAUSTED
SAP Sybase Error Number	2436
SQL State	5RW28
SQL Code	-789L
ODBC 2 State	42000
ODBC 3 State	42S02
Severity Code	16 on page 2
Parameter 1	Name of the application.
Probable Cause	Cannot register the application until one is unregistered.

Error 790	"Cannot register connection to '%1' since automatic label exhausted"
Constant	CONN_REG_AUTO_LABEL_EXHAUSTED
SAP Sybase Error Number	2437
SQL State	5RW29
SQL Code	-790L

Error 790	"Cannot register connection to '%1' since automatic label exhausted"
ODBC 2 State	42000
ODBC 3 State	42S02
Severity Code	<i>16 on page 2</i>
Parameter 1	Name of the application.
Probable Cause	You may register using a specified label instead.

Error 791	"Invalid day of week or month '%1' for event '%2'"
Constant	INVALID_EVENT_DAY
SAP Sybase Error Number	2438
SQL State	WE005
SQL Code	-791L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>15 on page 2</i>
Parameter 1	Day-of-week name or day-of-month number.
Parameter 2	Name of the event being scheduled.
Probable Cause	You have attempted to create a schedule with an invalid day-of-week name or day-of-month number.

Error 792	"Invalid time '%1' for event '%2'"
Constant	INVALID_EVENT_TIME
SAP Sybase Error Number	2439
SQL State	WE006
SQL Code	-792L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>15 on page 2</i>

Error 792	"Invalid time '%1' for event '%2'"
Parameter 1	Time value.
Parameter 2	Name of the event being scheduled.
Probable Cause	You have attempted to create a schedule with an invalid start or stop time.

Error 793	"Invalid start date/time for event '%1'"
Constant	INVALID_EVENT_START
SAP Sybase Error Number	2440
SQL State	WE007
SQL Code	-793L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	15 on page 2
Parameter 1	Name of the event being scheduled.
Probable Cause	You have specified an event starting date that is invalid.

Error 794	"Synchronization server failed to commit the upload"
Constant	UPLOAD_FAILED_AT_SERVER
SAP Sybase Error Number	2441
SQL State	0AW09
SQL Code	-794L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	You attempted to synchronize an UltraLite database. During the synchronization session, a complete upload stream was sent that could not be committed to the consolidated database. The reason for the upload failure can be found in the synchronization log file.

Error 797	"Synchronization option '%1' contains semicolon, equal sign, curly brace, or is null"
Constant	BAD_SYNC_OPTION_VALUE
SAP Sybase Error Number	2444
SQL State	5RW32
SQL Code	-797L
ODBC 2 State	42000
ODBC 3 State	42S02
Severity Code	16 on page 2
Parameter 1	The name of the synchronization option.
Probable Cause	You attempted to set a synchronization option with an invalid value.

Error 799	"DTC transactions are not supported on this platform"
Constant	DTC_TRANSACTIONS_NOT_SUPPORTED
SAP Sybase Error Number	2446
SQL State	0AW10
SQL Code	-799L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You tried to enlist a DTC transaction on a platform that does not support this feature.

Error 800	"Cannot commit or rollback while enlisted in a transaction"
Constant	CANNOT_COMMIT_OR_ROLLBACK_WHILE_ENLISTED
SAP Sybase Error Number	2447
SQL State	55W09
SQL Code	-800
ODBC 2 State	ERROR

Error 800	"Cannot commit or rollback while enlisted in a transaction"
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	You tried to explicitly commit or rollback on a connection that is enlisted in a transaction. You must use the Commit/Abort protocol of the transaction instead.

Error 801	"Cannot enlist in a transaction while already enlisted in a transaction"
Constant	CANNOT_ENLIST_WHILE_ALREADY_ENLISTED
SAP Sybase Error Number	2448
SQL State	55W10
SQL Code	-801L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	You tried to enlist a second transaction on a connection that is already enlisted in a transaction.

Error 802	"Cannot enlist in a transaction with uncommitted data pending"
Constant	CANNOT_ENLIST_WITH_UNCOMMITTED_DATA
SAP Sybase Error Number	2449
SQL State	55W11
SQL Code	-802L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	You tried to enlist a transaction on a connection that has pending uncommitted data.

Error 803	"Unable to enlist transaction; DTC may be down"
Constant	FAILED_TO_ENLIST
SAP Sybase Error Number	2450
SQL State	WL005
SQL Code	-803L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	17 on page 2
Probable Cause	You tried to enlist a transaction but DTC does not seem to be available at this time.

Error 804	"Unable to re-enlist transaction; DTC may be down"
Constant	FAILED_TO_REENLIST
SAP Sybase Error Number	2451
SQL State	WL006
SQL Code	-804L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	17 on page 2
Probable Cause	You tried to recover a transaction but DTC does not seem to be available at this time.

Error 805	"Synchronization option '%1' not found"
Constant	SYNC_OPTION_NOT_FOUND
SAP Sybase Error Number	2452
SQL State	5RW33
SQL Code	-805L
ODBC 2 State	42000
ODBC 3 State	42S02

Error 805	"Synchronization option '%1' not found"
Severity Code	<i>16</i> on page 2
Parameter 1	The name of the synchronization option.
Probable Cause	You attempted to delete an undefined synchronization option.

Error 806	"System event type '%1' not found"
Constant	EVENT_TYPE_NOT_FOUND
SAP Sybase Error Number	2453
SQL State	WE008
SQL Code	-806L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>11</i> on page 2
Parameter 1	Name of the system event type that could not be found.
Probable Cause	You have attempted to create an event with a system event type name that does not exist in the database.

Error 807	"Host variables must not be used within a batch"
Constant	HOSTVARS_IN_BATCH
SAP Sybase Error Number	2454
SQL State	07W07
SQL Code	-807L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>15</i> on page 2
Probable Cause	You have attempted to execute a batch that contains host variable references. Host variables are not supported within a batch.

Error 809	"Synchronization option is too long"
Constant	SYNC_OPTION_TOO_LONG

Error 809	"Synchronization option is too long"
SAP Sybase Error Number	2456
SQL State	5RW34
SQL Code	-809L
ODBC 2 State	42000
ODBC 3 State	42S02
Severity Code	16 on page 2
Probable Cause	Synchronization option list cannot be longer than the database page size.

Messages 810 through 829

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 810	"External object '%1' not found"
Constant	EXTENV_OBJECT_NOT_FOUND
SAP Sybase Error Number	2457
SQL State	42W57
SQL Code	-810L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Name of the Java class or external object.
Probable Cause	The Java class or external object with this name does not exist in the database.

Error 811	"JAR '%1' not found"
Constant	JAR_NOT_FOUND
SAP Sybase Error Number	2458
SQL State	42W58
SQL Code	-811L

Error 811	"JAR '%1' not found"
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Name of the JAR.
Probable Cause	The JAR with this name does not exist in the database.

Error 812	"The SELECT list for the derived table '%1' has no expression to match '%2'"
Constant	NO_MATCHING_SELECT_ITEM
SAP Sybase Error Number	2459
SQL State	42W59
SQL Code	-812L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Parameter 1	Name of the derived table.
Parameter 2	Name of the alias for which there is no matching expression.
Probable Cause	The specified alias from the derived table's AS clause has no matching expression from the SELECT statement for that derived table. Ensure that each SELECT list item has a matching alias in the derived table's AS clause, and vice-versa.

Error 813	"FOR UPDATE has been incorrectly specified for a READ ONLY cursor"
Constant	NON_UPDATEABLE_CURSOR
SAP Sybase Error Number	2460
SQL State	42W36
SQL Code	-813L

Error 813	"FOR UPDATE has been incorrectly specified for a READ ONLY cursor"
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	15 on page 2
Probable Cause	You attempted to declare a cursor FOR UPDATE on a query that is not updatable. Queries that contain DISTINCT, GROUP BY, HAVING, INTERSECT, EXCEPT, or UNION, or that contain aggregate functions are read-only. If the ansi_update_constraints option is on, then queries that contain a join are read-only. If the query references a view then the view may be non-updatable.

Error 814	"Cannot update column '%1' since it appears in the ORDER BY clause"
Constant	CANNOT_UPDATE_ORDER_BY_COLUMN
SAP Sybase Error Number	2461
SQL State	42W37
SQL Code	-814L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	15 on page 2
Parameter 1	Name of the column that appears in the ORDER BY clause.
Probable Cause	You attempted to update a column that appears in the ORDER BY clause. The ansi_update_constraints option controls whether this update is allowed.

Error 815	"Cannot update column '%1' since it does not appear in the SELECT clause"
Constant	UPDATE_NOT_IN_SELECT
SAP Sybase Error Number	2462
SQL State	42W38
SQL Code	-815L

Error 815	"Cannot update column '%1' since it does not appear in the SELECT clause"
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	15 on page 2
Parameter 1	Name of the column that does not appear in the SELECT clause.
Probable Cause	You attempted to update a column that does not explicitly appear in the SELECT list. The ansi_update_constraints option controls whether this update is allowed.

Error 816	"Specified database file already in use"
Constant	FILE_IN_USE
SAP Sybase Error Number	2463
SQL State	08W56
SQL Code	-816L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	14 on page 2
Probable Cause	The database server could not start the specified database because the file is already in use.

Error 817	"Too many temporary tables in connection"
Constant	TOO_MANY_TEMP_TABLES
SAP Sybase Error Number	2464
SQL State	52W41
SQL Code	-817L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2

Error 817	"Too many temporary tables in connection"
Probable Cause	A CREATE TABLE or DECLARE LOCAL TEMPORARY TABLE statement attempted to create a temporary table, but the resulting number of distinct table IDs used for temporary tables in the current connection would exceed the limit.

Error 818	"Version 'V%1' interface used by external function call '%2' is not supported for execution in the current context."
Constant	INCOMPATIBLE_EXTERNAL_CALL
SAP Sybase Error Number	2465
SQL State	WW026
SQL Code	-818L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	API version of the external function that is being called.
Parameter 2	Name of the external function that is being called.
Probable Cause	You attempted to call an external function. The attempt to load the associated library failed because of incompatibility with the server. Incompatibility may arise because the dynamic library is using an external function API that is either not supported by the server or is newer than the one supported by the server. It may also arise if the external API is not compatible with the data in the current context.

Error 819	"Table '%1' is part of a synchronization subscription and can only be ALTERed within a synchronization schema change"
Constant	SYNC_CONTAINS_TABLE
SAP Sybase Error Number	2466
SQL State	5RW35
SQL Code	-819L
ODBC 2 State	42000

Error 819	"Table '%1' is part of a synchronization subscription and can only be ALTERed within a synchronization schema change"
ODBC 3 State	42S02
Severity Code	16 on page 2
Parameter 1	The name of the table.
Probable Cause	A table belonging to a synchronization subscription cannot be altered except within a synchronization schema change or by using dbmlsync.

Error 820	"Invalid scroll position '%1'"
Constant	INVALID_POSITION
SAP Sybase Error Number	2467
SQL State	24504
SQL Code	-820L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The scroll position that is invalid.
Probable Cause	You attempted to scroll to a position that is not supported. Scroll positions must be between -2147483647 and 2147483646.

Error 821	"DbSPACE for table '%1' not found"
Constant	DBSPACE_FOR_TABLE_UNAVAILABLE
SAP Sybase Error Number	2468
SQL State	52W19
SQL Code	-821L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	11 on page 2

Error 821	"Dbospace for table '%1' not found"
Parameter 1	Name of the table whose dbospace could not be found.
Probable Cause	You tried to access a table in a dbospace that the database server could not find. You may need to change the file name associated with the dbospace using the ALTER DBSPACE statement.

Error 822	"Table '%1' is already included"
Constant	TABLE_ALREADY_INCLUDED
SAP Sybase Error Number	2469
SQL State	5RW36
SQL Code	-822L
ODBC 2 State	42000
ODBC 3 State	42S02
Severity Code	<i>16 on page 2</i>
Parameter 1	The name of the table.
Probable Cause	You attempted to add or modify a publication or synchronization definition such that the same table is included twice.

Error 823	"Cannot handle expressions involving remote tables inside stored procedures"
Constant	OMNI_EXPRESSION_IN_PROC
SAP Sybase Error Number	2470
SQL State	WO023
SQL Code	-823L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>12 on page 2</i>
Probable Cause	The server encountered an expression involving remote tables inside a stored procedure. The expression was too complicated to process.

Error 824	"Illegal reference to correlation name '%1'"
Constant	INVALID_CORRELATION_NAME_REFERENCE
SAP Sybase Error Number	2471
SQL State	42U01
SQL Code	-824L
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	15 on page 2
Parameter 1	The correlation name that is incorrectly referenced.
Probable Cause	Your query contains a reference in a table expression to a correlation name that is not contained in that table expression.

Error 825	"Previous error lost before RESIGNAL"
Constant	PREVIOUS_ERROR_LOST
SAP Sybase Error Number	2472
SQL State	WP011
SQL Code	-825L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	A RESIGNAL statement in an exception handler of a stored procedure was executed but the context of the previous error was unavailable. A possible cause of this error is a SELECT statement that returns a result set in the exception handler.

Error 826	"Database upgrade not possible; RowGenerator table not owned by user dbo"
Constant	DBO_DOES_NOT_OWN_ROWGENERATOR
SAP Sybase Error Number	2473

Error 826	"Database upgrade not possible; RowGenerator table not owned by user dbo"
SQL State	08W57
SQL Code	-826L
ODBC 2 State	08004
ODBC 3 State	08004
Severity Code	21 on page 2
Probable Cause	An attempt to upgrade a database failed. The RowGenerator table is not owned by user dbo.

Error 827	"Database upgrade not possible; user tables have table IDs in system table range"
Constant	USER_TABLES_IN_SYSTEM_RANGE
SAP Sybase Error Number	2474
SQL State	08W58
SQL Code	-827L
ODBC 2 State	08004
ODBC 3 State	08004
Severity Code	21 on page 2
Probable Cause	An attempt to upgrade a database failed. User table IDs should not be in system table ID range.

Error 828	"A conflict with the dbmlsync download phase was detected"
Constant	RECORDING_CONFLICT_DETECTED
SAP Sybase Error Number	2475
SQL State	WW027
SQL Code	-828L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	11 on page 2

Error 828	"A conflict with the dbmlsync download phase was detected"
Probable Cause	Dbmlsync uses this error to detect download phase conflicts with rows modified by other connections.

Error 829	"TLS handshake failure"
Constant	TLS_HANDSHAKE_FAILED
SAP Sybase Error Number	2476
SQL State	08W59
SQL Code	-829L
ODBC 2 State	08S01
ODBC 3 State	08S01
Severity Code	21 on page 2
Probable Cause	The connection failed because of a failure in the TLS handshaking process.

Messages 830 through 854

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 830	"Alias '%1' is not unique"
Constant	ALIAS_NOT_UNIQUE
SAP Sybase Error Number	2477
SQL State	42W60
SQL Code	-830L
ODBC 2 State	37000
ODBC 3 State	ERROR
Severity Code	15 on page 2
Parameter 1	Name of the alias.
Probable Cause	The same alias is used more than once in a SELECT list.

Error 831	"Definition for alias '%1' must appear before its first reference"
Constant	ALIAS_NOT_YET_DEFINED
SAP Sybase Error Number	2478
SQL State	42W61
SQL Code	-831L
ODBC 2 State	37000
ODBC 3 State	ERROR
Severity Code	15 on page 2
Parameter 1	Name of the alias.
Probable Cause	An expression contains a reference to an alias, but the alias is defined later in the SELECT list. The alias definition must appear before its first reference.

Error 832	"Connection error: %1"
Constant	CONNECTION_ERROR
SAP Sybase Error Number	2479
SQL State	08W60
SQL Code	-832L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	16 on page 2
Parameter 1	Description of the connection error.
Probable Cause	An error occurred while attempting to establish a connection with the database server, but before attempting to connect to a database. Failure to initialize a communication link during the connection attempt is an example of this error. Creating a debug log file using the LogFile connection parameter may provide more information.

Error 833	"Row in table '%1' was modified or deleted in BEFORE trigger"
Constant	ROW_REMODIFIED_OR_DELETED
SAP Sybase Error Number	2480
SQL State	42W62
SQL Code	-833L
ODBC 2 State	37000
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the table.
Probable Cause	A BEFORE trigger has updated or deleted the row that caused the trigger to fire, preventing the original operation from completing. The trigger must be re-written so that it does not attempt to change the row via UPDATE or DELETE statements.

Error 834	"Column '%1' not found in table '%2'"
Constant	COLUMN_NOT_FOUND_IN_TABLE
SAP Sybase Error Number	2083
SQL State	52005
SQL Code	-834L
ODBC 2 State	S0002
ODBC 3 State	42S22
Severity Code	11 on page 2
Parameter 1	Name of the column that could not be found.
Parameter 2	Name of the table that was supposed to contain the column.
Probable Cause	You misspelled the name of a column, or the column you are looking for is in a different table.

Error 835	"Event '%1' in use"
Constant	EVENT_IN_USE
SAP Sybase Error Number	2482
SQL State	WE009
SQL Code	-835L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the event that is in use.
Probable Cause	You have attempted to drop an event that is currently in use.

Error 836	"Procedure '%1' is no longer valid"
Constant	PROCEDURE_NO_LONGER_VALID
SAP Sybase Error Number	2483
SQL State	42W63
SQL Code	-836L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Parameter 1	Name of the procedure.
Probable Cause	A procedure definition cannot be loaded from the catalog. Check for tables or columns that have been renamed or that may be reserved words. If this procedure is an internal procedure, you may have an older version. Database upgrade may be needed to run it successfully.

Error 837	"Trigger or foreign key for table '%1' is no longer valid"
Constant	TRIGGER_NO_LONGER_VALID
SAP Sybase Error Number	2484
SQL State	42W64

Error 837	"Trigger or foreign key for table '%1' is no longer valid"
SQL Code	-837L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Parameter 1	Name of the table.
Probable Cause	A trigger definition cannot be loaded from the catalog. Check for tables or columns that have been renamed or that may be reserved words. The trigger may be a system-generated trigger to enforce the referential actions of a foreign key.

Error 838	"TLS initialization on server failed"
Constant	TLS_INIT_FAILED_ON_SRV
SAP Sybase Error Number	2485
SQL State	08W61
SQL Code	-838L
ODBC 2 State	08S01
ODBC 3 State	08S01
Severity Code	21 on page 2
Probable Cause	The connection failed because the initialization of the TLS library on the server failed.

Error 839	"Download failed because of conflicts with existing rows on table '%1' (row: %2)"
Constant	DOWNLOAD_CONFLICT
SAP Sybase Error Number	2486
SQL State	0AW11
SQL Code	-839L
ODBC 2 State	37000
ODBC 3 State	42000

Error 839	"Download failed because of conflicts with existing rows on table '%1' (row: %2)"
Severity Code	<i>16</i> on page 2
Parameter 1	Name of the table with the conflict.
Parameter 2	The value of the primary key of the row that conflicted.
Probable Cause	During synchronization, there was a conflict between one or more rows in the download stream and rows modified locally in the UltraLite database. The download has been rolled back. You can avoid this error by coordinating local database modifications with synchronization, or synchronizing again when the local modifications are complete.

Error 840	"Incorrect or missing encryption key"
Constant	BAD_ENCRYPTION_KEY
SAP Sybase Error Number	2487
SQL State	08W62
SQL Code	-840L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	<i>21</i> on page 2
Probable Cause	The database is encrypted with a key. There was no key given to start the database, or the specified key was incorrect.

Error 843	"Cannot find synchronization user with the name '%1'"
Constant	SYNC_SITE_NOT_FOUND
SAP Sybase Error Number	2490
SQL State	5RW37
SQL Code	-843L
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	<i>16</i> on page 2
Parameter 1	Name of the synchronization user.

Error 843	"Cannot find synchronization user with the name '%1'"
Probable Cause	You misspelled the name of a synchronization site or you did not qualify it correctly with a user name.

Error 845	"Owner '%1' used in a qualified column reference does not match correlation name '%2'"
Constant	INVALID_COLUMN_QUALIFICATION
SAP Sybase Error Number	2492
SQL State	42U02
SQL Code	-845L
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	15 on page 2
Parameter 1	The owner name specified in the column reference.
Parameter 2	The correlation name that is incorrectly referenced.
Probable Cause	Your query contains a qualified column reference to a table name, but either a correlation name has been used for that table, or the owner of the table does not match the owner name specified in the column reference. Remove the owner qualification, and qualify column references only by correlation name.

Error 846	"SET clause for column '%1' used incorrectly"
Constant	INVALID_SET_CLAUSE
SAP Sybase Error Number	2493
SQL State	42U03
SQL Code	-846L
ODBC 2 State	S0002
ODBC 3 State	42S03
Severity Code	15 on page 2
Parameter 1	The SET clause that is invalid.

Error 846	"SET clause for column '%1' used incorrectly"
Probable Cause	Your UPDATE statement contains an invalid SET clause, for example, there are multiple SET clauses for the same column.

Error 849	"Referential integrity actions other than RESTRICT not allowed for temporary tables"
Constant	INVALID_FOREIGN_KEY_ACTION
SAP Sybase Error Number	2496
SQL State	42R01
SQL Code	-849L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	You attempted to specify an unsupported referential integrity action for a temporary table.

Error 850	"Tables related by key constraint must both be permanent, or both be temporary and not created with ON COMMIT DELETE ROWS. For global temporary tables they must both be shared if one is shared."
Constant	INVALID_FOREIGN_KEY_TABLE
SAP Sybase Error Number	2497
SQL State	42R02
SQL Code	-850L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	Tables involved in a key constraint relationship must both be permanent user tables or both be temporary tables not created with ON COMMIT DELETE ROWS. Change the definition of one or both tables using ALTER TABLE.

Error 851	"Decryption error: %1"
Constant	DECRYPT_ERROR
SAP Sybase Error Number	2498
SQL State	08W63
SQL Code	-851L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	11 on page 2
Parameter 1	Description of the error that occurred.
Probable Cause	An error occurred during decryption.

Error 852	"Table name '%1' is ambiguous"
Constant	AMBIGUOUS_TABLE_NAME
SAP Sybase Error Number	2499
SQL State	52W42
SQL Code	-852L
ODBC 2 State	S0013
ODBC 3 State	42S13
Severity Code	16 on page 2
Parameter 1	Name of an ambiguous table.
Probable Cause	A statement has referred to a table name that is not unique. Preface the table name by an owner name.

Error 853	"Cursor not in a valid state"
Constant	CURSOR_INVALID_STATE
SAP Sybase Error Number	2501
SQL State	24000
SQL Code	-853L

Error 853	"Cursor not in a valid state"
ODBC 2 State	24000
ODBC 3 State	24000
Severity Code	16 on page 2
Probable Cause	You attempted to use a cursor that is not in a valid state for the attempted operation. For example, the cursor may have encountered an error. In UltraLite, this error occurs if you attempt to set parameters for a prepared statement while a result set (cursor) is open for the statement.

Error 854	"Function or column reference to '%1' in the ORDER BY clause is invalid"
Constant	INVALID_ORDERBY_COLUMN
SAP Sybase Error Number	2502
SQL State	42W65
SQL Code	-854L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Parameter 1	Name of the column referenced directly, or in an expression, in the ORDER BY clause.
Probable Cause	You specified a function or column reference in the ORDER BY clause that is semantically invalid. For example, for DISTINCT queries the ORDER BY clause may only refer to items in the query's SELECT list.

Messages 855 through 876

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 855	"Trigger name '%1' is ambiguous"
Constant	AMBIGUOUS_TRIGGER_NAME
SAP Sybase Error Number	2503
SQL State	42W66

Error 855	"Trigger name '%1' is ambiguous"
SQL Code	-855L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Name of the ambiguous trigger.
Probable Cause	A statement has referred to a trigger name that is not unique. Qualify the trigger name with the table and/or owner name.

Error 856	"Invalid sqlen field in SQLDA"
Constant	INVALID_SQLLEN
SAP Sybase Error Number	2504
SQL State	07W08
SQL Code	-856L
ODBC 2 State	HY090
ODBC 3 State	HY090
Severity Code	16 on page 2
Probable Cause	An invalid length was specified in a SQLDA sqlen field. All variable length types must have a non-negative length. The DT_BINARY and DT_VARCHAR types must have length greater than one.

Error 857	"Synchronization failed due to an error on the MobiLink server: %1"
Constant	SERVER_SYNCHRONIZATION_ERROR
SAP Sybase Error Number	2505
SQL State	0AW12
SQL Code	-857L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2

Error 857	"Synchronization failed due to an error on the MobiLink server: %1"
Parameter 1	The description of the error from the MobiLink server.
Probable Cause	Synchronization failed at the MobiLink server. More details can be found in the MobiLink server log file.

Error 858	"CREATE/DROP STATISTICS statement cannot refer to virtual tables"
Constant	HISTOGRAMS_NOT_SUPPORTED_ON_OBJECT
SAP Sybase Error Number	2506
SQL State	42W67
SQL Code	-858L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	You attempted to use CREATE/DROP STATISTICS to create/drop one or more histograms on a virtual database object, such as a view or remote table. The CREATE STATISTICS and DROP STATISTICS statements can only refer to base tables, local temporary tables, or global temporary tables in the SQL Anywhere database that you are connected to.

Error 860	"At least one of the specified dbspaces was not calibrated"
Constant	DBSPACE_NOT_CALIBRATED
SAP Sybase Error Number	2509
SQL State	WW028
SQL Code	-860L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	You attempted to calibrate a dspace that was not open or was too small.

Error 861	"Aggregated expression '%1' contains multiple columns of which one or more are outer references"
Constant	MULTIPLE_AGGREGATE_COLUMNS
SAP Sybase Error Number	2510
SQL State	42W68
SQL Code	-861L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Parameter 1	The aggregated expression in error.
Probable Cause	A subselect within the nested query contains an aggregate function whose parameters include an outer reference. In such cases, the outer reference must be the only column referenced in the expression.

Error 862	"The aggregate expression '%1' must appear in either the SELECT list or a HAVING clause subquery"
Constant	INVALID_AGGREGATE_PLACEMENT
SAP Sybase Error Number	2511
SQL State	42W69
SQL Code	-862L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Parameter 1	The aggregated expression in error.
Probable Cause	An aggregated expression containing an outer reference must either appear in a SELECT list expression (a subselect), or in a HAVING clause subquery in the query whose FROM clause contains the table with the column being aggregated.

Error 863	"Grouped query contains more than one distinct aggregate function"
Constant	INVALID_DISTINCT_AGGREGATE
SAP Sybase Error Number	2512
SQL State	42W70
SQL Code	-863L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Probable Cause	Two or more DISTINCT aggregate functions were specified in the same grouped query. This is only permitted if the Hash Group By operator is available. Any query block can only contain at most one DISTINCT aggregate function if the Hash Group By operator is not available.

Error 864	"Statement contains an illegal usage of the NUMBER(*) function"
Constant	INVALID_NUMBER
SAP Sybase Error Number	2514
SQL State	42W71
SQL Code	-864L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Probable Cause	The NUMBER and IDENTITY functions can only appear in the SELECT list of the outer-most SELECT block. It cannot be used in any subquery or in a predicate.

Error 865	"Key constraint between temporary tables requires a primary key (not unique constraint)"
Constant	INVALID_FOREIGN_KEY_INDEX

Error 865	"Key constraint between temporary tables requires a primary key (not unique constraint)"
SAP Sybase Error Number	2515
SQL State	42R03
SQL Code	-865L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	<i>16 on page 2</i>
Probable Cause	The key constraint between temporary tables requires a primary key (not a UNIQUE constraint) if the database uses combined indexes. Change the definition of the primary table using ALTER TABLE or rebuild the database.

Error 866	"%1 returned a result set with a different schema than expected"
Constant	BAD_RESULT_SET
SAP Sybase Error Number	2516
SQL State	WP012
SQL Code	-866L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>12 on page 2</i>
Parameter 1	Name of the procedure that returned the incorrect result set.
Probable Cause	When calling a procedure in the FROM clause of a SELECT statement, the expected schema of the result is taken from the WITH clause. If no WITH clause is given, the expected schema is taken from the system catalog. The result set returned from the call must match the expected schema or it must be possible to convert every column so that it matches.

Error 867	"Cannot change synchronization user_name when status of the last upload is unknown"
Constant	CANNOT_CHANGE_USER_NAME
SAP Sybase Error Number	2517
SQL State	0AW13
SQL Code	-867L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	The MobiLink server uses the user_name to track synchronizations. If the status of the previous upload is unknown then you must resolve this condition before changing the user.

Error 868	""%1' is an unknown character set encoding label"
Constant	UNKNOWN_CHARSET
SAP Sybase Error Number	2518
SQL State	WC001
SQL Code	-868L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The character set encoding label that is not recognized.
Probable Cause	The specified character set label is not recognized, so conversion from/to that character set is not possible.

Error 869	"Database server cannot convert data from/to character set '%1'"
Constant	UNSUPPORTED_CHARACTER_SET_ERROR
SAP Sybase Error Number	2519
SQL State	08W64

Error 869	"Database server cannot convert data from/to character set '%1'"
SQL Code	-869L
ODBC 2 State	08S01
ODBC 3 State	08S01
Severity Code	21 on page 2
Parameter 1	Name of the requested character set.
Probable Cause	The database server cannot convert character data from/to the character set requested by the application because the character set is not supported. The connection fails.

Error 870	"Cannot convert between requested character set '%1' and database character set '%2'"
Constant	FAILED_TO_START_CONVERTER
SAP Sybase Error Number	2520
SQL State	WC002
SQL Code	-870L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the requested character set encoding.
Parameter 2	The name of the database character set encoding.
Probable Cause	The server is unable to convert between the connection character set that was specified and the database character set. This could happen when the dbicu and dbicudt DLLs are not installed.

Error 872	"%1 does not return a result set"
Constant	NO_RESULT_SET
SAP Sybase Error Number	2522
SQL State	WP014

Error 872	"%1 does not return a result set"
SQL Code	-872L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the procedure.
Probable Cause	A procedure called in the FROM clause of a SELECT statement must return a result set.

Error 873	"%1 returned multiple result sets"
Constant	TOO_MANY_RESULT_SETS
SAP Sybase Error Number	2523
SQL State	WP013
SQL Code	-873L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the procedure.
Probable Cause	A procedure called in the FROM clause of a SELECT statement cannot return multiple result sets.

Error 874	"Column must be named: %1"
Constant	NO_XML_IDENTIFIER
SAP Sybase Error Number	2526
SQL State	WX001
SQL Code	-874L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2

Error 874	"Column must be named: %1"
Parameter 1	The number of the column that must be named.
Probable Cause	Unnamed columns cannot be used as XML element or attribute names. Unnamed JSON columns can only be used within the top-level SELECT where the tag and parent are defined. In this context, the unnamed column is a directive to generate a JSON value rather than a JSON object for the given column. Name unnamed columns in the SELECT list by using AS.

Error 875	"There is no way to join to '%1'"
Constant	CANNOT_JOIN_TABEXPR
SAP Sybase Error Number	2527
SQL State	42W73
SQL Code	-875L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Parameter 1	Name of table or view that cannot be joined.
Probable Cause	The server cannot discover a valid join condition involving this table. If the join is an outer join, you may be missing an ON clause. If the join is a KEY JOIN, the server cannot discover a foreign key-primary key relationship with this table that can be used to generate the join condition. If the join is a NATURAL JOIN, the table has no common column names with the table expression it is being joined to.

Error 876	"Client out of memory"
Constant	CLIENT_OUT_OF_MEMORY
SAP Sybase Error Number	2528
SQL State	08W65
SQL Code	-876L
ODBC 2 State	S1001
ODBC 3 State	HY001

Error 876	"Client out of memory"
Severity Code	<i>17 on page 2</i>
Probable Cause	A failure occurred when the database client was trying to allocate memory.

Messages 877 through 901

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 877	"SETUSER not allowed in procedures, triggers, events, or batches"
Constant	SETUSER_NOT_IN_PROCEDURES
SAP Sybase Error Number	2534
SQL State	42W09
SQL Code	-877L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	The SETUSER statement is not allowed in stored procedures, triggers, event handlers, or batches, and cannot be called from an EXECUTE IMMEDIATE statement.

Error 878	"Index '%1' cannot be clustered"
Constant	CLUSTERED_INDEX_NOT_ALLOWED
SAP Sybase Error Number	2535
SQL State	42W74
SQL Code	-878L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	<i>16 on page 2</i>
Parameter 1	Name of the index that could not be made clustered.

Error 878	"Index '%1' cannot be clustered"
Probable Cause	You attempted to create a clustered index (including key indexes) but the new index cannot be created, for example, because the table already has a clustered index.

Error 879	"An invalid multi-byte input character was encountered when converting from %1 to %2"
Constant	ILLEGAL_MULTIBYTE_ERROR
SAP Sybase Error Number	2536
SQL State	WC003
SQL Code	-879L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The character set of the input string.
Parameter 2	The character set of the output string.
Probable Cause	While the server was performing character set conversion on an input string, an invalid multi-byte character was encountered. The operation was aborted.

Error 881	"Character substitution was required when converting from %1 to %2"
Constant	SIMPLE_SUBSTITUTION_ERROR
SAP Sybase Error Number	2540
SQL State	WC005
SQL Code	-881L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The character set of the input string.
Parameter 2	The character set of the output string.

Error 881	"Character substitution was required when converting from %1 to %2"
Probable Cause	While the server was performing character set conversion on an input string, some characters could not be represented in the database character set. The operation was aborted. See on_charset_conversion_failure option.

Error 883	"Character conversion error or warning report is not available when the single-byte converter is used"
Constant	CHARACTER_CONVERSION_REPORT_NOT_AVAILABLE
SAP Sybase Error Number	2544
SQL State	WC007
SQL Code	-883L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You attempted to set the on_charset_conversion_failure option to produce either a warning or error report. This setting is not available when the single-byte to single-byte converter is used.

Error 887	"Virtual index creation with more than %1 columns"
Constant	TOO_MANY_VIRTUAL_INDEX_COLUMNS
SAP Sybase Error Number	2548
SQL State	54W50
SQL Code	-887L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The maximum number of virtual index columns.
Probable Cause	You attempted to create a virtual index with more than the maximum number of columns.

Error 888	"XML parser error: %1"
Constant	XML_PARSER_ERROR
SAP Sybase Error Number	2550
SQL State	WX002
SQL Code	-888L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The error message returned by the XML parser.
Probable Cause	An XML instance will only parse correctly if it is well-formed as defined by the XML 1.0 specification.

Error 889	"Statement contains an illegal usage of the non-deterministic function '%1'"
Constant	NONDETERMINISTIC_FUNCTION
SAP Sybase Error Number	2551
SQL State	42W79
SQL Code	-889L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Parameter 1	The name of the non-deterministic user-defined function used in error.
Probable Cause	Non-deterministic functions cannot appear in a CHECK constraint, or any other type of integrity constraint. They may appear anywhere within a query, view, or derived table. However, if an aliased SELECT list expression contains a non-deterministic function, that alias cannot be referred to elsewhere in the query.

Error 890	"Statement size or complexity exceeds server limits"
Constant	SYNTACTIC_LIMIT

Error 890	"Statement size or complexity exceeds server limits"
SAP Sybase Error Number	2553
SQL State	54W01
SQL Code	-890L
ODBC 2 State	37000
ODBC 3 State	54000
Severity Code	19 on page 2
Probable Cause	The statement contains one or more constructs whose size make it impossible to process. Increasing the maximum cache size, page size, or stack size may resolve this error. Consider rewriting the query so that the internal limit is not exceeded. For example, if the query contains a large IN-list, consider inserting the IN-list's values into a temporary table. Then rewrite the query to join this temporary table to the other table(s) in the original statement.

Error 891	"Cannot convert between requested character sets '%1' and '%2'"
Constant	FAILED_TO_START_CONVERTER_2_CHARSETS
SAP Sybase Error Number	2554
SQL State	WC008
SQL Code	-891L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the first requested character set encoding.
Parameter 2	The name of the second requested character set encoding.
Probable Cause	The server is unable to convert between the two specified character sets. This could happen when the dbicu and dbicudt DLLs are not installed.

Error 892	"XPath parser error: %1"
Constant	XQUERY_PARSER_ERROR

Error 892	"XPath parser error: %1"
SAP Sybase Error Number	2555
SQL State	WX003
SQL Code	-892L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The error message returned by the XPath parser.
Probable Cause	The XPath expression is illegal or uses features that are not currently supported.

Error 893	"Illegal flags value passed to OPENXML "
Constant	BAD_OPENXML_FLAG
SAP Sybase Error Number	2556
SQL State	WX004
SQL Code	-893L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	The flags value passed to OPENXML as the third argument must be either 1 (attribute-centric mapping), or 2 (element-centric mapping).

Error 894	"Plan cannot be generated for this type of statement"
Constant	STMT_NOT_ALLOWED_IN_PLAN
SAP Sybase Error Number	2557
SQL State	0AW14
SQL Code	-894L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 894	"Plan cannot be generated for this type of statement"
Severity Code	<i>15</i> on page 2
Probable Cause	You tried to get the execution plan for a statement type that is not supported.

Error 895	"Encryption error: %1"
Constant	ENCRYPT_ERROR
SAP Sybase Error Number	2558
SQL State	08W66
SQL Code	-895L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	<i>11</i> on page 2
Parameter 1	Description of the error that occurred.
Probable Cause	An error occurred during encryption.

Error 896	"Cannot delete PUBLIC option '%1' since user settings exist"
Constant	UNSET_PUBLIC_ID
SAP Sybase Error Number	2560
SQL State	42W82
SQL Code	-896L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	<i>15</i> on page 2
Parameter 1	Name of the option.
Probable Cause	You tried to delete a PUBLIC option, but there are user settings for the same option. The user settings must be deleted before the PUBLIC option is deleted.

Error 897	"Illegal tag value: '%1'"
Constant	BAD_FOR_XML_EXPLICIT_TAG
SAP Sybase Error Number	2563
SQL State	WX005
SQL Code	-897L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The illegal tag value.
Probable Cause	FOR XML EXPLICIT and FOR JSON EXPLICIT tag values must be greater than 0 and less than 256. NULL values are not allowed in the Tag column.

Error 898	"Unknown FOR XML EXPLICIT directive: '%1'"
Constant	BAD_FOR_XML_EXPLICIT_DIRECTIVE
SAP Sybase Error Number	2564
SQL State	WX006
SQL Code	-898L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The unknown directive.
Probable Cause	Legal FOR XML EXPLICIT directives are: id, idref, idrefs, hide, element, xml, and cdata. Legal FOR JSON EXPLICIT directives are: hide, and element.

Error 899	"Illegal column name: '%1'"
Constant	BAD_FOR_XML_EXPLICIT_COLUMN_NAME
SAP Sybase Error Number	2565
SQL State	WX007

Error 899	"Illegal column name: '%1'"
SQL Code	-899L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The reason the column name was illegal.
Probable Cause	FOR XML EXPLICIT and FOR JSON EXPLICIT column names can consist of up to four fields separated by exclamation marks. The first two columns must be named Tag and Parent.

Error 900	"Parent not open: '%1'"
Constant	EXPLICIT_TAG_NOT_OPEN
SAP Sybase Error Number	2566
SQL State	WX008
SQL Code	-900L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The parent tag ID that is not among the open tags.
Probable Cause	FOR XML EXPLICIT and FOR JSON EXPLICIT require the parent tag for a row to be opened when that row is read. Check the order of the rows returned by the query with the FOR XML EXPLICIT or FOR JSON EXPLICIT clause removed.

Error 901	"Undeclared tag ID: '%1'"
Constant	UNDECLARED_FOR_XML_EXPLICIT_TAG
SAP Sybase Error Number	2567
SQL State	WX009
SQL Code	-901L
ODBC 2 State	ERROR

Error 901	"Undeclared tag ID: '%1'"
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The value of the undeclared tag ID.
Probable Cause	Every value appearing in the Tag column of the table must be declared in the TagNumber field of at least one column name.

Messages 902 through 923

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 902	"Too few columns"
Constant	FOR_XML_EXPLICIT_TOO_FEW_COLUMNS
SAP Sybase Error Number	2568
SQL State	WX010
SQL Code	-902L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	FOR XML EXPLICIT and FOR JSON EXPLICIT require at least three columns: the tag column, the parent column, and one or more data columns.

Error 903	"CDATA has a name"
Constant	FOR_XML_EXPLICIT_NAMED_CDATA
SAP Sybase Error Number	2569
SQL State	WX011
SQL Code	-903L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>

Error 903	"CDATA has a name"
Probable Cause	A CDATA directive in a FOR XML EXPLICIT query must not be given a name.

Error 904	"Illegal ORDER BY in aggregate function"
Constant	INVALID_ORDERBY_IN_AGGREGATE
SAP Sybase Error Number	2570
SQL State	42W90
SQL Code	-904L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Probable Cause	An ORDER BY can be used in an aggregate function only if there are no DISTINCT aggregates in the SELECT list, or there is a single DISTINCT aggregate with the DISTINCT column equal to the first column of the ORDER BY. Also, multiple ordered aggregates cannot be used in the same SELECT list unless they have the exact same ORDER BY clause.

Error 905	"Invalid XQuery constructor"
Constant	INVALID_XQUERY_CONSTRUCTOR
SAP Sybase Error Number	2571
SQL State	WX012
SQL Code	-905L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The XQuery constructor passed as the first argument to XMLGEN was not valid.

Error 906	"XMLGEN evaluation failure"
Constant	XMLGEN_EVALUATION_FAILURE

Error 906	"XMLGEN evaluation failure"
SAP Sybase Error Number	2572
SQL State	WX013
SQL Code	-906L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	One of the variables referenced in the XQuery constructor was not found in the list of arguments.

Error 907	"No name for argument"
Constant	NO_SQLX_ARGUMENT_NAME
SAP Sybase Error Number	2573
SQL State	WX014
SQL Code	-907L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	Unnamed arguments cannot be used as XML element or attribute names. Name unnamed items in the argument list using AS.

Error 908	"Invalid operation on a closed object"
Constant	ULTRALITE_OBJ_CLOSED
SAP Sybase Error Number	2574
SQL State	55W14
SQL Code	-908L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2

Error 908	"Invalid operation on a closed object"
Probable Cause	An illegal attempt was made to access a closed UltraLite object.

Error 910	"System command failed with return code %1"
Constant	SYSTEM_COMMAND_FAILED
SAP Sybase Error Number	2575
SQL State	38W01
SQL Code	-910L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Return code value.
Probable Cause	A non-zero return code resulted when executing a system command.

Error 911	"Control character in XML output"
Constant	CONTROL_CHARACTER_IN_XML_OUTPUT
SAP Sybase Error Number	2576
SQL State	WX015
SQL Code	-911L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	A non-space character less than hex 20 was encountered while generating XML content. Consider base64 encoding strings that contain control characters before using them as XML content. This can be accomplished in a FOR XML query or SQLX function by casting the string to a type such as LONG BINARY.

Error 912	"Insufficient memory for OPENXML query"
Constant	XQUERY_MEMORY_ERROR

Error 912	"Insufficient memory for OPENXML query"
SAP Sybase Error Number	2577
SQL State	WX016
SQL Code	-912L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	17 on page 2
Probable Cause	The memory used by an OPENXML query may be proportional to the maximum distance between elements or attributes returned by a single row. For example, a query where some row uses the value from both the first and last element in the document may use memory proportional to the size of the document. One solution is to increase the cache size. Another is to break a query that refers to distant elements into several queries that refer to nearby elements and join the results.

Error 913	"A transaction log file is required for auditing"
Constant	AUDITING_WITHOUT_TRANSACTION_LOG
SAP Sybase Error Number	2578
SQL State	42W91
SQL Code	-913L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	This database is running without a transaction log file. You must use the Transaction Log utility (dblog) to create a transaction log file before using auditing.

Error 914	"Cycle in common table expression references"
Constant	COMMON_TABLE_EXPRESSION_CYCLE
SAP Sybase Error Number	2579
SQL State	42W93

Error 914	"Cycle in common table expression references"
SQL Code	-914L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	Cycles involving multiple common table expressions are not allowed.

Error 915	"Service type required for CREATE SERVICE"
Constant	SERVICE_TYPE_REQUIRED
SAP Sybase Error Number	2580
SQL State	42W92
SQL Code	-915L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The CREATE SERVICE statement requires a service type to be specified.

Error 916	"'%1' is an unrecognized service type"
Constant	UNKNOWN_SERVICE_TYPE
SAP Sybase Error Number	2581
SQL State	42W94
SQL Code	-916L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The service type that is unrecognized.
Probable Cause	An unrecognized service type was specified.

Error 918	"A user name must be specified if AUTHORIZATION is Off"
Constant	SERVICE_REQUIRES_USER_NAME
SAP Sybase Error Number	2583
SQL State	42W96
SQL Code	-918L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	A valid user name must be specified if AUTHORIZATION is Off.

Error 919	"Service '%1' already exists"
Constant	SERVICE_ALREADY_EXISTS
SAP Sybase Error Number	2584
SQL State	42W97
SQL Code	-919L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the service that already exists.
Probable Cause	You have attempted to create a service with a name that already exists in the database.

Error 920	"Service '%1' not found"
Constant	SERVICE_NOT_FOUND
SAP Sybase Error Number	2585
SQL State	42W98
SQL Code	-920L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 920	"Service '%1' not found"
Severity Code	<i>16 on page 2</i>
Parameter 1	Name of the specified service that could not be found.
Probable Cause	You have attempted to reference a service with a name that does not exist in the database.

Error 921	"Invalid recursive query"
Constant	INVALID_RECURSION
SAP Sybase Error Number	2586
SQL State	42W99
SQL Code	-921L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	<i>16 on page 2</i>
Probable Cause	A recursive query must consist of the UNION ALL of an initial query and an iteration query. The only set operation allowed in the iteration query is UNION ALL. A recursive reference to the name of the common table expression can only appear in the iteration query, and must not be in a SELECT that uses DISTINCT, ORDER BY, or an aggregate function. A recursive reference also cannot appear on the NULL-supplying side of an outer join, or in a subquery.

Error 922	"No column list for recursive query"
Constant	NO_RECURSIVE_COLUMN_LIST
SAP Sybase Error Number	2587
SQL State	42W9A
SQL Code	-922L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	<i>16 on page 2</i>
Probable Cause	A common table expression defining a recursive query must have a column list.

Error 923	"Too many recursive iterations"
Constant	TOO_MANY_RECURSIVE_ITERATIONS
SAP Sybase Error Number	2588
SQL State	57015
SQL Code	-923L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	A recursive query ran for more iterations than allowed by the current max_recursive_iterations option setting.

Messages 924 through 944

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 924	"Service '%1' in use"
Constant	SERVICE_IN_USE
SAP Sybase Error Number	2582
SQL State	55W15
SQL Code	-924L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the service that is in use.
Probable Cause	You have attempted to drop a service that is currently in use.

Error 925	"Invalid service name '%1'"
Constant	INVALID_SERVICE_NAME
SAP Sybase Error Number	2589
SQL State	42W95

Error 925	"Invalid service name '%1'"
SQL Code	-925L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	Name of the service.
Probable Cause	You have attempted to create a service with an invalid name. The name may contain characters that are not allowed, or it may conflict with the URL PATH setting specified for the service.

Error 926	"Host variable reference in service definition must be named"
Constant	HOSTVAR_MUST_BE_NAMED
SAP Sybase Error Number	2590
SQL State	42W9B
SQL Code	-926L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	You have attempted to create a service with an unnamed host variable reference.

Error 927	"Service statement definition is inconsistent with service type"
Constant	SERVICE_STATEMENT_MISMATCH
SAP Sybase Error Number	2591
SQL State	42W9C
SQL Code	-927L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>

Error 927	"Service statement definition is inconsistent with service type"
Probable Cause	Either no statement was provided for a service whose type requires one, or a statement was provided when the service type does not allow one to be defined.

Error 928	"Constant expressions must not appear in GROUP BY clause"
Constant	NO_CONSTANTS_IN_GROUP_BY
SAP Sybase Error Number	2592
SQL State	42W9D
SQL Code	-928L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Probable Cause	You used a constant in the GROUP BY clause. Constants must not appear in the GROUP BY clause for a query. References to columns in a view that are constant are permitted in a GROUP BY clause. Also, expressions that use a view column that is constant are permitted.

Error 929	"Constraint '%1' not found"
Constant	CONSTRAINT_NOT_FOUND
SAP Sybase Error Number	2593
SQL State	42U04
SQL Code	-929L
ODBC 2 State	S0002
ODBC 3 State	42S23
Severity Code	16 on page 2
Parameter 1	Name of the constraint that could not be found.
Probable Cause	You misspelled the name of a constraint, or the constraint you are looking for is on a different table.

Error 930	"Attempt to alter unnamed column constraint when named constraints exist"
Constant	AMBIGUOUS_CONSTRAINT
SAP Sybase Error Number	2594
SQL State	42U05
SQL Code	-930
ODBC 2 State	S0002
ODBC 3 State	42S24
Severity Code	16 on page 2
Probable Cause	You have asked for an unnamed column constraint to be altered, but there is at least one named constraint.

Error 931	"Service definition requires a statement when authorization is off"
Constant	SERVICE_AUTH_REQUIRED
SAP Sybase Error Number	2595
SQL State	42W9E
SQL Code	-931L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The service definition for the specified service type requires a statement to be specified when authorization is set to Off.

Error 933	"A log is required for SAP Sybase IQ databases"
Constant	IQ_LOG_REQUIRED
SAP Sybase Error Number	2597
SQL State	0AQ48
SQL Code	-933L
ODBC 2 State	37000

Error 933	"A log is required for SAP Sybase IQ databases"
ODBC 3 State	42000
Severity Code	<i>16</i> on page 2
Probable Cause	SAP Sybase IQ databases require the use of a transaction log file.

Error 934	"Unable to start specified database: Server must be upgraded to start database %1"
Constant	UNABLE_TO_START_DATABASE_VER_NEWER
SAP Sybase Error Number	2598
SQL State	08W67
SQL Code	-934L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	<i>11</i> on page 2
Parameter 1	Name of the database that could not be started, if known.
Probable Cause	The database server was unable to start the database since the database version is newer than the server version. The server must be upgraded to at least the version of the database to be able to start the database.

Error 935	"Unable to start specified database: Log file error"
Constant	UNABLE_TO_START_DATABASE_LOG_ERROR
SAP Sybase Error Number	2599
SQL State	08W68
SQL Code	-935L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	<i>11</i> on page 2

Error 935	"Unable to start specified database: Log file error"
Probable Cause	The database server was unable to start the database since the log file is missing, for a different database, or some other reason. Check the server messages window for more details.

Error 936	"Too many constraints in database"
Constant	TOO_MANY_CONSTRAINTS
SAP Sybase Error Number	2600
SQL State	54W02
SQL Code	-936L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	An attempt to create a new constraint failed because the corresponding system table is full. Reloading the database will reclaim any unused space.

Error 937	"Invalid reference to or operation on constraint '%1'"
Constant	INVALID_CONSTRAINT_REF
SAP Sybase Error Number	2601
SQL State	42U06
SQL Code	-937L
ODBC 2 State	S0002
ODBC 3 State	42S23
Severity Code	16 on page 2
Parameter 1	Name of the constraint that cannot be used for the specified purpose.
Probable Cause	You specified an invalid operation on a constraint. For example, you tried to alter a primary key constraint.

Error 938	"Recursion is not allowed without the RECURSIVE keyword"
Constant	RECURSIVE_KEYWORD_REQUIRED

Error 938	"Recursion is not allowed without the RECURSIVE keyword"
SAP Sybase Error Number	2602
SQL State	42WA0
SQL Code	-938L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	<i>16 on page 2</i>
Probable Cause	The common table expressions for a recursive query must be defined using a WITH RECURSIVE clause.

Error 939	"Invalid setting for HTTP option '%1'"
Constant	INVALID_HTTP_OPTION_SETTING
SAP Sybase Error Number	2603
SQL State	42W83
SQL Code	-939L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	<i>16 on page 2</i>
Parameter 1	Name of the invalid HTTP option.
Probable Cause	You supplied an invalid value for an HTTP option. Some options allow only numeric values, while other options allow only the values On and Off.

Error 940	"Invalid setting for HTTP header '%1'"
Constant	INVALID_HTTP_HEADER_SETTING
SAP Sybase Error Number	2604
SQL State	42W84
SQL Code	-940L
ODBC 2 State	37000

Error 940	"Invalid setting for HTTP header '%1'"
ODBC 3 State	42000
Severity Code	<i>16</i> on page 2
Parameter 1	Name of the invalid HTTP header.
Probable Cause	You supplied an invalid value for an HTTP header.

Error 941	"jConnect does not support encryption"
Constant	NO_ENCRYPTION_FOR_JCONNECT
SAP Sybase Error Number	2605
SQL State	08W69
SQL Code	-941L
ODBC 2 State	08004
ODBC 3 State	08004
Severity Code	<i>18</i> on page 2
Probable Cause	You supplied an encryption type for a connection using jConnect. jConnect does not support encryption.

Error 942	"A workload capture (%1) is already in progress"
Constant	WORKLOAD_CAPTURE_ALREADY_EXISTS
SAP Sybase Error Number	2606
SQL State	WW029
SQL Code	-942L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	<i>16</i> on page 2
Parameter 1	The name of the workload capture that is already in progress.
Probable Cause	You have tried to initiate a workload capture when one is already in progress. You need to wait for the other capture to complete.

Error 943	"No workload capture currently exists"
Constant	WORKLOAD_CAPTURE_DOES_NOT_EXIST
SAP Sybase Error Number	2607
SQL State	WW030
SQL Code	-943L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	You have tried to stop, pause, resume, or get the status of a workload capture, but no workload captures exist.

Error 944	"Too many expressions in GROUP BY list for ROLLUP, CUBE, or GROUPING SETS operation"
Constant	TOO_MANY_GROUPING_EXPRESSIONS
SAP Sybase Error Number	2608
SQL State	42WA1
SQL Code	-944L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Probable Cause	You specified too many expressions in the GROUP BY list for the requested ROLLUP, CUBE, or GROUPING SETS operation. The current environment where SQL Anywhere is executing cannot support this number of expressions in the GROUP BY list for the requested operation.

Messages 945 through 964

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 945	"Recursive column %1: conversion from '%2' to '%3' loses precision"
Constant	BAD_RECURSIVE_COLUMN_CONVERSION

Error 945	"Recursive column %1: conversion from '%2' to '%3' loses precision"
SAP Sybase Error Number	2609
SQL State	42WA2
SQL Code	-945L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	<i>16 on page 2</i>
Parameter 1	Column number of the recursive subquery.
Parameter 2	Type converted from.
Parameter 3	Type converted to.
Probable Cause	Every column in the recursive subquery must be convertible to the type of the corresponding column in the initial subquery without loss of precision. Try casting the column in the initial subquery to an appropriate type.

Error 946	"Result set not permitted in '%1'"
Constant	RESULT_SET_NOT_PERMITTED
SAP Sybase Error Number	2610
SQL State	09W03
SQL Code	-946L
ODBC 2 State	07005
ODBC 3 State	07005
Severity Code	<i>16 on page 2</i>
Parameter 1	Name of object containing the invalid statement.
Probable Cause	You attempted to execute a SELECT statement in a context where a result set is not permitted.

Error 947	"Window '%1' not found"
Constant	WINDOW_NOT_FOUND
SAP Sybase Error Number	2611

Error 947	"Window '%1' not found"
SQL State	42WA3
SQL Code	-947L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	Name of the window that could not be found.
Probable Cause	You have attempted to reference a window name that is not defined in the window list of the SELECT statement.

Error 948	"PARTITION BY not allowed in reference to window '%1'"
Constant	PARTITIONBY_NOT_ALLOWED
SAP Sybase Error Number	2612
SQL State	42WA4
SQL Code	-948L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The name of the window.
Probable Cause	When an existing window name is referenced from an inline window specification, the inline specification must not have a PARTITION BY clause.

Error 949	"ORDER BY not allowed in window '%1'"
Constant	ORDERBY_NOT_ALLOWED
SAP Sybase Error Number	2613
SQL State	42WA5
SQL Code	-949L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 949	"ORDER BY not allowed in window '%1'"
Severity Code	<i>16 on page 2</i>
Parameter 1	The name of the window.
Probable Cause	When an existing window name is referenced from an inline window specification, either the inline window or the referenced window may have an ORDER BY, but not both.

Error 950	"Frame not allowed for window '%1'"
Constant	FRAME_NOT_ALLOWED
SAP Sybase Error Number	2614
SQL State	42WA6
SQL Code	-950L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The name of the window.
Probable Cause	Frames are not allowed on windows referenced from inline window specifications.

Error 951	"Cannot access schema file '%1'"
Constant	CANNOT_ACCESS_SCHEMA_FILE
SAP Sybase Error Number	2615
SQL State	WW031
SQL Code	-951L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The name of the file or indication that no name was given.
Probable Cause	UltraLite requires a schema file to perform the current operation. Either no schema file was specified or the one specified was not accessible or was corrupt.

Error 952	"The status of the last synchronization upload is unknown"
Constant	SYNC_STATUS_UNKNOWN
SAP Sybase Error Number	2616
SQL State	WW032
SQL Code	-952L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	The status of the last synchronization upload is unknown. The current operation cannot proceed until a successful upload is synchronized.

Error 953	"A schema upgrade is not currently allowed"
Constant	SCHEMA_UPGRADE_NOT_ALLOWED
SAP Sybase Error Number	2617
SQL State	WW033
SQL Code	-953L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	A schema upgrade cannot proceed because of concurrent use of the database. For example, all cursors must be closed before a schema upgrade can occur.

Error 954	"The database '%1' was not found"
Constant	ULTRALITE_DATABASE_NOT_FOUND
SAP Sybase Error Number	2618
SQL State	WW034
SQL Code	-954L
ODBC 2 State	ERROR

Error 954	"The database '%1' was not found"
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The name of the database specified or the default database name.
Probable Cause	The named database was not found. Ensure your connection string properly names the desired database.

Error 955	"This connection already exists"
Constant	CONNECTION_ALREADY_EXISTS
SAP Sybase Error Number	2619
SQL State	WW035
SQL Code	-955L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	A connection with the given SQLCA and name (or no name) already exists. Before connecting you must disconnect the existing connection, or specify a different connection name.

Error 956	"Information for synchronization is incomplete or invalid, check '%1'"
Constant	SYNC_INFO_INVALID
SAP Sybase Error Number	2620
SQL State	WW036
SQL Code	-956L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The name of the parameter not properly initialized.

Error 956	"Information for synchronization is incomplete or invalid, check '%1'"
Probable Cause	Information for synchronization is incomplete or invalid. Correct the indicated parameter before attempting to synchronize again. If 'init_verify' is indicated, the InitSyncInfo function was not called.

Error 957	"Invalid preceding or following size in OLAP function"
Constant	INVALID_FRAME_BOUNDARY
SAP Sybase Error Number	2621
SQL State	22X13
SQL Code	-957L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The expression for the preceding or following size evaluated to NULL or a negative value.

Error 958	"Password cannot be longer than %1 characters"
Constant	PASSWORD_TOO_LONG
SAP Sybase Error Number	2622
SQL State	54W08
SQL Code	-958L
ODBC 2 State	37000
ODBC 3 State	54000
Severity Code	15 on page 2
Probable Cause	The password is longer than that allowed by the server.

Error 959	"Compression error: %1"
Constant	COMPRESSION_ERROR
SAP Sybase Error Number	2623
SQL State	WW037

Error 959	"Compression error: %1"
SQL Code	-959L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	An error occurred during compression.

Error 960	"Decompression error: %1"
Constant	DECOMPRESSION_ERROR
SAP Sybase Error Number	2624
SQL State	WW038
SQL Code	-960L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	An error occurred during decompression.

Error 961	"Input string is not base64-encoded"
Constant	BASE64_DECODING_ERROR
SAP Sybase Error Number	2625
SQL State	WW039
SQL Code	-961L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	An error occurred during base64 decoding.

Error 962	"Argument to GROUPING aggregate must be a grouping column in the GROUP BY clause"
Constant	INVALID_GROUPING_AGGREGATE

Error 962	"Argument to GROUPING aggregate must be a grouping column in the GROUP BY clause"
SAP Sybase Error Number	2626
SQL State	42WA7
SQL Code	-962L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Probable Cause	Only a grouping column is permitted as an argument to the GROUPING aggregate function. An argument that contains anything other than a single grouping column expression will not be accepted.

Error 963	"Password contains an illegal character"
Constant	ILLEGAL_PASSWORD
SAP Sybase Error Number	2627
SQL State	08005
SQL Code	-963L
ODBC 2 State	28000
ODBC 3 State	28000
Severity Code	11 on page 2
Probable Cause	The specified password contains an illegal character.

Error 964	"Window function used in predicate"
Constant	ILLEGAL_WINDOW_PREDICATE
SAP Sybase Error Number	2628
SQL State	42WA8
SQL Code	-964L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 964	"Window function used in predicate"
Severity Code	<i>16 on page 2</i>
Probable Cause	A window function was used in the WHERE or HAVING clause of a SELECT statement. Consider making the SELECT into a derived table, putting the window function in the SELECT list of the derived table, and changing the predicate to reference the derived column.

Messages 965 through 985

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 965	"Window function requires ORDER BY"
Constant	OBSOLETE_ORDERBY_REQUIRED
SAP Sybase Error Number	2629
SQL State	42WA9
SQL Code	-965L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	Rank functions and window functions that use the RANGE keyword must specify an ORDER BY clause.

Error 966	"Composite ORDER BY not allowed with RANGE"
Constant	ILLEGAL_COMPOSITE_ORDERBY
SAP Sybase Error Number	2630
SQL State	42WAA
SQL Code	-966L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	Window functions that use the RANGE keyword may only ORDER BY a single column.

Error 967	"Backup file '%1' already exists"
Constant	BACKUP_FILE_EXISTS
SAP Sybase Error Number	2631
SQL State	WB012
SQL Code	-967L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the file.
Probable Cause	A file that would normally be created by this BACKUP statement already exists.

Error 968	"User '%1' already has EXECUTE permission"
Constant	ALREADY_HAS_EXEC_PERMS
SAP Sybase Error Number	2632
SQL State	42WAB
SQL Code	-968L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Name of the user that already has EXECUTE permission.
Probable Cause	You attempted to give EXECUTE permission on a stored procedure to a user that already has EXECUTE permission on that procedure.

Error 969	"Required operators excluded"
Constant	REQUIRED_OPERATORS_EXCLUDED
SAP Sybase Error Number	2633
SQL State	WI011
SQL Code	-969L

Error 969	"Required operators excluded"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	18 on page 2
Probable Cause	The database server was unable to construct a valid access plan for the given request because required data flow operators were excluded by the exclude_operators option. Re-enable the required operators to execute the statement.

Error 970	"Invalid hint specified for table '%1'"
Constant	INVALID_HINT
SAP Sybase Error Number	2634
SQL State	42U07
SQL Code	-970L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Parameter 1	The name of the table for which the hint was specified.
Probable Cause	A hint was specified for the current statement is not valid in this context. In a single statement, all references to a table must specify the same hint or none at all.

Error 971	"Checksums are not enabled in this database"
Constant	CHECKSUMS_NOT_ENABLED
SAP Sybase Error Number	2637
SQL State	WW042
SQL Code	-971L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2

Error 971	"Checksums are not enabled in this database"
Probable Cause	An attempt was made to perform checksum validation but the database does not have checksums enabled.

Error 972	"Database page size too small: %1"
Constant	PAGE_SIZE_TOO_SMALL
SAP Sybase Error Number	2638
SQL State	54W03
SQL Code	-972L
ODBC 2 State	08004
ODBC 3 State	08004
Severity Code	14 on page 2
Parameter 1	Database name.
Probable Cause	You attempted to load statistics that were too large for the current database page size. Rebuilding this database with a larger page size could prevent this error.

Error 973	"The string is too long (%1)"
Constant	STRING_PARM_TOO_LONG
SAP Sybase Error Number	2639
SQL State	54W06
SQL Code	-973L
ODBC 2 State	37000
ODBC 3 State	54000
Severity Code	15 on page 2
Parameter 1	The string that is longer than that allowed by the server.
Probable Cause	The string is longer than that allowed by the server.

Error 974	"File I/O failed for '%1'"
Constant	DEVICE_IO_FAILED

Error 974	"File I/O failed for '%1'"
SAP Sybase Error Number	2640
SQL State	WW043
SQL Code	-974L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The file name.
Probable Cause	An error occurred while trying to access the file. If the file is located on a removable media card, the card may have been removed.

Error 975	"Incorrect volume ID for '%1'"
Constant	INCORRECT_VOLUME_ID
SAP Sybase Error Number	2641
SQL State	WW044
SQL Code	-975L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The file name.
Probable Cause	The file can be accessed, but the volume ID has changed. Insert the original removable media card.

Error 976	"Could not load the encryption DLL \"%1\No message
Constant	MISSING_ENCRYPTION_DLL
SAP Sybase Error Number	2643
SQL State	08W70
SQL Code	-976L
ODBC 2 State	ERROR

Error 976	"Could not load the encryption DLL \"%1\"No message"
ODBC 3 State	ERROR
Severity Code	19 on page 2
Parameter 1	The name of the encryption DLL that could not be loaded.
Probable Cause	An attempt to load the encryption DLL failed.

Error 978	"Directory for output file does not exist"
Constant	DIRECTORY_INACCESSIBLE
SAP Sybase Error Number	2645
SQL State	WW047
SQL Code	-978L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	20 on page 2
Probable Cause	The file cannot be written because the directory does not exist.

Error 979	"Output file cannot be written"
Constant	CANNOT_WRITE_FILE
SAP Sybase Error Number	2646
SQL State	WW048
SQL Code	-979L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	20 on page 2
Probable Cause	Unable to create or write an output file. The file may be locked or read-only.

Error 980	"The URI '%1' is invalid"
Constant	INVALID_URI
SAP Sybase Error Number	2647

Error 980	"The URI '%1' is invalid"
SQL State	WW049
SQL Code	-980L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The invalid URI.
Probable Cause	The specified URI is not valid.

Error 981	"Unable to connect to the remote host specified by '%1'"
Constant	UNABLE_TO_CONNECT_TO_HOST
SAP Sybase Error Number	2648
SQL State	WW050
SQL Code	-981L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	19 on page 2
Parameter 1	The URI referencing the remote host.
Probable Cause	A connection could not be initiated to the remote server.

Error 982	"Connection timed out"
Constant	REMOTE_CONNECTION_TIMED_OUT
SAP Sybase Error Number	2649
SQL State	WW051
SQL Code	-982L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	19 on page 2
Probable Cause	The connection to the remote host timed out due to inactivity.

Error 983	"HTTP request failed. Status code '%1'"
Constant	HTTP_REQUEST_FAILED
SAP Sybase Error Number	2650
SQL State	WW052
SQL Code	-983L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	19 on page 2
Parameter 1	The HTTP status code.
Probable Cause	The HTTP request returned a status code that indicated failure.

Error 984	"Could not initialize the encryption DLL: '%1'"
Constant	ENCRYPTION_INITIALIZATION_FAILED
SAP Sybase Error Number	2651
SQL State	WW053
SQL Code	-984L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	19 on page 2
Parameter 1	Reason the initialization failed, if known.
Probable Cause	An attempt to initialize the encryption DLL failed.

Error 985	"The database name 'utility_db' is reserved for the utility database."
Constant	DB_ALIAS_RESERVED_UTILDB
SAP Sybase Error Number	2845
SQL State	08W20
SQL Code	-985L
ODBC 2 State	ERROR

Error 985	"The database name 'utility_db' is reserved for the utility database."
ODBC 3 State	ERROR
Severity Code	<i>19 on page 2</i>
Probable Cause	You are attempting to start a database with the name "utility_db". This name is reserved for the utility database.

Messages 986 through 1005

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 986	"Invalid procedure type '%1'"
Constant	INVALID_PROCEDURE_TYPE
SAP Sybase Error Number	2653
SQL State	WW055
SQL Code	-986L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The procedure type.
Probable Cause	A procedure or function was specified with an invalid type.

Error 987	"Invalid procedure subtype '%1' for type '%2'"
Constant	INVALID_PROCEDURE_SUBTYPE
SAP Sybase Error Number	2654
SQL State	WW056
SQL Code	-987L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The procedure subtype.

Error 987	"Invalid procedure subtype '%1' for type '%2'"
Parameter 2	The procedure type.
Probable Cause	A procedure or function was specified with an invalid subtype for the given procedure type.

Error 988	"Invalid response from the HTTP server"
Constant	INVALID_HTTP_RESPONSE
SAP Sybase Error Number	2655
SQL State	WW057
SQL Code	-988L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	19 on page 2
Probable Cause	The response from the remote HTTP server was invalid. It may have been empty, malformed, missing header information, and so on.

Error 989	"NAMESPACE attribute is not valid with procedure type '%1'"
Constant	INVALID_NAMESPACE_ATTRIBUTE
SAP Sybase Error Number	2656
SQL State	WW058
SQL Code	-989L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The NAMESPACE attribute on the procedure.
Probable Cause	The NAMESPACE attribute is only applicable to procedures of type SOAP.

Error 990	"The secure connection to the remote host failed: %1"
Constant	SECURE_CONNECTION_FAILED

Error 990	"The secure connection to the remote host failed: %1"
SAP Sybase Error Number	2657
SQL State	WW059
SQL Code	-990L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	19 on page 2
Parameter 1	A message describing the error that occurred.
Probable Cause	The server was unable to initiate a secure connection with the remote host.

Error 991	"Clause '%1' has invalid attribute '%2'"
Constant	INVALID_PROCEDURE_ATTRIBUTE
SAP Sybase Error Number	2658
SQL State	WW060
SQL Code	-991L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The attribute on the procedure.
Parameter 2	The attribute value or cause of failure.
Probable Cause	The attribute value specified on the procedure is not valid.

Error 992	"The specified listener could not be registered"
Constant	CANNOT_REGISTER_LISTENER
SAP Sybase Error Number	2659
SQL State	54W04
SQL Code	-992L
ODBC 2 State	ERROR

Error 992	"The specified listener could not be registered"
ODBC 3 State	ERROR
Severity Code	<i>17</i> on page 2
Probable Cause	The specified listener could not be registered because the maximum number of listeners has been reached, the class name is already in use, or system resources are not available.

Error 993	"LOAD TABLE not allowed on temporary table with ON COMMIT DELETE ROWS"
Constant	INVALID_TEMP_TABLE_COMMIT_ACTION
SAP Sybase Error Number	2660
SQL State	WL007
SQL Code	-993L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Probable Cause	The LOAD TABLE statement automatically commits at completion. If a temporary table being loaded was declared with ON COMMIT DELETE ROWS, the rows are discarded at completion.

Error 994	"Too many arguments for function or procedure '%1'"
Constant	TOO_MANY_ARGUMENTS
SAP Sybase Error Number	2661
SQL State	42WAC
SQL Code	-994L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	<i>16</i> on page 2
Parameter 1	The name of the function or procedure.

Error 994	"Too many arguments for function or procedure '%1'"
Probable Cause	You supplied an argument list that the database server cannot handle. This can happen if the argument list of the function or stored procedure is too long. Rebuilding the database with a larger page size could prevent this error.

Error 995	"Warning detected when optimizing SELECT INTO is treated as an error"
Constant	SELECT_INTRO_WARNING_TREATED_AS_ERROR
SAP Sybase Error Number	2662
SQL State	WP016
SQL Code	-995L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The SELECT...INTO #TEMPTABLE statement cannot proceed if a warning is detected while optimizing the query. To fix the problem, test the query by removing the INTO clause, and resolve the reported warning.

Error 996	"Specified local connection ID not found"
Constant	LOCAL_CONNECTION_NOT_FOUND
SAP Sybase Error Number	2663
SQL State	WO024
SQL Code	-996L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	There is no connection with the specified connection ID.

Error 997	"Local connection ID does not refer to the current database"
Constant	LOCAL_CONNECTION_NOT_TO_CURRENT_DB
SAP Sybase Error Number	2664
SQL State	WO025
SQL Code	-997L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	The specified connection ID is for a connection to a database other than the current database.

Error 998	"Cannot close a remote JDBC connection that is not the current connection"
Constant	CANNOT_CLOSE_JDBC_CONNECTION
SAP Sybase Error Number	2665
SQL State	WO026
SQL Code	-998L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	When attempting to close a remote JDBC connection, the specified connection must be the local connection.

Error 999	"Invalid request log format on line %1"
Constant	INVALID_REQUEST_LOG_FORMAT
SAP Sybase Error Number	2667
SQL State	WW020
SQL Code	-999L
ODBC 2 State	ERROR

Error 999	"Invalid request log format on line %1"
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The line number in the log file.
Probable Cause	The request log file format is invalid. The request log may have been created with an older version of the software.

Error 1000	"Temporary space limit exceeded"
Constant	TEMP_SPACE_LIMIT
SAP Sybase Error Number	2668
SQL State	54W05
SQL Code	-1000L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>19</i> on page 2
Probable Cause	The connection has exceeded its temporary-space usage limit. This limit is based in part on the amount of free-space remaining on the drive containing the temporary file. Try deleting unused files from the drive, or placing the temporary file on a drive with more space available. See the -dt server option to specify a directory for temporary files.

Error 1001	"Parameter '%1' in procedure or function '%2' does not have a default value"
Constant	NO_DEFAULT_FOR_PARM
SAP Sybase Error Number	2669
SQL State	08W71
SQL Code	-1001L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2

Error 1001	"Parameter '%1' in procedure or function '%2' does not have a default value"
Parameter 1	The name of the parameter.
Parameter 2	The name of the procedure or function.
Probable Cause	An attempt was made to use DEFAULT as a procedure or function argument, but the corresponding parameter does not have a default value.

Error 1002	"The option '%1' is not recognized"
Constant	UNRECOGNIZED_OPTION
SAP Sybase Error Number	2670
SQL State	WW062
SQL Code	-1002L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the option.
Probable Cause	The specified option was not recognized. The option may have been spelled incorrectly.

Error 1003	"Too many distinct group mappings for integrated user"
Constant	INTEGRATED_LOGON_TOO_MANY_MAPPINGS
SAP Sybase Error Number	2671
SQL State	28W10
SQL Code	-1003L
ODBC 2 State	28000
ODBC 3 State	28000
Severity Code	16 on page 2

Error 1003	"Too many distinct group mappings for integrated user"
Probable Cause	The integrated user does not have an explicit mapping in the database but does have group mappings. There are too many distinct group mappings. You must either reduce the number of distinct group mappings or add an explicit mapping for the user.

Error 1004	"Unable to start specified database: '%1' is not a database"
Constant	FILE_NOT_DB
SAP Sybase Error Number	2672
SQL State	08W85
SQL Code	-1004L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	<i>// on page 2</i>
Parameter 1	The name of the database file.
Probable Cause	The specified file is not a valid database file.

Error 1005	"Unable to start specified database: '%1' was created by a different version of the software"
Constant	FILE_WRONG_VERSION
SAP Sybase Error Number	2673
SQL State	08W86
SQL Code	-1005L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	<i>// on page 2</i>
Parameter 1	The name of the database file.
Probable Cause	The specified database file was created by a different version of the software, and it cannot be read by this version.

1006 - 1217

Messages 1006 through 1028

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1006	"Unable to start specified database: '%1' is not a valid database file"
Constant	FILE_BAD_DB
SAP Sybase Error Number	2674
SQL State	08W87
SQL Code	-1006L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	// on page 2
Parameter 1	The name of the database file.
Probable Cause	The specified file is not a valid database.
Error 1007	"Unable to start specified database: '%1' is an invalid transaction log"
Constant	CORRUPT_REDO
SAP Sybase Error Number	2675
SQL State	08W88
SQL Code	-1007L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	// on page 2
Parameter 1	The name of the transaction log file.
Probable Cause	The specified file is not a valid transaction log.

Error 1008	"Unable to start specified database: '%1' is an invalid transaction log mirror"
Constant	CORRUPT_REDO_MIRROR
SAP Sybase Error Number	2676
SQL State	08W72
SQL Code	-1008L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	11 on page 2
Parameter 1	The name of the transaction log mirror file.
Probable Cause	The specified file is not a valid transaction log mirror.
Error 1009	"Unable to start specified database: The transaction log '%1' or its mirror '%2' is invalid"
Constant	CORRUPT_REDO_OR_MIRROR
SAP Sybase Error Number	2677
SQL State	08W73
SQL Code	-1009L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	11 on page 2
Parameter 1	The name of the transaction log file.
Parameter 2	The name of the transaction log mirror file.
Probable Cause	The transaction log differs from the transaction log mirror. Either the transaction log or its mirror is invalid.
Error 1010	"Unable to start specified database: '%1' not expecting any operations in transaction log"
Constant	EXPECTING_NO_REDO
SAP Sybase Error Number	2678

Error 1010	"Unable to start specified database: '%1' not expecting any operations in transaction log"
SQL State	08W74
SQL Code	-1010L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	<i>11</i> on page 2
Parameter 1	The name of the transaction log file.
Probable Cause	The transaction log contains operations, but the database server was not expecting any.

Error 1011	"Unable to start specified database: Unknown encryption algorithm"
Constant	UNKNOWN_ENCRYPTION_ALGORITHM
SAP Sybase Error Number	2679
SQL State	08W75
SQL Code	-1011L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	<i>11</i> on page 2
Probable Cause	The database is encrypted with an algorithm not supported by this server.

Error 1012	"Unable to start specified database: '%1' must be upgraded to start with this server (capability %2 missing)"
Constant	UPGRADE_DATABASE
SAP Sybase Error Number	2680
SQL State	08W76
SQL Code	-1012L
ODBC 2 State	08001
ODBC 3 State	08001

Error 1012	"Unable to start specified database: '%1' must be upgraded to start with this server (capability %2 missing)"
Severity Code	<i>11</i> on page 2
Parameter 1	The name of the database file.
Parameter 2	The capability that is missing from the database file.
Probable Cause	The specified database must be upgraded to start with this server.

Error 1016	"Unable to start specified database: Cannot use log file '%1' since it has been used more recently than the database file"
Constant	LOG_NEWER_THAN_DB
SAP Sybase Error Number	2684
SQL State	08W80
SQL Code	-1016L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	<i>11</i> on page 2
Parameter 1	The name of the transaction log mirror file.
Probable Cause	The transaction log file has been used more recently than the database file.

Error 1017	"Unable to start specified database: '%1': transaction log file not found"
Constant	LOG_NOT_FOUND
SAP Sybase Error Number	2685
SQL State	08W81
SQL Code	-1017L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	<i>11</i> on page 2
Parameter 1	The name of the transaction log file.

Error 1017	"Unable to start specified database: '%1': transaction log file not found"
Probable Cause	The transaction log file was not found.

Error 1018	"Unable to start specified database: Cannot use log file '%1' since the offsets do not match the offsets in the database file"
Constant	LOG_OFFSETS_DONT_MATCH
SAP Sybase Error Number	2686
SQL State	08W82
SQL Code	-1018L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	// on page 2
Parameter 1	The name of the transaction log file.
Probable Cause	The transaction log file has an offset that does not match the offset expected by the database file.

Error 1019	"Unable to start specified database: Cannot use log file '%1' since the database file has been used more recently"
Constant	LOG_OLDER_THAN_DB
SAP Sybase Error Number	2687
SQL State	08W83
SQL Code	-1019L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	// on page 2
Parameter 1	The name of the transaction log file.
Probable Cause	The database file has been used more recently than the transaction log file.

Error 1020	"Unable to start specified database: Cannot use log file '%1' since it is shorter than expected"
Constant	LOG_TOO_SHORT
SAP Sybase Error Number	2688
SQL State	08W84
SQL Code	-1020L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	11 on page 2
Parameter 1	The name of the transaction log file.
Probable Cause	The transaction log file is shorter than expected.

Error 1021	"Invalid backup operation"
Constant	INVALID_BACKUP_OPERATION
SAP Sybase Error Number	2689
SQL State	WB013
SQL Code	-1021L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The specified backup operation is not valid because of previous backup operation(s).

Error 1022	"Invalid value for attribute '%1' in service"
Constant	SERVICE_PARM_INVALID_VALUE
SAP Sybase Error Number	2691
SQL State	42WAD
SQL Code	-1022L
ODBC 2 State	ERROR

Error 1022	"Invalid value for attribute '%1' in service"
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the invalid attribute.
Probable Cause	The service definition contains a USING, FORMAT, or GROUP attribute with an invalid value.

Error 1023	"Missing value for attribute '%1' in service"
Constant	SERVICE_PARM_MISSING_VALUE
SAP Sybase Error Number	2692
SQL State	42WAE
SQL Code	-1023L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the invalid attribute.
Probable Cause	The service definition contains a USING, FORMAT, or GROUP attribute with a missing value.

Error 1024	"Unsupported property '%1' in service USING attribute"
Constant	SERVICE_PARM_UNSUPPORTED_PROPERTY
SAP Sybase Error Number	2693
SQL State	42WAF
SQL Code	-1024L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the unsupported property.
Probable Cause	The service definition contains a USING attribute with an unsupported property.

Error 1025	"Duplicate attribute '%1' in service"
Constant	SERVICE_PARM_DUPLICATE_PROPERTY
SAP Sybase Error Number	2694
SQL State	42WB0
SQL Code	-1025L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the duplicate attribute.
Probable Cause	The service definition contains a duplicate attribute.

Error 1026	"USING attribute cannot coexist with FORMAT or GROUP attributes"
Constant	SERVICE_ATTR_COEXIST
SAP Sybase Error Number	2695
SQL State	42WB1
SQL Code	-1026L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The service definition for the specified service type cannot specify a USING attribute along with a FORMAT or GROUP attribute.

Error 1027	"Service type does not allow '%1' attribute"
Constant	SERVICE_ATTR_NOT_ALLOWED
SAP Sybase Error Number	2696
SQL State	42WB2
SQL Code	-1027L
ODBC 2 State	ERROR

Error 1027	"Service type does not allow '%1' attribute"
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the attribute that is not allowed.
Probable Cause	The service definition for the specified service type does not allow the given attribute to be specified.

Error 1028	"Connection attempting BACKUP has uncommitted transactions"
Constant	BACKUP_HAS_UNCOMMITTED_TRANS
SAP Sybase Error Number	2697
SQL State	WB014
SQL Code	-1028L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	A connection attempting to perform a BACKUP...WAIT BEFORE START or BACKUP...WAIT AFTER END has uncommitted transactions. A COMMIT or ROLLBACK must be performed before executing the backup.

Messages 1029 through 1050

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1029	"Support for materialized views is not available for this database"
Constant	MAT_VIEWS_NOT_SUPPORTED
SAP Sybase Error Number	2698
SQL State	0AW15
SQL Code	-1029L
ODBC 2 State	ERROR

Error 1029	"Support for materialized views is not available for this database"
ODBC 3 State	ERROR
Severity Code	15 on page 2
Probable Cause	The statement being executed requires support for materialized views, but the database being used does not have the materialized view capability.

Error 1030	"Secure HTTP connections are not supported on this platform"
Constant	SECURE_CONNECTION_UNAVAILABLE
SAP Sybase Error Number	2699
SQL State	WW063
SQL Code	-1030L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	19 on page 2
Probable Cause	A Secure HTTP connection was attempted, but is not supported on this platform.

Error 1031	"Syntax error near '%1' -- Materialized view definition must not use the following construct: '%2'"
Constant	MATVIEW_SYNTAX_ERROR
SAP Sybase Error Number	2700
SQL State	42WB3
SQL Code	-1031L
ODBC 2 State	42000
ODBC 3 State	ERROR
Severity Code	15 on page 2
Parameter 1	Location of the feature used that is not permitted.
Parameter 2	The feature used that is not permitted.

Error 1031	"Syntax error near '%1' -- Materialized view definition must not use the following construct: '%2'"
Probable Cause	You attempted to create a materialized view whose definition violates one of the restrictions.
Error 1032	"Syntax error near '%1' -- The materialized view cannot be changed to immediate because its definition contains an illegal construct: '%2'"
Constant	UPDATABLE_MATVIEW_SYNTAX_ERROR
SAP Sybase Error Number	2701
SQL State	42WB4
SQL Code	-1032L
ODBC 2 State	42000
ODBC 3 State	ERROR
Severity Code	15 on page 2
Parameter 1	Location of the feature used that is not permitted.
Parameter 2	The feature used that is not permitted.
Probable Cause	You attempted to change the refresh type to immediate for a materialized view whose definition violates one of the restrictions.
Error 1033	"Unable to start database server: Server fatal error"
Constant	UNABLE_TO_START_ENGINE_FATAL_ERROR
SAP Sybase Error Number	2702
SQL State	08W89
SQL Code	-1033L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	17 on page 2
Probable Cause	The database server failed to start because a fatal error or assertion failure occurred. More information may be available in the Windows event log or Unix system log or by manually starting the database server.

Error 1034	"The '%1' attribute is not valid with procedure type '%2'"
Constant	INVALID_ATTRIBUTE_WITH_TYPE
SAP Sybase Error Number	2703
SQL State	WW064
SQL Code	-1034L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The attribute on the procedure.
Parameter 2	The procedure type.
Probable Cause	This attribute is not applicable to the given procedure type.

Error 1035	"LOAD TABLE ... WITH FILE NAME LOGGING not permitted on mirrored database"
Constant	LOAD_TABLE_ON_MIRRORED_DB
SAP Sybase Error Number	2704
SQL State	WL008
SQL Code	-1035L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	LOAD TABLE ... WITH FILE NAME LOGGING statements are not permitted when a database is being mirrored, since the file being loaded might not be accessible by the other server.

Error 1036	"The DBN/DBF parameters do not match the database for this alternate server name"
Constant	WRONG_DB_ON_ALT_SERVER_NAME
SAP Sybase Error Number	2705
SQL State	08W90

Error 1036	"The DBN/DBF parameters do not match the database for this alternate server name"
SQL Code	-1036L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	11 on page 2
Probable Cause	The DBN or DBF parameters specified do not match the database using the specified alternate server name.

Error 1037	"Cannot drop or modify object '%1' because at least one other object (%2 '%3') depends upon it"
Constant	OBJECT_HAS_DEPENDENTS
SAP Sybase Error Number	2706
SQL State	55W16
SQL Code	-1037L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	The name of the object that could not be dropped or modified.
Parameter 2	The type of the object that depends on the object that could not be dropped or modified.
Parameter 3	The name of the object that depends on the object that could not be dropped or modified.
Probable Cause	You attempted to drop or modify an object, such as a table or a column, that is used by another object, such as a materialized view, that cannot be automatically invalidated. The dependent object must be disabled or dropped before a drop or modification can be permitted.

Error 1038	"Cannot use view '%1' because it has been disabled"
Constant	VIEW_DISABLED
SAP Sybase Error Number	2707

Error 1038	"Cannot use view '%1' because it has been disabled"
SQL State	55W17
SQL Code	-1038L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	The name of the view.
Probable Cause	You attempted to reference a view that has been disabled. The view must be enabled before it can be used again.

Error 1039	"Cannot connect to mirror server. Use server name '%1' to find the primary server"
Constant	CONNECTED_TO_MIRROR_SERVER
SAP Sybase Error Number	2708
SQL State	08W91
SQL Code	-1039L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	11 on page 2
Parameter 1	The server name for the mirroring system.
Probable Cause	You have attempted to connect to the mirror server in a mirroring system. You should change your connection string or DSN to use the server name for the mirroring system.

Error 1040	"Cannot use view '%1' because it is invalid"
Constant	VIEW_INVALID
SAP Sybase Error Number	2709
SQL State	55W18
SQL Code	-1040L
ODBC 2 State	42000

Error 1040	"Cannot use view '%1' because it is invalid"
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	The name of the view.
Probable Cause	You attempted to reference an invalid view. The view must be enabled before it can be used again.

Error 1041	"Materialized View '%1' not found"
Constant	MATVIEW_NOT_FOUND
SAP Sybase Error Number	2710
SQL State	42WB5
SQL Code	-1041L
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	11 on page 2
Parameter 1	Name of the materialized view that could not be found.
Probable Cause	You misspelled the name of a materialized view, or you did not qualify a materialized view name with a user name. For example, you might have referred to "mat_view" instead of "owner"."mat_view".

Error 1042	"Cannot add a comment to a table declared as LOCAL TEMPORARY"
Constant	COMMENT_NOT_ALLOWED
SAP Sybase Error Number	2711
SQL State	WW065
SQL Code	-1042L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	11 on page 2

Error 1042	"Cannot add a comment to a table declared as LOCAL TEMPORARY"
Probable Cause	You attempted to add a comment to a table that has been declared as LOCAL TEMPORARY. This is not allowed.

Error 1043	"Request interrupted due to timeout"
Constant	REQUEST_TIMEOUT
SAP Sybase Error Number	2712
SQL State	57W01
SQL Code	-1043L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The current request was canceled during its execution since it ran for longer than the request_timeout database option value. The database was able to stop the operation without doing a rollback. If the statement is an INSERT, UPDATE, or DELETE, any changes made by the statement will be canceled. If the statement is a data definition statement (for example CREATE TABLE), the statement will be canceled, but the COMMIT that was done as a side effect will not be canceled.

Error 1044	"Invalid password: %1"
Constant	INVALID_NEW_PASSWORD
SAP Sybase Error Number	2713
SQL State	28W11
SQL Code	-1044L
ODBC 2 State	28000
ODBC 3 State	28000
Severity Code	16 on page 2
Probable Cause	The attempt to create a new user ID or change a password failed. The function specified by the verify_password_function option disallowed the password.

Error 1045	"Invalid backup parameter value"
Constant	INVALID_BACKUP_PARM_VALUE
SAP Sybase Error Number	2714
SQL State	WB015
SQL Code	-1045L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	One or more of the parameters supplied to the backup operation has an invalid value.

Error 1046	"Illegal column definition: %1"
Constant	ILLEGAL_COLUMN_DEFINITION
SAP Sybase Error Number	2715
SQL State	55W19
SQL Code	-1046L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	A message describing the error that occurred.
Probable Cause	You are attempting to define a column in a way that is not allowed.

Error 1047	"This database does not support encrypted tables"
Constant	ENCRYPTED_TABLES_NOT_SUPPORTED
SAP Sybase Error Number	2716
SQL State	55W20
SQL Code	-1047L
ODBC 2 State	42000
ODBC 3 State	42000

Error 1047	"This database does not support encrypted tables"
Severity Code	<i>16</i> on page 2
Probable Cause	You tried to create an encrypted table in a database that does not support them.

Error 1050	"Cannot return NULL result as requested data type"
Constant	VALUE_IS_NULL
SAP Sybase Error Number	2719
SQL State	22030
SQL Code	-1050L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Probable Cause	You tried to retrieve a value from the database that was NULL and assign it to a variable that cannot be NULL.

Messages 1051 through 1075

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1051	"Cannot create a materialized view because option '%1' has an inappropriate setting"
Constant	CANNOT_CREATE_MATVIEW
SAP Sybase Error Number	2720
SQL State	42WB6
SQL Code	-1051L
ODBC 2 State	42000
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	Name of the option with the incorrect setting.

Error 1051	"Cannot create a materialized view because option '%1' has an inappropriate setting"
Probable Cause	You attempted to create a materialized view, but one of the database options is currently set to a value not permitted while creating a materialized view.

Error 1052	"Cannot update materialized view because option '%1' has an inappropriate setting"
Constant	CANNOT_UPDATE_MATVIEW
SAP Sybase Error Number	2721
SQL State	42WB7
SQL Code	-1052L
ODBC 2 State	42000
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Name of the option with the incorrect setting.
Probable Cause	You attempted to update/refresh a materialized view but one of the database options is currently set to a value that is not permitted while updating a materialized view, or, the option's setting does not match the value when the view was created.

Error 1053	"'%1' is an invalid value for '%2'"
Constant	INVALID_OPTION_VALUE
SAP Sybase Error Number	2722
SQL State	42W85
SQL Code	-1053L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	The invalid value.
Parameter 2	Name of the option.

Error 1053	""%1' is an invalid value for '%2'"
Probable Cause	You supplied an invalid value for an option. Some options only allow numeric values and some options only allow true or false. Also, many options do not permit the empty string as a value.

Error 1054	"Snapshot isolation disabled or pending"
Constant	SNAPSHOT_ISOLATION_DISABLED
SAP Sybase Error Number	2723
SQL State	55W23
SQL Code	-1054L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	Snapshot isolation is disabled or its activation is still pending. You must enable snapshot isolation before using it.

Error 1057	"BACKUP clause '%1' conflicts with '%2'"
Constant	INVALID_BACKUP_STATEMENT
SAP Sybase Error Number	2726
SQL State	WB016
SQL Code	-1057L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	First BACKUP clause.
Parameter 2	Second BACKUP clause.
Probable Cause	Clauses specified in the BACKUP STATEMENT are mutually exclusive.

Error 1060	"Operation conflict with publication type"
Constant	CONFLICTING_PUB_TYPE

Error 1060	"Operation conflict with publication type"
SAP Sybase Error Number	2729
SQL State	5RW38
SQL Code	-1060L
ODBC 2 State	42000
ODBC 3 State	42S02
Severity Code	16 on page 2
Probable Cause	You attempted to perform an operation not applicable to the type of publication. For example, you applied operations specific to a scripted upload publication to a logscan publication.

Error 1061	"Table created or altered after start of snapshot"
Constant	SNAPSHOT_TABLE_CHANGED
SAP Sybase Error Number	2730
SQL State	42WB8
SQL Code	-1061L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	A snapshot transaction attempted to use a table that was created or altered after the transaction began.

Error 1062	"Statement not allowed during snapshot"
Constant	STATEMENT_NOT_ALLOWED_IN_SNAPSHOT
SAP Sybase Error Number	2731
SQL State	42WB9
SQL Code	-1062L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1062	"Statement not allowed during snapshot"
Severity Code	<i>16</i> on page 2
Probable Cause	A connection with an outstanding snapshot attempted to use CREATE INDEX, DROP INDEX, ALTER INDEX or ALTER TABLE. Make sure all cursors for the connection are closed.

Error 1063	"Unable to start database %1: Cannot use read-only mode if auditing is enabled"
Constant	AUDITING_DB_READ_ONLY
SAP Sybase Error Number	2732
SQL State	08W93
SQL Code	-1063L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	<i>11</i> on page 2
Parameter 1	Name of the database.
Probable Cause	The specified database has auditing enabled, and cannot be started read-only.

Error 1064	"Update conflict on snapshot transaction"
Constant	SNAPSHOT_UPDATE_CONFLICT
SAP Sybase Error Number	2733
SQL State	42WBA
SQL Code	-1064L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Probable Cause	A snapshot transaction attempted to update or delete a row that was changed by another transaction after the snapshot began.

Error 1065	"Attempt to use snapshot isolation in a non-snapshot transaction"
Constant	NON_SNAPSHOT_TRANSACTION
SAP Sybase Error Number	2734
SQL State	42WBB
SQL Code	-1065L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	A transaction tried to use snapshot isolation but did not begin with snapshot isolation.

Error 1066	"File system error: %1"
Constant	OMNI_FILE_SYSTEM_ERROR
SAP Sybase Error Number	2735
SQL State	WO027
SQL Code	-1066L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	12 on page 2
Parameter 1	Error description.
Probable Cause	This error results from an error in the underlying file system that was encountered while accessing a file directory as a proxy table.

Error 1068	"Default dbspace '%1' not found"
Constant	DEFAULT_DBSPACE_NOT_FOUND
SAP Sybase Error Number	2737
SQL State	52W43
SQL Code	-1068L
ODBC 2 State	S0002

Error 1068	"Default dbspace '%1' not found"
ODBC 3 State	42S02
Severity Code	<i>11</i> on page 2
Parameter 1	Name of the default dbspace that could not be found.
Probable Cause	You tried to create a table with the default_dbspace option set to a dbspace that could not be found.

Error 1069	"Kerberos login failed"
Constant	KERBEROS_LOGON_FAILED
SAP Sybase Error Number	2738
SQL State	28W12
SQL Code	-1069L
ODBC 2 State	28000
ODBC 3 State	28000
Severity Code	<i>16</i> on page 2
Probable Cause	The Kerberos login failed due to a failure of the client to authenticate the user's principal with the KDC or a failure of the server to authenticate the client. The most likely causes are the Kerberos principal may not be signed in, the principal's ticket may have expired, or the client, server, or KDC's system time are not within a few minutes of each other. The LogFile connection parameter or the server's -z option may provide more information.

Error 1070	"Kerberos logins are not supported"
Constant	KERBEROS_LOGONS_UNSUPPORTED
SAP Sybase Error Number	2739
SQL State	28W13
SQL Code	-1070L
ODBC 2 State	28000
ODBC 3 State	28000
Severity Code	<i>16</i> on page 2

Error 1070	"Kerberos logins are not supported"
Probable Cause	The client and/or server does not support Kerberos logins. Kerberos may not be supported by the platform, the Kerberos client software including the GSS-API runtime may not be installed or found on the client, or Kerberos was not enabled on the server. The LogFile connection parameter or the server's -z option may provide more information.

Error 1071	"The %1 algorithm is not available in FIPS mode"
Constant	FIPS_NOT_AVAILABLE
SAP Sybase Error Number	2740
SQL State	0AW16
SQL Code	-1071L
ODBC 2 State	ERROR
ODBC 3 State	08001
Severity Code	19 on page 2
Parameter 1	Name of the algorithm.
Probable Cause	The specified algorithm is not available when the server is running in FIPS mode.

Error 1072	""%1' is not a valid character set encoding for use with collation '%2'"
Constant	INVALID_ENCODING_FOR_COLLATION
SAP Sybase Error Number	2741
SQL State	WC009
SQL Code	-1072L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The character set encoding that is invalid.
Parameter 2	The collation for which the character set encoding is invalid.

Error 1072	""%1' is not a valid character set encoding for use with collation '%2'"
Probable Cause	The specified character set cannot be used with the specified collation.

Error 1073	""%1' cannot be used as the NCHAR collation: only UCA and UTF8BIN may be used"
Constant	INVALID_NCHAR_COLLATION
SAP Sybase Error Number	2742
SQL State	WC010
SQL Code	-1073L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The collation that cannot be used as the NCHAR collation.
Probable Cause	The specified collation cannot be used as the NCHAR collation. NCHAR always uses UTF-8, so the collation must be either UCA or UTF8BIN.

Error 1074	"Login mode '%1' not permitted by login_mode setting"
Constant	LOGON_MODE_NOT_PERMITTED
SAP Sybase Error Number	2743
SQL State	28W14
SQL Code	-1074L
ODBC 2 State	28000
ODBC 3 State	28000
Severity Code	16 on page 2
Parameter 1	Name of the login mode not included in the current login_mode database option setting.

Error 1074	"Login mode '%1' not permitted by login_mode setting"
Probable Cause	You attempted to connect using a login mode not included in the current login_mode database option setting. Change the option setting or connect using a different login mode.

Error 1075	"Failed to convert from character set '%1' to '%2'"
Constant	FAILED_TO_CONVERT_CHARSET
SAP Sybase Error Number	2744
SQL State	WC011
SQL Code	-1075L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The character set of the input string.
Parameter 2	The character set of the output string.
Probable Cause	The server failed to convert between the two specified character sets. This could happen when the dbicu and dbicudt DLLs are not installed.

Messages 1076 through 1096

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1076	"dbicu libraries are required but not installed"
Constant	ICU_NOT_AVAILABLE
SAP Sybase Error Number	2745
SQL State	WC012
SQL Code	-1076L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2

Error 1076	"dbicu libraries are required but not installed"
Probable Cause	The server is unable to load ICU components that are required by this database. Ensure that the dbicu and dbicudt DLLs are installed.

Error 1077	"Cannot use materialized view '%1' because it has not yet been initialized"
Constant	CANNOT_USE_MATVIEW
SAP Sybase Error Number	2746
SQL State	42WBC
SQL Code	-1077L
ODBC 2 State	42000
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Name of the materialized view.
Probable Cause	You attempted to use a materialized view but it has not yet been initialized. In order for a materialized view to become available for first use after being created or enabled, it must be initialized at least once using the REFRESH MATERIALIZED VIEW statement.

Error 1078	"Cycle in computed column dependencies"
Constant	COMPUTED_COLUMN_CYCLE
SAP Sybase Error Number	2747
SQL State	42WBD
SQL Code	-1078L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	The table has a cycle in the dependencies between its computed columns. Cycles are not allowed.

Error 1079	"Backup is unable to open database file '%1'"
Constant	BACKUP_UNABLE_TO_OPEN_FILE
SAP Sybase Error Number	2748
SQL State	WB017
SQL Code	-1079L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the file.
Probable Cause	The database file cannot be opened by the backup. It may have been erased or otherwise corrupted.

Error 1080	"Cannot revoke these permissions while user '%1' is actively replicating transactions"
Constant	MUST_NOT_BE_REPLICATING
SAP Sybase Error Number	2749
SQL State	42WBE
SQL Code	-1080L
ODBC 2 State	40001
ODBC 3 State	40001
Severity Code	16 on page 2
Parameter 1	The name of the user.
Probable Cause	You attempted to revoke permissions from a user while there are transactions currently being replicated for that user. This is not allowed.

Error 1081	"Could not refresh tracing: at least one enabled tracing level must be specified"
Constant	NO_TRACING_LEVELS
SAP Sybase Error Number	2750
SQL State	55W24

Error 1081	"Could not refresh tracing: at least one enabled tracing level must be specified"
SQL Code	-1081L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	Table sa_diagnostic_tracing_level contains no rows (tracing levels) or no tracing levels are enabled.

Error 1082	"Could not refresh tracing: invalid tracing specification on sa_diagnostic_tracing_level row %1"
Constant	INVALID_TRACING_SPEC
SAP Sybase Error Number	2751
SQL State	WW066
SQL Code	-1082L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The primary key of the row that is invalid.
Probable Cause	You specified an invalid combination of values for the tracing level. Some invalid combinations are: specified condition is not valid for the tracing type, or specified tracing type is not valid for the scope.

Error 1083	"Could not refresh tracing: failed to find object %1 on row %2"
Constant	TRACING_OBJ_NOT_FOUND
SAP Sybase Error Number	2752
SQL State	WW067
SQL Code	-1083L
ODBC 2 State	ERROR

Error 1083	"Could not refresh tracing: failed to find object %1 on row %2"
ODBC 3 State	ERROR
Severity Code	11 on page 2
Parameter 1	The specified name of the object.
Parameter 2	The primary key of the row on which the check failed.
Probable Cause	You misspelled the object name, or you did not qualify the name with user (and, possibly, table) name. For example, you might have referred to table_name instead of "owner"."table_name", or you might have referred to table_name_trigger instead of "owner"."table_names"."table_name_trigger".

Error 1084	"Use of feature '%1' is not allowed"
Constant	SECURE_FEATURE
SAP Sybase Error Number	2753
SQL State	57W02
SQL Code	-1084L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Name of the SQL statement or feature.
Probable Cause	You have attempted to use a feature that was disabled by the server administrator when the database server was started.

Error 1085	"Duplicate key column (%1)"
Constant	DUPLICATE_KEY_COLUMN
SAP Sybase Error Number	2754
SQL State	42WC0
SQL Code	-1085L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2

Error 1085	"Duplicate key column (%1)"
Parameter 1	The name of the duplicate column.
Probable Cause	You supplied a duplicate column name in the list of columns for the key of a primary key, foreign key, or unique constraint, or an index.

Error 1087	"Could not refresh tracing: volatile_statistics have to be collected in order for %1 specified on row %2 to be collected"
Constant	NO_VOLATILE_LEVEL_SPEC
SAP Sybase Error Number	2756
SQL State	WW068
SQL Code	-1087L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The tracing level that caused the error.
Parameter 2	The primary key of the row on which the check failed.
Probable Cause	Volatile statistics have to be collected in order for the non-volatile and connection statistics to be collected.

Error 1088	"ATTACH TRACING TO LOCAL DATABASE cannot be used with a strongly encrypted database"
Constant	NO_LOCAL_CONNECTIONS_TO_ENCRYPTED
SAP Sybase Error Number	2757
SQL State	WW069
SQL Code	-1088L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>

Error 1088	"ATTACH TRACING TO LOCAL DATABASE cannot be used with a strongly encrypted database"
Probable Cause	The local database is strongly encrypted, so you cannot use the LOCAL DATABASE clause of the ATTACH TRACING statement. You must specify a connection string with the encryption key for the database.

Error 1089	"Invalid commit action for shared temporary table"
Constant	INVALID_SHARED_COMMIT_ACTION
SAP Sybase Error Number	2758
SQL State	52W26
SQL Code	-1089L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	A global shared temporary table must be declared as ON COMMIT PRESERVE ROWS or NOT TRANSACTIONAL.

Error 1090	"Function '%1' has invalid parameter '%2' ('%3')"
Constant	INVALID_PARAMETER_W_PARM
SAP Sybase Error Number	2759
SQL State	08W94
SQL Code	-1090L
ODBC 2 State	08004
ODBC 3 State	08004
Severity Code	18 on page 2
Parameter 1	The name of the function.
Parameter 2	The name of the parameter.
Parameter 3	Information about the parameter that caused the error.
Probable Cause	An error occurred while evaluating a parameter.

Error 1091	"Constraint '%1' violated: Invalid value in table '%2'"
Constant	TABLE_CONSTRAINT_VIOLATED
SAP Sybase Error Number	2760
SQL State	23508
SQL Code	-1091L
ODBC 2 State	42000
ODBC 3 State	23000
Severity Code	16 on page 2
Parameter 1	Name of the constraint (if defined) that was violated by an invalid value.
Parameter 2	Name of the table containing the column.
Probable Cause	You attempted an insert or update that violates a CHECK constraint. A CHECK constraint is violated if it evaluates to FALSE; it is deemed to hold if the condition evaluates to TRUE or UNKNOWN.

Error 1092	"The method you attempted to invoke was not enabled for your application"
Constant	FEATURE_NOT_ENABLED
SAP Sybase Error Number	2762
SQL State	0A001
SQL Code	-1092L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You attempted to call a method or use a feature that has not been enabled. In UltraLite, features are enabled using ULEnable functions or by using ULEnableDatabaseManager instead of ULEnableDatabaseManagerNoSQL.

Error 1093	"The size of the character column, variable, or value data type exceeds 32767"
Constant	CHAR_FIELD_SIZE_EXCEEDED
SAP Sybase Error Number	2763
SQL State	54W09
SQL Code	-1093L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	19 on page 2
Probable Cause	The declaration or conversion has specified a character type with byte length greater than 32767.

Error 1094	"The HTTP header '%1' is reserved and cannot be modified"
Constant	HTTP_HEADER_ATTRIBUTE_RESERVED_XXX
SAP Sybase Error Number	2764
SQL State	WW070
SQL Code	-1094L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The header causing the failure.
Probable Cause	The specified HTTP header is reserved and cannot be modified.

Error 1095	"The specified HTTP header contains illegal or non-ASCII characters"
Constant	HTTP_HEADER_ATTRIBUTE_ASCII
SAP Sybase Error Number	2765
SQL State	WW071
SQL Code	-1095L

Error 1095	"The specified HTTP header contains illegal or non-ASCII characters"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	HTTP headers must contain printable ASCII characters.

Error 1096	"The specified HTTP header is malformed"
Constant	HTTP_HEADER_ATTRIBUTE_MALFORMED
SAP Sybase Error Number	2766
SQL State	WW072
SQL Code	-1096L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	The HTTP header is missing the colon delimiter or a folding construct is malformed.

Messages 1097 through 1117

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1097	"ATTACH TRACING could not connect to the tracing database"
Constant	ATTACH_TRACING_FAILED
SAP Sybase Error Number	2767
SQL State	08W95
SQL Code	-1097L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1097	"ATTACH TRACING could not connect to the tracing database"
Severity Code	<i>16</i> on page 2
Probable Cause	A connection to the tracing database could not be established. Check your connection string and verify that other clients can connect. Note that if you are trying to attach tracing to another server, perhaps the connection is being blocked by a firewall.

Error 1098	"A tracing connection is already active"
Constant	TRACING_ALREADY_ATTACHED
SAP Sybase Error Number	2768
SQL State	08W96
SQL Code	-1098L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Probable Cause	This database is already participating in a tracing connection, either as the sender (the database being traced) or as the receiver (the tracing database). A database can only send or receive one stream of tracing data at a time.

Error 1099	"Transact-SQL outer joins are currently disabled"
Constant	TSQL_OUTER_JOINS_DISABLED
SAP Sybase Error Number	2769
SQL State	55W25
SQL Code	-1099L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>15</i> on page 2

Error 1099	"Transact-SQL outer joins are currently disabled"
Probable Cause	The ability to specify a Transact-SQL outer join in a query is currently disabled by the setting of the <code>tsql_outer_joins</code> connection option. Transact-SQL outer joins are deprecated in this release of SQL Anywhere.
Error 1100	"The operation failed because column '%1's type does not support streaming"
Constant	COLUMN_NOT_STREAMABLE
SAP Sybase Error Number	2771
SQL State	WW045
SQL Code	-1100L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The number of the column whose type is invalid.
Probable Cause	The only column types that support streaming are: BINARY, LONG BINARY, VARCHAR and LONG VARCHAR. This error could also occur when allocating a stream object twice on the same column.
Error 1101	"Column '%1' not part of any indexes in its containing table"
Constant	COLUMN_NOT_INDEXED
SAP Sybase Error Number	2772
SQL State	WW073
SQL Code	-1101L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the column not found in any index.

Error 1101	"Column '%1' not part of any indexes in its containing table"
Probable Cause	The specified column is not part of any indexes belonging to the containing table.

Error 1102	"Unable to retry download because upload is not finished"
Constant	DOWNLOAD_RESTART_FAILED
SAP Sybase Error Number	2773
SQL State	WW074
SQL Code	-1102L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The MobiLink server could not restart the download because the MobiLink server has not received the entire upload stream.

Error 1103	"No partial download was found"
Constant	PARTIAL_DOWNLOAD_NOT_FOUND
SAP Sybase Error Number	2774
SQL State	WW075
SQL Code	-1103L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	A partial download was not found for the synchronizing user. This error could occur if trying to resume from a non-existent partial download or trying to rollback a non-existent partial download.

Error 1104	"Too many users in database"
Constant	TOO_MANY_USERS

Error 1104	"Too many users in database"
SAP Sybase Error Number	2775
SQL State	54W10
SQL Code	-1104L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You have exceeded the maximum number of users permitted to access the database. The maximum number of users that are allowed granted access to a single UltraLite database is four.

Error 1106	"Too many publications specified for operation"
Constant	TOO_MANY_PUBLICATIONS
SAP Sybase Error Number	2777
SQL State	WW077
SQL Code	-1106L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You have specified too many publications for the required operation. For example, when retrieving the last download timestamp, you are only allowed to select one publication.

Error 1107	"Too many references to a BLOB"
Constant	TOO_MANY_BLOB_REFS
SAP Sybase Error Number	2778
SQL State	54W11
SQL Code	-1107L

Error 1107	"Too many references to a BLOB"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	You have exceeded the maximum number of references to a particular BLOB. In UltraLite you may have at most 256 references to any one particular BLOB.

Error 1108	"Unable to access the file system on the device"
Constant	CANNOT_ACCESS_FILESYSTEM
SAP Sybase Error Number	2779
SQL State	WW078
SQL Code	-1108L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	On a Palm device, you have tried to utilize the VFS file system, but that feature has not been enabled on the device.

Error 1109	"Unable to perform requested operation since this database uses keyless encryption"
Constant	KEYLESS_ENCRYPTION
SAP Sybase Error Number	2780
SQL State	WW079
SQL Code	-1109L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>

Error 1109	"Unable to perform requested operation since this database uses keyless encryption"
Probable Cause	The operation you requested on the encryption key failed since the UltraLite database uses keyless encryption. This can occur when you try to change the encryption key for a database that uses keyless encryption (obfuscation for example).

Error 1110	"UltraLite cannot synchronize because a synchronization is already running"
Constant	SYNC_NOT_REENTRANT
SAP Sybase Error Number	2781
SQL State	WW080
SQL Code	-1110L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You attempted to synchronize an UltraLite database which is already synchronizing. You must wait until the current synchronization completes before starting another. UltraLite allows most operations to run concurrently with synchronization, but only a single synchronization can be active at a time. This is generally caused by two different threads attempting a synchronize call or statement at the same time.

Error 1111	"Information for synchronization was not provided"
Constant	SYNC_INFO_REQUIRED
SAP Sybase Error Number	2782
SQL State	WW081
SQL Code	-1111L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2

Error 1111	"Information for synchronization was not provided"
Probable Cause	You must supply information for synchronization in the synchronization call.

Error 1112	"Specified file system volume not found for database '%1'"
Constant	FILE_VOLUME_NOT_FOUND
SAP Sybase Error Number	2783
SQL State	WW082
SQL Code	-1112L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the database.
Probable Cause	The file system volume you specified in the database file name was not found. Check the volume name or ordinal.

Error 1113	"Correlation name '%1' is not valid for use with the ROWID function"
Constant	INVALID_CORRELATION_FOR_ROWID
SAP Sybase Error Number	2784
SQL State	42WBF
SQL Code	-1113L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	15 on page 2
Parameter 1	Name of the invalid correlation name.
Probable Cause	The correlation name used was not valid for the ROWID function. Only the correlation names of base tables, temporary tables, global temporary tables or proxy tables may be used with the ROWID function. The argument of a ROWID function should not refer to a view, derived table, common table expression, or a procedure.

Error 1114	"Invalid setting for SOAP header '%1'"
Constant	INVALID_SOAP_HEADER_SETTING
SAP Sybase Error Number	2785
SQL State	42W86
SQL Code	-1114L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Name of the invalid SOAP header.
Probable Cause	You supplied an invalid value for a SOAP header.

Error 1115	"Table '%1' contains an invalid reference to the ROWID function"
Constant	INVALID_ROWID_PLACEMENT
SAP Sybase Error Number	2786
SQL State	42WC1
SQL Code	-1115L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	15 on page 2
Parameter 1	Name of the table that contains the invalid reference.
Probable Cause	The ROWID function cannot be used in a computed column expression or in a CHECK constraint.

Error 1116	"Collation '%1' not supported on this platform"
Constant	COLLATION_NOT_SUPPORTED
SAP Sybase Error Number	2787
SQL State	WC013
SQL Code	-1116L

Error 1116	"Collation '%1' not supported on this platform"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The collation that is not supported.
Probable Cause	The specified collation is not supported on the current platform.

Error 1117	"A row cannot be stored because it exceeds the database page size"
Constant	ROW_EXCEEDS_PAGE_SIZE
SAP Sybase Error Number	2789
SQL State	WW083
SQL Code	-1117L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You attempted to insert or update a row which is too large to be stored on a database page. For UltraLite, with the exception of BLOB columns, a row must fit entirely on a single database page. Larger page sizes may be used to accommodate larger rows.

Messages 1118 through 1137

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1118	"Cannot change the MobiLink remote ID when the status of the last upload is unknown"
Constant	CANNOT_CHANGE_ML_REMOTE_ID
SAP Sybase Error Number	2790
SQL State	0AW17
SQL Code	-1118L

Error 1118	"Cannot change the MobiLink remote ID when the status of the last upload is unknown"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The MobiLink server uses the remote ID to track synchronization progress. If the status of the previous upload is unknown then you must resolve this condition before changing the remote ID.

Error 1119	"The '%1' property is no longer supported"
Constant	UNSUPPORTED_PROPERTY
SAP Sybase Error Number	2791
SQL State	42WC2
SQL Code	-1119L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the invalid property.
Probable Cause	The specified property is not supported in the current release.

Error 1120	"The dbspace '%1' cannot be dropped because it contains tables or indexes"
Constant	DBSPACE_CONTAINS_TABLES
SAP Sybase Error Number	2792
SQL State	55W26
SQL Code	-1120L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the dbspace

Error 1120	"The dbspace '%1' cannot be dropped because it contains tables or indexes"
Probable Cause	You attempted to drop the named dbspace, but it contains tables or indexes. You must drop the tables and/or indexes before dropping the dbspace.

Error 1121	"Not enough free space on device to grow dbspace '%1' by requested amount"
Constant	NO_ROOM_TO_GROW_DBSPACE
SAP Sybase Error Number	2793
SQL State	57W03
SQL Code	-1121L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the dbspace
Probable Cause	You attempted to grow a dbspace using the ALTER DBSPACE statement, but there is not enough free space on the device to grow by the amount specified.

Error 1122	"Exceeded maximum of '%1' allowable parameters"
Constant	INVALID_MAXIMUM_PARAMETERS
SAP Sybase Error Number	2794
SQL State	WW084
SQL Code	-1122L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The maximum number of allowable parameters
Probable Cause	The maximum allowable parameters for the given web client procedure or function has been exceeded.

Error 1123	"Invalid mime type '%1'"
Constant	INVALID_MIMETYPE
SAP Sybase Error Number	2795
SQL State	WW085
SQL Code	-1123L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the mime type
Probable Cause	The mime type specifier is invalid.

Error 1124	"The dbicu library and server versions do not match."
Constant	ICU_DLL_VERSION_MISMATCH
SAP Sybase Error Number	2796
SQL State	WC014
SQL Code	-1124L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The server is unable to load ICU components that are required by this database. Ensure that the correct version of the dbicu libraries are installed.

Error 1125	"Conflicting INSTEAD OF trigger and WITH CHECK OPTION on view '%1'"
Constant	CHECK_TRIGGER_CONFLICT
SAP Sybase Error Number	2797
SQL State	42W39
SQL Code	-1125L

Error 1125	"Conflicting INSTEAD OF trigger and WITH CHECK OPTION on view '%1'"
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	15 on page 2
Parameter 1	Name of the view with an INSTEAD OF trigger
Probable Cause	You attempted an operation that involves a WITH CHECK OPTION clause that conflicts with an INSTEAD OF trigger. A view defined with the WITH CHECK OPTION clause cannot refer to a view (possibly nested) with an INSTEAD OF trigger.

Error 1126	"Operation failed because table or view '%1' has an INSTEAD OF trigger"
Constant	INSTEAD_TRIGGER
SAP Sybase Error Number	2798
SQL State	42W3A
SQL Code	-1126L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	15 on page 2
Parameter 1	Name of the view or table with an INSTEAD OF trigger
Probable Cause	You attempted an operation that cannot succeed because an INSTEAD OF trigger is defined on a target table or view (possibly nested in another view).

Error 1127	"Positioned update operation attempted on a view with an INSTEAD OF trigger"
Constant	INSTEAD_TRIGGER_POSITIONED
SAP Sybase Error Number	2799
SQL State	42W3B
SQL Code	-1127L

Error 1127	"Positioned update operation attempted on a view with an INSTEAD OF trigger"
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	15 on page 2
Probable Cause	You attempted a positioned update, positioned delete, put, or wide insert operation that would involve an INSTEAD OF trigger on a view (possibly nested). These operations are not supported with INSTEAD OF triggers on views.

Error 1128	"Start date/time for non-recurring event '%1' is in the past"
Constant	EVENT_START_TIME_IN_PAST
SAP Sybase Error Number	2800
SQL State	WE010
SQL Code	-1128L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	15 on page 2
Parameter 1	Name of the event being scheduled.
Probable Cause	You have specified an event starting date or time that has already passed, and the event is not recurring.

Error 1129	"The '%1' attribute contains mismatched parentheses within '%2'"
Constant	INVALID_ATTRIBUTE_MISMATCH_BRACES
SAP Sybase Error Number	2801
SQL State	WW086
SQL Code	-1129L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1129	"The '%1' attribute contains mismatched parentheses within '%2'"
Severity Code	<i>16</i> on page 2
Parameter 1	The attribute on the procedure.
Parameter 2	The value of the attribute.
Probable Cause	The value of the attribute is not valid due to mismatched parenthesis (or possibly braces if specifying a port option).

Error 1130	"The '%1' attribute is missing a comma within '%2'"
Constant	INVALID_ATTRIBUTE_MISSING_COMMA
SAP Sybase Error Number	2802
SQL State	WW087
SQL Code	-1130L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The attribute on the procedure.
Parameter 2	The value of the attribute.
Probable Cause	The value of the attribute is not valid due to a missing comma.

Error 1131	"The attribute '%1' sets an option '%2' that is incompatible with '%3'"
Constant	INVALID_ATTRIBUTE_OPTIONS
SAP Sybase Error Number	2803
SQL State	WW088
SQL Code	-1131L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The attribute on the procedure.

Error 1131	"The attribute '%1' sets an option '%2' that is incompatible with '%3'"
Parameter 2	The first option of the attribute.
Parameter 3	The second option of the attribute.
Probable Cause	The options specified for this attribute are not compatible.

Error 1132	"Maximum row size for table '%1' would be exceeded"
Constant	MAX_ROW_SIZE_EXCEEDED
SAP Sybase Error Number	2804
SQL State	WW089
SQL Code	-1132L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Table name.
Probable Cause	You tried to create or alter a table with a maximum row size greater than 64 KB. In UltraLite, tables must be defined such that the maximum row size (the sum of the bytes required to store each column) is less than 64 KB.

Error 1133	"Invalid trigger type for view '%1'"
Constant	INVALID_TRIGGER_VIEW
SAP Sybase Error Number	2805
SQL State	42W3C
SQL Code	-1133L
ODBC 2 State	42000
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Name of the view

Error 1133	"Invalid trigger type for view '%1'"
Probable Cause	You attempted to create a trigger on a view, but the type of trigger is supported on base tables only. Only INSTEAD OF triggers can be created on views.

Error 1134	"Triggers cannot be created on materialized view '%1'"
Constant	INVALID_TRIGGER_MATVIEW
SAP Sybase Error Number	2806
SQL State	42W3D
SQL Code	-1134L
ODBC 2 State	42000
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Name of the materialized view
Probable Cause	You attempted to create a trigger on a materialized view. A materialized view is not a valid target for a trigger.

Error 1135	"Invalid regular expression: %1 in '%2'"
Constant	INVALID_REGULAR_EXPRESSION
SAP Sybase Error Number	2808
SQL State	2201B
SQL Code	-1135L
ODBC 2 State	S1000
ODBC 3 State	2201B
Severity Code	16 on page 2
Parameter 1	The reason the regular expression is invalid.
Parameter 2	The invalid regular expression.
Probable Cause	The specified regular expression is invalid.

Error 1136	"Invalid use of escape character '%1'"
Constant	INVALID_USE_OF_ESCAPE_CHARACTER
SAP Sybase Error Number	2809
SQL State	2200C
SQL Code	-1136L
ODBC 2 State	S1000
ODBC 3 State	2200C
Severity Code	16 on page 2
Parameter 1	The escape character that is invalid.
Probable Cause	The specified escape character cannot be used.

Error 1137	"Escape character conflict '%1'"
Constant	ESCAPE_CHARACTER_CONFLICT
SAP Sybase Error Number	2810
SQL State	2200B
SQL Code	-1137L
ODBC 2 State	S1000
ODBC 3 State	2200B
Severity Code	16 on page 2
Parameter 1	The escape character that is invalid.
Probable Cause	The specified escape character cannot be used.

Messages 1138 through 1157

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1138	"The mirror '%1' does not match database '%2'"
Constant	MIRROR_FILE_MISMATCH
SAP Sybase Error Number	2811

Error 1138	"The mirror '%1' does not match database '%2'"
SQL State	WW090
SQL Code	-1138L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the mirror file
Parameter 2	The name of the database file
Probable Cause	The named mirror file does not correspond to the database file. This could happen if the database was not shut down properly, or if the wrong mirror file was specified. The mirror file must be moved or discarded before proceeding, or a different mirror specified.

Error 1139	"The remote data access feature is not supported on this platform"
Constant	OMNI_FEATURE_NOT_SUPPORTED
SAP Sybase Error Number	2812
SQL State	0AW18
SQL Code	-1139L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Probable Cause	You attempted to use a remote data access feature; however, remote data access is not supported on this platform.

Error 1140	"Unable to start database \"%1\": CHAR collation or tailoring not supported on this platform"
Constant	CHAR_COLLATION_NOT_SUPPORTED
SAP Sybase Error Number	2813
SQL State	WC015
SQL Code	-1140L

Error 1140	"Unable to start database \"%1\": CHAR collation or tailoring not supported on this platform"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The database name.
Probable Cause	The specified CHAR collation is not supported on the current platform.

Error 1141	"Unable to start database \"%1\": NCHAR collation or tailoring not supported on this platform"
Constant	NCHAR_COLLATION_NOT_SUPPORTED
SAP Sybase Error Number	2814
SQL State	WC016
SQL Code	-1141L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The database name.
Probable Cause	The specified NCHAR collation is not supported on the current platform.

Error 1142	"Use of statement '%1', which requires feature '%2', is not allowed"
Constant	SECURE_STATEMENT
SAP Sybase Error Number	2815
SQL State	57W04
SQL Code	-1142L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2

Error 1142	"Use of statement '%1', which requires feature '%2', is not allowed"
Parameter 1	Name of the SQL statement.
Parameter 2	Name of the feature.
Probable Cause	You have attempted to use a statement which requires a feature that was disabled by the server administrator when the database server was started.

Error 1143	"Encryption has not been enabled."
Constant	ENCRYPTION_NOT_ENABLED
SAP Sybase Error Number	2816
SQL State	55W27
SQL Code	-1143L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You attempted to use encryption without first enabling it. Call ULEnableAesDBEncryption or ULEnableAesFipsDBEncryption to enable encryption.

Error 1144	""%1' cannot be used as the encoding specification for '%2' data"
Constant	INVALID_OPENSTRING_ENCODING
SAP Sybase Error Number	2818
SQL State	WC017
SQL Code	-1144L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The encoding that has been specified

Error 1144	""%1' cannot be used as the encoding specification for '%2' data"
Parameter 2	The data type for which the encoding has been specified
Probable Cause	The specified encoding cannot be used for interpreting the given data. For CHAR data, the encoding must be the database's CHAR character encoding and for NCHAR data, it must be the database's NCHAR character encoding.

Error 1145	"Unable to connect: The server did not accept the requested encryption type"
Constant	ENCRYPTION_TYPE_NOT_ACCEPTED
SAP Sybase Error Number	2819
SQL State	08W97
SQL Code	-1145L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	16 on page 2
Probable Cause	The server only accepts certain encryption types, and the connection's encryption type is not one of the accepted types. The -ec server option is used to configure the encryption types that the server accepts.

Error 1146	"LOAD TABLE not allowed on temporary table which has foreign key references from another table"
Constant	INVALID_LOAD_TABLE_WITH_FOREIGN_KEY
SAP Sybase Error Number	2820
SQL State	WL009
SQL Code	-1146L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2

Error 1146	"LOAD TABLE not allowed on temporary table which has foreign key references from another table"
Probable Cause	The LOAD TABLE statement removes all rows in a temporary table upon failure. If a temporary table being loaded caused an error then the foreign rows would be orphaned.

Error 1147	"Database '%1' cannot be started on this platform. See http://ianywhere.com/developer/product_manuals/sqlanywhere/notes/en/endian_corruption_warning.html"
Constant	POSSIBLE_DATABASE_CORRUPTION
SAP Sybase Error Number	2821
SQL State	08W98
SQL Code	-1147L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	11 on page 2
Parameter 1	The name of the database.
Probable Cause	It was determined that the database may be corrupt. More information and instructions on how to proceed are available at: http://ianywhere.com/developer/product_manuals/sqlanywhere/notes/en/endian_corruption_warning.html

Error 1148	"Feature not supported by the client version or the client interface"
Constant	NOT_SUPPORTED_BY_CLIENT
SAP Sybase Error Number	2824
SQL State	0AW19
SQL Code	-1148L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2

Error 1148	"Feature not supported by the client version or the client interface"
Probable Cause	You have attempted to use a feature which the server supports but the client does not. To use the feature, you must upgrade the client library or use a different client interface. Some features are not supported by the jConnect or Open Client client interfaces.

Error 1149	"Database '%1' cannot be started on this platform. See http://ianywhere.com/developer/product_manuals/sqlanywhere/notes/en/indian_cant_change_platform.html"
Constant	DATABASE_ENDIAN_FAILURE
SAP Sybase Error Number	2825
SQL State	08W99
SQL Code	-1149L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	// on page 2
Parameter 1	The name of the database.
Probable Cause	It was determined that the database cannot be started on the current platform because doing so could possibly cause an endian related database file corruption. It will continue to start without problems on a platform with the opposite endian. More information and instructions on how to proceed are available at: http://ianywhere.com/developer/product_manuals/sqlanywhere/notes/en/indian_cant_change_platform.html

Error 1150	"The SQL scripts DLL cannot be loaded"
Constant	INVALID_SCRIPT_DLL
SAP Sybase Error Number	2826
SQL State	WW091
SQL Code	-1150L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1150	"The SQL scripts DLL cannot be loaded"
Severity Code	<i>16 on page 2</i>
Probable Cause	The SQL scripts DLL cannot be loaded. The DLL might be missing or the version found might not match the version of the database server being used.

Error 1151	"The logging type ('%1') specified is invalid, not supported or incompatible"
Constant	INVALID_LOAD_LOGGING_TYPE
SAP Sybase Error Number	2827
SQL State	WL010
SQL Code	-1151L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>19 on page 2</i>
Parameter 1	The specified logging type.
Probable Cause	The logging type specified for LOAD TABLE is not supported for the version of the database being used, is incompatible with other specifications of the statement or is not supported for the specific table being loaded into.

Error 1152	"Password has expired"
Constant	PASSWORD_EXPIRED
SAP Sybase Error Number	2828
SQL State	08WA0
SQL Code	-1152L
ODBC 2 State	28000
ODBC 3 State	28000
Severity Code	<i>16 on page 2</i>

Error 1152	"Password has expired"
Probable Cause	You attempted to connect using a valid user ID, but with an expired password. You can change your password by supplying the New-Password connection parameter along with the current expired password.

Error 1153	"Password has expired but cannot be changed because the database is read-only"
Constant	PASSWORD_EXPIRED_READONLY_DB
SAP Sybase Error Number	2829
SQL State	08WA1
SQL Code	-1153L
ODBC 2 State	28000
ODBC 3 State	28000
Severity Code	16 on page 2
Probable Cause	You attempted to connect to a read-only database using a valid user ID, but with an expired password. The password cannot be changed unless the database is started without the -r option on the database server command line. Removing -r will permit modifications to the database.

Error 1154	"Traced query (%1, %2) does not exist"
Constant	INVALID_TRACED_PLAN
SAP Sybase Error Number	2830
SQL State	55W28
SQL Code	-1154L
ODBC 2 State	28000
ODBC 3 State	28000
Severity Code	16 on page 2
Parameter 1	The specified logging session ID.
Parameter 2	The specified query ID.

Error 1154	"Traced query (%1, %2) does not exist"
Probable Cause	You attempted to generate a graphical plan for a query saved by diagnostic tracing, identified by a logging_session_id and query ID. However, no such query exists in this database. If it was traced, it was sent to a different database.

Error 1155	"Unable to close the cursor on table \"%1\". LOAD TABLE cannot be executed."
Constant	CANNOT_LOAD_TEMP_WITH_CURSOR
SAP Sybase Error Number	2831
SQL State	WL011
SQL Code	-1155L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the table.
Probable Cause	You cannot perform LOAD TABLE on a temporary table that has an open cursor on it. An attempt to close the cursor failed. A failed LOAD TABLE would cause all of the rows in the temporary table to be deleted thereby invalidating the cursor.

Error 1156	"Argument \"%1\" must be a column reference."
Constant	TEXT_BAD_COLUMN_REFERENCE
SAP Sybase Error Number	2832
SQL State	WT001
SQL Code	-1156L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The argument number.
Probable Cause	The CONTAINS argument must be a column reference.

Error 1157	"All column reference arguments must refer to the same table."
Constant	TEXT_TOO_MANY_TABLE_REFERENCES
SAP Sybase Error Number	2833
SQL State	WT002
SQL Code	-1157L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	All column references in a CONTAINS query must refer to the same table.

Messages 1158 through 1177

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1158	"No matching text index."
Constant	TEXT_NO_MATCHING_INDEX
SAP Sybase Error Number	2834
SQL State	WT003
SQL Code	-1158L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	A single text index must exist on all columns referenced in a CONTAINS query.

Error 1159	"Non-constant or unknown text query string."
Constant	TEXT_QUERY_NOT_KNOWN
SAP Sybase Error Number	2835
SQL State	WT004

Error 1159	"Non-constant or unknown text query string."
SQL Code	-1159L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The query string argument to a CONTAINS query must be a constant, or a non-null value in a variable.

Error 1160	"Text configuration \"%1\".\"%2\" not found."
Constant	TEXT_CONFIG_NOT_FOUND
SAP Sybase Error Number	2836
SQL State	WT005
SQL Code	-1160L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The text configuration creator.
Parameter 2	The text configuration name.
Probable Cause	The specified text configuration does not exist.

Error 1161	"Text configuration \"%1\" already exists."
Constant	TEXT_CONFIG_ALREADY_EXISTS
SAP Sybase Error Number	2837
SQL State	WT006
SQL Code	-1161L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The text configuration name.

Error 1161	"Text configuration \"%1\" already exists."
Probable Cause	The specified text configuration name already exists.

Error 1162	"Term length outside allowed range."
Constant	TEXT_BAD_TERM_LENGTH
SAP Sybase Error Number	2838
SQL State	WT007
SQL Code	-1162L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The minimum and maximum term lengths must both be greater than 0 and less than or equal to 60 characters.

Error 1163	"Invalid collation: \"%1\"."
Constant	TEXT_BAD_COLLATION
SAP Sybase Error Number	2839
SQL State	WT008
SQL Code	-1163L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The invalid collation string.
Probable Cause	The collation was not found, or the tailoring options were invalid.

Error 1164	"Text query parser error: %1"
Constant	TEXT_PARSER_ERROR
SAP Sybase Error Number	2840
SQL State	WT009
SQL Code	-1164L

Error 1164	"Text query parser error: %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The error message returned by the text query parser.
Probable Cause	The text query could not be parsed.

Error 1165	"Error creating text index \"%1\" on table \"%2\"No message"
Constant	TEXT_INDEX_CREATION_ERROR
SAP Sybase Error Number	2841
SQL State	WT010
SQL Code	-1165L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The name of the text index.
Parameter 2	The name of the table.
Probable Cause	There was an internal error creating a text index.

Error 1166	"Text indexes are not supported for this database."
Constant	TEXT_UPGRADE_REQUIRED
SAP Sybase Error Number	2842
SQL State	WT011
SQL Code	-1166L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	The current database does not have catalog support for text indexes. To use this feature, upgrade your database to the most recent version.

Error 1167	"Cannot drop a user that owns text configurations"
Constant	USER_OWNS_TEXT_CONFIG
SAP Sybase Error Number	2843
SQL State	55W12
SQL Code	-1167L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	You attempted to drop a user that is the creator of a text configuration. The text configuration must be dropped first.

Error 1168	"Cannot alter or drop a text configuration referenced by a text index."
Constant	TEXT_CANNOT_ALTER_CONFIG
SAP Sybase Error Number	2844
SQL State	WT012
SQL Code	-1168L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	It is not possible to alter or drop a text configuration referenced by a populated text index or currently being used by a text procedure. Either copy the configuration and alter the copy, or close all cursors on text procedures and truncate all indexes that use the configuration.

Error 1169	"Cannot access a table that is part of a text index."
Constant	TEXT_CANNOT_USE_TEXT_INDEX
SAP Sybase Error Number	2846
SQL State	WT013
SQL Code	-1169L

Error 1169	"Cannot access a table that is part of a text index."
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	It is not possible to directly manipulate tables created as part of a text index.

Error 1170	"The materialized view %1 cannot be changed to immediate because it has already been initialized"
Constant	IMMEDIATE_MV_REFRESH_NOT_ALLOWED
SAP Sybase Error Number	2847
SQL State	42WC3
SQL Code	-1170L
ODBC 2 State	42000
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	Name of the materialized view.
Probable Cause	You attempted to change the refresh type to immediate for a materialized view which is already in an initialized state. Truncate the view before changing the refresh type.

Error 1171	"Client application does not allow transfer of data ('%1')"
Constant	CLIENT_TRANSFER_NO_VALIDATION
SAP Sybase Error Number	2848
SQL State	WW092
SQL Code	-1171L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>

Error 1171	"Client application does not allow transfer of data ('%1')"
Parameter 1	The name of the object being transferred to/from the application.
Probable Cause	The client application does not allow the transfer of server initiated data. To allow transfer of server initiated data, the application must register a validation callback mechanism with the client library.

Error 1172	"Client application disallowed the transfer of data ('%1')"
Constant	CLIENT_TRANSFER_DISALLOWED
SAP Sybase Error Number	2849
SQL State	WW093
SQL Code	-1172L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the object being transferred to/from the application.
Probable Cause	The client application rejected the transfer of server initiated data. To allow transfer of server initiated data, the application registered a validation callback which rejected the transfer of requested data.

Error 1173	"Client library reported an error accessing data during transfer ('%1')"
Constant	CLIENT_TRANSFER_ACCESS_ERROR
SAP Sybase Error Number	2850
SQL State	WW094
SQL Code	-1173L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the object being transferred to/from the application.

Error 1173	"Client library reported an error accessing data during transfer ('%1')"
Probable Cause	The client application reported an error while attempting to access the data for a transfer request from the server. Reasons could include the client application lacking permissions to the data object or other operating system reported errors.

Error 1174	"Cannot create text configuration '%1' because option '%2' has an inappropriate setting"
Constant	TEXT_BAD_OPTION
SAP Sybase Error Number	2851
SQL State	WT014
SQL Code	-1174L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the configuration.
Parameter 2	Name of the option with the incorrect setting.
Probable Cause	You attempted an operation that needs to create or alter the database options settings for a text configuration, but one of the options is currently set to a value not permitted for a text configuration.

Error 1175	"Unable to acquire table locks in specified time"
Constant	LOCK_TIMEOUT
SAP Sybase Error Number	2852
SQL State	42WC4
SQL Code	-1175L
ODBC 2 State	40001
ODBC 3 State	40001
Severity Code	21 on page 2

Error 1175	"Unable to acquire table locks in specified time"
Probable Cause	The LOCK TABLE statement could not acquire all the locks in specified time period.
Error 1176	"Plan not available. NOEXEC plan cannot be generated for this type of statement"
Constant	STMT_NOT_ALLOWED_FOR_NOEXEC_PLAN
SAP Sybase Error Number	2853
SQL State	0AW20
SQL Code	-1176L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	15 on page 2
Probable Cause	You tried to get the NOEXEC plan for a statement type for which SAP Sybase IQ cannot generate a NOEXEC plan.
Error 1177	"No plan. HTML_PLAN function is not supported for this type of statement or database."
Constant	HTML_PLAN_NOT_SUPPORTED
SAP Sybase Error Number	2854
SQL State	0AW21
SQL Code	-1177L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	15 on page 2
Probable Cause	You tried to get the HTML plan for a query which is either a SQL Anywhere query or a remote data access/CIS decomposed query. HTML_PLAN is supported for a pure SAP Sybase IQ query.

Messages 1178 through 1197

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1178	"Transaction log mirroring cannot be used with database mirroring"
Constant	MIRROR_LOG_WITH_DB_MIRROR
SAP Sybase Error Number	2855
SQL State	WW095
SQL Code	-1178L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	Transaction log mirroring cannot be used with database mirroring. Use the dblog utility to disable transaction log mirroring.

Error 1179	"Unable to start database server: missing license file"
Constant	UNABLE_TO_START_ENGINE_MISSING_LICENSE
SAP Sybase Error Number	2856
SQL State	08WA2
SQL Code	-1179L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	17 on page 2
Probable Cause	It was not possible to start the database server because the server license file was not found. The server license file has the same name as the server executable with the extension ".lic".

Error 1180	"Cannot set database option \"%1\" because it is on the options watch list"
Constant	OPTION_ON_WATCH_LIST
SAP Sybase Error Number	2857
SQL State	WW096
SQL Code	-1180L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The name of the option.
Probable Cause	An attempt was made to set a database option that is on the options watch list. The options watch list is used to help find references to options that have been removed or deprecated.

Error 1181	"The materialized view cannot be changed to immediate because its definition must not contain more than one query block"
Constant	UPDATABLE_MATVIEW_MULTIPLE_BLOCK_ERR
SAP Sybase Error Number	2858
SQL State	42WC5
SQL Code	-1181L
ODBC 2 State	42000
ODBC 3 State	ERROR
Severity Code	<i>15 on page 2</i>
Probable Cause	You attempted to change the refresh type to immediate for a materialized view whose definition contains more than one query block.

Error 1182	"Statement not allowed on IMMEDIATE REFRESH text index"
Constant	TEXT_IMMEDIATE_NOT_ALLOWED

Error 1182	"Statement not allowed on IMMEDIATE REFRESH text index"
SAP Sybase Error Number	2859
SQL State	WT015
SQL Code	-1182L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You cannot use REFRESH TEXT INDEX or TRUNCATE TEXT INDEX on an index that is created with immediate refresh. You cannot alter a text index to use or stop using immediate refresh.

Error 1183	"Support for permissions on dbspaces is not available for this database"
Constant	DBSPACE_PERMS_NOT_SUPPORTED
SAP Sybase Error Number	2860
SQL State	0AW22
SQL Code	-1183L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	15 on page 2
Probable Cause	The statement being executed requires support for permissions on dbspaces, but the database being used does not have this capability. The database must be recreated or upgraded using a version of the server that supports permissions on dbspaces.

Error 1184	"Cannot drop last unique index of an immediate materialized view"
Constant	DELETE_UPDATABLE_MATVIEW_INDEX_ERR
SAP Sybase Error Number	2861

Error 1184	"Cannot drop last unique index of an immediate materialized view"
SQL State	55W21
SQL Code	-1184L
ODBC 2 State	42000
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You attempted to drop the last unique index on non-nullable columns of an immediate materialized view. Immediate materialized view needs at least one unique index on non-nullable columns to be valid.

Error 1185	"Index validation failed for table %1, index %2 with code: %3"
Constant	CORRUPT_ULTRALITE_INDEX
SAP Sybase Error Number	2862
SQL State	WI002
SQL Code	-1185L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	The name of the table.
Parameter 2	The name of the index.
Parameter 3	The specific kind of corruption that was found.
Probable Cause	UltraLite database validation failed while validating the specified index. The code provides more specific information on the validation failure.

Error 1186	"Database page validation failed with code: %1"
Constant	CORRUPT_ULTRALITE_DATABASE
SAP Sybase Error Number	2863
SQL State	WI003

Error 1186	"Database page validation failed with code: %1"
SQL Code	-1186L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	The specific kind of corruption that was found.
Probable Cause	UltraLite database validation failed while validating the database pages. The code provides more specific information on the validation failure.

Error 1187	"Cannot append when using compression or encryption"
Constant	UNLOAD_CANNOT_APPEND
SAP Sybase Error Number	2864
SQL State	WL012
SQL Code	-1187L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The UNLOAD statement cannot append to a file when using compression or encryption. Either the compressed or encrypted keywords were specified, or the file being appended to is compressed or encrypted.

Error 1188	"LOAD TABLE error: %1"
Constant	LOAD_TABLE_ERROR
SAP Sybase Error Number	2865
SQL State	WL013
SQL Code	-1188L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1188	"LOAD TABLE error: %1"
Severity Code	<i>16</i> on page 2
Parameter 1	Description of the failure encountered
Probable Cause	The LOAD TABLE statement failed. The message specifies the actual problem that occurred.

Error 1189	"The UTF-16 endian specified does not match the Byte Order Mark found in the data"
Constant	UTF16_ENDIAN_MISMATCH
SAP Sybase Error Number	2866
SQL State	WC004
SQL Code	-1189L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Probable Cause	The specified UTF-16 encoding explicitly specifies the expected endian of the data; however, the Byte Order Mark found at the beginning of the data indicates that the data is encoded in the opposite endian.

Error 1190	"LOAD TABLE is not allowed on a materialized view %1"
Constant	LOAD_TABLE_ON_MATVIEW_ERROR
SAP Sybase Error Number	2867
SQL State	WL014
SQL Code	-1190L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	Name of the materialized view on which load was attempted.
Probable Cause	LOAD TABLE statement is not allowed on a materialized view.

Error 1191	"LOAD TABLE not allowed: initialized immediate materialized view %1 depends on %2"
Constant	LOAD_TABLE_WITH_IMV
SAP Sybase Error Number	2868
SQL State	WL015
SQL Code	-1191L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the dependent initialized immediate materialized view.
Parameter 2	Name of the table on which load was performed.
Probable Cause	LOAD TABLE is not permitted on any table that has dependent initialized immediate materialized views.

Error 1192	"Cannot update multiple tables immediate materialized view %1 depends on"
Constant	CANNOT_UPDATE_TWO_TABLES_IMV
SAP Sybase Error Number	2869
SQL State	55W29
SQL Code	-1192L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the view that depends on two or more tables in the update statement.
Probable Cause	You attempted to simultaneously update two or more tables initialized immediate materialized view depends on. No more than one base table an immediate materialized view depends on can be updated in a statement.

Error 1193	"TRUNCATE TABLE not allowed: initialized immediate materialized view %1 depends on %2"
Constant	TRUNCATE_TABLE_WITH_IMV
SAP Sybase Error Number	2870
SQL State	55W30
SQL Code	-1193L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the dependent initialized immediate materialized view.
Parameter 2	Name of the table on which TRUNCATE TABLE was performed.
Probable Cause	TRUNCATE TABLE is not permitted on any table that has dependent initialized immediate materialized views.

Error 1194	"Login policy \"%1\" already exists"
Constant	LOGIN_POLICY_ALREADY_EXISTS
SAP Sybase Error Number	2871
SQL State	WW097
SQL Code	-1194L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the login policy.
Probable Cause	An attempt was made to create a login policy that already exists in the database.

Error 1195	"Login policy \"%1\" not found"
Constant	LOGIN_POLICY_NOT_FOUND
SAP Sybase Error Number	2872
SQL State	WW098

Error 1195	"Login policy \"%1\" not found"
SQL Code	-1195L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the login policy.
Probable Cause	The named login policy was not found in the database.

Error 1196	"Login policies are not supported for this database"
Constant	LOGIN_POLICY_UPGRADE
SAP Sybase Error Number	2873
SQL State	WW099
SQL Code	-1196L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The current database does not have catalog support for login policies. To use this feature, upgrade your database to the most recent version.

Error 1197	"Login policy \"%1\" in use"
Constant	LOGIN_POLICY_IN_USE
SAP Sybase Error Number	2874
SQL State	WW100
SQL Code	-1197L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the login policy.

Error 1197	"Login policy \"%1\" in use"
Probable Cause	The named login policy is associated with a user in the database. Any users associated with the login policy must be assigned a different login policy before the named login policy can be dropped.

Messages 1198 through 1217

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1198	"User \"%1\" already exists"
Constant	USER_ALREADY_EXISTS
SAP Sybase Error Number	2875
SQL State	WW101
SQL Code	-1198L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the user.
Probable Cause	An attempt was made to create a user that already exists in the database.

Error 1199	"The materialized view cannot be changed to immediate because COUNT(*) must be part of the SELECT list."
Constant	UPDATABLE_MATVIEW_MISSING_COUNT
SAP Sybase Error Number	2876
SQL State	42WC6
SQL Code	-1199L
ODBC 2 State	42000
ODBC 3 State	ERROR
Severity Code	15 on page 2

Error 1199	"The materialized view cannot be changed to immediate because COUNT(*) must be part of the SELECT list."
Probable Cause	You attempted to change the refresh type to immediate for a materialized view whose definition does not include COUNT(*) in the SELECT list.

Error 1200	"Client library reported a permissions error accessing object ('%1') during transfer"
Constant	CLIENT_TRANSFER_PERMS_ERROR
SAP Sybase Error Number	2877
SQL State	WW103
SQL Code	-1200L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the object being transferred to/from the application.
Probable Cause	The client application reported a permissions error while attempting to access the object for a data transfer request from the server. The client application likely does not have the necessary operating system authorization required to access the object.

Error 1201	"Client library reported an error opening object ('%1') during transfer"
Constant	CLIENT_TRANSFER_OPEN_ERROR
SAP Sybase Error Number	2878
SQL State	WW102
SQL Code	-1201L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2

Error 1201	"Client library reported an error opening object ('%1') during transfer"
Parameter 1	The name of the object being transferred to/from the application.
Probable Cause	The client application reported an error while attempting to open the object for a data transfer request from the server. Reasons could include an invalid name for the object or a missing object.

Error 1202	"Operation not allowed on a table with dependent immediate materialized views"
Constant	INVALID_OPERATION_FOR_TBL_WITH_IMV
SAP Sybase Error Number	2879
SQL State	55W31
SQL Code	-1202L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	Requested operation cannot be applied to a table with dependent immediate materialized views.

Error 1203	"WRITETEXT not allowed: immediate materialized view %1 depends on %2"
Constant	WRITETEXT_TABLE_WITH_IMV
SAP Sybase Error Number	2880
SQL State	55W32
SQL Code	-1203L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the dependent immediate materialized view.
Parameter 2	Name of the base table.

Error 1203	"WRITETEXT not allowed: immediate materialized view %1 depends on %2"
Probable Cause	WRITETEXT is not allowed on base tables that have dependent initialized immediate materialized views. No operation that does not fire triggers is allowed on base tables with dependent initialized immediate materialized views.

Error 1204	"INSERT...ON EXISTING UPDATE not allowed: immediate materialized view %1 depends on %2"
Constant	UPDATE_ON_EXISTING_DEP_IMV
SAP Sybase Error Number	2881
SQL State	55W33
SQL Code	-1204L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of dependent immediate materialized view.
Parameter 2	The name of the base table into which the insert was performed.
Probable Cause	Insert statement with ON EXISTING clause is not permitted on a base table if the base table has dependent initialized immediate materialized view.

Error 1205	"External environment '%1' could not be found"
Constant	EXTERN_ENV_NOT_FOUND
SAP Sybase Error Number	2882
SQL State	WJ030
SQL Code	-1205L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	11 on page 2
Parameter 1	Name of the external environment.

Error 1205	"External environment '%1' could not be found"
Probable Cause	You attempted to define an object for an external environment that has not been added.

Error 1206	"External environments are not supported for this database"
Constant	EXTERN_ENV_UPGRADE
SAP Sybase Error Number	2883
SQL State	WW104
SQL Code	-1206L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The current database does not have catalog support for external environments. To use this feature, upgrade your database to the most recent version.

Error 1207	"Invalid use of NEAR operator in text query."
Constant	TEXT_INVALID_NEAR
SAP Sybase Error Number	2884
SQL State	WT016
SQL Code	-1207L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	15 on page 2
Probable Cause	Only terms and prefixes are allowed as arguments to a NEAR operator.

Error 1208	"Invalid partition bound value '%1'"
Constant	BAD_PARTITION_BOUND_VALUE
SAP Sybase Error Number	2885

Error 1208	"Invalid partition bound value '%1'"
SQL State	WW105
SQL Code	-1208L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The partition bound value.
Probable Cause	The partition bound value is invalid and cannot be used.

Error 1209	"Cannot convert value '%1' to an %2"
Constant	PARTITION_BOUND_VALUE_CONVERSION
SAP Sybase Error Number	2886
SQL State	WW106
SQL Code	-1209L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The partition bound value.
Parameter 2	The type of the partition key.
Probable Cause	The value is not compatible with the type of the partition key.

Error 1210	"Partition bound value '%1' out of order"
Constant	PARTITION_BOUND_VALUE_ORDER
SAP Sybase Error Number	2887
SQL State	WW107
SQL Code	-1210L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2

Error 1210	"Partition bound value '%1' out of order"
Parameter 1	The partition bound value.
Probable Cause	Range partition bound values must be provided in ascending order.

Error 1211	"MERGE statement ANSI cardinality violation on table '%1'"
Constant	MERGE_CARDINALITY_VIOLATION
SAP Sybase Error Number	2888
SQL State	23509
SQL Code	-1211L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	Name of the table being updated
Probable Cause	You have attempted to execute the MERGE statement and the same row is the target of a WHEN MATCHED clause more than once.

Error 1212	"Connection disallowed by login policy for this user"
Constant	CONNECTION_DISALLOWED_BY_LOGIN_POLICY
SAP Sybase Error Number	2889
SQL State	28W15
SQL Code	-1212L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	A connection attempt was disallowed based on the login policy for the user. It may be necessary for a user with DBA authority to reset this user via the ALTER USER statement.

Error 1213	"External environment does not support result sets"
Constant	EXTERN_ENV_NO_RESULT_SET_SUPPORT

Error 1213	"External environment does not support result sets"
SAP Sybase Error Number	2891
SQL State	WJ031
SQL Code	-1213L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	11 on page 2
Probable Cause	You attempted to define dynamic result sets for an external environment that does not support result sets.

Error 1214	"External library '%1' is in use"
Constant	EXTERNAL_LIBRARY_IN_USE
SAP Sybase Error Number	2892
SQL State	WW108
SQL Code	-1214L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The external library that is in use
Probable Cause	The external library cannot be unloaded as it is currently in use.

Error 1215	"External library '%1' not loaded"
Constant	EXTERNAL_LIBRARY_NOT_LOADED
SAP Sybase Error Number	2893
SQL State	WW109
SQL Code	-1215L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2

Error 1215	"External library '%1' not loaded"
Parameter 1	The external library that is not loaded
Probable Cause	The external library cannot be unloaded as it is not current loaded.

Error 1216	"The arguments to this procedure must be literal strings."
Constant	TEXT_NEED_CONSTANT_ARGUMENT
SAP Sybase Error Number	2894
SQL State	WT017
SQL Code	-1216L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	This procedure only accepts literal strings as arguments.

Error 1217	"Synchronization profile '%1' not found"
Constant	SYNC_PROFILE_NOT_FOUND
SAP Sybase Error Number	2895
SQL State	42W75
SQL Code	-1217L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the synchronization profile.
Probable Cause	You tried to access a synchronization profile that the database could not find.

1218 - 1427

Messages 1218 through 1237

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1218	"The materialized view cannot be changed to immediate because it does not have a unique index on non-aggregate, non-nullable columns"
Constant	UPDATABLE_MATVIEW_NON_AGGR_INDEX
SAP Sybase Error Number	2896
SQL State	42WC7
SQL Code	-1218L
ODBC 2 State	42000
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You attempted to change the refresh type to immediate for a materialized view which does not have a unique index on non-aggregate non-nullable columns. Create a unique index on the materialized view before changing the refresh type.

Error 1219	"Maintenance of dependent immediate materialized view(s) failed"
Constant	MAINTENANCE_OF_IMV_FAILED
SAP Sybase Error Number	2897
SQL State	42WC8
SQL Code	-1219L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	Maintenance of immediate materialized view(s) dependent on the base table failed.

Error 1220	"User cannot be dropped because external logins exist for this user."
Constant	USER_HAS_EXTERNLOGINS
SAP Sybase Error Number	2898
SQL State	WO028
SQL Code	-1220L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>11</i> on page 2
Probable Cause	The user cannot be dropped while an external login for the user still exists.

Error 1221	"Duplicate options not allowed in the CREATE DATABASE statement"
Constant	DUPLICATE_CREATE_DB_OPTION
SAP Sybase Error Number	2899
SQL State	42U08
SQL Code	-1221L
ODBC 2 State	S0002
ODBC 3 State	ERROR
Severity Code	<i>11</i> on page 2
Probable Cause	You have specified one of the options more than once when executing the CREATE DATABASE statement.

Error 1222	"Multiplex Server '%1' not found"
Constant	IQ_MULTIPLEX_SERVER_NOT_FOUND
SAP Sybase Error Number	2900
SQL State	WW110
SQL Code	-1222L
ODBC 2 State	ERROR

Error 1222	"Multiplex Server '%1' not found"
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The name of Multiplex Server.
Probable Cause	Multiplex Server with this name does not exist.

Error 1223	"Synchronization profile '%1' already exists"
Constant	SYNC_PROFILE_ALREADY_EXISTS
SAP Sybase Error Number	2901
SQL State	42W76
SQL Code	-1223L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	Name of the synchronization profile.
Probable Cause	You tried to create a synchronization profile that already exists.

Error 1224	"Synchronization profile '%1' has invalid parameter '%2'"
Constant	SYNC_PROFILE_INVALID
SAP Sybase Error Number	2902
SQL State	42W77
SQL Code	-1224L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	Name of the synchronization profile that is invalid.
Parameter 2	Name of the parameter in the profile that has the problem.
Probable Cause	You tried to create or alter a synchronization profile using a string containing an invalid parameter setting.

Error 1225	"Synchronization profiles are not supported for this database"
Constant	SYNC_PROFILE_UPGRADE
SAP Sybase Error Number	2903
SQL State	42W78
SQL Code	-1225L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Probable Cause	The current database does not have catalog support for synchronization profiles. To use this feature, upgrade your database to the most recent version.

Error 1226	"Foreign key columns do not match the primary key or a uniqueness constraint in \"%1\"No message"
Constant	NO_MATCHING_INDEX
SAP Sybase Error Number	2904
SQL State	42R04
SQL Code	-1226L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The name of the primary table.
Probable Cause	An attempt was made to create a foreign key, but the columns specified do not match the primary key or a uniqueness constraint for the referenced table.

Error 1227	"Internal error. Contact SAP Sybase IQ support. %1."
Constant	IQ_MPX_INTERNAL_ERROR
SAP Sybase Error Number	2905
SQL State	WI111

Error 1227	"Internal error. Contact SAP Sybase IQ support. %1."
SQL Code	-1227L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The error description.
Probable Cause	The multiplex DDL statement (CREATE/ALTER/DROP) failed with internal error due to specified reason.

Error 1228	"Syntax error, cannot specify SAP Sybase IQ specific options (%1) when creating a table in a SQL Anywhere database"
Constant	IQ_ONLY_SYNTAX_ERROR
SAP Sybase Error Number	2907
SQL State	42W72
SQL Code	-1228L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Parameter 1	SAP Sybase IQ option used.
Probable Cause	An attempt was made to use SAP Sybase IQ specific create table syntax when creating a table in a SQL Anywhere database.

Error 1229	"Reorganize table is already being run on table \"%1\No message"
Constant	REORG_ALREADY_IN_PROGRESS
SAP Sybase Error Number	2908
SQL State	54W51
SQL Code	-1229L
ODBC 2 State	54000
ODBC 3 State	54000

Error 1229	"Reorganize table is already being run on table \"%1\No message"
Severity Code	<i>16 on page 2</i>
Parameter 1	The name of the table.
Probable Cause	There is already a REORGANIZE TABLE statement being run on this table. Only one such statement can be executing on a table at any time.

Error 1230	"Too many open cursors"
Constant	TOO_MANY_CURSORS
SAP Sybase Error Number	2909
SQL State	54W12
SQL Code	-1230L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>17 on page 2</i>
Probable Cause	You exceeded the number of cursors that can be open on a single UltraLite database. Check to ensure you are freeing statements when you are done with them.

Error 1231	"Statement timed out: \"%1!s!\""
Constant	STATEMENT_TIMEOUT
SAP Sybase Error Number	2910
SQL State	57W05
SQL Code	-1231L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	Statement type
Probable Cause	The statement failed because it did not complete within the allotted or specified time.

Error 1232	"Attempt to start a second snapshot in a transaction"
Constant	SNAPSHOT_ALREADY_STARTED
SAP Sybase Error Number	2911
SQL State	42WC9
SQL Code	-1232L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	A transaction tried to start a snapshot (for example, using the BEGIN SNAPSHOT statement) while another snapshot was already active.

Error 1233	"The materialized view %1 cannot be changed to immediate because it does not have a unique index on non-nullable columns."
Constant	IMMEDIATE_MV_NO_UNIQUE_INDEX
SAP Sybase Error Number	2912
SQL State	42WCA
SQL Code	-1233L
ODBC 2 State	42000
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Name of the materialized view.
Probable Cause	You attempted to change the refresh type to immediate for a materialized view which does not have a unique index on non-nullable columns. Create a unique index on the materialized view before changing the refresh type.

Error 1234	"DbSPACE file with name or path '%1' already exists."
Constant	IQ_DBSPACEFILE_UPDATE_ERROR
SAP Sybase Error Number	2913
SQL State	42W7A

Error 1234	"Dbospace file with name or path '%1' already exists."
SQL Code	-1234L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Parameter 1	Logical file name or physical path from CREATE/ALTER DBSPACE SQL statement.
Probable Cause	Error code to use for catalog update errors in SAP Sybase IQ code.

Error 1235	"Too many columns in SELECT list"
Constant	TOO_MANY_COLUMNS_IN_SELECT
SAP Sybase Error Number	2914
SQL State	54W13
SQL Code	-1235L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You executed a statement with too many expressions in the SELECT list. The number of expressions within a SELECT list is limited to 60000.

Error 1236	"Too many expressions in GROUP BY list"
Constant	TOO_MANY_COLUMNS_IN_GROUPBY
SAP Sybase Error Number	2915
SQL State	54W14
SQL Code	-1236L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2

Error 1236	"Too many expressions in GROUP BY list"
Probable Cause	You executed a statement with too many expressions in the GROUP BY list. The number of expressions within a GROUP BY list is limited to 60000.

Error 1237	"Too many columns in procedure result set"
Constant	TOO_MANY_COLUMNS_IN_PROC_RES
SAP Sybase Error Number	2916
SQL State	54W15
SQL Code	-1237L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You executed a statement with too many expressions in the GROUP BY list. The number of expressions within a GROUP BY list is limited to 60000. You executed a CREATE PROCEDURE or ALTER PROCEDURE statement. The resulting number of columns in the result set of the procedure would exceed the server's limit.

Messages 1239 through 1260

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1239	"Partition name '%1' is not part of table '%2'"
Constant	UNKNOWN_PARTITION_NAME
SAP Sybase Error Number	2918
SQL State	WW113
SQL Code	-1239L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The partition name.

Error 1239	"Partition name '%1' is not part of table '%2'"
Parameter 2	The table name.
Probable Cause	This partition name is not part of this table.

Error 1240	"The provided stoplist is too long."
Constant	TEXT_STOPLIST_TOO_LONG
SAP Sybase Error Number	2920
SQL State	WT018
SQL Code	-1240L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	A text configuration stop list must be less than 8000 bytes.

Error 1241	"Value-sensitive cursor used after a TRUNCATE"
Constant	HOLD_CURSOR_AFTER_TRUNCATE
SAP Sybase Error Number	2924
SQL State	24001
SQL Code	-1241L
ODBC 2 State	24000
ODBC 3 State	24000
Severity Code	16 on page 2
Probable Cause	You attempted to use a value-sensitive cursor opened WITH HOLD after a TRUNCATE or after a COMMIT removed all rows from a temporary table declared as ON COMMIT DELETE ROWS.

Error 1242	"Parameter ('%1') is already in the configuration specification of the specified Multiplex Server"
Constant	IQ_MULTIPLEX_ALERTOSAMECONFIG
SAP Sybase Error Number	2925

Error 1242	"Parameter ('%1') is already in the configuration specification of the specified Multiplex Server"
SQL State	WW117
SQL Code	-1242L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Current configuration of a Multiplex Server.
Probable Cause	The ALTER MULTIPLEX SERVER statement tried to alter configuration parameters with values that are the same as the current values.

Error 1243	"An attempt to encrypt database '%1' failed"
Constant	ENCRYPT_DATABASE_FAILED
SAP Sybase Error Number	2926
SQL State	WW118
SQL Code	-1243L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the database that could not be encrypted.
Probable Cause	Your attempt to encrypt a database file failed.

Error 1244	"An attempt to decrypt database '%1' failed"
Constant	DECRYPT_DATABASE_FAILED
SAP Sybase Error Number	2927
SQL State	WW119
SQL Code	-1244L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1244	"An attempt to decrypt database '%1' failed"
Severity Code	<i>16 on page 2</i>
Parameter 1	The name of the database that could not be decrypted.
Probable Cause	Your attempt to decrypt a database file failed.

Error 1245	"Partition name '%1' already used"
Constant	CANNOT_USE_PARTITION_NAME
SAP Sybase Error Number	2928
SQL State	WW221
SQL Code	-1245L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The partition name.
Probable Cause	This partition name has already been used.

Error 1246	"Partition '%1' is not adjacent to or before partition '%2'"
Constant	PARTITIONS_NOT_ADJACENT
SAP Sybase Error Number	2929
SQL State	WW222
SQL Code	-1246L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The partition name.
Parameter 2	The partition name.
Probable Cause	These partitions are not adjacent - they cannot be merged.

Error 1249	"Logical file '%1' is not part of dbspace '%2'"
Constant	UNKNOWN_LOGICALFILE_NAME
SAP Sybase Error Number	2932
SQL State	WW224
SQL Code	-1249L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The logical file name.
Parameter 2	The dbspace name.
Probable Cause	This logical file is not part of this dbspace.

Error 1250	"Table '%1' is not a partitioned table"
Constant	TABLE_NOT_PARTITIONED
SAP Sybase Error Number	2933
SQL State	WW225
SQL Code	-1250L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The table name.
Probable Cause	This table is not partitioned.

Error 1251	"Table '%1' is already partitioned or subpartitioned"
Constant	TABLE_PARTITIONED
SAP Sybase Error Number	2934
SQL State	WW226
SQL Code	-1251L

Error 1251	"Table '%1' is already partitioned or subpartitioned"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The table name.
Probable Cause	This table is already partitioned or the table is incorrectly partitioned for this command. If a table is range partitioned, a user can "partition by hash" to create a hash-range partitioned table but if a table is partitioned by hash, it is incorrect to "partition by range".

Error 1252	"DbSPACE '%1' is the incorrect type"
Constant	WRONG_DBSPACE_TYPE
SAP Sybase Error Number	2935
SQL State	WW227
SQL Code	-1252L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The dbspace name.
Probable Cause	Tried to put data into the incorrect dbspace (for example, putting a primary key into the wrong store).

Error 1253	"The text index %1 needs to be refreshed"
Constant	TEXT_MATCHING_INDEX_NOT_REFRESHED
SAP Sybase Error Number	2936
SQL State	WT019
SQL Code	-1253L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2

Error 1253	"The text index %1 needs to be refreshed"
Parameter 1	The name of the text index that needs to be refreshed.
Probable Cause	There is a text index that matches the query, but it needs to be re-freshed before it is used.

Error 1254	"MERGE statement for table '%1' failed because of a RAISERROR specification in the statement"
Constant	MERGE_USER_SPECIFIED_ERROR
SAP Sybase Error Number	2937
SQL State	23510
SQL Code	-1254L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the table being merged into
Probable Cause	You have attempted to execute a MERGE statement that contains the RAISERROR clause in one or more merge operation branches and one of the input rows satisfies the conditions for one of these branches.

Error 1255	"Cannot merge partition '%1' into '%2' for column '%3'"
Constant	CANNOT_MERGE_COLUMN_PARTITION
SAP Sybase Error Number	2938
SQL State	WW228
SQL Code	-1255L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	merge partition.
Parameter 2	merge to partition.
Parameter 3	column name.

Error 1255	"Cannot merge partition '%1' into '%2' for column '%3'"
Probable Cause	These column partitions cannot be merged.

Error 1256	"Event of %1 type already exists"
Constant	IQ_EVENT_TYPE_ALREADY_EXISTS
SAP Sybase Error Number	2939
SQL State	42WD0
SQL Code	-1256L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Event type
Probable Cause	An attempt was made to define a new event of the type that already exists.

Error 1257	"Multiple event conditions cannot be specified with this event type"
Constant	IQ_EVENT_MULTIPLE_CONDITIONS
SAP Sybase Error Number	2940
SQL State	42WD1
SQL Code	-1257L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	An attempt was made to specify more than one condition for an event type.

Error 1258	"'<' or '<=' operator can only be used in the event condition with this event type"
Constant	IQ_EVENT_WRONG_OPERATOR
SAP Sybase Error Number	2941

Error 1258	"<' or '<=' operator can only be used in the event condition with this event type"
SQL State	42WD2
SQL Code	-1258L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	Event of this type can be defined with a condition having < or <= operator only.

Error 1259	"Hash error: %1"
Constant	HASH_ERROR
SAP Sybase Error Number	2942
SQL State	08W92
SQL Code	-1259L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	11 on page 2
Parameter 1	Description of the error that occurred.
Probable Cause	An error occurred during hashing.

Error 1260	"This server is not licensed to support the '%1' feature"
Constant	FEATURE_NOT_LICENSED
SAP Sybase Error Number	2944
SQL State	0A002
SQL Code	-1260L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2

Error 1260	"This server is not licensed to support the '%1' feature"
Parameter 1	The unlicensed feature.
Probable Cause	You attempted to carry out an operation or use a feature that is not licensed in this edition of SQL Anywhere.

Messages 1261 through 1280

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1261	"This server is not licensed to support '%1' connections"
Constant	CONNECTION_PROTOCOL_NOT_LICENSED
SAP Sybase Error Number	2945
SQL State	0A003
SQL Code	-1261L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The unlicensed connection type.
Probable Cause	You attempted to use a connection protocol or API that is not licensed in this edition of SQL Anywhere.

Error 1262	"This edition of SQL Anywhere is not available on this platform"
Constant	PLATFORM_NOT_LICENSED
SAP Sybase Error Number	2946
SQL State	0A004
SQL Code	-1262L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2

Error 1262	"This edition of SQL Anywhere is not available on this platform"
Probable Cause	This edition of SQL Anywhere is not available on this platform. You must use a different license key to use SQL Anywhere on this platform.

Error 1263	"Event notification queue '%1' not found"
Constant	EVENT_NOTIFICATION_QUEUE_NOT_FOUND
SAP Sybase Error Number	2950
SQL State	WE014
SQL Code	-1263L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	11 on page 2
Parameter 1	The name of the event notification queue
Probable Cause	The named event notification queue was not found. The operation failed.

Error 1264	"Event object name '%1' is not valid"
Constant	INVALID_EVENT_OBJECT_NAME
SAP Sybase Error Number	2951
SQL State	WE015
SQL Code	-1264L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the event object
Probable Cause	The given name is not valid for an event object (notification queue or user event). Names are limited in length to 32 characters (bytes), and cannot contain certain characters such as '*' or '@'.

Error 1265	"Event object named '%1' already exists"
Constant	EVENT_OBJECT_ALREADY_EXISTS
SAP Sybase Error Number	2952
SQL State	WE016
SQL Code	-1265L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the event object
Probable Cause	An event object (notification queue or user event) with the given name already exists.

Error 1266	"No notification within timeout on queue '%1'"
Constant	EVENT_NOTIFICATION_QUEUE_TIMEOUT
SAP Sybase Error Number	2953
SQL State	WE017
SQL Code	-1266L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the event notification queue
Probable Cause	The pending get-notification operation has timed out. No notification arrived before the given timeout elapsed.

Error 1267	"Event parameter '%1' not found"
Constant	EVENT_PARAMETER_NOT_FOUND
SAP Sybase Error Number	2954
SQL State	WE018
SQL Code	-1267L

Error 1267	"Event parameter '%1' not found"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>11 on page 2</i>
Parameter 1	The name of the event parameter
Probable Cause	The named event parameter was not found in the event notification.

Error 1268	"The materialized view cannot be changed to immediate because its definition contains an illegal construct."
Constant	UPDATABLE_MATVIEW_ERR
SAP Sybase Error Number	2955
SQL State	42WCB
SQL Code	-1268L
ODBC 2 State	42000
ODBC 3 State	ERROR
Severity Code	<i>15 on page 2</i>
Probable Cause	You attempted to change the refresh type to immediate for a materialized view whose definition contains an illegal construct.

Error 1269	"Service statement definition is invalid or unsupported"
Constant	SERVICE_STATEMENT_INVALID
SAP Sybase Error Number	2956
SQL State	42WCC
SQL Code	-1269L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	Either the statement provided is invalid or it is unsupported within the context of a service.

Error 1270	"Must own table '%1' to make an immediate view reference it"
Constant	NO_PERMS_FOR_IMV
SAP Sybase Error Number	2957
SQL State	42WD3
SQL Code	-1270L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the table
Probable Cause	You have attempted to change the refresh type of a materialized view to immediate and the view references a table that is not owned by you. To perform this operation, you must either own all the tables referenced by the materialized view or have DBA privileges.

Error 1271	"Synchronization download failed to complete"
Constant	INCOMPLETE_SYNCHRONIZATION
SAP Sybase Error Number	2958
SQL State	0AW23
SQL Code	-1271L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	You attempted to synchronize an UltraLite database. During the synchronization session, an incomplete download stream was received from the consolidated database. The reason for the upload failure can be found in the synchronization log file.

Error 1272	"Synchronization is already in progress"
Constant	SYNCHRONIZATION_IN_PROGRESS
SAP Sybase Error Number	2959

Error 1272	"Synchronization is already in progress"
SQL State	0AW24
SQL Code	-1272L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	You attempted to synchronize an UltraLite database but this database is being synchronized on another thread.

Error 1273	"Table '%1' has no columns"
Constant	TABLE_HAS_NO_COLUMNS
SAP Sybase Error Number	2960
SQL State	0EW00
SQL Code	-1273L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	The name of the table.
Probable Cause	You attempted to create a table without columns.

Error 1274	"Index '%1' has no columns"
Constant	INDEX_HAS_NO_COLUMNS
SAP Sybase Error Number	2961
SQL State	0EW01
SQL Code	-1274L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	The name of the index.

Error 1274	"Index '%1' has no columns"
Probable Cause	You attempted to create an index without columns.

Error 1275	"Invalid domain '%1'"
Constant	INVALID_DOMAIN
SAP Sybase Error Number	2962
SQL State	54W52
SQL Code	-1275L
ODBC 2 State	ERROR
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	The invalid domain specification.
Probable Cause	You attempted to create an invalid domain. The size/scale/precision is invalid.

Error 1276	"Configuration cannot not be modified while in use"
Constant	CONFIG_IN_USE
SAP Sybase Error Number	2963
SQL State	55W34
SQL Code	-1276L
ODBC 2 State	ERROR
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	You attempted to modify a configuration object that is in use by an open connection.

Error 1277	"Parameter '%1' cannot be null"
Constant	PARAMETER_CANNOT_BE_NULL
SAP Sybase Error Number	2964
SQL State	WW229

Error 1277	"Parameter '%1' cannot be null"
SQL Code	-1277L
ODBC 2 State	ERROR
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Name of the parameter.
Probable Cause	The specified parameter cannot be null.

Error 1278	"Operation is not allowed"
Constant	ULTRALITEJ_OPERATION_NOT_ALLOWED
SAP Sybase Error Number	2965
SQL State	WW230
SQL Code	-1278L
ODBC 2 State	ERROR
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	The requested operation is not allowed while schema is being modified.

Error 1279	"Operation '%1' failed for reason: '%2'"
Constant	ULTRALITEJ_OPERATION_FAILED
SAP Sybase Error Number	2966
SQL State	WW231
SQL Code	-1279L
ODBC 2 State	ERROR
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	The name of the operation.
Parameter 2	The cause of the failure.

Error 1279	"Operation '%1' failed for reason: '%2'"
Probable Cause	The requested operation failed.

Error 1280	"Underflow when converting '%1'"
Constant	UNDERFLOW
SAP Sybase Error Number	2967
SQL State	WW232
SQL Code	-1280L
ODBC 2 State	ERROR
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	The type being converted.
Probable Cause	An underflow occurred when converting the specified type. The source type may be too small (for example zero length binary) or value may be too small to be represented by the destination type.

Messages 1281 through 1301

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1281	"Another connection has the row in '%1' locked"
Constant	ROW_LOCKED
SAP Sybase Error Number	2968
SQL State	42W80
SQL Code	-1281L
ODBC 2 State	40001
ODBC 3 State	40001
Severity Code	21 on page 2
Parameter 1	Table that generates the error.

Error 1281	"Another connection has the row in '%1' locked"
Probable Cause	You attempted modify or delete a row that is locked by another connection. The row will be unlocked once that connection commits or rolls back.

Error 1283	"A CONTAINS query is not allowed on the view or derived table '%1'."
Constant	TEXT_INVALID_VIEW_FOR_CONTAINS
SAP Sybase Error Number	2970
SQL State	WT020
SQL Code	-1283L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the view or derived table that cannot be queried with CONTAINS.
Probable Cause	A view or derived table can only be queried using CONTAINS if it does not use TOP, FIRST, DISTINCT, GROUP BY, or FOR XML. In addition, the list of columns to search must all come from a single base table in the FROM clause of the view. They cannot come from multiple tables, or from another view or derived table in the FROM clause.

Error 1284	"Invalid partition key specification: must use '%1'. "
Constant	CANNOT_CHANGE_PARTITION_KEY
SAP Sybase Error Number	2971
SQL State	WW233
SQL Code	-1284L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The partition key column name.

Error 1284	"Invalid partition key specification: must use '%1'. "
Probable Cause	Partition key cannot be changed for ALTER TABLE ADD PARTITION. It must specify the same partition key column as the CREATE TABLE did.

Error 1285	"%1 -- Transaction rolled back"
Constant	IQ_TRANSACTION_ROLLBACK
SAP Sybase Error Number	2973
SQL State	40W09
SQL Code	-1285L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Error because of which the transaction rolled back.
Probable Cause	This transaction has been rolled back because the server encountered an error during a critical operation.

Error 1286	"Immediate materialized view definition cannot contain a SUM function over a nullable expression."
Constant	UPDATABLE_MATVIEW_SUM_NULL_EXPR
SAP Sybase Error Number	2974
SQL State	42WCD
SQL Code	-1286L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	15 on page 2
Probable Cause	You attempted to change the refresh type to immediate for a materialized view whose definition contains a SUM function over a nullable expression.

Error 1287	"Operation not allowed on global temporary table %1 as it is in use. Reconnect and try again."
Constant	IQ_GTT_ALTER_DROP_NOTALLOWED
SAP Sybase Error Number	2975
SQL State	55W35
SQL Code	-1287L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the table.
Probable Cause	A global temporary table cannot be modified if it is in use. The user must reconnect and re-execute the statement.

Error 1288	"'%1' statement is not allowed on a mirrored database"
Constant	STMT_NOT_ALLOWED_WITH_MIRRORING
SAP Sybase Error Number	2976
SQL State	WW120
SQL Code	-1288L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Statement that generates the error.
Probable Cause	You attempted to execute a statement that is not allowed when using a mirrored database.

Error 1289	"LOAD TABLE option '%1' not allowed with FORMAT %2"
Constant	INVALID_LOAD_TABLE_OPTION
SAP Sybase Error Number	2977
SQL State	WL016
SQL Code	-1289L

Error 1289	"LOAD TABLE option '%1' not allowed with FORMAT %2"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	Name of the option.
Parameter 2	The load table format.
Probable Cause	The specified LOAD TABLE option is not meaningful for the LOAD TABLE FORMAT.

Error 1290	"FOR UPDATE or FOR READ ONLY clause must be specified on PREPARE (not on DECLARE CURSOR)"
Constant	CURSOR_UPDATABILITY_CHANGED
SAP Sybase Error Number	2978
SQL State	42WD4
SQL Code	-1290L
ODBC 2 State	S1009
ODBC 3 State	HY092
Severity Code	<i>16</i> on page 2
Probable Cause	You specified the FOR UPDATE or FOR READ ONLY clause on a DECLARE CURSOR statement. The FOR UPDATE or FOR READ ONLY clause must be specified on the PREPARE statement and not the DECLARE CURSOR statement.

Error 1291	"Column '%1' Partition '%2' may not be assigned to a dbspace because partitioning is not supported for datatype '%3'."
Constant	INVALID_COL_PARTITION_PLACEMENT
SAP Sybase Error Number	2979
SQL State	WW235
SQL Code	-1291L
ODBC 2 State	ERROR

Error 1291	"Column '%1' Partition '%2' may not be assigned to a dbspace because partitioning is not supported for datatype '%3'."
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The column name
Parameter 2	The partition name
Parameter 3	The data type
Probable Cause	The column storage for certain datatypes (such as the BIT datatype) cannot be assigned to a dbspace.

Error 1292	"Column '%1' may not be assigned to a dbspace because partitioning is not supported for datatype '%2'."
Constant	INVALID_COL_PLACEMENT
SAP Sybase Error Number	2980
SQL State	WW236
SQL Code	-1292L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The column name
Parameter 2	The data type
Probable Cause	The column storage for certain datatypes (such as the BIT datatype) cannot be assigned to a dbspace.

Error 1293	"Partition key of '%1' is unsupported."
Constant	UNSUPPORTED_PARTITION_KEY
SAP Sybase Error Number	2981
SQL State	WW237
SQL Code	-1293L
ODBC 2 State	ERROR

Error 1293	"Partition key of '%1' is unsupported."
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The column datatype
Probable Cause	Partitioning over the specified datatype is not supported.

Error 1294	"Parameter (%1) length has exceeded its limit (%2)."
Constant	IQ_PARAM_LENGTH_EXCEED_LIMIT
SAP Sybase Error Number	2983
SQL State	WW122
SQL Code	-1294L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	Parameter name.
Parameter 2	Allowed Maximum length.
Probable Cause	Given parameter's length has exceeded the specified limit.

Error 1295	"Database path must be absolute."
Constant	IQ_MPX_ABS_DBPATH
SAP Sybase Error Number	2984
SQL State	WW123
SQL Code	-1295L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	Specified Database path must be absolute.

Error 1296	"(%1) is not unique."
Constant	IQ_PARAM_VALUE_NOT_UNIQUE
SAP Sybase Error Number	2985
SQL State	WW124
SQL Code	-1296L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Parameter name.
Probable Cause	Specified value for a given parameter already exist in the multiplex configuration.

Error 1297	"No of servers in multiplex setup has reached to the maximum limit."
Constant	IQ_MULTIPLEX_SERVER_LIMIT_EXCEEDED
SAP Sybase Error Number	2986
SQL State	WW125
SQL Code	-1297L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	No of servers in multiplex setup has reached to the maximum limit. User cannot add any more secondary servers.

Error 1298	"Cannot alter multiplex failover node and other multiplex server properties in the same statement."
Constant	IQ_INVALID_CONFIG_FAILOVER_COMBINATION
SAP Sybase Error Number	2987
SQL State	WW126
SQL Code	-1298L

Error 1298	"Cannot alter multiplex failover node and other multiplex server properties in the same statement."
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	Users are not allowed to alter the multiplex failover node status and other multiplex server properties in the same statement.

Error 1299	"Drop multiplex server is allowed only in a multiplex setup."
Constant	IQ_DROP_MPX_ALLOWED_ONLY_IN_MPX
SAP Sybase Error Number	2988
SQL State	WW127
SQL Code	-1299L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	Drop multiplex server is allowed only in a multiplex setup.

Error 1300	"Cannot add first multiplex server with excluded status."
Constant	IQ_FIRST_SECONDARY_SERVER_CANNOT_BE_EXCLUDED
SAP Sybase Error Number	2989
SQL State	WW128
SQL Code	-1300L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	Users are not allowed to add the first multiplex server with status excluded.

Error 1301	"Cannot create multiplex server with role coordinator."
Constant	IQ_CANNOT_CREATE_MPX_COORDINATOR
SAP Sybase Error Number	2990
SQL State	WW129
SQL Code	-1301L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	Users are not allowed to create a multiplex server with role as coordinator.

Messages 1302 through 1321

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1302	"Host Port specification (%1) is invalid."
Constant	IQ_INVALID_HOSTNAME
SAP Sybase Error Number	2982
SQL State	WW121
SQL Code	-1302L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	Host Port Specification.
Probable Cause	Host port specification is invalid.

Error 1303	"Too many MESSAGE...FOR CONNECTION messages"
Constant	CONNECTION_MESSAGE_QUEUE_FULL
SAP Sybase Error Number	2991
SQL State	54W16

Error 1303	"Too many MESSAGE...FOR CONNECTION messages"
SQL Code	-1303L
ODBC 2 State	37000
ODBC 3 State	54000
Severity Code	19 on page 2
Probable Cause	You executed a MESSAGE...FOR CONNECTION statement and the maximum number of messages for the connection have already been queued.

Error 1304	"Could not create a new text index for this table with the same settings as \"%1\No message"
Constant	TEXT_INDEX_SAME_SETTING_IDX
SAP Sybase Error Number	2992
SQL State	WT021
SQL Code	-1304L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the other text index with the same settings.
Probable Cause	Two text indexes with the same column list and configuration settings cannot be created for a table.

Error 1305	"MobiLink communication error -- code: %1, parameter: %2, system code: %3"
Constant	MOBILINK_COMMUNICATIONS_ERROR
SAP Sybase Error Number	2993
SQL State	0AWD5
SQL Code	-1305L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2

Error 1305	"MobiLink communication error -- code: %1, parameter: %2, system code: %3"
Parameter 1	The MobiLink communication error code.
Parameter 2	The parameter to the MobiLink communication error if one exists.
Parameter 3	The system error code.
Probable Cause	An error was encountered while communicating with a MobiLink server.

Error 1306	"IN DBSPACE clause cannot be used for column '%1' since table '%2' is a partitioned table."
Constant	IN_DBSpace_NOT_ALLOWED
SAP Sybase Error Number	2994
SQL State	WW238
SQL Code	-1306L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The column name
Parameter 2	The table name
Probable Cause	Entire column cannot be assigned to a dbspace using the IN DBSPACE clause, if the table is a partitioned table.

Error 1307	"Database mirroring options are not supported for this database"
Constant	MIRRORING_OPTIONS_NOT_SUPPORTED
SAP Sybase Error Number	2995
SQL State	WW130
SQL Code	-1307L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1307	"Database mirroring options are not supported for this database"
Severity Code	<i>16 on page 2</i>
Probable Cause	The current database does not have catalog support for database mirroring servers and options. To use this feature, upgrade your database to the most recent version.

Error 1308	"Mirror server \"%1\" not found"
Constant	MIRROR_SERVER_NOT_FOUND
SAP Sybase Error Number	2996
SQL State	WW131
SQL Code	-1308L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The name of the mirror server.
Probable Cause	The named mirror server was not found in the database.

Error 1309	"Mirror server \"%1\" already exists"
Constant	MIRROR_SERVER_ALREADY_EXISTS
SAP Sybase Error Number	2997
SQL State	WW132
SQL Code	-1309L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The name of the mirror server.
Probable Cause	An attempt was made to create a mirror server that already exists in the database.

Error 1310	"Mirror server \"%1\" is referenced by another server"
Constant	MIRROR_SERVER_IN_USE
SAP Sybase Error Number	2998
SQL State	WW133
SQL Code	-1310L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the mirror server.
Probable Cause	An attempt was made to drop a mirror server that is referenced by another mirror server in the database.

Error 1311	"Principal mirror servers are already defined"
Constant	MIRROR_PARTNERS_ALREADY_DEFINED
SAP Sybase Error Number	2999
SQL State	WW134
SQL Code	-1311L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	An attempt was made to create a mirror server without a parent server, but two principal mirror servers are already defined in the database.

Error 1312	"Mirror server \"%1\" is not a valid parent server"
Constant	INVALID_MIRROR_PARENT
SAP Sybase Error Number	3000
SQL State	WW135
SQL Code	-1312L
ODBC 2 State	ERROR

Error 1312	"Mirror server \"%1\" is not a valid parent server"
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the mirror server.
Probable Cause	An attempt was made to define a parent for a mirror server that would result in a cycle.

Error 1313	"Maximum string length exceeded"
Constant	MAX_STRING_LENGTH_EXCEEDED
SAP Sybase Error Number	2969
SQL State	54W17
SQL Code	-1313L
ODBC 2 State	37000
ODBC 3 State	54000
Severity Code	15 on page 2
Probable Cause	A string operation attempted to create a string longer than the maximum allowed by the server.

Error 1314	"Cannot force failover when current server is marked as preferred"
Constant	CANNOT_FORCE_FAILOVER_ON_PREFERRED
SAP Sybase Error Number	3001
SQL State	WW136
SQL Code	-1314L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	An attempt was made to execute ALTER DATABASE SET PARTNER FAILOVER but the current server is marked as preferred. Attempting to force a failover in this situation is not allowed.

Error 1315	"Script file missing statement \"go\" delimiter on a separate line"
Constant	SCRIPT_MISSING_DELIMITER
SAP Sybase Error Number	2931
SQL State	WW046
SQL Code	-1315L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	15 on page 2
Probable Cause	For UltraLite, all non-comment SQL statements in a script file (including the final one) must be followed by "go" on a line by itself. For strings, you can use "\ngo" to end a statement.

Error 1316	"Unsupported load column specification used for a catalog store table."
Constant	IQ_LOAD_TABLE_UNSUPPORTED_COLUMN_SPEC
SAP Sybase Error Number	2930
SQL State	0AW25
SQL Code	-1316L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	For catalog store tables, only some of the load column specifications (for example, filler) are permitted.

Error 1317	"Multiplex server '%1' is shutting down due to a successful configuration change"
Constant	MPX_CONFIG_CHANGES_SRV_SHUTDOWN
SAP Sybase Error Number	2919
SQL State	WW239

Error 1317	"Multiplex server '%1' is shutting down due to a successful configuration change"
SQL Code	-1317L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the multiplex server.
Probable Cause	Successful execution of certain statements to change multiplex configuration forces a server shutdown. You will get the above error if you issue such a command.

Error 1318	"More articles are being dropped from publication '%1' than are defined"
Constant	TOO_MANY_ARTICLES_DELETED
SAP Sybase Error Number	2890
SQL State	42W89
SQL Code	-1318L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Name of the publication from which the article could not be dropped.
Probable Cause	The number of articles in a publication can never fall below one. Your ALTER PUBLICATION has more drop/delete article clauses than the current number of articles in the publication.

Error 1319	"Synchronization schema changes and script versions are not supported for this database"
Constant	SYNC_SCHEMA_UPGRADE
SAP Sybase Error Number	3002
SQL State	WW137

Error 1319	"Synchronization schema changes and script versions are not supported for this database"
SQL Code	-1319L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The current database does not have catalog support for synchronization schema changes and script versions. To use this feature, upgrade your database to the most recent version.

Error 1320	"Error raised by user-defined function: %1"
Constant	EMSG_UDF_RAISED_ERROR
SAP Sybase Error Number	2822
SQL State	QFA62
SQL Code	-1320L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Error message provided by UDF to accompany UDF SQLCODE.
Probable Cause	An error was raised by a user-defined function.

Error 1321	"Table or view '%1' is not valid for use with this statement"
Constant	INVALID_TABLE_TYPE
SAP Sybase Error Number	3004
SQL State	WW139
SQL Code	-1321L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of table

Error 1321	"Table or view '%1' is not valid for use with this statement"
Probable Cause	The named table or view cannot be used with this statement. For example, the statement may not allow temporary tables or views.

Messages 1322 through 1341

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1322	"A synchronization schema change is already in progress"
Constant	SYNC_SCHEMA_IN_PROGRESS
SAP Sybase Error Number	3005
SQL State	WW140
SQL Code	-1322L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	A START SYNCHRONIZATION SCHEMA CHANGE statement is already in progress.

Error 1323	"Subscription to publication '%1' for '%2' omitted from statement"
Constant	SUBSCRIPTION_OMITTED
SAP Sybase Error Number	3006
SQL State	WW141
SQL Code	-1323L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	Name of publication
Parameter 2	Name of MobiLink user

Error 1323	"Subscription to publication '%1' for '%2' omitted from statement"
Probable Cause	A START SYNCHRONIZATION SCHEMA CHANGE statement lists a table that will be modified, but a subscription which refers to that table was omitted from the statement.

Error 1324	"Connection is not allowed to have table locks when executing this statement"
Constant	CONNECTION_HAS_LOCKS
SAP Sybase Error Number	3007
SQL State	WW142
SQL Code	-1324L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	An attempt was made to execute a statement by a connection that is holding table locks. Because the statement could release all locks, including those held before the statement started, the locks must be released before the statement can be executed.

Error 1325	"Column subset for table '%1' in publication '%2' does not match that specified in publication '%3'"
Constant	COLUMN_SUBSET_MISMATCH
SAP Sybase Error Number	3003
SQL State	WW138
SQL Code	-1325L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of table
Parameter 2	Name of first publication

Error 1325	"Column subset for table '%1' in publication '%2' does not match that specified in publication '%3'"
Parameter 3	Name of second publication
Probable Cause	The columns included for a table must be identical for all subscribed publications which reference the table.

Error 1326	"Subscription '%1' not found"
Constant	SUBSCRIPTION_NAME_NOT_FOUND
SAP Sybase Error Number	3008
SQL State	5RW40
SQL Code	-1326L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of subscription
Probable Cause	You attempted to ALTER, DROP, or otherwise reference a subscription that does not exist.

Error 1327	"The materialized view cannot be changed to immediate because its SELECT list contains a SUM function over a nullable expression and it doesn't contain a COUNT function over the same expression"
Constant	UPDATABLE_MATVIEW_COUNT_NULL_EXPR
SAP Sybase Error Number	3009
SQL State	42WCE
SQL Code	-1327L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	15 on page 2

Error 1327	"The materialized view cannot be changed to immediate because its SELECT list contains a SUM function over a nullable expression and it doesn't contain a COUNT function over the same expression"
Probable Cause	You attempted to change the refresh type to immediate for a materialized view whose definition contains a SUM function over a nullable expression but it doesn't contain COUNT function over the same expression.

Error 1328	"Table '%1' must synchronize to be in publication '%2'"
Constant	TABLE_MUST_SYNCHRONIZE_IN_PUB
SAP Sybase Error Number	3010
SQL State	WW143
SQL Code	-1328L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of table
Parameter 2	Name of publication
Probable Cause	A publication cannot contain a table with a SYNCHRONIZE OFF constraint; all tables in a publication must synchronize. You attempted to add a table with a SYNCHRONIZE OFF constraint to a publication, or to alter a table to use SYNCHRONIZE OFF when the table is already in a publication.

Error 1329	"This operation is only allowed within a synchronization schema change"
Constant	REQUIRES_SYNC_SCHEMA_CHANGE
SAP Sybase Error Number	3011
SQL State	5RW41
SQL Code	-1329L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1329	"This operation is only allowed within a synchronization schema change"
Severity Code	<i>16</i> on page 2
Probable Cause	You attempted an operation that is only allowed within a synchronization schema change.

Error 1330	"The function '%1' does not allow use of the '%2' clause"
Constant	FUNCTION_DOES_NOT_ALLOW
SAP Sybase Error Number	2823
SQL State	42WE0
SQL Code	-1330L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The name of the function.
Parameter 2	The SQL clause not allowed.
Probable Cause	You have attempted to use the specified SQL clause within the context of a function that does not permit such use. Note that the function may have been used directly in the query or indirectly within a named window.

Error 1331	"The function '%1' requires the use of the '%2' clause"
Constant	FUNCTION_REQUIRES
SAP Sybase Error Number	2807
SQL State	42WE1
SQL Code	-1331L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The name of the function.
Parameter 2	The SQL clause required.

Error 1331	"The function '%1' requires the use of the '%2' clause"
Probable Cause	You have attempted to invoke the specified function without the use of a mandatory SQL clause within the context of the function. Note that the function may have been used directly in the query or indirectly within a named window.

Error 1332	"Feature '%1' is unknown or invalid"
Constant	FEATURE_UNKNOWN_OR_INVALID
SAP Sybase Error Number	3012
SQL State	WW144
SQL Code	-1332L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Feature name
Probable Cause	You attempted to lock or unlock an unknown feature.

Error 1333	"Feature '%1' was not locked by this connection"
Constant	FEATURE_NOT_LOCKED
SAP Sybase Error Number	3013
SQL State	WW145
SQL Code	-1333L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Feature name
Probable Cause	You attempted to unlock a feature that was not previously locked by this connection.

Error 1334	"Feature '%1' is locked by another connection"
Constant	FEATURE_LOCKED

Error 1334	"Feature '%1' is locked by another connection"
SAP Sybase Error Number	3014
SQL State	WW146
SQL Code	-1334L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	Feature name
Probable Cause	You attempted to use a feature that was previously locked by another connection.

Error 1335	"Type '%1' does not support method calls (near '%2')."
Constant	METHOD_ON_NON_EXT
SAP Sybase Error Number	3015
SQL State	42X00
SQL Code	-1335L
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	<i>11</i> on page 2
Parameter 1	The name of the data type.
Parameter 2	The invalid expression.
Probable Cause	You attempted to invoke a method on a value of a data type that does not define any methods.

Error 1336	"Type '%1' has no method named '%2' (near '%3')."
Constant	METHOD_NOT_FOUND
SAP Sybase Error Number	3016
SQL State	42X01
SQL Code	-1336L

Error 1336	"Type '%1' has no method named '%2' (near '%3')."
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	<i>11</i> on page 2
Parameter 1	The name of the type with the unmatched method.
Parameter 2	Name of the method that could not be matched.
Parameter 3	The invalid expression.
Probable Cause	When attempting to match a method invocation, no method was found with the appropriate name. Check for spelling errors.

Error 1337	"Method invocation '%1' does not match an overload (near '%2'). Available overloads are '%3'."
Constant	METHOD_NO_OVERLOAD
SAP Sybase Error Number	3017
SQL State	42X02
SQL Code	-1337L
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	<i>11</i> on page 2
Parameter 1	The method name and data types used in the method invocation.
Parameter 2	The invalid expression.
Parameter 3	The available method overloads.
Probable Cause	When attempting to match a method invocation, none of the defined overloads was found to match the provided argument types. You may need to use CAST to select the appropriate call.

Error 1338	"Type '%1' is not instantiable (near '%2')"
Constant	METHOD_NO_CONSTRUCTOR
SAP Sybase Error Number	3018
SQL State	42X03

Error 1338	"Type '%1' is not instantiable (near '%2')"
SQL Code	-1338L
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	<i>// on page 2</i>
Parameter 1	The name of the type that is not instantiable.
Parameter 2	The invalid expression.
Probable Cause	A NEW expression was used for a data type that does not define any constructor methods.

Error 1339	"Method '%1' cannot be called with %2 arguments (near '%3')"
Constant	METHOD_NO_OVERLOAD_N_ARGS
SAP Sybase Error Number	3019
SQL State	42X04
SQL Code	-1339L
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	<i>// on page 2</i>
Parameter 1	The name of the method.
Parameter 2	The number of arguments supplied.
Parameter 3	The invalid expression.
Probable Cause	No overload of the specified method can be called with the number of arguments provided.

Error 1340	"Type '%1' cannot be instantiated with %2 arguments (near '%3')"
Constant	METHOD_NO_CONSTRUCTOR_N_ARGS
SAP Sybase Error Number	3020
SQL State	42X05

Error 1340	"Type '%1' cannot be instantiated with %2 arguments (near '%3')"
SQL Code	-1340L
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	<i>11 on page 2</i>
Parameter 1	The name of the type that cannot be instantiated.
Parameter 2	The number of arguments supplied.
Parameter 3	The invalid expression.
Probable Cause	A NEW expression was used for a data type that does not define any constructor methods.

Error 1341	"The instantiation '%1' does not match an overload (near '%2'). Available overloads are '%3'."
Constant	METHOD_NO_CONSTRUCTOR_OVERLOAD
SAP Sybase Error Number	3021
SQL State	42X06
SQL Code	-1341L
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity Code	<i>11 on page 2</i>
Parameter 1	The type name and data types used in the new specification.
Parameter 2	The invalid expression.
Parameter 3	The available constructor overloads.
Probable Cause	When attempting to match a new specification, none of the defined constructor overloads was found to match the provided argument types. You may need to use CAST to select the appropriate call.

Messages 1342 through 1363

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1342	"Data modifications are not allowed in a synchronization schema change"
Constant	SYNC_SCHEMA_CHANGE_DISALLOWS_DML
SAP Sybase Error Number	3022
SQL State	5RW42
SQL Code	-1342L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You attempted a data modification operation within a synchronization schema change.

Error 1343	"Feature '%1' is locked because synchronization is in progress"
Constant	FEATURE_LOCKED_SYNC
SAP Sybase Error Number	3023
SQL State	WW147
SQL Code	-1343L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Feature name
Probable Cause	You attempted to use a feature that was previously locked because a synchronization is in progress.

Error 1344	"Rollback occurred due to blocking_others_timeout"
Constant	BLOCKING_OTHERS_ROLLBACK

Error 1344	"Rollback occurred due to blocking_others_timeout"
SAP Sybase Error Number	3024
SQL State	WW148
SQL Code	-1344L
ODBC 2 State	40001
ODBC 3 State	40001
Severity Code	13 on page 2
Probable Cause	This connection has been rolled back because another connection was blocked on this connection for longer than the blocking_others_timeout option setting. All requests on this connection will get this error until it is disconnected.

Error 1347	"Use of authority '%1' is not supported on the current database"
Constant	OLIN_AUTHORITIES_UNSUPPORTED
SAP Sybase Error Number	2776
SQL State	28W16
SQL Code	-1347L
ODBC 2 State	28000
ODBC 3 State	28000
Severity Code	16 on page 2
Parameter 1	The unsupported authority.
Probable Cause	The current database is an older database and does not have the capability to support given authority. You must upgrade your database to use this authority.

Error 1348	"Mirror server name '%1' does not match current server name"
Constant	INVALID_CHILD_SERVER_NAME
SAP Sybase Error Number	3027
SQL State	WW151

Error 1348	"Mirror server name '%1' does not match current server name"
SQL Code	-1348L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The server name
Probable Cause	The server name specified in a CREATE MIRROR SERVER statement must match the current server name when the statement is executed on a child server.

Error 1349	"The parent of this mirror server is not currently connected"
Constant	PARENT_NOT_CONNECTED
SAP Sybase Error Number	3028
SQL State	WW152
SQL Code	-1349L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	The statement being executed requires a connection from this mirror server to its parent, but the parent is not currently connected.

Error 1350	"The parent of this mirror server is not the primary server"
Constant	PARENT_NOT_PRIMARY
SAP Sybase Error Number	3029
SQL State	WW153
SQL Code	-1350L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1350	"The parent of this mirror server is not the primary server"
Severity Code	<i>16 on page 2</i>
Probable Cause	The statement being executed requires a connection from this mirror server to the primary server, but the parent is not the primary server. The connection string to this server's parent does not match the connection string for the primary server.

Error 1351	"Mirror child server creation failed"
Constant	CHILD_SERVER_CREATION_FAILED
SAP Sybase Error Number	3030
SQL State	WW154
SQL Code	-1351L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	The creation of a child server on the primary server failed or was disallowed.

Error 1352	"Mirror server with type '%1' is already defined"
Constant	MIRROR_SERVER_TYPE_ALREADY_DEFINED
SAP Sybase Error Number	3031
SQL State	WW155
SQL Code	-1352L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The server type
Probable Cause	A CREATE MIRROR SERVER statement specified a server type that has already been defined.

Error 1353	"Invalid operation '%2' on sequence '%1'"
Constant	INVALID_SEQUENCE_OPERATION
SAP Sybase Error Number	3033
SQL State	52W46
SQL Code	-1353L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Name of the operation attempted.
Parameter 2	Name of the sequence.
Probable Cause	An invalid operation has been attempted on a sequence object. The only valid operations on a sequence are currval and nextval.

Error 1354	"Sequence '%1' already exists"
Constant	SEQUENCE_ALREADY_EXISTS
SAP Sybase Error Number	3034
SQL State	52W47
SQL Code	-1354L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Name of the sequence.
Probable Cause	A sequence with the specified name already exists.

Error 1355	"No more values available in sequence %1"
Constant	SEQUENCE_EXHAUSTED
SAP Sybase Error Number	3035
SQL State	52W48
SQL Code	-1355L

Error 1355	"No more values available in sequence %1"
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Name of the sequence.
Probable Cause	No more values can be supplied by the sequence; the next value to be supplied would be either larger than the maximum value, or smaller than the minimum value, and this sequence has been specified with NO CYCLE.

Error 1356	"Definition for sequence '%1' is invalid"
Constant	INVALID_SEQUENCE_DEFINITION
SAP Sybase Error Number	3036
SQL State	52W49
SQL Code	-1356L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Name of the sequence.
Probable Cause	An invalid combination of modifiers has been used for the sequence. Make sure that the MAXVAL is greater than the MINVAL and that START WITH is between MINVAL and MAXVAL.

Error 1357	"Multiple settings of same option specified for sequence '%1'"
Constant	DUPLICATE_SEQUENCE_OPTION
SAP Sybase Error Number	3037
SQL State	52W50
SQL Code	-1357L
ODBC 2 State	42000
ODBC 3 State	42000

Error 1357	"Multiple settings of same option specified for sequence '%1'"
Severity Code	<i>16 on page 2</i>
Parameter 1	Name of the sequence.
Probable Cause	Multiple settings of the same sequence option have been specified in the sequence definition. Even if the setting is the same, you can only specify each option once.

Error 1358	"Sequence name '%1' is ambiguous"
Constant	AMBIGUOUS_SEQUENCE_NAME
SAP Sybase Error Number	3038
SQL State	52W45
SQL Code	-1358L
ODBC 2 State	S0013
ODBC 3 State	42S13
Severity Code	<i>16 on page 2</i>
Parameter 1	Name of an ambiguous sequence.
Probable Cause	A statement has referred to a sequence name that is not unique. Preface the sequence name by an owner name.

Error 1359	"Sequence '%1' not found"
Constant	SEQUENCE_NOT_FOUND
SAP Sybase Error Number	3039
SQL State	52W44
SQL Code	-1359L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	<i>16 on page 2</i>
Parameter 1	Name of the sequence.
Probable Cause	The sequence with this name does not exist in the database.

Error 1360	"Cannot assign automatic mirror server parent"
Constant	CANNOT_ASSIGN_AUTO_PARENT
SAP Sybase Error Number	3040
SQL State	WW156
SQL Code	-1360L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	A CREATE MIRROR SERVER or ALTER MIRROR SERVER statement requested that a mirror parent be automatically assigned, but a parent server could not be found. The auto_add_server option may not be set, or might be set to an invalid server name.

Error 1361	"TREAT AS can only be used with extended types. Cannot treat %1 as a %2."
Constant	TREAT_AS_ONLY_EXTENDED
SAP Sybase Error Number	3041
SQL State	53020
SQL Code	-1361L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The value that could not be converted.
Parameter 2	The name of the type for the conversion.
Probable Cause	An error occurred while trying to treat a value as another data type.

Error 1362	"Cannot treat value '%1' as type %2. The dynamic type is %3."
Constant	TREAT_AS_DYNAMIC_MISMATCH
SAP Sybase Error Number	3042

Error 1362	"Cannot treat value '%1' as type %2. The dynamic type is %3."
SQL State	53021
SQL Code	-1362L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The value that could not be converted.
Parameter 2	The name of the type for the conversion.
Parameter 3	The type of the value that could not be converted.
Probable Cause	An error occurred while trying to treat a value as another data type. The dynamic type of the value does not match the destination type.

Error 1363	"The 'currval' operator is not defined yet for sequence '%1' for this connection"
Constant	SEQUENCE_CURRVAL_NOT_DEFINED
SAP Sybase Error Number	3043
SQL State	52W51
SQL Code	-1363L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Parameter 1	Name of the sequence.
Probable Cause	The currval operator of a sequence generator is only defined once nextval has been called for the sequence within the current connection.

Messages 1366 through 1386

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1366	"Sequence '%1' in use by another connection"
Constant	SEQUENCE_IN_USE
SAP Sybase Error Number	3046
SQL State	42WE3
SQL Code	-1366L
ODBC 2 State	40001
ODBC 3 State	40001
Severity Code	16 on page 2
Parameter 1	Name of user.
Probable Cause	You have attempted to drop a sequence that is currently being used by another connection.

Error 1367	"User owns sequences in use"
Constant	USER_OWNS_SEQUENCES_IN_USE
SAP Sybase Error Number	3047
SQL State	42WE2
SQL Code	-1367L
ODBC 2 State	40001
ODBC 3 State	40001
Severity Code	16 on page 2
Probable Cause	You attempted to drop a user that owns a sequence being used by other active users of the database.

Error 1369	"Sequence generators are not supported for this database"
Constant	SEQUENCES_NOT_SUPPORTED
SAP Sybase Error Number	3049

Error 1369	"Sequence generators are not supported for this database"
SQL State	52W52
SQL Code	-1369L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The current database does not have catalog support for sequence generators. To use this feature, upgrade your database to the most recent version.

Error 1370	"Text queries cannot contain more than 300 terms."
Constant	TEXT_QUERY_TOO_LONG
SAP Sybase Error Number	3050
SQL State	WT022
SQL Code	-1370L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	A text query should contain 300 terms or less.

Error 1371	"The materialized view cannot be changed to immediate because the ON conditions must refer to both sides of the OUTER JOIN."
Constant	UPDATABLE_MATVIEW_PSNS_ON_CONDITION
SAP Sybase Error Number	3051
SQL State	42WE4
SQL Code	-1371L
ODBC 2 State	42000
ODBC 3 State	ERROR

Error 1371	"The materialized view cannot be changed to immediate because the ON conditions must refer to both sides of the OUTER JOIN."
Severity Code	<i>15</i> on page 2
Probable Cause	You attempted to change the refresh type to immediate for a materialized view whose definition contains an illegal ON condition.

Error 1372	"The server is not able to establish TCP/IP connections."
Constant	TCP_CONNECTIONS_NOT_ENABLED
SAP Sybase Error Number	2736
SQL State	08WA3
SQL Code	-1372L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Probable Cause	This database server is not able to establish TCP/IP connections. The personal server (dbeng) does not permit TCP/IP connections by default. This error may also occur if a network server (dbsrv) was started with the -xd command line option. The ability to establish TCP/IP connections is required to use diagnostic tracing and application profiling.

Error 1373	"Synchronization failed with internal error: %1"
Constant	SYNCCMD_INTERNAL_ERROR
SAP Sybase Error Number	3052
SQL State	5RW43
SQL Code	-1373L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The internal error number

Error 1373	"Synchronization failed with internal error: %1"
Probable Cause	An internal error occurred during the execution of the SYNCHRONIZE statement.

Error 1374	"Synchronization failed. Check the results of the call to sp_get_last_synchronize_result(%1) for more information."
Constant	SYNCCMD_SYNCH_FAILED
SAP Sybase Error Number	3053
SQL State	5RW44
SQL Code	-1374L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The connection ID on which the failed synchronization took place
Probable Cause	The synchronization completed, but the exit code from the synchronization indicates that the synchronization was not successful. Check the results of the call to sp_get_last_synchronize_result() for more information.

Error 1375	"Failed to start the dbmlsync server"
Constant	SYNCCMD_START_SERVER_FAIL
SAP Sybase Error Number	3054
SQL State	5RW45
SQL Code	-1375L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The database server failed to start a new dbmlsync process or failed to connect to an existing dbmlsync server running on the port number specified in the SYNCHRONIZE statement.

Error 1376	"Failed to connect to the dbmlsync server"
Constant	SYNCCMD_CONNECT_SERVER_FAIL
SAP Sybase Error Number	3055
SQL State	5RW46
SQL Code	-1376L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The database server failed to make a connection to the dbmlsync server.

Error 1377	"The SYNCHRONIZE statement timed out"
Constant	SYNCCMD_TIMEOUT
SAP Sybase Error Number	3056
SQL State	5RW47
SQL Code	-1377L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The SYNCHRONIZE statement did not complete within the timeout value specified. Check the results of the call to sp_get_last_synchronize_result() for more information.

Error 1378	"The database server failed to shut down the dbmlsync server"
Constant	SYNCCMD_SHUTDOWN_FAIL
SAP Sybase Error Number	3057
SQL State	5RW48
SQL Code	-1378L
ODBC 2 State	ERROR

Error 1378	"The database server failed to shut down the dbmlsync server"
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Probable Cause	The database server started a new dbmlsync server to process the SYNCHRONIZE statement, but encountered an error while attempting to shut the process down.

Error 1379	"The dbmlsync server failed to shut down in a timely manner"
Constant	SYNCCMD_SHUTDOWN_SLOW
SAP Sybase Error Number	3058
SQL State	5RW49
SQL Code	-1379L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Probable Cause	The database server started a new dbmlsync server to process the SYNCHRONIZE statement, was successful in requesting that the process shut down, but the process did not shut down within the timeout value that was specified.

Error 1380	"Client redirected more than once"
Constant	TOO_MANY_REDIRECTS
SAP Sybase Error Number	3059
SQL State	08WA4
SQL Code	-1380L
ODBC 2 State	08S01
ODBC 3 State	08S01
Severity Code	<i>21</i> on page 2
Probable Cause	The connection was redirected by the primary server to another server, which also attempted to redirect the connection.

Error 1381	"Database server name '%1' cannot be the same as either the primary or mirror server"
Constant	MIRROR_SERVER_NAME_CONFLICT
SAP Sybase Error Number	3060
SQL State	WW159
SQL Code	-1381L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The server name
Probable Cause	The mirror servers defined with type PRIMARY or MIRROR cannot have names that match actual server names.

Error 1382	"Download failed due to an invalid or unsupported row value"
Constant	INVALID_DOWNLOAD_VALUE
SAP Sybase Error Number	3061
SQL State	0AW26
SQL Code	-1382L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The synchronization download failed because a downloaded row contained a column value that was either invalid or not supported.

Error 1383	"The licensed maximum number of mirror servers with type COPY has been exceeded"
Constant	MIRROR_COPY_SERVER_LIMIT_EXCEEDED
SAP Sybase Error Number	3062
SQL State	WW160

Error 1383	"The licensed maximum number of mirror servers with type COPY has been exceeded"
SQL Code	-1383L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The maximum number of mirror servers with type COPY that may be defined is limited by the database server license. An attempt was made to create a new mirror server with type COPY when the maximum allowed number of such servers already existed.

Error 1384	"Unable to stop specified database: %1"
Constant	UNABLE_TO_STOP_DATABASE
SAP Sybase Error Number	2728
SQL State	08WA5
SQL Code	-1384L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	11 on page 2
Parameter 1	Reason the database could not be stopped, if known.
Probable Cause	The database server was unable to stop the specified database.

Error 1385	"Synchronization failed. Check the dbmlsync log file for more details."
Constant	MLA_SYNC_FAILED
SAP Sybase Error Number	3063
SQL State	WW161
SQL Code	-1385L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2

Error 1385	"Synchronization failed. Check the dbmlsync log file for more details."
Probable Cause	The synchronization was not successful. Check the dbmlsync log file for more details.

Error 1386	"Failed to connect to the dbmlsync server. Check the dbmlsync log file for more details."
Constant	MLA_SYNC_CONNECT_SERVER_FAIL
SAP Sybase Error Number	3064
SQL State	WW162
SQL Code	-1386L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The MobiLink agent adapter failed to make a connection to the dbmlsync server. Check the dbmlsync log file for more details.

Messages 1387 through 1406

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1387	"Failed to shut down the dbmlsync server. Check the dbmlsync log file for more details."
Constant	MLA_SYNC_SHUTDOWN_FAIL
SAP Sybase Error Number	3065
SQL State	WW163
SQL Code	-1387L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The MobiLink agent adapter encountered an error while attempting to shut down the server. Check the dbmlsync log file for more details.

Error 1388	"Failed to start the dbmlsync server. Check the dbmlsync log file for more details."
Constant	MLA_SYNC_START_SERVER_FAIL
SAP Sybase Error Number	3066
SQL State	WW164
SQL Code	-1388L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The MobiLink agent adapter failed to start a new dbmlsync process or the server did not begin processing requests before the timeout expired. Check the dbmlsync log file for more details.

Error 1389	"The value for the stoplist cannot be NULL."
Constant	TEXT_STOPLIST_NULL
SAP Sybase Error Number	2727
SQL State	WT023
SQL Code	-1389L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The value for a text configuration stoplist cannot be NULL. To remove a stoplist, use the ALTER TEXT CONFIGURATION...DROP STOPLIST statement.

Error 1390	"An incremental refresh is not possible when handles are exhausted."
Constant	TEXT_HANDLES_EXHAUSTED
SAP Sybase Error Number	2724
SQL State	WT024

Error 1390	"An incremental refresh is not possible when handles are exhausted."
SQL Code	-1390L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	Incremental refresh of a MANUAL or AUTO REFRESH text index is not possible when handles are exhausted. You need to rebuild the text index before you can use incremental refresh.

Error 1391	"Invalid stoplist value."
Constant	TEXT_INVALID_STOPLIST_VALUE
SAP Sybase Error Number	2725
SQL State	WT025
SQL Code	-1391L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The value specified for the stoplist is not valid.

Error 1392	"Unique indexes with the clause WITH NULLS NOT DISTINCT are not supported for this database"
Constant	UNIQUE_INDEX_NULLS_NOT_DISTINCT_NOT_SUPPORTED
SAP Sybase Error Number	3067
SQL State	52W53
SQL Code	-1392L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2

Error 1392	"Unique indexes with the clause WITH NULLS NOT DISTINCT are not supported for this database"
Probable Cause	The current database does not have support for unique indexes with the clause WITH NULLS NOT DISTINCT. To use this feature, upgrade your database to the most recent version.

Error 1393	"Error initializing external term breaker"
Constant	ERROR_INITIALIZING_EXT_TERMBREAKER
SAP Sybase Error Number	2717
SQL State	WT028
SQL Code	-1393L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The external term breaker could not be initialized because of an internal error.

Error 1394	"Invalid external prefilter name specified"
Constant	INVALID_EXT_PREFILTER_NAME
SAP Sybase Error Number	2682
SQL State	WT029
SQL Code	-1394L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	External prefilter name specified in the text configuration is invalid.

Error 1395	"Invalid external term breaker name specified"
Constant	INVALID_EXT_TERMBREAKER_NAME
SAP Sybase Error Number	2683
SQL State	WT026

Error 1395	"Invalid external term breaker name specified"
SQL Code	-1395L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	External term breaker name specified in the text configuration is invalid.

Error 1396	"Error initializing external prefilter"
Constant	ERROR_INITIALIZING_EXT_PREFILTER
SAP Sybase Error Number	2718
SQL State	WT027
SQL Code	-1396L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The external prefilter could not be initialized because of an internal error.

Error 1397	"The definition of temporary table '%1' has changed since last used"
Constant	TEMP_TABLE_DEFINITION_CHANGED
SAP Sybase Error Number	3068
SQL State	WW165
SQL Code	-1397L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The table name

Error 1397	"The definition of temporary table '%1' has changed since last used"
Probable Cause	The definition of a temporary table has changed since it was last used in a stored procedure or trigger. The procedure must be recompiled.

Error 1398	"VERIFY and RENAME cannot be used together"
Constant	RENAME_WITH_VERIFY_NOT_ALLOWED
SAP Sybase Error Number	2681
SQL State	42WE5
SQL Code	-1398L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	15 on page 2
Probable Cause	Since VERIFY will never write to any dbspaces, renaming dbspaces cannot be done during restore verification.

Error 1399	"Invalid intersection matrix '%1'"
Constant	SLERR_INVALID_RELATE_MATRIX
SAP Sybase Error Number	3069
SQL State	2FF04
SQL Code	-1399L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The intersection matrix string.
Probable Cause	The provided value is not a valid intersection matrix string. A valid string contains nine characters, each is one of T, F, *, 0, 1, or 2.

Error 1400	"Point is duplicated %1"
Constant	SLERR_DUPLICATE_POINT
SAP Sybase Error Number	3070

Error 1400	"Point is duplicated %1"
SQL State	2FF05
SQL Code	-1400L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The duplicated point
Probable Cause	A linestring or circularstring geometry contains two adjacent points that are identical. This represents an invalid geometry.

Error 1401	"Element is an empty set (near '%1')"
Constant	SLERR_ELEMENT_IS_EMPTY
SAP Sybase Error Number	3071
SQL State	2FF06
SQL Code	-1401L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The value or method where the empty geometry has been detected.
Probable Cause	An element of a geometry is the empty set. Empty geometries cannot be used as the points in linestrings or circularstrings; empty curves cannot be used as elements of compoundcurves; empty curves cannot be used as rings of polygons.

Error 1402	"Mixed spatial reference systems %1 and %2 (near %3)"
Constant	SLERR_MIXED_SRS
SAP Sybase Error Number	3072
SQL State	2FF10
SQL Code	-1402L
ODBC 2 State	ERROR

Error 1402	"Mixed spatial reference systems %1 and %2 (near %3)"
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The SRID of the first spatial reference system.
Parameter 2	The SRID of the second spatial reference system.
Parameter 3	The value or method where the mixed spatial reference systems were detected.
Probable Cause	The method does not support working with geometries from different spatial reference systems.

Error 1403	"Non-contiguous curves near '%1'"
Constant	SLERR_COMPOUNDCURVE_NOT_CONTIGUOUS
SAP Sybase Error Number	3073
SQL State	2FF11
SQL Code	-1403L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The value or method where the non-contiguous curves were detected.
Probable Cause	A compoundcurve geometry is composed of curves, and adjacent curves must be joined at their endpoints.

Error 1404	"Unknown unit of measure '%1'"
Constant	SLERR_UNKNOWN_UOM
SAP Sybase Error Number	3074
SQL State	2FF14
SQL Code	-1404L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>

Error 1404	"Unknown unit of measure '%1'"
Parameter 1	The name of the unit of measure.
Probable Cause	The name does not match a defined unit of measure.

Error 1405	"Failed to transform geometry (error %1)"
Constant	SLERR_TRANSFORM_FAIL
SAP Sybase Error Number	3075
SQL State	2FF15
SQL Code	-1405L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The error code from the projection library.
Probable Cause	An error occurred when performing a transform from one spatial reference system to another. This error may occur if a point in the first geometry is outside of the bounds for the transform definition. The error may also be reported for particular transform definitions. The integer error code from the transform library may be used to diagnose the transform definition.

Error 1406	"Error parsing well-known-text (WKT) scanning '%1' at offset %2"
Constant	SLERR_WKT_PARSE_NEAR
SAP Sybase Error Number	3076
SQL State	2FF22
SQL Code	-1406L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The text where the problem was detected.

Error 1406	"Error parsing well-known-text (WKT) scanning '%1' at offset %2"
Parameter 2	The offset within the input string where the problem was detected.
Probable Cause	An error was detected while parsing the well-known text of a geometry.

Messages 1407 through 1427

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1407	"Error parsing well-known-binary (WKB) at offset %1"
Constant	SLERR_WKB_PARSE
SAP Sybase Error Number	3077
SQL State	2FF23
SQL Code	-1407L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The byte offset within the binary string where the error was detected.
Probable Cause	An error was detected while parsing the well-known binary of a geometry.

Error 1408	"Mixed coordinate dimensions"
Constant	SLERR_MIXED_DIM
SAP Sybase Error Number	3078
SQL State	2FF25
SQL Code	-1408L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2

Error 1408	"Mixed coordinate dimensions"
Probable Cause	The method contains geometries that have a mixture of coordinate dimensions (Z and M values).

Error 1409	"Unknown spatial reference system (%1)"
Constant	SLERR_SRID_UNKNOWN
SAP Sybase Error Number	3079
SQL State	2FF59
SQL Code	-1409L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The spatial reference system identifier.
Probable Cause	The provided SRID does not match a defined spatial reference system.

Error 1410	"An ST_CircularString cannot be constructed from %1 points (near '%2')"
Constant	SLERR_CIRC_NUM_POINTS
SAP Sybase Error Number	3080
SQL State	2FF71
SQL Code	-1410L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The incorrect number of points given.
Parameter 2	The value or method where the error was detected.
Probable Cause	A circularstring geometry should consist of three points followed optionally by an arbitrary number of pairs of points.

Error 1411	"Cannot convert from %1 to %2 (near %3)."
Constant	SLERR_ST_TO_XXX_FAILN
SAP Sybase Error Number	3081
SQL State	2FF16
SQL Code	-1411L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The geometry type of the value.
Parameter 2	The geometry type of the target.
Parameter 3	The value or method where the error was detected.
Probable Cause	The value could not be converted to the specified target type.

Error 1412	"Support for spatial is not available for this database"
Constant	SLERR_NEED_UPGRADE
SAP Sybase Error Number	3082
SQL State	2FW02
SQL Code	-1412L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	Operations involving spatial support cannot be used with this database because it needs to be upgraded to use spatial features.

Error 1413	"Spatial feature %1 is not supported"
Constant	SLERR_NYI
SAP Sybase Error Number	3083
SQL State	2FW03
SQL Code	-1413L

Error 1413	"Spatial feature %1 is not supported"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the unsupported feature.
Probable Cause	The specified feature is not supported.

Error 1414	"Error parsing well-known-text (WKT): inconsistent dimensions at offset %1"
Constant	SLERR_WKT_PARSE_INCONSISTENT_ZM
SAP Sybase Error Number	3084
SQL State	2FW05
SQL Code	-1414L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The offset within the well-known text string where the error was detected.
Probable Cause	There was a mixture of coordinate dimensions detected at the specified offset. For example, one geometry in a collection might have a Z value while another doesn't.

Error 1415	"Error parsing geometry internal serialization at offset %1"
Constant	SLERR_SERIAL_PARSE
SAP Sybase Error Number	3085
SQL State	2FW06
SQL Code	-1415L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2

Error 1415	"Error parsing geometry internal serialization at offset %1"
Parameter 1	The byte offset within the internal serialization.
Probable Cause	There was an error parsing the internal serialization string.

Error 1417	"Error parsing well-known-binary (WKB): type code %1 at offset %2 is invalid"
Constant	SLERR_WKB_PARSE_TYPE
SAP Sybase Error Number	3087
SQL State	2FW08
SQL Code	-1417L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The unsupported type code value.
Parameter 2	The byte offset within the binary string where the error was detected.
Probable Cause	The well-known binary string contains a type code that is not supported.

Error 1418	"Error parsing well-known-binary (WKB): type code %1 at offset %2 is not a valid subtype of the parent"
Constant	SLERR_WKB_PARSE_TYPE_NOT_PERMITTED
SAP Sybase Error Number	3088
SQL State	2FW09
SQL Code	-1418L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The unsupported type code value.
Parameter 2	The byte offset within the binary string where the error was detected.

Error 1418	"Error parsing well-known-binary (WKB): type code %1 at offset %2 is not a valid subtype of the parent"
Probable Cause	The well-known binary string contains a child geometry within a parent geometry and the child is not one of the types allowed by the parent.

Error 1419	"Error parsing well-known-binary (WKB): unexpected end of input"
Constant	SLERR_WKB_PARSE_UNEXPECTED_EOF
SAP Sybase Error Number	3089
SQL State	2FW10
SQL Code	-1419L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	A well-known binary string was shorter than expected.

Error 1420	"Error parsing well-known-binary (WKB): inconsistent dimensions at offset %1"
Constant	SLERR_WKB_PARSE_INCONSISTENT_ZM
SAP Sybase Error Number	3090
SQL State	2FW11
SQL Code	-1420L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The byte offset within the binary string where the error was detected.
Probable Cause	The well-known binary string contains geometries with different numbers of coordinate dimensions. For example, it could contain a point with a Z value and another without a Z value.

Error 1421	"Error parsing well-known-binary (WKB): invalid byte order mark %1 at offset %2"
Constant	SLERR_WKB_PARSE_INVALID_BOM
SAP Sybase Error Number	3091
SQL State	2FW12
SQL Code	-1421L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The value of the byte-order mark.
Parameter 2	The byte offset within the binary string where the error was detected.
Probable Cause	The well-known binary string has an invalid byte order mark. This could happen if a binary string that is not in the well-known binary format is used.

Error 1422	"Error parsing shapefile record"
Constant	SLERR_SHAPE_PARSE
SAP Sybase Error Number	3092
SQL State	2FW13
SQL Code	-1422L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The shapefile contains an invalid record.

Error 1423	"Error parsing shapefile attributes"
Constant	SLERR_SHAPE_PARSE_ATTRIBUTES
SAP Sybase Error Number	3093
SQL State	2FW14

Error 1423	"Error parsing shapefile attributes"
SQL Code	-1423L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The shapefile contains invalid attributes.

Error 1424	"Invalid shapefile filename"
Constant	SLERR_SHAPE_INVALID_FILENAME
SAP Sybase Error Number	3094
SQL State	2FW15
SQL Code	-1424L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The specified shapefile filename is not valid.

Error 1425	"The multi patch shapefile shape is not supported"
Constant	SLERR_SHAPE_MULTIPATCH
SAP Sybase Error Number	3095
SQL State	2FW16
SQL Code	-1425L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The shapefile contains a multi patch object; this type is not supported.

Error 1426	"The embedded SRID (%1) conflicts with the provided SRID (%2)."
Constant	SLERR_SRID_CONFLICT_EMBED_PARAM

Error 1426	"The embedded SRID (%1) conflicts with the provided SRID (%2)."
SAP Sybase Error Number	3096
SQL State	2FW19
SQL Code	-1426L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The SRID within the parsed string.
Parameter 2	The SRID provided as a parameter.
Probable Cause	A call to a spatial method had a string with an embedded SRID that differed from the SRID parameter to the method.

Error 1427	"The embedded SRID are inconsistent (%1 and %2)."
Constant	SLERR_SRID_CONFLICT_EMBED_EMBED
SAP Sybase Error Number	3097
SQL State	2FW20
SQL Code	-1427L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The first SRID.
Parameter 2	The second SRID.
Probable Cause	A geometry in a string representation contains objects from different spatial reference systems.

1428 - 1629

Messages 1428 through 1448

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1428	"The format type '%1' is not recognized."
Constant	SLERR_FMT_UNKNOWN
SAP Sybase Error Number	3098
SQL State	2FW21
SQL Code	-1428L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The invalid format type.
Probable Cause	The specified format type is not recognized.

Error 1429	"The format type '%1' cannot be used here."
Constant	SLERR_FMT_NOT_ALLOWED
SAP Sybase Error Number	3099
SQL State	2FW22
SQL Code	-1429L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The invalid format type.
Probable Cause	The specified format type cannot be used in this context.

Error 1430	"An input string in '%1' format cannot be used here."
Constant	SLERR_WRONG_FORMAT
SAP Sybase Error Number	3100
SQL State	2FW23

Error 1430	"An input string in '%1' format cannot be used here."
SQL Code	-1430L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The invalid format.
Probable Cause	A string with the specified format cannot be used in this context.

Error 1431	"The format specification syntax is invalid."
Constant	SLERR_INVALID_FORMAT_SPECIFICATION
SAP Sybase Error Number	3101
SQL State	2FW24
SQL Code	-1431L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	The format specification is invalid.

Error 1432	"The format specification option '%1' is not recognized."
Constant	SLERR_INVALID_FORMAT_SPECIFICATION_OPTION
SAP Sybase Error Number	3102
SQL State	2FW25
SQL Code	-1432L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The invalid option.
Probable Cause	The named option is not supported for the format specification.

Error 1433	"The value '%2' is not a valid setting for the '%1' format specification option."
Constant	SLERR_INVALID_FORMAT_SPECIFICATION_OPTION_VALUE
SAP Sybase Error Number	3103
SQL State	2FW26
SQL Code	-1433L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The invalid value.
Parameter 2	The format specification option.
Probable Cause	The value is not accepted by the specification option.

Error 1434	"The data is not in a recognized format."
Constant	SLERR_UNKOWNN_FORMAT
SAP Sybase Error Number	3104
SQL State	2FW27
SQL Code	-1434L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The provided string is not in a recognized format to parse a geometry.

Error 1435	"A geometry with SRID=%1 is not supported for method %2."
Constant	SLERR_ROUND_EARTH_UNSUPPORTED
SAP Sybase Error Number	3105
SQL State	2FW28
SQL Code	-1435L

Error 1435	"A geometry with SRID=%1 is not supported for method %2."
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The SRID of the geometry.
Parameter 2	The name of the method that does not support this SRID.
Probable Cause	The named method does not support geometries in the specified spatial reference system. For example, the method might not support round-Earth data.

Error 1436	"A geometry with SRID=%1 is not supported when computing distance between non-point geometries."
Constant	SLERR_ROUND_EARTH_UNSUPPORTED_DIS
SAP Sybase Error Number	3106
SQL State	2FW29
SQL Code	-1436L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The SRID of the geometry.
Probable Cause	When operating with round-Earth data, distance between non-point geometries is not supported.

Error 1438	"Error reading configuration file."
Constant	SLERR_CONFIG_FILE_ERR
SAP Sybase Error Number	3108
SQL State	2FW31
SQL Code	-1438L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1438	"Error reading configuration file."
Severity Code	<i>16</i> on page 2
Probable Cause	An error occurred while reading a configuration file for spatial support. This error can occur if the "st_geometry_config.tgz" file is not installed.

Error 1439	"Invalid configuration name %1"
Constant	SLERR_CONFIG_NO_SUBFILE
SAP Sybase Error Number	3109
SQL State	2FW32
SQL Code	-1439L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The invalid configuration name.
Probable Cause	The named configuration is not supported.

Error 1440	"The comparison '%1' cannot be used with geometries."
Constant	SLERR_COMPARISON_PREDICATE
SAP Sybase Error Number	3110
SQL State	2FW33
SQL Code	-1440L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The type of comparison relation.
Probable Cause	Geometry values cannot be compared with operators such as < or >. Geometries can only be compared with = and <>.

Error 1441	"Invalid spatial reference system well-known-text (WKT)."
Constant	SLERR_SRS_PARSE_ERROR
SAP Sybase Error Number	3111
SQL State	2FW34
SQL Code	-1441L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The provided string does not represent a valid spatial reference system definition in well-known text format.

Error 1442	"Invalid transform definition '%1'."
Constant	SLERR_INVALID_TRANSFORM_DEF
SAP Sybase Error Number	3112
SQL State	2FW35
SQL Code	-1442L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The invalid transform definition string.
Probable Cause	The provided string does not represent a valid transform definition.

Error 1443	"Transform definition is too long."
Constant	SLERR_TRANSFORM_DEF_TOO_LONG
SAP Sybase Error Number	3113
SQL State	2FW36
SQL Code	-1443L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1443	"Transform definition is too long."
Severity Code	<i>16 on page 2</i>
Probable Cause	The provided transform definition is too long.

Error 1444	"Transform from SRID %1 to %2 not supported."
Constant	SLERR_NO_XFORM_DEF
SAP Sybase Error Number	3114
SQL State	2FW37
SQL Code	-1444L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The SRID of the value.
Parameter 2	The SRID of the destination.
Probable Cause	There is no way to transform from the value's spatial reference system to the specified target.

Error 1445	"Transform from SRID %1 not supported."
Constant	SLERR_NO_SRC_XFORM_DEF
SAP Sybase Error Number	3115
SQL State	2FW38
SQL Code	-1445L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The SRID of the value.
Probable Cause	There is no way to transform from values of the specified spatial reference system.

Error 1446	"Unit of measure \"%1\" is not a linear unit."
Constant	SLERR_UOM_NOT_LINEAR
SAP Sybase Error Number	3116
SQL State	2FW39
SQL Code	-1446L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the invalid unit of measure.
Probable Cause	The specified unit of measure is not a linear unit of measure.

Error 1447	"Unit of measure \"%1\" is not an angular unit."
Constant	SLERR_UOM_NOT_ANGULAR
SAP Sybase Error Number	3117
SQL State	2FW40
SQL Code	-1447L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the invalid unit of measure.
Probable Cause	The specified unit of measure is not a linear unit of measure.

Error 1448	"Invalid polygon format \"%1\""
Constant	SLERR_INVALID_POLY_ORD
SAP Sybase Error Number	3118
SQL State	2FW41
SQL Code	-1448L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1448	"Invalid polygon format '%1'"
Severity Code	<i>16 on page 2</i>
Parameter 1	The invalid polygon format.
Probable Cause	The specified polygon format is not a valid format.

Messages 1449 through 1468

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1449	"Invalid polygon: no exterior ring"
Constant	SLERR_INVALID_POLY_NO_EXT
SAP Sybase Error Number	3119
SQL State	2FW42
SQL Code	-1449L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	The provided polygon is invalid as it does not have an exterior ring.

Error 1450	"Invalid polygon nesting"
Constant	SLERR_INVALID_POLY_NESTING
SAP Sybase Error Number	3120
SQL State	2FW43
SQL Code	-1450L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	The provided rings cannot be interpreted as a valid polygons.

Error 1451	"Invalid polygon: multiple exterior rings"
Constant	SLERR_INVALID_POLY_MULT_EXT

Error 1451	"Invalid polygon: multiple exterior rings"
SAP Sybase Error Number	3121
SQL State	2FW44
SQL Code	-1451L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	There are multiple exterior rings that do not form a single valid polygon.

Error 1452	"Table '%1' contains a spatial column '%2' and no primary key"
Constant	SLERR_UPDDEL_NO_PK
SAP Sybase Error Number	3122
SQL State	2FW45
SQL Code	-1452L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The table name.
Parameter 2	The spatial column name.
Probable Cause	An update or delete statement cannot be performed for a table that contains a spatial column unless there is a primary key defined for the table.

Error 1453	"Spatial column '%1' cannot be included in a primary key or unique index"
Constant	SLERR_CREATE_INDEX_UNIQUE
SAP Sybase Error Number	3123
SQL State	2FW46
SQL Code	-1453L

Error 1453	"Spatial column '%1' cannot be included in a primary key or unique index"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the spatial column.
Probable Cause	A spatial column cannot be included in a primary key or unique index.

Error 1454	"Spatial column '%1' cannot be included in an index because it is not constrained to a single SRID"
Constant	SLERR_CREATE_INDEX_NOSRID
SAP Sybase Error Number	3124
SQL State	2FW47
SQL Code	-1454L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the spatial column.
Probable Cause	The named spatial column cannot be included in a spatial index because the column is not constrained to have values from a single spatial reference system. The column definition should be of the form "col ST_Geometry(SRID=0)".

Error 1455	"The CONVERT USING clause must be specified when creating a unit of measure"
Constant	SLERR_DDL_UOM_NOFACT
SAP Sybase Error Number	3125
SQL State	2FW48
SQL Code	-1455L
ODBC 2 State	ERROR

Error 1455	"The CONVERT USING clause must be specified when creating a unit of measure"
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Probable Cause	A CREATE SPATIAL UNIT OF MEASURE statement was used without including the CONVERT USING clause.

Error 1456	"The string '%1' is not a valid axis order"
Constant	SLERR_DDL_SRS_AXISORDER
SAP Sybase Error Number	3126
SQL State	2FW49
SQL Code	-1456L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The invalid axis order.
Probable Cause	The specified string is not a valid axis order.

Error 1457	"The string '%1' is not a valid coordinate name"
Constant	SLERR_DDL_SRS_COORDNAME
SAP Sybase Error Number	3127
SQL State	2FW50
SQL Code	-1457L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The invalid coordinate name.
Probable Cause	The provided string is not the name of a coordinate. Coordinate names are X, Y, Z, M, Latitude and Longitude.

Error 1458	"Unit of measure '%1' not found"
Constant	SLERR_DDL_NO_UOM
SAP Sybase Error Number	3128
SQL State	2FW51
SQL Code	-1458L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The unit of measure name.
Probable Cause	The named unit of measure is not defined.

Error 1459	"Spatial reference system '%1' not found"
Constant	SLERR_DDL_NO_SRS
SAP Sybase Error Number	3129
SQL State	2FW52
SQL Code	-1459L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the spatial reference system.
Probable Cause	The named spatial reference system is not defined.

Error 1460	"Unit of measure '%1' already exists"
Constant	SLERR_DDL_UOM_EXISTS
SAP Sybase Error Number	3130
SQL State	2FW53
SQL Code	-1460L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1460	"Unit of measure '%1' already exists"
Severity Code	<i>16</i> on page 2
Parameter 1	The name of the unit of measure.
Probable Cause	The named unit of measure is already defined.

Error 1461	"Spatial reference system '%1' already exists"
Constant	SLERR_DDL_SRS_EXISTS
SAP Sybase Error Number	3131
SQL State	2FW54
SQL Code	-1461L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The name of the spatial reference system.
Probable Cause	The named spatial reference system already exists.

Error 1462	"Spatial reference system must specify the SRID to use"
Constant	SLERR_DDL_SRS_NOSRID
SAP Sybase Error Number	3132
SQL State	2FW55
SQL Code	-1462L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Probable Cause	When creating a spatial reference system, the statement must specify IDENTIFIED BY to specify the SRID to use.

Error 1463	"Error parsing definition string '%1'"
Constant	SLERR_DDL_SRS_BADWKT
SAP Sybase Error Number	3133

Error 1463	"Error parsing definition string '%1'"
SQL State	2FW56
SQL Code	-1463L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	Coordinate system name
Probable Cause	The provided definition string is not a valid well known text of the coordinate system.

Error 1464	"The spatial reference system type is not supported ('%1')"
Constant	SLERR_DDL_SRS_BAD_SRS_TYPE
SAP Sybase Error Number	3134
SQL State	2FW57
SQL Code	-1464L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The unsupported spatial reference system type.
Probable Cause	The specified spatial reference system type is not supported.

Error 1465	"Ellipsoid parameters missing for geographic spatial reference system"
Constant	SLERR_DDL_SRS_NOELLIPSOID
SAP Sybase Error Number	3135
SQL State	2FW58
SQL Code	-1465L
ODBC 2 State	ERROR

Error 1465	"Ellipsoid parameters missing for geographic spatial reference system"
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	When creating a geographic spatial reference system, the ellipsoid parameters must be specified, either in the DEFINITION clause or explicitly. These parameters are used to calculate the distance between points.

Error 1466	"Ellipsoid parameters specified for non-geographic spatial reference system"
Constant	SLERR_DDL_SRS_ELLIPSOID
SAP Sybase Error Number	3136
SQL State	2FW59
SQL Code	-1466L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The ELLIPSOID parameters can only be specified for geographic spatial reference systems.

Error 1467	"Coordinate bounds missing for coordinate %1"
Constant	SLERR_DDL_SRS_MUSTBOUND
SAP Sybase Error Number	3137
SQL State	2FW60
SQL Code	-1467L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The coordinate name.
Probable Cause	No bounds were specified for the named coordinate.

Error 1468	"The specified axis order is not supported for this type of spatial reference system"
Constant	SLERR_DDL_SRS_AXISORD
SAP Sybase Error Number	3138
SQL State	2FW61
SQL Code	-1468L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Probable Cause	The specified axis order is not supported for this type of spatial reference system.

Messages 1469 through 1489

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1469	"The specified polygon format '%1' is not supported for this type of spatial reference system"
Constant	SLERR_DDL_SRS_POLYFORMAT
SAP Sybase Error Number	3139
SQL State	2FW62
SQL Code	-1469L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The polygon format string.
Probable Cause	The specified polygon format is not supported for this type of spatial reference system.

Error 1470	"Invalid storage format '%1'"
Constant	SLERR_DDL_SRS_STGFORMAT

Error 1470	"Invalid storage format '%1'"
SAP Sybase Error Number	3140
SQL State	2FW63
SQL Code	-1470L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The invalid storage format string.
Probable Cause	The specified storage format string is not valid.

Error 1471	"Spatial reference system %1 cannot be modified because it is in use"
Constant	SLERR_DDL_SRS_INUSE
SAP Sybase Error Number	3141
SQL State	2FW64
SQL Code	-1471L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The coordinate system name
Probable Cause	The coordinate system is currently in use and cannot be dropped.

Error 1472	"Spatial reference system \"%1\" is reserved"
Constant	SLERR_DDL_SRS_RESERVED
SAP Sybase Error Number	3142
SQL State	2FW65
SQL Code	-1472L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1472	"Spatial reference system \"%1\" is reserved"
Severity Code	<i>16</i> on page 2
Parameter 1	The name of the reserved spatial reference system.
Probable Cause	The named spatial reference system is reserved for system use.

Error 1473	"Spatial unit of measure \"%1\" is reserved"
Constant	SLERR_DDL_UOM_RESERVED
SAP Sybase Error Number	3143
SQL State	2FW66
SQL Code	-1473L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The name of the reserved unit of measure.
Probable Cause	The named unit of measure is reserved for system use.

Error 1474	"SRID %1 is referenced by column '%2' of table '%3'"
Constant	SLERR_SRS_INUSE_TAB
SAP Sybase Error Number	3144
SQL State	2FW67
SQL Code	-1474L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The spatial reference system identifier.
Parameter 2	The name of the referencing column.
Parameter 3	The name of the referencing table.
Probable Cause	The specified spatial reference system is in use by the column of a table, and it cannot be modified.

Error 1475	"SRID %1 is referenced by parameter '%2' of procedure '%3'"
Constant	SLERR_SRS_INUSE_PROC
SAP Sybase Error Number	3145
SQL State	2FW68
SQL Code	-1475L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The spatial reference system identifier.
Parameter 2	The referencing parameter name.
Parameter 3	The referencing procedure name.
Probable Cause	The specified spatial reference system is in use by the parameter of a procedure, and it cannot be modified.

Error 1476	"SRID %1 is referenced by domain \"%3\".\"%2\"No message"
Constant	SLERR_SRS_INUSE_TYPE
SAP Sybase Error Number	3146
SQL State	2FW69
SQL Code	-1476L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The spatial reference system identifier.
Parameter 2	The owner of the domain.
Parameter 3	The name of the domain.
Probable Cause	The specified spatial reference system is in use by a user-defined domain, and it cannot be modified.

Error 1477	"The SRID %1 does not identify a geographic spatial reference system"
Constant	SLERR_NOT_GEOGRAPHIC
SAP Sybase Error Number	3147
SQL State	2FW70
SQL Code	-1477L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The spatial reference system identifier.
Probable Cause	The methods ST_Lat() and ST_Long() can only be used for geographic spatial reference systems.

Error 1478	"ST_Geometry arguments not supported by SQL function %1"
Constant	SLERR_SPATIAL_IN_BUILTIN
SAP Sybase Error Number	3148
SQL State	2FW71
SQL Code	-1478L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the SQL function.
Probable Cause	The specified SQL function does not support geometry parameters.

Error 1479	"An expression of type %1 is not union-compatible with type %2"
Constant	SLERR_NOT_UNION_COMPAT
SAP Sybase Error Number	3149
SQL State	2FW72

Error 1479	"An expression of type %1 is not union-compatible with type %2"
SQL Code	-1479L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The type of expression 1.
Parameter 2	The type of expression 2.
Probable Cause	The two types cannot be combined, for example in a set operation such as UNION or in a SQL function such as COALESCE.

Error 1480	"An internal error has occurred in the spatial library"
Constant	SLERR_INTERNAL_ERROR
SAP Sybase Error Number	3150
SQL State	2FW73
SQL Code	-1480L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	An unexpected error occurred.

Error 1482	"Curve contains nearly antipodal points %1 and %2 (near '%3')"
Constant	SLERR_NEARLY_ANTIPODAL
SAP Sybase Error Number	3152
SQL State	2FW77
SQL Code	-1482L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>

Error 1482	"Curve contains nearly antipodal points %1 and %2 (near '%3')"
Parameter 1	The first point.
Parameter 2	The second point.
Parameter 3	The value or method where the error was detected.
Probable Cause	A curve contains two points that are nearly antipodal. These define an ambiguous segment in a round-Earth spatial reference system.

Error 1483	"LineString must contain at least 2 points (near '%1')"
Constant	SLERR_LINESTRING_MIN_POINTS
SAP Sybase Error Number	3153
SQL State	2FW78
SQL Code	-1483L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The value or method where the error was detected.
Probable Cause	The linestring contains only a single point.

Error 1484	"Value %1 out of range for coordinate %2 (SRS bounds [%3, %4] exceeded by more than 50%)"
Constant	SLERR_OBJECT_OUT_OF_SRS_BOUNDS
SAP Sybase Error Number	3154
SQL State	2FW79
SQL Code	-1484L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The value is out of the defined bounds.

Error 1484	"Value %1 out of range for coordinate %2 (SRS bounds [%3, %4] exceeded by more than 50%)"
Parameter 2	The coordinate name that is out of range.
Parameter 3	The minimum value allowed by the spatial reference system.
Parameter 4	The maximum value allowed by the spatial reference system.
Probable Cause	The geometry contains a point outside of the bounds specified by the spatial reference system.

Error 1485	"Invalid polygon: ring is not closed (near '%1')"
Constant	SLERR_INVALID_POLY_RING_CLOSE
SAP Sybase Error Number	3155
SQL State	2FW80
SQL Code	-1485L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The value or method where the error was detected.
Probable Cause	One of the provided curves is not a closed ring.

Error 1486	"Invalid polygon: ring has zero area (near '%1')"
Constant	SLERR_INVALID_POLY_EMPTY_RING
SAP Sybase Error Number	3156
SQL State	2FW81
SQL Code	-1486L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The value or method where the error was detected.
Probable Cause	One of the provided rings has zero area and cannot be a valid polygon ring.

Error 1487	"Invalid polygon: curve is not a ring"
Constant	SLERR_INVALID_POLY_NON_RING
SAP Sybase Error Number	3157
SQL State	2FW82
SQL Code	-1487L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	One of the curves is not a ring and cannot be used to form a polygon.

Error 1488	"Invalid polygon: ring is larger than allowed for SRID=%1 (near '%2')"
Constant	SLERR_INVALID_POLY_RE_SIZE
SAP Sybase Error Number	3158
SQL State	2FW83
SQL Code	-1488L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The spatial reference system identifier.
Parameter 2	The value or method where the error was detected.
Probable Cause	One of the rings is larger than the specified spatial reference system supports.

Error 1489	"Position %1 is invalid (should be between %2 and %3)"
Constant	SLWARN_INVALID_POSITION
SAP Sybase Error Number	3159
SQL State	01F01
SQL Code	-1489L

Error 1489	"Position %1 is invalid (should be between %2 and %3)"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The provided position.
Parameter 2	The minimum supported position.
Parameter 3	The maximum supported position.
Probable Cause	The provided position is not valid. It should be between the specified minimum and maximum.

Messages 1490 through 1509

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1490	"Polygon ring order has been reoriented"
Constant	SLWARN_POLYGON_RING_REORIENTED
SAP Sybase Error Number	3160
SQL State	01FW1
SQL Code	-1490L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	The rings of a polygon were automatically reoriented on input. This is a notification only.

Error 1491	"CircularString with 3 points has been converted to use 5 points"
Constant	SLWARN_CIRCULARSTRING_3POINT
SAP Sybase Error Number	3161
SQL State	01FW2
SQL Code	-1491L

Error 1491	"CircularString with 3 points has been converted to use 5 points"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	A curve containing a CircularString with a 3-point circle has been converted to use a 5-point circle. This is a notification only.

Error 1492	"Could not create a text index without external prefilter library on column \"%1\"No message
Constant	TEXT_INDEX_NO_PREFILTER
SAP Sybase Error Number	2652
SQL State	WT030
SQL Code	-1492L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The name of the column for which external prefilter library is required.
Probable Cause	A text configuration object with a specified external prefilter library is required to build a text index on a binary column.

Error 1493	"Could not create a text index with external prefilter library on column \"%1\"No message
Constant	TEXT_INDEX_PREFILTER_NOT_ALLOWED
SAP Sybase Error Number	2644
SQL State	WT031
SQL Code	-1493L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1493	"Could not create a text index with external prefilter library on column \"%1\"No message
Severity Code	<i>16 on page 2</i>
Parameter 1	The name of the column for which external prefilter library is not allowed.
Probable Cause	A text configuration object without external prefilter library is required if any column in the text index is not of a binary or string data type.

Error 1494	"Geometries with CircularString not supported (near \"%1\")"
Constant	SLERR_CIRCULAR_METHOD
SAP Sybase Error Number	3162
SQL State	2FW84
SQL Code	-1494L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The method or context where the CircularString was detected.
Probable Cause	The method or operation does not support geometries with Circular-String elements.

Error 1495	"Geometries with CircularString are not supported in spatial reference system %1"
Constant	SLERR_CIRCULAR_SRS
SAP Sybase Error Number	3163
SQL State	2FW85
SQL Code	-1495L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The SRID of the round-Earth spatial reference system.

Error 1495	"Geometries with CircularString are not supported in spatial reference system %1"
Probable Cause	The method does not support geometries with CircularString elements.

Error 1496	"LOAD TABLE error: Invalid content encountered on row %1 of the data file"
Constant	LOAD_TABLE_DATA_FILE_ERROR
SAP Sybase Error Number	3164
SQL State	WL017
SQL Code	-1496L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Line number of the data file where the invalid content occurred.
Probable Cause	The LOAD TABLE statement failed because a scanning error occurred on the indicated line of the data file specified in the statement. This error can occur if a line is truncated or if delimiters are missing.

Error 1497	"The synchronization failed because MobiLink returned authentication status '%1' with value '%2'"
Constant	MOBILINK_AUTHENTICATION_FAILED
SAP Sybase Error Number	3165
SQL State	28W17
SQL Code	-1497L
ODBC 2 State	28000
ODBC 3 State	28000
Severity Code	14 on page 2
Parameter 1	The authentication status number.
Parameter 2	The authentication value number.

Error 1497	"The synchronization failed because MobiLink returned authentication status '%1' with value '%2'"
Probable Cause	MobiLink returned an authentication status to the remote database indicating failure. The status and value numbers indicate why the authentication failed. For example, the password was invalid, or a synchronization is already in progress for this remote.

Error 1498	"'%1' is an unknown property"
Constant	UNKNOWN_PROPERTY
SAP Sybase Error Number	3166
SQL State	WU001
SQL Code	-1498L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The property name (or ID).
Probable Cause	The specified property is unknown.

Error 1499	"Invalid grid size %1"
Constant	SLERR_INVALID_GRID_SIZE
SAP Sybase Error Number	3167
SQL State	2FW86
SQL Code	-1499L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The grid size that is not valid.
Probable Cause	The specified grid size cannot be used with the spatial reference system. The grid size must be selected based on the bounds of space.

Error 1500	"Invalid tolerance %1"
Constant	SLERR_INVALID_TOLERANCE
SAP Sybase Error Number	3168
SQL State	2FW87
SQL Code	-1500L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The invalid tolerance.
Probable Cause	The specified tolerance cannot be used with the spatial reference system. The tolerance must be selected based on the bounds of space.

Error 1501	"Invalid bounds for coordinate %1 (near \"BETWEEN %2 AND %3\")"
Constant	SLERR_INVALID_BOUNDS
SAP Sybase Error Number	3169
SQL State	2FW88
SQL Code	-1501L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The coordinate with the invalid bounds.
Parameter 2	The first value of the invalid bounds.
Parameter 3	The second value of the invalid bounds.
Probable Cause	The specified coordinate bounds are not valid.

Error 1502	"ST_MultiSurface contains elements with an invalid intersection (near \"%1\")"
Constant	SLERR_INVALID_MULTISURF_I

Error 1502	"ST_MultiSurface contains elements with an invalid intersection (near \"%1\")"
SAP Sybase Error Number	3170
SQL State	2FW89
SQL Code	-1502L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The method or context where the invalid ST_MultiSurface was detected.
Probable Cause	The interiors of any two ST_Surface values in an ST_MultiSurface shall not intersect. The boundaries of any two elements in an ST_MultiSurface may intersect at a finite number of points (and not, for example, in a line segment).

Error 1503	"Operation not supported for ST_GeomCollection with intersecting elements (near \"%1\")"
Constant	SLERR_GEOM_COLL_INTERSECT
SAP Sybase Error Number	3171
SQL State	2FW90
SQL Code	-1503L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The method or context where the invalid ST_GeomCollection was detected.
Probable Cause	The ST_GeomCollection contains elements that intersect in a way that is not valid for an ST_MultiSurface. The operation is not supported for this kind of geometry.

Error 1504	"Error from external library: -%1: %2"
Constant	TEXT_USER_SPECIFIED_ERROR
SAP Sybase Error Number	2642
SQL State	WT032
SQL Code	-1504L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Error number specified by the external library
Parameter 2	Error message specified by the external library
Probable Cause	The external library used by the text index has reported the specified error.

Error 1505	"Mirror server \"%1\" defined with type COPY does not include a parent definition"
Constant	COPY_SERVER_NEEDS_PARENT
SAP Sybase Error Number	3172
SQL State	42WE6
SQL Code	-1505L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The mirror server name
Probable Cause	In a CREATE MIRROR SERVER statement for a server with type COPY, a parent server is not defined.

Error 1506	"Unknown collation \"%1\""
Constant	UNKNOWN_COLLATION
SAP Sybase Error Number	3174
SQL State	WC018

Error 1506	"Unknown collation '%1'"
SQL Code	-1506L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name that is not a database collation.
Probable Cause	The specified collation is unknown. Ensure the name is spelled correctly.

Error 1507	"The materialized view cannot be changed to immediate because the ON conditions refer to tables which are not in the null-supplying and preserved sides of the OUTER JOINS."
Constant	UPDATABLE_MATVIEW_OUTERREFERENCE_ON_CONDITION
SAP Sybase Error Number	3175
SQL State	42WE7
SQL Code	-1507L
ODBC 2 State	42000
ODBC 3 State	ERROR
Severity Code	15 on page 2
Probable Cause	You attempted to change the refresh type to immediate for a materialized view whose definition contains an illegal ON condition.

Error 1508	"The materialized view cannot be changed to immediate because at least one non-nullable column from any null-supplying side of an OUTER JOIN must exist in the SELECT list."
Constant	UPDATABLE_MATVIEW_ISNOTNULL
SAP Sybase Error Number	3176
SQL State	42WE8
SQL Code	-1508L

Error 1508	"The materialized view cannot be changed to immediate because at least one non-nullable column from any null-supplying side of an OUTER JOIN must exist in the SELECT list."
ODBC 2 State	42000
ODBC 3 State	ERROR
Severity Code	15 on page 2
Probable Cause	You attempted to change the refresh type to immediate for a materialized view whose SELECT list doesn't contain at least one non-nullable column for any null-supplying side of an OUTER JOIN.

Error 1509	"The materialized view cannot be changed to immediate because the primary key columns of any table in the preserved side of an OUTER JOIN must exist in the SELECT list."
Constant	UPDATABLE_MATVIEW_PK
SAP Sybase Error Number	3177
SQL State	42WE9
SQL Code	-1509L
ODBC 2 State	42000
ODBC 3 State	ERROR
Severity Code	15 on page 2
Probable Cause	You attempted to change the refresh type to immediate for a materialized view whose SELECT list doesn't contain the primary key columns of any table in the preserved side of an OUTER JOIN.

Messages 1510 through 1529

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1510	"Cannot specify range that excludes next value for sequence %1"
Constant	INVALID_ALTER_SEQUENCE

Error 1510	"Cannot specify range that excludes next value for sequence %1"
SAP Sybase Error Number	3178
SQL State	52W54
SQL Code	-1510L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	<i>16 on page 2</i>
Parameter 1	Name of the sequence.
Probable Cause	You attempted to modify either the MINVAL or MAXVAL boundary of a sequence to a value that would make the next invocation of the nextval expression for the sequence invalid. If you want to change the range boundaries to these values, you must also specify a RESTART WITH clause and supply a value within the new range.

Error 1511	"Text indexes are not allowed across server types."
Constant	TEXT_NOT_ALLOWED_ACROSS_SERVERS
SAP Sybase Error Number	2596
SQL State	WT033
SQL Code	-1511L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	Text indexes are not allowed across server types if the query is processed in full-passthrough mode.

Error 1512	"Text index with external prefilter cannot contain both binary and string columns"
Constant	TEXT_INDEX_MIXED_COLUMNS
SAP Sybase Error Number	2561

Error 1512	"Text index with external prefilter cannot contain both binary and string columns"
SQL State	WT034
SQL Code	-1512L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	One or more, but not all, of the columns specified for the text index is of type binary, and the text configuration object has a prefilter library specified. Text indexes using a prefilter library can contain either binary columns or string data type columns, but not both.

Error 1513	"Sysam License Manager initialization failed."
Constant	IQ_LICENSE_INITIALIZATION_FAILURE
SAP Sybase Error Number	2547
SQL State	0A005
SQL Code	-1513L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	Sysam License Manager initialization failed.

Error 1514	"Failed to checkout a SAP Sybase IQ core license."
Constant	IQ_CORE_LICENSE_CHECKOUT_FAILURE
SAP Sybase Error Number	2546
SQL State	0A006
SQL Code	-1514L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2

Error 1514	"Failed to checkout a SAP Sybase IQ core license."
Probable Cause	Sysam License Manager was unable to obtain a valid IQ_CORE license.

Error 1515	"Support for spatial is not available for this CPU."
Constant	SLERR_CPU_NEED_SSE
SAP Sybase Error Number	3179
SQL State	2FW91
SQL Code	-1515L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	Spatial data support for 32-bit Windows and 32-bit Linux requires a CPU that supports the SSE2 instructions.

Error 1516	"The intermediate point (%3) of the ST_CircularString segment between %1 and %2 is collinear with but not between the start and end points."
Constant	SLERR_CIRC_COLLINEAR_MIDPOINT
SAP Sybase Error Number	3180
SQL State	2FF72
SQL Code	-1516L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The start point of the ST_CircularString segment
Parameter 2	The end point of the ST_CircularString segment
Parameter 3	The specified intermediate point of the ST_CircularString segment

Error 1516	"The intermediate point (%3) of the ST_CircularString segment between %1 and %2 is collinear with but not between the start and end points."
Probable Cause	When the intermediate point of a ST_CircularString segment is collinear with the start and end point the result is interpreted as a straight line between the start and the end point. In this case, the intermediate point must be located on the line segment between the start and end point.

Error 1517	"Logical Server \"%1\" not found"
Constant	LOGICAL_SERVER_NOT_FOUND
SAP Sybase Error Number	2545
SQL State	WQ001
SQL Code	-1517L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the logical server.
Probable Cause	The named logical server was not found in the database.

Error 1518	"Logical Server Policy \"%1\" does not allow coordinator membership in logical servers."
Constant	LS_COORD_MEMBERSHIP_NOT_ALLOWED
SAP Sybase Error Number	2543
SQL State	WQ002
SQL Code	-1518L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the logical server policy.
Probable Cause	Logical server policy does not allow coordinator as a member of logical server.

Error 1519	"Cannot determine the logical server context due to overlapping logical server memberships for login policy \"%1\"."
Constant	LS_MEMBERSHIP_OVERLAP_NOT_ALLOWED
SAP Sybase Error Number	2541
SQL State	WQ003
SQL Code	-1519L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the login policy.
Probable Cause	Cannot determine the logical server context for named login policy. Specify the logical server in the connection string.

Error 1520	"Cannot recreate an already existing logical server membership."
Constant	LS_MEMBERSHIP_ALREADY_EXISTS
SAP Sybase Error Number	2539
SQL State	WQ004
SQL Code	-1520L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	Multiplex server which is to be added as a member is already a member of logical server.

Error 1521	"Cannot drop a non-existing logical server membership."
Constant	LS_MEMBERSHIP_NOT_FOUND
SAP Sybase Error Number	2537
SQL State	WQ005
SQL Code	-1521L

Error 1521	"Cannot drop a non-existing logical server membership."
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Probable Cause	Multiplex server membership about to be dropped was not found.

Error 1522	"Database needs to be upgraded to support the use of external libraries with text indexes."
Constant	TEXT_EXT_UPGRADE_REQUIRED
SAP Sybase Error Number	2530
SQL State	WT035
SQL Code	-1522L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Probable Cause	The current database does not have catalog support for prefilter and term breaker external libraries. To use this feature, upgrade your database to the most recent version.

Error 1523	"Cannot reassign logical server '%1' to login policy '%2'."
Constant	LS_LP_ASSIGNMENT_EXISTS
SAP Sybase Error Number	2507
SQL State	WQ006
SQL Code	-1523L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The name of the logical server.
Parameter 2	The name of the login policy.

Error 1523	"Cannot reassign logical server '%1' to login policy '%2'."
Probable Cause	Logical Server - Login Policy assignment already exists.

Error 1524	"Cannot drop a non-existing assignment between logical server '%1' and login policy '%2'."
Constant	LS_LP_NON_EXISTING_ASSIGNMENT
SAP Sybase Error Number	2508
SQL State	WQ007
SQL Code	-1524L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the logical server.
Parameter 2	The name of the login policy.
Probable Cause	Logical Server - Login Policy assignment does not exist.

Error 1525	"Cannot perform specified operation, number of administrators for role '%1' falls below min_role_admins option value"
Constant	MIN_ROLE_ADMIN_VIOLATION
SAP Sybase Error Number	3181
SQL State	55W36
SQL Code	-1525L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the role that violates minimum number of administrators condition

Error 1525	"Cannot perform specified operation, number of administrators for role '%1' falls below min_role_admins option value"
Probable Cause	Specified operation cannot be performed because it will make the number of administrators for the specified role go below the threshold value set through database option min_role_admins.

Error 1526	"Text index %1 cannot be used with text procedure %2"
Constant	TEXT_INVALID_INDEX_FOR_PROC
SAP Sybase Error Number	2010
SQL State	WT036
SQL Code	-1526L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the text index.
Parameter 2	The name of the procedure for which the specified index is invalid.
Probable Cause	The specified text procedure cannot be used with the text index. The text procedure charset has to correspond to the charset of the text index it is accessing.

Error 1527	"Task '%1' is not allowed"
Constant	SYSPRIV_CREATION_NOT_ALLOWED
SAP Sybase Error Number	3182
SQL State	28W18
SQL Code	-1527L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the internal task that was provided by the user.

Error 1527	"Task '%1' is not allowed"
Probable Cause	Creation of system privilege is an internal task, allowed only during database creation or upgrade.

Error 1528	"No more role grant permitted"
Constant	ROLE_GRANT_ID_NOT_AVAILABLE
SAP Sybase Error Number	3183
SQL State	28W19
SQL Code	-1528L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	Maximum limit for role grants has been reached. No more role grants are permitted. Remove some role grants and try again.

Error 1529	"Outer reference not permitted in DML derived table"
Constant	SELECT_DML_OUTER_REFERENCE
SAP Sybase Error Number	3184
SQL State	42U09
SQL Code	-1529L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	Outer references are not permitted in derived tables based on INSERT, UPDATE, DELETE, or MERGE statements. These derived tables may only appear in subqueries that are uncorrelated.

Messages 1530 through 1549

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1530	"Format '%1' is not supported in the UNLOAD statement"
Constant	UNSUPPORTED_UNLOAD_FORMAT
SAP Sybase Error Number	3185
SQL State	WL018
SQL Code	-1530L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>19 on page 2</i>
Parameter 1	The specified format.
Probable Cause	An unsupported file format was specified for the UNLOAD statement.

Error 1531	"Geometry expressions cannot be used in the ORDER BY specification (near '%1')"
Constant	SLERR_GEOM_ORDER_BY
SAP Sybase Error Number	3186
SQL State	2FW92
SQL Code	-1531L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The geometry expression.
Probable Cause	Geometry expressions cannot be used in the ORDER BY clause. The ST_LinearHash() method may be used in the ORDER BY specification to order geometry values using the same rules used for spatial indexes, or a conversion method such as ST_AsText() may be used to order the rows by their string representation.

Error 1532	"Failed to transform point %1 (error %2)"
Constant	SLERR_TRANSFORM_POINT_FAIL
SAP Sybase Error Number	3187
SQL State	2FF17
SQL Code	-1532L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The point that could not be transformed.
Parameter 2	The error code from the projection library.
Probable Cause	An error occurred when performing a transform from one spatial reference system to another. This error may occur if a point in the first geometry is outside of the bounds for the transform definition. The error may also be reported for particular transform definitions. The integer error code from the transform library may be used to diagnose the transform definition.

Error 1533	"Logical server policy \"%1\" not found"
Constant	LS_POLICY_NOT_FOUND
SAP Sybase Error Number	2445
SQL State	WQ008
SQL Code	-1533L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the logical server policy.
Probable Cause	The named logical server policy was not found in the database.

Error 1534	"Logical server operations not allowed on a simplex database."
Constant	LS_OPS_DISALLOWED_ON_SIMPLEX

Error 1534	"Logical server operations not allowed on a simplex database."
SAP Sybase Error Number	2443
SQL State	WQ009
SQL Code	-1534L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	Logical server operations are disallowed on a simplex database.

Error 1535	"System Privileges and Roles feature is not supported in this database"
Constant	ROLES_NOT_SUPPORTED
SAP Sybase Error Number	3188
SQL State	0AW27
SQL Code	-1535L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	The current database is an older database and does not have catalog support for System Privileges and Roles feature. To use this feature, upgrade your database to the most recent version.

Error 1536	"Invalid user ID or role name '%1' specified"
Constant	INVALID_USER_ROLE_NAME
SAP Sybase Error Number	3189
SQL State	28000
SQL Code	-1536L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1536	"Invalid user ID or role name '%1' specified"
Severity Code	<i>14</i> on page 2
Parameter 1	Name of the invalid user or role that was specified.
Probable Cause	You supplied an invalid name for a user or role.

Error 1537	"Role \"%1\" already exists"
Constant	ROLE_ALREADY_EXISTS
SAP Sybase Error Number	3190
SQL State	28000
SQL Code	-1537L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The name of the role.
Probable Cause	An attempt was made to create a role that already exists in the database.

Error 1538	"User or Role ID '%1' does not exist"
Constant	UNKNOWN_USER_ROLE_ID
SAP Sybase Error Number	3191
SQL State	28000
SQL Code	-1538L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	Name of the user or role that could not be found.
Probable Cause	You used a user or role ID that does not exist.

Error 1539	"Use of WITH NO SYSTEM PRIVILEGE INHERITANCE option is not allowed with %1"
Constant	INVALID_ROLE_GRANT_OPTION
SAP Sybase Error Number	3192
SQL State	28000
SQL Code	-1539L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	The name of the role.
Probable Cause	WITH NO SYSTEM PRIVILEGE INHERITANCE option can be specified only with user defined roles corresponding to legacy non-inheritable authorities.

Error 1540	"Operation would cause a role cycle"
Constant	ROLE_CYCLE
SAP Sybase Error Number	3193
SQL State	28000
SQL Code	-1540L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	You attempted to grant role to a grantee that would result in a grantee belonging to itself. Role membership may be direct or indirect.

Error 1541	"Specified System Privilege '%1' is Invalid"
Constant	INVALID_SYSTEM_PRIVILEGE
SAP Sybase Error Number	3194
SQL State	28000
SQL Code	-1541L

Error 1541	"Specified System Privilege '%1' is Invalid"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	The name of the system privilege.
Probable Cause	System Privilege specified does not exist in the database.

Error 1542	"Invalid logical server combination for ADD or SET clause."
Constant	LS_INVALID_COMBINATION_FOR_ADD_SET
SAP Sybase Error Number	2442
SQL State	WQ010
SQL Code	-1542L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	The specified logical server combination for ADD or SET clause of ALTER LOGIN POLICY is invalid. SERVER and NONE cannot be specified with ADD clause. SERVER and NONE cannot be specified with any other logical server.

Error 1543	"Logical server configuration of the user's login policy does not allow access to the current multiplex server."
Constant	CONNECTION_DISALLOWED_BY_LOGIN_POLICY_LS_CONFIG
SAP Sybase Error Number	2428
SQL State	WQ011
SQL Code	-1543L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>

Error 1543	"Logical server configuration of the user's login policy does not allow access to the current multiplex server."
Probable Cause	Logical server configuration of the user's login policy does not allow access to the current multiplex server. You may need to change logical server configuration of user's login policy to allow access to the current multiplex server.

Error 1544	"Login disallowed. User does not have sufficient authority to access SERVER logical server."
Constant	CONNECTION_DISALLOWED_TO_SERVER_LS
SAP Sybase Error Number	2423
SQL State	WQ012
SQL Code	-1544L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	Accessing SERVER logical server requires either DBA or MULTIPLEX ADMIN authority.

Error 1545	"Cannot create logical server named '%1'. Choose another name for logical server."
Constant	INVALID_LS_NAME
SAP Sybase Error Number	2422
SQL State	WQ013
SQL Code	-1545L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of logical server.
Probable Cause	Logical server names ALL, NONE, SERVER, OPEN, DEFAULT and COORDINATOR are reserved for the current or future releases.

Error 1546	"Cannot drop Multiplex server '%1' as it is part of a Logical Server. Use the \"WITH DROP MEMBERSHIP\" clause."
Constant	IQ_MPX_SRV_IS_LS_MEMBER
SAP Sybase Error Number	2387
SQL State	WQ014
SQL Code	-1546L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of multiplex server.
Probable Cause	If an MPX server is part of a Logical Server then the DROP MPX command should have WITH MEMBERSHIP clause to drop it.

Error 1547	"Cannot drop Multiplex server '%1' without dropping all the logical servers as it will convert the Multiplex to Simplex. Use the \"WITH DROP LOGICAL SERVER\" clause."
Constant	IQ_MPX_SRV_IS_LAST_SEC_MEMBER
SAP Sybase Error Number	2371
SQL State	WQ015
SQL Code	-1547L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of multiplex server.
Probable Cause	If dropping the secondary server will result in conversion from MPX to SPX then all the user created logical servers should be dropped.

Error 1548	"Cannot drop Multiplex server '%1'. This is not the last secondary server. Remove the \"WITH DROP LOGICAL SERVER\" clause."
Constant	IQ_MPX_SRV_IS_NOT_LAST_SEC_MEMBER
SAP Sybase Error Number	2370
SQL State	WQ016
SQL Code	-1548L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of multiplex server.
Probable Cause	WITH DROP LOGICAL SERVER clause should be used ONLY when dropping the last secondary Server.

Error 1549	"Cannot set the '%1' option as Login Policy option '%2' is set to off."
Constant	LS_LP_MODIFY_OPT_NOT_ALLOWED
SAP Sybase Error Number	2369
SQL State	WQ017
SQL Code	-1549L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the temporary option
Parameter 2	The name of the Login Policy Option.
Probable Cause	If an option of the login policy is set to off then user cannot set the temporary option which is directly depending on it. For example, if the login policy option DQP_ENABLED is set to Off, then the temporary option DQP_ENABLED cannot be set to On.

Messages 1550 through 1569

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1550	"Overriding ROOT login policy options for logical servers is not allowed."
Constant	LS_ROOT_LP_OVERRIDE_NOT_ALLOWED
SAP Sybase Error Number	2368
SQL State	WQ018
SQL Code	-1550L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	A user cannot override login policy options of ROOT login policy for logical servers.

Error 1551	"Login redirection is required to complete the connection, but it is not supported by the client"
Constant	LOGIN_REDIRECTION_REQUIRED
SAP Sybase Error Number	3195
SQL State	08WA6
SQL Code	-1551L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	<i>16 on page 2</i>
Probable Cause	The connection needs to be redirected to another server, but the version of the client library does not support login redirection. You must upgrade the client library to use login redirection. Alternatively, you can connect to a different server or change the logical server configuration.

Errors and Warnings

Error 1552	"Invalid text index type for the materialized view"
Constant	TEXT_MV_INVALID_COMBO
SAP Sybase Error Number	3196
SQL State	WT037
SQL Code	-1552L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	Text index with the specified refresh type cannot be created on the materialized view. Only IMMEDIATE REFRESH text indexes are allowed on materialized views.

Error 1553	"Cannot perform specified operation, set user condition violated"
Constant	SET_USER_VIOLATION
SAP Sybase Error Number	3197
SQL State	55W37
SQL Code	-1553L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	Specified operation cannot be performed because it will invalidate the on going SET USER statements in the database.

Error 1554	"Specified LDAP server '%1' is not found"
Constant	UNKNOWN_LDAP_SERVER
SAP Sybase Error Number	3198
SQL State	28000
SQL Code	-1554L
ODBC 2 State	ERROR

Error 1554	"Specified LDAP server '%1' is not found"
ODBC 3 State	ERROR
Severity Code	11 on page 2
Parameter 1	The name of the LDAP server.
Probable Cause	The LDAP server specified does not exist in the database.

Error 1555	"Statement not allowed on text index for a materialized view"
Constant	TEXT_MV_TIND_NOT_ALLOWED
SAP Sybase Error Number	3199
SQL State	WT038
SQL Code	-1555L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You cannot use REFRESH TEXT INDEX or TRUNCATE TEXT INDEX on a text index that is created for a materialized view. You cannot alter the text index to use a different refresh type.

Error 1556	"External environment failed to start and establish a connection within the %1 second timeout"
Constant	EXTENV_START_TIMED_OUT
SAP Sybase Error Number	3200
SQL State	WP017
SQL Code	-1556L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The amount of time in seconds the server will wait for the external environment to start and establish a connection.

Error 1556	"External environment failed to start and establish a connection within the %1 second timeout"
Probable Cause	The External Environment took too long to start up and establish a connection with the server. The problem may be due to the system being over stressed or incorrectly configured.

Error 1557	"External environment cannot be started during database startup"
Constant	EXTENV_START_ON_STARTUP
SAP Sybase Error Number	3201
SQL State	WP018
SQL Code	-1557L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	An external environment cannot be started while a database is starting up. Wait for the database startup to complete before attempting to start an external environment.

Error 1558	"Specified user '%1' is a role"
Constant	CAN_NOT_DROP_ROLE
SAP Sybase Error Number	3202
SQL State	28000
SQL Code	-1558L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Name of the user being dropped.
Probable Cause	You attempted to drop a role. Use DROP ROLE statement.

Error 1559	"Specified role '%1' is not a user extended as role"
Constant	NOT_AN_EXTENDED_USER
SAP Sybase Error Number	3203
SQL State	28000
SQL Code	-1559L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Name of the role being dropped.
Probable Cause	The role name provided is not a user extended as role. Use of FROM USER clause is not allowed in such cases.

Error 1560	"Specified role '%1' is a user extended as role"
Constant	AN_EXTENDED_USER
SAP Sybase Error Number	3204
SQL State	28000
SQL Code	-1560L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Name of the role being dropped.
Probable Cause	Specified role is a user extended as role but FROM USER clause is not specified in DROP ROLE command.

Error 1561	"Use of WITH DROP OBJECTS is not allowed with '%1'"
Constant	WITH_DROP_OBJECTS_NOT_ALLOWED
SAP Sybase Error Number	3205
SQL State	28000
SQL Code	-1561L

Error 1561	"Use of WITH DROP OBJECTS is not allowed with '%1'"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	Name of the role being dropped.
Probable Cause	Use of WITH DROP OBJECTS is not allowed with user extended as role.

Error 1562	"The role '%1' was not dropped because it is granted to other users or roles. Use the 'WITH REVOKE' option to drop it."
Constant	CONTAINS_PRIV_GRANTS
SAP Sybase Error Number	3206
SQL State	28000
SQL Code	-1562L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	Name of the role being dropped.
Probable Cause	The role being dropped has been granted to other users or roles with WITH NO ADMIN OPTION or with WITH ADMIN OPTION. A role can be dropped when either all of its grants are with WITH ADMIN ONLY OPTION or WITH REVOKE option is specified in DROP ROLE command. Either revoke all such grants or use WITH REVOKE option for DROP ROLE.

Error 1563	"Cannot drop a role that owns sequences in runtime server"
Constant	USER_OWNS_SEQUENCES
SAP Sybase Error Number	3207
SQL State	55W38
SQL Code	-1563L
ODBC 2 State	42000

Error 1563	"Cannot drop a role that owns sequences in runtime server"
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	You attempted to drop a role that owns sequences while using the runtime server. This operation would result in dropping sequences. The runtime server cannot drop sequences.

Error 1564	"Cannot drop a role that owns events in runtime server"
Constant	USER_OWNS_EVENTS
SAP Sybase Error Number	3208
SQL State	55W39
SQL Code	-1564L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	You attempted to drop a role that owns events while using the runtime server. This operation would result in dropping events. The runtime server cannot drop events.

Error 1565	"Cannot drop a role that owns web services in runtime server"
Constant	USER_OWNS_WEB_SERVICES
SAP Sybase Error Number	3209
SQL State	55W40
SQL Code	-1565L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	You attempted to drop a role that owns web services while using the runtime server. This operation would result in dropping web services. The runtime server cannot drop web services.

Error 1566	"Cannot drop a role that owns external environment objects in runtime server"
Constant	USER_OWNS_EXTENENVOBJECTS
SAP Sybase Error Number	3210
SQL State	55W41
SQL Code	-1566L
ODBC 2 State	42000
ODBC 3 State	42000
Severity Code	16 on page 2
Probable Cause	You attempted to drop a role that owns external environment objects while using the runtime server. This operation would result in dropping external environment objects. The runtime server cannot drop external environment objects.

Error 1567	"External environment cannot be started, external process terminated on start up"
Constant	EXTENV_PID_NOT_FOUND
SAP Sybase Error Number	3211
SQL State	WP019
SQL Code	-1567L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The request to start an external environment could not be completed due to the fact that the external process terminated on start up. This problem is usually due to a client configuration issue.

Error 1568	"Unable to generate a logical server ID."
Constant	LS_MAX_ID_LIMIT_REACHED
SAP Sybase Error Number	2365

Error 1568	"Unable to generate a logical server ID."
SQL State	WQ019
SQL Code	-1568L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	Last generated logical server ID reached maximum limit. The database catalog needs to be rebuilt.

Error 1569	"LDAP Server \"%1\" already exists"
Constant	LDAPSERVER_ALREADY_EXISTS
SAP Sybase Error Number	3212
SQL State	WW202
SQL Code	-1569L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the LDAP Server.
Probable Cause	An attempt was made to create an LDAP server that already exists in the database.

Messages 1570 through 1589

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1570	"Attempt to allocate memory for LDAP server \"%1\" failed."
Constant	LDAPSERVER_ALLOC_FAILED
SAP Sybase Error Number	3213
SQL State	WW203
SQL Code	-1570L

Error 1570	"Attempt to allocate memory for LDAP server \"%1\" failed."
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the LDAP Server.
Probable Cause	An attempt to allocate memory for an LDAP Server class object failed.

Error 1571	"The attempt to drop LDAP server \"%1\" failed, suspend the server to drop it."
Constant	INVALID_STATE_CHANGE
SAP Sybase Error Number	3214
SQL State	WW204
SQL Code	-1571L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the LDAP Server.
Probable Cause	An attempt to drop an LDAP Server failed because it was in the READY or ACTIVE state. Use WITH SUSPEND to change state before dropping server.

Error 1572	"LDAP User Authentication feature is not supported in this database"
Constant	LDAPUA_NOT_SUPPORTED
SAP Sybase Error Number	3215
SQL State	WW205
SQL Code	-1572L
ODBC 2 State	ERROR

Error 1572	"LDAP User Authentication feature is not supported in this database"
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Probable Cause	The current database is an older database and does not have catalog support for LDAP User Authentication feature. To use this feature, upgrade your database to the most recent version.

Error 1573	"MIRROR server class is not supported for SAP Sybase IQ databases"
Constant	OMNI_NO_MIRROR_FOR_IQ
SAP Sybase Error Number	3216
SQL State	WO029
SQL Code	-1573L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Probable Cause	You attempted to create a remote data access server of type MIRROR while connected to an SAP Sybase IQ database. The MIRROR server class is not supported for SAP Sybase IQ databases.

Error 1574	"You must upgrade your database in order to use the MIRROR server class"
Constant	OMNI_MIRROR_NEEDS_UPGRADE
SAP Sybase Error Number	3217
SQL State	WO030
SQL Code	-1574L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2

Error 1574	"You must upgrade your database in order to use the MIRROR server class"
Probable Cause	You attempted to create a remote data access server of type mirror while connected to a database that was created with older software. You must upgrade your database in order to make use of the mirror server class.
Error 1575	"Database upgrade not possible; the name or ID of new IQ_SHARED_TEMP dbspace is already in use."
Constant	IQ_SHTEMP_DBSPACE_CONFLICT
SAP Sybase Error Number	2364
SQL State	WQ020
SQL Code	-1575L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	An attempt to upgrade a database failed. Retry upgrade of the database when no existing dbspace is using the name or ID of the IQ_SHARED_TEMP dbspace.
Error 1576	"LDAP server \"%1\" is in use by login policy \"%2\"."
Constant	LDAPSERVER_IN_USE
SAP Sybase Error Number	3218
SQL State	WW206
SQL Code	-1576L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the LDAP server.
Parameter 2	The name of the login policy.

Error 1576	"LDAP server \"%1\" is in use by login policy \"%2\"."
Probable Cause	The named login policy references the LDAP server. The login policy must be changed to avoid referencing the LDAP server before the LDAP server can be dropped. Otherwise, use DROP LDAP SERVER <server name> WITH DROP ALL REFERENCES to remove any references in login policies to the LDAP server.
Error 1577	"Invalid error raised by user-defined function: (%1) %2."
Constant	EMSG_UDF_RAISED_INVALID_ERROR
SAP Sybase Error Number	3219
SQL State	QFA67
SQL Code	-1577L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Invalid error code used by UDF.
Parameter 2	Error message provided by UDF to accompany UDF SQLCODE.
Probable Cause	An error was raised by a user-defined function that is outside reserved range.
Error 1578	"Table parameterized functions are not allowed across server types."
Constant	TPF_NOT_ALLOWED_ACROSS_SERVERS
SAP Sybase Error Number	3220
SQL State	WO009
SQL Code	-1578L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	Table parameterized functions are not allowed across server types if a query is not processed in full-passthrough mode.

Error 1579	"External procedures or functions are not allowed across server types."
Constant	PROC_NOT_ALLOWED_ACROSS_SERVERS
SAP Sybase Error Number	3221
SQL State	WO031
SQL Code	-1579L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	External procedure or function calls are not allowed across server types if the query is not processed in full-passthrough mode.

Error 1580	"Failed to load the MobiLink client support libraries."
Constant	COULD_NOT_LOAD_SYNC_LIBRARY
SAP Sybase Error Number	3222
SQL State	WW207
SQL Code	-1580L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>19 on page 2</i>
Probable Cause	To use the SYNCHRONIZE command, a MobiLink client must be installed on the same computer where the database server is running.

Error 1581	"Database name must be specified when connecting to a cloud database server"
Constant	NO_DEFAULT_DATABASE
SAP Sybase Error Number	3223
SQL State	08WA7
SQL Code	-1581L
ODBC 2 State	08001

Error 1581	"Database name must be specified when connecting to a cloud database server"
ODBC 3 State	08001
Severity Code	<i>16</i> on page 2
Probable Cause	When connecting to a cloud database server, a database name must be specified by the connection string. Cloud database servers do not have a default database.

Error 1582	"Server name can only be specified when connecting to a cloud database server with NODETYPE=DIRECT"
Constant	SERVER_NAME_NOT_ALLOWED
SAP Sybase Error Number	3224
SQL State	08WA8
SQL Code	-1582L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	<i>16</i> on page 2
Probable Cause	When connecting to a cloud database server, specifying a server name on the connection string is only allowed for NODETYPE=DIRECT. When using other NODETYPE values to connect to a cloud database server, specifying the server name is not allowed. Typically, for connections to a cloud database server the HOST connection parameter or HOST protocol option is used to specify the address of one or more cloud database servers.

Error 1583	"Cannot upgrade the database. The database can be upgraded only after starting the coordinator in single node mode."
Constant	IQ_MPX_MUST_BE_SINGLE_NODE
SAP Sybase Error Number	3225
SQL State	WQ021
SQL Code	-1583L
ODBC 2 State	ERROR

Error 1583	"Cannot upgrade the database. The database can be upgraded only after starting the coordinator in single node mode."
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	In order to run ALTER DATABASE UPGRADE on the database, the coordinator must be started in single node mode using the '-iqmpx_sn 1' server startup option.

Error 1584	"Unable to load the dbrsakup shared object"
Constant	RSA_LOAD_FAILED
SAP Sybase Error Number	3226
SQL State	08WA9
SQL Code	-1584L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	16 on page 2
Probable Cause	The server was unable to load the dbrsakup DLL on Windows platforms or the libdbrsakup shared object on Unix platforms.

Error 1585	"Invalid tool name or admin user for generating security token"
Constant	INVALID_TOOL_NAME_OR_ADMIN_USER
SAP Sybase Error Number	3227
SQL State	08WB1
SQL Code	-1585L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	16 on page 2
Probable Cause	The tool name or admin user supplied is invalid for generating a security token.

Error 1586	"Error modifying refresh type for text index \"%1\" on materialized view \"%2\"No message
Constant	TEXT_INDEX_MV_ALTER_ERROR
SAP Sybase Error Number	3228
SQL State	WT039
SQL Code	-1586L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the text index.
Parameter 2	The name of the materialized view.
Probable Cause	Internal error encountered while changing the refresh type of the text index dependent on the materialized view.

Error 1587	"Storing certificates is not supported for this database"
Constant	CERTIFICATES_NOT_SUPPORTED
SAP Sybase Error Number	3229
SQL State	55W42
SQL Code	-1587L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The current database does not have catalog support for certificates. To use this feature, upgrade your database to the most recent version.

Error 1588	"The specified certificate is not valid"
Constant	INVALID_CERTIFICATE
SAP Sybase Error Number	3230
SQL State	55W43
SQL Code	-1588L

Error 1588	"The specified certificate is not valid"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Probable Cause	The certificate value does not represent a valid certificate.

Error 1589	"Certificate '%1' not found"
Constant	CERTIFICATE_NOT_FOUND
SAP Sybase Error Number	3231
SQL State	55W44
SQL Code	-1589L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	Name of the certificate that could not be found
Probable Cause	You misspelled the name of a certificate, or the certificate does not exist.

Messages 1590 through 1609

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1590	"You cannot use a security token when making remote connections"
Constant	INVALID_USE_OF_SECURITY_TOKEN
SAP Sybase Error Number	3232
SQL State	WO032
SQL Code	-1590L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2

Error 1590	"You cannot use a security token when making remote connections"
Probable Cause	A security token cannot be used to make remote data access connections.

Error 1591	"Invalid use of BEFORE operator in text query."
Constant	TEXT_INVALID_BEFORE
SAP Sybase Error Number	3233
SQL State	WT040
SQL Code	-1591L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	15 on page 2
Probable Cause	Only terms and prefixes are allowed as arguments to a BEFORE operator.

Error 1592	"Text indexes on materialized views are not supported for this database."
Constant	TEXT_MV_UPGRADE_REQUIRED
SAP Sybase Error Number	3234
SQL State	WT041
SQL Code	-1592L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The current database does not have catalog support for text indexes on materialized views. To use this feature, upgrade your database to the most recent version.

Error 1593	"Unable to copy file %1 to destination %2"
Constant	UNABLE_TO_COPY_DB_FILE_INTO_CLOUD

Error 1593	"Unable to copy file %1 to destination %2"
SAP Sybase Error Number	3235
SQL State	08WB2
SQL Code	-1593L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	<i>16 on page 2</i>
Parameter 1	The file name of the file on the client computer
Parameter 2	The file name of the destination within the cloud
Probable Cause	The client database file could not be copied to the requested cloud destination.

Error 1594	"LDAP server definition of \"%1\" is incomplete. A search URL, access distinguished name, password, and authentication URL are required."
Constant	LDAPSERVER_INCOMPLETE_DEF
SAP Sybase Error Number	3236
SQL State	WW208
SQL Code	-1594L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The name of the LDAP server.
Probable Cause	The named LDAP server is missing one or more of the values required to search for a user's distinguished name or authenticate a user. Use ALTER LDAP SERVER <server name> to specify any missing values.

Error 1595	"Column '%1' not found in variable '%2'"
Constant	COLUMN_NOT_FOUND_IN_VARIABLE

Error 1595	"Column '%1' not found in variable '%2'"
SAP Sybase Error Number	3237
SQL State	52006
SQL Code	-1595L
ODBC 2 State	S0002
ODBC 3 State	42S22
Severity Code	11 on page 2
Parameter 1	Name of the column that could not be found.
Parameter 2	Name of the row variable that was supposed to contain the column.
Probable Cause	You misspelled the name of a column or variable, or the variable has a different schema than you expect.

Error 1596	"Database contains users with 'SYS_' prefix and '_ROLE' suffix."
Constant	INVALID_USER_NAME
SAP Sybase Error Number	3238
SQL State	08WB3
SQL Code	-1596L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The database to be upgraded contains users with 'SYS_' prefix and '_ROLE' suffix. Drop or migrate these users before upgrading the database.

Error 1597	"The transaction may not be committed because the primary server lost quorum"
Constant	LOST_QUORUM_ON_COMMIT
SAP Sybase Error Number	2363

Error 1597	"The transaction may not be committed because the primary server lost quorum"
SQL State	WW166
SQL Code	-1597L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You attempted to commit a transaction on a primary server that just lost quorum with the partner and arbiter servers. The transaction may or may not have been committed. The partner servers will attempt to determine which server will become the new primary server.

Error 1598	"Array element error: array index '%1' is out of range"
Constant	INVALID_ARRAY_INDEX
SAP Sybase Error Number	3239
SQL State	2202E
SQL Code	-1598L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Value of the array index expression
Probable Cause	You tried to access an array element with an index outside the declared size of the array. For an array of size N, valid array elements are numbered 1 through N.

Error 1599	"Invalid use of collection type"
Constant	INVALID_USE_OF_COLLECTION
SAP Sybase Error Number	3240
SQL State	WW210
SQL Code	-1599L

Error 1599	"Invalid use of collection type"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	You tried to use an ARRAY or ROW type in an unsupported context. You cannot store these values in tables or read them directly from client interfaces such as ODBC, ESQL, and JDBC. You must extract the individual values you are interested in.

Error 1600	"The bind to URL '%1' failed. The most recently reported LDAP API error is: '%2'"
Constant	LDAPUA_BINDFAIL
SAP Sybase Error Number	3241
SQL State	WW211
SQL Code	-1600L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The LDAP URL used with bind().
Parameter 2	The LDAP API error message.
Probable Cause	The message is reported from the LDAP API client with context from the LDAP User Authentication methods. An LDAP administrator or Sybase Tech Support may use these low level messages to direct the DBA how to resolve a problem.

Error 1601	"Password encryption failed. Error message '%1'."
Constant	PWD_CIPHER_ERROR
SAP Sybase Error Number	3242
SQL State	WW212
SQL Code	-1601L
ODBC 2 State	OK

Error 1601	"Password encryption failed. Error message '%1'."
ODBC 3 State	OK
Severity Code	<i>16 on page 2</i>
Parameter 1	The error message reported by block encrypter.
Probable Cause	Run-time block encrypter initialization failed.

Error 1602	"The specified distinguished name '%1' does not match the search result '%2'."
Constant	LDAPUA_DN_NOMAT
SAP Sybase Error Number	3243
SQL State	WW213
SQL Code	-1602L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The expected distinguished name that was specified in command.
Parameter 2	The result distinguished name returned by LDAP search.
Probable Cause	VALIDATE LDAP SERVER command did a successful search to find a user distinguished name, but the value differs from the expected distinguished name specified in the command.

Error 1603	"The search using '%1' failed due to one or more invalid values set."
Constant	LDAPUA_SEARCHFAIL
SAP Sybase Error Number	3244
SQL State	WW214
SQL Code	-1603L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1603	"The search using '%1' failed due to one or more invalid values set."
Severity Code	<i>16 on page 2</i>
Parameter 1	The LDAP server name or search URL specifying the search.
Probable Cause	An LDAPUA search or validate failed returning LDAP_INVALID_CREDENTIALS, LDAP_INSUFFICIENT_ACCESS, LDAP_INVALID_DN_SYNTAX, LDAP_NO_SUCH_OBJECT, or LDAP_FILTER_ERROR due to the invalid settings. Check the access account values for the named LDAP server or search URL.

Error 1604	"Cannot use logical server policy clause more than once"
Constant	LS_POLICY_USED_TWICE
SAP Sybase Error Number	3245
SQL State	WQ022
SQL Code	-1604L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	Is policy clause appeared more than once in a create/alter logical server policy statement

Error 1605	"Table Parameterized Functions and V4 TableUDFs are not supported for this database."
Constant	TPF_UPGRADE_REQUIRED
SAP Sybase Error Number	3246
SQL State	WP020
SQL Code	-1605L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>

Error 1605	"Table Parameterized Functions and V4 TableUDFs are not supported for this database."
Probable Cause	The current database does not have catalog support for table parameterized functions. To use this feature, upgrade your database to the most recent version.

Error 1606	"Multiple table parameters are not supported."
Constant	ONLY_SINGLE_TABLE_PARM_SUPPORTED
SAP Sybase Error Number	3247
SQL State	WP021
SQL Code	-1606L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	Table parameterized functions are limited to only having at most a single table parameter.

Error 1607	"Outer references are not allowed for TPF input tables."
Constant	TPF_OUTER_REFERENCES_NOT_ALLOWED
SAP Sybase Error Number	3249
SQL State	WP022
SQL Code	-1607L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	Outer references in the select list for a TPF input table are not allowed.

Error 1608	"Unable to delete file %1"
Constant	UNABLE_TO_DELETE_FILE
SAP Sybase Error Number	3250
SQL State	08WB4

Error 1608	"Unable to delete file %1"
SQL Code	-1608L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	16 on page 2
Parameter 1	The file name of the file to be deleted
Probable Cause	The request to delete a file failed.

Error 1609	"File %1 already exists"
Constant	FILE_ALREADY_EXISTS
SAP Sybase Error Number	3251
SQL State	08WB5
SQL Code	-1609L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	16 on page 2
Parameter 1	The file name of the file that already exists
Probable Cause	The request to create a file or directory failed because the file or directory already exists.

Messages 1610 through 1629

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1610	"Unable to create directory %1"
Constant	UNABLE_TO_CREATE_DIRECTORY
SAP Sybase Error Number	3252
SQL State	08WB6
SQL Code	-1610L
ODBC 2 State	08001

Error 1610	"Unable to create directory %1"
ODBC 3 State	08001
Severity Code	<i>16 on page 2</i>
Parameter 1	The file name of the directory that could not be created
Probable Cause	The request to create a directory failed.

Error 1611	"Unable to copy file %1"
Constant	UNABLE_TO_COPY_FILE
SAP Sybase Error Number	3253
SQL State	08WB7
SQL Code	-1611L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	<i>16 on page 2</i>
Parameter 1	The file name of the file to be copied
Probable Cause	The request to copy a file failed.

Error 1612	"Cannot ALTER LDAP SERVER '%1' while ldap server is in active state."
Constant	LDAPSERVER_IS_ACTIVE
SAP Sybase Error Number	3254
SQL State	WW215
SQL Code	-1612L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The LDAP SERVER name.

Error 1612	"Cannot ALTER LDAP SERVER '%1' while ldap server is in active state."
Probable Cause	When an LDAP server is active, an ALTER statement may not change the ldap server options without also specifying WITH SUSPEND clause to also put the server in suspended state. This is an invalid LDAP server state change.

Error 1613	"Tag ID: '%1' specifies a value not bounded by an array"
Constant	FOR_JSON_EXPLICIT_NOT_IN_ARRAY
SAP Sybase Error Number	3255
SQL State	WX017
SQL Code	-1613L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The value of the tag ID which is not bounded by an array.
Probable Cause	A union of multiple queries whose tags have the same parent may generate this error when the queries mix object and value notation.

Error 1614	"Logical Server '%1' is used in both add and drop clauses"
Constant	LS_IN_ADD_DROP
SAP Sybase Error Number	3256
SQL State	WQ023
SQL Code	-1614L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the logical server.
Probable Cause	A logical Server appears in both the add and drop clauses of an alter logical server statement.

Error 1615	"LS Policy '%1' cannot be dropped because this policy is currently being used by a logical server"
Constant	LSP_IN_USE_BY_LS
SAP Sybase Error Number	3257
SQL State	WQ024
SQL Code	-1615L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	LS policy name.
Probable Cause	A logical server policy cannot be dropped if a logical server is using it.

Error 1616	""%1' being used incorrectly in ls policy statement"
Constant	LSP_USING_INCORRECT_ARGS
SAP Sybase Error Number	3258
SQL State	WQ025
SQL Code	-1616L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	LS policy option name.
Probable Cause	A clause in a ls policy sql statement has been used incorrectly.

Error 1617	"The %1 remote data access class is no longer supported, please use %2 instead"
Constant	OMNI_JDBC_NO_LONGER_SUPPORTED
SAP Sybase Error Number	3259
SQL State	WO033

Error 1617	"The %1 remote data access class is no longer supported, please use %2 instead"
SQL Code	-1617L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The JDBC based remote data access class.
Parameter 2	The preferred ODBC based remote data access class.
Probable Cause	You attempted to use a JDBC based remote data access class which is no longer supported. Please use the appropriate ODBC based class instead.

Error 1618	"The %1 remote data access class has been deprecated, please use %2 instead or change cis_option"
Constant	OMNI_JDBC_DEPRECATED
SAP Sybase Error Number	3260
SQL State	WO034
SQL Code	-1618L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The JDBC based remote data access class.
Parameter 2	The preferred ODBC based remote data access class.
Probable Cause	You attempted to use a JDBC based remote data access class which has been deprecated. Please use the appropriate ODBC based class instead; or change the cis_option setting to re-enable this feature.

Error 1619	"logical server '%1' cannot be used in a connect string"
Constant	LS_NOT_ALLOWED
SAP Sybase Error Number	3261

Error 1619	"logical server '%1' cannot be used in a connect string"
SQL State	WQ026
SQL Code	-1619L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	logical servername.
Probable Cause	This logical server cannot be used as an argument to the connection string parameter logicalserver.

Error 1620	"The value specified is not within the required range %1 to %2."
Constant	LDAPUA_OPT_OUT_OF_RANGE
SAP Sybase Error Number	3262
SQL State	WW217
SQL Code	-1620L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The minimum value for this option.
Parameter 2	The maximum value for this option.
Probable Cause	The specified value for an LDAP server option is too big or too small.

Error 1621	"LDAP server %1 may not accept anonymous binds."
Constant	LDAPUA_ANONBINDERR
SAP Sybase Error Number	3263
SQL State	WW218
SQL Code	-1621L
ODBC 2 State	ERROR

Error 1621	"LDAP server %1 may not accept anonymous binds."
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The LDAP server name or search URL specifying the search.
Probable Cause	An LDAPUA search or validate failed returning LDAP_INAPPROPRIATE_AUTH due to invalid settings for the target LDAP server. Check the access account values for the named LDAP server or search URL.

Error 1622	"Bind to LDAP server %1 without a password is not allowed."
Constant	LDAPUA_UTP
SAP Sybase Error Number	3264
SQL State	WW219
SQL Code	-1622L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	The LDAP server name or search URL specifying the search.
Probable Cause	An LDAPUA search or validate failed returning LDAP_UNWILLING_TO_PERFORM due to invalid settings for the target LDAP server. Check access account values for the named LDAP server or search URL.

Error 1623	"The search on LDAP server %1 completed with no matching results."
Constant	LDAPUA_NO_SEARCH_RESULTS
SAP Sybase Error Number	3265
SQL State	WW220
SQL Code	-1623L
ODBC 2 State	ERROR

Error 1623	"The search on LDAP server %1 completed with no matching results."
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The LDAP server name or search URL specifying the search.
Probable Cause	An LDAPUA search or validate failed returning LDAP_NO_RESULTS_RETURNED. This error is expected when the user does not exist in the LDAP server.

Error 1624	"The length of the value specified is too long, it exceeds the limit of %1 bytes."
Constant	LDAPUA_OPT_TOO_LONG
SAP Sybase Error Number	3266
SQL State	WW216
SQL Code	-1624L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The maximum length of the value.
Probable Cause	The specified value for an LDAP server option is too long. Specify a shorter string.

Error 1625	"The UltraLite database deploy file is invalid (code: %1, file: %2)"
Constant	ULTRALITE_DEPLOY_FILE_INVALID
SAP Sybase Error Number	3267
SQL State	WU002
SQL Code	-1625L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1625	"The UltraLite database deploy file is invalid (code: %1, file: %2)"
Severity Code	<i>16 on page 2</i>
Parameter 1	The diagnostic code.
Parameter 2	The associated filename, if applicable.
Probable Cause	The UltraLite database deploy file is invalid. This can occur if the wrong file is deployed, or if the file is damaged. Diagnostic code 1 indicates the file is not a deploy file or has subsequently been corrupted. Diagnostic code 2 indicates the file is not a valid size.

Error 1626	"The logical server policy for logical server '%1' does not allow 'redirect=yes' in the connection string"
Constant	LS_POLICY_DOES_NOT_ALLOW_REDIRECTION
SAP Sybase Error Number	3268
SQL State	WQ027
SQL Code	-1626L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Parameter 1	logical servername.
Probable Cause	This logical server policy for this logical server does not allow redirection.

Error 1627	"TLS ON cannot be used with URL %1"
Constant	LDAPUA_TLS_WITH_LDAPS
SAP Sybase Error Number	3269
SQL State	WW240
SQL Code	-1627L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1627	"TLS ON cannot be used with URL %1"
Severity Code	<i>16</i> on page 2
Parameter 1	The LDAP URL that is using Secure LDAP.
Probable Cause	The LDAP server is specified with TLS ON and the specified LDAP URL uses Secure LDAP, that is, 'ldaps' instead of 'ldap', which is not a valid combination. Use either TLS ON or an 'ldaps' URL.

Error 1628	"logical server '%1' cannot be used as a default logical server"
Constant	LS_NOT_ALLOWED_AS_DEFAULT
SAP Sybase Error Number	3270
SQL State	WQ028
SQL Code	-1628L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	logical servername.
Probable Cause	This logical server cannot be used as a default logical server.

Error 1629	"Only one IDENTIFIED BY value may be specified."
Constant	LDAPUA_TOO_MANY_IDENTBY
SAP Sybase Error Number	3271
SQL State	WW241
SQL Code	-1629L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Probable Cause	The LDAP server is specified with more than one password or is specified with both IDENTIFIED BY and IDENTIFIED BY ENCRYPTED. Set only one password.

1630 - 1000133

Messages 1630 through 1649

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1630	"Server '%1' is not allowed to have different values for ls policy option temp_data_in_shared_temp"
Constant	LS_POLICY_OPTION_VALUE_DIFFERENT
SAP Sybase Error Number	3272
SQL State	WQ029
SQL Code	-1630L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	multiplex servername.
Probable Cause	A server is not allowed to have different values for temp_data_in_shared_temp ls policy option.

Error 1631	"Use of table privilege '%1' is not supported on the current database"
Constant	TABPRIV_LOAD_TRUNCATE_UNSUPPORTED
SAP Sybase Error Number	3273
SQL State	0A007
SQL Code	-1631L
ODBC 2 State	28000
ODBC 3 State	28000
Severity Code	16 on page 2

Error 1631	"Use of table privilege '%1' is not supported on the current database"
Parameter 1	The table privilege, load or truncate.
Probable Cause	The current database is an older database and does not have the capability to support table privileges load or truncate. You must upgrade your database to use these table privileges.

Error 1632	"Dropping or altering arbiter \"%1\" requires a connection to the partner."
Constant	MIRROR_DROP_ARBITER_REQUIRES_PARTNER_CONN
SAP Sybase Error Number	3274
SQL State	WW242
SQL Code	-1632L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the arbiter server.
Probable Cause	An attempt was made to drop or alter an arbiter that is not connected to the partner server.

Error 1633	"Trace event '%1' is not valid"
Constant	INVALID_TRACE_EVENT_NAME
SAP Sybase Error Number	3275
SQL State	WE019
SQL Code	-1633L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	11 on page 2
Parameter 1	The trace event name.
Probable Cause	The specified trace event name is not valid.

Error 1634	"The specified session name '%1' is not valid"
Constant	INVALID_TRACE_EVENT_SESSION_NAME
SAP Sybase Error Number	3276
SQL State	WE020
SQL Code	-1634L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	// on page 2
Parameter 1	The trace event session name.
Probable Cause	The specified trace event session name is not valid.

Error 1635	"Trace event '%1' already exists"
Constant	TRACE_EVENT_ALREADY_EXISTS
SAP Sybase Error Number	3277
SQL State	WE021
SQL Code	-1635L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	// on page 2
Parameter 1	The trace event name.
Probable Cause	The specified trace event name already exists.

Error 1636	"Trace event '%1' is referenced by one or more sessions. Drop referencing sessions first."
Constant	TRACE_EVENT_IS_IN_USE
SAP Sybase Error Number	3278
SQL State	WE022
SQL Code	-1636L
ODBC 2 State	ERROR

Error 1636	"Trace event '%1' is referenced by one or more sessions. Drop referencing sessions first."
ODBC 3 State	ERROR
Severity Code	// on page 2
Parameter 1	The trace event name.
Probable Cause	The specified trace event name is used and cannot be dropped before dropping referencing sessions.

Error 1637	"Trace event session '%1' is active. Stop active session before dropping the session."
Constant	TRACE_EVENT_SESSION_IS_ACTIVE
SAP Sybase Error Number	3279
SQL State	WE023
SQL Code	-1637L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	// on page 2
Parameter 1	The trace event session name.
Probable Cause	The specified trace event session is active. The session must be not be active in order to be dropped.

Error 1638	"Too many arguments for trace event '%1'."
Constant	TOO_MANY_PARAMETERS_FOR_TRACE_EVENT
SAP Sybase Error Number	3280
SQL State	WE024
SQL Code	-1638L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	// on page 2
Parameter 1	The trace event name.

Error 1638	"Too many arguments for trace event '%1'."
Probable Cause	Too many arguments were provided for the trace event specified.

Error 1639	"Database alter failed: %1"
Constant	DATABASE_NOT_ALTERED
SAP Sybase Error Number	3281
SQL State	08WB8
SQL Code	-1639L
ODBC 2 State	08004
ODBC 3 State	08004
Severity Code	14 on page 2
Parameter 1	Reason that the database was not altered.
Probable Cause	Your attempt to alter a database failed.

Error 1640	"Too many active trace event sessions."
Constant	TOO_MANY_ACTIVE_TRACE_SESSIONS
SAP Sybase Error Number	3282
SQL State	WE025
SQL Code	-1640L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	11 on page 2
Probable Cause	Too many active trace sessions.

Error 1641	"Trace event session '%1' already active."
Constant	TRACE_SESSION_ALREADY_ACTIVE
SAP Sybase Error Number	3283
SQL State	WE026
SQL Code	-1641L

Error 1641	"Trace event session '%1' already active."
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>11 on page 2</i>
Parameter 1	The trace event session name.
Probable Cause	The specified trace event session is already active.

Error 1642	"One or more targets in the trace event session '%1' failed to start."
Constant	ONE_OR_MORE_TRACE_SESSION_TARGETS_FAILED_TO_START
SAP Sybase Error Number	3284
SQL State	WE027
SQL Code	-1642L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>11 on page 2</i>
Parameter 1	The trace event session name.
Probable Cause	The specified trace event session is already active.

Error 1643	"Trace event session '%1' failed to start."
Constant	TRACE_SESSION_FAILED_TO_START
SAP Sybase Error Number	3285
SQL State	WE028
SQL Code	-1643L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>11 on page 2</i>
Parameter 1	The trace event session name.

Error 1643	"Trace event session '%1' failed to start."
Probable Cause	The specified trace event session failed to start.

Error 1644	"Trace event session '%1' is already stopped."
Constant	TRACE_SESSION_ALREADY_STOPPED
SAP Sybase Error Number	3286
SQL State	WE029
SQL Code	-1644L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	// on page 2
Parameter 1	The trace event session name.
Probable Cause	The specified trace event session is already stopped.

Error 1645	"Trace event session '%1' already has trace event '%2'."
Constant	TRACE_SESSION_ALREADY_HAS_EVENT
SAP Sybase Error Number	3287
SQL State	WE030
SQL Code	-1645L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	// on page 2
Parameter 1	The trace event session name.
Parameter 2	The trace event name.
Probable Cause	The specified trace event session already has the specified event.

Error 1646	"The specified target type '%1' is not valid"
Constant	INVALID_TRACE_EVENT_TARGET_TYPE
SAP Sybase Error Number	3288

Error 1646	"The specified target type '%1' is not valid"
SQL State	WE031
SQL Code	-1646L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	// on page 2
Parameter 1	The trace event target type.
Probable Cause	The specified trace event target type is not valid.

Error 1647	"Unknown option '%1' specified for target type '%2'."
Constant	UNKNOWN_OPTION_FOR_TARGET_TYPE
SAP Sybase Error Number	3289
SQL State	WE032
SQL Code	-1647L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	// on page 2
Parameter 1	The option name.
Parameter 2	The trace event target type.
Probable Cause	An unknown option name was specified for given target type.

Error 1648	"The option '%1' was not specified for target type '%2'."
Constant	OPTION_FOR_TARGET_TYPE_NOT_SPECIFIED
SAP Sybase Error Number	3290
SQL State	WE033
SQL Code	-1648L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	// on page 2

Error 1648	"The option '%1' was not specified for target type '%2'."
Parameter 1	The option name.
Parameter 2	The trace event target type.
Probable Cause	A required option for target type was not specified.

Error 1649	"Trace event session '%1' already has target type '%2'."
Constant	TRACE_SESSION_ALREADY_HAS_TARGET_TYPE
SAP Sybase Error Number	3291
SQL State	WE034
SQL Code	-1649L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>// on page 2</i>
Parameter 1	The trace event session name.
Parameter 2	The trace event target type.
Probable Cause	The specified trace event session already has the specified target type.

Messages 1650 through 1669

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1650	"Trace event session '%1' does not have trace event '%2'."
Constant	TRACE_SESSION_DOES_NOT_HAVE_TRACE_EVENT
SAP Sybase Error Number	3292
SQL State	WE035
SQL Code	-1650L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>// on page 2</i>

Error 1650	"Trace event session '%1' does not have trace event '%2'."
Parameter 1	The trace event session name.
Parameter 2	The trace event name.
Probable Cause	The trace event session does not have the specified trace event.

Error 1651	"Trace event session '%1' does not have trace event '%2'."
Constant	TRACE_SESSION_DOES_NOT_HAVE_TARGET_TYPE
SAP Sybase Error Number	3293
SQL State	WE036
SQL Code	-1651L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	11 on page 2
Parameter 1	The trace event session name.
Parameter 2	The trace event target type.
Probable Cause	The trace event session does not have the specified trace target type.

Error 1652	"Trace event session '%1' already exists."
Constant	TRACE_SESSION_ALREADY_EXISTS
SAP Sybase Error Number	3294
SQL State	WE037
SQL Code	-1652L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	11 on page 2
Parameter 1	The trace event session name.
Probable Cause	A trace event session with that name already exists.

Error 1653	"RLV dbspace already exists. Cannot create more than one RLV dbspace."
Constant	RLV_DBSPACE_CREATION_NOT_ALLOWED
SAP Sybase Error Number	3295
SQL State	WQ030
SQL Code	-1653L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	Creation of more than one user defined RLV dbspace is not allowed.

Error 1654	"Cannot enable RLV storage for table '%1'. A RLV dbspace does not exist."
Constant	RLV_DBSPACE_DOES_NOT_EXIST
SAP Sybase Error Number	3296
SQL State	WQ031
SQL Code	-1654L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	table name.
Probable Cause	Creation of more than one user defined RLV dbspace is not allowed.

Error 1655	"Invalid value for login policy option \'%1\No message
Constant	INVALID_LOGIN_POLICY_OPTION_VALUE
SAP Sybase Error Number	3297
SQL State	WW243
SQL Code	-1655L
ODBC 2 State	ERROR

Error 1655	"Invalid value for login policy option \"%1\"No message
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The name of login policy option.
Probable Cause	The value supplied for login policy option is not within valid bounds.

Error 1656	"Database upgrade not possible; the name of a new SYSTEM logical server is already in use."
Constant	IQ_LOGICAL_SERVER_CONFLICT
SAP Sybase Error Number	3298
SQL State	WQ032
SQL Code	-1656L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Probable Cause	An attempt to upgrade a database failed. Retry upgrade of the database when no existing logical server is using the name of the documented system logical servers.

Error 1657	"Database upgrade not possible; Join Index in use."
Constant	IQ_JOININDEX_PRESENT
SAP Sybase Error Number	3299
SQL State	WQ033
SQL Code	-1657L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Probable Cause	An attempt to upgrade a database failed. Retry upgrade of the database when join indexes have been dropped from the database.

Error 1658	"To '%1' column '%2' Table '%3' must be partitioned by '%4'"
Constant	COLUMN_PARTITIONED_INCORRECTLY
SAP Sybase Error Number	3300
SQL State	WW244
SQL Code	-1658L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Partition type
Parameter 2	The column name
Parameter 3	The table name
Parameter 4	Partition type
Probable Cause	The partitioning of this column must be consistent with the table partitioning.

Error 1659	"File or directory %1 not found"
Constant	FILE_NOT_FOUND
SAP Sybase Error Number	3301
SQL State	08WB9
SQL Code	-1659L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	16 on page 2
Parameter 1	The file or directory name that does not exist or fail to access
Probable Cause	You attempted to perform an operation using a file or directory name that does not exist or fail to access.

Error 1660	"Fail to compare %1 and %2"
Constant	FILE_COMPARE_FAIL

Error 1660	"Fail to compare %1 and %2"
SAP Sybase Error Number	3302
SQL State	08WC1
SQL Code	-1660L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	16 on page 2
Parameter 1	The source file or directory name that fails to compare
Parameter 2	The target file or directory name that fails to compare
Probable Cause	Failed to compare files or directories.

Error 1661	"%1 is not a directory"
Constant	NOT_A_DIRECTORY
SAP Sybase Error Number	3303
SQL State	08WC2
SQL Code	-1661L
ODBC 2 State	08001
ODBC 3 State	08001
Severity Code	16 on page 2
Parameter 1	The path name that is not a directory
Probable Cause	Failed to perform an operation using directory name.

Error 1662	"%1 and %2 must not be the same"
Constant	SAME_SOURCE_TARGET
SAP Sybase Error Number	3304
SQL State	08WC3
SQL Code	-1662L
ODBC 2 State	08001
ODBC 3 State	08001

Error 1662	"%1 and %2 must not be the same"
Severity Code	<i>16</i> on page 2
Parameter 1	The source file or directory name
Parameter 2	The target file or directory name
Probable Cause	You attempted to perform an operation using the same source and target file or directory.

Error 1663	"Prevented removal of LDAP server because it is referenced by login policy \"%1\" which is the only login policy with an LDAP server and the value of login_mode is \"LDAPUA\"."
Constant	ONLY_LDAP_POLICY
SAP Sybase Error Number	3305
SQL State	WW245
SQL Code	-1663L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The name of the login policy.
Probable Cause	The setting for server-wide login_mode option is LDAPUA so to avoid locking out users from connecting, prevent the only login policy supporting LDAPUA reference removal. Change login_mode before proceeding to DROP LDAP SERVER <server name> WITH DROP ALL REFERENCES.

Error 1664	"Prevented removal of LDAP server \"%1\" because it is the only LDAP server and the value of login_mode is \"LDAPUA\"."
Constant	ONLY_LDAP_SERVER
SAP Sybase Error Number	3306
SQL State	WW246
SQL Code	-1664L

Error 1664	"Prevented removal of LDAP server \"%1\" because it is the only LDAP server and the value of login_mode is \"LDAPUA \"."
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The name of the LDAP server.
Probable Cause	The setting for server-wide login_mode option is LDAPUA so to avoid locking out users from connecting, prevent the removal of the only LDAP server. Change login_mode before proceeding to DROP LDAP SERVER <server name>.

Error 1665	"Cannot change password because change_password_dual_control process is in progress"
Constant	CHANGE_PWD_DUAL_CONTROL_INPROGRESS
SAP Sybase Error Number	3307
SQL State	28W20
SQL Code	-1665L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Probable Cause	You attempted to change password while changing password by change_password_dual_control option is in progress.

Error 1666	"Expression is not an array"
Constant	NOT_AN_ARRAY
SAP Sybase Error Number	3308
SQL State	42X07
SQL Code	-1666L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1666	"Expression is not an array"
Severity Code	<i>16</i> on page 2
Probable Cause	You either tried to apply an ARRAY dereference (using double square brackets) to an expression that does not evaluate to an array, or else you tried to pass a non-ARRAY expression to UNNEST.

Error 1667	"The option '%1' cannot be set in user-defined logical server policies."
Constant	LSP_OPTION_OVERRIDE_NOT_ALLOWED
SAP Sybase Error Number	3309
SQL State	WQ034
SQL Code	-1667L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The name of the option
Probable Cause	There are certain options that can only be set in the root logical server policy, not in user-defined logical server policies.

Error 1668	"'%1' is not a valid logical server policy option"
Constant	LSP_OPTION_DOES_NOT_EXIST
SAP Sybase Error Number	3310
SQL State	WQ035
SQL Code	-1668L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16</i> on page 2
Parameter 1	The name of the option
Probable Cause	The LSP option specified by the user does not exist.

Error 1669	"The value given for the option '%1' is not of the correct type or value."
Constant	INVALID_LSP_OPTION_VALUE
SAP Sybase Error Number	3311
SQL State	WQ036
SQL Code	-1669L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the option
Probable Cause	Different options accept different types of values, such as boolean, string or integer.

Messages 1670 through 1689

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1670	"Cannot create table '%1' in a RLV dbspace."
Constant	RLV_TABLE_CREATION_NOT_ALLOWED
SAP Sybase Error Number	3312
SQL State	WQ037
SQL Code	-1670L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	table name.
Probable Cause	Creation of a table in a RLV dbspace is not allowed.

Error 1671	"The file '%1' is invalid when the disk sandbox feature is enabled for database '%2'"
Constant	DISKSANDBOX_INVALID_PATH

Error 1671	"The file '%1' is invalid when the disk sandbox feature is enabled for database '%2'"
SAP Sybase Error Number	3313
SQL State	57W06
SQL Code	-1671L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	15 on page 2
Parameter 1	The name of the invalid file.
Parameter 2	The name of the database that the disk sandbox feature is enabled for.
Probable Cause	The file passed to the operation is invalid when the sandbox feature is enabled.

Error 1672	"A disk sandbox error occurred for database '%1' when determining the disk sandbox status for file '%2' "
Constant	DISKSANDBOX_UNABLE_TO_DETERMINE
SAP Sybase Error Number	3314
SQL State	57W07
SQL Code	-1672L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	15 on page 2
Parameter 1	The name of the database that could not determine the disk sandbox status of the file.
Parameter 2	The name of the invalid file.
Probable Cause	The file passed to the operation caused an error when determining the disk sandbox status.

Error 1673	"A disk sandbox error occurred for database '%1' when finding the full path for file '%1'"
Constant	DISKSANDBOX_FULLPATH_ERROR

Error 1673	"A disk sandbox error occurred for database '%1' when finding the full path for file '%1'"
SAP Sybase Error Number	3315
SQL State	57W08
SQL Code	-1673L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	15 on page 2
Parameter 1	The name of the database that could not find the full path of the file.
Parameter 2	The name of the invalid file.
Probable Cause	There was an error in finding the full path of the file that was passed to the operation.

Error 1674	"Error at offset '%1': unexpected token '%2'"
Constant	PARSE_JSON_UNEXPECTED_TOKEN
SAP Sybase Error Number	3316
SQL State	WX018
SQL Code	-1674L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The offset where the error occurred.
Parameter 2	The unexpected token.
Probable Cause	An unexpected token such as a comma, bracket, or brace was encountered.

Error 1675	"Error at offset '%1': unexpected trailing text"
Constant	PARSE_JSON_UNEXPECTED_TEXT
SAP Sybase Error Number	3317
SQL State	WX019

Error 1675	"Error at offset '%1': unexpected trailing text"
SQL Code	-1675L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The offset where the error occurred.
Probable Cause	Trailing text was encountered after parsing the JSON data.

Error 1676	"Error at offset '%1': invalid data"
Constant	PARSE_JSON_INVALID_DATA
SAP Sybase Error Number	3318
SQL State	WX020
SQL Code	-1676L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The offset where the error occurred.
Probable Cause	A JSON object or array contains invalid data.

Error 1677	"Error at offset '%1': expected token '%2'"
Constant	PARSE_JSON_EXPECTED_TOKEN
SAP Sybase Error Number	3319
SQL State	WX021
SQL Code	-1677L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The offset where the error occurred.
Parameter 2	The token that was expected.

Error 1677	"Error at offset '%1': expected token '%2'"
Probable Cause	The expected token was missing in the JSON data.

Error 1678	"Error at offset '%1': expected JSON name/value pair"
Constant	PARSE_JSON_EXPECTED_PAIR
SAP Sybase Error Number	3320
SQL State	WX022
SQL Code	-1678L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The offset where the error occurred.
Probable Cause	A name/value pair was expected within the JSON object.

Error 1679	"Error at offset '%1': mismatched object or array terminator"
Constant	PARSE_JSON_MISMATCH_TERMINATOR
SAP Sybase Error Number	3321
SQL State	WX023
SQL Code	-1679L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The offset where the error occurred.
Probable Cause	Encountered a mismatched terminator for a JSON object or array.

Error 1680	"Invalid variable or type"
Constant	PARSE_JSON_INVALID_VARIABLE_TYPE
SAP Sybase Error Number	3322
SQL State	WX024

Error 1680	"Invalid variable or type"
SQL Code	-1680L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The named variable is invalid or of the wrong data type for the JSON result.

Error 1681	"Procedure is currently being altered or dropped"
Constant	PROCEDURE_IN_USE_DDL
SAP Sybase Error Number	3323
SQL State	42WF0
SQL Code	-1681L
ODBC 2 State	40001
ODBC 3 State	40001
Severity Code	16 on page 2
Probable Cause	You have attempted to use a procedure that is currently being altered or dropped.

Error 1682	"The RLV dbspace '%1' cannot be made read only because it contains RLV enabled tables"
Constant	RLV_DBSPACE_CONTAINS_TABLES
SAP Sybase Error Number	3324
SQL State	WQ038
SQL Code	-1682L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the dbspace

Error 1682	"The RLV dbspace '%1' cannot be made read only because it contains RLV enabled tables"
Probable Cause	You attempted to make the named RLV dbspace read only, but it contains RLV enabled tables. You must drop or disable the tables before making the dbspace read only.
Error 1683	"Cannot change the mirror server type from %1 to %2"
Constant	CANNOT_CHANGE_MIRROR_SERVER_TYPE
SAP Sybase Error Number	3325
SQL State	42WF2
SQL Code	-1683L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The original mirror server type
Parameter 2	The proposed new mirror server type
Probable Cause	You attempted to use the CREATE OR REPLACE MIRROR SERVER or ALTER MIRROR SERVER statement to change the mirror server type, but the proposed change is not supported.
Error 1684	"Trace target option '%1' conflicts with already used option '%2'."
Constant	TARGET_OPTIONS_CONFLICT
SAP Sybase Error Number	3326
SQL State	WE038
SQL Code	-1684L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	11 on page 2
Parameter 1	The trace target option name.

Error 1684	"Trace target option '%1' conflicts with already used option '%2'."
Parameter 2	The trace target option name.
Probable Cause	A trace target option conflict with another target option used.

Error 1685	"There was insufficient memory to complete the %1 operation"
Constant	SFC_MEM_ERROR
SAP Sybase Error Number	3327
SQL State	08S01
SQL Code	-1685L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>17 on page 2</i>
Parameter 1	The name of the procedure that detected the error.
Probable Cause	A call to the specified procedure could not complete the operation due to insufficient memory.

Error 1686	"Invalid parameter was used in the call to %1"
Constant	SFC_INVALID_PARM
SAP Sybase Error Number	3328
SQL State	08S02
SQL Code	-1686L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>15 on page 2</i>
Parameter 1	The name of the procedure.
Probable Cause	An invalid parameter value was passed to the specified procedure.

Error 1687	"The secure feature key name '%2' is not valid in the call to %1"
Constant	SFC_INVALID_NAME
SAP Sybase Error Number	3329
SQL State	08S03
SQL Code	-1687L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	15 on page 2
Parameter 1	The name of the procedure.
Parameter 2	The secure feature key name.
Probable Cause	An invalid secure feature key name was passed to the specified procedure.

Error 1688	"An invalid authorization key was specified in the call to %1"
Constant	SFC_INVALID_KEY
SAP Sybase Error Number	3330
SQL State	08S04
SQL Code	-1688L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	15 on page 2
Parameter 1	The name of the procedure.
Probable Cause	An invalid secure feature key value was passed to the specified procedure.

Error 1689	"An invalid secure feature list '%2' was specified in the call to %1"
Constant	SFC_INVALID_FEAT
SAP Sybase Error Number	3331

Error 1689	"An invalid secure feature list '%2' was specified in the call to %1"
SQL State	08S05
SQL Code	-1689L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	15 on page 2
Parameter 1	The name of the procedure.
Parameter 2	The secure feature list.
Probable Cause	An invalid list of secure features was passed to the specified procedure.

Messages 1690 through 1709

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1690	"You are not authorized to assign the feature list '%2' to a secure feature key using %1"
Constant	SFC_NO_AUTH_FOR_FEAT
SAP Sybase Error Number	3332
SQL State	08S06
SQL Code	-1690L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	The name of the procedure.
Parameter 2	The secure feature list.
Probable Cause	An attempt was made to define a secure feature key to use a secure feature that the user is not authorized to use or assign.

Error 1691	"You are not authorized to change the secure feature key named '%2' using %1"
Constant	SFC_NO_AUTH_FOR_KEY
SAP Sybase Error Number	3333
SQL State	08S07
SQL Code	-1691L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	The name of the procedure.
Parameter 2	The secure feature key name.
Probable Cause	The user is not authorized to change the named secure feature key.

Error 1692	"Call to %1 failed - the maximum number of secure feature keys has already been created"
Constant	SFC_HIT_MAX_LIMIT
SAP Sybase Error Number	3334
SQL State	08S08
SQL Code	-1692L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	17 on page 2
Parameter 1	The name of the procedure.
Probable Cause	The limit on the number of secure feature keys has been reached.

Error 1693	"Call to %1 failed - the secure feature key named '%2' already exists"
Constant	SFC_KEY_EXISTS
SAP Sybase Error Number	3335
SQL State	08S09

Error 1693	"Call to %1 failed - the secure feature key named '%2' already exists"
SQL Code	-1693L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	15 on page 2
Parameter 1	The name of the procedure.
Parameter 2	The secure feature key name.
Probable Cause	The user attempted to create a secure feature key with the name of a key that already exists.

Error 1694	"Call to %1 failed - the secure feature key named '%2' does not exist"
Constant	SFC_NOT_FOUND
SAP Sybase Error Number	3336
SQL State	08S10
SQL Code	-1694L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	15 on page 2
Parameter 1	The name of the procedure.
Parameter 2	The secure feature key name.
Probable Cause	The user attempted to reference a secure feature key that does not exist.

Error 1695	"Call to %1 failed - the authorization key specified for the secure feature key named '%2' is incorrect"
Constant	SFC_NOT_MATCH
SAP Sybase Error Number	3337
SQL State	08S11
SQL Code	-1695L

Error 1695	"Call to %1 failed - the authorization key specified for the secure feature key named '%2' is incorrect"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	The name of the procedure.
Parameter 2	The secure feature key name.
Probable Cause	The provided authorization key did not match the value stored for the specified named key.

Error 1696	"Call to %1 failed - the key named '%2' is the last key with the MANAGE_FEATURES and MANAGE_KEYS features"
Constant	SFC_CANNOT_REMOVE_LAST
SAP Sybase Error Number	3338
SQL State	08S12
SQL Code	-1696L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The name of the procedure.
Parameter 2	The secure feature key name.
Probable Cause	The call attempted to remove the last secure feature key that would enable both MANAGE_FEATURES and MANAGE_KEYS and this is not allowed.

Error 1697	"Database upgrade not possible; LD Index in use."
Constant	IQ_LDINDEX_PRESENT
SAP Sybase Error Number	3339
SQL State	WQ039
SQL Code	-1697L
ODBC 2 State	ERROR

Error 1697	"Database upgrade not possible; LD Index in use."
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	An attempt to upgrade a database failed. Retry upgrade of the database when LD indexes have been dropped from the database.

Error 1698	"change_password_dual_control is enabled for this user. Use ALTER USER to change password."
Constant	CHANGE_PWD_DUAL_CONTROL_ENABLED
SAP Sybase Error Number	3340
SQL State	28W21
SQL Code	-1698L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	You attempted to change a password while the change_password_dual_control option is set for this user. When this option is set, you must use the ALTER USER statement to change the dual password.

Error 1699	"Cannot convert database to multiplex. An RLV dbspace exists."
Constant	MPX_CONVERSION_NOT_ALLOWED_WITH_RLV_STORE
SAP Sybase Error Number	3341
SQL State	WQ040
SQL Code	-1699L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>16 on page 2</i>
Probable Cause	A simplex database with RLV dbspace cannot be converted to a multiplex database.

Error 1700	"TDS login requests with unencrypted passwords are not permitted"
Constant	UNENCRYPTED_TDS_LOGIN_REQUESTS_NOT_PERMITTED
SAP Sybase Error Number	3342
SQL State	28W22
SQL Code	-1700L
ODBC 2 State	28000
ODBC 3 State	28000
Severity Code	16 on page 2
Probable Cause	You attempted to perform a TDS login without using RSA encryption for the password. The current TDS login setting does not allow unencrypted TDS login requests. Change the tds server option setting or connect using an RSA encrypted password.

Error 1701	"TDS login requests with RSA encrypted passwords must also use a nonce"
Constant	RSA_ENCRYPTED_TDS_LOGIN_MUST_HAVE_NONCE
SAP Sybase Error Number	3343
SQL State	28W23
SQL Code	-1701L
ODBC 2 State	28000
ODBC 3 State	28000
Severity Code	16 on page 2
Probable Cause	You attempted to perform a TDS login with a client that does not use a nonce with the RSA encrypted password. The current TDS login setting does not allow RSA encrypted TDS login requests without a nonce. Change the tds server option setting or connect using a TDS client that supports a nonce with the RSA encrypted password.

Error 1702	"Collection types not supported"
Constant	COLLECTION_TYPES_NOT_SUPPORTED

Error 1702	"Collection types not supported"
SAP Sybase Error Number	3344
SQL State	0AW28
SQL Code	-1702L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Probable Cause	The current database is an older database and does not have support for row or array types. To use this feature, upgrade your database to the most recent version.

Error 1703	"The user name specified must be the user name of the current connection"
Constant	CREATE_SCHEMA_USER_DOES_NOT_MATCH
SAP Sybase Error Number	3345
SQL State	42WD5
SQL Code	-1703L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	In the CREATE SCHEMA AUTHORIZATION clause, you specified a user name other than the user name of the current connection.

Error 1704	"Remote column %1 has been specified with the wrong case"
Constant	OMNI_RMT_COLUMN_WRONG_CASE
SAP Sybase Error Number	3346
SQL State	WO035
SQL Code	-1704L

Error 1704	"Remote column %1 has been specified with the wrong case"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	11 on page 2
Parameter 1	The complete name of the remote column.
Probable Cause	The remote server requires that columns be specified in the correct case.

Error 1705	"Illegal RLV Merge Type '%1'"
Constant	RLV_ILLEGAL_MERGE_TYPE
SAP Sybase Error Number	3347
SQL State	WQ041
SQL Code	-1705L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The illegal merge string
Probable Cause	Legal RLV merge types are: BLOCKING, NONBLOCKING.

Error 1706	"The use of foreign keys in a RLV table is not supported"
Constant	RLV_FOREIGNKEY_UNSUPPORTED
SAP Sybase Error Number	3348
SQL State	WQ043
SQL Code	-1706L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You attempted to use a foreign key within a RLV table which is unsupported.

Error 1707	"The datatype '%1' cannot be used with an RLV enabled table"
Constant	RLV_UNSUPPORTED_DATATYPE
SAP Sybase Error Number	3349
SQL State	WQ042
SQL Code	-1707L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the unsupported datatype
Probable Cause	You attempted to use an datatype that is not supported in combination with RLV.

Error 1708	"The option '%1' cannot be used with RLV enabled"
Constant	RLV_UNSUPPORTED_OPTION
SAP Sybase Error Number	3350
SQL State	WQ044
SQL Code	-1708L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the unsupported option
Probable Cause	You attempted to use an option that is not supported in combination with RLV.

Error 1709	"Invalid DEFAULT value near '%1' on line %2"
Constant	INVALID_DEFAULT_VALUE
SAP Sybase Error Number	3351
SQL State	42W10
SQL Code	-1709L

Error 1709	"Invalid DEFAULT value near '%1' on line %2"
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Parameter 1	The word or symbol where the invalid DEFAULT value has been detected.
Parameter 2	Line number.
Probable Cause	An invalid DEFAULT value was specified when creating or altering a table column.

Messages 1710 through 1000008

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1710	"Invalid value for INSERT near '%1' on line %2"
Constant	INVALID_INSERT_VALUE
SAP Sybase Error Number	3352
SQL State	42W11
SQL Code	-1710L
ODBC 2 State	37000
ODBC 3 State	42000
Severity Code	15 on page 2
Parameter 1	The word or symbol where the invalid value has been detected.
Parameter 2	Line number.
Probable Cause	An invalid value was specified for a value in an INSERT statements.

Error 1711	"Cannot use a RLV DBSpace in this context."
Constant	RLV_DBSPACE_INVALID
SAP Sybase Error Number	3353
SQL State	WQ045
SQL Code	-1711L

Error 1711	"Cannot use a RLV DBSpace in this context."
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	A RLV dbspace is not a valid type of dbspace for the specified operation.

Error 1712	"An RLV forced merge on table '%1' has failed"
Constant	RLV_FORCED_MERGE_FAILED
SAP Sybase Error Number	3354
SQL State	WQ046
SQL Code	-1712L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The table name for the merge that failed
Probable Cause	A forced DDL merge has failed.

Error 1713	"The index type '%1' cannot be used with an RLV enabled table"
Constant	RLV_UNSUPPORTED_INDEX
SAP Sybase Error Number	3355
SQL State	WQ047
SQL Code	-1713L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	Name of the unsupported index type
Probable Cause	You attempted to use an index type that is not supported in combination with RLV.

Error 1714	"The dbmlsync server did not have sufficient database permissions"
Constant	SYNCCMD_CANT_ACCESS_RESULT
SAP Sybase Error Number	3356
SQL State	5RW50
SQL Code	-1714L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The SYNCHRONIZE statement attempts to store the results of the synchronization in the synchronize_results and synchronize_parameters tables. The user who executed the command, or the user specified in the USER clause of the SYNCHRONIZE statement must have permission to insert rows into these tables.

Error 1715	"Invalid options for UPGRADE: SCRIPT FILE can only be specified with RESTART"
Constant	UPGRADE_SCRIPT_EXTRA_CLAUSE
SAP Sybase Error Number	3387
SQL State	08X01
SQL Code	-1715L
ODBC 2 State	08004
ODBC 3 State	08004
Severity Code	21 on page 2
Probable Cause	ALTER DATABASE UPGRADE statement with SCRIPT FILE clause cannot be combined with any other clause except for RESTART ON/OFF.

Error 1716	"Statement %1 disallowed during upgrade from script"
Constant	UPGRADE_DISALLOWED_STMT
SAP Sybase Error Number	3386

Error 1716	"Statement %1 disallowed during upgrade from script"
SQL State	08X02
SQL Code	-1716L
ODBC 2 State	08004
ODBC 3 State	08004
Severity Code	21 on page 2
Parameter 1	Disallowed statement.
Probable Cause	Upgrade from script is not allowed to use the following statements: BACKUP, ALTER DATABASE UPGRADE.

Error 1717	"The LOCK TABLE command is not supported for RLV tables"
Constant	RLV_LOCK_TABLE_UNSUPPORTED
SAP Sybase Error Number	3388
SQL State	WQ048
SQL Code	-1717L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	You attempted to use the LOCK TABLE command on an RLV enabled table.

Error 1718	"A local main cache already exists for this node"
Constant	CACHE_DBSPACE_CREATION_NOT_ALLOWED
SAP Sybase Error Number	3389
SQL State	WQ049
SQL Code	-1718L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2

Error 1718	"A local main cache already exists for this node"
Probable Cause	Creation of more than one user defined CACHE dbspace is not allowed per node.

Error 1719	"The RENAME PATH of file for local main cache is not allowed"
Constant	ALTER_DBSPACE_RENAME_PATH_NOT_ALLOWED
SAP Sybase Error Number	3399
SQL State	WQ050
SQL Code	-1719L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Probable Cause	The ALTER DBSPACE to RENAME PATH is not allowed for local main cache.

Error 1720	"Multiplex Agent for Server '%1' not found"
Constant	IQ_MULTIPLEX_AGENT_NOT_FOUND
SAP Sybase Error Number	3400
SQL State	WW111
SQL Code	-1720L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	There is no Agent assigned to this Multiplex Server.
Probable Cause	This Multiplex Server has no agent assigned to it.

Error 1721	"Multiplex Agent for Server '%1' exists"
Constant	IQ_MULTIPLEX_AGENT_EXISTS
SAP Sybase Error Number	3401

Error 1721	"Multiplex Agent for Server '%1' exists"
SQL State	WW157
SQL Code	-1721L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	There is already an Agent assigned to this Multiplex Server.
Probable Cause	This Multiplex Server already has an agent assigned to it.

Error 1726	"The length of the agent password must be > 0 and cannot exceeds %1 bytes."
Constant	IQ_MULTIPLEX_INCORRECT_AGENT_PWD_LEN
SAP Sybase Error Number	3406
SQL State	WW158
SQL Code	-1726L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	16 on page 2
Parameter 1	The maximum length of the value.
Probable Cause	The specified value for an agent password is 0 or too long. Specify a string or shorter string.

Error 1728	"Function '%1' has invalid parameter '%2' ('%3')"
Constant	SLERR_INVALID_PARAMETER_W_PARM
SAP Sybase Error Number	3408
SQL State	2FW93
SQL Code	-1728L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1728	"Function '%1' has invalid parameter '%2' ('%3')"
Severity Code	<i>16</i> on page 2
Parameter 1	The name of the function.
Parameter 2	The name of the parameter.
Parameter 3	Information about the parameter that caused the error.
Probable Cause	An error occurred while evaluating a parameter.

Error 1000000	"ESCAPES option must be OFF. %1 "
Constant	EMSG_INVALIDQUOTESESCAPES
SAP Sybase Error Number	20660
SQL State	QDA00
SQL Code	-1000000L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	Sybase IQ only supports 'LOAD TABLE' commands where the ESCAPES options must be OFF.

Error 1000002	"Cannot get the index id for %2 from the catalog. %1 "
Constant	EMSG_CAT_CANTGETINDEXID
SAP Sybase Error Number	20662
SQL State	QDA02
SQL Code	-1000002L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>23</i> on page 2
Parameter 1	location of the exception
Parameter 2	index id

Error 1000002	"Cannot get the index id for %2 from the catalog. %1"
Probable Cause	This is an internal error. Join processing is not able to find an index in the catalog. If this error occurs, it should be reported to Sybase.

Error 1000003	"Cross-database joins are not supported. (%2 and %3) %1"
Constant	EMSG_CAT_CROSSDBJOIN
SAP Sybase Error Number	20663
SQL State	QDA03
SQL Code	-1000003L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Fully qualified name of table specified in join.
Parameter 3	Fully qualified name of table specified in join.
Probable Cause	Cannot join tables from different databases.

Error 1000004	"Index '%2' already exists in the catalog. %1"
Constant	EMSG_CAT_DUPINDEXID
SAP Sybase Error Number	20664
SQL State	QDA04
SQL Code	-1000004L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Name of index that already exists.
Probable Cause	This is an internal error. Join processing is trying to create an index id that already exists. If this error occurs, it should be reported to Sybase.

Error 1000006	"Only %2 NULL specifications on a column are permitted. %1"
Constant	EMSG_TOO_MANY_NULL_STRINGS
SAP Sybase Error Number	20666
SQL State	QDA06
SQL Code	-1000006L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	maximum NULL specifications permitted
Probable Cause	A column specification in a LOAD statement can have a maximum number of NULL clauses.

Error 1000008	"Unknown error. %1"
Constant	EMSG_CAT_UNKNOWN
SAP Sybase Error Number	20668
SQL State	QDA08
SQL Code	-1000008L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	An error condition was encountered for which there is no message. If this error occurs, it should be reported to Sybase.

Messages 1000009 through 1000040

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1000009	"Cannot DISABLE index '%2'. It is open Read/Write and may have updates pending. %1"
Constant	EMSG_CAT_INDEXENABLERW
SAP Sybase Error Number	20669
SQL State	QDA09
SQL Code	-1000009L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Name of the index user is attempting to disable.
Parameter 2	The index the user is attempting to disable.
Probable Cause	This index cannot be DISABLED. It is open for write access and may have updates pending. Wait until no other users are using the index.

Error 1000010	"Cannot DISABLE index '%2'. The index is in use. %1"
Constant	EMSG_CAT_INDEXENABLESINDEX
SAP Sybase Error Number	20670
SQL State	QDA10
SQL Code	-1000010L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Name of the index user is attempting to disable.
Probable Cause	This index cannot be DISABLED. It is in use. Wait until no other users are using the index.

Error 1000011	"Transaction %2 attempted to access '%4' created by transaction %3. %1"
Constant	EMSG_CAT_FUTUREVERSION
SAP Sybase Error Number	20671
SQL State	QDA11
SQL Code	-1000011L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	The current transaction ID.
Parameter 3	The transaction ID that created the object the user is attempting to access.
Parameter 4	table or join index name
Probable Cause	Table Level Versioning doesn't allow access to versions newer than your current transaction ID.

Error 1000012	"Index '%2' cannot be closed because it has %3 users. %1"
Constant	EMSG_CAT_INDEXINUSE
SAP Sybase Error Number	20672
SQL State	QDA12
SQL Code	-1000012L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Name of the index that is being closed.
Parameter 3	The number of users currently using the index.

Error 1000012	"Index '%2' cannot be closed because it has %3 users. %1"
Probable Cause	This is an internal error. The index cannot be closed because it is in use. If this error occurs, it should be reported to Sybase.

Error 1000014	"%2 MB is not sufficient for the load, update, or delete. %1"
Constant	EMSG_INSUFFICIENT_LOAD_MEMORY
SAP Sybase Error Number	20674
SQL State	QDA14
SQL Code	-1000014L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	user specified upper bound on megabytes of heap memory load/delete/update can actually use
Probable Cause	The user can control the amount of heap memory a load/delete/update process (LOAD, INSERT VALUE, DELETE, SYNCHRONIZE, UPDATE) can use via the Load_Memory_MB option. If this memory limit isn't sufficient for the load/delete/update to run, then this exception is raised. To proceed, the user must either turnoff the limit (i.e., set Load_Memory_MB to zero) or increase the limit.

Error 1000018	"The object cannot be opened for DROP or ALTER. It is already open. %1"
Constant	EMSG_CAT_CANNOTOPENFORMETA
SAP Sybase Error Number	20678
SQL State	QDA18
SQL Code	-1000018L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1000018	"The object cannot be opened for DROP or ALTER. It is already open. %1"
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	The object that you have requested to DROP or ALTER cannot be opened for META access. Either the current connection or another connection has a cursor open on the table you are trying to DROP or ALTER or on the table to which the field or index you are trying open for META belongs. In order to proceed, all cursors open on this object must be closed.

Error 1000022	"Index '%2' has an invalid index type: %3. %1"
Constant	EMSG_CAT_INDEXBADTYPE
SAP Sybase Error Number	20682
SQL State	QDA22
SQL Code	-1000022L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	The index which has a bad type.
Parameter 3	The bad index type in question.
Probable Cause	This is an internal error. The index is of a type that is unknown to ASIQ. If this error occurs, it should be reported to Sybase.

Error 1000024	"For table pair %2, table '%3' has a datatype mismatch for column %4. %1"
Constant	EMSG_CAT_JINDEXDATATYPE
SAP Sybase Error Number	20684
SQL State	QDA24
SQL Code	-1000024L
ODBC 2 State	ERROR

Error 1000024	"For table pair %2, table '%3' has a datatype mismatch for column %4. %1"
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	tablename
Parameter 3	table number
Parameter 4	column number
Probable Cause	Corresponding columns' in the table pairs must be of the same datatype. (For example, INTEGER and INTEGER or CHAR and CHAR.) Matching datatypes such as CHAR and VARCHAR or INT and SMALLINT are not allowed.

Error 1000026	"The join virtual table for table '%2' has duplicate columns in positions %3 and %4. %1"
Constant	EMSG_CAT_JINDEXDUPFIELDS
SAP Sybase Error Number	20686
SQL State	QDA26
SQL Code	-1000026L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	tablename
Parameter 3	column position
Parameter 4	column position
Probable Cause	The join virtual table for table has duplicate columns. Perhaps the join predicate is improperly specified.

Error 1000028	"For table pair %2, table '%3' has a length value mismatch for column %4. %1"
Constant	EMSG_CAT_JINDEXKEYSIZE
SAP Sybase Error Number	20688
SQL State	QDA28
SQL Code	-1000028L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	table pair
Parameter 3	table name
Parameter 4	column number
Probable Cause	Corresponding columns in the table pair must be of the same length.

Error 1000029	"Cannot open the requested object for write in the current transaction (%2). Another user has write access in transaction %3. %1"
Constant	EMSG_CAT_ONLY1WRITER
SAP Sybase Error Number	20689
SQL State	QDA29
SQL Code	-1000029L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	The transaction id of the hopeful writer.
Parameter 3	The transaction id of the user currently writing.

Error 1000029	"Cannot open the requested object for write in the current transaction (%2). Another user has write access in transaction %3. %1"
Probable Cause	The ASIQ catalog allows only one transaction at a time to have write access to an object. The id of the user that is currently writing to the object can be found by running sp_iqtransaction and scanning the output for the transaction id of the writer that currently has write access.

Warning 1000030	"\nMaster archive header information\n"
Constant	EMSG__DB_HEADER_MSG1
SAP Sybase Error Number	20690
SQL State	QDA30
SQL Code	1000030L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	1 on page 2
Probable Cause	This is an informational message displayed in context with other messages.

Warning 1000032	"The ultimate/top table is %1\n"
Constant	EMSG_CAT_JINDEXLOADMSGLINKTABLE1
SAP Sybase Error Number	20692
SQL State	00A32
SQL Code	1000032L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	1 on page 2
Parameter 1	table name
Probable Cause	This information message appears in the log when the CREATE JOIN command is executed.

Warning 1000033	"Database: %1"
Constant	EMSG_DB_HEADER_MSG2
SAP Sybase Error Number	20693
SQL State	QDA33
SQL Code	1000033L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>1</i> on page 2
Parameter 1	Database
Probable Cause	This message is displayed in context with other messages.

Warning 1000034	" Table Name Relationship"
Constant	EMSG_CAT_JINDEXLOADMSGLINKTABLE3
SAP Sybase Error Number	20694
SQL State	00A34
SQL Code	1000034L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>1</i> on page 2
Probable Cause	This information message appears in the log when the CREATE JOIN command is executed.

Warning 1000036	"%1. %2 joined to '%3' %4"
Constant	EMSG_CAT_JINDEXLOADMSGTABLE
SAP Sybase Error Number	20696
SQL State	00A36
SQL Code	1000036L
ODBC 2 State	OK
ODBC 3 State	OK

Warning 1000036	"%1. %2 joined to '%3' %4"
Severity Code	<i>1</i> on page 2
Parameter 1	argument 1 comment
Parameter 2	argument 2 comment
Parameter 3	argument 3 comment
Parameter 4	argument 4 comment
Probable Cause	This information message appears in the log when the CREATE JOIN command is executed.

Warning 1000037	"-----"
Constant	EMSG_CAT_JINDEXLOADMSGTRAILER
SAP Sybase Error Number	20697
SQL State	00A37
SQL Code	1000037L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>1</i> on page 2
Probable Cause	This information message appears in the log when the CREATE JOIN command is executed.

Warning 1000038	"Backup date: %1"
Constant	EMSG_DB_HEADER_MSG3
SAP Sybase Error Number	20698
SQL State	QDA38
SQL Code	1000038L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>1</i> on page 2
Parameter 1	backup date

Warning 1000038	"Backup date: %1"
Probable Cause	This message displays the backup date.

Warning 1000039	"Backup created by: %1"
Constant	EMSG_DB_HEADER_MSG4
SAP Sybase Error Number	20699
SQL State	QDA39
SQL Code	1000039L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>1</i> on page 2
Parameter 1	user name
Probable Cause	This message displays the user who created the backup.

Warning 1000040	"Comment: %1"
Constant	EMSG_DB_HEADER_MSG5
SAP Sybase Error Number	20700
SQL State	QDA40
SQL Code	1000040L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>1</i> on page 2
Parameter 1	comment
Probable Cause	This is an informational message displayed in context with other messages.

Messages 1000041 through 1000061

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Warning 1000041	"Backup version: %1"
Constant	EMSG_DB_HEADER_MSG6
SAP Sybase Error Number	20701
SQL State	QDA41
SQL Code	1000041L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	1 on page 2
Parameter 1	backup version
Probable Cause	This message displays the backup version.

Warning 1000042	"Number of archive media in backup: %1"
Constant	EMSG_DB_HEADER_MSG7
SAP Sybase Error Number	20702
SQL State	QDA42
SQL Code	1000042L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	1 on page 2
Parameter 1	number of archive media in backup
Probable Cause	This message displays how many media are in the backup.

Warning 1000043	"Number of files in backup: %1"
Constant	EMSG_DB_HEADER_MSG8
SAP Sybase Error Number	20703
SQL State	QDA43

Warning 1000043	"Number of files in backup: %1"
SQL Code	1000043L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	1 on page 2
Parameter 1	number of files in backup
Probable Cause	This message displays the number of files in the backup.

Error 1000044	"The join for table '%2' does not have enough columns defined (%3). %1"
Constant	EMSG_CAT_JINDEXNOFIELDS
SAP Sybase Error Number	20704
SQL State	QDA44
SQL Code	-1000044L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	table name
Parameter 3	number of columns
Probable Cause	Cannot define a join with zero columns. If this error occurs, it should be reported to Sybase.

Error 1000045	"Index %2 does not exist. %1"
Constant	EMSG_UTILITY_INDEXNOTFOUND
SAP Sybase Error Number	20705
SQL State	QDA45
SQL Code	-1000045L
ODBC 2 State	ERROR

Error 1000045	"Index %2 does not exist. %1"
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	index name given by the user
Probable Cause	User has specified an index which does not exist in any table within the current database.

Error 1000046	"No Field passed to PutMCIField. %1"
Constant	EMSG_CAT_NOFIELDPUTMCI
SAP Sybase Error Number	20706
SQL State	QDA46
SQL Code	-1000046L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	This error should not occur during normal operation and should be reported to Sybase. See the iqmsg file for additional diagnostic information.

Error 1000047	"For table pair %2, table '%3' has a precision mismatch in column %4. %1"
Constant	EMSG_CAT_JINDEXPRECISION
SAP Sybase Error Number	20707
SQL State	QDA47
SQL Code	-1000047L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2

Error 1000047	"For table pair %2, table '%3' has a precision mismatch in column %4. %1"
Parameter 1	location of the exception
Parameter 2	table pair
Parameter 3	table name
Parameter 4	column number
Probable Cause	Corresponding columns in the join must have equal precision.

Error 1000048	"For table pair %2, table '%3' has a scale mismatch in column %4. %1"
Constant	EMSG_CAT_JINDEXSCALE
SAP Sybase Error Number	20708
SQL State	QDA48
SQL Code	-1000048L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	table pair
Parameter 3	table name
Parameter 4	column number
Probable Cause	Corresponding columns in the join must have equal scale.

Error 1000049	""%2' is being used in a self join. Self joins are not allowed. %1"
Constant	EMSG_CAT_JINDEXSELFJOIN
SAP Sybase Error Number	20709
SQL State	QDA49
SQL Code	-1000049L
ODBC 2 State	ERROR

Error 1000049	""%2' is being used in a self join. Self joins are not allowed. %1"
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	table name
Probable Cause	Self joins are not allowed.

Error 1000050	"Table '%2' is used in the join twice. %1"
Constant	EMSG_CAT_JINDEXTABLETWICE
SAP Sybase Error Number	20710
SQL State	QDA50
SQL Code	-1000050L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	tablename
Probable Cause	A table cannot be used twice in a join.

Error 1000051	"Cannot retrieve a row from the SYSIQJOINIXTABLE system table. %1"
Constant	EMSG_CAT_JIXTABLEFIND
SAP Sybase Error Number	20711
SQL State	QDA51
SQL Code	-1000051L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2

Error 1000051	"Cannot retrieve a row from the SYSIQJOINIXTABLE system table. %1"
Parameter 1	location of the exception
Probable Cause	This is an internal error. Cannot retrieve a row from the SYSIQJOINIXTABLE system table. If this error occurs, it should be reported to Sybase.

Error 1000052	"Cannot delete a row from the SYSIQJOINIXTABLE system table. %1"
Constant	EMSG_CAT_JIXTABLEDELETE
SAP Sybase Error Number	20712
SQL State	QDA52
SQL Code	-1000052L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Probable Cause	This is an internal error. Cannot delete a row from the SYSIQJOINIXTABLE system table. If this error occurs, it should be reported to Sybase.

Error 1000053	"Cannot commit changes to the SYSIQJOINIXTABLE system table. %1"
Constant	EMSG_CAT_JIXTABLEFLUSH
SAP Sybase Error Number	20713
SQL State	QDA53
SQL Code	-1000053L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception

Error 1000053	"Cannot commit changes to the SYSIQJOINIXTABLE system table. %1"
Probable Cause	This is an internal error. Cannot commit changes to the SYSIQJOINIXTABLE system table. If this error occurs, it should be reported to Sybase.

Error 1000054	"Cannot open %2 in Meta (exclusive) mode. Object is already open. %1"
Constant	EMSG_CAT_METAACCESS
SAP Sybase Error Number	20714
SQL State	QDA54
SQL Code	-1000054L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	object name
Probable Cause	The object cannot be opened for exclusive access; it is already open.

Warning 1000055	"Warning: %1"
Constant	EMSG_CLBK_WARNING
SAP Sybase Error Number	20715
SQL State	01A55
SQL Code	1000055L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	explanation of %1
Probable Cause	This message appears in context with other messages.

Error 1000056	"Cannot convert from datatype '%2' to '%3' for column '%4'. %1"
Constant	EMSG_CAT_NOCONVERSIONPOSSIBLE
SAP Sybase Error Number	20716
SQL State	QDA56
SQL Code	-1000056L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	datatype
Parameter 3	datatype
Parameter 4	column name
Probable Cause	Implicit conversion for this column is not possible.

Error 1000057	"Column '%2' has an unknown datatype: '%3'. %1"
Constant	EMSG_CAT_NODATATYPE
SAP Sybase Error Number	20717
SQL State	QDA57
SQL Code	-1000057L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	column number
Parameter 3	the unknown datatype
Probable Cause	The column is of a datatype that is unknown to ASIQ. This is an internal error. If this error occurs, it should be reported to Sybase.

Warning 1000058	"Platform: %1"
Constant	EMSG_DB_HEADER_MSG9
SAP Sybase Error Number	20718
SQL State	QDA58
SQL Code	1000058L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	1 on page 2
Parameter 1	platform
Probable Cause	This is an informational message reporting the platform type.

Error 1000060	"Column '%2', PRECISION (%3) cannot be greater than %4. %1"
Constant	EMSG_CAT_PRECISIONTOOBIG
SAP Sybase Error Number	20720
SQL State	QDA60
SQL Code	-1000060L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	column number
Parameter 3	requested precision
Parameter 4	maximum allowed precision
Probable Cause	The precision requested by the user is larger than what is allowed for the datatype.

Error 1000061	"Column %2, PRECISION (%3) cannot be less than 0. %1"
Constant	EMSG_CAT_PRECISIONTOOSMALL

Error 1000061	"Column %2, PRECISION (%3) cannot be less than 0. %1"
SAP Sybase Error Number	20721
SQL State	QDA61
SQL Code	-1000061L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	column name
Parameter 3	column precision
Probable Cause	The precision specified by the user is less than zero.

Messages 1000062 through 1000084

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1000062	"Cannot add column '%3' with 'not null' constraint on table %2 with data. %1"
Constant	EMSG_TABLEHASDATA
SAP Sybase Error Number	20722
SQL State	QDC35
SQL Code	-1000062L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	table name
Parameter 3	column name

Error 1000062	"Cannot add column '%3' with 'not null' constraint on table %2 with data. %1"
Probable Cause	The user tried to ALTER ADD a NOT NULL column to a table that has data. The newly added column would violate the NOT NULL constraint as it would have null data.
Error 1000063	"Cannot enforce the NOT NULL constraint. Column %2 has NULL data. %1"
Constant	EMSG_COLUMNHASNULLDATA
SAP Sybase Error Number	20723
SQL State	QDC34
SQL Code	-1000063L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	column name
Probable Cause	The user tried ALTER MODIFY column NOT NULL on a column that used to allow nulls and has null data. The user has to first delete the null rows before altering the column to enforce the NOT NULL constraint.
Error 1000064	"Column %2 can not be altered because it participates in join %3. %1"
Constant	EMSG_CAT_JOINFIELDINPREJOIN
SAP Sybase Error Number	20724
SQL State	QDA64
SQL Code	-1000064L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the error

Error 1000064	"Column %2 can not be altered because it participates in join %3. %1"
Parameter 2	columns
Parameter 3	join
Probable Cause	A column/field that participates in a join cannot be altered. Joins on this field must be deleted before an ALTER can be performed.

Error 1000065	"Table %2 must be owned by the creator of the join. %1"
Constant	EMSG_CAT_TABLEOWNERDIFF
SAP Sybase Error Number	20725
SQL State	QDA65
SQL Code	-1000065L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the error
Parameter 2	tablename
Probable Cause	This error message is given during CREATE JOIN when one of the tables specified is not owned by the owner of the join. Joins can only be created from tables of the same owner.

Error 1000066	"ALTER on the column would interfere with the natural join to table %2 in join %3. %1"
Constant	EMSG_CAT_JOINFIELDNATMAT
SAP Sybase Error Number	20726
SQL State	QDA66
SQL Code	-1000066L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the error

Error 1000066	"ALTER on the column would interfere with the natural join to table %2 in join %3. %1"
Parameter 2	tablename
Parameter 3	join
Probable Cause	This message is displayed when using the ALTER command or adding columns to a table that participates in a join.

Error 1000067	"Table '%2' is not defined in the catalog. %1"
Constant	EMSG_CAT_TABLENOTINCAT
SAP Sybase Error Number	20727
SQL State	QDA67
SQL Code	-1000067L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	tablename
Probable Cause	This is an internal error. The table does not exist in the catalog. If this error occurs, it should be reported to Sybase.

Warning 1000069	" %1; %2 blocks; %3"
Constant	EMSG_DB_HEADER_MSG10
SAP Sybase Error Number	20729
SQL State	QDA69
SQL Code	1000069L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	1 on page 2
Parameter 1	argument 1 comment
Parameter 2	argument 2 comment

Warning 1000069	" %1; %2 blocks; %3"
Parameter 3	argument 3 comment
Probable Cause	This message is an informational message displayed in context with other messages.

Warning 1000070	"File listing:"
Constant	EMSG_DB_HEADER_MSG11
SAP Sybase Error Number	20730
SQL State	QDA70
SQL Code	1000070L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>1</i> on page 2
Probable Cause	This message is an informational message displayed in context with other messages.

Warning 1000071	" %1"
Constant	EMSG_DB_HEADER_MSG14
SAP Sybase Error Number	20731
SQL State	QDA71
SQL Code	1000071L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>1</i> on page 2
Parameter 1	argument 1 comment
Probable Cause	This message is an informational message displayed in context with other messages.

Warning 1000072	"Hole listing (%1):"
Constant	EMSG_DB_HEADER_MSG20

Warning 1000072	"Hole listing (%1):"
SAP Sybase Error Number	20732
SQL State	QDA72
SQL Code	1000072L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>1</i> on page 2
Parameter 1	argument 1 comment
Probable Cause	This message is an informational message displayed in context with other messages.

Warning 1000073	" start: %1; size: %2"
Constant	EMSG_DB_HEADER_MSG21
SAP Sybase Error Number	20733
SQL State	QDA73
SQL Code	1000073L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>1</i> on page 2
Parameter 1	Parameter 1 description
Parameter 2	Parameter 2 description
Probable Cause	This message is displayed in context with other messages.

Warning 1000074	"Offset %1 Length %2, %3%4%5"
Constant	EMSG_PREVIEWFILLER
SAP Sybase Error Number	20734
SQL State	QDA74
SQL Code	1000074L
ODBC 2 State	ERROR

Warning 1000074	"Offset %1 Length %2, %3%4%5"
ODBC 3 State	ERROR
Severity Code	/ on page 2
Parameter 1	Parameter 1 description
Parameter 2	Parameter 2 description
Parameter 3	Parameter 3 description
Parameter 4	Parameter 4 description
Parameter 5	Parameter 5 description
Probable Cause	This message is displayed in context with other messages.

Warning 1000075	"%1, %2%3%4"
Constant	EMSG_PREVIEWFILLER1
SAP Sybase Error Number	20735
SQL State	QDA75
SQL Code	1000075L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	/ on page 2
Parameter 1	Parameter 1 description
Parameter 2	Parameter 2 description
Parameter 3	Parameter 3 description
Parameter 4	Parameter 4 description
Probable Cause	This message is displayed in context with other messages.

Warning 1000076	"%1, %2%3%4"
Constant	EMSG_PREVIEWFILLER2
SAP Sybase Error Number	20736
SQL State	QDA76
SQL Code	1000076L

Warning 1000076	"%1, %2%3%4"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>1</i> on page 2
Parameter 1	Parameter 1 description
Parameter 2	Parameter 2 description
Parameter 3	Parameter 3 description
Parameter 4	Parameter 4 description
Probable Cause	This message is displayed in context with other messages.

Warning 1000077	"%1, %2%3%4"
Constant	EMSG_PREVIEWFILLER4
SAP Sybase Error Number	20737
SQL State	QDA77
SQL Code	1000077L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>1</i> on page 2
Parameter 1	Parameter 1 description
Parameter 2	Parameter 2 description
Parameter 3	Parameter 3 description
Parameter 4	Parameter 4 description
Probable Cause	This message is displayed in context with other messages.

Error 1000078	"IQ PAGE SIZE of '%2' for database '%3' is not valid. %1"
Constant	EMSG_HDB_INVALIDPAGESIZE
SAP Sybase Error Number	20738
SQL State	QDA78
SQL Code	-1000078L

Error 1000078	"IQ PAGE SIZE of '%2' for database '%3' is not valid. %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	requested PAGE SIZE
Parameter 3	database name
Probable Cause	An invalid IQ PAGE SIZE was specified. IQ PAGE SIZE must be one of 1024, 2048, 4096, 8192, 16384, 32768, 65536, 131072, 262144, 524288. See the Reference Manual and Admin and Performance Guide for IQ PAGE SIZE recommendations.

Error 1000079	"IQ SIZE of '%2' for database '%3' is not valid. %1"
Constant	EMSG_HDB_INVALIDDATABASESIZE
SAP Sybase Error Number	20739
SQL State	QDA79
SQL Code	-1000079L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	requested IQ SIZE
Parameter 3	database name
Probable Cause	The maximum IQ SIZE is 128GB.

Error 1000082	"The insert must contain all of the table %2 columns because it participates in one or more joins. %1"
Constant	EMSG_INSRT_MUSTBE_FULLWIDTH
SAP Sybase Error Number	20742
SQL State	QDA82

Error 1000082	"The insert must contain all of the table %2 columns because it participates in one or more joins. %1"
SQL Code	-1000082L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	table name
Probable Cause	If a table participates in a join, then the user cannot load data into that table using a partial width insert.

Error 1000083	"The field array entry must be given a name. %1"
Constant	EMSG_HDB_FIELDNONAME
SAP Sybase Error Number	20743
SQL State	QDA83
SQL Code	-1000083L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000084	"The %2th join field array entry for table '%3' must have a name. %1"
Constant	EMSG_HDB_FIELDNOJOINNAME
SAP Sybase Error Number	20744
SQL State	QDA84
SQL Code	-1000084L
ODBC 2 State	ERROR

Error 1000084	"The %2th join field array entry for table '%3' must have a name. %1"
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	field array entry
Parameter 3	tablename
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Messages 1000085 through 1000107

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1000085	"The join field array for table '%2' must have at least one entry. %1"
Constant	EMSG_HDB_FIELDNOJOINNAMES
SAP Sybase Error Number	20745
SQL State	QDA85
SQL Code	-1000085L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	tablename
Probable Cause	This an internal error. If this error occurs, it should be reported to Sybase.

Warning 1000086	"Length %1 %2%3%4"
Constant	EMSG_PREVIEWFILLERA
SAP Sybase Error Number	20746

Warning 1000086	"Length %1 %2%3%4"
SQL State	QDA86
SQL Code	1000086L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>1</i> on page 2
Parameter 1	Parameter 1 description
Parameter 2	Parameter 2 description
Parameter 3	Parameter 3 description
Parameter 4	Parameter 4 description
Probable Cause	This is an informational message displayed in context with other messages.

Warning 1000087	"Delimiter %1 %2%3%4"
Constant	EMSG_PREVIEWFILLERCD
SAP Sybase Error Number	20747
SQL State	QDA87
SQL Code	1000087L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>1</i> on page 2
Parameter 1	delimiter name
Parameter 2	Parameter 2 description
Parameter 3	Parameter 3 description
Parameter 4	Parameter 4 description
Probable Cause	This is an informational message displayed in context with other messages.

Warning 1000088	"Offset %1, Length %2, %3 nulls, %4%5%6 %7"
Constant	EMSG_PREVIEWOFFSET
SAP Sybase Error Number	20748
SQL State	QDA88
SQL Code	1000088L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	1 on page 2
Parameter 1	offset
Parameter 2	length
Parameter 3	nulls
Parameter 4	parameter 4 description
Parameter 5	parameter 5 description
Parameter 6	parameter 6 description
Parameter 7	parameter 7 description
Probable Cause	This is an informational message displayed in context with other messages.

Warning 1000089	"Length %1, %2 nulls, %3%4%5 %6"
Constant	EMSG_PREVIEWLENGTH
SAP Sybase Error Number	20749
SQL State	QDA89
SQL Code	1000089L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	1 on page 2
Parameter 1	length
Parameter 2	nulls

Warning 1000089	"Length %1, %2 nulls, %3%4%5 %6"
Parameter 3	parameter 3 description
Parameter 4	parameter 4 description
Parameter 5	parameter 5 description
Parameter 6	parameter 6 description
Probable Cause	This is an informational message displayed in context with other messages.

Warning 1000090	"%1, %2 nulls, %3%4%5 %6"
Constant	EMSG_PREVIEWPREFIX1
SAP Sybase Error Number	20750
SQL State	QDA90
SQL Code	1000090L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	1 on page 2
Parameter 1	length
Parameter 2	nulls
Parameter 3	parameter 3 description
Parameter 4	parameter 4 description
Parameter 5	parameter 5 description
Parameter 6	parameter 6 description
Probable Cause	This is an informational message displayed in context with other messages.

Warning 1000091	"%1, %2 nulls, %3%4%5 %6"
Constant	EMSG_PREVIEWPREFIX2
SAP Sybase Error Number	20751
SQL State	QDA91

Warning 1000091	"%1, %2 nulls, %3%4%5 %6"
SQL Code	1000091L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	1 on page 2
Parameter 1	length
Parameter 2	nulls
Parameter 3	parameter 3 description
Parameter 4	parameter 4 description
Parameter 5	parameter 5 description
Parameter 6	parameter 6 description
Probable Cause	This is an informational message displayed in context with other messages.

Error 1000092	"Table %2 must have a name for the join field array. %1"
Constant	EMSG_HDB_TABLENOJOINNAME
SAP Sybase Error Number	20752
SQL State	QDA92
SQL Code	-1000092L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for %2
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Warning 1000093	"%1, %2 nulls, %3%4%5 %6"
Constant	EMSG_PREVIEWPREFIX4

Warning 1000093	"%1, %2 nulls, %3%4%5 %6"
SAP Sybase Error Number	20753
SQL State	QDA93
SQL Code	1000093L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>1</i> on page 2
Parameter 1	Parameter 1 description
Parameter 2	Parameter 2 description
Parameter 3	Parameter 3 description
Parameter 4	Parameter 4 description
Parameter 5	Parameter 5 description
Parameter 6	Parameter 6 description
Probable Cause	This is an informational message displayed in context with other messages.

Error 1000094	"Sufficient memory cannot be found for the LOAD. Increasing the Load_Memory_MB or decreasing the BLOCK FACTOR or BLOCK SIZE will allow the LOAD to proceed. %1"
Constant	EMSG_BLOCK_FACTOR_SIZE_LOAD_MEMORY
SAP Sybase Error Number	20754
SQL State	QDA94
SQL Code	-1000094L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	Location of the exception.

Error 1000094	"Sufficient memory cannot be found for the LOAD. Increasing the Load_Memory_MB or decreasing the BLOCK FACTOR or BLOCK SIZE will allow the LOAD to proceed. %1"
Probable Cause	When the user explicitly sets Load_Memory_MB, the LOAD process applies various heuristics for load parameters in an attempt to find a combination such that the memory required is not more than what the user specified. For a fixed width LOAD, BLOCK FACTOR indicates the minimal number of rows that must be read into memory for each read. The default BLOCK FACTOR is 10,000. Decreasing the BLOCK FACTOR will make the LOAD's internal memory requirements smaller. For a variable length input LOAD, BLOCK SIZE represents the size in bytes in which input data should be read. The default BLOCK SIZE is 500,000 bytes. Decreasing the BLOCK SIZE for a variable width input load will reduce LOAD's memory requirements. Alternatively, the Load_Memory_MB option setting could be raised.

Warning 1000096	"Delimiter %1 %2 nulls, %3%4%5 %6"
Constant	EMSG_PREVIEWCD
SAP Sybase Error Number	20756
SQL State	QDA96
SQL Code	1000096L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	1 on page 2
Parameter 1	delimiter
Parameter 2	nulls
Parameter 3	parameter 3 description
Parameter 4	parameter 4 description
Parameter 5	parameter 5 description
Parameter 6	parameter 6 description
Probable Cause	This is an informational message displayed in context with other messages.

Error 1000097	"Parse Error in Command String at '%2'. %1"
Constant	EMSG_PARSEERROR
SAP Sybase Error Number	20757
SQL State	QDA97
SQL Code	-1000097L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	Start of the parse error
Probable Cause	Consult the IQ reference manual for the DBCC grammar

Error 1000099	"The PAGE SIZE divided by the BLOCK SIZE must be equal to 2, 4, 8, or 16. DATABASE: %2 PAGE SIZE: %3 BLOCK SIZE: %4 %1"
Constant	EMSG_HDB_INVALIDCHUNKSIZE
SAP Sybase Error Number	20759
SQL State	QDA99
SQL Code	-1000099L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	database name
Parameter 3	page size
Parameter 4	block size
Probable Cause	(PAGE SIZE)/(BLOCK SIZE) must be one of 2, 4, 8, 16. Adjust the PAGE SIZE or the BLOCK SIZE in the CREATE DATABASE statement.

Error 1000100	"Cannot INSERT, LOAD, or UPDATE a join virtual table. %1"
Constant	EMSG_SQL_NOINSERTJVT
SAP Sybase Error Number	20760
SQL State	QDB00
SQL Code	-1000100L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	The user is not allowed to INSERT to or LOAD a join virtual table. Instead you must INSERT to or LOAD the tables which participate in the join and and execute the SYNCHRONIZE command.

Error 1000101	"%2 not supported by Sybase IQ. %1"
Constant	EMSG_SQL_STMT_NOTSUPPORTED
SAP Sybase Error Number	20761
SQL State	QDB01
SQL Code	-1000101L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	sql statement type
Parameter 2	location of the exception
Probable Cause	The statement in question is not supported by Sybase IQ.

Error 1000103	"Cannot find an index for field '%2'. Every field must have at least one index. Current IndexCount = %3. %1"
Constant	EMSG_CAT_FIELD_HAS_NOINDEX
SAP Sybase Error Number	20763

Error 1000103	"Cannot find an index for field '%2'. Every field must have at least one index. Current IndexCount = %3. %1"
SQL State	QDB03
SQL Code	-1000103L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Field name
Parameter 2	Number of indexes found for the named field.
Parameter 3	location of the exception
Probable Cause	This error should not occur during normal operation. Every field in ASIQ will have at least one index (the automatically generated FP index). This error occurs, the operation should be retried. If the error persists, it should be reported to Sybase. Extra information may have been output to the iqmsg file.

Warning 1000104	"in join virtual table '%1'%2"
Constant	EMSG_DELETE_CBTNAMEJOIN
SAP Sybase Error Number	20764
SQL State	01B04
SQL Code	1000104L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	Parameter 1 description
Parameter 2	Parameter 2 description
Probable Cause	This is an informational message displayed in context with other messages.

Warning 1000105	"%1"
Constant	EMSG_DELETE_CBTNAME1TABLE

Warning 1000105	"%1"
SAP Sybase Error Number	20765
SQL State	01B05
SQL Code	1000105L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	Parameter 1 description
Probable Cause	This is an informational message displayed in context with other messages.

Error 1000106	"Local temporary table, %2, must be committed in order to create an index. %1"
Constant	EMSG_CAT_CANNOT_CREATEIDX_ONLTT
SAP Sybase Error Number	20766
SQL State	QDB06
SQL Code	-1000106L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception.
Parameter 2	Tablename
Probable Cause	To be able to create an index for a local temporary table, the table must be in a committed state. If this message occurs, the user has tried to execute a CREATE INDEX on a local temporary table that has had data inserted, deleted, or updated that has not yet been committed.

Warning 1000107	"For table '%1' in join virtual table '%2', \n%3 left outer rows with %4 columns will be moved (inserted/deleted).\n"
Constant	EMSG_DELETE_CBTLOUTERROWSMOVED

Warning 1000107	"For table '%1' in join virtual table '%2', \n%3 left outer rows with %4 columns will be moved (inserted/deleted).\n"
SAP Sybase Error Number	20767
SQL State	01B07
SQL Code	1000107L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	tablename
Parameter 2	join virtual table
Parameter 3	number of rows moved
Parameter 4	number of columns
Probable Cause	This is an informational message displayed in context with other messages. The message displays the number of rows moved during an insert to or delete from a join.

Messages 1000108 through 1000133

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Warning 1000108	"The DELETE where clause yielded %1 rows, but table '%2' has no data."
Constant	EMSG_DELETE_TABLENODATA
SAP Sybase Error Number	20768
SQL State	01B08
SQL Code	1000108L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	number of rows
Parameter 2	tablename

Warning 1000108	"The DELETE where clause yielded %1 rows, but table '%2' has no data."
Probable Cause	This is an internal error. This warning should not occur during normal use. If this error occurs, it should be reported to Sybase.

Error 1000110	"The wrong SIndex has been opened for a fast projection index. %1"
Constant	EMSG_CAT_WRONGSINDEX
SAP Sybase Error Number	20770
SQL State	QDB10
SQL Code	-1000110L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Probable Cause	This is an internal error and should not occur. Diagnostic information has been output to the iqmsg file. If the error occurs, it should be reported to Sybase. The operation that caused the error may be tried again.

Error 1000111	"The wrong FP Index has been opened for a field. %1"
Constant	EMSG_CAT_WRONGFPOOPENED
SAP Sybase Error Number	20771
SQL State	QDB11
SQL Code	-1000111L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.

Error 1000111	"The wrong FP Index has been opened for a field. %1"
Probable Cause	This is an internal error and should not occur. Diagnostic information has been output to the iqmsg file. If the error occurs, it should be reported to Sybase. The operation that caused the error may be tried again.

Error 1000112	"The EBM on the field's columnDescriptor does not match the column EBM on the FPIndex. %1"
Constant	EMSG_CAT_EBMSDONTMATCH
SAP Sybase Error Number	20772
SQL State	QDB12
SQL Code	-1000112L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Probable Cause	This is an internal error and should not occur. Diagnostic information has been output to the iqmsg file. If the error occurs, it should be reported to Sybase. The operation that caused the error may be tried again.

Error 1000113	"Field %2 does not have an FP index. %1"
Constant	EMSG_CAT_FIELD_HAS_NOFPINDEX
SAP Sybase Error Number	20773
SQL State	QDB13
SQL Code	-1000113L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Parameter 2	Field name.

Error 1000113	"Field %2 does not have an FP index. %1"
Probable Cause	This error should not occur during normal operation. Every field has an FP index which is created automatically when the field is created. If the error occurs, diagnostic information will be output to the iqmsg file and the operation that caused it may be tried again. If the problem persists, the server should be shutdown and restarted. An occurrence of this error should be reported to Sybase.
Error 1000114	"CMP index can only be created on two distinct columns having identical datatypes. %1"
Constant	EMSG_CMP_NOT_ON_TWOCOLUMNS
SAP Sybase Error Number	20774
SQL State	QDB14
SQL Code	-1000114L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	A CMP index is an index that can be only created on two columns. You cannot create a single column CMP index; nor can you create a CMP index on three or more columns. Furthermore, when specifying two columns, the two columns must have identical datatypes.
Warning 1000117	"The data to be inserted into table '%2', column '%1' cannot be converted to the datatype of the column. NULL will be inserted if the column allows NULLs."
Constant	EMSG_CANNOT_CONVERT_FOR_INSERT
SAP Sybase Error Number	20777
SQL State	00B17
SQL Code	1000117L
ODBC 2 State	OK
ODBC 3 State	OK

Warning 1000117	"The data to be inserted into table '%2', column '%1' cannot be converted to the datatype of the column. NULL will be inserted if the column allows NULLs."
Severity Code	<i>1 on page 2</i>
Parameter 1	The table that is being inserted to.
Parameter 2	The column that is being inserted to.
Probable Cause	The database option <code>CONVERSION_ERROR</code> has been set to 'OFF' for this INSERT. The data to be inserted to the named column cannot be converted to the datatype of that column. If the column allows NULL, then NULL will be inserted instead.
Warning 1000119	"The data to be inserted into table '%2', column '%1' from row %3 of the select results cannot be converted to the datatype of the destination column. NULL will be inserted if the column allows NULLs."
Constant	<code>EMSG_CANNOT_CONVERT_FOR_INSERT_SELECT</code>
SAP Sybase Error Number	20779
SQL State	00B19
SQL Code	1000119L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>1 on page 2</i>
Parameter 1	The table being inserted to.
Parameter 2	The column being inserted to.
Parameter 3	The row number in the SELECT results that contains the data that cannot be converted.
Probable Cause	The database option <code>CONVERSION_ERROR</code> has been set to 'OFF' for this INSERT...SELECT. During INSERT...SELECT, the data to be inserted to one of the columns cannot be converted to the datatype of that column. If the column allows NULL, then NULL will be inserted instead.
Error 1000120	"Join %2 was not found in the catalog. %1"
Constant	<code>EMSG_DELETE_NOJOINTABLE</code>

Error 1000120	"Join %2 was not found in the catalog. %1"
SAP Sybase Error Number	20780
SQL State	QDB20
SQL Code	-1000120L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	join virtual table name
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000121	"binary data not supported on data longer than 32767 %2, %1"
Constant	EMSG_BINARYINPUTTOOLARGE
SAP Sybase Error Number	20781
SQL State	QDB21
SQL Code	-1000121L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	SA parse source code line
Probable Cause	The user has input a binary string that is too wide

Warning 1000122	"The data to update table '%2', column '%1' cannot be converted to the datatype of the destination column for update number %3 to the table. NULL will be inserted if the column allows NULLs."
Constant	EMSG_CANNOT_CONVERT_FOR_UPDATE

Warning 1000122	"The data to update table '%2', column '%1' cannot be converted to the datatype of the destination column for update number %3 to the table. NULL will be inserted if the column allows NULLs."
SAP Sybase Error Number	20782
SQL State	00B22
SQL Code	1000122L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	1 on page 2
Parameter 1	The table being updated.
Parameter 2	The column being updated.
Parameter 3	The n'th update to the table.
Probable Cause	The database option <code>CONVERSION_ERROR</code> has been set to 'OFF' for this UPDATE. During UPDATE, the data to update one of the columns cannot be converted to the datatype of the column. The update number represents the number of updates made to the table which is not necessarily the row number of the table being updated. The column will be updated with NULL if the column definition allows NULLs.

Error 1000123	"Index '%2' cannot be created. Multicolumn indexes must be created using distinct columns. %1"
Constant	EMSG_MCINDEX_NEEDS_DISTINCT_COLS
SAP Sybase Error Number	20783
SQL State	QDB23
SQL Code	-1000123L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	The name of the index being created.
Parameter 2	Location of the exception.

Error 1000123	"Index '%2' cannot be created. Multicolumn indexes must be created using distinct columns. %1"
Probable Cause	Multicolumn indexes must be created using distinct columns. That is, you cannot use the same column more than once when creating a multicolumn index.
Error 1000124	"Function or Operator not supported on data longer than %2 bytes. %1"
Constant	EMSG_BINARYINPUTFIELDTOOLARGE
SAP Sybase Error Number	20784
SQL State	QDB24
SQL Code	-1000124L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	number of bytes
Probable Cause	The user has entered a binary string that is too wide.
Error 1000126	"This database must be upgraded. %1"
Constant	EMSG_VERSION_2OLD
SAP Sybase Error Number	20786
SQL State	QDB26
SQL Code	-1000126L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Probable Cause	This database must be upgraded with the ALTER DATABASE UPGRADE command in order to continue.

Error 1000127	"The LIMIT specified, '%2', is too large. %1"
Constant	EMSG_SQL_LIMIT_INVALIDSIZE
SAP Sybase Error Number	20787
SQL State	QDB27
SQL Code	-1000127L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Parameter 2	The LIMIT that was entered.
Probable Cause	The LIMIT entered is too large. The LIMIT entered on the command line must be between 0 and 4294967295. However, this limitation is only for the LIMIT clause in the sql command. See the ASIQ Reference Manual for the actual, valid LIMIT size.

Warning 1000129	"%1 row(s) deleted from index '%2' in %3 seconds."
Constant	EMSG_DELETE_INDEX_A
SAP Sybase Error Number	20789
SQL State	QDB29
SQL Code	1000129L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	Number of rows
Parameter 2	index name
Parameter 3	number of seconds to complete the operation
Probable Cause	This is an informational message displayed after a delete.

Warning 1000130	"%1 row(s) deleted from index '%2' on field '%3', %4 seconds."
Constant	EMSG_DELETE_1INDEX
SAP Sybase Error Number	20790
SQL State	01B30
SQL Code	1000130L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	Number of rows
Parameter 2	index name
Parameter 3	field name
Parameter 4	number of seconds to complete the operation
Probable Cause	This is an informational message displayed after a delete.

Error 1000131	"The DELIMITED BY and LIMIT options are valid for WD indexes only. %1"
Constant	EMSG_OPTION_FOR_WDINDEX_ONLY
SAP Sybase Error Number	20791
SQL State	QDB31
SQL Code	-1000131L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Probable Cause	The DELIMITED BY and LIMIT options may be used only when creating a WD (WORD) index.

Error 1000132	"In table '%2', the START ROW ID value (%3) must be greater than %4. Data has already been inserted at this location. %1"
Constant	EMSG_INSRT_BADSTARTRECID
SAP Sybase Error Number	20792
SQL State	QDB32
SQL Code	-1000132L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	tablename
Parameter 3	requested START ROW ID value
Parameter 4	row id value
Probable Cause	You have entered an incorrect START ROW ID and are trying to insert into a column that already contains data. See the Administration and Performance Guide's chapter Moving Data in and out of Databases. The section on partial width inserts contains information regarding the START ROW ID option.

Error 1000133	"During the LOAD into table '%2', the LOAD statement's column count (%3) must be between 1 and %4. Check the LOAD statement's 'load-specification'. %1"
Constant	EMSG_INSRT_COLUMNCOUNT
SAP Sybase Error Number	20793
SQL State	QDB33
SQL Code	-1000133L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2

Error 1000133	"During the LOAD into table '%2', the LOAD statement's column count (%3) must be between 1 and %4. Check the LOAD statement's 'load-specification'. %1"
Parameter 1	location of the exception
Parameter 2	tablename
Parameter 3	number of columns attempting to insert to
Parameter 4	number of columns in the table.
Probable Cause	The number of columns you are trying to insert to is not consistent with the number of columns specified in the LOAD statement's 'load-specification'. You must specify by name each column you are attempting to insert to via the LOAD statement.

1000134 - 1000328

Messages 1000134 through 1000154

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1000134	"Column '%2' is being inserted into twice by this INSERT command. %1"
Constant	EMSG_INSRT_DUPFIELD
SAP Sybase Error Number	20794
SQL State	QDB34
SQL Code	-1000134L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	column name
Probable Cause	The specified column was listed twice in the insert command.

Error 1000135	"Cannot open the existence list for table '%2'. %1"
Constant	EMSG_INSRT_EXISTENCEBM
SAP Sybase Error Number	20795
SQL State	QDB35
SQL Code	-1000135L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	tablename
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000136	"A mismatch exists between the existence bitmaps in the insert object. %1"
Constant	EMSG_INSRT_EXISTENCEMISMATCH
SAP Sybase Error Number	20796
SQL State	QDB36
SQL Code	-1000136L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000137	"While inserting, table '%2' already had a Complete started. %1"
Constant	EMSG_INSRT_HADDONE
SAP Sybase Error Number	20797

Error 1000137	"While inserting, table '%2' already had a Complete started. %1"
SQL State	QDB37
SQL Code	-1000137L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	tablename
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000138	"A data conversion error has occurred while loading record %2. This error should be reported to Sybase. %1"
Constant	EMSG_INSRT_CONVERTDATA
SAP Sybase Error Number	20798
SQL State	QDB38
SQL Code	-1000138L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	Location of the exception.
Parameter 2	The input record number when the error occurred.
Probable Cause	A data conversion error occurred during an insert. The input datatype cannot converted to the datatype of the data's destination field. This error should be reported to Sybase. Diagnostic information has been output to the iqmsg file.

Error 1000139	"You cannot insert into table '%2' past the original end of the table while there are %3 join virtual tables based on it. %1"
Constant	EMSG_INSRT_HASJOINPASTEND
SAP Sybase Error Number	20799
SQL State	QDB39
SQL Code	-1000139L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	tablename
Parameter 3	number of join virtual tables
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000140	"You cannot change column '%2' because it is a 'link' column. %1"
Constant	EMSG_INSRT_HASLINK
SAP Sybase Error Number	20800
SQL State	QDB40
SQL Code	-1000140L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	column name
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Warning 1000142	"Insert into '%1', \n%2 Inners added, %3 Left Outers converted to Inners, %4 Right Outers added."
Constant	EMSG_INSRT_JOINTABLEDONE
SAP Sybase Error Number	20802
SQL State	01B42
SQL Code	1000142L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	Join name
Parameter 2	number of inners added
Parameter 3	number of left outers converted to inners
Parameter 4	number of right outers added
Probable Cause	This is an informational message displayed upon completion of an insert to a join.

Error 1000143	"While inserting, table '%2' must be Complete(d) before it can be (re)Prepare(d). %1"
Constant	EMSG_INSRT_NODONE
SAP Sybase Error Number	20803
SQL State	QDB43
SQL Code	-1000143L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	tablename
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000144	"Cannot insert into table '%2'. Column %3 does not have a name. %1"
Constant	EMSG_INSRT_NOFIELDNAME
SAP Sybase Error Number	20804
SQL State	QDB44
SQL Code	-1000144L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	tablename
Parameter 3	column number
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000145	"The insert for table '%2' has no insertable columns in the column list. %1"
Constant	EMSG_INSRT_NOINSERTTABLEFIELDS
SAP Sybase Error Number	20805
SQL State	QDB45
SQL Code	-1000145L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	table to insert into
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000146	"Cannot get the index buffer for the column '%2'. %1"
Constant	EMSG_INSRT_NOSINDEX
SAP Sybase Error Number	20806
SQL State	QDB46
SQL Code	-1000146L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	column name
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000147	"Table '%2' must be Prepare(d) before inserting. %1"
Constant	EMSG_INSRT_NOPREPARE
SAP Sybase Error Number	20807
SQL State	QDB47
SQL Code	-1000147L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	tablename
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000148	"The table being inserted to does not have a name. %1"
Constant	EMSG_INSRT_NOTABLENAME
SAP Sybase Error Number	20808

Error 1000148	"The table being inserted to does not have a name. %1"
SQL State	QDB48
SQL Code	-1000148L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000149	"Unable to open table '%2' with Read/Write access for insert. %1"
Constant	EMSG_INSRT_NOTABLE
SAP Sybase Error Number	20809
SQL State	QDB49
SQL Code	-1000149L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	tablename
Probable Cause	The table cannot be opened for write access. The insert cannot proceed. Another user has this table open with write access.

Error 1000150	"Cannot insert into the table. Column '%2' has no index. %1"
Constant	EMSG_INSRT_NOTNULLNOIDX
SAP Sybase Error Number	20810
SQL State	QDB50
SQL Code	-1000150L

Error 1000150	"Cannot insert into the table. Column '%2' has no index. %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	column name
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000151	"NOT NULL column '%2' was not included in this insert. Data is needed at row %3. %1"
Constant	EMSG_INSRT_NOTNULLFIELDNOTINC
SAP Sybase Error Number	20811
SQL State	QDB51
SQL Code	-1000151L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	column name
Parameter 3	row number
Probable Cause	Data must be provided for insertion into columns defined as "NOT NULL".

Error 1000152	"The NOT NULL column '%2' was not included in this insert. %1"
Constant	EMSG_INSRT_NOTNULLNOTINC
SAP Sybase Error Number	20812
SQL State	QDB52
SQL Code	-1000152L

Error 1000152	"The NOT NULL column '%2' was not included in this insert. %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	column name
Probable Cause	Data must be provided for insertion into columns defined as "NOT NULL".

Error 1000153	"Table '%2', pass-x index count mismatch (%3/%4). %1"
Constant	EMSG_INSRT_PXCOUNT
SAP Sybase Error Number	20813
SQL State	QDB53
SQL Code	-1000153L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	tablename
Parameter 3	number used for comparison
Parameter 4	number used for comparison
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000154	"While inserting into table '%2', the record number recycled (%3). %1"
Constant	EMSG_INSRT_RECNUMRECYCLED
SAP Sybase Error Number	20814
SQL State	QDB54

Error 1000154	"While inserting into table '%2', the record number recycled (%3). %1"
SQL Code	-1000154L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	tablename
Parameter 3	record number
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Messages 1000155 through 1000174

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1000155	"The attempted insert length (%3) for column %2 is longer than the maximum allowed (%4). %1"
Constant	EMSG_INSRT_TOOLONG
SAP Sybase Error Number	20815
SQL State	QDB55
SQL Code	-1000155L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	column name
Parameter 3	requested insert length
Parameter 4	maximum insert length allowed.
Probable Cause	The attempted insert length is too long. The maximum length allowed is 65535.

Error 1000156	"Tried to insert into too many (%2) LOW FAST indexes at one time in table '%3'. %1"
Constant	EMSG_INSRT_TOOMANYINDICES
SAP Sybase Error Number	20816
SQL State	QDB56
SQL Code	-1000156L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	requested number of indexes to insert to
Parameter 3	tablename
Probable Cause	The maximum number allowed is 32727.
Error 1000157	"Columns for the index must be in ascending sort order. %1"
Constant	EMSG_ASCENDING_SORT_ONLY
SAP Sybase Error Number	20817
SQL State	QDB57
SQL Code	-1000157L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Probable Cause	It is required that ASC (ascending) sort order be used for the columns in the indexes.
Error 1000158	"An Identity size mismatch has occurred. The current transaction will rollback. %1"
Constant	EMSG_CAT_IDSIZE_MISMATCH

Error 1000158	"An Identity size mismatch has occurred. The current transaction will rollback. %1"
SAP Sybase Error Number	20818
SQL State	QDB58
SQL Code	-1000158L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	Location of the exception.
Probable Cause	IQ has encountered an Identity size mismatch. The current command will be rolled back. If this error occurs, the operation that caused it may be tried again. If the error occurs again, the server should be stopped and restarted. If the problem persists, Sybase should be notified of the error.

Warning 1000159	"\n\nIn table '%1', the %2 width insert of %3 columns will begin at record %4."
Constant	EMSG_INSRT_STARTRECID
SAP Sybase Error Number	20819
SQL State	00B59
SQL Code	1000159L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>1</i> on page 2
Parameter 1	tablename
Parameter 2	partial/fixed
Parameter 3	number of columns
Parameter 4	row number
Probable Cause	Informational message displayed during insert.

Warning 1000160	"Option %1 has an invalid setting: %2."
Constant	EMSG_INVALID_OPTION_SETTING
SAP Sybase Error Number	20820
SQL State	00B60
SQL Code	1000160L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10</i> on page 2
Parameter 1	Name of the option with the invalid setting.
Parameter 2	The current value of the option.
Probable Cause	The named OPTION is set to an invalid value. See the documentation for the valid values for the option.

Warning 1000161	"You have %1 and %2 available, respectively."
Constant	EMSG_INSRT_MEMNEEDEDWARN
SAP Sybase Error Number	20821
SQL State	01B61
SQL Code	1000161L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10</i> on page 2
Parameter 1	amount of memory
Parameter 2	amount of memory
Probable Cause	Informational message displayed with other messages regarding available memory.

Error 1000162	"Unable to create the requested object. %1"
Constant	EMSG_CAT_CANNOT_CREATE_OBJECT
SAP Sybase Error Number	20822

Error 1000162	"Unable to create the requested object. %1"
SQL State	QDB62
SQL Code	-1000162L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Probable Cause	IQ is not able to create the object that was requested. This object may be an FP index that is being created during a CREATE TABLE. This error will occur if IQ finds that the index already exists in the table for which it is being created. This can happen if you FORCE DROP a table and then try to recreate the table that was dropped. If this error occurs after a FORCE DROP, the server needs to be rebooted before continuing. If this error occurs for some other reason, Sybase should be notified. Extra diagnostic information will have output to the iqmsg file.

Error 1000163	"%1 not supported."
Constant	EMSG_NOT_SUPPORTED
SAP Sybase Error Number	20823
SQL State	QNA32
SQL Code	-1000163L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	operation name
Probable Cause	The named operation is not supported.

Error 1000164	"Only %1 supported."
Constant	EMSG_RESTRICT_ONLY
SAP Sybase Error Number	20824
SQL State	QNA33

Error 1000164	"Only %1 supported."
SQL Code	-1000164L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	type of RESTRICT supported
Probable Cause	Only UPDATE RESTRICT and DELETE RESTRICT supported

Error 1000165	"Only a single foreign key constraint can be created on the same foreign key column(s) and same candidate key column(s)."
Constant	EMSG_SINGLE_FKEY_CONSTRAINT
SAP Sybase Error Number	20825
SQL State	QNA34
SQL Code	-1000165L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	For a given set of foreign key columns and candidate key columns,

Error 1000166	"Cannot specify IGNORE CONSTRAINT ALL or DATA VALUE when option CONVERSION_ERROR is on. %1"
Constant	EMSG_DATAVALUE_CONVERSION_ON
SAP Sybase Error Number	20826
SQL State	QDB66
SQL Code	-1000166L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception

Error 1000166	"Cannot specify IGNORE CONSTRAINT ALL or DATA VALUE when option CONVERSION_ERROR is on. %1"
Probable Cause	When choosing to ignore DATA TYPE or ALL integrity constraint violations on LOAD command, you must also have option CONVERSION_ERROR set to 'off'.

Error 1000167	"Cannot %3 table %2 because of RI concurrency conflict. %1"
Constant	EMSG_RI_CONCURRENCY_CONFLICT
SAP Sybase Error Number	20827
SQL State	QDB67
SQL Code	-1000167L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception
Parameter 2	name of table undergoing the given operation
Parameter 3	operation being performed on specified table
Probable Cause	The named table cannot be modified in the manner specified because of an RI concurrency conflict. Such a conflict arises under the following conditions. delete/truncate/update candidate key at the same time its corresponding foreign key is being loaded/inserted/updated

Error 1000168	"Cannot create %1 HG index because one already exists on the given columns."
Constant	EMSG_CANNOT_CREATE_HG
SAP Sybase Error Number	20828
SQL State	QNA35
SQL Code	-1000168L
ODBC 2 State	ERROR

Error 1000168	"Cannot create %1 HG index because one already exists on the given columns."
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	type of HG index to be created (non-unique vs. unique)
Probable Cause	Only a single HG index of a given type can be created on the same column set. For example, you cannot have two unique HG indexes on the same column set, but you are allowed to have a unique HG and a non-unique HG index on the same set of columns.

Error 1000169	"Cannot create unique HG index because primary key or unique constraint already exists on the given columns."
Constant	EMSG_CANNOT_CREATE_UNIQUE_HG
SAP Sybase Error Number	20829
SQL State	QNA36
SQL Code	-1000169L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	When you create a primary key or unique constraint, IQ automatically creates a unique HG index as the mechanism for enforcing the 'uniqueness' attribute of a primary key or unique constraint. Consequently, a user cannot create another unique HG on the same columns on which the primary key or unique constraint is defined.

Error 1000170	"Cannot create a duplicate '%1' index '%2'."
Constant	EMSG_DUPLICATE_INDEX
SAP Sybase Error Number	20830
SQL State	QNA37
SQL Code	-1000170L
ODBC 2 State	ERROR

Error 1000170	"Cannot create a duplicate '%1' index '%2'."
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	indextype
Parameter 2	indexname
Probable Cause	Cannot create duplicate indexes of the same type on a set of columns.

Warning 1000171	"Insert Pass IP2.2 started."
Constant	EMSG_INSRT_SORTPASS22_STARTED
SAP Sybase Error Number	20831
SQL State	00B71
SQL Code	1000171L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>1</i> on page 2
Probable Cause	Informational message.

Warning 1000172	"Insert Pass %1 (%2 of %3) started."
Constant	EMSG_INSRT_SORTPASS234_STARTED
SAP Sybase Error Number	20832
SQL State	00B72
SQL Code	1000172L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>1</i> on page 2
Parameter 1	pass number
Parameter 2	pass number
Parameter 3	number
Probable Cause	This is an informational message.

Error 1000173	"Index '%1' cannot be created. Multicolumn indexes must be created using distinct columns."
Constant	EMSG_NEED_DISTINCT_COLUMNS
SAP Sybase Error Number	20833
SQL State	QNA38
SQL Code	-1000173L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	The name of the index being created.
Probable Cause	Multicolumn indexes must be created using distinct columns. That is, you cannot use the same column more than once when creating a multicolumn index.

Warning 1000174	"\n\t%1 records were inserted into '%2'.\n"
Constant	EMSG_INSRT_COMPLETE
SAP Sybase Error Number	20834
SQL State	01B74
SQL Code	1000174L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10</i> on page 2
Parameter 1	number of insertions
Parameter 2	tablename
Probable Cause	Informational message displayed after insert.

Messages 1000175 through 1000197

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Warning 1000175	"%1 records were inserted into %2 join virtual tables (%3 sections)\n for '%4'.\n"
Constant	EMSG_INSRT_COMPLETEJOINS
SAP Sybase Error Number	20835
SQL State	01B75
SQL Code	1000175L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	number of records
Parameter 2	number of join virtual tables
Parameter 3	number of join sorts
Parameter 4	join virtual table name
Probable Cause	This is an informational message displayed at the end of insert.

Error 1000176	"Cannot perform foreign key create/alter operation because one is already in progress. %1"
Constant	EMSG_FK_INPROGRESS
SAP Sybase Error Number	20836
SQL State	QDB76
SQL Code	-1000176L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception

Error 1000176	"Cannot perform foreign key create/alter operation because one is already in progress. %1"
Probable Cause	Concurrent foreign key create/alter operations are not supported. This error means that there is such an operation already in progress. Consequently, this new operation will be denied.
Warning 1000177	"Only the catalog entry for the '%1' index was created, no data was available to populate the index."
Constant	EMSG_APICREATEINDEXNODATA
SAP Sybase Error Number	20837
SQL State	QDB77
SQL Code	1000177L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	1 on page 2
Parameter 1	The index name
Probable Cause	This is an internal error. The new index was to be populated from another, existing index but a source index could not be found. If this error occurs, it should be reported to Sybase.
Error 1000178	"The DATA parameter must have a non-NULL value. %1"
Constant	EMSG_APIDATAMUSTHAVEVALUE
SAP Sybase Error Number	20838
SQL State	QDB78
SQL Code	-1000178L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000179	"The column length (%2) must be [if variable sized, between 0 and] %3. %1"
Constant	EMSG_APISETACTUALFIELDLENGTH
SAP Sybase Error Number	20839
SQL State	QDB79
SQL Code	-1000179L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	column length
Parameter 3	column length
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000180	"The maximum column length (%2) must be between 0 and %3. %1"
Constant	EMSG_APISETMAXFIELDLENGTH
SAP Sybase Error Number	20840
SQL State	QDB80
SQL Code	-1000180L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	column length
Parameter 3	column length
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000181	"The maximum column length (%2) is less than the actual length (%3). %1"
Constant	EMSG_APIMAXACTUALFLEN
SAP Sybase Error Number	20841
SQL State	QDB81
SQL Code	-1000181L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	column length
Parameter 3	column length
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000182	"Table %2 cannot be opened because it is currently involved in a foreign key create/alter operation. %1"
Constant	EMSG_CANNOT_OPEN_FK_INPROGRESS
SAP Sybase Error Number	20842
SQL State	QDB82
SQL Code	-1000182L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception
Parameter 2	The name of the table being opened.
Probable Cause	The named table cannot be opened for read or write access because it is currently undergoing a create/alter foreign operation.

Error 1000183	"Attempt to insert data into column '%2' with a non-insertable datatype (%3) ignored. %1"
Constant	EMSG_APIINSERTDATATYPEIGNORED
SAP Sybase Error Number	20843
SQL State	QDB83
SQL Code	-1000183L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for %2
Parameter 3	explanation for %3
Probable Cause	This is an internal error. The datatype IQ is inserting to is unknown. If this error occurs, it should be reported to Sybase.

Error 1000185	"Cannot drop table %1 because foreign keys still reference it."
Constant	EMSG_FKEY_STILL_EXISTS_TO_TABLE
SAP Sybase Error Number	20845
SQL State	QNA39
SQL Code	-1000185L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	name of the table
Probable Cause	The named table cannot be dropped until all foreign keys referencing it have first been dropped.

Error 1000186	"Cannot create foreign key constraint on a candidate key that is also a foreign key."
Constant	EMSG_CKEY_IS_ALSO_FKEY

Error 1000186	"Cannot create foreign key constraint on a candidate key that is also a foreign key."
SAP Sybase Error Number	20846
SQL State	QNA40
SQL Code	-1000186L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	A candidate key cannot also be a foreign key. Here's an example illustrating what is meant by this exception. (1) A [pk] <----- B [fk] [pk] <-- ADD THIS ONE -- C[fk] (2) A [pk] <-- ADD THIS ONE -- B[fk] [pk] <----- C[fk] In case (1), adding foreign key C[fk] is disallowed. In case (2), adding foreign key B[fk] is disallowed.

Error 1000187	"Unable to implicitly convert column '%2' to datatype (%3) from datatype (%4). %1"
Constant	EMSG_SQL_IMPLICITCONVERSION
SAP Sybase Error Number	20847
SQL State	QCB87
SQL Code	-1000187L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	column converting
Parameter 3	datatype being converted to
Parameter 4	datatype being converted from

Error 1000187	"Unable to implicitly convert column '%2' to datatype (%3) from datatype (%4). %1"
Probable Cause	The attempted implicit conversion is not possible. The conversion must be done explicitly. If implicit conversion is being attempted to or from a NUMERIC and this error results, the datatype displayed in the error for the NUMERIC will be SMALLINT, INT, or INT64 depending on the precision of the NUMERIC. This is because NUMERICs are treated internally as multiple precision signed integers.

Error 1000188	"Only ASCII, BCP and BINARY are supported LOAD formats. %1"
Constant	EMSG_LOAD_FORMAT_NOT_SUPPORTED
SAP Sybase Error Number	20848
SQL State	QDB88
SQL Code	-1000188L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	The user specified a LOAD format that is not supported.

Error 1000189	"DDL statements cannot proceed while the %2 is in an out of space condition. %1"
Constant	EMSG_CAT_NODDL_WHILE_OUTOFSPACE
SAP Sybase Error Number	20849
SQL State	QDB89
SQL Code	-1000189L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	The store that is out of space.

Error 1000189	"DDL statements cannot proceed while the %2 is in an out of space condition. %1"
Parameter 2	Location of the exception.
Probable Cause	The DDL statement cannot proceed until the named db store is no longer in an out of space condition. The out of space condition had been previously reported. The only course of action available is to stop and restart the server. The database is in an out-of-space condition. Space needs to be added to the database.

Error 1000190	"The index '%2' cannot be opened in the current transaction (%3). %1"
Constant	EMSG_CANNOTFINDINDEX
SAP Sybase Error Number	20850
SQL State	QDB90
SQL Code	-1000190L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Parameter 2	Name of the index.
Parameter 3	The current transaction.
Probable Cause	The procedure cannot open the named index. It is likely that the index was created by a transaction that began after the one that is trying to open it. In order to proceed, COMMIT the current transaction and try again.

Error 1000192	"The cursor for table '%2' has no data to fetch. %1"
Constant	EMSG_JOIN_CURSORNOFETCH
SAP Sybase Error Number	20852
SQL State	QDB92
SQL Code	-1000192L
ODBC 2 State	ERROR

Error 1000192	"The cursor for table '%2' has no data to fetch. %1"
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	tablename
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000193	"The table '%2' is either not part of the join virtual table or has had its data loaded through linked indices. %1"
Constant	EMSG_JOIN_CURSORNOTUSED
SAP Sybase Error Number	20853
SQL State	QDB93
SQL Code	-1000193L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	tablename
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000194	"You must supply either a cursor count (%2) and a cursor array, or neither. %1"
Constant	EMSG_JOIN_CURSORS
SAP Sybase Error Number	20854
SQL State	QDB94
SQL Code	-1000194L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1000194	"You must supply either a cursor count (%2) and a cursor array, or neither. %1"
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	cursor count
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000195	"Load specification '%2' only valid for column(s) having datatype '%3'. %1"
Constant	EMSG_BINARYFILE
SAP Sybase Error Number	20855
SQL State	QDB95
SQL Code	-1000195L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	type of load specification
Parameter 3	datatype of column
Probable Cause	The named load specification is only valid for columns that have the given datatype.

Error 1000197	"Table '%2' has no columns in the cursor that don't already have data, \nor the join field(s) are not part of the cursor. %1"
Constant	EMSG_JOIN_NOCOLUMNSTOINSERTINTO
SAP Sybase Error Number	20857
SQL State	QDB97
SQL Code	-1000197L
ODBC 2 State	ERROR

Error 1000197	"Table '%2' has no columns in the cursor that don't already have data, \nor the join field(s) are not part of the cursor. %1"
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	tablename
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Messages 1000199 through 1000218

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Warning 1000199	"Table '%1' has no data."
Constant	EMSG_JOIN_NODATAINBASESRC
SAP Sybase Error Number	20859
SQL State	01B99
SQL Code	1000199L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	the name of the table that has no data %1
Probable Cause	This is a warning that there is no data in a base table.

Error 1000200	"Table '%2' has no data with which to join the other tables. %1"
Constant	EMSG_JOIN_NODATAINSRC
SAP Sybase Error Number	20860
SQL State	QDC00
SQL Code	-1000200L

Error 1000200	"Table '%2' has no data with which to join the other tables. %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	tablename
Probable Cause	There is no data in a table which participates in a join.

Error 1000201	"JOIN cannot be created or updated because the thread's stack space has been exceeded. %1"
Constant	EMSG_CAT_NEAR_END_OF_STACK
SAP Sybase Error Number	20861
SQL State	QDC01
SQL Code	-1000201L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	Creation or update of this JOIN has exceeded the thread's stack space. Create or update the JOIN after restarting the engine with a larger value for the -iqts startup parameter. See the ASIQ Reference Manual for information on setting iqtss.

Error 1000202	"In join virtual table '%2', there is no table cursor at index %3. %1"
Constant	EMSG_JOIN_NOTABLECURSOR
SAP Sybase Error Number	20862
SQL State	QDC02
SQL Code	-1000202L

Error 1000202	"In join virtual table '%2', there is no table cursor at index %3. %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	jvt name
Parameter 3	index
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000203	"In join virtual table '%2', there is no tablename at index %3. %1"
Constant	EMSG_JOIN_NOTABLENAME
SAP Sybase Error Number	20863
SQL State	QDC03
SQL Code	-1000203L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	join virtual table name
Parameter 3	index
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000204	"Within the join, the portion for table '%2' already has data. %1"
Constant	EMSG_JOIN_TABLEHASDATA
SAP Sybase Error Number	20864
SQL State	QDC04

Error 1000204	"Within the join, the portion for table '%2' already has data. %1"
SQL Code	-1000204L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	tablename
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000205	"Within the join, the cursor for table '%2' yielded no data. %1"
Constant	EMSG_JOIN_TABLEHASNODATA
SAP Sybase Error Number	20865
SQL State	QDC05
SQL Code	-1000205L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	tablename
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000206	"Within the join, there remain no rows to insert into table '%2' \nafter processing the INNER and OUTER rows. %1"
Constant	EMSG_JOIN_TABLEHASNOROWS
SAP Sybase Error Number	20866
SQL State	QDC06
SQL Code	-1000206L

Error 1000206	"Within the join, there remain no rows to insert into table '%2' \nafter processing the INNER and OUTER rows. %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	tablename
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000207	"Within the join, the portion for table '%2' has no data. \nINSERT INTO or LOAD this table first. %1"
Constant	EMSG_JOIN_TABLENEEDSDATA
SAP Sybase Error Number	20867
SQL State	QDC07
SQL Code	-1000207L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	tablename
Probable Cause	The named table must be populated with data.

Error 1000208	"Within the non-appending partial width insert into the join virtual table '%2', \nthere must be at least one other column besides the join field(s). %1"
Constant	EMSG_JOIN_VINSERTNEEDSDATACOL
SAP Sybase Error Number	20868
SQL State	QDC08
SQL Code	-1000208L
ODBC 2 State	ERROR

Error 1000208	"Within the non-appending partial width insert into the join virtual table '%2', \nthere must be at least one other column besides the join field(s). %1"
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	join virtual table name
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000209	"Within the partial width insert into the join virtual table '%2', \nrow %3 is no longer an inner join. %1"
Constant	EMSG_JOIN_VINSERTNOTINNER
SAP Sybase Error Number	20869
SQL State	QDC09
SQL Code	-1000209L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	join virtual table name
Parameter 3	row number
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000210	"For the partial width insert into the join virtual table '%2', \nrow %3 is no longer a left outer. %1"
Constant	EMSG_JOIN_VINSERTNOTLOUTER
SAP Sybase Error Number	20870
SQL State	QDC10
SQL Code	-1000210L

Error 1000210	"For the partial width insert into the join virtual table '%2', \nrow %3 is no longer a left outer. %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	join virtual table name
Parameter 3	row
Probable Cause	This is an internal error. If this error occurs, then it should be reported to Sybase.

Error 1000211	"For the partial width insert into the join virtual table '%2', \nrow %3 is no longer a right outer. %1"
Constant	EMSG_JOIN_VINSERTNOTROUTER
SAP Sybase Error Number	20871
SQL State	QDC11
SQL Code	-1000211L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	join virtual table name
Parameter 3	row
Probable Cause	This is an internal error. If this error occurs, then it should be reported to Sybase.

Error 1000212	"For the partial width insert into join virtual table '%2', \nrow %3 is now a duplicate row (but was not before or vice-versa). %1"
Constant	EMSG_JOIN_VINSERTNOTT1TRUE
SAP Sybase Error Number	20872

Error 1000212	"For the partial width insert into join virtual table '%2', \nrow %3 is now a duplicate row (but was not before or vice-versa). %1"
SQL State	QDC12
SQL Code	-1000212L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	join virtual table name
Parameter 3	row
Probable Cause	This is an internal error. If this error occurs, then it should be reported to Sybase.

Warning 1000213	No message
Constant	EMSG_JOIN_WARNNOCURSORS_EMPTY_SLOT
SAP Sybase Error Number	20873
SQL State	01C13
SQL Code	1000213L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Probable Cause	No additional information available.

Error 1000214	"Duplicate records seen in table %2. The SYNCHRONIZE operation will rollback. %1"
Constant	EMSG_JOIN_DUPLICATE_ROWS
SAP Sybase Error Number	20874
SQL State	QDC14
SQL Code	-1000214L

Error 1000214	"Duplicate records seen in table %2. The SYNCHRONIZE operation will rollback. %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	table containing duplicate records
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1000215	"An invalid filler option (e.g., filler()) was specified in the load statement. %1"
Constant	EMSG_INVALID_FILLER_OPTION
SAP Sybase Error Number	20875
SQL State	QDC15
SQL Code	-1000215L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Probable Cause	An invalid filler option was specified on the load statement.

Warning 1000216	No message
Constant	EMSG_JOIN_EJP1ADD_EMPTY_SLOT
SAP Sybase Error Number	20876
SQL State	01C16
SQL Code	1000216L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10 on page 2</i>

Warning 1000216	No message
Probable Cause	No additional information available.

Warning 1000217	No message
Constant	EMSG_JOIN_EJP1STARTRECID_EMPTY_SLOT
SAP Sybase Error Number	20877
SQL State	01C17
SQL Code	1000217L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Probable Cause	No additional information available.

Warning 1000218	"Join virtual table fetches (JP1%1) complete for '%2'."
Constant	EMSG_JOIN_EJP12DONE
SAP Sybase Error Number	20878
SQL State	01C18
SQL Code	1000218L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	Parameter 1 description
Parameter 2	Parameter 2 description
Probable Cause	This is an informational message displayed in context with other messages.

Messages 1000219 through 1000235

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1000219	"The specified indextype does not exist in the given target. %1"
Constant	EMSG_DBCC_INDEXTYPE_NOT_FOUND
SAP Sybase Error Number	20879
SQL State	QDC19
SQL Code	-1000219L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Probable Cause	The indextype the user requested to check with sp_iqcheckdb does not exist in the given table or database.

Warning 1000220	" Left Rows: %1, Right Rows: %2, Ratio: %3 to %4\n"
Constant	EMSG_JOIN_EJP12CNTS
SAP Sybase Error Number	20880
SQL State	01C20
SQL Code	1000220L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	Parameter 1 description
Parameter 2	Parameter 2 description
Parameter 3	Parameter 3 description
Parameter 4	Parameter 4 description

Warning 1000220	" Left Rows: %1, Right Rows: %2, Ratio: %3 to %4\n"
Probable Cause	This is an informational message displayed in context with other messages.

Warning 1000221	" Right Rows Skipped: %1 (former left outers).\n"
Constant	EMSG_JOIN_EJP12SKIPS
SAP Sybase Error Number	20881
SQL State	01C21
SQL Code	1000221L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	Parameter 1 description
Probable Cause	This is an informational message displayed in context with other messages.

Error 1000222	"JP3&4"
Constant	EMSG_JOIN_ESORT34
SAP Sybase Error Number	20882
SQL State	QDC22
SQL Code	-1000222L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	This is an informational message displayed in context with other messages.

Error 1000223	"Column name '%2' is invalid. The column name must follow the format [OWNER.]TABLE.COLUMN. %1"
Constant	EMSG_INVALID_COLUMN_NAME
SAP Sybase Error Number	20883

Error 1000223	"Column name '%2' is invalid. The column name must follow the format [OWNER.]TABLE.COLUMN. %1"
SQL State	QDC23
SQL Code	-1000223L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Parameter 2	The name of the column typed by the user.
Probable Cause	The column name must follow the format [OWNER.]TABLE.COLUMN.

Warning 1000224	"Join record rejected: '%1', duplicate rows in 1st indexset. lnRow# %2 & %3X, row %4 rejected."
Constant	EMSG_CLBK_JOINIDXRECORDREJECTEDX
SAP Sybase Error Number	20884
SQL State	01C24
SQL Code	1000224L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	Parameter 1 description
Parameter 2	Parameter 2 description
Parameter 3	Parameter 3 description
Parameter 4	Parameter 4 description
Probable Cause	This is an informational message displayed in context with other messages.

Error 1000225	"Cannot open table %2. The table has already been opened by a cursor declared FOR UPDATE in transaction %3. %1"
Constant	EMSG_CAT_CANNOT_OPEN_TABLE

Error 1000225	"Cannot open table %2. The table has already been opened by a cursor declared FOR UPDATE in transaction %3. %1"
SAP Sybase Error Number	20885
SQL State	QDC25
SQL Code	-1000225L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Parameter 2	Tablename.
Parameter 3	The id of the transaction during which the cursor was opened.
Probable Cause	A table opened by a CURSOR that has been declared FOR UPDATE cannot be opened again by another operation.

Warning 1000226	"\n Inner Rows: %1, Left Outer Rows: %2, Right Outer Rows: %3"
Constant	EMSG_JOIN_EJP3CNT1
SAP Sybase Error Number	20886
SQL State	01C26
SQL Code	1000226L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	Parameter 1 description
Parameter 2	Parameter 2 description
Parameter 3	Parameter 3 description
Probable Cause	This is an informational message displayed in context with other messages.

Error 1000226	"The LOCATION string passed to the attached database insert is invalid. %1"
Constant	EMSG_INVALIDLOCATION
SAP Sybase Error Number	20996
SQL State	QDC36
SQL Code	-1000226L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	The user passed an invalid LOCATION string in an attached database insert. Check the format of the string. It must be of the form "servername.dbname".

Warning 1000227	" Join Rows: %1, Left m2m Rows: %2, Right m2m Rows: %3\n"
Constant	EMSG_JOIN_EJP3CNT2
SAP Sybase Error Number	20887
SQL State	01C27
SQL Code	1000227L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	Parameter 1 description
Parameter 2	Parameter 2 description
Parameter 3	Parameter 3 description
Probable Cause	This is an informational message displayed in context with other messages.

Error 1000227	"Cannot load data with both BINARY and delimited columns. %1"
Constant	EMSG_LOADBINARYDELIMITED
SAP Sybase Error Number	20997
SQL State	QDC37
SQL Code	-1000227L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	You cannot load data with both BINARY and delimited columns in the same LOAD command.

Error 1000228	"JP4&5"
Constant	EMSG_JOIN_ESORT45
SAP Sybase Error Number	20888
SQL State	QDC28
SQL Code	-1000228L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	This is an informational message displayed in context with other messages.

Warning 1000229	"%1 records were inserted and %2 records were rejected for %3 tables \nfor join index '%4'.\n"
Constant	EMSG_JOIN_COMPLETE
SAP Sybase Error Number	20889
SQL State	01C29
SQL Code	1000229L

Warning 1000229	"%1 records were inserted and %2 records were rejected for %3 tables \nfor join index '%4'.\n"
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	Parameter 1 description
Parameter 2	Parameter 2 description
Parameter 3	Parameter 3 description
Parameter 4	Parameter 4 description
Probable Cause	This is an informational message displayed in context with other messages.

Error 1000229	"Only BINARY [WITH NULL BYTE] can be used as a column specification when using UNLOAD FORMAT. %1"
Constant	EMSG_CANTUSEINLOAD
SAP Sybase Error Number	20998
SQL State	QDC38
SQL Code	-1000229L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	When using UNLOAD FORMAT, you cannot specify any column specification other than BINARY. If need to load null values for a column using the BINARY column spec, you must specify the WITH NULL BYTE option. You cannot use the [ROW] DELIMITED BY options with UNLOAD FORMAT.

Warning 1000230	"\nInsert for '%1',\n completed in %2 seconds."
Constant	EMSG_DELETE_INSERTDONE
SAP Sybase Error Number	20890

Warning 1000230	"\nInsert for '%1',\n completed in %2 seconds."
SQL State	01C30
SQL Code	1000230L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	Parameter 1 description
Parameter 2	Parameter 2 description
Probable Cause	This is an informational message displayed in context with other messages.

Error 1000230	"Columns that allow nulls must use the WITH NULL BYTE option. %1"
Constant	EMSG_MUSTUSENULLBYTE
SAP Sybase Error Number	20999
SQL State	QDC39
SQL Code	-1000230L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	The user must use the WITH NULL BYTE option for a BINARY column spec for columns that allow nulls.

Error 1000232	"Partial input record skipped at EOF. %1"
Constant	EMSG_PARTIAL_INPUT_ROW
SAP Sybase Error Number	20892
SQL State	QDC32
SQL Code	-1000232L
ODBC 2 State	ERROR

Error 1000232	"Partial input record skipped at EOF. %1"
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	A partial input record was detected during a 'load' operation. This can occur as a result of an OS/hardware error or simply because the input data file was missing values for one or more columns in the table.

Warning 1000234	"\nInsert into table '%1', %2 rows rejected (in all)."
Constant	EMSG_CLBK_INSERTREJECTTOTAL
SAP Sybase Error Number	20894
SQL State	01C34
SQL Code	1000234L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	table name
Parameter 2	number of rows rejected.
Probable Cause	This is an informational message displayed in context with other messages. During the LOAD, some records were rejected.

Error 1000234	"The record size of the unloaded data: %2, does not match the record size of the load: %3. %1"
Constant	EMSG_RECSIZEWRONG
SAP Sybase Error Number	21000
SQL State	QDC40
SQL Code	-1000234L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2

Error 1000234	"The record size of the unloaded data: %2, does not match the record size of the load: %3. %1"
Parameter 1	location of the exception
Parameter 2	record size in the tape being read
Parameter 3	record size of the load command.
Probable Cause	The record size of the unloaded data does not match the size of the record described by the LOAD command.

Warning 1000235	"%3 Pass %1 completed in %2 seconds."
Constant	EMSG_CLBK_INSERTPASSDONE
SAP Sybase Error Number	20895
SQL State	00C35
SQL Code	1000235L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	1 on page 2
Parameter 1	Parameter 1 description
Parameter 2	Parameter 2 description
Parameter 3	Parameter 3 description
Probable Cause	This is an informational message displayed in context with other messages.

Messages 1000235 through 1000245

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1000235	"The total number of columns of unloaded data: %2, does not match the total number of columns in the load: %3. %1"
Constant	EMSG_NUMCOLSWRONG
SAP Sybase Error Number	21001
SQL State	QDC42

Error 1000235	"The total number of columns of unloaded data: %2, does not match the total number of columns in the load: %3. %1"
SQL Code	-1000235L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	number of columns in the tape being read
Parameter 3	number of columns in the load command.
Probable Cause	The total number of columns in the unloaded data does not match the number of columns in the LOAD command.

Warning 1000236	"%4 for '%1' completed in %2 seconds. %3 rows %5."
Constant	EMSG_CLBK_INSERTDONE
SAP Sybase Error Number	20896
SQL State	01C36
SQL Code	1000236L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	table name
Parameter 2	number of seconds
Parameter 3	number of rows inserted
Parameter 4	operation performed
Parameter 5	operation performed
Probable Cause	This is an informational message displayed in context with other messages.

Error 1000236	"The total number of null columns in the unloaded data, %2, does not match the total number of null columns in the LOAD command, %3. %1"
Constant	EMSG_NUMNULLCOLSWRONG
SAP Sybase Error Number	21002
SQL State	QDC43
SQL Code	-1000236L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	number of null columns in the tape being read
Parameter 3	number of null columns in the load command.
Probable Cause	The total number of null columns in the unloaded data does not match the number of null columns in the LOAD command.

Warning 1000237	"t%1 Rows, %2 Seconds"
Constant	EMSG_CLBK_INSERTNRECS
SAP Sybase Error Number	20897
SQL State	00C37
SQL Code	1000237L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	1 on page 2
Parameter 1	Parameter 1 description
Parameter 2	Parameter 2 description
Probable Cause	This is an informational message displayed in context with other messages.

Error 1000237	"The total number of variable width columns in the unloaded data, %2, does not match the total number of variable width columns in the LOAD command, %3. %1"
Constant	EMSG_NUMVARCOLSWRONG
SAP Sybase Error Number	21003
SQL State	QDC44
SQL Code	-1000237L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	number of variable width columns in the tape being read
Parameter 3	number of variable width columns in the load command.
Probable Cause	The total number of variable width columns in the unloaded data does not match the number of variable width columns in the LOAD command.

Warning 1000238	"t%1 Rows, %2 Seconds, %3"
Constant	EMSG_CLBK_INSERTNRECSINDEX
SAP Sybase Error Number	20898
SQL State	01C38
SQL Code	1000238L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	Parameter 1 description
Parameter 2	Parameter 2 description
Parameter 3	Parameter 3 description
Probable Cause	This is an informational message displayed in context with other messages.

Error 1000238	"The platform type of the unloaded data, %2, does not match the platform type on the load, %3. %1"
Constant	EMSG_PLATIDWRONG
SAP Sybase Error Number	21009
SQL State	QDC45
SQL Code	-1000238L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Platform ID in the tape being read
Parameter 3	Platform ID the load command command is executing in.
Probable Cause	The Platform ID of unloaded data does not match the Platform ID of load. The LOAD command detected that the platform on which the UNLOAD was performed, is not the same platform on which the LOAD is being attempted. Cross platform UNLOAD-LOAD cannot be done.

Warning 1000239	"Inserting into table '%1',\ncolumn '%2'.\nInput record %3 was rejected."
Constant	EMSG_CLBK_INSERTRECORDREJECTED
SAP Sybase Error Number	20899
SQL State	01C39
SQL Code	1000239L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	The name of the table being inserted to.
Parameter 2	The column being inserted to.
Parameter 3	The data Being inserted to the column.

Warning 1000239	"Inserting into table '%1',\ncolumn '%2'.\nInput record %3 was rejected."
Probable Cause	Some data cannot be inserted. Examine the data and column definition to determine why.
Error 1000239	"UNLOAD version number: %2, does not match the LOAD version number: %3. %1"
Constant	EMSG_VERSIONWRONG
SAP Sybase Error Number	21010
SQL State	QDC46
SQL Code	-1000239L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	version number of data in the tape being read
Parameter 3	version number of the load command.
Probable Cause	The UNLOAD version number does not match the LOAD version number. The version number of the data on the tape being read does not match the version number of the LOAD command. The version numbers must match before the data on the tape can be loaded.
Warning 1000240	"Inserting into table '%1',\nColumn '%2'.\nOn input record %3, the value was rejected."
Constant	EMSG_CLBK_INSERTVALUEREJECTED
SAP Sybase Error Number	20900
SQL State	01C40
SQL Code	1000240L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2

Warning 1000240	"Inserting into table '%1',\nColumn '%2'.\nOn input record %3, the value was rejected."
Parameter 1	The name of the table being inserted to.
Parameter 2	The column being inserted to.
Parameter 3	This is the nth record being inserted.
Probable Cause	Some data was rejected on insert. Examine the input data and column definition to determine why.

Error 1000240	"The total number of blocks of unloaded data: %2, does not match the total number of blocks loaded: %3. %1"
Constant	EMSG_BLOCKCOUNTWRONG
SAP Sybase Error Number	21011
SQL State	QDC47
SQL Code	-1000240L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	number of blocks on the tape being read
Parameter 3	number of blocks in the load command.
Probable Cause	Total number of blocks of unloaded data on the tape does not match the number of blocks of data that were just loaded.

Warning 1000241	"The insert to the table will be single threaded."
Constant	EMSG_CLBK_INSERT_SINGLE_THREADED
SAP Sybase Error Number	20901
SQL State	QDC41
SQL Code	1000241L
ODBC 2 State	OK
ODBC 3 State	OK

Warning 1000241	"The insert to the table will be single threaded."
Severity Code	<i>10</i> on page 2
Probable Cause	There are not enough threads available to do a multithreaded insert or load. The number of users doing parallel processing has limited the number of threads available for your insert/load. The insert/load will proceed, but will be done serially.

Warning 1000242	"Insert completed. Index '%1',\n in %2 seconds."
Constant	EMSG_CLBK_INSERTINDEXDONE
SAP Sybase Error Number	20902
SQL State	01C42
SQL Code	1000242L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10</i> on page 2
Parameter 1	index name
Parameter 2	number of seconds
Probable Cause	This is an informational message that is displayed after an insert to an index.

Error 1000242	"Total number of rows of unloaded data: %2, does not match the total number of rows in the load: %3. %1"
Constant	EMSG_ROWCOUNTWRONG
SAP Sybase Error Number	21012
SQL State	QDC48
SQL Code	-1000242L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	number of rows on the tape being read

Error 1000242	"Total number of rows of unloaded data: %2, does not match the total number of rows in the load: %3. %1"
Parameter 3	number of rows in the load command.
Probable Cause	The total number of rows of unloaded data on the tape does not match the numbers of rows of data just loaded.

Warning 1000243	"\nInsert into join virtual table '%1' started.\n\t\t%2 tables will be modified (in all)."
Constant	EMSG_CLBK_INSERTJOINSTART
SAP Sybase Error Number	20903
SQL State	01C43
SQL Code	1000243L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	join virtual table name
Parameter 2	number of tables
Probable Cause	This is an informational message.

Error 1000243	"The unload format number: %2, does not match the load format number: %3. %1"
Constant	EMSG_FORMATWRONG
SAP Sybase Error Number	21013
SQL State	QDC49
SQL Code	-1000243L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	format number of data in the tape being read.

Error 1000243	"The unload format number: %2, does not match the load format number: %3. %1"
Parameter 3	format number of the load command.
Probable Cause	The unload format number does not match the load format number. The data on the tape being read contains a format number. This number does not match the format number of the LOAD command. In order to load the data, the numbers must match.

Warning 1000244	"\nInsert into join virtual table '%1' completed\n in %2 seconds.\n\t\t%3 tables modified (in all).\n"
Constant	EMSG_CLBK_INSERTJOINDONE
SAP Sybase Error Number	20904
SQL State	01C44
SQL Code	1000244L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10</i> on page 2
Parameter 1	join virtual table name
Parameter 2	number of seconds
Parameter 3	number of tables
Probable Cause	This is an informational message.

Error 1000244	"The BLOCK FACTOR of unloaded data: %2 does not match the BLOCK FACTOR of the LOAD: %3. %1"
Constant	EMSG_BLOCKFACTORWRONG
SAP Sybase Error Number	21014
SQL State	QDC50
SQL Code	-1000244L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2

Error 1000244	"The BLOCK FACTOR of unloaded data: %2 does not match the BLOCK FACTOR of the LOAD: %3. %1"
Parameter 1	location of the exception
Parameter 2	Block Factor of data in the tape being read.
Parameter 3	Block Factor specified in the load command.
Probable Cause	The BLOCK FACTOR used in the LOAD command must be the same as the BLOCK FACTOR that was used in the LOAD command to unload the data.

Warning 1000245	"Insert into join virtual table '%1' started.\n%2 rows will be inserted (in all)."
Constant	EMSG_CLBK_INSERTJOINTABLESTART
SAP Sybase Error Number	20905
SQL State	01C45
SQL Code	1000245L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10</i> on page 2
Parameter 1	join virtual table name
Parameter 2	number of rows to be inserted
Probable Cause	This is an informational message.

Error 1000245	"Tape / File already loaded. Block number %2 repeats. %1"
Constant	EMSG_FILEALREADYLOADED
SAP Sybase Error Number	21015
SQL State	QDC51
SQL Code	-1000245L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2

Error 1000245	"Tape / File already loaded. Block number %2 repeats. %1"
Parameter 1	location of the exception
Parameter 2	block number that was already loaded.
Probable Cause	LOAD has encountered a block that has already been loaded. This tape (or file) has already been loaded.

Messages 1000246 through 1000264

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Warning 1000246	"%1 Rows, %2 Seconds"
Constant	EMSG_CLBK_INSERTJOINRECS
SAP Sybase Error Number	20906
SQL State	01C46
SQL Code	1000246L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	rows
Parameter 2	seconds
Probable Cause	This is an informational message displayed in context with other messages.

Error 1000246	"The number of rows loaded: %3, does not match the number of rows unloaded: %2. %1"
Constant	EMSG_ROWCOUNTMISMATCH
SAP Sybase Error Number	21016
SQL State	QDC52
SQL Code	-1000246L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1000246	"The number of rows loaded: %3, does not match the number of rows unloaded: %2. %1"
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	Number of rows of data in all tapes that were read.
Parameter 3	Number of rows of data actually loaded by the load command.
Probable Cause	The number of rows of data on all of the tapes that were loaded does not match the number of rows of data that were unloaded by the LOAD command.

Warning 1000247	"Insert into join virtual table '%1' completed in %2 seconds.\n%3 rows inserted (in all)."
Constant	EMSG_CLBK_INSERTJOINTABLEDONE
SAP Sybase Error Number	20907
SQL State	01C47
SQL Code	1000247L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10</i> on page 2
Parameter 1	join virtual table name
Parameter 2	number of seconds
Parameter 3	number of rows inserted
Probable Cause	This is an informational message.

Error 1000247	"The number of blocks loaded: %3, does not match the number of blocks unloaded: %2. %1"
Constant	EMSG_BLOCKCOUNTMISMATCH
SAP Sybase Error Number	21017
SQL State	QDC54
SQL Code	-1000247L
ODBC 2 State	ERROR

Error 1000247	"The number of blocks loaded: %3, does not match the number of blocks unloaded: %2. %1"
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Number of blocks of data in all tapes that were read.
Parameter 3	Number of blocks of data actually loaded by the load command.
Probable Cause	The number of blocks of data on all of the tapes that were loaded does not match the number of blocks of data that were unloaded by the LOAD command.

Warning 1000248	"\nJoin virtual table passes started for '%1'.\n"
Constant	EMSG_CLBK_JOINIDXPASSESSTART
SAP Sybase Error Number	20908
SQL State	01C48
SQL Code	1000248L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	index name
Probable Cause	This is an informational message.

Warning 1000249	"\nJoin Virtual Table Pass 1 started for '%1'.\n"
Constant	EMSG_CLBK_JOINIDXPASS1START
SAP Sybase Error Number	20909
SQL State	01C49
SQL Code	1000249L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2

Warning 1000249	"\nJoin Virtual Table Pass 1 started for '%1'.\n"
Parameter 1	index name
Probable Cause	This is an informational message.

Warning 1000250	"\nJoin virtual table Pass %1 completed for '%2', %3 seconds.\n\t\t%4 rows processed.\n"
Constant	EMSG_CLBK_JOINIDXPASSCOMPLETE
SAP Sybase Error Number	20910
SQL State	01C50
SQL Code	1000250L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10</i> on page 2
Parameter 1	pass
Parameter 2	index
Parameter 3	seconds
Parameter 4	rows
Probable Cause	This is an informational message.

Warning 1000251	"\nJoin virtual table passes 1 and 2 complete for '%1' in %2 seconds.\n%3 rows processed.\n"
Constant	EMSG_CLBK_JOINIDXPASS1AND2COMPLETE
SAP Sybase Error Number	20911
SQL State	01C51
SQL Code	1000251L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10</i> on page 2
Parameter 1	index name

Warning 1000251	"\nJoin virtual table passes 1 and 2 complete for '%1' in %2 seconds.\n%3 rows processed.\n"
Parameter 2	number of seconds
Parameter 3	number of rows processed
Probable Cause	This is an informational message.

Error 1000253	"Cannot drop the constraint '%1'."
Constant	EMSG_ALTER_DROP_CONSTRAINT
SAP Sybase Error Number	20913
SQL State	QDC53
SQL Code	-1000253L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Constraint name.
Probable Cause	IQ is unable to drop the named constraint because the index associated with the constraint could not be found or opened.

Warning 1000254	"\t%1 Rows, JP%2, %3 Seconds"
Constant	EMSG_CLBK_JOINIDXNRECS
SAP Sybase Error Number	20914
SQL State	01C54
SQL Code	1000254L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	rows
Parameter 2	explanation of %2
Parameter 3	seconds

Warning 1000254	"\t%1 Rows, JP%2, %3 Seconds"
Probable Cause	This is an informational message displayed in the context of other messages.

Warning 1000255	"Join Record Rejected: '%1', duplicate rows in 1st table. \nRow# %2 & %3, row %4 rejected."
Constant	EMSG_CLBK_JOINIDXRECORDREJECTED
SAP Sybase Error Number	20915
SQL State	01C55
SQL Code	1000255L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	rejected record
Parameter 2	duplicate row number
Parameter 3	duplicate row number
Parameter 4	rejected row
Probable Cause	This is an informational message describing duplicate rows encountered.

Warning 1000256	"Join virtual table '%1'. \nTotal rows rejected: %2"
Constant	EMSG_CLBK_JOINIDXREJECTEDTOTAL
SAP Sybase Error Number	20916
SQL State	01C56
SQL Code	1000256L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	Join virtual table name
Parameter 2	number of records rejected

Warning 1000256	"Join virtual table '%1'. \nTotal rows rejected: %2"
Probable Cause	This is an informational message displayed in context with other messages.

Warning 1000257	"Delete of %1 rows started for table: "
Constant	EMSG_CLBK_DELETESTART
SAP Sybase Error Number	20917
SQL State	00C57
SQL Code	1000257L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>1</i> on page 2
Parameter 1	number of rows
Probable Cause	This is an informational message foretelling the number of rows to be deleted from a table.

Warning 1000258	"Portions of the insert/load will be single threaded."
Constant	EMSG_CLBK_INSERT_SINGLE_THREADED1
SAP Sybase Error Number	20918
SQL State	QDC58
SQL Code	1000258L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10</i> on page 2
Probable Cause	The load will proceed, but portions of it will be done serially. This can be caused by constraining the amount of memory available to the load with the LOAD_MEMORY_MB option; executing a variable length load without row delimiters; or executing a partial width, variable length load.

Warning 1000259	"\nDelete of %1 rows completed for table: %2, %3 seconds."
Constant	EMSG_CLBK_DELETEDONE
SAP Sybase Error Number	20919
SQL State	01C59
SQL Code	1000259L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	number of rows deleted
Parameter 2	table name
Parameter 3	number of seconds to do the delete
Probable Cause	This is an informational message displayed at the end of a delete.

Error 1000260	"ALTER DBSPACE <dbspace-name> ADD <number> is not supported. %1"
Constant	EMSG_ALTER_ADD_NOTSUPPORTED
SAP Sybase Error Number	20920
SQL State	QDC60
SQL Code	-1000260L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	For a Sybase IQ database, one can add space to a database only using the CREATE DBSPACE command. The size of existing dbspaces cannot be changed.

Error 1000261	"A Sybase IQ system dbspace, '%2', cannot be renamed. %1"
Constant	EMSG_ALTER_CANT_RENAME_DBSPACE

Error 1000261	"A Sybase IQ system dbspace, '%2', cannot be renamed. %1"
SAP Sybase Error Number	20921
SQL State	QDC61
SQL Code	-1000261L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	dbspace name
Probable Cause	You cannot rename a dbspace in a Sybase IQ database.

Error 1000262	"You cannot specify BLANK PADDING OFF for CREATE DATABASE. %1"
Constant	EMSG_BLANKPADDINGOFF
SAP Sybase Error Number	20922
SQL State	QDC62
SQL Code	-1000262L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Probable Cause	The BLANK PADDING OFF clause is not valid while creating a Sybase IQ database.

Error 1000263	"Undo failure for row %2. Statement will rollback to statement before the first insert..values. %1"
Constant	EMSG_UNDO_UNDO_FAILED
SAP Sybase Error Number	20973
SQL State	QDC63

Error 1000263	"Undo failure for row %2. Statement will rollback to statement before the first insert..values. %1"
SQL Code	-1000263L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	row for which the 'undo' operation failed
Probable Cause	There was a unrecoverable error encountered while attempting to undo an 'insert' operation for the specified row. Consequently, the statement now rolls back to the first insert..values statement that occurred since the most recent commit, rollback, or non-insert..values command.

Error 1000264	"Ambiguous index name '%2'. Please specify owner. %1"
Constant	EMSG_INDEXAMBIGUOUS
SAP Sybase Error Number	21077
SQL State	QDB04
SQL Code	-1000264L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	Name of ambiguous index
Probable Cause	The specified index name is shared by more than one owner. The owner can be specified as OWNER.TABLE.INDEX

Messages 1000265 through 1000284

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1000265	"Index '%2' not found. %1"
Constant	EMSG_INDEX_NOTFOUND

Error 1000265	"Index '%2' not found. %1"
SAP Sybase Error Number	21078
SQL State	QDB05
SQL Code	-1000265L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	Name of user specified index
Probable Cause	The specified index could not be opened. Either the index does not exist or the name format is incorrect. The index name must follow the format [OWNER.]TABLE.INDEX

Error 1000266	"Table '%2' not found. %1"
Constant	EMSG_TABLE_NOTFOUND
SAP Sybase Error Number	21079
SQL State	QDB09
SQL Code	-1000266L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	Name of user specified table
Probable Cause	The specified table could not be opened. Either the table does not exist or the name format is incorrect. The table name must follow the format [OWNER.]TABLE

Error 1000267	"Cannot convert '%2' to an integer percent. %1"
Constant	EMSG_RESOURCE_CONVERTERROR
SAP Sybase Error Number	21080

Error 1000267	"Cannot convert '%2' to an integer percent. %1"
SQL State	QDB07
SQL Code	-1000267L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	Percent specified for RESOURCES
Probable Cause	The percent must be an integer value

Error 1000268	"The target '%2' overlaps an earlier target. %1"
Constant	EMSG_TARGETS_OVERLAP
SAP Sybase Error Number	21081
SQL State	QDB08
SQL Code	-1000268L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	Name of table or index
Probable Cause	The user cannot specify an index or table multiple times. This also applies to an index that was already included by specifying its table.

Error 1000269	"DBCC: Multiple modes specified with a write mode. %1"
Constant	EMSG_DBCC_MULTI_WRITE_MODES
SAP Sybase Error Number	21082
SQL State	QDB59
SQL Code	-1000269L
ODBC 2 State	ERROR

Error 1000269	"DBCC: Multiple modes specified with a write mode. %1"
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Probable Cause	The user can only specify one mode if a mode that updates the database is present. Update modes are dbcc command REPAIR, server switch -iqdrplks, database options Convert_HG_To_1242 and Convert_Varchar_To_1242

Error 1000270	"DBCC: FP Recreate failed for index '%2'. %1"
Constant	EMSG_DBCC_FP_RECREATE_FAILED
SAP Sybase Error Number	21083
SQL State	QDB60
SQL Code	-1000270L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	Name of index
Probable Cause	If an FP re-create fails, the command must rollback

Error 1000271	"Table '%2' is a temporary table, a view, or not an IQ table. %1"
Constant	EMSG_NOT_IQ_TABLE
SAP Sybase Error Number	21084
SQL State	QDB61
SQL Code	-1000271L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2

Error 1000271	"Table '%2' is a temporary table, a view, or not an IQ table. %1"
Parameter 1	location of the exception
Parameter 2	Name of user specified table
Probable Cause	The specified table was opened, but it was a non-IQ or temporary table or a view. Only non-temporary IQ tables can be processed.

Error 1000272	"Invalid table name '%2'. %1"
Constant	EMSG_INVALID_TABLE_NAME
SAP Sybase Error Number	21085
SQL State	QDB63
SQL Code	-1000272L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	Name of user specified table
Probable Cause	The table name must follow the format [OWNER.]TABLE

Error 1000273	"Invalid index name '%2'. %1"
Constant	EMSG_INVALID_INDEX_NAME
SAP Sybase Error Number	21086
SQL State	QDB64
SQL Code	-1000273L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	Name of user specified index

Error 1000273	"Invalid index name '%2'. %1"
Probable Cause	The index name must follow the format [OWNER.]TABLE.INDEX
Error 1000274	"DBCC: Upgrade options can be used only with CHECK or REPAIR mode. %1"
Constant	EMSG_DBCC_UPGRADE_OPTIONS
SAP Sybase Error Number	21087
SQL State	QDB65
SQL Code	-1000274L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	Location of the exception.
Probable Cause	Upgrade options (such as Convert_HG_To_1242) can be used only with CHECK or REPAIR. They cannot be used with ALLOCATION.
Error 1000275	"Cannot process object '%2' at the current transaction level. %1"
Constant	EMSG_FUTUREVERSION
SAP Sybase Error Number	21088
SQL State	QDB68
SQL Code	-1000275L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	Location of the exception.
Parameter 2	Name of the object that cannot be processed.
Probable Cause	The requested object cannot be opened because it was created by a future transaction. A COMMIT or ROLLBACK must be issued before the object can be opened

Error 1000276	"At least one mode and target must be specified. %1"
Constant	EMSG_NOTHING_TO_DO
SAP Sybase Error Number	21094
SQL State	QDB69
SQL Code	-1000276L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	Location of the exception.
Probable Cause	DBCC has no default target or mode. The user must explicitly specify both a mode and target.

Error 1000277	"\dropleaks {database dbspace dbspace-name}\" is the only command allowed in drop leaks mode. %1"
Constant	EMSG_DBCC_DROPLEAKS_COMMAND
SAP Sybase Error Number	21095
SQL State	QDB70
SQL Code	-1000277L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	Location of the exception.
Probable Cause	Modes are restricted to avoid long DBCC sessions during forced recovery

Error 1000278	"\resetclks\" must be run in single-node mode with \"allocation database\". %1"
Constant	EMSG_DBCC_RESETCLKS_COMMAND
SAP Sybase Error Number	21096
SQL State	QDB71

Error 1000278	"\resetclks\" must be run in single-node mode with \"allocation database\". %1"
SQL Code	-1000278L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	Location of the exception.
Probable Cause	resetclks is restricted to allocation mode and single-node mode, and requires checking entire DB

Error 1000279	"Column '%2' must be included in the insert. It is part of a multicolumn index. %1"
Constant	EMSG_INSRT_MISSING_COLUMN_ON_INSERT
SAP Sybase Error Number	21108
SQL State	QDB99
SQL Code	-1000279L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Parameter 2	The name of the column missing in the insert.
Probable Cause	All columns of a multicolumn index must be included in an insert.

Error 1000280	"Secondary server version information has not changed"
Constant	EMSG_IQ_QUERY_NOTCHANGED
SAP Sybase Error Number	21109
SQL State	QDC64
SQL Code	-1000280L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1000280	"Secondary server version information has not changed"
Severity Code	<i>14 on page 2</i>
Probable Cause	ev_iqmpxstatus has run the query event but there is nothing for it to do.

Error 1000281	"Column %2 has unsupported data type for index rebuild. %1"
Constant	EMSG_FPSTYLE_UNSUPPORTED
SAP Sybase Error Number	21110
SQL State	QDC56
SQL Code	-1000281L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	Index name
Probable Cause	You have tried to rebuild an FP index of unsupported index style.

Error 1000282	"DBCC must be restricted to the MAIN or LOCAL store only. %1"
Constant	EMSG_DBCC_ONEMPXSTORE
SAP Sybase Error Number	21116
SQL State	QDB72
SQL Code	-1000282L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>23 on page 2</i>
Parameter 1	Location of the exception.
Probable Cause	DBCC is restricted to either the main or the local store only. It may not combine checking of tables in both main and local in the same dbcc run.

Error 1000283	"Identity/Autoincrement Column value range exceeded for column %2. %1"
Constant	EMSG_IDENTITY_EXCEEDS_RANGE
SAP Sybase Error Number	20030
SQL State	QDC65
SQL Code	-1000283L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	column name
Probable Cause	Data overflow: An Identity/Autoincrement Column has reached its maximum value. To correct this create a new table in which the datatype of the new Identity/Autoincrement Column is larger and copy this table into the new table. Alternatively add a new Identity/Autoincrement Column to the table with a larger datatype and delete the old one.

Error 1000284	"Identity/Autoincrement Column value for column %2 must be positive. %1"
Constant	EMSG_IDENTITY_VALUE_MUST_BE_POSITIVE
SAP Sybase Error Number	20032
SQL State	QDC66
SQL Code	-1000284L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	column name

Error 1000284	"Identity/Autoincrement Column value for column %2 must be positive. %1"
Probable Cause	All values in Identity/Autoincrement Columns must be positive. To correct this, only use positive values when manually inserting into Identity/Autoincrement Columns.

Messages 1000285 through 1000306

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1000285	"The value specified for the Identity/Autoincrement Column %2 exceeds the range of its datatype. %1"
Constant	EMSG_VALUE_TOO_LARGE
SAP Sybase Error Number	20034
SQL State	QDC67
SQL Code	-1000285L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	column name
Probable Cause	The value specified does not fit in the Identity/Autoincrement Column. To correct this, choose a smaller value

Error 1000286	"Invalid table argument %2 to sp_iq_reset_identity, Table has no Identity/Autoincrement Column. %1"
Constant	EMSG_TABLE_HAS_NO_IDENTITY
SAP Sybase Error Number	20035
SQL State	QDC68
SQL Code	-1000286L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1000286	"Invalid table argument %2 to sp_iq_reset_identity, Table has no Identity/Autoincrement Column. %1"
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	name of table
Probable Cause	Table's without Identity/Autoincrement Columns cannot be used in calls to stored procedure sp_iq_reset_identity.

Error 1000287	"Invalid table argument %2 to sp_iq_reset_identity, Table cannot be a JVT. %1"
Constant	EMSG_NO_JVT_RESET_IDENTITY
SAP Sybase Error Number	20036
SQL State	QDC69
SQL Code	-1000287L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	table name
Probable Cause	Tables of type JVT are not allowed as arguments to the stored procedure sp_iq_reset_identity

Error 1000288	"Invalid table argument %2 for set option 'identity_insert', Table cannot be a JVT. %1"
Constant	EMSG_TABLE_CANNOT_BE_JVT
SAP Sybase Error Number	20037
SQL State	QDC70
SQL Code	-1000288L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2

Error 1000288	"Invalid table argument %2 for set option 'identity_insert', Table cannot be a JVT. %1"
Parameter 1	location of the exception
Parameter 2	table name
Probable Cause	Tables of type JVT are not allowed as a value for the set option 'identity_insert'

Error 1000289	"Invalid table argument %2 for set option 'identity_insert', Table must be an IQ table. %1"
Constant	EMSG_TABLE_MUST_BE_IQ_IDENTITY_INSERT
SAP Sybase Error Number	20038
SQL State	QDC71
SQL Code	-1000289L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	table name
Probable Cause	Only IQ tables are allowed as an argument value to the set option 'identity_insert'

Error 1000290	"Invalid table argument %2 for stored procedure sp_iq_reset_identity, Table must be an IQ Table. %1"
Constant	EMSG_TABLE_MUST_BE_IQ_RESET_IDENTITY
SAP Sybase Error Number	20039
SQL State	QDC72
SQL Code	-1000290L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception

Error 1000290	"Invalid table argument %2 for stored procedure sp_iq_reset_identity, Table must be an IQ Table. %1"
Parameter 2	table name
Probable Cause	Only IQ tables are allowed as a table argument to the stored procedure sp_iq_reset_identity

Error 1000291	"You do not have insert permission on table %2. %1"
Constant	EMSG_NO_PERM_IDENTITY_INSERT
SAP Sybase Error Number	20041
SQL State	QDC73
SQL Code	-1000291L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	table name
Probable Cause	You cannot set the option 'identity_insert' to a table for which you do not have insert permission

Error 1000292	"Invalid use of set option 'identity insert'. Table %2 does not have an Identity/Autoincrement Column. %1"
Constant	EMSG_PARAM_TABLE_HAS_NO_IDENTITY
SAP Sybase Error Number	20474
SQL State	QDC74
SQL Code	-1000292L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception
Parameter 2	table name

Error 1000292	"Invalid use of set option 'identity insert'. Table %2 does not have an Identity/Autoincrement Column. %1"
Probable Cause	the set option 'identity insert' cannot be used on a table without an Identity/Autoincrement Column.
Error 1000293	"Cannot insert or update Column %2: set option 'identity_insert' to the specific table name containing the identity column to be modified. %1"
Constant	EMSG_IDENTITY_INSERT_IS_OFF
SAP Sybase Error Number	20644
SQL State	QDC75
SQL Code	-1000293L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception
Parameter 2	column name
Probable Cause	set option 'identity_insert' must be set to the specific table for which you want to insert or update an Identity column. To turn it on use set identity_insert <table_name>
Error 1000294	"Cannot set 'identity_insert', it is already on for a different table. %1"
Constant	EMSG_IDENTITY_INSERT_ON_FOR_OTHER
SAP Sybase Error Number	20645
SQL State	QDC76
SQL Code	-1000294L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception

Error 1000294	"Cannot set 'identity_insert', it is already on for a different table. %1"
Probable Cause	the set option 'identity_insert' can only be set for one table at a time. To set it for a different table, first turn it off using 'set identity_insert '' then set it to the desired table.

Error 1000295	"Invalid table name %2 specified for option 'identity_insert'. %1"
Constant	EMSG_INVALID_TAB_NAME
SAP Sybase Error Number	20646
SQL State	QDC77
SQL Code	-1000295L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception
Parameter 2	table name
Probable Cause	The table associated with the table name specified for the 'identity_insert' option could not be found.

Error 1000296	" Invalid load specification for LOAD ... FORMAT BCP. %1"
Constant	EMSG_INVALIDLOADSPECFORBCPLOAD
SAP Sybase Error Number	21124
SQL State	QDC78
SQL Code	-1000296L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception
Probable Cause	The user specified a load specification that is not supported with FORMAT BCP option.

Warning 1000297	"%1. Message logging stopped."
Constant	EMSG_SQL_IQMSG_MANAGEMENT_ERROR
SAP Sybase Error Number	21149
SQL State	QCB17
SQL Code	1000297L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>1</i> on page 2
Parameter 1	Reason behind stopping of message logging. Can be either due to disk error, or due to message log management error.
Probable Cause	Message log management operation failed due to error in file renaming / deletion / creation. Or log could not be written in the IQMSG file because some DISK IO error occurred.

Warning 1000298	" Message logging resumed."
Constant	EMSG_MESSAGE_LOGGING_RESUMED
SAP Sybase Error Number	21150
SQL State	QCB18
SQL Code	1000298L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>1</i> on page 2
Probable Cause	Engine has detected that reason behind message log management / message logging failure has been resolved. Message logging is resumed now.

Error 1000299	" Partition key of %2 is unsupported. %1"
Constant	EMSG_CAT_UNSUPPORTED_PARTITION_KEY
SAP Sybase Error Number	21152
SQL State	QDC79

Error 1000299	" Partition key of %2 is unsupported. %1"
SQL Code	-1000299L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	datatype
Parameter 2	location of exception
Probable Cause	Partiiton key of LOB/CLOB/char/varchar/binary/varbinary over 255 is not supported.

Error 1000302	" Exceed maximum number of partitions. %1"
Constant	EMSG_CAT_EXCEED_MAX_NUM_PARTITIONS
SAP Sybase Error Number	21155
SQL State	QDC82
SQL Code	-1000302L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception
Probable Cause	Exceed maximum number of partitions.

Error 1000303	" Object %2 not usable in current context. %1"
Constant	EMSG_CAT_OBJECT_NOT_USABLE
SAP Sybase Error Number	21156
SQL State	QDC83
SQL Code	-1000303L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2

Error 1000303	" Object %2 not usable in current context. %1"
Parameter 1	location of exception
Parameter 2	object name
Probable Cause	Table of TBLTYP_PARTITION type cannot be used.

Error 1000304	" Cannot drop a partition key column. %1"
Constant	EMSG_CAT_CANNOT_DROP_PARTITION_KEY
SAP Sybase Error Number	21157
SQL State	QDC84
SQL Code	-1000304L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception
Probable Cause	Can not drop a partition key column.

Error 1000305	" Allocation failure. %1"
Constant	EMSG_DBCC_ALLOCATION_FAILURE
SAP Sybase Error Number	21158
SQL State	QDC85
SQL Code	-1000305L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	DBCC allocation failure

Error 1000306	" Different DB space, cannot merge partition %2 into %3. %1"
Constant	EMSG_CAT_PARTITION_MERGE_ERROR

Error 1000306	" Different DB space, cannot merge partition %2 into %3. %1"
SAP Sybase Error Number	21164
SQL State	QDC86
SQL Code	-1000306L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception
Parameter 2	partition1
Parameter 3	partition2
Probable Cause	Cannot merge Partition partition name 1 into Partition partition name2 in different dbspaces

Messages 1000307 through 1000328

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1000307	" No data move is allowed, cannot split partition %2. %1"
Constant	EMSG_CAT_PARTITION_SPLIT_ERROR
SAP Sybase Error Number	21165
SQL State	QDC87
SQL Code	-1000307L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception
Parameter 2	partition1
Probable Cause	Cannot split Partition partition name 1 into Partition partition name2 and Partition name3 as the split requires to move data.

Error 1000308	" Boundary value for the partition %2 cannot be changed. %1"
Constant	EMSG_CAT_PARTITION_SPLIT_BOUNDARY_ERROR
SAP Sybase Error Number	21166
SQL State	QDC88
SQL Code	-1000308L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception
Parameter 2	partition name1
Probable Cause	Cannot change boundary value for split Partition partition name 1 into (partition-decl-1, partition-decl-2). Boundary value for partition-decl-2 must be the same as partition name 1.

Error 1000309	" Not all partitions in each column are in same dbspace, cannot unpartition %2. %1"
Constant	EMSG_CAT_UNPARTITION_ERROR
SAP Sybase Error Number	21167
SQL State	QDC89
SQL Code	-1000309L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception
Parameter 2	tablename
Probable Cause	Cannot alter partitioned table to an unpartitioned table as not all partitions in each column are in the same dbspace.

Error 1000310	" Cannot truncate table partition on a non-partitioned table %2. %1"
Constant	EMSG_TABLE_NOT_PARTITIONED
SAP Sybase Error Number	21168
SQL State	QDC90
SQL Code	-1000310L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception
Parameter 2	tablename
Probable Cause	Cannot truncate table partition on a non-partitioned table.

Error 1000311	" '%2' is not an IQ DBSPACE. %1"
Constant	EMSG_NO_SUCH_IQ_DBSPACE
SAP Sybase Error Number	21169
SQL State	QDC91
SQL Code	-1000311L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception
Parameter 2	supplied dbspace name
Probable Cause	Specified dbspace does not exist or is a catalog dbspace.

Error 1000312	" ALTER INDEX MOVE can not move FP indexes. Command failed for %2. Use ALTER TABLE MOVE COLUMN instead. %1"
Constant	EMSG_CANNOT_MOVE_FP_INDEX
SAP Sybase Error Number	21170

Error 1000312	" ALTER INDEX MOVE can not move FP indexes. Command failed for %2. Use ALTER TABLE MOVE COLUMN instead. %1"
SQL State	QDC92
SQL Code	-1000312L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception
Parameter 2	Index name
Probable Cause	ALTER INDEX MOVE command does not move FP indexes. Use ALTER TABLE MOVE COLUMN instead.

Error 1000314	" All rows must be in the first partition. %1"
Constant	EMSG_CAT_PARTITION_ERROR
SAP Sybase Error Number	21173
SQL State	QDC94
SQL Code	-1000314L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception
Probable Cause	Cannot alter unpartitioned table to a partitioned table as not all rows in the first partition.

Error 1000315	" Cannot drop the last partition of a partitioned table. %1"
Constant	EMSG_CAT_CANNOT_DROP_LAST_PARTITION_ERROR
SAP Sybase Error Number	21174
SQL State	QDC95
SQL Code	-1000315L

Error 1000315	" Cannot drop the last partition of a partitioned table. %1 "
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception
Probable Cause	Cannot drop the last partition of a partitioned table.

Error 1000316	"The NoExec option is set. The current operation will be rolled back. %1"
Constant	EMSG_NOEXEC_OP_PROHIBITED
SAP Sybase Error Number	21175
SQL State	QDC96
SQL Code	-1000316L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Probable Cause	Certain operations will not be allowed whenever the NoExec option is set. They are: Alter table Split Partition & Alter Table Partition

Error 1000317	"The current operation is not allowed on RO partition. %1"
Constant	EMSG_ROPARTITION_OP_PROHIBITED
SAP Sybase Error Number	21181
SQL State	QDC97
SQL Code	-1000317L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.

Error 1000317	"The current operation is not allowed on RO partition. %1"
Probable Cause	Alter table drop/split/merge on a RO partition is not allowed.

Error 1000318	"Unexpected type encountered for column '%2'. %1"
Constant	EMSG_UNEXPECTED_COLUMN_TYPE
SAP Sybase Error Number	21182
SQL State	QDC98
SQL Code	-1000318L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Exception Location
Parameter 2	Column Name
Probable Cause	Parse tree contains an expected column type.

Error 1000319	"Server (%2) is no longer a Multiplex coordinator. %1"
Constant	EMSG_MPX_NODE_NOT_COORDINATOR
SAP Sybase Error Number	21185
SQL State	QDC99
SQL Code	-1000319L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Parameter 1 description
Parameter 2	Parameter 2 description
Probable Cause	Specified server is no longer a Multiplex coordinator.

Error 1000320	"Table with table id %2 no longer exists. %1"
Constant	EMSG_INVALID_TABLE_ID

Error 1000320	"Table with table id %2 no longer exists. %1"
SAP Sybase Error Number	21189
SQL State	QDD00
SQL Code	-1000320L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Table identifier
Probable Cause	There is no table with the given table id. It would have been dropped.

Error 1000321	"dropleaks is not allowed in multiplex mode. %1"
Constant	EMSG_DBCC_DROPLEAKS_NEED_SIMPLEX
SAP Sybase Error Number	22006
SQL State	QDB85
SQL Code	-1000321L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	Location of the exception.
Probable Cause	Dropleaks require server to be started in simplex configuration

Error 1000322	"Use CREATE DBSPACE USING FILE syntax for creating IQ dbspaces. %1"
Constant	EMSG_CREATE_DBSPACE_FILE_SYNTAX_NOT_USED
SAP Sybase Error Number	22007
SQL State	QDB86
SQL Code	-1000322L

Error 1000322	"Use CREATE DBSPACE USING FILE syntax for creating IQ dbspaces. %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	Location of the exception.
Probable Cause	In Atomic IQ dbspaces can be created using the FILE Syntax for create dbspace. Old pre-atomic syntax can be used to create catalog store dbspaces only.

Error 1000324	"Maximum secondary node license limit reached. Cannot add new secondary node. %1"
Constant	EMSG_MPX_MAX_SECONDARY_LICENSE_EXCEEDED
SAP Sybase Error Number	21193
SQL State	QDD03
SQL Code	-1000324L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Probable Cause	New secondary node cannot be added since the license limit for adding a new secondary node has been reached.

Error 1000325	"%2 node cannot be made a failover node. %1"
Constant	EMSG_MPX_CANNOT_BE_FAILOVER
SAP Sybase Error Number	21194
SQL State	QDD04
SQL Code	-1000325L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>

Error 1000325	"%2 node cannot be made a failover node. %1"
Parameter 1	location of the exception
Parameter 2	Could be either Excluded or Coordinator
Probable Cause	An excluded or coordinator node cannot be made a failover node.

Error 1000326	"%2 of Coordinator node cannot be changed. %1"
Constant	EMSG_MPX_COORD_ATTR_CANNOT_CHANGE
SAP Sybase Error Number	21195
SQL State	QDD05
SQL Code	-1000326L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Could be either ROLE or STATUS
Probable Cause	ROLE or STATUS of Coordinator node cannot be changed.

Error 1000327	"Failover node cannot be Excluded. %1"
Constant	EMSG_MPX_CANNOT_EXCLUDE_FAILOVER
SAP Sybase Error Number	21196
SQL State	QDD06
SQL Code	-1000327L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	A designated failover node cannot be Excluded.

Error 1000328	"%2 node cannot be dropped. %1"
Constant	EMSG_MPX_CANNOT_BE_DROPPED
SAP Sybase Error Number	21197
SQL State	QDD07
SQL Code	-1000328L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Could be either COORDINATOR or FAILOVER
Probable Cause	A Coordinator or a Failover node cannot be dropped from the multiplex configuration.

1000329 - 1006035

Messages 1000329 through 1001010

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1000329	"The move target %2 is already in the specified dbspace. %1"
Constant	EMSG_MOVE_TARGET_DBSPACE_UNCHANGED
SAP Sybase Error Number	21198
SQL State	QDD02
SQL Code	-1000329L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Target name to be moved.
Parameter 2	Location of the exception.

Error 1000329	"The move target %2 is already in the specified dbspace. %1"
Probable Cause	The move target for alter table or alter index is already in the specified dbspace.
Error 1000330	"Default value %2 cannot be used as a LOAD default value. %1"
Constant	EMSG_INVALIDLOADDEFAULTVALUE
SAP Sybase Error Number	21199
SQL State	QDD17
SQL Code	-1000330L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception
Parameter 2	load default value
Probable Cause	Specified default value cannot be used as a LOAD default value.
Error 1000331	"The requested FP style (%1) for %2 cannot be rebuilt. It will be rebuilt as %3."
Constant	EMSG_CANNOT_REBUILD_FP
SAP Sybase Error Number	21204
SQL State	QDD19
SQL Code	-1000331L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Requested FP style
Parameter 2	FP index
Parameter 3	Actual Rebuilt FP style

Error 1000331	"The requested FP style (%1) for %2 cannot be rebuilt. It will be rebuilt as %3."
Probable Cause	The requested FP style cannot be rebuilt. Increase main cache or set FP_Lookup_Size_PPM to a higher percentage for 3-byte FP.
Error 1000332	"Odd length of binary data value detected on column %2 - %1"
Constant	EMSG_ODDNUMBER_NIBBLES
SAP Sybase Error Number	21206
SQL State	QDD20
SQL Code	-1000332L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	the column where the error occurs
Probable Cause	When loading hexadecimal data into BLOB, the total number of nibbles has to be an even number. If an odd number is detected, the load engine will rollback. This restriction does not apply to binary and varbinary data type.
Error 1000333	"DBCC IQ_SHARED_TEMP dbspace target not allowed with other targets. %1"
Constant	EMSG_DBCC_SHTEMP_MODE
SAP Sybase Error Number	22021
SQL State	QDD22
SQL Code	-1000333L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	Location of the exception.

Error 1000333	"DBCC IQ_SHARED_TEMP dbspace target not allowed with other targets. %1"
Probable Cause	When specifying the IQ_SHARED_TEMP dbspace as a DBCC mode target, no other targets may be specified.

Error 1000334	"Unsupported DBCC dbspace target \"%2\". %1"
Constant	EMSG_DBCC_UNSUPPORTED_DBSPACE
SAP Sybase Error Number	22022
SQL State	QDD23
SQL Code	-1000334L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	Location of the exception.
Parameter 2	Dbspace name.
Probable Cause	DBCC Does not support checking modes on this dbspace target.

Error 1000335	"Cannot add writer when coordinator started with - iqmpx_nowr %1"
Constant	EMSG_MPX_NO_WRITER_ALLOWED
SAP Sybase Error Number	21214
SQL State	QDD25
SQL Code	-1000335L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	Please restart coordinator without -iqmpx_nowr switch to add writer node

Error 1000336	"Cannot convert to writer when coordinator started with -iqmpx_nowr %1"
Constant	EMSG_MPX_ROLE_CHANGE_DENIED_NOWR
SAP Sybase Error Number	21215
SQL State	QDD26
SQL Code	-1000336L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	Please restart coordinator without -iqmpx_nowr switch to change role to writer

Error 1000337	" Number of columns in Hash Partition key cannot be greater than %2. %1"
Constant	EMSG_CAT_NUM_HASH_PARTITION_KEY_COL_EXCEEDED
SAP Sybase Error Number	21216
SQL State	QDD27
SQL Code	-1000337L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of exception
Parameter 2	Maximum number of allowed columns in hash key
Probable Cause	Hash partition key columns cannot be greater than the allowed value.

Error 1001000	"DFE Sum or Average overflow - try CASTing the argument to a larger datatype. %1"
Constant	EMSG_SUMAVGOVERFLOW

Error 1001000	"DFE Sum or Average overflow - try CASTing the argument to a larger datatype. %1"
SAP Sybase Error Number	20509
SQL State	QFA00
SQL Code	-1001000L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1001001	"DFE Typechecking error %1"
Constant	EMSG_TCHECKERROR
SAP Sybase Error Number	20510
SQL State	QFA01
SQL Code	-1001001L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1001002	"Feature is not yet implemented %1"
Constant	EMSG_NOTIMPLEMENTED
SAP Sybase Error Number	20511
SQL State	QFA02
SQL Code	-1001002L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1001002	"Feature is not yet implemented %1"
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1001003	"Internal error: subclass responsibility %1"
Constant	EMSG_SUBCLASSRESPONSIBILITY
SAP Sybase Error Number	20512
SQL State	QFA03
SQL Code	-1001003L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	18 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1001004	"Data exception - substring error. %1"
Constant	EMSG_SUBSTRINGERROR
SAP Sybase Error Number	20513
SQL State	QFA04
SQL Code	-1001004L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1001005	"Data exception - string length error. %1"
Constant	EMSG_STRINGLENEROR

Error 1001005	"Data exception - string length error. %1"
SAP Sybase Error Number	20514
SQL State	QFA05
SQL Code	-1001005L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1001006	"Data exception - data type conversion is not possible. %1"
Constant	EMSG_TYPECONVERSION
SAP Sybase Error Number	20515
SQL State	QFA06
SQL Code	-1001006L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1001007	"Data exception - operation resulted in division by zero. %1"
Constant	EMSG_DIVIDEBYZERO
SAP Sybase Error Number	20516
SQL State	QFA07
SQL Code	-1001007L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1001007	"Data exception - operation resulted in division by zero. %1"
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1001008	"Data exception - invalid character data for cast. %1"
Constant	EMSG_BADCASTVALUE
SAP Sybase Error Number	20517
SQL State	QFA08
SQL Code	-1001008L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1001009	"Data exception - string data, right truncation. %1"
Constant	EMSG_TRUNCATEDSTRING
SAP Sybase Error Number	20518
SQL State	QFA09
SQL Code	-1001009L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1001010	"Data exception - numeric value out of range. %1"
Constant	EMSG_NUMERICOUTOFRANGE

Error 1001010	"Data exception - numeric value out of range. %1"
SAP Sybase Error Number	20519
SQL State	QFA10
SQL Code	-1001010L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Messages 1001011 through 1001030

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1001011	"Data exception - argument must be DATE or DATETIME %1"
Constant	EMSG_ARGMUSTBEDATETIME
SAP Sybase Error Number	20520
SQL State	QFA11
SQL Code	-1001011L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1001012	"Internal state violation, please contact Sybase IQ support %1"
Constant	EMSG_INTERNALERROR
SAP Sybase Error Number	20521
SQL State	QFA12

Error 1001012	"Internal state violation, please contact Sybase IQ support %1"
SQL Code	-1001012L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	18 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1001013	"Invalid data type comparison %2, %1"
Constant	EMSG_TYPECOMPAREERROR
SAP Sybase Error Number	20522
SQL State	QFA13
SQL Code	-1001013L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	SA parse source code line
Probable Cause	No additional information available.

Error 1001014	"Data conversion failed %1"
Constant	EMSG_DATACONVERSIONERROR
SAP Sybase Error Number	20523
SQL State	QFA14
SQL Code	-1001014L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2

Error 1001014	"Data conversion failed %1"
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1001015	"QUARTER, WEEK and MILLISECOND dateparts are not currently supported %1"
Constant	EMSG_DATEPARTNOTSUPPORTED
SAP Sybase Error Number	20524
SQL State	QFA15
SQL Code	-1001015L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1001016	"Invalid datepart"
Constant	EMSG_INVALIDDATEPARTTYPE
SAP Sybase Error Number	20525
SQL State	QFA16
SQL Code	-1001016L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	No additional information available.

Error 1001017	"IQ Internal error in exception code. %1 "
Constant	EMSG_PROGERRORINEXCEPTION
SAP Sybase Error Number	20526
SQL State	QFA17

Error 1001017	"IQ Internal error in exception code. %1 "
SQL Code	-1001017L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	18 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1001018	"INSERT ... VALUES ... accepts only constant expressions as values %2, %1"
Constant	EMSG_BADINSERTVALUES
SAP Sybase Error Number	20527
SQL State	QFA18
SQL Code	-1001018L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	SA parse source code line
Probable Cause	No additional information available.

Error 1001019	"Function not supported on varchars longer than 32767 %2, %1"
Constant	EMSG_FUNCNOTSUPONLVCHAR
SAP Sybase Error Number	20528
SQL State	QFA19
SQL Code	-1001019L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1001019	"Function not supported on varchars longer than 32767 %2, %1"
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	SA parse source code line
Probable Cause	No additional information available.

Error 1001020	"Incompatible data types %2, %1"
Constant	EMSG_UNIONNOTCOMPATIBLE
SAP Sybase Error Number	20529
SQL State	QFA20
SQL Code	-1001020L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	SA parse source code line
Probable Cause	No additional information available.

Error 1001021	"DFO State machine error %1"
Constant	EMSG_DFOSTATE
SAP Sybase Error Number	20530
SQL State	QFA21
SQL Code	-1001021L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>18 on page 2</i>
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1001022	"Subquery cardinality violation, > 1 row returned from a subquery %1"
Constant	EMSG_SUBQCARDVIOLATION
SAP Sybase Error Number	20531
SQL State	QFA22
SQL Code	-1001022L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	18 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1001023	"Query rejected because it exceeds resource: Query_Temp_Space_Limit %1"
Constant	EMSG_QUERY_EXCEEDS_SPACE_LIMIT
SAP Sybase Error Number	20532
SQL State	QFA23
SQL Code	-1001023L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	17 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1001024	"Metadata for column %2 is internally inconsistent (%3): database may be corrupted %1"
Constant	EMSG_INCONSISTENT_INDEX_INFO
SAP Sybase Error Number	20533
SQL State	QFA24
SQL Code	-1001024L

Error 1001024	"Metadata for column %2 is internally inconsistent (%3): database may be corrupted %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	column name
Parameter 3	what was apparently corrupted
Probable Cause	No additional information available.

Error 1001025	"Function not currently supported. %2 %1"
Constant	EMSG_DFFUNCNOTSUPPORTED
SAP Sybase Error Number	20534
SQL State	QFA25
SQL Code	-1001025L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	The SA code line
Probable Cause	No additional information available.

Warning 1001026	"%1"
Constant	EMSG_DF_ONEPLANLINE
SAP Sybase Error Number	20535
SQL State	QFA26
SQL Code	1001026L
ODBC 2 State	OK
ODBC 3 State	OK

Warning 1001026	"%1"
Severity Code	<i>1</i> on page 2
Parameter 1	prefix and detail string
Probable Cause	No additional information available.

Error 1001027	"Query rejected because plan exceeds stack space %1"
Constant	EMSG_QUERY_NEAR_END_OF_STACK
SAP Sybase Error Number	20536
SQL State	QFA27
SQL Code	-1001027L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1001028	"Query rejected because it exceeds resource: Query_Rows_Returned_Limit %1"
Constant	EMSG_QUERY_EXCEEDS_ROW_LIMIT
SAP Sybase Error Number	20537
SQL State	QFA28
SQL Code	-1001028L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>17</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1001029	"Index metadata for %2 is internally inconsistent: database may be corrupted %1"
Constant	EMSG_INCONSISTENT_COLUMN_INFO
SAP Sybase Error Number	20538
SQL State	QFA29
SQL Code	-1001029L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	column name
Probable Cause	No additional information available.

Error 1001030	"Feature, %2, is not supported. %1"
Constant	EMSG_NOTIMPLEMENTED_W_ARG
SAP Sybase Error Number	20539
SQL State	QFA2A
SQL Code	-1001030L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	feature name
Parameter 2	SA parse source code line
Probable Cause	No additional information available.

Messages 1001031 through 1001050

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1001031	"Non-aggregate select/having (%2) must appear in the group by %1"
Constant	EMSG_INVALIDGROUPINGEXPR
SAP Sybase Error Number	20540
SQL State	QFA2B
SQL Code	-1001031L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	name of illegal expression
Parameter 2	location of the exception
Probable Cause	No additional information available.

Error 1001032	"Thread stack ran past the end of its allocated stack space %1"
Constant	EMSG_THREAD_PAST_END_OF_STACK
SAP Sybase Error Number	20541
SQL State	QFA2C
SQL Code	-1001032L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1001033	"Internal state violation, please contact Sybase IQ support %2, %1"
Constant	EMSG_INTERNALERROR_W_ARG
SAP Sybase Error Number	20542
SQL State	QFA2D
SQL Code	-1001033L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Exception line number
Parameter 2	SA parse source code line
Probable Cause	No additional information available.

Error 1001034	"Invalid argument to the rowid function."
Constant	EMSG_INVALID_ROWID_ARG
SAP Sybase Error Number	20543
SQL State	QFA30
SQL Code	-1001034L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1001035	"Global variable '%2' in SELECT...FROM... statement is not supported by Sybase IQ, %1"
Constant	EMSG_GLOBVARNOTSUPPORTED
SAP Sybase Error Number	20544
SQL State	QFA31
SQL Code	-1001035L

Error 1001035	"Global variable '%2' in SELECT...FROM... statement is not supported by Sybase IQ, %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	variable name
Probable Cause	No additional information available.

Error 1001036	"Host variable '%2' is not initialized, %1"
Constant	EMSG_HOSTVARNOTINIT
SAP Sybase Error Number	20545
SQL State	QFA32
SQL Code	-1001036L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	variable name
Probable Cause	No additional information available.

Error 1001037	"Text-style CONTAINS left-hand arg must be a character type column from a base table. %1"
Constant	EMSG_CONTAINS_LHS
SAP Sybase Error Number	20546
SQL State	QFA33
SQL Code	-1001037L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1001037	"Text-style CONTAINS left-hand arg must be a character type column from a base table. %1"
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1001038	"Text-style CONTAINS right-hand arglist must be string constants each containing exactly one word. %1"
Constant	EMSG_CONTAINS_RHS
SAP Sybase Error Number	20547
SQL State	QFA34
SQL Code	-1001038L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1001039	"CONTAINS right-hand arglist too large. %1"
Constant	EMSG_CONTAINS_RHS2LARGE
SAP Sybase Error Number	20548
SQL State	QFA35
SQL Code	-1001039L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1001040	"String contains a multi-byte character fragment. %1"
Constant	EMSG_CHARFRAG
SAP Sybase Error Number	20549
SQL State	QFA36
SQL Code	-1001040L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1001041	"Word-style CONTAINS left-hand arg must have a WD index. %1"
Constant	EMSG_CONTAINS_NOINDEX
SAP Sybase Error Number	20550
SQL State	QFA37
SQL Code	-1001041L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1001042	"Table, '%2', is not accessible in this context. %1"
Constant	EMSG_TABLEACCESS_ERR_WARG
SAP Sybase Error Number	20551
SQL State	QFA38
SQL Code	-1001042L
ODBC 2 State	ERROR

Error 1001042	"Table, '%2', is not accessible in this context. %1"
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	table name
Probable Cause	No additional information available.

Error 1001043	"Report to Sybase IQ Support. Query '%2', %1"
Constant	EMSG_REWRITE_QUERY_WARG
SAP Sybase Error Number	20552
SQL State	QFA39
SQL Code	-1001043L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	error message
Probable Cause	No additional information available.

Error 1001044	"Incompatible datatypes in ARGN. %1"
Constant	EMSG_BAD_ARGN
SAP Sybase Error Number	20553
SQL State	QFA40
SQL Code	-1001044L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1001045	"Invalid argument in Extract option: %2. %1"
Constant	EMSG_BAD_EXTRACT_WARG
SAP Sybase Error Number	20554
SQL State	QFA41
SQL Code	-1001045L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Invalid option
Probable Cause	No additional information available.

Error 1001046	"Extract exceeds maximum supported row width of %2 (width %3). %1"
Constant	EMSG_EXTRACT_TOO_WIDE_WARG
SAP Sybase Error Number	20555
SQL State	QFA42
SQL Code	-1001046L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	maximum width supported
Parameter 3	current width
Probable Cause	No additional information available.

Error 1001047	"%2. %1"
Constant	EMSG_QUERY_GENERIC_WARG
SAP Sybase Error Number	20556

Error 1001047	"%2. %1"
SQL State	QFA43
SQL Code	-1001047L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	error message
Probable Cause	No additional information available.

Error 1001048	"To display a varbinary column > 32k you must set the parameter Ase_Binary_Display to off. %1"
Constant	EMSG_VARBIN_TOOBIG
SAP Sybase Error Number	20557
SQL State	QFA44
SQL Code	-1001048L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	cannot convert any varbinary > 32k to varchar.

Error 1001049	"Expression, \"%2\" changed datatypes between CURSOR DESCRIBE and CURSOR OPEN from %3. The CURSOR DESCRIBE needs to be rerun %1"
Constant	EMSG_DATATYPE_CHANGE
SAP Sybase Error Number	20558
SQL State	QFA45
SQL Code	-1001049L
ODBC 2 State	ERROR

Error 1001049	"Expression, \"%2\" changed datatypes between CURSOR DESCRIBE and CURSOR OPEN from %3. The CURSOR DESCRIBE needs to be rerun %1"
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	column number
Parameter 3	datatype info
Probable Cause	Given a database's BLOCK SIZE and the number of blocks specified by the user for the dbspace, the dbspace size (in bytes) would exceed the OS's limit of bytes per file.

Error 1001050	"this row is too wide to extract. Reduce the row width to less than %2 (iq page size) %1"
Constant	EMSG_EXTRACT_ROW_TOO_WIDE
SAP Sybase Error Number	20559
SQL State	QFA46
SQL Code	-1001050L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	this row width
Probable Cause	An attempt was made to extract a row that is larger than this database's pagesize.

Messages 1001051 through 1001071

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1001051	"Query returns %2 data > 2GB. Use %3 %1"
Constant	EMSG_LOB_OVER_2G_W_ARG

Error 1001051	"Query returns %2 data > 2GB. Use %3 %1"
SAP Sybase Error Number	21097
SQL State	QFA47
SQL Code	-1001051L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	long binary or long varchar data type
Parameter 2	function recommended
Parameter 3	SA parse source code line
Probable Cause	No additional information available.

Error 1001052	"Parameter %2 must be long binary/varchar type. %3 %1"
Constant	EMSG_ONLY_SUPPORT_LOB_W_ARG
SAP Sybase Error Number	21098
SQL State	QFA48
SQL Code	-1001052L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	lob argument name
Parameter 2	recommended function name
Parameter 3	SA parse source code line
Probable Cause	No additional information available.

Error 1001053	"Wrong number of parameters to function %2 %1"
Constant	EMSG_WRONG_NUM_PARAMS_W_ARG
SAP Sybase Error Number	21099
SQL State	QFA49

Error 1001053	"Wrong number of parameters to function %2 %1"
SQL Code	-1001053L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	function name
Parameter 2	SA parse source code line
Probable Cause	No additional information available.

Error 1001054	"You cannot specify long binary/varchar column in the ORDER/GROUP by clause or in an aggregate function. %1"
Constant	EMSG_LOB_NOT_ALLOWED_GROUP
SAP Sybase Error Number	21100
SQL State	QFA50
SQL Code	-1001054L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Warning 1001055	"An error occurred loading %1 column, %2, for %3, rowid %4. "
Constant	EMSG_LOB_LOAD_ERROR_WARN
SAP Sybase Error Number	21101
SQL State	QFA51
SQL Code	1001055L
ODBC 2 State	OK
ODBC 3 State	OK

Warning 1001055	"An error occurred loading %1 column, %2, for %3, rowid %4. "
Severity Code	<i>10</i> on page 2
Parameter 1	long binary or long varchar data type
Parameter 2	FP index name
Parameter 3	secondary file name
Parameter 4	rowid
Probable Cause	No additional information available.

Warning 1001056	"An error occurred extracting %1 column, %2, for %3. "
Constant	EMSG_LOB_EXTRACT_ERROR_WARN
SAP Sybase Error Number	21102
SQL State	QFA52
SQL Code	1001056L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10</i> on page 2
Parameter 1	long binary or long varchar data type
Parameter 2	FP index name
Parameter 3	secondary file name
Probable Cause	No additional information available.

Error 1001057	"You must use BFILE() to extract %2 column. %1"
Constant	EMSG_LOB_EXTRACT_USE_BFILE
SAP Sybase Error Number	21103
SQL State	QFA53
SQL Code	-1001057L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1001057	"You must use BFILE() to extract %2 column. %1"
Severity Code	<i>14</i> on page 2
Parameter 1	long binary or long varchar data type
Parameter 2	location of the exception
Probable Cause	No additional information available.

Error 1001058	"The secondary file name, %2, is too long. %1"
Constant	EMSG_LOB_SECONDARY_FILE_TOOLONG
SAP Sybase Error Number	21104
SQL State	QFA54
SQL Code	-1001058L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>14</i> on page 2
Parameter 1	secondary file name
Parameter 2	location of the exception
Probable Cause	No additional information available.

Error 1001059	"IQ does not support ASE extended group by syntax (%2) with join tables %1"
Constant	EMSG_EXTGROUPINGWITHJOIN
SAP Sybase Error Number	21106
SQL State	QFA2F
SQL Code	-1001059L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	name of illegal expression
Parameter 2	location of the exception

Error 1001059	"IQ does not support ASE extended group by syntax (%2) with join tables %1"
Probable Cause	No additional information available.
Error 1001060	"IQ does not support ASE extended group by columns (%2) from view/derived table with distinct/group by/aggregations %1"
Constant	EMSG_EXTGROUPINGFROMVIEW
SAP Sybase Error Number	21107
SQL State	QFA2G
SQL Code	-1001060L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	name of illegal expression
Parameter 2	location of the exception
Probable Cause	No additional information available.
Error 1001061	"extract error: incorrect \"%2\" size: valid sizes \"0 to %3\" %1"
Constant	EMSG_EXTRACT_ERROR
SAP Sybase Error Number	20560
SQL State	QFA55
SQL Code	-1001061L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	type of extract delimiter error
Parameter 3	max size

Error 1001061	"extract error: incorrect \"%2\" size: valid sizes \"0 to %3\" %1"
Probable Cause	either a column delimiter or a row delimiter is of incorrect length

Error 1001062	"IQ does not support ASE extended group by syntax (%2) with OLAP function %1"
Constant	EMSG_EXTGROUPINGWITHOLAP
SAP Sybase Error Number	21120
SQL State	QFA2H
SQL Code	-1001062L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	name of illegal expression
Parameter 2	location of the exception
Probable Cause	No additional information available.

Error 1001063	"Encrypt/Decrypt: Currently only AES algorithm is supported."
Constant	EMSG_ENCRYPT_ALGO_ERROR
SAP Sybase Error Number	20561
SQL State	QFA56
SQL Code	-1001063L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	when the algorithm string is other than AES.

Error 1001064	"Decryption error: %2. %1"
Constant	EMSG_DECRYPTION_ERROR

Error 1001064	"Decryption error: %2. %1"
SAP Sybase Error Number	20562
SQL State	QFA57
SQL Code	-1001064L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	error message
Probable Cause	An error occurred during decryption.

Error 1001065	"Encryption/Decryption for %2 datatype is not supported. %1"
Constant	EMSG_ENCRYPT_UNSUPPORTED_DATATYPE
SAP Sybase Error Number	20563
SQL State	QFA58
SQL Code	-1001065L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	datatype value which is not supported like float.
Probable Cause	An error occurred during encryption/decryption.

Error 1001066	"Encrypt/Decrypt Error: %2. %1"
Constant	EMSG_ENCRYPT_SIZE_ERROR
SAP Sybase Error Number	20564
SQL State	QFA59
SQL Code	-1001066L

Error 1001066	"Encrypt/Decrypt Error: %2. %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	large input and key size not supported.
Probable Cause	An error occurred during encryption/decryption.

Error 1001067	"Encrypt/Decrypt Error: %2. %1"
Constant	EMSG_ENCRYPT_NULL_ERROR
SAP Sybase Error Number	20565
SQL State	QFA60
SQL Code	-1001067L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	key and algorithm string as null are not supported.
Probable Cause	An error occurred during encryption/decryption.

Error 1001068	"Datatype, %2 is not supported for this operation. %1"
Constant	EMSG_DATATYPE_NOT_SUPPORTED_ERROR
SAP Sybase Error Number	20567
SQL State	QFA61
SQL Code	-1001068L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception

Error 1001068	"Datatype, %2 is not supported for this operation. %1"
Parameter 2	datatype.
Probable Cause	The reported datatype is not supported by Sybase IQ.

Error 1001070	"Unable to load shared library for user-defined function. %1"
Constant	EMSG_UDF_LIBRARY_ERROR
SAP Sybase Error Number	20569
SQL State	QFA63
SQL Code	-1001070L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	Shared library for the UDF could not be loaded.

Error 1001071	"No valid license found for user-defined function. Feature: %2 %1"
Constant	EMSG_UDF_LICENSE_ERROR
SAP Sybase Error Number	20572
SQL State	QFA64
SQL Code	-1001071L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	licensed feature
Parameter 2	location of the exception
Probable Cause	No valid license found for UDF feature.

Messages 1001072 through 1003001

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1001072	"User-defined function %2 internal programming error. %3 . %1"
Constant	EMSG_UDF_PROGRAMMING_ERROR
SAP Sybase Error Number	20573
SQL State	QFA65
SQL Code	-1001072L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	function name
Parameter 3	specific UDF programming error
Probable Cause	User-defined function has an internal programming error.

Error 1001073	"The result datatype for function '%2' exceeds the maximum supported numeric precision of 255. Please set the proper value for precision in numeric function, %1"
Constant	EMSG_PRECISIONOVERFLOW
SAP Sybase Error Number	20574
SQL State	QFA66
SQL Code	-1001073L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Field Name

Error 1001073	"The result datatype for function '%2' exceeds the maximum supported numeric precision of 255. Please set the proper value for precision in numeric function, %1"
Probable Cause	Precision requested for numeric function is larger than what is allowed. Please set the proper value for precision if not set.

Error 1001074	"The number of select list columns do not match the required for the input table parameter %2, %1"
Constant	EMSG_TPF_INBL_INSEL_COLNUM_MISMATCH
SAP Sybase Error Number	20575
SQL State	QFA67
SQL Code	-1001074L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	input table parameter name
Probable Cause	MARKNEW Please check your input query or definition of the UDF.

Error 1001100	"Load/insert/update/delete/RLV are not supported for 15.x char/varchar/varbinary columns of width greater than 255 and LOB datatypes. Please execute sp_iqrebuildindex first to convert the index to IQ version 16. %1"
Constant	EMSG_15_LVC_LOB_UPDATE_NOT_SUPPORTED
SAP Sybase Error Number	22150
SQL State	QSB92
SQL Code	-1001100L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception

Error 1001100	"Load/insert/update/delete/RLV are not supported for 15.x char/varchar/varbinary columns of width greater than 255 and LOB datatypes. Please execute sp_iqrebuildindex first to convert the index to IQ version 16. %1"
Probable Cause	When IQ 16.x engine attempts to load/insert/update data into a 15.x char/varchar/varbinary greater than 255 or LOB FP index, this exception is thrown to indicate that the operation is not allowed. It is required to run sp_iqrebuildindex first so as to convert the index to IQ version 16.

Error 1001102	"RLV store merge already in progress for table %2. %1"
Constant	EMSG_RV_MERGE_IN_PROGRESS
SAP Sybase Error Number	22038
SQL State	QRA02
SQL Code	-1001102L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	The illegal merge string
Probable Cause	There is already an RLV store merge in progress for this table. Only one RLV merge is allowed at a time for an RLV table.

Error 1001103	"Table %2 is not RLV enabled. %1"
Constant	EMSG_RV_MERGE_NOT_RLV_ENABLED
SAP Sybase Error Number	22039
SQL State	QRA03
SQL Code	-1001103L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception

Error 1001103	"Table %2 is not RLV enabled. %1"
Parameter 2	The table name
Probable Cause	An RLV store merge was attempted on a table which was not RLV enabled. Only tables which are RLV enabled may be merged.

Error 1001104	"Unable to perform merge, table %2 has too many fragments. %1"
Constant	EMSG_RV_MERGE_TOO_MANY_FRAGMENTS
SAP Sybase Error Number	22040
SQL State	QRA04
SQL Code	-1001104L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	table name
Probable Cause	Long running transactions are keeping too many old fragments of the table in memory. Table cannot be merged until the long running transactions terminate.

Error 1001105	"Table %2 requires an RLV store merge before table-level modification. %1"
Constant	EMSG_RV_MERGE_NEEDED
SAP Sybase Error Number	22041
SQL State	QRA05
SQL Code	-1001105L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2

Error 1001105	"Table %2 requires an RLV store merge before table-level modification. %1"
Parameter 1	location of the exception
Parameter 2	The table name
Probable Cause	An table-level RW operation was attempted on an RLV table requiring merge of the RLV store. This merge cannot be done automatically because the current transaction has already established a snapshot version for this table. Either run a manual merge first using sp_iqmergerlvstore or modify the transaction such that blocking is enabled and the the first statement in the transaction is a table-level RW command.

Error 1001106	"Transaction attempted to delete or update a row in '%2' already deleted or updated by another transaction. %1"
Constant	EMSG_RV_FUTUREVERSION
SAP Sybase Error Number	22042
SQL State	QRA06
SQL Code	-1001106L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	The table name
Probable Cause	A transaction attempted to delete or update a row that has already been deleted or updated by another transaction. Row Level Versioning does not allow access to future versions of the row.

Error 1001107	"PARALLEL IQ is not supported for RLV enabled tables."
Constant	EMSG_RV_NO_PARALLEL_IQ
SAP Sybase Error Number	22043
SQL State	QRA07
SQL Code	-1001107L
ODBC 2 State	ERROR

Error 1001107	"PARALLEL IQ is not supported for RLV enabled tables."
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	BEGIN .. END PARALLEL IQ is not supported if any of the tables on which (parallel) index is to be created is RLV enabled.

Error 1001108	"The option 'Revert_To_V15_Optimizer' is not supported for queries involving RLV enabled tables"
Constant	EMSG_RV_V15_CONFLICT
SAP Sybase Error Number	22044
SQL State	QRA08
SQL Code	-1001108L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	Pre-Elan optimization is used with revert_to_v15_optimizer option, query tree creation itself does not allow it if table is RLV enabled.

Error 1002000	"Unknown error: %1"
Constant	EMSG_DATA_UNKNOWN
SAP Sybase Error Number	20502
SQL State	QGA00
SQL Code	-1002000L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1002001	"Data has already been inserted into index %2 for row %3. %1"
Constant	EMSG_DATA_ALREADYINSERTED
SAP Sybase Error Number	20503
SQL State	QGA01
SQL Code	-1002001L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Parameter 3	explanation for arg %3 delete if no %3
Probable Cause	No additional information available.

Error 1002002	" for IQ_ROWID row "
Constant	EMSG_NOT_USED
SAP Sybase Error Number	20504
SQL State	QGA02
SQL Code	-1002002L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1002003	"Tried to insert a duplicate value into a unique index %2 on row %3. %1"
Constant	EMSG_DATA_DUPLICATEVALUE
SAP Sybase Error Number	20505
SQL State	QGA03

Error 1002003	"Tried to insert a duplicate value into a unique index %2 on row %3. %1"
SQL Code	-1002003L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Parameter 3	explanation for arg %3 delete if no %3
Probable Cause	No additional information available.

Error 1002004	No message
Constant	EMSG_DATA_DUPLICATEVALUE2_EMPTY_SLOT
SAP Sybase Error Number	20506
SQL State	QGA04
SQL Code	-1002004L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1002005	"Tried to insert a null value into a non-null field %2 on row %3. %1"
Constant	EMSG_DATA_NONULLSALLOWED
SAP Sybase Error Number	20507
SQL State	QGA05
SQL Code	-1002005L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1002005	"Tried to insert a null value into a non-null field %2 on row %3. %1"
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Parameter 3	explanation for arg %3 delete if no %3
Probable Cause	No additional information available.

Error 1002006	No message
Constant	EMSG_DATA_NONULLSALLOWED2_EMPTY_SLOT
SAP Sybase Error Number	20508
SQL State	QGA06
SQL Code	-1002006L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	No additional information available.

Error 1003000	"Datatype %2, returned by Client Library, is not valid in Sybase IQ. %1"
Constant	EMSG_HQM_BAD_DATATYPE
SAP Sybase Error Number	20172
SQL State	QHA00
SQL Code	-1003000L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	name of the CTLib datatype

Error 1003000	"Datatype %2, returned by Client Library, is not valid in Sybase IQ. %1"
Probable Cause	Sybase IQ doesn't support a number of datatypes that ASE does (text or image, for example). Refer to documentation for the respective products to see what datatypes are supported.
Error 1003001	"Cannot convert to Sybase IQ datatype: %2 from Client Library datatype %3. %1"
Constant	EMSG_HQM_CANT_CONVERT
SAP Sybase Error Number	20173
SQL State	QHA01
SQL Code	-1003001L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	name of the IQ datatype
Parameter 3	name of the CTLib datatype
Probable Cause	Error converting CSLIB datatype to IQ datatype.

Messages 1003002 through 1004007

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1003002	"CtLibrary Error: %2, Severity: %3, Origin: %4, Layer: %5\nError Message: %6\nOS Error: %7, OS Message: %8. %1"
Constant	EMSG_HQM_CTLIB_ERROR
SAP Sybase Error Number	20174
SQL State	QHA02
SQL Code	-1003002L
ODBC 2 State	ERROR

Error 1003002	"CtLibrary Error: %2, Severity: %3, Origin: %4, Layer: %5\nError Message: %6\nOS Error: %7, OS Message: %8. %1"
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	CtLib error number
Parameter 3	CtLib severity number
Parameter 4	CtLib origin number
Parameter 5	CtLib layer number
Parameter 6	CtLib error message
Parameter 7	OS error number (optional)
Parameter 8	OS error message (optional)
Probable Cause	General CTLIB/CSLIB error message. Refer to the CTLibrary/CSLibrary for error information.

Error 1003003	"Adaptive Server Error: %2, Severity: %3, State: %4, Line: %5\nServer Name: %6, Procedure Name: %7\nError Message: %8. %1"
Constant	EMSG_HQM_SERVER_ERROR
SAP Sybase Error Number	20175
SQL State	QHA03
SQL Code	-1003003L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Server error number
Parameter 3	Server severity number
Parameter 4	Server state number

Error 1003003	"Adaptive Server Error: %2, Severity: %3, State: %4, Line: %5\nServer Name: %6, Procedure Name: %7\nError Message: %8. %1"
Parameter 5	Server line number
Parameter 6	Server name (optional)
Parameter 7	Server stored procedure name (optional)
Parameter 8	Server error message
Probable Cause	ASE error. Refer to the ASE error documentation for information regarding the error.

Error 1003004	"COMPUTE values cannot be used in attached database queries. %1"
Constant	EMSG_HQM_NOCOMPUTES
SAP Sybase Error Number	20176
SQL State	QHA04
SQL Code	-1003004L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	Sybase IQ doesn't process COMPUTE clauses.

Error 1003005	"Connectivity libraries cannot be found (check your dynamic library search path). Selects from attached databases are not possible without these libraries. %1"
Constant	EMSG_HQM_CTSTUB
SAP Sybase Error Number	20177
SQL State	QHA05
SQL Code	-1003005L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1003005	"Connectivity libraries cannot be found (check your dynamic library search path). Selects from attached databases are not possible without these libraries. %1"
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Probable Cause	Cannot process attached DB request without the connectivity libraries. Check your dynamic library search path to make sure it is correct.

Error 1003006	"A call to ct_con_props failed trying to get the msglist from the connection. %1"
Constant	EMSG_HQM_GET_MSG
SAP Sybase Error Number	20178
SQL State	QHA06
SQL Code	-1003006L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	Location of the exception.
Probable Cause	While trying to report an error condition, another error occurred trying to retrieve the original error from the connection in order to report it to the user. If this error occurs, retry the operation that caused it.

Error 1003007	"%2 functionality is not licensed on this server. %1"
Constant	EMSG_NO_LICENSE
SAP Sybase Error Number	20179
SQL State	QHA07
SQL Code	-1003007L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>

Error 1003007	"%2 functionality is not licensed on this server. %1"
Parameter 1	Location of the exception.
Parameter 2	Product or feature that is not licensed on the server.
Probable Cause	The named feature is not licensed on the server.

Error 1003008	"Licensing error. Code = %2. %1"
Constant	EMSG_CAT_LICENSE_ERROR
SAP Sybase Error Number	20180
SQL State	QHA08
SQL Code	-1003008L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Parameter 2	Error code returned from the license checking.
Probable Cause	An error occurred while verifying the license. Refer to the documentation for information about the Code reported in the error.

Error 1003009	"The specified target contains no indexes on which to report. %1"
Constant	EMSG_NOTHING_TO_REPORT
SAP Sybase Error Number	20181
SQL State	QHA09
SQL Code	-1003009L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Probable Cause	sp_iqindexfragmentation will report this error if it is run on a table that contains only FP indexes.

Error 1003010	No message
Constant	EMSG_HQM_EMPTY_SLOT6
SAP Sybase Error Number	20182
SQL State	QHA10
SQL Code	-1003010
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1003011	No message
Constant	EMSG_HQM_EMPTY_SLOT7
SAP Sybase Error Number	20183
SQL State	QHA11
SQL Code	-1003011L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1003012	No message
Constant	EMSG_HQM_EMPTY_SLOT8
SAP Sybase Error Number	20184
SQL State	QHA12
SQL Code	-1003012L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Errors and Warnings

Error 1003013	No message
Constant	EMSG_HQM_EMPTY_SLOT9
SAP Sybase Error Number	20185
SQL State	QHA13
SQL Code	-1003013L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1003014	No message
Constant	EMSG_HQM_EMPTY_SLOT10
SAP Sybase Error Number	20186
SQL State	QHA14
SQL Code	-1003014L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1004000	"The number of connections in the connection pool have exceeded the upper limit"
Constant	EMSG_INC_MAXCONNEXCEEDED
SAP Sybase Error Number	20209
SQL State	QIA00
SQL Code	-1004000L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1004000	"The number of connections in the connection pool have exceeded the upper limit"
Severity Code	<i>14 on page 2</i>
Probable Cause	The number of connections in the connection pool have exceeded the total number of connections allowed in the connection pool. No more connections can be allocated.

Error 1004001	"Number of unused connections exceeded the maximum number of unused connections in the connection pool"
Constant	EMSG_INC_MAXUNUSEDEXCEEDED
SAP Sybase Error Number	20210
SQL State	QIA01
SQL Code	-1004001L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	The number of unused connections in the connection pool has exceeded the maximum number of unused connections in the connection pool.

Error 1004003	"Timeout period should be greater than or equal to the heartbeat frequency"
Constant	EMSG_INVALIDTIMEOUTPERIOD1
SAP Sybase Error Number	20212
SQL State	QIA03
SQL Code	-1004003L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	All the timeout periods should be greater than or equal to the heartbeat frequency.

Error 1004004	"No connection found for the server id %1 on the coordinator"
Constant	EMSG_CONNECTIONNOTFOUND
SAP Sybase Error Number	20215
SQL State	QIA04
SQL Code	-1004004L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Parameter 1 description
Probable Cause	A secondary node with the given server id does not exist on the coordinator connection list

Error 1004005	"Timeout period should be multiple of the Heartbeat Frequency"
Constant	EMSG_INVALIDTIMEOUTPERIOD2
SAP Sybase Error Number	20216
SQL State	QIA05
SQL Code	-1004005L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	All the timeout periods of INC(e.g.,AUTOEXCLUDE,LIVENESS,IDLE_CONNECTION) requires to be multiple of the Heartbeat Frequency.

Error 1004006	"Unused Connection Pool size should be always less than the Maximum Connection Pool size"
Constant	EMSG_INVALIDUNUSEDPOOLSIZE
SAP Sybase Error Number	20217
SQL State	QIA06

Error 1004006	"Unused Connection Pool size should be always less than the Maximum Connection Pool size"
SQL Code	-1004006L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	Unused Connection pool size can not be greater than the maximum allowable size of the Connection pool

Error 1004007	"Unable to acquire a pooled connection to the coordinator node"
Constant	EMSG_INC_NOPOOLEDCONNECTION
SAP Sybase Error Number	20218
SQL State	QIA07
SQL Code	-1004007L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	There are no empty pooled connections on the secondary node and also no new connections can be established because the total number of connections has exceeded the maximum capacity of the connection pool

Messages 1004008 through 1005010

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1004008	"Coordinator node is offline"
Constant	EMSG_INC_NODE_OFFLINE
SAP Sybase Error Number	20219
SQL State	QIA08
SQL Code	-1004008L

Error 1004008	"Coordinator node is offline"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	Coordinator node is offline and hence, all the suspended commands on the suspended connections will be terminated

Error 1004009	"INC communication failure %1"
Constant	EMSG_INC_CONN_INTERNAL_ERROR
SAP Sybase Error Number	20220
SQL State	QIA09
SQL Code	-1004009L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	Location of exception
Probable Cause	INC communication failure. This can happen if either the coordinator or the secondary node is restarted or shutdown down when the other node is trying to connect to it

Error 1004010	"Error in getting current user information"
Constant	EMSG_INC_NOUSERFOUND
SAP Sybase Error Number	20221
SQL State	QIA10
SQL Code	-1004010L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	Error returned while trying to find out the current user connected to the given node

Error 1004011	"Coordinator node not responding"
Constant	EMSG_INC_NODE_NOT_ALIVE
SAP Sybase Error Number	21222
SQL State	QIA11
SQL Code	-1004011L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	Coordinator node is not responding. Check to see if the Coordinator is running

Error 1004012	"INC communication between coordinator and secondary failed due to : %2 %1"
Constant	EMSG_INC_CONN_ERROR
SAP Sybase Error Number	21223
SQL State	QIA12
SQL Code	-1004012L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of exception
Parameter 2	Error message returned from target server
Probable Cause	INC communication failed between coordinator and secondary nodes. The error returned from target node is also displayed. This connection is similar to a client connection.

Error 1004013	"Cannot drop multiplex server %2 as it holds freelist. %1"
Constant	EMSG_MPX_CANNOT_DROP_HOLDS_FREELIST
SAP Sybase Error Number	21224

Error 1004013	"Cannot drop multiplex server %2 as it holds freelist. %1"
SQL State	QDD08
SQL Code	-1004013L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception
Parameter 2	Multiplex Server Name
Probable Cause	If a writer holds a freelist, it cannot be dropped. If the writer can be started, start it. This is because a startup or a clean shutdown will clear the freelist. If the writer cannot be restarted, restart the coordinator with -iqmpx_reclaim-writerfreelist <server name> server switch to force the coordinator to reset the writer freelist.

Error 1004014	"Trying to execute an unknown SQL type over the INC connection"
Constant	EMSG_INC_CONN_UNKNOWN_STMT
SAP Sybase Error Number	20225
SQL State	QIA14
SQL Code	-1004014L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	The node is trying to execute an unknown SQL over the dblib connections

Error 1004015	"Permission denied: Command not allowed on Multiplex %2 servers. %1"
Constant	EMSG_MPX_CMD_PERMISSION_LEVEL_DENIED
SAP Sybase Error Number	21225
SQL State	QIA15

Error 1004015	"Permission denied: Command not allowed on Multiplex %2 servers. %1"
SQL Code	-1004015L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception
Parameter 2	Role of current node
Probable Cause	The command is not permitted on current multiplex node

Warning 1004060	"Warning: Heartbeat frequency should be less than or equal to other timeout periods"
Constant	EMSG_INVALIDHEARTBEATFREQUENCY1
SAP Sybase Error Number	20211
SQL State	01A60
SQL Code	1004060L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	01 on page 2
Probable Cause	The heartbeat frequency should always be less than or equal to other timeout period. This is to make sure that the time lag between the timeout occurring and the time when it is detected is minimal.

Warning 1004061	"Warning: All INC timeout periods should be multiple of Heartbeat frequency"
Constant	EMSG_INVALIDHEARTBEATFREQUENCY2
SAP Sybase Error Number	20213
SQL State	QIA61
SQL Code	1004061L
ODBC 2 State	OK
ODBC 3 State	OK

Warning 1004061	"Warning: All INC timeout periods should be multiple of Heartbeat frequency"
Severity Code	<i>01</i> on page 2
Probable Cause	All the timeout periods of INC(e.g.,AUTOEXCLUDE,LIVEN-ESS,IDLE_CONNECTION) requires to be multiple of the Heartbeat Frequency.

Error 1005000	"Bind parameters are not supported in data flow query processing"
Constant	EMSG_BINDPARAMETERS_UNSUPPORTED
SAP Sybase Error Number	20154
SQL State	QTA00
SQL Code	-1005000L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Probable Cause	No additional information available.

Error 1005001	"Query has exceeded the supported maximum number of tables that can be joined. %1"
Constant	EMSG_TOO_MANY_TABLES_TO_JOIN
SAP Sybase Error Number	20155
SQL State	QTA01
SQL Code	-1005001L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1005002	"Subquery predicates are not supported in the ON clause of outer joins in this release. %1"
Constant	EMSG_NO_SUBQ_PREDS_IN_OUTER_JOINS
SAP Sybase Error Number	20156
SQL State	QTA02
SQL Code	-1005002L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.
Error 1005003	"A maximum of one subquery predicate per conjunct is supported in this release. %1"
Constant	EMSG_ONLY_ONE_SUBQ_PER_CONJUNCT
SAP Sybase Error Number	20157
SQL State	QTA03
SQL Code	-1005003L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.
Error 1005004	"Subqueries are allowed only as arguments of comparisons, IN, and EXISTS %2, %1"
Constant	EMSG_ILLEGAL_SUBQUERY_USAGE
SAP Sybase Error Number	20158
SQL State	QTA04
SQL Code	-1005004L

Error 1005004	"Subqueries are allowed only as arguments of comparisons, IN, and EXISTS %2, %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	SA code line
Probable Cause	No additional information available.

Error 1005005	"Deleting from views is not supported. %1"
Constant	EMSG_NO_UPDATABLE_VIEWS
SAP Sybase Error Number	20159
SQL State	QTA05
SQL Code	-1005005L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1005006	"The target DELETE table must also appear in FROM. %1"
Constant	EMSG_ILLEGAL_FROMCLAUSE_FOR_DELETE
SAP Sybase Error Number	20160
SQL State	QTA06
SQL Code	-1005006L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception

Error 1005006	"The target DELETE table must also appear in FROM. %1"
Probable Cause	No additional information available.

Error 1005008	"Sybase IQ does not support nested aggregations. %1"
Constant	EMSG_UNSUPPORTEDNESTEDAGG
SAP Sybase Error Number	20162
SQL State	QTA08
SQL Code	-1005008L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1005009	"Cannot perform an aggregate function on a column from a table not declared in the same query. %2, %1"
Constant	EMSG_OUTERSINAGG
SAP Sybase Error Number	20163
SQL State	QTA09
SQL Code	-1005009L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	SQL Commandline line
Probable Cause	No additional information available.

Error 1005010	"The field '%2' is not unique and needs to be qualified, %1"
Constant	EMSG_FIELDNOTUNIQUE
SAP Sybase Error Number	20164

Error 1005010	"The field '%2' is not unique and needs to be qualified, %1"
SQL State	QTA10
SQL Code	-1005010L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Messages 1005011 through 1005030

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1005011	"There are two tables named '%2'. Please specify an alias for one of them. %1"
Constant	EMSG_TABLENOTUNIQUE
SAP Sybase Error Number	20165
SQL State	QTA11
SQL Code	-1005011L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	table name which is not unique
Probable Cause	No additional information available.

Error 1005012	"The field '%2' specified in the query cannot be found, %1"
Constant	EMSG_FIELDNOTDEFINED
SAP Sybase Error Number	20166

Error 1005012	"The field '%2' specified in the query cannot be found, %1"
SQL State	QTA12
SQL Code	-1005012L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1005013	"The FROM clause must have at least one table identifier %1"
Constant	EMSG_SEMANTIC_NO_TABLES_IN_FROM_CLAUSE
SAP Sybase Error Number	20167
SQL State	QTA13
SQL Code	-1005013L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1005014	"Non-space text found after ending quote character for an enclosed field. %1"
Constant	EMSG_NONSPACE_AFTER_QUOTE
SAP Sybase Error Number	20168
SQL State	QTA14
SQL Code	-1005014L
ODBC 2 State	ERROR

Error 1005014	"Non-space text found after ending quote character for an enclosed field. %1"
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	Non-space text found after ending quote character for an enclosed field.

Error 1005015	"The optimizer was unable to find a query plan that avoided cartesian product joins larger than the Max_Cartesian_Result setting %1"
Constant	EMSG_CARTESION_RESULT_TOO_BIG
SAP Sybase Error Number	20169
SQL State	QTA15
SQL Code	-1005015L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1005016	"Aggregate functions are not allowed in a GROUP BY clause %1"
Constant	EMSG_ILLEGAL_SET_FUNCTION_USAGE
SAP Sybase Error Number	20170
SQL State	QTA16
SQL Code	-1005016L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception

Error 1005016	"Aggregate functions are not allowed in a GROUP BY clause %1"
Probable Cause	No additional information available.

Error 1005017	"You cannot DELETE from a join virtual table. (%2) %1"
Constant	EMSG_CANNOT_DELETE_FROM_JVT
SAP Sybase Error Number	20171
SQL State	QTA17
SQL Code	-1005017L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Tablename
Probable Cause	If this message occurs, it means that the user has tried to DELETE from a join virtual table. This is not permitted.

Error 1005018	"Illegal ORDER BY item %2, %1"
Constant	EMSG_BAD_ORDERBY_ITEM
SAP Sybase Error Number	20989
SQL State	QTA18
SQL Code	-1005018L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	argument
Probable Cause	No additional information available.

Error 1005019	"The update FROM list must match the table-clause exactly"
Constant	EMSG_BAD_UPDATE_FROM_LIST
SAP Sybase Error Number	21060
SQL State	QTA19
SQL Code	-1005019L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1005020	"Only single-table updates are supported by Sybase IQ"
Constant	EMSG_SINGLE_TABLE_UPDATE_ONLY
SAP Sybase Error Number	21062
SQL State	QTA20
SQL Code	-1005020L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1005021	"Sybase IQ does not allow subqueries in update set-items"
Constant	EMSG_SUBQ_NOT_ALLOWED_IN_SETITEM
SAP Sybase Error Number	21063
SQL State	QTA21
SQL Code	-1005021L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2

Error 1005021	"Sybase IQ does not allow subqueries in update set-items"
Probable Cause	No additional information available.

Error 1005022	"Aggregate not valid in update set-item expression."
Constant	EMSG_AGG_NOT_ALLOWED_IN_SETITEM
SAP Sybase Error Number	21066
SQL State	QTA22
SQL Code	-1005022L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1005023	"Unmatched number of select list items in union"
Constant	EMSG_UNMATCHED_SELECT_LISTS_IN_UNION
SAP Sybase Error Number	21073
SQL State	QTA23
SQL Code	-1005023L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	Cube message here

Error 1005024	"Estimate number: %2 exceed the MAX_CUBE_RESULT of GROUP BY CUBE or ROLLUP %1"
Constant	EMSG_EXCEED_MAX_CUBE_RESULT
SAP Sybase Error Number	21074
SQL State	QTA24
SQL Code	-1005024L
ODBC 2 State	ERROR

Error 1005024	"Estimate number: %2 exceed the MAX_CUBE_RESULT of GROUP BY CUBE or ROLLUP %1"
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location
Parameter 2	the estimated total result of hash base cube
Probable Cause	location of the exception the estimated total result of hash base cube or rollup

Error 1005025	"Query rejected as too complex. After join simplifications there were still %2 tables to be joined, which exceeds the current setting of Max_Join_Enumeration. %1"
Constant	EMSG_JOINS_TOO_COMPLEX
SAP Sybase Error Number	21089
SQL State	QTA25
SQL Code	-1005025L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	the user name specified
Probable Cause	The query will take too long to optimize, so it is being rejected

Error 1005026	"Update not supported on null supplying side of outer join."
Constant	EMSG_UPDATE_NOT_ALLOWED_NULL_OUTER
SAP Sybase Error Number	21090
SQL State	QTA26
SQL Code	-1005026L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1005026	"Update not supported on null supplying side of outer join."
Severity Code	<i>14</i> on page 2
Probable Cause	No additional information available.

Error 1005027	"An error occurs during unistring conversion - %2. %1"
Constant	EMSG_UNILIB_ERR
SAP Sybase Error Number	21091
SQL State	QTA27
SQL Code	-1005027L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	the details of unilib error
Probable Cause	No additional information available.

Error 1005028	"Syntax error - %2. %1"
Constant	EMSG_SYNTAX_ERROR
SAP Sybase Error Number	21092
SQL State	QTA28
SQL Code	-1005028L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	the details of syntax error
Probable Cause	No additional information available.

Error 1005029	"You cannot SELECT from a join virtual table. (%2) %1"
Constant	EMSG_CANNOT_SELECT_FROM_JVT
SAP Sybase Error Number	21143
SQL State	QTA29
SQL Code	-1005029L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	the details of the syntax error
Probable Cause	No additional information available.

Error 1005030	"Query has an ambiguous table reference between prepare and open cursor (%2). %1"
Constant	EMSG_INCONSISTENT_TABLES
SAP Sybase Error Number	21145
SQL State	QTA30
SQL Code	-1005030L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	Location of the exception.
Parameter 2	table name
Probable Cause	SA allows a base and temp table to both have the same table name. In some places, such as when a temp table is created in a stored procedure between the describe and open, IQ can find the base table in the describe and the temp table in the open, giving inconsistent results.

Messages 1005031 through 1006015

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1005031	"Illegal PARTITION BY item %2, %1"
Constant	EMSG_BAD_PARTITIONBY_ITEM
SAP Sybase Error Number	21217
SQL State	QTA31
SQL Code	-1005031L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	column name or ordinal number
Probable Cause	MARKNEW The specified column name or ordinal number is not present within the select list.

Error 1005032	"Conflicting partitioning requirements were detected in UDF '%2' and SQL '%3', %1"
Constant	EMSG_PARTITIONBY_SPECS_CONFLICT
SAP Sybase Error Number	21218
SQL State	QTA32
SQL Code	-1005032L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	specification described by the UDF
Parameter 3	specification contained within SQL select

Error 1005032	"Conflicting partitioning requirements were detected in UDF '%2' and SQL '%3', %1"
Probable Cause	MARKNEW The partition by specification described by the UDF and contained within the SQL select conflict.

Error 1005033	"Conflicting ordering requirements were detected: %2, %1"
Constant	EMSG_ORDERBY_SPECS_CONFLICT
SAP Sybase Error Number	21219
SQL State	QTA33
SQL Code	-1005033L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	conflict message
Probable Cause	MARKNEW The order by specification described by the UDF and contained within the SQL select conflict.

Error 1005034	"column is not present in the projection list, %1"
Constant	EMSG_COLUMN_NOT_PRESENT_IN_PROJECTION_LIST
SAP Sybase Error Number	21220
SQL State	QTA34
SQL Code	-1005034L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available..

Error 1006000	"IQ Internal error. Please report this to Sybase IQ support. %1"
Constant	EMSG_PROGERROR
SAP Sybase Error Number	20238
SQL State	QBA00
SQL Code	-1006000L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006001	"IQ Internal error. Please report this to Sybase IQ support. %2 %1"
Constant	EMSG_PROGERROR2
SAP Sybase Error Number	20239
SQL State	QBA01
SQL Code	-1006001L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006002	"IQ Internal error. Please report this to Sybase IQ support. %2 %3 %1"
Constant	EMSG_PROGERROR3
SAP Sybase Error Number	20240
SQL State	QBA02

Error 1006002	"IQ Internal error. Please report this to Sybase IQ support. %2 %3 %1"
SQL Code	-1006002L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Parameter 3	explanation for arg %3 delete if no %3
Probable Cause	No additional information available.

Error 1006003	"IQ Internal error. Please report this to Sybase IQ support. %2 %3 %4 %1"
Constant	EMSG_PROGERROR4
SAP Sybase Error Number	20241
SQL State	QBA03
SQL Code	-1006003L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Parameter 3	explanation for arg %3 delete if no %3
Parameter 4	explanation for arg %4 delete if no %4
Probable Cause	No additional information available.

Error 1006004	"IQ Internal error. Please report this to Sybase IQ support. %2 %3 %4 %5 %1"
Constant	EMSG_PROGERROR5
SAP Sybase Error Number	20242

Error 1006004	"IQ Internal error. Please report this to Sybase IQ support. %2 %3 %4 %5 %1"
SQL State	QBA04
SQL Code	-1006004L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Parameter 3	explanation for arg %3 delete if no %3
Parameter 4	explanation for arg %4 delete if no %4
Parameter 5	explanation for arg %5 delete if no %5
Probable Cause	No additional information available.

Error 1006005	"IQ Internal error. Please report this to Sybase IQ support. %2 %3 %4 %5 %6 %1"
Constant	EMSG_PROGERROR6
SAP Sybase Error Number	20243
SQL State	QBA05
SQL Code	-1006005L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Parameter 3	explanation for arg %3 delete if no %3
Parameter 4	explanation for arg %4 delete if no %4
Parameter 5	explanation for arg %5 delete if no %5
Parameter 6	explanation for arg %6 delete if no %6

Error 1006005	"IQ Internal error. Please report this to Sybase IQ support. %2 %3 %4 %5 %6 %1"
Probable Cause	No additional information available.

Error 1006006	"IQ Internal error. Please report this to Sybase IQ support. %2 %3 %4 %5 %6 %7 %1"
Constant	EMSG_PROGERROR7
SAP Sybase Error Number	20244
SQL State	QBA06
SQL Code	-1006006L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Parameter 3	explanation for arg %3 delete if no %3
Parameter 4	explanation for arg %4 delete if no %4
Parameter 5	explanation for arg %5 delete if no %5
Parameter 6	explanation for arg %6 delete if no %6
Parameter 7	explanation for arg %7 delete if no %7
Probable Cause	No additional information available.

Error 1006007	"IQ Internal error. Please report this to Sybase IQ support. %2 %3 %4 %5 %6 %7 %8 %1"
Constant	EMSG_PROGERROR8
SAP Sybase Error Number	20245
SQL State	QBA07
SQL Code	-1006007L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1006007	"IQ Internal error. Please report this to Sybase IQ support. %2 %3 %4 %5 %6 %7 %8 %1"
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Parameter 3	explanation for arg %3 delete if no %3
Parameter 4	explanation for arg %4 delete if no %4
Parameter 5	explanation for arg %5 delete if no %5
Parameter 6	explanation for arg %6 delete if no %6
Parameter 7	explanation for arg %7 delete if no %7
Parameter 8	explanation for arg %8 delete if no %8
Probable Cause	No additional information available.

Error 1006008	"IQ Internal error. Please report this to Sybase IQ support. %2 %3 %4 %5 %6 %7 %8 %9 %1"
Constant	EMSG_PROGERROR9
SAP Sybase Error Number	20246
SQL State	QBA08
SQL Code	-1006008L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Parameter 3	explanation for arg %3 delete if no %3
Parameter 4	explanation for arg %4 delete if no %4
Parameter 5	explanation for arg %5 delete if no %5
Parameter 6	explanation for arg %6 delete if no %6
Parameter 7	explanation for arg %7 delete if no %7

Error 1006008	"IQ Internal error. Please report this to Sybase IQ support. %2 %3 %4 %5 %6 %7 %8 %9 %1"
Parameter 8	explanation for arg %8 delete if no %8
Parameter 9	explanation for arg %9 delete if no %9
Probable Cause	No additional information available.

Error 1006009	"Exception Stack Full %1"
Constant	EMSG_ERRORSTACKFULL
SAP Sybase Error Number	20247
SQL State	QBA09
SQL Code	-1006009L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006010	"No TRY Found %1"
Constant	EMSG_ERRORNOTRYFOUND
SAP Sybase Error Number	20248
SQL State	QBA10
SQL Code	-1006010L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006011	"No Exception object found"
Constant	EMSG_ERRORTHROWNNOEXCEPT

Error 1006011	"No Exception object found"
SAP Sybase Error Number	20249
SQL State	QBA11
SQL Code	-1006011L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006012	"No Top Of Stack Set %1"
Constant	EMSG_ERRORNOTOPOFSTACK
SAP Sybase Error Number	20250
SQL State	QBA12
SQL Code	-1006012L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006013	"Try Stack Corrupt %1"
Constant	EMSG_ERRORTRYSTACKCORRUPT
SAP Sybase Error Number	20251
SQL State	QBA13
SQL Code	-1006013L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception

Error 1006013	"Try Stack Corrupt %1"
Probable Cause	No additional information available.

Error 1006014	"Object Not Found"
Constant	EMSG_ERRORNOOBJECTFOUND
SAP Sybase Error Number	20252
SQL State	QBA14
SQL Code	-1006014L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006015	"Invalid Object size on stack"
Constant	EMSG_ERRORSTACKOBJSIZE
SAP Sybase Error Number	20253
SQL State	QBA15
SQL Code	-1006015L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Messages 1006016 through 1006035

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1006016	"hdb_sqlcode thrown: "
Constant	EMSG_ERRORHDBSQLCODETHROWN
SAP Sybase Error Number	20254
SQL State	QBA16

Error 1006016	"hdb_sqlcode thrown: "
SQL Code	-1006016L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006017	"Number of REGISTER()/UNREGISTER() calls do not match"
Constant	EMSG_ERRORREGUNREG
SAP Sybase Error Number	20255
SQL State	QBA17
SQL Code	-1006017L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006018	"Exception Stack could not malloc more memory"
Constant	EMSG_ERRORBADMALLOC
SAP Sybase Error Number	20256
SQL State	QBA18
SQL Code	-1006018L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006019	"Exception Stack overflow during grow"
Constant	EMSG_ERRORGROWOVFL

Error 1006019	"Exception Stack overflow during grow"
SAP Sybase Error Number	20257
SQL State	QBA19
SQL Code	-1006019L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006020	"Group Object Not Found"
Constant	EMSG_ERRORGROUPOBJECTNOTFOUND
SAP Sybase Error Number	20258
SQL State	QBA20
SQL Code	-1006020L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006021	"objects still registered on hos_ObjectStack when ~hos_ObjectStack() called"
Constant	EMSG_ERRORSTILLREGISTERED
SAP Sybase Error Number	20259
SQL State	QBA21
SQL Code	-1006021L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006022	**** Aborting because AbortOnErrorNumber Matched ****
Constant	EMSG_ERRORTHROW_ABORTONNUMBER
SAP Sybase Error Number	20260
SQL State	QBA22
SQL Code	-1006022L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006023	**** Aborting because AbortOnErrorFile&Line Matched ****
Constant	EMSG_ERRORTHROW_ABORTONFILELINE
SAP Sybase Error Number	20261
SQL State	QBA23
SQL Code	-1006023L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006024	"Memory Corruption Found %1"
Constant	EMSG_MEMORY_CORRUPTED
SAP Sybase Error Number	20262
SQL State	QBA24
SQL Code	-1006024L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2

Error 1006024	"Memory Corruption Found %1"
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006025	"No Shared Memory Manager %1"
Constant	EMSG_MEMORY_NOSHAREDMEMMGR
SAP Sybase Error Number	20263
SQL State	QBA25
SQL Code	-1006025L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006026	"Zero Pointer Passed to hos_free %1"
Constant	EMSG_MEMORY_BADPTR
SAP Sybase Error Number	20264
SQL State	QBA26
SQL Code	-1006026L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006027	"Mark Stack Invalid %1"
Constant	EMSG_MEMORY_INVALIDMARKSTACK
SAP Sybase Error Number	20265

Error 1006027	"Mark Stack Invalid %1"
SQL State	QBA27
SQL Code	-1006027L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006028	"Memory Type Invalid\nFound Object %2. Size %3 Type %4\nAllocated from %5 : %6 %1"
Constant	EMSG_MEMORY_BADTYPE
SAP Sybase Error Number	20266
SQL State	QBA28
SQL Code	-1006028L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Parameter 3	explanation for arg %3 delete if no %3
Parameter 4	explanation for arg %4 delete if no %4
Parameter 5	explanation for arg %5 delete if no %5
Parameter 6	explanation for arg %6 delete if no %6
Probable Cause	No additional information available.

Error 1006029	"Memory Manager Leak Found\nCurrent Allocated Memory %2\nFound object %3 Size %4 Type %5\nAllocated from %6 : %7 %1"
Constant	EMSG_MEMORY_LEAK

Error 1006029	"Memory Manager Leak Found\nCurrent Allocated Memory %2 \nFound object %3 Size %4 Type %5 \nAllocated from %6 : %7 %1 "
SAP Sybase Error Number	20267
SQL State	QBA29
SQL Code	-1006029L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Parameter 3	explanation for arg %3 delete if no %3
Parameter 4	explanation for arg %4 delete if no %4
Parameter 5	explanation for arg %5 delete if no %5
Parameter 6	explanation for arg %6 delete if no %6
Parameter 7	explanation for arg %7 delete if no %7
Probable Cause	No additional information available.

Error 1006030	"Command line error. Invalid command line variable name or value. %1"
Constant	EMSG_CMDERROR
SAP Sybase Error Number	20268
SQL State	QBA30
SQL Code	-1006030L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of failure
Probable Cause	No additional information available.

Error 1006031	"Invalid SQL code %1"
Constant	EMSG_INCORRECT_SQLCODE
SAP Sybase Error Number	20269
SQL State	QBA31
SQL Code	-1006031L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	invalid SQL code
Probable Cause	No additional information available.

Warning 1006032	"\n=n*** File: %1\n\n"
Constant	EMSG_MVION_INFO
SAP Sybase Error Number	20270
SQL State	QBA32
SQL Code	1006032L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	1 on page 2
Parameter 1	file
Probable Cause	No additional information available.

Warning 1006033	"team id %1 : # threads = %2"
Constant	EMSG_THREAD_TEAM_INFO
SAP Sybase Error Number	20271
SQL State	QBA33
SQL Code	1006033L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Warning 1006033	"team id %1 : # threads = %2"
Severity Code	<i>1</i> on page 2
Parameter 1	team id
Parameter 2	thread id
Probable Cause	No additional information available.

Error 1006034	No message
Constant	EMSG_MEMORY_LEAK6_EMPTY_SLOT
SAP Sybase Error Number	20272
SQL State	QBA34
SQL Code	-1006034L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Probable Cause	No additional information available.

Error 1006035	No message
Constant	EMSG_MEMORY_LEAKSHORTFORMHDRTRAILER_EMPTY_SLOT
SAP Sybase Error Number	20273
SQL State	QBA35
SQL Code	-1006035L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Probable Cause	No additional information available.

1006036 - 1006238

Messages 1006036 through 1006055

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1006036	No message
Constant	EMSG_MEMORY_LEAKSHORTFORMTRAILER_EMPTY_SLOT
SAP Sybase Error Number	20274
SQL State	QBA36
SQL Code	-1006036L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006037	No message
Constant	EMSG_MEMORY_LEAKSHORTFORMHDR0_EMPTY_SLOT
SAP Sybase Error Number	20275
SQL State	QBA37
SQL Code	-1006037L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006038	No message
Constant	EMSG_MEMORY_LEAKSHORTFORMHDR1_EMPTY_SLOT
SAP Sybase Error Number	20276
SQL State	QBA38
SQL Code	-1006038L

Error 1006038	No message
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	No additional information available.

Error 1006039	No message
Constant	EMSG_MEMORY_LEAKSHORTFORMHDR2_EMPTY_SLOT
SAP Sybase Error Number	20277
SQL State	QBA39
SQL Code	-1006039L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	No additional information available.

Error 1006040	No message
Constant	EMSG_MEMORY_LEAKSHORTFORM_EMPTY_SLOT
SAP Sybase Error Number	20278
SQL State	QBA40
SQL Code	-1006040L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	No additional information available.

Error 1006041	"No Mark Pointer Found %1"
Constant	EMSG_MEMORY_NOMARK
SAP Sybase Error Number	20279

Error 1006041	"No Mark Pointer Found %1"
SQL State	QBA41
SQL Code	-1006041L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006042	"All available virtual memory has been used; allocation cancelled: [Extra info: %2] %1"
Constant	EMSG_MEMORY_NOMEMORY
SAP Sybase Error Number	20280
SQL State	QBA42
SQL Code	-1006042L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006043	"No more event handlers %1"
Constant	EMSG_MEMORY_NOMOREEVENTHANDLERS
SAP Sybase Error Number	20281
SQL State	QBA43
SQL Code	-1006043L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1006043	"No more event handlers %1"
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006044	"No more Mark Stack slots available %1"
Constant	EMSG_MEMORY_NOMOREMARKSTACKSLOTS
SAP Sybase Error Number	20282
SQL State	QBA44
SQL Code	-1006044L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006045	"Not a Vector: delete[] was called on an object that is not a vector %1"
Constant	EMSG_MEMORY_NOTAVECTOR
SAP Sybase Error Number	20283
SQL State	QBA45
SQL Code	-1006045L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006046	"Is a Vector: delete was called on an object that is a vector; use delete[] %1"
Constant	EMSG_MEMORY_ISAVECTOR
SAP Sybase Error Number	20284
SQL State	QBA46
SQL Code	-1006046L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006047	"Error Memory Object errnum %2 %1"
Constant	EMSG_MEMORY_DEFAULT
SAP Sybase Error Number	20285
SQL State	QBA47
SQL Code	-1006047L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006048	"hos_memArena: memory corrupt %1"
Constant	EMSG_MEMARENA_CORRUPT
SAP Sybase Error Number	20286
SQL State	QBA48
SQL Code	-1006048L

Error 1006048	"hos_memArena: memory corrupt %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006049	"hos_memArena: not all memory returned %1"
Constant	EMSG_MEMARENA_MEMLEAK
SAP Sybase Error Number	20287
SQL State	QBA49
SQL Code	-1006049L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006050	"hos_memArena: out of memory %1"
Constant	EMSG_MEMARENA_OUTOFMEM
SAP Sybase Error Number	20288
SQL State	QBA50
SQL Code	-1006050L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006051	"hos_memArena: could not get memory during initialization %1"
Constant	EMSG_MEMARENA_COULDNOTINIT
SAP Sybase Error Number	20289
SQL State	QBA51
SQL Code	-1006051L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006052	"hos_memArena: unknown error %1"
Constant	EMSG_MEMARENA_DEFAULT
SAP Sybase Error Number	20290
SQL State	QBA52
SQL Code	-1006052L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006053	"Vector index out of bounds %1"
Constant	EMSG_VECTOR_OUTOFBOUNDS
SAP Sybase Error Number	20291
SQL State	QBA53
SQL Code	-1006053L
ODBC 2 State	ERROR

Error 1006053	"Vector index out of bounds %1"
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006054	"Error processing hos_vector_exception. _errnum: %2 %1"
Constant	EMSG_VECTOR_DEFAULT
SAP Sybase Error Number	20292
SQL State	QBA54
SQL Code	-1006054L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006055	No message
Constant	EMSG_BIO_FILESTR_EMPTY_SLOT
SAP Sybase Error Number	20293
SQL State	QBA55
SQL Code	-1006055L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Probable Cause	No additional information available.

Messages 1006056 through 1006075

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1006056	"Invalid File Access argument. File: %2 %1"
Constant	EMSG_BIO_BADACCESS
SAP Sybase Error Number	20294
SQL State	QBA56
SQL Code	-1006056L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006057	"Bad seek in Allocate. File: %2 %1"
Constant	EMSG_BIO_BADALLOCATE
SAP Sybase Error Number	20295
SQL State	QBA57
SQL Code	-1006057L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006058	"Partial read on hos_bio object. File: %2 %1"
Constant	EMSG_BIO_PARTBLK

Error 1006058	"Partial read on hos_bio object. File: %2 %1"
SAP Sybase Error Number	20296
SQL State	QBA58
SQL Code	-1006058L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006059	"An I/O error has occurred on this object. File: %2 %1"
Constant	EMSG_BIO_IOERRORSET
SAP Sybase Error Number	20297
SQL State	QBA59
SQL Code	-1006059L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006060	"Object not open for file %2 %1"
Constant	EMSG_BIO_NOTOPEN
SAP Sybase Error Number	20298
SQL State	QBA60
SQL Code	-1006060L
ODBC 2 State	ERROR

Error 1006060	"Object not open for file %2 %1"
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006061	"Invalid Blocksize %2 %3 %1"
Constant	EMSG_BIO_INVBLKSIZE
SAP Sybase Error Number	20299
SQL State	QBA61
SQL Code	-1006061L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Parameter 3	explanation for arg %3 delete if no %3
Probable Cause	No additional information available.

Error 1006062	"OS error %2 reported on file %3. %1"
Constant	EMSG_BIO_OSERROR
SAP Sybase Error Number	20300
SQL State	QBA62
SQL Code	-1006062L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception

Error 1006062	"OS error %2 reported on file %3. %1"
Parameter 2	The OS has returned Erno.
Parameter 3	The file on which the error occurred.
Probable Cause	No additional information available.

Error 1006063	"Invalid block %2. File: %3 %1"
Constant	EMSG_BIO_BADBLKNO
SAP Sybase Error Number	20301
SQL State	QBA63
SQL Code	-1006063L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Parameter 3	explanation for arg %3 delete if no %3
Probable Cause	No additional information available.

Error 1006064	No message
Constant	EMSG_BIO_BLKNOTOOBIG_EMPTY_SLOT
SAP Sybase Error Number	20302
SQL State	QBA64
SQL Code	-1006064L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Probable Cause	No additional information available.

Error 1006065	No message
Constant	EMSG_BIO_BLKNOTOOBIG2_EMPTY_SLOT
SAP Sybase Error Number	20303
SQL State	QBA65
SQL Code	-1006065L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006066	"Invalid number of blocks File: %2 %1"
Constant	EMSG_BIO_BADNBLKS
SAP Sybase Error Number	20304
SQL State	QBA66
SQL Code	-1006066L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006067	"Filename does not exist. File: %2 %1"
Constant	EMSG_BIO_NOSUCHOBJECT
SAP Sybase Error Number	20305
SQL State	QBA67
SQL Code	-1006067L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1006067	"Filename does not exist. File: %2 %1"
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006068	No message
Constant	EMSG_BIO_NOMESSAGE_EMPTY_SLOT
SAP Sybase Error Number	20306
SQL State	QBA68
SQL Code	-1006068L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Probable Cause	No additional information available.

Error 1006069	"No more system record locks available %1"
Constant	EMSG_BIO_NOMORELOCKS
SAP Sybase Error Number	20307
SQL State	QBA69
SQL Code	-1006069L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006070	"Attempt to use object after EOF on file %2 %1"
Constant	EMSG_BIO_IOEOF

Error 1006070	"Attempt to use object after EOF on file %2 %1"
SAP Sybase Error Number	20308
SQL State	QBA70
SQL Code	-1006070L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006071	"Handle must be greater than 0 File: %2 %1"
Constant	EMSG_BIO_INVHANDLE
SAP Sybase Error Number	20309
SQL State	QBA71
SQL Code	-1006071L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006072	"The file is/will be too big. File: %2 %1"
Constant	EMSG_BIO_FILETOOBIG
SAP Sybase Error Number	20310
SQL State	QBA72
SQL Code	-1006072L
ODBC 2 State	ERROR

Error 1006072	"The file is/will be too big. File: %2 %1"
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006073	"Operation failed, user not owner. File: %2 %1"
Constant	EMSG_BIO_NOTOWNER
SAP Sybase Error Number	20311
SQL State	QBA73
SQL Code	-1006073L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006074	"No such process %2 %1"
Constant	EMSG_BIO_NOSUCHPROCESS
SAP Sybase Error Number	20312
SQL State	QBA74
SQL Code	-1006074L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2

Error 1006074	"No such process %2 %1"
Probable Cause	No additional information available.

Error 1006075	"Operation on file interrupted by user. File: %2 %1"
Constant	EMSG_BIO_INTERRUPT
SAP Sybase Error Number	20313
SQL State	QBA75
SQL Code	-1006075L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Messages 1006076 through 1006095

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1006076	"I/O Error on file %2 %1"
Constant	EMSG_BIO_IOERROR
SAP Sybase Error Number	20314
SQL State	QBA76
SQL Code	-1006076L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006077	"No such device or address %2 %1"
Constant	EMSG_BIO_NOSUCHDEVADDR
SAP Sybase Error Number	20315
SQL State	QBA77
SQL Code	-1006077L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006078	"Argument list too big %2 %1"
Constant	EMSG_BIO_ARGTOBIG
SAP Sybase Error Number	20316
SQL State	QBA78
SQL Code	-1006078L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006079	"Exec format error %2 %1"
Constant	EMSG_BIO_EXECSYNTAX
SAP Sybase Error Number	20317
SQL State	QBA79
SQL Code	-1006079L

Error 1006079	"Exec format error %2 %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006080	"Bad file handle passed to OS on file %2 %1"
Constant	EMSG_BIO_BADFILEHANDLE
SAP Sybase Error Number	20318
SQL State	QBA80
SQL Code	-1006080L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006081	"No children %2 %1"
Constant	EMSG_BIO_NOCHILDREN
SAP Sybase Error Number	20319
SQL State	QBA81
SQL Code	-1006081L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception

Error 1006081	"No children %2 %1"
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006082	"No more processes %2 %1"
Constant	EMSG_BIO_NOMOREPROCESSES
SAP Sybase Error Number	20320
SQL State	QBA82
SQL Code	-1006082L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006083	"No more memory %2 %1"
Constant	EMSG_BIO_NOMOREMEMORY
SAP Sybase Error Number	20321
SQL State	QBA83
SQL Code	-1006083L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006084	"Operation failed on file due to file permissions. File: %2 %1"
Constant	EMSG_BIO_PERMISSION
SAP Sybase Error Number	20322
SQL State	QBA84
SQL Code	-1006084L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006085	"Bad address %2 %1"
Constant	EMSG_BIO_BADADDRESS
SAP Sybase Error Number	20323
SQL State	QBA85
SQL Code	-1006085L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006086	"File already exists. File: %2 %1"
Constant	EMSG_BIO_FILEEXISTS
SAP Sybase Error Number	20324
SQL State	QBA86

Error 1006086	"File already exists. File: %2 %1"
SQL Code	-1006086L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006087	"%2 is not a directory %1"
Constant	EMSG_BIO_NOTDIR
SAP Sybase Error Number	20325
SQL State	QBA87
SQL Code	-1006087L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006088	"%2 is a directory %1"
Constant	EMSG_BIO_ISDIR
SAP Sybase Error Number	20326
SQL State	QBA88
SQL Code	-1006088L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2

Error 1006088	"%2 is a directory %1"
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006089	"Invalid Block I/O argument, maybe %2 is a directory, or it exceeds maximum file size limit for the platform, or trying to use Direct IO on unsupported OS %1"
Constant	EMSG_BIO_INVARG
SAP Sybase Error Number	20327
SQL State	QBA89
SQL Code	-1006089L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006090	No message
Constant	EMSG_BIO_INVARG2_EMPTY_SLOT
SAP Sybase Error Number	20328
SQL State	QBA90
SQL Code	-1006090L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	No additional information available.

Error 1006091	"File table is full %2 %1"
Constant	EMSG_BIO_FILETABLEFULL
SAP Sybase Error Number	20329
SQL State	QBA91
SQL Code	-1006091L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006092	"Too many files %2 %1"
Constant	EMSG_BIO_TOMANYFILES
SAP Sybase Error Number	20330
SQL State	QBA92
SQL Code	-1006092L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006093	"File is too large. File: %2 %1"
Constant	EMSG_BIO_FILETOLARGE
SAP Sybase Error Number	20331
SQL State	QBA93
SQL Code	-1006093L

Error 1006093	"File is too large. File: %2 %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006094	"Disk is or will be full on I/O to or allocation of file %2 %1"
Constant	EMSG_BIO_DISKFULL
SAP Sybase Error Number	20332
SQL State	QBA94
SQL Code	-1006094L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006095	"Read only filesystem on file %2 %1"
Constant	EMSG_BIO_READONLYFS
SAP Sybase Error Number	20333
SQL State	QBA95
SQL Code	-1006095L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception

Error 1006095	"Read only filesystem on file %2 %1"
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Messages 1006096 through 1006116

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1006096	"Backup device is busy %2 %1"
Constant	EMSG_IO_DEVICEBUSY
SAP Sybase Error Number	20334
SQL State	QBA96
SQL Code	-1006096L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	file that caused the problem
Probable Cause	No additional information available.

Error 1006097	"The database is locked by another user File: "
Constant	EMSG_BIO_FILELOCKED
SAP Sybase Error Number	20335
SQL State	QBA97
SQL Code	-1006097L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006098	"Blockmap Bufman For "
Constant	EMSG_BUFMAN_BMID
SAP Sybase Error Number	20336
SQL State	QBA98
SQL Code	-1006098L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006099	"Shared Bufman For "
Constant	EMSG_BUFMAN_SHRBUFMANID
SAP Sybase Error Number	20337
SQL State	QBA99
SQL Code	-1006099L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006100	"Shared Temp Bufman For "
Constant	EMSG_BUFMAN_SHRTEMPBUFMANID
SAP Sybase Error Number	20338
SQL State	QBB00
SQL Code	-1006100L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006101	"Buffer too small %1"
Constant	EMSG_CMPRS_BUFFTOOSMALL
SAP Sybase Error Number	20339
SQL State	QBB01
SQL Code	-1006101L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006102	"Unknown error"
Constant	EMSG_LZSTACK_UNKNOWN
SAP Sybase Error Number	20340
SQL State	QBB02
SQL Code	-1006102L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Probable Cause	No additional information available.

Error 1006103	"Stack underflow during expansion"
Constant	EMSG_LZSTACK_UNDERFLOW
SAP Sybase Error Number	20341
SQL State	QBB03
SQL Code	-1006103L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2

Error 1006103	"Stack underflow during expansion"
Probable Cause	No additional information available.

Error 1006104	"Stack overflow during expansion"
Constant	EMSG_LZSTACK_OVERFLOW
SAP Sybase Error Number	20342
SQL State	QBB04
SQL Code	-1006104L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006106	"Invalid file path: %2 %1"
Constant	EMSG_FN_BAD_PATH
SAP Sybase Error Number	20344
SQL State	QBB06
SQL Code	-1006106L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006107	"Invalid disk name: %2 %1"
Constant	EMSG_FN_BAD_DISK
SAP Sybase Error Number	20345
SQL State	QBB07

Error 1006107	"Invalid disk name: %2 %1"
SQL Code	-1006107L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006108	"Invalid directory name(s): %2 %1"
Constant	EMSG_FN_BAD_DIRS
SAP Sybase Error Number	20346
SQL State	QBB08
SQL Code	-1006108L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006109	"Invalid file name: %2 %1"
Constant	EMSG_FN_BAD_NAME
SAP Sybase Error Number	20347
SQL State	QBB09
SQL Code	-1006109L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2

Error 1006109	"Invalid file name: %2 %1"
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.
Error 1006110	"Invalid file extension : %2 %1"
Constant	EMSG_FN_BAD_EXT
SAP Sybase Error Number	20348
SQL State	QBB10
SQL Code	-1006110L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.
Error 1006111	"Invalid file version : %2 %1"
Constant	EMSG_FN_BAD_VERS
SAP Sybase Error Number	20349
SQL State	QBB11
SQL Code	-1006111L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006112	"Unknown file error : %2 %1"
Constant	EMSG_FN_UNKNOWN
SAP Sybase Error Number	20350
SQL State	QBB12
SQL Code	-1006112L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006113	"Unknown error %1"
Constant	EMSG_BITVEC_UNKNOWN
SAP Sybase Error Number	20351
SQL State	QBB13
SQL Code	-1006113L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006114	"Operation on two hos_bitvec objects that are not the same size %1"
Constant	EMSG_BITVEC_SIZEERROR
SAP Sybase Error Number	20352
SQL State	QBB14
SQL Code	-1006114L

Error 1006114	"Operation on two hos_bitvec objects that are not the same size %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006115	"Operation on hos_bitvec object is out of range. %1"
Constant	EMSG_BITVEC_INDEXERROR
SAP Sybase Error Number	20353
SQL State	QBB15
SQL Code	-1006115L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006116	"Attempting to set/unset an already set/unset bit. %1"
Constant	EMSG_BITVEC_SETERROR
SAP Sybase Error Number	20354
SQL State	QBB16
SQL Code	-1006116L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Messages 1006117 through 1006137

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1006117	"Record Size Invalid"
Constant	EMSG_OS_SORT_INVALIDRECSIZE
SAP Sybase Error Number	20355
SQL State	QBB17
SQL Code	-1006117L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006118	"This class does not support multiple instances"
Constant	EMSG_SORT_MULTIPLEINSTANCES
SAP Sybase Error Number	20356
SQL State	QBB18
SQL Code	-1006118L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006119	"SORT Error: %s"
Constant	EMSG_SORT_COSORTERROR
SAP Sybase Error Number	20357
SQL State	QBB19
SQL Code	-1006119L
ODBC 2 State	ERROR

Error 1006119	"SORT Error: %s"
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	No additional information available.

Error 1006120	"The operation has been cancelled - Max_Query_Time exceeded"
Constant	EMSG_ATTN_OUTOFTIME
SAP Sybase Error Number	20358
SQL State	QBB20
SQL Code	-1006120L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	No additional information available.

Error 1006121	"Unknown error message"
Constant	EMSG_SORT_UNKNOWN
SAP Sybase Error Number	20359
SQL State	QBB21
SQL Code	-1006121L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	No additional information available.

Error 1006123	"Attempt to add an invalid extent %1"
Constant	EMSG_MVBIO_EXTENTSIZE
SAP Sybase Error Number	20361
SQL State	QBB23

Error 1006123	"Attempt to add an invalid extent %1"
SQL Code	-1006123L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006124	"Attempt to operate on object before being opened %1"
Constant	EMSG_MVBIO_NOTOPEN
SAP Sybase Error Number	20362
SQL State	QBB24
SQL Code	-1006124L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006125	"Bad block number %2 passed to object %1"
Constant	EMSG_MVBIO_BADBLK
SAP Sybase Error Number	20363
SQL State	QBB25
SQL Code	-1006125L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) bad block number

Error 1006125	"Bad block number %2 passed to object %1"
Probable Cause	No additional information available.

Error 1006126	"The File access and MVBIO access do not match %1"
Constant	EMSG_MVBIO_BADACCESS
SAP Sybase Error Number	20364
SQL State	QBB26
SQL Code	-1006126L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006127	"The File is out of space. File: %2 %1"
Constant	EMSG_MVBIO_DBFULL
SAP Sybase Error Number	20365
SQL State	QBB27
SQL Code	-1006127L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006128	"Invalid File Access argument. %1"
Constant	EMSG_IO_BADACCESS
SAP Sybase Error Number	20366

Error 1006128	"Invalid File Access argument. %1"
SQL State	QBB28
SQL Code	-1006128L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006129	"An I/O error has occurred on this object."
Constant	EMSG_IO_IOERRORSET
SAP Sybase Error Number	20367
SQL State	QBB29
SQL Code	-1006129L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006130	"Object not open for file %2 %1"
Constant	EMSG_IO_NOTOPEN
SAP Sybase Error Number	20368
SQL State	QBB30
SQL Code	-1006130L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	file that could not be opened.

Error 1006130	"Object not open for file %2 %1"
Probable Cause	Unable to open file.

Error 1006131	"OS error reported on file: %2 . OS error: %3 %1"
Constant	EMSG_IO_OSERROR
SAP Sybase Error Number	20369
SQL State	QBB31
SQL Code	-1006131L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	file that reports error
Parameter 3	system error IO operation reported (errno)
Probable Cause	No additional information available.

Error 1006132	". OS error: "
Constant	EMSG_IO_OSERROR2_NOT_USED
SAP Sybase Error Number	20370
SQL State	QBB32
SQL Code	-1006132L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006133	"File does not exist. File: %2 %1"
Constant	EMSG_IO_NOSUCHOBJECT
SAP Sybase Error Number	20371

Error 1006133	"File does not exist. File: %2 %1"
SQL State	QBB33
SQL Code	-1006133L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	file that does not exist
Probable Cause	No additional information available.

Error 1006134	"Invalid filename: %2. ':' is not allowed in the filename for this statement. %1"
Constant	EMSG_IO_INVALID_FILE
SAP Sybase Error Number	20372
SQL State	QBB34
SQL Code	-1006134L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Parameter 2	File or device name that is invalid.
Probable Cause	A ":" (colon-colon) is not allowed in the filename by Sybase IQ for the statement being executed."

Error 1006135	"Attempt to use object after EOF on file %2 %1"
Constant	EMSG_IO_IOEOF
SAP Sybase Error Number	20373
SQL State	QBB35
SQL Code	-1006135L

Error 1006135	"Attempt to use object after EOF on file %2 %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	file we have read past EOF on
Probable Cause	No additional information available.

Error 1006136	"The file is/will be too big "
Constant	EMSG_IO_FILETOOBIG
SAP Sybase Error Number	20374
SQL State	QBB36
SQL Code	-1006136L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006137	"Operation failed on file, user not owner. File: %2 %1"
Constant	EMSG_IO_NOTOWNER
SAP Sybase Error Number	20375
SQL State	QBB37
SQL Code	-1006137L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	file that cannot be accessed
Probable Cause	No additional information available.

Messages 1006138 through 1006157

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1006138	"No such process %2 %1"
Constant	EMSG_IO_NOSUCHPROCESS
SAP Sybase Error Number	20376
SQL State	QBB38
SQL Code	-1006138L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006139	"Operation on file interrupted by user. File: %2 %1"
Constant	EMSG_IO_INTERRUPT
SAP Sybase Error Number	20377
SQL State	QBB39
SQL Code	-1006139L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	file being used when the interrupt occurred
Probable Cause	No additional information available.

Error 1006140	"I/O Error on file %2 %1"
Constant	EMSG_IO_IOERROR

Error 1006140	"I/O Error on file %2 %1"
SAP Sybase Error Number	20378
SQL State	QBB40
SQL Code	-1006140L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	file the I/O operation failed on
Probable Cause	No additional information available.

Error 1006141	"No such device or address %2 %1"
Constant	EMSG_IO_NOSUCHDEVADDR
SAP Sybase Error Number	20379
SQL State	QBB41
SQL Code	-1006141L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006142	"Argument list too big %2 %1"
Constant	EMSG_IO_ARGTOBIG
SAP Sybase Error Number	20380
SQL State	QBB42
SQL Code	-1006142L
ODBC 2 State	ERROR

Error 1006142	"Argument list too big %2 %1"
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	file the I/O operation failed on
Probable Cause	No additional information available.

Error 1006143	"Exec format error %2 %1"
Constant	EMSG_IO_EXECFORMAT
SAP Sybase Error Number	20381
SQL State	QBB43
SQL Code	-1006143L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006144	"Bad file handle passed to OS on file %2 %1"
Constant	EMSG_IO_BADFILEHANDLE
SAP Sybase Error Number	20382
SQL State	QBB44
SQL Code	-1006144L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2

Error 1006144	"Bad file handle passed to OS on file %2 %1"
Probable Cause	No additional information available.

Error 1006145	"No children %2 %1"
Constant	EMSG_IO_NOCHILDREN
SAP Sybase Error Number	20383
SQL State	QBB45
SQL Code	-1006145L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006146	"No more processes %2 %1"
Constant	EMSG_IO_NOMOREPROCESSES
SAP Sybase Error Number	20384
SQL State	QBB46
SQL Code	-1006146L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006147	"No more memory %2 %1 "
Constant	EMSG_IO_NOMOREMEMORY

Error 1006147	"No more memory %2 %1 "
SAP Sybase Error Number	20385
SQL State	QBB47
SQL Code	-1006147L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006148	"Operation failed on file due to file permissions. File: %2 %1"
Constant	EMSG_IO_PERMISSION
SAP Sybase Error Number	20386
SQL State	QBB48
SQL Code	-1006148L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	file that the operation failed on.
Probable Cause	No additional information available.

Error 1006149	"Bad address %2 %1"
Constant	EMSG_IO_BADADDRESS
SAP Sybase Error Number	20387
SQL State	QBB49
SQL Code	-1006149L

Error 1006149	"Bad address %2 %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006150	"File already exists. File: %2 %1"
Constant	EMSG_IO_FILEEXISTS
SAP Sybase Error Number	20388
SQL State	QBB50
SQL Code	-1006150L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006151	"%2 is not a directory %1"
Constant	EMSG_IO_NOTDIR
SAP Sybase Error Number	20389
SQL State	QBB51
SQL Code	-1006151L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception

Error 1006151	"%2 is not a directory %1"
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006152	"'%2'is a directory %1"
Constant	EMSG_IO_ISDIR
SAP Sybase Error Number	20390
SQL State	QBB52
SQL Code	-1006152L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006153	"Invalid stream I/O argument, maybe %2 is a directory, or it contains more than 2,147,483,647 bytes, %1"
Constant	EMSG_IO_INVARG
SAP Sybase Error Number	20391
SQL State	QBB53
SQL Code	-1006153L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006154	"Perhaps the device (%2) is not in variable block mode? %1"
Constant	EMSG_IO_NOTVARBLOCKMODE
SAP Sybase Error Number	20392
SQL State	QBB54
SQL Code	-1006154L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006155	"File table is full %2 %1"
Constant	EMSG_IO_FILETABLEFULL
SAP Sybase Error Number	20393
SQL State	QBB55
SQL Code	-1006155L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006156	"Too many files %2 %1"
Constant	EMSG_IO_TOMANYFILES
SAP Sybase Error Number	20394
SQL State	QBB56

Error 1006156	"Too many files %2 %1"
SQL Code	-1006156L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006157	"File is too large. File: %2 %1"
Constant	EMSG_IO_FILETOLARGE
SAP Sybase Error Number	20395
SQL State	QBB57
SQL Code	-1006157L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Messages 1006158 through 1006177

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1006158	"Disk is full on I/O to file %2 %1"
Constant	EMSG_IO_DISKFULL
SAP Sybase Error Number	20396
SQL State	QBB58
SQL Code	-1006158L

Error 1006158	"Disk is full on I/O to file %2 %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	file that grew to fill the disk.
Probable Cause	No additional information available.

Error 1006159	"Read only filesystem on file %2 %1"
Constant	EMSG_IO_READONLYFS
SAP Sybase Error Number	20397
SQL State	QBB59
SQL Code	-1006159L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	file invalid operation was tried on
Probable Cause	No additional information available.

Error 1006160	"Bad tape blocksize %2 %1"
Constant	EMSG_IO_BADBLOCKSIZE
SAP Sybase Error Number	20398
SQL State	QBB60
SQL Code	-1006160L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception

Error 1006160	"Bad tape blocksize %2 %1"
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006161	"Operation Canceled %2 %1"
Constant	EMSG_IO_OPCANCELED
SAP Sybase Error Number	20399
SQL State	QBB61
SQL Code	-1006161L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	file that had an I/O operation cancelled
Probable Cause	No additional information available.

Error 1006162	"Tape IO Error %2 %1 "
Constant	EMSG_IO_TAPEIOERROR
SAP Sybase Error Number	20400
SQL State	QBB62
SQL Code	-1006162L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006163	"Operating system error : %2 %1"
Constant	EMSG_LS_OSERROR
SAP Sybase Error Number	20401
SQL State	QBB63
SQL Code	-1006163L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006164	"The text in the DateString for Day is not a valid number. Day: "
Constant	EMSG_DATE_FORMATSTRINGDAY
SAP Sybase Error Number	20402
SQL State	QBB64
SQL Code	-1006164L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006165	"The text in the DateString for Month is not a valid number. Month: "
Constant	EMSG_DATE_FORMATSTRINGMONTH
SAP Sybase Error Number	20403
SQL State	QBB65
SQL Code	-1006165L

Error 1006165	"The text in the DateString for Month is not a valid number. Month: "
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	No additional information available.

Error 1006166	"The text in the DateString for Year is not a valid number. Year: "
Constant	EMSG_DATE_FORMATSTRINGYEAR
SAP Sybase Error Number	20404
SQL State	QBB66
SQL Code	-1006166L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	No additional information available.

Error 1006167	"DateTime is invalid (%2) %1"
Constant	EMSG_DATE_INVALIDDATETIME
SAP Sybase Error Number	20405
SQL State	QBB67
SQL Code	-1006167L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006168	"Date is invalid (%2) %1"
Constant	EMSG_DATE_INVALIDDATE
SAP Sybase Error Number	20406
SQL State	QBB68
SQL Code	-1006168L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006169	"Time is invalid (%2) %1"
Constant	EMSG_DATE_INVALIDTIME
SAP Sybase Error Number	20407
SQL State	QBB69
SQL Code	-1006169L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006170	"Date is invalid because of the year (%2) %1"
Constant	EMSG_DATE_INVALIDYEAR
SAP Sybase Error Number	20408
SQL State	QBB70
SQL Code	-1006170L

Error 1006170	"Date is invalid because of the year (%2) %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006171	"Date is invalid because of the day of the year (%2) %1"
Constant	EMSG_DATE_INVALIDJDAY
SAP Sybase Error Number	20409
SQL State	QBB71
SQL Code	-1006171L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006172	"Date is invalid because of the Month (%2) %1"
Constant	EMSG_DATE_INVALIDMONTH
SAP Sybase Error Number	20410
SQL State	QBB72
SQL Code	-1006172L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception

Error 1006172	"Date is invalid because of the Month (%2) %1"
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006173	"Date is invalid because of the day the Month (%2) %1"
Constant	EMSG_DATE_INVALIDMDAY
SAP Sybase Error Number	20411
SQL State	QBB73
SQL Code	-1006173L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006174	"Date is invalid (Year:%2 Month:%3 Day:%4) %1"
Constant	EMSG_DATE_INVALIDYMD
SAP Sybase Error Number	20412
SQL State	QBB74
SQL Code	-1006174L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Parameter 3	explanation for arg %3 delete if no %3
Parameter 4	explanation for arg %4 delete if no %4
Probable Cause	No additional information available.

Error 1006175	"Time is invalid (Hour:%2 Minute:%3 Second:%4 MicroSecond:%5) %1"
Constant	EMSG_DATE_INVALIDHMS
SAP Sybase Error Number	20413
SQL State	QBB75
SQL Code	-1006175L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Parameter 3	explanation for arg %3 delete if no %3
Parameter 4	explanation for arg %4 delete if no %4
Parameter 5	explanation for arg %5 delete if no %5
Probable Cause	No additional information available.

Error 1006176	No message
Constant	EMSG_DATE_INVALIDDAYS_EMPTY_SLOT
SAP Sybase Error Number	20414
SQL State	QBB76
SQL Code	-1006176L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006177	"Time is invalid because of the MicroSeconds (%2) %1"
Constant	EMSG_DATE_INVALIDUSECONDS
SAP Sybase Error Number	20415

Error 1006177	"Time is invalid because of the MicroSeconds (%2) %1"
SQL State	QBB77
SQL Code	-1006177L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Messages 1006178 through 1006197

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1006178	"DateTime is invalid because of the MicroSeconds from 1/1/0000 (%2) %1"
Constant	EMSG_DATE_INVALIDUSECONDSBOE
SAP Sybase Error Number	20416
SQL State	QBB78
SQL Code	-1006178L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006179	"Cannot allocate space for CS context %1 "
Constant	EMSG_DATE_INVALIDDCSCONTEXTALLOC
SAP Sybase Error Number	20417

Error 1006179	"Cannot allocate space for CS context %1 "
SQL State	QBB79
SQL Code	-1006179L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006180	"Cannot allocate space for CS locale %1 "
Constant	EMSG_DATE_INVALIDCSLOCALEALLOC
SAP Sybase Error Number	20418
SQL State	QBB80
SQL Code	-1006180L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006181	"Cannot set CS locale %1 "
Constant	EMSG_DATE_INVALIDCSLOCALE
SAP Sybase Error Number	20419
SQL State	QBB81
SQL Code	-1006181L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception

Error 1006181	"Cannot set CS locale %1 "
Probable Cause	No additional information available.

Error 1006182	"Cannot configure CS context %1 "
Constant	EMSG_DATE_INVALIDCSCONFIG
SAP Sybase Error Number	20420
SQL State	QBB82
SQL Code	-1006182L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006183	"Raw device is not open %1"
Constant	EMSG_RAWIO_NO_FD
SAP Sybase Error Number	20421
SQL State	QBB83
SQL Code	-1006183L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006184	"Unable to query raw device %1"
Constant	EMSG_RAWIO_BAD_IOCTL
SAP Sybase Error Number	20422
SQL State	QBB84

Error 1006184	"Unable to query raw device %1"
SQL Code	-1006184L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006185	"Unsupported raw device type %1"
Constant	EMSG_RAWIO_UNSUPP
SAP Sybase Error Number	20423
SQL State	QBB85
SQL Code	-1006185L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006186	"Program error on raw device %1"
Constant	EMSG_RAWIO_PROGERROR
SAP Sybase Error Number	20424
SQL State	QBB86
SQL Code	-1006186L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006187	"OS error was found on a lock (mutex,condvar,etc) Call: error = %2 %1"
Constant	EMSG_LOCK_OSERROR
SAP Sybase Error Number	20425
SQL State	QBB87
SQL Code	-1006187L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006188	"USEAGE error was found on a lock (mutex,condvar,etc) Call %1"
Constant	EMSG_LOCK_USEERROR
SAP Sybase Error Number	20426
SQL State	QBB88
SQL Code	-1006188L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006189	"The condition variable was killed %1"
Constant	EMSG_LOCK_KILLED
SAP Sybase Error Number	20427
SQL State	QBB89

Error 1006189	"The condition variable was killed %1"
SQL Code	-1006189L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006190	"The semaphore variable was canceled %1"
Constant	EMSG_SEMA_KILLED
SAP Sybase Error Number	20428
SQL State	QBB90
SQL Code	-1006190L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006191	"Unknown error was found on a lock (mutex,condvar,etc) Call %1"
Constant	EMSG_LOCK_DEFAULT
SAP Sybase Error Number	20429
SQL State	QBB91
SQL Code	-1006191L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception

Error 1006191	"Unknown error was found on a lock (mutex,condvar,etc) Call %1"
Probable Cause	No additional information available.

Error 1006192	"OS error was found on Thread Call: error = %2, %1"
Constant	EMSG_THREAD_OSERROR
SAP Sybase Error Number	20430
SQL State	QBB92
SQL Code	-1006192L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006193	"Unknown error was found on Thread Call %1"
Constant	EMSG_THREAD_DEFAULT
SAP Sybase Error Number	20431
SQL State	QBB93
SQL Code	-1006193L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006194	"Could not get a thread %1"
Constant	EMSG_THREAD_COULDNT_GET_THREAD
SAP Sybase Error Number	20432

Error 1006194	"Could not get a thread %1"
SQL State	QBB94
SQL Code	-1006194L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006195	"OS error was found on hos_threadman Call: error = %2 %1"
Constant	EMSG_THREADMAN_OSERROR
SAP Sybase Error Number	20433
SQL State	QBB95
SQL Code	-1006195L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006196	"hos_threadman: the environment variable HOS_NUM_OF_CPUS does not exist %1"
Constant	EMSG_THREADMAN_NOENVVAR
SAP Sybase Error Number	20434
SQL State	QBB96
SQL Code	-1006196L
ODBC 2 State	ERROR

Error 1006196	"hos_threadman: the environment variable HOS_NUM_OF_CPUS does not exist %1"
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006197	"Unknown error was found during hos_threadman Constructor %1"
Constant	EMSG_THREADMAN_CSTRFAILED
SAP Sybase Error Number	20435
SQL State	QBB97
SQL Code	-1006197L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Messages 1006198 through 1006217

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1006198	"Unknown error was found during hos_threadman Destructor %1"
Constant	EMSG_THREADMAN_DSTRFAILED
SAP Sybase Error Number	20436
SQL State	QBB98
SQL Code	-1006198L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1006198	"Unknown error was found during hos_threadman Destructor %1"
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006199	"Unknown error was found on hos_threadman Call %1"
Constant	EMSG_THREADMAN_DEFAULT
SAP Sybase Error Number	20437
SQL State	QBB99
SQL Code	-1006199L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006200	" and last packet was "
Constant	EMSG_IPCC_BAD_SEQ_PACKET2
SAP Sybase Error Number	20438
SQL State	QBC00
SQL Code	-1006200L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	No additional information available.

Error 1006201	" and last packet was "
Constant	EMSG_IPCS_BAD_SEQ_PACKET2
SAP Sybase Error Number	20439

Error 1006201	" and last packet was "
SQL State	QBC01
SQL Code	-1006201L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006202	"Syntax error in conversion of string to DATETIME value."
Constant	EMSG_INVALID_DATETIMESYNTAX
SAP Sybase Error Number	20440
SQL State	QBC02
SQL Code	-1006202L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006203	"Syntax error in conversion of string to DATE value."
Constant	EMSG_INVALID_DATESYNTAX
SAP Sybase Error Number	20441
SQL State	QBC03
SQL Code	-1006203L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006204	"Syntax error in conversion of string to TIME value."
Constant	EMSG_INVALID_TIMESYNTAX
SAP Sybase Error Number	20442
SQL State	QBC04
SQL Code	-1006204L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006205	"A lock was acquired on an object which has inconsistent state"
Constant	EMSG_CATCHLOCK_STATE_INCONSISTENT
SAP Sybase Error Number	20443
SQL State	QBC05
SQL Code	-1006205L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006206	No message
Constant	EMSG_ASSERT_DEFAULT_EMPTY_SLOT
SAP Sybase Error Number	20444
SQL State	QBC06
SQL Code	-1006206L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2

Error 1006206	No message
Probable Cause	No additional information available.

Error 1006207	"ACCESS exception: OS error %1"
Constant	EMSG_ACCESS_OSERROR
SAP Sybase Error Number	20445
SQL State	QBC07
SQL Code	-1006207L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006208	"CONSTRAINT exception: OS error %2 %1"
Constant	EMSG_CONSTRAINT_OSERROR
SAP Sybase Error Number	20446
SQL State	QBC08
SQL Code	-1006208L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	error number
Probable Cause	No additional information available.

Error 1006209	"The exception handler's memory manager could not get memory during initialization"
Constant	EMSG_EXMEM_COULDNOTINIT
SAP Sybase Error Number	20447

Error 1006209	"The exception handler's memory manager could not get memory during initialization"
SQL State	QBC09
SQL Code	-1006209L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006210	"The exception handler's memory manager has run out of memory"
Constant	EMSG_EXMEM_OUTOFMEM
SAP Sybase Error Number	20448
SQL State	QBC10
SQL Code	-1006210L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006211	"Not all memory was returned to the exception handler's memory manager"
Constant	EMSG_EXMEM_MEMLEAK
SAP Sybase Error Number	20449
SQL State	QBC11
SQL Code	-1006211L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006212	"The exception handler's memory manager has been corrupted"
Constant	EMSG_EXMEM_MEMCORRUPT
SAP Sybase Error Number	20450
SQL State	QBC12
SQL Code	-1006212L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006213	"Unable to use shared memory because "
Constant	EMSG_SHRMEM_BECAUSE
SAP Sybase Error Number	20451
SQL State	QBC13
SQL Code	-1006213L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006214	"the semaphore for shared memory did not exist"
Constant	EMSG_SHRMEM_NO_SUCH_SEMAPHORE
SAP Sybase Error Number	20452
SQL State	QBC14
SQL Code	-1006214L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2

Error 1006214	"the semaphore for shared memory did not exist"
Probable Cause	No additional information available.

Error 1006215	"the semaphore for shared memory was deleted"
Constant	EMSG_SHRMEM_SEMAPHORE_DELETED
SAP Sybase Error Number	20453
SQL State	QBC15
SQL Code	-1006215L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006216	"of insufficient system semaphore resources"
Constant	EMSG_SHRMEM_INSUF_SEM_RESOURCES
SAP Sybase Error Number	20454
SQL State	QBC16
SQL Code	-1006216L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006217	"the system limit on the number of processes allowed to request semaphore undos would be exceeded"
Constant	EMSG_SHRMEM_SEM_UNDOS_ENOSPC
SAP Sybase Error Number	20455
SQL State	QBC17
SQL Code	-1006217L
ODBC 2 State	ERROR

Error 1006217	"the system limit on the number of processes allowed to request semaphore undos would be exceeded"
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	No additional information available.

Messages 1006218 through 1006238

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1006218	"the system limit on the number of semaphore undo requests allowed per process (semume) would be exceeded"
Constant	EMSG_SHRMEM_SEM_UNDOS_EINVAL
SAP Sybase Error Number	20456
SQL State	QBC18
SQL Code	-1006218L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	No additional information available.

Error 1006219	"the creation of a new semaphore would exceed the system limit on either the maximum number of semaphores allowed or the maximum number of semaphore identifiers allowed"
Constant	EMSG_SHRMEM_SEMGET_CREATE_ENOSPC
SAP Sybase Error Number	20457
SQL State	QBC19
SQL Code	-1006219L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1006219	"the creation of a new semaphore would exceed the system limit on either the maximum number of semaphores allowed or the maximum number of semaphore identifiers allowed"
Severity Code	<i>14 on page 2</i>
Probable Cause	No additional information available.

Error 1006220	"of insufficient system shared memory resources"
Constant	EMSG_SHRMEM_INSUF_SHM_RESOURCES
SAP Sybase Error Number	20458
SQL State	QBC20
SQL Code	-1006220L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	No additional information available.

Error 1006221	"the creation of a new shared memory segment would exceed the system limit on the maximum number of shared segments allowed"
Constant	EMSG_SHRMEM_SHMGET_CREATE_ENOSPC
SAP Sybase Error Number	20459
SQL State	QBC21
SQL Code	-1006221L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	No additional information available.

Error 1006222	"the requested shared memory segment size is less than the system-imposed minimum (shmmin) or greater than the system-imposed maximum (shmmax)"
Constant	EMSG_SHRMEM_SHMGET_CREATE_EINVAL
SAP Sybase Error Number	20460
SQL State	QBC22
SQL Code	-1006222L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006223	"of insufficient available physical memory to create a new shared memory segment"
Constant	EMSG_SHRMEM_SHMGET_CREATE_ENOMEM
SAP Sybase Error Number	20461
SQL State	QBC23
SQL Code	-1006223L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006224	"the system limit of shared memory segments attached per process (shmseg) would be exceeded"
Constant	EMSG_SHRMEM_SHMAT_EMFILE
SAP Sybase Error Number	20462
SQL State	QBC24
SQL Code	-1006224L
ODBC 2 State	ERROR

Error 1006224	"the system limit of shared memory segments attached per process (shmseg) would be exceeded"
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Probable Cause	No additional information available.

Error 1006225	"the available data space is not large enough to accommodate the shared memory segment"
Constant	EMSG_SHRMEM_SHMAT_ENOMEM
SAP Sybase Error Number	20463
SQL State	QBC25
SQL Code	-1006225L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Probable Cause	No additional information available.

Error 1006226	"you have no permission to access the shared memory semaphore"
Constant	EMSG_SHRMEM_SEM_NO_ACCESS
SAP Sybase Error Number	20464
SQL State	QBC26
SQL Code	-1006226L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Probable Cause	No additional information available.

Error 1006227	"you have no permission to access the shared memory segment"
Constant	EMSG_SHRMEM_SHM_NO_ACCESS

Error 1006227	"you have no permission to access the shared memory segment"
SAP Sybase Error Number	20465
SQL State	QBC27
SQL Code	-1006227L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006228	"the attach failed because the shared memory segment was created by a process with significantly different settings (e.g. max threads)"
Constant	EMSG_SHRMEM_SHM_ATTACH_FAILED
SAP Sybase Error Number	20466
SQL State	QBC28
SQL Code	-1006228L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006229	"the attach failed because the shared memory segment was created by a process running a different version of sybase_iq"
Constant	EMSG_SHRMEM_SHM_IMAGE_MISMATCH
SAP Sybase Error Number	20467
SQL State	QBC29
SQL Code	-1006229L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1006229	"the attach failed because the shared memory segment was created by a process running a different version of sybase_iq"
Severity Code	<i>14 on page 2</i>
Probable Cause	No additional information available.

Error 1006230	"lock request was interrupted"
Constant	EMSG_SHRMEM_SHM_INTERRUPTED
SAP Sybase Error Number	20468
SQL State	QBC30
SQL Code	-1006230L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	No additional information available.

Error 1006231	"ACCESS exception: OS error %2: %3 %1"
Constant	EMSG_ACCESS_OSERROR2
SAP Sybase Error Number	20469
SQL State	QBC31
SQL Code	-1006231L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	error number
Parameter 3	working directory
Probable Cause	No additional information available.

Error 1006232	"Unknown ParamSet error %1"
Constant	EMSG_PARAM_UNKNOWN
SAP Sybase Error Number	20470
SQL State	QBC32
SQL Code	-1006232L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006233	"CONSTRAINT exception: OS error %2: pathname len is %3, your buffer size is %4. Pathname is %5 %1"
Constant	EMSG_CONSTRAINT_OSERROR2
SAP Sybase Error Number	20471
SQL State	QBC33
SQL Code	-1006233L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	error number
Parameter 3	pathname length
Parameter 4	buffer size
Parameter 5	pathname
Probable Cause	No additional information available.

Error 1006234	"The IQ SET command has no option named '%2' %1"
Constant	EMSG_PARAM_UNKNOWNPARAM

Error 1006234	"The IQ SET command has no option named '%2' %1"
SAP Sybase Error Number	20472
SQL State	QBC34
SQL Code	-1006234L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006235	"The IQ SET SERVERDEFAULT command requires the SA_ROLE %1"
Constant	EMSG_PARAM_SERVER_ONLY_SA
SAP Sybase Error Number	20473
SQL State	QBC35
SQL Code	-1006235L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1006237	"The IQ SET option, '%2', can not be set server-wide %1"
Constant	EMSG_PARAM_NOT_SET_SERV2
SAP Sybase Error Number	20475
SQL State	QBC37
SQL Code	-1006237L
ODBC 2 State	ERROR

Error 1006237	"The IQ SET option, '%2', can not be set server-wide %1"
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006238	"The IQ SET option, '%2', can only be set server-wide and not for a session %1"
Constant	EMSG_PARAM_NOT_SESSION2
SAP Sybase Error Number	20476
SQL State	QBC38
SQL Code	-1006238L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

1006239 - 1009145

Messages 1006239 through 1006258

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1006239	"The IQ SET option, '%2', can only be changed by users with SA_ROLE or DBO_ROLE %1"
Constant	EMSG_PARAM_NEEDS_DBO_OR_SA2
SAP Sybase Error Number	20477

Error 1006239	"The IQ SET option, '%2', can only be changed by users with SA_ROLE or DBO_ROLE %1"
SQL State	QBC39
SQL Code	-1006239L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006240	"The value, %2, is not valid for the SQL Anywhere option, '%3' %1"
Constant	EMSG_PARAM_BADPARAMVALUESA
SAP Sybase Error Number	20478
SQL State	QBC40
SQL Code	-1006240L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Parameter 3	explanation for arg %3 delete if no %3
Probable Cause	No additional information available.

Error 1006241	"The value, %2, is not valid for the integer option, '%3' %1"
Constant	EMSG_PARAM_BADPARAMVALUEINT
SAP Sybase Error Number	20479
SQL State	QBC41

Error 1006241	"The value, %2, is not valid for the integer option, '%3' %1"
SQL Code	-1006241L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Parameter 3	explanation for arg %3 delete if no %3
Probable Cause	No additional information available.

Error 1006242	"The value, %2, is not valid for the unsigned integer option, '%3' %1"
Constant	EMSG_PARAM_BADPARAMVALUEUINT
SAP Sybase Error Number	20480
SQL State	QBC42
SQL Code	-1006242L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Parameter 3	explanation for arg %3 delete if no %3
Probable Cause	No additional information available.

Error 1006243	"The value, %2, is not valid for the boolean option, '%3' %1"
Constant	EMSG_PARAM_BADPARAMVALUEBOOL
SAP Sybase Error Number	20481
SQL State	QBC43
SQL Code	-1006243L

Error 1006243	"The value, %2, is not valid for the boolean option, '%3' %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Parameter 3	explanation for arg %3 delete if no %3
Probable Cause	No additional information available.

Error 1006244	"The value, %2, is not valid for the unsigned 64bit integer option, '%3' %1"
Constant	EMSG_PARAM_BADPARAMVALUEUINT64
SAP Sybase Error Number	20482
SQL State	QBC44
SQL Code	-1006244L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Parameter 3	explanation for arg %3 delete if no %3
Probable Cause	No additional information available.

Error 1006245	"The value, %2, is not valid for the string option, '%3' %1"
Constant	EMSG_PARAM_BADPARAMVALUESTRING
SAP Sybase Error Number	20483
SQL State	QBC45
SQL Code	-1006245L
ODBC 2 State	ERROR

Error 1006245	"The value, %2, is not valid for the string option, '%3' %1"
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Parameter 3	explanation for arg %3 delete if no %3
Probable Cause	No additional information available.

Error 1006246	No message
Constant	EMSG_PARAM_UNKNOWNDATATYPE_EMPTY_SLOT
SAP Sybase Error Number	20484
SQL State	QBC46
SQL Code	-1006246L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006247	"shared segment: os error"
Constant	EMSG_SHAREDSEG_OSERR
SAP Sybase Error Number	20485
SQL State	QBC47
SQL Code	-1006247L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006248	"shared segment: virtual addr does not match"
Constant	EMSG_SHAREDSEG_VADDRERR
SAP Sybase Error Number	20486
SQL State	QBC48
SQL Code	-1006248L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006249	"Shared segment attach failed because the shared memory segment was created by a process running a different version of sybase_iq."
Constant	EMSG_SHAREDSEG_IMG_MISMATCH
SAP Sybase Error Number	20487
SQL State	QBC49
SQL Code	-1006249L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006250	"Requested shared memory size, SHMEMMB & TEMP SHMEMMB, too big for available shared memory segments, SYSTEMSHMMAX & SYSTEMSHMSEG"
Constant	EMSG_SHAREDSEG_TOO_BIG
SAP Sybase Error Number	20488
SQL State	QBC50
SQL Code	-1006250L
ODBC 2 State	ERROR

Error 1006250	"Requested shared memory size, SHMEMMB & TEMP SHMEMMB, too big for available shared memory segments, SYSTEMSHMMAX & SYSTEMSHMSEG"
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006251	"Requested shared memory size, SHMEMMB & TEMP SHMEMMB, greater than system limit (max 4GB)"
Constant	EMSG_SHAREDSEG_SHMEMMB_TOO_BIG
SAP Sybase Error Number	20489
SQL State	QBC51
SQL Code	-1006251L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006252	"Requested shared memory size, SHMEMMB or TEMP SHMEMMB, too small (min 1MB)"
Constant	EMSG_SHAREDSEG_SHMEMMB_TOO_SMALL
SAP Sybase Error Number	20490
SQL State	QBC52
SQL Code	-1006252L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006253	"Requested shared memory size, SYSTEMSHMMAX, greater than system limit"
Constant	EMSG_SHAREDSEG_SYSTEMSHMMAX_TOO_BIG
SAP Sybase Error Number	20491
SQL State	QBC53
SQL Code	-1006253L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006254	"Data overflow %2 %1"
Constant	EMSG_ERROR_OVERFLOW
SAP Sybase Error Number	20492
SQL State	QBC54
SQL Code	-1006254L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006255	"Maximum exceeded %2 %1"
Constant	EMSG_ERROR_EXCEEDMAX
SAP Sybase Error Number	20493
SQL State	QBC55
SQL Code	-1006255L
ODBC 2 State	ERROR

Error 1006255	"Maximum exceeded %2 %1"
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006256	"Invalid arithmetic construction %2 %1"
Constant	EMSG_NUMERIC_CONSTRUCTOR
SAP Sybase Error Number	20494
SQL State	QBC56
SQL Code	-1006256L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006257	"Invalid arithmetic conversion %2 %1"
Constant	EMSG_NUMERIC_CONVERSION
SAP Sybase Error Number	20495
SQL State	QBC57
SQL Code	-1006257L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2

Error 1006257	"Invalid arithmetic conversion %2 %1"
Probable Cause	No additional information available.

Error 1006258	"Invalid arithmetic operation %2 %1"
Constant	EMSG_NUMERIC_OPERATOR
SAP Sybase Error Number	20496
SQL State	QBC58
SQL Code	-1006258L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Messages 1006259 through 1008005

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1006259	"Invalid arithmetic function arguments %2 %1"
Constant	EMSG_NUMERIC_FUNCTION
SAP Sybase Error Number	20497
SQL State	QBC59
SQL Code	-1006259L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	No additional information available.

Error 1006260	" Could not open file: "
Constant	EMSG_FILEINFO_OPENERR
SAP Sybase Error Number	20498
SQL State	QBC60
SQL Code	-1006260L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006261	"\n\n*** File: %s\n\n"
Constant	EMSG_FILENAME
SAP Sybase Error Number	20499
SQL State	QBC61
SQL Code	-1006261L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006262	" This new operator should never be called "
Constant	EMSG_SHOULDNOCALLNEW
SAP Sybase Error Number	20500
SQL State	QBC62
SQL Code	-1006262L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006263	" This delete operator should never be called "
Constant	EMSG_SHOULDNOCALLDELETE
SAP Sybase Error Number	20501
SQL State	QBC63
SQL Code	-1006263L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1006264	"Invalid Blocksize %2 less than the Device Sectorsize %3 %4 %1"
Constant	EMSG_BIO_INVBLKSZFORDEV
SAP Sybase Error Number	21072
SQL State	QBC64
SQL Code	-1006264L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	%2 Invalid block size
Parameter 3	%3 Device Sector Size
Parameter 4	%4 Name of Raw device
Probable Cause	No additional information available.

Error 1006265	"Invalid Filename: %2. %1"
Constant	EMSG_IO_INVALID_FILENAME
SAP Sybase Error Number	21093
SQL State	QBC65

Error 1006265	"Invalid Filename: %2. %1"
SQL Code	-1006265L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	%2 Invalid filename
Probable Cause	A bad filename (perhaps zero-length) was specified.

Error 1006266	"Found bad sector on raw device: %1"
Constant	EMSG_RAWIO_BAD_SECTOR
SAP Sybase Error Number	21105
SQL State	QBC66
SQL Code	-1006266L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	A bad sector was detected on the given raw device.

Error 1006267	"%2 blocks is greater than the partition size of %3 blocks %1"
Constant	EMSG_BIO_RESIZETOOBIG
SAP Sybase Error Number	21119
SQL State	QBC67
SQL Code	-1006267L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2

Error 1006267	"%2 blocks is greater than the partition size of %3 blocks %1"
Parameter 1	location of the exception
Parameter 2	user specified size
Parameter 3	partition size
Probable Cause	No additional information available.

Error 1006268	"The current operation has been cancelled: Max_Temp_Space_Per_Connection exceeded"
Constant	EMSG_ATTEN_MAXTEMPSPACE
SAP Sybase Error Number	21151
SQL State	QBC68
SQL Code	-1006268L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	User has exhausted maximum temp dbspace limit for this connection

Error 1006269	"No SYSAM License Available"
Constant	EMSG_NO_SYSAMLICENSE
SAP Sybase Error Number	21161
SQL State	QBC69
SQL Code	-1006269L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	SYSAM license for the product is either not available or not configured.

Error 1006270	"SYSAM Failure while doing: %1"
Constant	EMSG_SYLAPI_FAILURE
SAP Sybase Error Number	21162
SQL State	QBC70
SQL Code	-1006270L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Parameter 1 description
Probable Cause	SYSAM internal failure.

Error 1006271	"IQ_CORE License has expired"
Constant	EMSG_IQCORE_EXPIRED
SAP Sybase Error Number	21163
SQL State	QBC71
SQL Code	-1006271L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	SYSAM IQ_CORE license has expired leading to server shutdown

Error 1006272	"IQ Main store cannot be larger than licensed limit"
Constant	EMSG_IQSTORE_LIMIT
SAP Sybase Error Number	21172
SQL State	QBC72
SQL Code	-1006272L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2

Error 1006272	"IQ Main store cannot be larger than licensed limit"
Probable Cause	SYSAM IQ Main store is larger than the limit specified in product license leading to server shutdown

Error 1006273	"License limit for dbspaces reached. Cannot create new dbspace"
Constant	EMSG_VLDBMGMT_LIMIT
SAP Sybase Error Number	21203
SQL State	QBC73
SQL Code	-1006273L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	SYSAM Number of IQ Main DBSpaces higher than the licensed limit

Error 1006274	"Transaction cannot continue due to unrecoverable INC failure. Roll back current transaction. %1"
Constant	EMSG_INC_FAILURE_ROLLBACKTXN
SAP Sybase Error Number	22036
SQL State	QBC74
SQL Code	-1006274L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	The underlying INC for current transaction has failed to connect to coordinator in Mpx_Liveness_Timeout seconds or coordinator side state of transaction is unknown.

Error 1008000	"Users are not allowed to create an FP index. FP indexes are created automatically when the table is created."
Constant	EMSG_IQ_NOCREATEFP

Error 1008000	"Users are not allowed to create an FP index. FP indexes are created automatically when the table is created."
SAP Sybase Error Number	20596
SQL State	QNA00
SQL Code	-1008000L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	Users are not able to create Fast Projection indexes on columns. They are created automatically when the table is created.

Error 1008001	"The user cannot create indexes on a join virtual table."
Constant	EMSG_IQ_NOCREATEINDEXJVT
SAP Sybase Error Number	20621
SQL State	QNA01
SQL Code	-1008001L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	Users cannot create indexes on a join virtual table. They are automatically created.

Error 1008004	"Cannot DROP index '%1'."
Constant	EMSG_IQ_NODROPIQINDEX
SAP Sybase Error Number	20673
SQL State	QNA04
SQL Code	-1008004L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2

Error 1008004	"Cannot DROP index '%1'."
Parameter 1	Name of the index the user is attempting to drop.
Probable Cause	Users cannot drop internally created indexes except by dropping the table, join index, or alter-dropping the table or join index. Fast Projection indexes are internally created indexes.

Error 1008005	"Cannot ALTER join virtual table '%1'."
Constant	EMSG_IQ_NOALTERJVT
SAP Sybase Error Number	20675
SQL State	QNA05
SQL Code	-1008005L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	The join virtual table the user is attempting to alter.
Probable Cause	The user cannot alter a join virtual table.

Messages 1008006 through 1008027

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1008006	"You cannot specify a DEFAULT value for a column."
Constant	EMSG_IQ_INVALIDDEFAULT
SAP Sybase Error Number	20676
SQL State	QNA06
SQL Code	-1008006L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	The user cannot specify a DEFAULT value for a column during CREATE TABLE or ALTER TABLE ADD COLUMN.

Error 1008007	"The ALTER TABLE option '%2' is not supported by Sybase IQ. %1"
Constant	EMSG_IQ_NOSUPPORT
SAP Sybase Error Number	20677
SQL State	QNA07
SQL Code	-1008007L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Parameter 2	The ALTER TABLE option the user is attempting to use.
Probable Cause	The user entered an option that is not supported by Sybase IQ but is supported by ASA (like REPLICATION ON).

Error 1008008	"You cannot TRUNCATE a join virtual table."
Constant	EMSG_IQ_NOTTRUNCATEJVT
SAP Sybase Error Number	20679
SQL State	QNA08
SQL Code	-1008008L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	The user is not allowed to TRUNCATE a join virtual table.

Error 1008009	"This statement is not supported by Sybase IQ."
Constant	EMSG_IQ_STMTNOTSUPPORTED
SAP Sybase Error Number	20680
SQL State	QNA09
SQL Code	-1008009L

Error 1008009	"This statement is not supported by Sybase IQ."
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	The statement entered is supported by Adaptive Server Anywhere, but not by Sybase IQ.

Error 1008010	"A request was made to delete the primary key constraint, but the primary key cannot be found."
Constant	EMSG_IQ_NOPRIMARYKEY
SAP Sybase Error Number	20681
SQL State	QNA10
SQL Code	-1008010L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	The user wanted to delete the primary key constraint on the table but the primary key could not be found.

Error 1008012	"This unique index/constraint must be ENFORCED."
Constant	EMSG_IQ_NEEDENFORCED
SAP Sybase Error Number	20990
SQL State	QNA12
SQL Code	-1008012L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	This unique index/constraint must be ENFORCED (The UNENFORCED keyword not allowed for this index/constraint).

Error 1008013	"This multi-column unique index/constraint must be UNENFORCED."
Constant	EMSG_IQ_NEEDUNENFORCED
SAP Sybase Error Number	20991
SQL State	QNA13
SQL Code	-1008013L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	This multi-column unique index/constraint must be UNENFORCED (The UNENFORCED keyword is required for this index/constraint).

Error 1008014	"This foreign key must be UNENFORCED."
Constant	EMSG_IQ_FKEYNOSUPP
SAP Sybase Error Number	20992
SQL State	QNA14
SQL Code	-1008014L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	This foreign key must be UNENFORCED (The UNENFORCED keyword is required for this foreign key).

Error 1008015	"This check constraint must be ENFORCED."
Constant	EMSG_IQ_CHCKENFORCED
SAP Sybase Error Number	20993
SQL State	QNA15
SQL Code	-1008015L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1008015	"This check constraint must be ENFORCED."
Severity Code	<i>14 on page 2</i>
Probable Cause	The keyword UNENFORCED is not supported.

Error 1008016	"Cannot ALTER DELETE a column that has a unique or primary key constraint."
Constant	EMSG_IQ_CONSTRAINTONCOL
SAP Sybase Error Number	20994
SQL State	QNA16
SQL Code	-1008016L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	Cannot ALTER DELETE a column that has a unique or primary key constraint. This is a duplicate of an SA error code.

Error 1008017	"Cannot ALTER DELETE a column that has multi-column index."
Constant	EMSG_IQ_MULTICOLONINDEX
SAP Sybase Error Number	20995
SQL State	QNA17
SQL Code	-1008017L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	Cannot ALTER DELETE a column that has multi-column index. This is a duplicate of an SA error code.

Error 1008019	"Multiplex is currently inactive."
Constant	EMSG_IQMPX_INACTIVE
SAP Sybase Error Number	21041

Error 1008019	"Multiplex is currently inactive."
SQL State	QNA19
SQL Code	-1008019L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	The user has either requested a multiplex function or has asked for multiplex status.

Error 1008020	"Multiplex command or request is unimplemented."
Constant	EMSG_IQMPX_NOTIMPL
SAP Sybase Error Number	21042
SQL State	QNA20
SQL Code	-1008020L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	The user has requested an unimplemented multiplex feature. This would typically be a status request which doesn't exist.

Error 1008021	"The SYSIQFILE table is not configured for this server to run in a multiplex."
Constant	EMSG_IQMPX_BADCONFIG
SAP Sybase Error Number	21043
SQL State	QNA21
SQL Code	-1008021L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2

Error 1008021	"The SYSIQFILE table is not configured for this server to run in a multiplex."
Probable Cause	SYSIQFILE identifies all files which make up the given stores that the IQ server requires (main, temp, and message). For multiplex, each entry in SYSIQFILE must be associated with a particular multiplex server before that server can access the particular file. This message indicates that some these rows are missing for the active server.

Error 1008022	"Bad commit identity block. The server may be out of synchronization. %1"
Constant	EMSG_IQMPX_BADCMID
SAP Sybase Error Number	21044
SQL State	QNA22
SQL Code	-1008022L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	Multiplex servers cannot start this database. Start the coordinator in single server mode.

Error 1008023	"Cannot start multiplex secondary server while the coordinator is in single server mode"
Constant	EMSG_IQMPX_SPXDB
SAP Sybase Error Number	21045
SQL State	QNA23
SQL Code	-1008023L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	Restart the secondary server after the coordinator has restarted in normal mode.

Error 1008024	"Multiplex coordinator must start as server@host: %2, on file: %3; to start with different settings, you must use the override switch. %1"
Constant	EMSG_IQMPX_TWOWRITERS
SAP Sybase Error Number	21046
SQL State	QNA24
SQL Code	-1008024L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	server@host names for coordinator
Parameter 3	catalog db filename for coordinator
Probable Cause	Only the configured coordinator can start the database. Start with the override switch (-iqmpx_ov 1) to bypass this check.

Error 1008025	"Multiplex secondary server cannot continue while the coordinator is in single server mode. %1"
Constant	EMSG_IQMPX_SPXONLY
SAP Sybase Error Number	21047
SQL State	QNA25
SQL Code	-1008025L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	Resynchronize and restart the secondary server after the coordinator has restarted in normal mode.

Error 1008026	"Multiplex secondary server out of synchronization with the coordinator. %1"
Constant	EMSG_IQMPX_CATSYNC
SAP Sybase Error Number	21048
SQL State	QNA26
SQL Code	-1008026L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Probable Cause	The secondary server's IQ catalog cannot be brought up to date with the coordinator's IQ catalog. This server must be synchronized.

Error 1008027	"Multiplex secondary node shutting down due to a file added to the IQ_SYSTEM_MAIN dbspace.\nThis node must be synchronized and restarted. %1"
Constant	EMSG_IQMPX_SEGCOUNT
SAP Sybase Error Number	21057
SQL State	QNA28
SQL Code	-1008027L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Probable Cause	The user has added a dbspace file to IQ_SYSTEM_MAIN on the coordinator. This causes secondary nodes to shut down. All secondary nodes must be synchronized and restarted after this operation.

Messages 1008029 through 1009023

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1008029	"Cannot create foreign key to an unenforced primary key or unenforced unique constraint."
Constant	EMSG_NOFKEY_TO_UNENFORCED
SAP Sybase Error Number	21059
SQL State	QNA29
SQL Code	-1008029L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	Existing unenforced primary keys or unique constraints cannot be used to create an referential integrity relationship to a foreign table.

Error 1008030	"Only IQ index types can be created on IQ tables within a Parallel IQ block."
Constant	EMSG_SQL_PLBEGINONLYCI
SAP Sybase Error Number	21064
SQL State	QNA30
SQL Code	-1008030L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	Parallel IQ Begin/End blocks allow users to create multiple indexes simultaneously. At this time, only Create Index statements for HG, HNG, LF, LD, DATE, TIME, WD, and CMP index types on IQ tables are allowed within Parallel IQ Begin and End statements.

Error 1008031	"Cannot do Create Index commands on global or local temporary tables or catalog server tables in a Parallel IQ block."
Constant	EMSG_SQL_NOTEMPINPLB
SAP Sybase Error Number	21065
SQL State	QNA31
SQL Code	-1008031L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	Cannot do Create Index commands on global or local temporary tables in a Parallel IQ block.

Error 1008032	"Foreign keys disallowed on Identity/Autoincrement Columns when set option identity_enforce_uniqueness is on"
Constant	EMSG_FOREIGN_KEY_DISALLOWED
SAP Sybase Error Number	20026
SQL State	QNA41
SQL Code	-1008032L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	An Identity/Autoincrement Column cannot be a foreign key when the set option identity_enforce_uniqueness is on. Either turn the option off, or chose a different column for the foreign key.

Error 1008033	"Identity/Autoincrement Column %2 has Invalid datatype: scale must be 0. %1"
Constant	EMSG_NON_ZERO_SCALE
SAP Sybase Error Number	20027
SQL State	QNA42

Error 1008033	"Identity/Autoincrement Column %2 has Invalid datatype: scale must be 0. %1"
SQL Code	-1008033L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	column name
Probable Cause	Identity/Autoincrement Columns defined as datatype numeric must have scale 0

Error 1008035	"Invalid datatype for Identity/Autoincrement Column %2. %1"
Constant	EMSG_INVALID_DATATYPE
SAP Sybase Error Number	20029
SQL State	QNA44
SQL Code	-1008035L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	column name
Probable Cause	The datatype used is not supported by Identity/Autoincrement column. Valid datatypes are bigint, unsigned bigint, integer, unsigned integer, smallint, tinyint, numeric scale 0 and decimal scale 0

Error 1008036	"Table %2 already has an Identity/Autoincrement Column. %1 "
Constant	EMSG_ALREADY_HAS_IDENTITY_COLUMN
SAP Sybase Error Number	20642
SQL State	QNA45

Error 1008036	"Table %2 already has an Identity/Autoincrement Column. %1 "
SQL Code	-1008036L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Table name
Probable Cause	An Identity/Autoincrement Column cannot be added to this table because it already has one.

Error 1008037	"Cannot drop %1 %2: set option 'identity_insert' must be off. "
Constant	EMSG_IDENTITY_INSERT_IS_ON
SAP Sybase Error Number	20643
SQL State	QNA46
SQL Code	-1008037L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	string literal 'Table' or 'Column'
Parameter 2	column name
Probable Cause	option 'identity insert' must not be set to any table name to drop an Identity Column. To turn it off use 'set identity_insert ''

Error 1008038	"create schema command not allowed on an active multiplex server. "
Constant	EMSG_NOSCHEMACMD_MULTIPLEX
SAP Sybase Error Number	21123
SQL State	QNA47
SQL Code	-1008038L

Error 1008038	"create schema command not allowed on an active multiplex server. "
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	the create schema command is not allowed on an active multiplex server

Error 1008039	"Permission denied: The current multiplex server is not a writer server"
Constant	EMSG_MPX_GLOBAL_CMD_PERMISSION_DENIED
SAP Sybase Error Number	22005
SQL State	QNA48
SQL Code	-1008039L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	The global command is not permitted on current multiplex node

Error 1009000	"Bit %2 is unexpectedly on in bitmap. If the error persists, you may have a damaged index; please run sp_iqcheckdb. %1"
Constant	EMSG_BM_BITON
SAP Sybase Error Number	20021
SQL State	QSA00
SQL Code	-1009000L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>23 on page 2</i>
Parameter 1	location of the exception
Parameter 2	Bit that is on.

Error 1009000	"Bit %2 is unexpectedly on in bitmap. If the error persists, you may have a damaged index; please run sp_iqcheckdb. %1"
Probable Cause	This is either an internal calling error (some component called bitmap SET with a duplicate bit), a corrupt bitmap (and dbcc needs be run), or a bitmap operator that has gone awry and mis-computed a result.

Error 1009001	"Bit %2 is unexpectedly off in bitmap. If the error persists, you may have a damaged index; please run sp_iqcheckdb. %1"
Constant	EMSG_BM_BITOFF
SAP Sybase Error Number	20022
SQL State	QSA01
SQL Code	-1009001L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	Bit that is off.
Probable Cause	This is either an internal calling error (some component called bitmap CLEAR with a duplicate bit), a corrupt bitmap (and dbcc needs be run), or a bitmap operator that has gone awry and mis-computed a result.

Warning 1009002	" Index %2: Starting Insert Pass 2. %1"
Constant	EMSG_HG_STARTING_PASS2
SAP Sybase Error Number	20023
SQL State	00002
SQL Code	1009002L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	1 on page 2

Warning 1009002	" Index %2: Starting Insert Pass 2. %1"
Parameter 1	location of the exception
Parameter 2	Index name
Probable Cause	No additional information available.

Warning 1009003	" Index %1: Thread %2 Inserting %3 Recs, %4 Secs."
Constant	EMSG_HG_INSERTED
SAP Sybase Error Number	20024
SQL State	00003
SQL Code	1009003L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>1</i> on page 2
Parameter 1	Index name
Parameter 2	Thread index
Parameter 3	Number of records
Parameter 4	Time
Probable Cause	No additional information available.

Error 1009004	"Statistics context = %2 %3\n %1"
Constant	EMSG_STATS_CONTEXT
SAP Sybase Error Number	20025
SQL State	QSA04
SQL Code	-1009004L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	majContext

Error 1009004	"Statistics context = %2 %3\n %1"
Parameter 3	minContext
Probable Cause	No additional information available.

Error 1009012	"Cannot create %2 index on a column having a datatype %3. %1"
Constant	EMSG_ERROR_INDEX_NOTALLOWED
SAP Sybase Error Number	20033
SQL State	QSA12
SQL Code	-1009012L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	the index type (e.g., LF, HG)
Parameter 3	textual name of the column's datatype
Probable Cause	A named index type index cannot be created on named datatype

Error 1009019	"An internal server component, a bitmap, was given invalid input. %1"
Constant	EMSG_BM_BADINPUT
SAP Sybase Error Number	20040
SQL State	QSA19
SQL Code	-1009019L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception

Error 1009019	"An internal server component, a bitmap, was given invalid input. %1"
Probable Cause	Some non-bitmap component has called a bitmap with an illegal argument. This is an internal programming error and not the (direct) result of customer error.
Error 1009021	"This server must first be started in Multiplex single-node mode (-iqmpx_sn 1) %1"
Constant	EMSG_DATABASE_MPX_BADTLVFORMAT_START_SINGLE
SAP Sybase Error Number	20042
SQL State	QSA21
SQL Code	-1009021L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	The tlv log has an incorrect format
Error 1009022	"Cannot create a WD index on a column narrower than 3 bytes. %1"
Constant	EMSG_ERROR_WD_NOTALLOWED_CW2SMALL
SAP Sybase Error Number	20043
SQL State	QSA22
SQL Code	-1009022L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1009023	"Cannot create a WD index on a column wider than 32767 bytes. %1"
Constant	EMSG_ERROR_WD_NOTALLOWED_CW2LARGE
SAP Sybase Error Number	20044
SQL State	QSA23
SQL Code	-1009023L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Messages 1009024 through 1009043

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1009024	"Cannot create a WD index with a max permitted word size less than 1 byte. %1"
Constant	EMSG_ERROR_WD_NOTALLOWED_WL2SMALL
SAP Sybase Error Number	20045
SQL State	QSA24
SQL Code	-1009024L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1009025	"Cannot create a WD index with a max permitted word size greater than 255 bytes. %1"
Constant	EMSG_ERROR_WD_NOTALLOWED_WL2LARGE

Error 1009025	"Cannot create a WD index with a max permitted word size greater than 255 bytes. %1"
SAP Sybase Error Number	20046
SQL State	QSA25
SQL Code	-1009025L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1009026	"Cannot create a WD index with a separator string this long. %1"
Constant	EMSG_ERROR_WD_NOTALLOWED_SS2LARGE
SAP Sybase Error Number	20047
SQL State	QSA26
SQL Code	-1009026L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1009027	"Cannot create a WD index with a separator string containing a character fragment. %1"
Constant	EMSG_ERROR_WD_NOTALLOWED_SSFRAG
SAP Sybase Error Number	20048
SQL State	QSA27
SQL Code	-1009027L
ODBC 2 State	ERROR

Error 1009027	"Cannot create a WD index with a separator string containing a character fragment. %1"
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1009028	"Cannot create a WD index with more than 256 separators. %1"
Constant	EMSG_ERROR_WD_NOTALLOWED_NS2LARGE
SAP Sybase Error Number	20049
SQL State	QSA28
SQL Code	-1009028L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1009029	"Words exceeding the maximum permitted word length not supported. %1"
Constant	EMSG_ERROR_WD_TRUNCWORD_NOT_SUPPORTED
SAP Sybase Error Number	20050
SQL State	QSA29
SQL Code	-1009029L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1009030	"Cannot create a WD index with the database IQ pagesize less than 4KB. %1"
Constant	EMSG_ERROR_WD_NOTALLOWED_PS2SMALL
SAP Sybase Error Number	20051
SQL State	QSA30
SQL Code	-1009030L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1009031	"%2: All buffer cache pages are in use, ask your DBA to increase the size of the buffer cache. %1"
Constant	EMSG_BUFMAN_ALLSLOTSLOCKED
SAP Sybase Error Number	20052
SQL State	QSA31
SQL Code	-1009031L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) The particular buffer cache throwing the exception.
Probable Cause	No additional information available.

Error 1009032	"%2: Bio ptr must be non-null; buffer={%3} page={%4}. %1"
Constant	EMSG_BUFMAN_BADBIOP
SAP Sybase Error Number	20053
SQL State	QSA32

Error 1009032	"%2: Bio ptr must be non-null; buffer={%3} page={%4}. %1"
SQL Code	-1009032L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) The particular buffer cache throwing the exception.
Parameter 3	3) Information about the sbuf involved, if any.
Parameter 4	4) Information about the disk block header involved, if any.
Probable Cause	No additional information available.
Error 1009033	"%2: Blocksize must be a multiple of sizeof(hos_mrdtype & hos_uint) and > 0; buffer={%3} page={%4}. %1"
Constant	EMSG_BUFMAN_BADBLOCKSIZE
SAP Sybase Error Number	20054
SQL State	QSA33
SQL Code	-1009033L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) The particular buffer cache throwing the exception.
Parameter 3	3) Information about the sbuf involved, if any.
Parameter 4	4) Information about the disk block header involved, if any.
Probable Cause	No additional information available.
Error 1009034	"%2: The number of blocks must be > 0; buffer={%3} page={%4}. %1"
Constant	EMSG_BUFMAN_BADNUMOFBLKS

Error 1009034	"%2: The number of blocks must be > 0; buffer={%3} page={%4}. %1"
SAP Sybase Error Number	20055
SQL State	QSA34
SQL Code	-1009034L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) The particular buffer cache throwing the exception.
Parameter 3	3) Information about the sbuf involved, if any.
Parameter 4	4) Information about the disk block header involved, if any.
Probable Cause	No additional information available.

Error 1009035	"%2: The logical or physical block number must be > 0; buffer={%3} page={%4}. %1"
Constant	EMSG_BUFMAN_BADBLOCKNUMBER
SAP Sybase Error Number	20056
SQL State	QSA35
SQL Code	-1009035L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) The particular buffer cache throwing the exception.
Parameter 3	3) Information about the sbuf involved, if any.
Parameter 4	4) Information about the disk block header involved, if any.

Error 1009035	"%2: The logical or physical block number must be > 0; buffer={%3} page={%4}. %1"
Probable Cause	Typically, production builds will abort here if trying to Find() a page that does not exist (non-existent pages have a 0 pbn in the blockmap entry).
Error 1009036	"%2: Invalid compression type; buffer={%3} page={%4}. %1"
Constant	EMSG_BUFMAN_BADCTYPE
SAP Sybase Error Number	20057
SQL State	QSA36
SQL Code	-1009036L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) The particular buffer cache throwing the exception.
Parameter 3	3) Information about the sbuf involved, if any.
Parameter 4	4) Information about the disk block header involved, if any.
Probable Cause	No additional information available.
Error 1009037	"%2: Buffer was not locked when it should have been; buffer={%3} page={%4}. %1"
Constant	EMSG_BUFMAN_MUSTBEACTIVEBUF
SAP Sybase Error Number	20058
SQL State	QSA37
SQL Code	-1009037L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	1) location of the exception

Error 1009037	"%2: Buffer was not locked when it should have been; buffer={%3} page={%4}. %1"
Parameter 2	2) The particular buffer cache throwing the exception.
Parameter 3	3) Information about the sbuf involved, if any.
Parameter 4	4) Information about the disk block header involved, if any.
Probable Cause	No additional information available.

Error 1009038	"%2: Tried to write to a readonly database; buffer={%3} page={%4}. %1"
Constant	EMSG_BUFMAN_MUSTHAVERWACCESS
SAP Sybase Error Number	20059
SQL State	QSA38
SQL Code	-1009038L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) The particular buffer cache throwing the exception.
Parameter 3	3) Information about the sbuf involved, if any.
Parameter 4	4) Information about the disk block header involved, if any.
Probable Cause	No additional information available.

Error 1009039	"%2: An error was detected on a database page. You may have a damaged index. For additional information, please check your IQ message file or run sp_iqcheckdb. %1"
Constant	EMSG_BUFMAN_INCORRECT_DISKBLOCKHEADER
SAP Sybase Error Number	20060
SQL State	QSA39
SQL Code	-1009039L
ODBC 2 State	ERROR

Error 1009039	"%2: An error was detected on a database page. You may have a damaged index. For additional information, please check your IQ message file or run sp_iqcheckdb. %1"
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) The particular buffer cache throwing the exception.
Probable Cause	When we read a page from the database, we detected that its header was either corrupt or that the header did not correspond to the page we thought we were reading. This is normally a fatal error; the database itself is likely to be corrupt.

Error 1009040	"%2: Memory & disk block number mismatch; buffer={%3} page={%4}. %1"
Constant	EMSG_BUFMAN_BIO_MISMATCH_BLOCK
SAP Sybase Error Number	20061
SQL State	QSA40
SQL Code	-1009040L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) The particular buffer cache throwing the exception.
Parameter 3	3) Information about the sbuf involved, if any.
Parameter 4	4) Information about the disk block header involved, if any.
Probable Cause	No additional information available.

Error 1009041	"%2: Memory & disk block type mismatch; buffer={%3} page={%4}. %1"
Constant	EMSG_BUFMAN_BIO_MISMATCH_BTTYPE
SAP Sybase Error Number	20062

Error 1009041	"%2: Memory & disk block type mismatch; buffer={%3} page={%4}. %1"
SQL State	QSA41
SQL Code	-1009041L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) The particular buffer cache throwing the exception.
Parameter 3	3) Information about the sbuf involved, if any.
Parameter 4	4) Information about the disk block header involved, if any.
Probable Cause	No additional information available.

Error 1009042	"%2: Attempted to write a page that was not dirty; buffer={%3} page={%4}. %1"
Constant	EMSG_BUFMAN_BIO_NOTDIRTY
SAP Sybase Error Number	20063
SQL State	QSA42
SQL Code	-1009042L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) The particular buffer cache throwing the exception.
Parameter 3	3) Information about the sbuf involved, if any.
Parameter 4	4) Information about the disk block header involved, if any.
Probable Cause	No additional information available.

Error 1009043	"%2: Memory & disk number of blocks mismatch. %1"
Constant	EMSG_BUFMAN_BIO_MISMATCH_NBLKS
SAP Sybase Error Number	20064
SQL State	QSA43
SQL Code	-1009043L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) The particular buffer cache throwing the exception.
Probable Cause	No additional information available.

Messages 1009044 through 1009064

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1009044	"An IO error was encountered while reading a database page in %2 DBSpace. %1"
Constant	EMSG_BUFMAN_BIO_READ_ERROR
SAP Sybase Error Number	20065
SQL State	QSA44
SQL Code	-1009044L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) dbspace name
Probable Cause	No additional information available.

Error 1009045	"Bitmap failed internal checks. You may have a damaged index. Please check your IQ message file for additional information. %1"
Constant	EMSG_BM_VERIFY
SAP Sybase Error Number	20066
SQL State	QSA45
SQL Code	-1009045L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	1) location of the exception
Probable Cause	No additional information available.

Error 1009046	"%2: An error was detected on a database page. You may have a damaged index. For additional information, please check your IQ message file or run sp_iqcheckdb. %1"
Constant	EMSG_BUFMAN_DECOMPRESSION_ERROR
SAP Sybase Error Number	20067
SQL State	QSA46
SQL Code	-1009046L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) The particular buffer cache throwing the exception.
Probable Cause	No additional information available.

Error 1009047	"%2: Blockmap info error; bmp={%3}. %1"
Constant	EMSG_BUFMAN_BLOCKMAP_INFO_ERROR
SAP Sybase Error Number	20068

Error 1009047	"%2: Blockmap info error; bmp={%3}. %1"
SQL State	QSA47
SQL Code	-1009047L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) The particular buffer cache throwing the exception.
Parameter 3	3) Information about the blockmap
Probable Cause	No additional information available.

Error 1009048	"%2: Tried to destroy a userlocked buffer; buffer={%3} page={%4}. %1"
Constant	EMSG_BUFMAN_LOCK_DURINGDESTROY
SAP Sybase Error Number	20069
SQL State	QSA48
SQL Code	-1009048L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) The particular buffer cache throwing the exception.
Parameter 3	3) Information about the sbuf involved, if any.
Parameter 4	4) Information about the disk block header involved, if any.
Probable Cause	No additional information available.

Error 1009049	"%2: The buffer manager is in an inconsistent state; buffer={%3} page={%4}. %1"
Constant	EMSG_BUFMAN_CORRUPT

Error 1009049	"%2: The buffer manager is in an inconsistent state; buffer={%3} page={%4}. %1"
SAP Sybase Error Number	20070
SQL State	QSA49
SQL Code	-1009049L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) The particular buffer cache throwing the exception.
Parameter 3	3) Information about the sbuf involved, if any.
Parameter 4	4) Information about the disk block header involved, if any.
Probable Cause	No additional information available.

Error 1009050	"%2: Btype specific truncation method returned invalid size for btype. %1"
Constant	EMSG_BUFMAN_TRUNC_BAD
SAP Sybase Error Number	20071
SQL State	QSA50
SQL Code	-1009050L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) The particular buffer cache throwing the exception.
Probable Cause	No additional information available.

Error 1009051	"An index cannot be created on a char, varchar or varbinary column greater than 255 characters. %1"
Constant	EMSG_VARCHAR_INDEX_NOT_SUPPORTED

Error 1009051	"An index cannot be created on a char, varchar or varbinary column greater than 255 characters. %1"
SAP Sybase Error Number	20072
SQL State	QSA51
SQL Code	-1009051L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1009052	"Internal error. Index %2 does not yet support the requested operation. %1"
Constant	EMSG_INDEX_OPERATION_NOT_IMPLEMENTED
SAP Sybase Error Number	20073
SQL State	QSA52
SQL Code	-1009052L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	name of the index
Probable Cause	An operation, for example SUM, was forwarded to an index, for example HG, that does not directly implement the operation. Normally, this should not be possible, but can be forced by setting command options.

Error 1009053	"%2: s_dbmvbio WriteCheck failed; buffer={%3} page={%4}. %1"
Constant	EMSG_BUFMAN_BIO_WRITECHECK
SAP Sybase Error Number	20074

Error 1009053	"%2: s_dbmvbio WriteCheck failed; buffer={%3} page={%4}. %1"
SQL State	QSA53
SQL Code	-1009053L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) The particular buffer cache throwing the exception.
Parameter 3	3) Information about the sbuf involved, if any.
Parameter 4	4) Information about the disk block header involved, if any.
Probable Cause	No additional information available.

Error 1009054	"Command prohibited on a multiplex coordinator, %1"
Constant	EMSG_NOCMD_MPX_WRITE
SAP Sybase Error Number	20075
SQL State	QSA54
SQL Code	-1009054L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Probable Cause	Command not allowed on a multiplex coordinator

Error 1009055	"Command prohibited on a multiplex query server, %1"
Constant	EMSG_NOCMD_MPX_QUERY
SAP Sybase Error Number	20076
SQL State	QSA55
SQL Code	-1009055L

Error 1009055	"Command prohibited on a multiplex query server, %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Probable Cause	Command not allowed on a multiplex query server

Error 1009056	"Command prohibited on a multiplex server, %1"
Constant	EMSG_NOCMD_MPX_SERVER
SAP Sybase Error Number	20077
SQL State	QSA56
SQL Code	-1009056L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Probable Cause	Command not allowed on a multiplex server

Error 1009057	"Cannot make all dbspaces readonly while there are active or uncheckpointed readwrite transactions, %1"
Constant	EMSG_CANNOT_ALTER_TOALLRO
SAP Sybase Error Number	20078
SQL State	QSA57
SQL Code	-1009057L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Probable Cause	Cannot make the last rw dbspace ro while there is rw activity.

Error 1009058	"There are no dbspaces open in readwrite mode for this RW operation, %1"
Constant	EMSG_NO_RWDBSPACE
SAP Sybase Error Number	20079
SQL State	QSA58
SQL Code	-1009058L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1009059	"Alter dbspace relocate requires at least one other readwrite dbspace (%2). %1"
Constant	EMSG_SDBEXT_NEEDRWFORRR
SAP Sybase Error Number	20080
SQL State	QSA59
SQL Code	-1009059L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	dbspace name
Probable Cause	Cannot alter the only readwrite dbspace to relocate mode.

Error 1009060	"Cannot alter this dbspace to relocate mode without a readwrite dbspace (%2). %1"
Constant	EMSG_SDBEXT_CANNOT_ALTER_RR
SAP Sybase Error Number	20081
SQL State	QSA60

Error 1009060	"Cannot alter this dbspace to relocate mode without a readwrite dbspace (%2). %1"
SQL Code	-1009060L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	dbspace name
Probable Cause	Cannot alter the readonly segment that contains the db identity to relocate mode.

Error 1009061	"There must be at least one readwrite dbspace and one relocate dbspace to relocate data. %1"
Constant	EMSG_NOT_OK_TO_RELOCATE
SAP Sybase Error Number	20082
SQL State	QSA61
SQL Code	-1009061L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	Must have at least one RW dbspace and one RR dbspace for sp_iq-relocate

Error 1009063	"Cannot alter this dbspace from relocate mode to readonly mode while there are active readwrite transactions that may be using it. %1"
Constant	EMSG_CANNOT_ALTER_RRTORO
SAP Sybase Error Number	20084
SQL State	QSA63
SQL Code	-1009063L

Error 1009063	"Cannot alter this dbspace from relocate mode to readonly mode while there are active readwrite transactions that may be using it. %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1009064	"Cannot create or add file %2 for dbspace %3 until new readwrite space is added to dbspace %4 to hold the new freelist. %1"
Constant	EMSG_SDBEXT_NO_FREELIST_SPACE
SAP Sybase Error Number	20085
SQL State	QSA64
SQL Code	-1009064L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	pathname of file being created
Parameter 3	name of dbspace for which file is being created
Parameter 4	name of IQ_SYSTEM_MAIN dbspace
Probable Cause	When creating a new dbspace in the IQ MAIN STORE, or creating a new file for a dbspace other than IQ_SYSTEM_MAIN in the IQ MAIN STORE, there must be sufficient freelist space available to describe the physical blocks we are adding to the database. If this is not the case, the above error occurs. (The space for the freelist can only be allocated in readwrite IQ_SYSTEM_MAIN files.) The corrective action is to first add a new file to the IQ_SYSTEM_MAIN dbspace so that new freelist space becomes available.

Messages 1009065 through 1009084

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1009065	"Operation '%2' not allowed in forced recovery. %1"
Constant	EMSG_DBSPACE_NOT_IN_FORCEDRECOVERY
SAP Sybase Error Number	20086
SQL State	QSA65
SQL Code	-1009065L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Dbpace name
Probable Cause	Certain operations are not permitted in forced recovery

Error 1009066	"Cannot execute '%2' yet since previous alter command is not yet propagated through the multiplex. Try again. %1"
Constant	EMSG_CMD_NOT_REPLAYED
SAP Sybase Error Number	20087
SQL State	QSA66
SQL Code	-1009066L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Dbpace name
Probable Cause	The command cannot be executed since the previous alter/create command has not propagated through multiplex yet.

Error 1009067	"%1"
Constant	EMSG_RFU_QSA67
SAP Sybase Error Number	20088
SQL State	QSA67
SQL Code	-1009067L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1009068	"Tried to insert a duplicate entry. %1"
Constant	EMSG_HASHTB_DUPENTRY
SAP Sybase Error Number	20089
SQL State	QSA68
SQL Code	-1009068L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1009069	"Could not find key in hashtable"
Constant	EMSG_HASHTB_KEYNOTFOUND
SAP Sybase Error Number	20090
SQL State	QSA69
SQL Code	-1009069L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1009069	"Could not find key in hashtable"
Severity Code	<i>14</i> on page 2
Probable Cause	No additional information available.

Error 1009070	"Hashtable is full"
Constant	EMSG_HASHTB_FULL
SAP Sybase Error Number	20091
SQL State	QSA70
SQL Code	-1009070L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Probable Cause	No additional information available.

Error 1009071	"Hash input key descriptor has zero fields (%2, %3). %1"
Constant	EMSG_PHASH_NOKEY
SAP Sybase Error Number	20092
SQL State	QSA71
SQL Code	-1009071L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>23</i> on page 2
Parameter 1	1) location of the exception
Parameter 2	2) major context (hos_StatsObj::SubStatementId, usually dfo number)
Parameter 3	3) minor context (s_phash::StatMinorContext, see s_phash.h for enum)
Probable Cause	No additional information available.

Error 1009072	"Insufficient buffers for hash. (%2, %3). %1"
Constant	EMSG_PHASH_MAXBUFFERS
SAP Sybase Error Number	20093
SQL State	QSA72
SQL Code	-1009072L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) major context (hos_StatsObj::SubStatementId, usually dfo number)
Parameter 3	3) minor context (s_phash::StatMinorContext, see s_phash.h for enum)
Probable Cause	Specifically, the number of estimated buffers given to the hash object exceeds the size of the buffer cache.

Error 1009073	"Hash function can't handle this datatype (%2, %3). %1"
Constant	EMSG_PHASH_HASHDT
SAP Sybase Error Number	20094
SQL State	QSA73
SQL Code	-1009073L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) major context (hos_StatsObj::SubStatementId, usually dfo number)
Parameter 3	3) minor context (s_phash::StatMinorContext, see s_phash.h for enum)
Probable Cause	No additional information available.

Error 1009074	"Key length in hash equality function is zero (%2, %3). %1"
Constant	EMSG_PHASH_EQUALKEYLEN
SAP Sybase Error Number	20095
SQL State	QSA74
SQL Code	-1009074L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) major context (hos_StatsObj::SubStatementId, usually dfo number)
Parameter 3	3) minor context (s_phash::StatMinorContext, see s_phash.h for enum)
Probable Cause	No additional information available.

Error 1009075	"Buffer mapper init incorrect (%2, %3). %1"
Constant	EMSG_PHASH_BUFMAPINIT
SAP Sybase Error Number	20096
SQL State	QSA75
SQL Code	-1009075L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) major context (hos_StatsObj::SubStatementId, usually dfo number)
Parameter 3	3) minor context (s_phash::StatMinorContext, see s_phash.h for enum)
Probable Cause	No additional information available.

Error 1009076	"Internal hash error; buffer was previously created: %2 (%3, %4). %1"
Constant	EMSG_PHASH_BUFDDOUBLECREATE
SAP Sybase Error Number	20097
SQL State	QSA76
SQL Code	-1009076L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) Buffer Number.
Parameter 3	3) major context (hos_StatsObj::SubStatementId, usually dfo number)
Parameter 4	4) minor context (s_phash::StatMinorContext, see s_phash.h for enum)
Probable Cause	No additional information available.

Error 1009077	"Internal hash error; next data entry should be valid (%2, %3). %1"
Constant	EMSG_PHASH_INVALID_NEXTENTRY
SAP Sybase Error Number	20098
SQL State	QSA77
SQL Code	-1009077L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) major context (hos_StatsObj::SubStatementId, usually dfo number)

Error 1009077	"Internal hash error; next data entry should be valid (%2, %3). %1"
Parameter 3	3) minor context (s_phash::StatMinorContext, see s_phash.h for enum)
Probable Cause	No additional information available.

Error 1009078	"Internal hash error; buffer not pinned (%2, %3). %1"
Constant	EMSG_PHASH_NOT_PINNED
SAP Sybase Error Number	20099
SQL State	QSA78
SQL Code	-1009078L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) major context (hos_StatsObj::SubStatementId, usually dfo number)
Parameter 3	3) minor context (s_phash::StatMinorContext, see s_phash.h for enum)
Probable Cause	No additional information available.

Error 1009079	"Internal hash error; too many buffers left in use: %2 (%3, %4). %1"
Constant	EMSG_PHASH_INUSE_HIGH
SAP Sybase Error Number	20100
SQL State	QSA79
SQL Code	-1009079L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	1) location of the exception

Error 1009079	"Internal hash error; too many buffers left in use: %2 (%3, %4). %1"
Parameter 2	2) Number of buffers.
Parameter 3	3) major context (hos_StatsObj::SubStatementId, usually dfo number)
Parameter 4	4) minor context (s_phash::StatMinorContext, see s_phash.h for enum)
Probable Cause	No additional information available.

Error 1009080	"Key doesn't fit on a single database page: %2 (%3, %4). %1"
Constant	EMSG_PHASH_KEY_TOO_LARGE
SAP Sybase Error Number	20101
SQL State	QSA80
SQL Code	-1009080L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) Key size.
Parameter 3	3) major context (hos_StatsObj::SubStatementId, usually dfo number)
Parameter 4	4) minor context (s_phash::StatMinorContext, see s_phash.h for enum)
Probable Cause	No additional information available.

Error 1009081	"Data doesn't fit on a single database page: %2 (%3, %4). %1"
Constant	EMSG_PHASH_DATA_TOO_LARGE
SAP Sybase Error Number	20102
SQL State	QSA81

Error 1009081	"Data doesn't fit on a single database page: %2 (%3, %4). %1"
SQL Code	-1009081L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) Data size.
Parameter 3	3) major context (hos_StatsObj::SubStatementId, usually dfo number)
Parameter 4	4) minor context (s_phash::StatMinorContext, see s_phash.h for enum)
Probable Cause	No additional information available.

Error 1009082	"Hash object has no data to retrieve, only keys (%2, %3). %1"
Constant	EMSG_PHASH_NO_DATA
SAP Sybase Error Number	20103
SQL State	QSA82
SQL Code	-1009082L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) major context (hos_StatsObj::SubStatementId, usually dfo number)
Parameter 3	3) minor context (s_phash::StatMinorContext, see s_phash.h for enum)
Probable Cause	No additional information available.

Error 1009083	"DBSpace '%2' must be OFFLINE for ALTER PATH. %1"
Constant	EMSG_ALTER_PATH_REQUIRES_OFFLINE_DBSPACE
SAP Sybase Error Number	20104
SQL State	QSA83
SQL Code	-1009083L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	dbspace name
Probable Cause	No additional information available.

Error 1009084	"Error opening DBSPACE '%2'. %1"
Constant	EMSG_DBSPACE_OPEN_ERROR
SAP Sybase Error Number	20105
SQL State	QSA84
SQL Code	-1009084L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	dbspace name
Probable Cause	No additional information available.

Messages 1009085 through 1009104

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1009085	"DBFILE '%2' is not valid. The catalog DBSpaceID is incorrect. DBSpaceID found: %3 DBSpaceID expected: %4. This segment cannot be used. %1"
Constant	EMSG_BAD_CAT_DBSPACEID
SAP Sybase Error Number	20106
SQL State	QSA85
SQL Code	-1009085L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Parameter 2	file path
Parameter 3	dbspace_id found
Parameter 4	dbspace_id expected
Probable Cause	No additional information available.

Error 1009086	"Error opening DBFILE '%2'. %1"
Constant	EMSG_DBFILE_OPEN_ERROR
SAP Sybase Error Number	20107
SQL State	QSA86
SQL Code	-1009086L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	file path

Error 1009086	"Error opening DBFILE '%2'. %1"
Probable Cause	No additional information available.

Error 1009087	"The dbfile '%2' must be in READONLY mode for this operation. %1"
Constant	EMSG_DBFILE_MUST_BE_RO
SAP Sybase Error Number	20108
SQL State	QSA87
SQL Code	-1009087L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	file path
Probable Cause	No additional information available.

Error 1009088	"Attempted to add a duplicate key. %1"
Constant	EMSG_BT_DUPLICATE
SAP Sybase Error Number	20109
SQL State	QSA88
SQL Code	-1009088L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1009089	"The size of the value is more than the maximum allowed for the field. Value: %2 %1"
Constant	EMSG_BT_KEYTOOBIG

Error 1009089	"The size of the value is more than the maximum allowed for the field. Value: %2 %1"
SAP Sybase Error Number	20110
SQL State	QSA89
SQL Code	-1009089L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Key value.
Probable Cause	No additional information available.

Error 1009090	"Page size selected is too small for this datatype. %1"
Constant	EMSG_BT_LARGERPAGE
SAP Sybase Error Number	20111
SQL State	QSA90
SQL Code	-1009090L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Parameter 1 description
Probable Cause	No additional information available.

Error 1009091	"Attempt to create a B-Tree with RecordSize+KeySize too large. %1"
Constant	EMSG_BT_SIZEERROR
SAP Sybase Error Number	20112
SQL State	QSA91
SQL Code	-1009091L

Error 1009091	"Attempt to create a B-Tree with RecordSize+KeySize too large. %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1009092	"Must provide a key comparison routine on object creation. %1"
Constant	EMSG_BT_NOKEYCOMPARE
SAP Sybase Error Number	20113
SQL State	QSA92
SQL Code	-1009092L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1009093	"The maximum key size must be between 1 and 5300. Key size: %2 %1"
Constant	EMSG_BT_MAXKEYSIZEWRONG
SAP Sybase Error Number	20114
SQL State	QSA93
SQL Code	-1009093L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception

Error 1009093	"The maximum key size must be between 1 and 5300. Key size: %2 %1"
Parameter 2	Key Size in error.
Probable Cause	No additional information available.
Error 1009094	"Cannot use raw partition for MESSAGE LOG or ROW LOG. %1"
Constant	EMSG_SVIOLATION_LOG_ON_RAW
SAP Sybase Error Number	20115
SQL State	QSA94
SQL Code	-1009094L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	The MESSAGE LOG and ROW LOG files for load integrity constraint handling must be regular files. They cannot be raw partitions.
Error 1009095	"MESSAGE LOG and ROW LOG cannot be the same on-disk file. %1"
Constant	EMSG_SVIOLATION_LOGS_SAMEFILE
SAP Sybase Error Number	20116
SQL State	QSA95
SQL Code	-1009095L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	The MESSAGE LOG and ROW LOG files cannot be the same on-disk files.

Error 1009096	"%3 integrity constraint limit (%2) exceeded. %1"
Constant	EMSG_SVIOLATION_IGNORE_LIMIT_EXCEEDED
SAP Sybase Error Number	20117
SQL State	QSA96
SQL Code	-1009096L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	user specified integrity constraint limit
Parameter 3	type of integrity constraint violation specified by the user
Probable Cause	The number of integrity constraint violations for the given type has been exceeded during the LOAD. The LOAD will rollback.

Error 1009097	"Cumulative total (%2) for all integrity constraint violations exceeded. %1"
Constant	EMSG_SVIOLATION_ALL_LIMIT_EXCEEDED
SAP Sybase Error Number	20118
SQL State	QSA97
SQL Code	-1009097L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception
Parameter 2	maximum number of constraint violations to ignore
Probable Cause	The total number of NULL, UNIQUE, DATA VALUE, and FOREIGN KEY integrity constraint violations has exceeded the user specified limit.

Errors and Warnings

Error 1009098	"Invalid MESSAGE LOG or ROW LOG filename. %1"
Constant	EMSG_SVIOLATION_INVALID_FILENAME
SAP Sybase Error Number	20119
SQL State	QSA98
SQL Code	-1009098L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception
Probable Cause	A bad filename (perhaps zero-length) was specified for either the MESSAGE LOG or ROW LOG files on the LOAD statement.

Error 1009099	"%1"
Constant	EMSG_RFU_QSA99
SAP Sybase Error Number	20120
SQL State	QSA99
SQL Code	-1009099L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1009100	"Database segment '%2' is not valid. It is of type '%3'. Type BTYPE_DBEXT was expected. This segment cannot be used. %1"
Constant	EMSG_SDBEXT_BAD_BTTYPE
SAP Sybase Error Number	20121
SQL State	QSB00

Error 1009100	"Database segment '%2' is not valid. It is of type '%3'. Type BTYPE_DBEXT was expected. This segment cannot be used. %1"
SQL Code	-1009100L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Parameter 2	Name of the segment.
Parameter 3	Internal segment type found.
Probable Cause	The segment type written to the segment header was found not to be of the expected type. You will need to restore your database from backup.

Error 1009101	"Database segment '%2' is not valid. PhysicalNBlocks Found: %3 PhysicalNBlocks Expected: 1. This segment cannot be used. %1"
Constant	EMSG_SDBEXT_BAD_NUMPHYSBLOCKS
SAP Sybase Error Number	20122
SQL State	QSB01
SQL Code	-1009101L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Parameter 2	Name of the segment.
Parameter 3	Number of Physical Blocks found.
Probable Cause	The number of physical blocks read from the segment header is incorrect. You will need to restore your database from backup.

Error 1009102	"Incorrect HG Index Version (%2): Index must be dropped by previous version of Sybase IQ and recreated. %1"
Constant	EMSG_ERROR_VERSION
SAP Sybase Error Number	20123
SQL State	QSB02
SQL Code	-1009102L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Incorrect version of index.
Probable Cause	No additional information available.

Error 1009103	"Number of unique values exceeded for index. %2 %3 %1"
Constant	EMSG_ERROR_KVTMAX
SAP Sybase Error Number	20124
SQL State	QSB03
SQL Code	-1009103L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Index.
Parameter 3	Number of values.
Probable Cause	No additional information available.

Error 1009104	"Bad args, both values must be >= 1 (%2 %3). %1"
Constant	EMSG_VDO_BADARGS
SAP Sybase Error Number	20125

Error 1009104	"Bad args, both values must be >= 1 (%2 %3). %1"
SQL State	QSB04
SQL Code	-1009104L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	Value 1
Parameter 3	Value 2
Probable Cause	No additional information available.

Messages 1009105 through 1009124

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1009105	"Could not find block: %2. %1"
Constant	EMSG_VDO_BLKNOTFOUND
SAP Sybase Error Number	20126
SQL State	QSB05
SQL Code	-1009105L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	Block Number
Probable Cause	No additional information available.

Error 1009106	"DBFILE '%2' is not valid. The catalog file id is incorrect. FileID found: %3 FileID expected: %4. This segment cannot be used. %1"
Constant	EMSG_SDBEXT_BAD_CATFILEID

Error 1009106	"DBFILE '%2' is not valid. The catalog file id is incorrect. FileID found: %3 FileID expected: %4. This segment cannot be used. %1"
SAP Sybase Error Number	20127
SQL State	QSB06
SQL Code	-1009106L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Parameter 2	Segment name.
Parameter 3	FileID found on the disk segment header.
Parameter 4	FileID expected to be found on the disk segment header.
Probable Cause	The FileID information stored on the disk segment's header is not correct. The disk segment cannot be used.

Error 1009107	"Duplicate entry for block: %2, record %3. %1"
Constant	EMSG_VDO_DUPENTRY
SAP Sybase Error Number	20128
SQL State	QSB07
SQL Code	-1009107L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	Block with duplication entry.
Parameter 3	Duplicate entry.
Probable Cause	No additional information available.

Error 1009108	"Database segment '%2' is not valid. Startblock found in the header: %3 Startblock expected: %4. This segment cannot be used. %1"
Constant	EMSG_SDBEXT_BAD_STARTBLOCK
SAP Sybase Error Number	20129
SQL State	QSB08
SQL Code	-1009108L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Parameter 2	Name of the segment.
Parameter 3	Starting block found in the disk header.
Parameter 4	Starting block expected.
Probable Cause	The start block of the disk segment that was found in the disk segment header is not the same as what was expected. The disk segment cannot be used.

Error 1009109	"Key size %2 is more than the maximum %3. %1"
Constant	EMSG_VDO_KEYTOOBIG
SAP Sybase Error Number	20130
SQL State	QSB09
SQL Code	-1009109L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	Key size.
Parameter 3	Max key size.

Error 1009109	"Key size %2 is more than the maximum %3. %1"
Probable Cause	No additional information available.

Error 1009110	"%1"
Constant	EMSG_RFU_QSB10
SAP Sybase Error Number	20131
SQL State	QSB10
SQL Code	-1009110L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1009111	"Could not find record %2 within block %3. %1"
Constant	EMSG_VDO_RECNOTFOUND
SAP Sybase Error Number	20132
SQL State	QSB11
SQL Code	-1009111L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	Record that could not be found.
Parameter 3	Block being searched.
Probable Cause	No additional information available.

Error 1009112	"%1"
Constant	EMSG_RFU_QSB12

Error 1009112	"%1"
SAP Sybase Error Number	20133
SQL State	QSB12
SQL Code	-1009112L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1009113	"Secondary error noted. Semi-Join not ready %2. %1"
Constant	EMSG_SECONDARY_ERR
SAP Sybase Error Number	20134
SQL State	QSB13
SQL Code	-1009113L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	more information about join node for which semi-join is not ready.
Probable Cause	No additional information available.

Error 1009114	"Tried to put too many records %2 into block %3. %1"
Constant	EMSG_VDO_TOOMANYRECS
SAP Sybase Error Number	20135
SQL State	QSB14
SQL Code	-1009114L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1009114	"Tried to put too many records %2 into block %3. %1"
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	Number of records.
Parameter 3	Block being inserted into.
Probable Cause	No additional information available.

Error 1009115	"Database segment '%2' is not valid. %3 imaginary freelist blocks were found, but %4 imaginary freelist blocks were expected. This segment cannot be used. %1"
Constant	EMSG_SDBEXT_DIF_NIBLOCKS
SAP Sybase Error Number	20136
SQL State	QSB15
SQL Code	-1009115L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Parameter 2	Name of the segment.
Parameter 3	Number of imaginary freelist blocks recorded in the segment header.
Parameter 4	Number of freelist blocks that were expected to be recorded in the header.
Probable Cause	When a database segment is opened, the segment header is read and the number of freelist blocks read from the header is compared with the number of freelist blocks that are expected to be read from the segment header. If the numbers do not match, the segment cannot be used and the database must be restored from backup.

Error 1009116	"Wrong new() was called. %1"
Constant	EMSG_VDO_WRONGNEW
SAP Sybase Error Number	20137

Error 1009116	"Wrong new() was called. %1"
SQL State	QSB16
SQL Code	-1009116L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1009117	"Update can not do different sized values yet. New size = %2, old size = %3. %1"
Constant	EMSG_VDO_UPDATESIZE
SAP Sybase Error Number	20138
SQL State	QSB17
SQL Code	-1009117L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	New size.
Parameter 3	Old size.
Probable Cause	No additional information available.

Error 1009118	"Database segment '%2' is not valid. %3 freelist blocks were found, but %4 freelist blocks were expected. This segment cannot be used. %1"
Constant	EMSG_SDBEXT_DIF_NFLBLOCKS
SAP Sybase Error Number	20139
SQL State	QSB18

Error 1009118	"Database segment '%2' is not valid. %3 freelist blocks were found, but %4 freelist blocks were expected. This segment cannot be used. %1"
SQL Code	-1009118L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Parameter 2	Name of the segment.
Parameter 3	Number of freelist blocks recorded in the segment header.
Parameter 4	Number of freelist blocks that were expected to be recorded in the header.
Probable Cause	When a database segment is opened, the segment header is read and the number of freelist blocks read from the header is compared with the number of freelist blocks that are expected to be read from the segment header. If the numbers do not match, the segment cannot be used and the database must be restored from backup.

Error 1009119	"Record size too large for database page size. %1"
Constant	EMSG_SORT_INVALIDRECSIZE
SAP Sybase Error Number	20140
SQL State	QSB19
SQL Code	-1009119L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Warning 1009120	" %1 Sort: Sorted #%2, %3 Recs, %4 Secs"
Constant	EMSG_SORT_INFOSORTED
SAP Sybase Error Number	20141

Warning 1009120	" %1 Sort: Sorted #%2, %3 Recs, %4 Secs"
SQL State	QSB20
SQL Code	1009120L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	1 on page 2
Parameter 1	What is being sorted.
Parameter 2	Which particular run of the sort.
Parameter 3	How many records were sorted.
Parameter 4	How long the sort took.
Probable Cause	No additional information available.

Warning 1009121	" %1 Sort: Saved #%2, %3 Recs, %4 Secs"
Constant	EMSG_SORT_INFOSAVED
SAP Sybase Error Number	20142
SQL State	QSB21
SQL Code	1009121L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	1 on page 2
Parameter 1	What is being sorted.
Parameter 2	Which particular run of the sort.
Parameter 3	How many records were sorted.
Parameter 4	How long the sort took.
Probable Cause	No additional information available.

Warning 1009122	" %1 Sort: Merged %2 runs, %3 Secs, %4 runs remaining"
Constant	EMSG_SORT_INFOMERGED
SAP Sybase Error Number	20143

Warning 1009122	" %1 Sort: Merged %2 runs, %3 Secs, %4 runs remaining"
SQL State	QSB22
SQL Code	1009122L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>1</i> on page 2
Parameter 1	What is being sorted.
Parameter 2	How many merged.
Parameter 3	Time taken.
Parameter 4	How many runs still requiring to be merged.
Probable Cause	No additional information available.

Error 1009123	"Database Segment %2 is not valid. Missing DBSignature. This Segment can not be used. %1"
Constant	EMSG_SDBEXT_BAD_DBSIGNATURE
SAP Sybase Error Number	20144
SQL State	QSB23
SQL Code	-1009123L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	Database segment.
Probable Cause	No additional information available.

Error 1009124	"Database Segment %2, blocksize %3 does not match catalog blocksize of %4. This Segment can not be used. %1"
Constant	EMSG_SDBEXT_DIF_BLOCKSIZE
SAP Sybase Error Number	20145

Error 1009124	"Database Segment %2, blocksize %3 does not match catalog blocksize of %4. This Segment can not be used. %1"
SQL State	QSB24
SQL Code	-1009124L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Database segment.
Parameter 3	Block size.
Parameter 4	Catalog Block size.
Probable Cause	No additional information available.

Messages 1009125 through 1009145

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1009125	"Database Segment %2, maxcompression %3 does not match catalog maxcompression of %4. This Segment can not be used. %1"
Constant	EMSG_SDBEXT_DIF_MAXCOMPRESSION
SAP Sybase Error Number	20146
SQL State	QSB25
SQL Code	-1009125L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Database segment.
Parameter 3	Max compression

Error 1009125	"Database Segment %2, maxcompression %3 does not match catalog maxcompression of %4. This Segment can not be used. %1"
Parameter 4	Catalog max compression.
Probable Cause	No additional information available.

Error 1009126	"Database Segment %2, createtime does not match catalog. This Segment can not be used. %1"
Constant	EMSG_SDBEXT_DIF_CREATETIME
SAP Sybase Error Number	20147
SQL State	QSB26
SQL Code	-1009126L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	Database segment.
Probable Cause	No additional information available.

Error 1009127	"Database Segment %2, %3 size does not match catalog size of %4. This Segment can not be used. %1"
Constant	EMSG_SDBEXT_DIF_NBLOCKS
SAP Sybase Error Number	20148
SQL State	QSB27
SQL Code	-1009127L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	Database segment.

Error 1009127	"Database Segment %2, %3 size does not match catalog size of %4. This Segment can not be used. %1"
Parameter 3	Size of segment.
Parameter 4	Catalog size of segment.
Probable Cause	No additional information available.

Error 1009128	"The IQ_SYSTEM_TEMP dbspace does not have dbfiles for this server. %1"
Constant	EMSG_SDBEXT_NOFREELIST
SAP Sybase Error Number	20149
SQL State	QSB28
SQL Code	-1009128L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1009129	"Database Segment %2, secondary server can not find a valid header. This segment can not be used. %1"
Constant	EMSG_SDBEXT_QSERVER_FAIL
SAP Sybase Error Number	20150
SQL State	QSB29
SQL Code	-1009129L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Database segment.
Probable Cause	No additional information available.

Error 1009130	"Database %2, does not have a segment for catalogfileid %3. %1"
Constant	EMSG_SDBEXT_MISSING_CATALOGFILEID
SAP Sybase Error Number	20151
SQL State	QSB30
SQL Code	-1009130L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Database segment.
Parameter 2	Max compression
Parameter 3	Catalog max compression.
Probable Cause	No additional information available.

Warning 1009131	"You have run out of %1 dbspace in database %2. In another session, please issue a CREATE DBSPACE ... %3 command and add a dbspace of at least %4 MB."
Constant	EMSG_IQSTORE_OUTOFDISK_HEADER
SAP Sybase Error Number	20152
SQL State	QSB31
SQL Code	1009131L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	string IQ STORE or IQ TEMPORARY STORE
Parameter 2	database name
Parameter 3	string IQ STORE or IQ TEMPORARY STORE
Parameter 4	the minimum number of megabytes to add

Warning 1009131	"You have run out of %1 dbspace in database %2. In another session, please issue a CREATE DBSPACE ... %3 command and add a dbspace of at least %4 MB."
Probable Cause	You have run out of DBSPACE in the named database. In order to continue, you must add another DBSPACE to the database unless space becomes available from another connection.

Warning 1009132	"The DBA has added %1 %2 dbspaces to database %3. Sybase IQ (TM) is no longer waiting for more dbspace."
Constant	EMSG_IQSTORE_OUTOFDISK_TRAILER
SAP Sybase Error Number	20153
SQL State	QSB32
SQL Code	1009132L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	explanation for arg %2 delete if no %1
Parameter 2	explanation for arg %3 delete if no %2
Parameter 3	explanation for %3
Probable Cause	No additional information available.

Error 1009133	"You have run out of space during the CHECKPOINT operation. %1"
Constant	EMSG_IQSTORE_OUTOFSPACE_CHECKPOINT
SAP Sybase Error Number	20982
SQL State	QSB33
SQL Code	-1009133L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2

Error 1009133	"You have run out of space during the CHECKPOINT operation. %1"
Parameter 1	location of the exception
Probable Cause	The checkpoint operation in progress needs to allocate blocks so that it can construct and save required checkpoint information. When space is exhausted during a checkpoint operation, it is not possible to add more space via a CREATE DBSPACE command. Consequently, the checkpoint operation will fail.

Error 1009134	"Insufficient buffers for '%2'. %1"
Constant	EMSG_SORT_MINBUFSAVAIL
SAP Sybase Error Number	21023
SQL State	QSB34
SQL Code	-1009134L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	clientType
Probable Cause	No additional information available.

Error 1009135	"Cannot perform requested command as there is a CREATE DBSPACE command in progress. %1"
Constant	EMSG_IQSTORE_INCREATEDDBSPACE
SAP Sybase Error Number	21034
SQL State	QSB36
SQL Code	-1009135L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception

Error 1009135	"Cannot perform requested command as there is a CREATE DBSPACE command in progress. %1"
Probable Cause	A CREATE DBSPACE or a DROP DBSPACE command was issued when there was already a DROP DBSPACE command in progress.
Error 1009136	"Cannot perform requested command as there is a DROP DBSPACE command in progress. %1"
Constant	EMSG_IQSTORE_INDROPDBSPACE
SAP Sybase Error Number	21035
SQL State	QSB37
SQL Code	-1009136L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	A CREATE DBSPACE or a DROP DBSPACE command was issued when there was already an ALTER DBSPACE command in progress.
Error 1009137	"Cannot perform DDL command now on table %2 as a DDL command is already in progress on that table. %1"
Constant	EMSG_DD LINPROGRESS
SAP Sybase Error Number	21036
SQL State	QDC55
SQL Code	-1009137L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Parameter 1 description
Parameter 2	location of the exception

Error 1009137	"Cannot perform DDL command now on table %2 as a DDL command is already in progress on that table. %1"
Probable Cause	There is already a DDL command in progress at the moment on the table specified and you must wait until it is finished before starting another DDL command on that table.
Error 1009139	"Cannot perform requested command as there is a CHECKPOINT command in progress. %1"
Constant	EMSG_IQSTORE_INCHECKPOINT
SAP Sybase Error Number	21038
SQL State	QSB38
SQL Code	-1009139L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	A CREATE DBSPACE or a DROP DBSPACE command was issued when there was already a CHECKPOINT command in progress.
Error 1009140	"Cannot restore dbspace '%2' to raw partition '%3' because its size is smaller than the size of the original raw partition (%4 vs. %5 blocks). %1"
Constant	EMSG_RESTORE_RAW_PARTITION_SIZE_MISMATCH
SAP Sybase Error Number	21039
SQL State	QCA49
SQL Code	-1009140L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	name of the IQ dbspace being restored

Error 1009140	"Cannot restore dbspace '%2' to raw partition '%3' because its size is smaller than the size of the original raw partition (%4 vs. %5 blocks). %1"
Parameter 3	raw partition to which the IQ dbspace is being restored
Parameter 4	size of the new raw partition
Parameter 5	size of the old raw partition
Probable Cause	This error means that the user is attempting to restore an IQ dbspace on a raw partition that is not the same size as the original raw partition on which the IQ dbspace existed at the time of the backup. The user must resize the raw partition and then retry the restore operation.

Error 1009141	"Table '%2' cannot be found in the IQ store. %1"
Constant	EMSG_SQL_IQTABLENOTFOUND
SAP Sybase Error Number	21061
SQL State	QCA51
SQL Code	-1009141L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	table name
Probable Cause	The stored procedure sp_iqtablesiz cannot find the table. This stored procedure is for IQ tables only. It cannot be run against system tables or ASA tables.

Warning 1009142	" %1 SortMerge0: %2 records, Phasel=%3 Secs, %4 runs total, %5 pgs=%6 M, runlen=%7, %8 est. phases"
Constant	EMSG_SORT_INFOMERGED0
SAP Sybase Error Number	21067
SQL State	QSB39
SQL Code	1009142L
ODBC 2 State	OK

Warning 1009142	" %1 SortMerge0: %2 records, Phasel=%3 Secs, %4 runs total, %5 pgs=%6 M, runlen=%7, %8 est. phases"
ODBC 3 State	OK
Severity Code	/ on page 2
Parameter 1	What is being sorted.
Parameter 2	How many records are being sorted.
Parameter 3	Time taken in Phase I.
Parameter 4	How many runs to be merged.
Parameter 5	How many pages of data to be sorted.
Parameter 6	How many Mbytes of data to be sorted.
Parameter 7	Average number of pages in a run.
Parameter 8	Estimated number of merge phases.
Probable Cause	This information is provided after the Phase I radix sorting is complete and the Phase II merge-sorting is about to begin. Each run consists of a sequence of pages that have been radix sorted in Phase I. These runs are merged together in Phase II to finish the sort.

Warning 1009143	" %1 SortMergePass: Merged %2 runs, %3 Secs, %4 runs remaining, %5 reads = %6 M, runlen=%7, phase %8, %9 M on disk"
Constant	EMSG_SORT_INFOMERGED1
SAP Sybase Error Number	21068
SQL State	QSB40
SQL Code	1009143L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	/ on page 2
Parameter 1	What is being sorted.
Parameter 2	How many runs were merged in this merge pass..
Parameter 3	Time taken in this merge pass.

Warning 1009143	" %1 SortMergePass: Merged %2 runs, %3 Secs, %4 runs remaining, %5 reads = %6 M, runlen=%7, phase %8, %9 M on disk"
Parameter 4	How many runs still to be merged.
Parameter 5	How many page reads done in this pass.
Parameter 6	How many Mbytes of data read in this pass.
Parameter 7	Average length of runs in pages, this pass.
Parameter 8	Fractional phase number reached.
Parameter 9	How many Mbytes of data physically read in this pass.
Probable Cause	This information is provided after each merge pass. One merge pass merges a certain number of runs, using one pinned buffer page per run plus one pinned buffer for the output run. Note that there can be several passes in a merge phase. One merge phase reads all the sort data and produces a new set of runs that provide input to the next phase.

Warning 1009144	" %1 SortMergeDone: Ave mem %2 M, %3 Secs, %4 passes, %5 reads, %6 M data= %7 pgs, %8 phases, %9 M on disk"
Constant	EMSG_SORT_INFOMERGED2
SAP Sybase Error Number	21069
SQL State	QSB41
SQL Code	1009144L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>1 on page 2</i>
Parameter 1	What is being sorted.
Parameter 2	Time-average number of pinned page buffers used by Phase II of the sort.
Parameter 3	Time taken for Phase II of the sort.
Parameter 4	Total number of passes in Phase II.
Parameter 5	Total number of page reads in Phase II.

Warning 1009144	" %1 SortMergeDone: Ave mem %2 M, %3 Secs, %4 passes, %5 reads, %6 M data= %7 pgs, %8 phases, %9 M on disk"
Parameter 6	Total Mbytes of data sorted.
Parameter 7	Total number of pages of data sorted.
Parameter 8	Number of merge phases in the merge sort of Phase II.
Parameter 9	Total Mbytes of physical reads in Phase II.
Probable Cause	This information is provided at the end of Phase II to summarize the resource usage of the whole merge sort. The last pass of the sort is separately reported on by an EMSG_SORT_INFOMERGED1 message.
Error 1009145	"Data exception - data type conversion is not possible. %2, %1"
Constant	EMSG_TYPECONVERSION_W_ARG
SAP Sybase Error Number	21070
SQL State	QFA2E
SQL Code	-1009145L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Exception line number
Parameter 2	SA parse source code line
Probable Cause	No additional information available.

1009146 - 1013018

Messages 1009146 through 1009165

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1009146	"Cannot perform requested command as there is a DBCC command in progress. %1"
Constant	EMSG_IQSTORE_INDBCC
SAP Sybase Error Number	21071
SQL State	QSB42
SQL Code	-1009146L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	A CHECKPOINT command was issued when there was already a DBCC command in progress.

Warning 1009147	"Space has become available in the %1 store of database %2. Sybase IQ (TM) is no longer waiting for more dbspace."
Constant	EMSG_IQSTORE_OUTOFDISK_SPACEAVAILABLE
SAP Sybase Error Number	20188
SQL State	QSB43
SQL Code	1009147L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	string IQ STORE or IQ TEMPORARY STORE
Parameter 2	Database Name
Probable Cause	No additional information available.

Error 1009148	"Cannot use -iqfrec to start a multiplex secondary server. %1"
Constant	EMSG_IQSTORE_NOFREC
SAP Sybase Error Number	21049
SQL State	QSB44
SQL Code	-1009148L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	A sp_iqcheckdb procedure call was issued on an IQ multiplex secondary server, or it was started in drop-leaks or forced recovery mode. These operations are only allowed on the coordinator

Error 1009149	"%2 Internal Inconsistency: %1 (%3,%4,%5)"
Constant	EMSG_INDEXCONTAINER_CORRUPT
SAP Sybase Error Number	20189
SQL State	QSB45
SQL Code	-1009149L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Container type
Parameter 3	Internal Error Code
Parameter 4	Internal Error Info 1
Parameter 5	Internal Error Info 2
Probable Cause	A corrupt index container was found. DBCC cannot repair the container. The database object using the container must be re-created.

Error 1009150	"Cannot delete/truncate CK %2 because of RI violation - FK has non-nulls. %1"
Constant	EMSG_RI_VIOLATION_FKNOTNULL
SAP Sybase Error Number	20190
SQL State	QSB46
SQL Code	-1009150L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception
Parameter 2	index name of candidate key
Probable Cause	No additional information available. Cannot truncate or delete all from candidate table if there exists any associated foreign key which has any all non-null data.

Error 1009151	"Cannot %2 CK %3 row %4 because of RI violation. %1"
Constant	EMSG_RI_VIOLATION_CK
SAP Sybase Error Number	20191
SQL State	QSB47
SQL Code	-1009151L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception
Parameter 2	operation: update or delete
Parameter 3	index name for CK
Parameter 4	row id that violated RI
Probable Cause	No additional information available. Cannot delete/update CK if there exists same value in associated FK. any associated foreign key which has any all non-null data.

Error 1009152	"Cannot %2 FK %3 row %4 because of RI violation. %1"
Constant	EMSG_RI_VIOLATION_FK
SAP Sybase Error Number	20192
SQL State	QSB48
SQL Code	-1009152L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception
Parameter 2	operation: update or insert/load
Parameter 3	role name for FK
Parameter 4	row id that violated RI
Probable Cause	No additional information available. Cannot insert/update FK if there does not exist same value in associated CK any associated foreign key which has any all non-null data.

Error 1009153	"Cannot remove row %3 from CK %2 during LOAD cleanup because of RI violation. %1"
Constant	EMSG_RI_VIOLATION_LOADCLEANUP
SAP Sybase Error Number	20193
SQL State	QSB49
SQL Code	-1009153L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception
Parameter 2	index name for CK
Parameter 3	row id that violated RI

Error 1009153	"Cannot remove row %3 from CK %2 during LOAD cleanup because of RI violation. %1"
Probable Cause	No additional information available. If removing self-referential CK during LOAD cleanup phase and there exists a FK of removed value, we roll back the whole operation.
Error 1009154	"Cannot alter dbspace when a backup is in progress"
Constant	EMSG_IQSTORE_CANNOT_ALTERDBSPACE
SAP Sybase Error Number	21118
SQL State	QSB50
SQL Code	-1009154L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	An alter dbspace operation was attempted while a backup was running. The alter dbspace operation cannot proceed since it may modify internal database structures that are being backed up.
Error 1009155	"Cannot perform requested command as there is an ALTER DBSPACE command in progress. %1"
Constant	EMSG_IQSTORE_INALTERDBSPACE
SAP Sybase Error Number	22000
SQL State	QSB55
SQL Code	-1009155L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	A CREATE DBSPACE or a DROP DBSPACE command was issued when there was already an ALTER DBSPACE command in progress.

Error 1009156	"Drop disallowed for dbspace %2. One or more of the file(s) are in use by the database. %1"
Constant	EMSG_SDBEXT_DROPSEGMENTINUSE
SAP Sybase Error Number	20194
SQL State	QSB51
SQL Code	-1009156L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Database segment.
Probable Cause	A segment must contain no user data and no database structures to drop

Error 1009157	"There is insufficient reserve space to add %3 blocks to segment %2. Only %4 blocks or less may be added. %1"
Constant	EMSG_SDBEXT_SEGMENTNORESERVE
SAP Sybase Error Number	20195
SQL State	QSB52
SQL Code	-1009157L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Database segment.
Parameter 3	Number of blocks user attempted to add
Parameter 4	Maximum blocks that may be added
Probable Cause	Since a segment must use a contiguous range of block numbers, it can only be resized larger when the blocks following it are not in use by the next segment.

Error 1009158	"Cannot resize segment %2 since the truncated region is in use. %1"
Constant	EMSG_SDBEXT_RESIZESEGMENTINUSE
SAP Sybase Error Number	20196
SQL State	QSB53
SQL Code	-1009158L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Database segment.
Probable Cause	A segment can only be resized smaller when no blocks in the truncated are in use.

Error 1009159	"The status specified for segment %2 is unchanged. %1"
Constant	EMSG_SDBEXT_SEGMENTSAMERWMODE
SAP Sybase Error Number	20197
SQL State	QSB54
SQL Code	-1009159L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Database segment.
Probable Cause	The "alter dbspace status" syntax requires the new status to be different than the original status.

Error 1009160	"There must be at least one readwrite dbspace (%2). %1"
Constant	EMSG_SDBEXT_MUST_HAVE_RW
SAP Sybase Error Number	20198

Error 1009160	"There must be at least one readwrite dbspace (%2). %1"
SQL State	QSB56
SQL Code	-1009160L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Database segment.
Probable Cause	There must at least one readwrite segment

Error 1009161	"Cannot resize segment %2 since it is readonly. %1"
Constant	EMSG_SDBEXT_RO_RESIZE
SAP Sybase Error Number	20199
SQL State	QSB57
SQL Code	-1009161L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Database segment.
Probable Cause	A readonly segment cannot be resized

Error 1009162	"Insufficient space to relocate structures on %2. %1"
Constant	EMSG_SDBEXT_NO_RELOCATE_SPACE
SAP Sybase Error Number	20200
SQL State	QSB58
SQL Code	-1009162L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1009162	"Insufficient space to relocate structures on %2. %1"
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	Database segment.
Probable Cause	Database structures may need to be relocated in order to drop a segment or make it readonly. This space must be available on other segments.

Error 1009163	"Segment %2 cannot be smaller than %3 blocks. %1"
Constant	EMSG_SDBEXT_SEGMENTTOOSMALL
SAP Sybase Error Number	20201
SQL State	QSB59
SQL Code	-1009163L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	Database segment.
Parameter 3	Minimum size in blocks
Probable Cause	Database structures may need to be relocated in order to drop a segment or make it readonly. This space must be available on other segments.

Error 1009164	"You cannot drop the last dbspace. %1"
Constant	EMSG_DATABASE_LASTDBSPACE
SAP Sybase Error Number	20202
SQL State	QSB60
SQL Code	-1009164L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1009164	"You cannot drop the last dbspace. %1"
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	You can drop the last dbspace only if it is a temp dbspace

Error 1009165	"Cannot perform requested command as the SYSIQFILE table is locked by another transaction. %1"
Constant	EMSG_IQSTORE_INREADSYSFILE
SAP Sybase Error Number	20203
SQL State	QSB61
SQL Code	-1009165L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	A CREATE DBSPACE, ALTER DBSPACE or DROP DBSPACE command was issued when there was another command or stored procedure accessing the system table SYSIQFILE.

Messages 1009166 through 1009185

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1009166	"%3 %4 is in use by dropped dbspace %2 on a secondary server. The drop dbspace command has not yet propagated through the multiplex. %1"
Constant	EMSG_SDBEXT_IN_USE_BY_QUERY_SERVER
SAP Sybase Error Number	20204
SQL State	QSB62
SQL Code	-1009166L
ODBC 2 State	ERROR

Error 1009166	"%3 %4 is in use by dropped dbspace %2 on a secondary server. The drop dbspace command has not yet propagated through the multiplex. %1"
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	DBSpace name
Parameter 3	Description of field in use (i.e. File, Name, File ID)
Parameter 4	Value of field in use
Probable Cause	Fields for dropped dbspaces cannot be re-used until the drop dbspace commands have propagated through the multiplex

Error 1009167	"dbspace %2 failed to open since it's definition conflicts with dbspace %3. Secondary server may need to be synchronized. %1"
Constant	EMSG_SDBEXT_DBSPACE_BLOCK_RANGE
SAP Sybase Error Number	20207
SQL State	QSB63
SQL Code	-1009167L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Name of DBSpace that was already open
Parameter 3	Name of DBSpace that failed to open
Probable Cause	The server has an invalid dbspace configuration. New dbspaces may fail to open or the server may fail to start until this is corrected.

Error 1009168	"The WORD SKIP limit (%2) has been exceeded. %1"
Constant	EMSG_SVIOLATION_WORDSKIP_LIMIT_EXCEEDED

Error 1009168	"The WORD SKIP limit (%2) has been exceeded. %1"
SAP Sybase Error Number	20208
SQL State	QSB64
SQL Code	-1009168L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	Location of the exception.
Parameter 2	The WORD SKIP limit specified in the LOAD TABLE statement.
Probable Cause	The number of words encountered that are longer than the limit specified when the word index was create has been exceeded for the load. The load will rollback.

Error 1009169	"Cannot write to RO DBSpace %2. %1"
Constant	EMSG_RODBSPACE_ILLEGAL_ACCESS
SAP Sybase Error Number	20222
SQL State	QSB65
SQL Code	-1009169L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	dbspace name
Probable Cause	No additional information available..

Error 1009170	"You have run out of space in %2 DBSpace. %1"
Constant	EMSG_OUT_OF_DBSPACE
SAP Sybase Error Number	20223
SQL State	QSB66

Error 1009170	"You have run out of space in %2 DBSpace. %1"
SQL Code	-1009170L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	name of dbspace
Probable Cause	No additional information available..

Error 1009171	"An IO error was encountered while writing a database page in %2 DBSpace. %1"
Constant	EMSG_BUFMAN_BIO_WRITE_ERROR
SAP Sybase Error Number	20224
SQL State	QSB67
SQL Code	-1009171L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	dbspace name
Probable Cause	No additional information available..

Error 1009172	"%2 is in use by another sp_iqemptyfile or ALTER DBSPACE command. %1"
Constant	EMSG_DBSPACE_FILE_IN_USE_BY_ALTER_OR_EMPTY
SAP Sybase Error Number	20226
SQL State	QSB68
SQL Code	-1009172L
ODBC 2 State	ERROR

Error 1009172	"%2 is in use by another sp_iqemptyfile or ALTER DBSPACE command. %1"
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Name of the FILE or DBSPACE locked.
Probable Cause	sp_iqemptyfile or ALTER DBSPACE commands disallow status change for the FILE(s) or DBSPACE. No other ALTER DBSPACE or sp_iqemptyfile command can run on those FILE(s) or DBSPACE.

Error 1009173	"Operation not permitted on an OFFLINE DBSpace %2. %1"
Constant	EMSG_OFFLINE_DBSPACE_ILLEGAL_ACCESS
SAP Sybase Error Number	20227
SQL State	QSB69
SQL Code	-1009173L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	dbspace name
Probable Cause	No additional information available..

Error 1009174	"Operation not yet supported. Sort metadata sources have incompatible record descriptors. %1"
Constant	EMSG_SORT_METADATADESC_MISMATCH
SAP Sybase Error Number	20228
SQL State	QSB70
SQL Code	-1009174L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1009174	"Operation not yet supported. Sort metadata sources have incompatible record descriptors. %1"
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available..

Error 1009175	"Database segment '%2' is not valid. Reserve Blocks found in the header: %3 Reserve Blocks expected: %4. This segment cannot be used. %1"
Constant	EMSG_SDBEXT_BAD_RESERVE
SAP Sybase Error Number	20229
SQL State	QSB71
SQL Code	-1009175L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	Location of the exception.
Parameter 2	Name of the segment.
Parameter 3	Reserve blocks found in the disk header.
Parameter 4	Reserve blocks expected.
Probable Cause	The start block of the disk segment that was found in the disk segment header is not the same as what was expected. The disk segment cannot be used. You will need to restore your database from backup.

Error 1009176	"Create temporary dbspace not allowed. %1"
Constant	EMSG_DBSPACE_TEMP_NOT_ALLOWED
SAP Sybase Error Number	20230
SQL State	QSB72
SQL Code	-1009176L

Error 1009176	"Create temporary dbspace not allowed. %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	Additional dbspaces may not be created in temp store. Temp space may only be added to IQ_SYSTEM_TEMP.

Error 1009177	"%2 is already %3. %1"
Constant	EMSG_DBSPACE_ATTRIB_UNCHANGED
SAP Sybase Error Number	20231
SQL State	QSB73
SQL Code	-1009177L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	dbspace name
Parameter 3	READONLY, READWRITE, ONLINE, OFFLINE
Probable Cause	The dbspace being altered already had the requested attributes

Error 1009178	"Operation not allowed on dbspaces that contain multiple files. %1"
Constant	EMSG_DBSPACE_NOT_FOR_MULTI_DBSPACE
SAP Sybase Error Number	20232
SQL State	QSB74
SQL Code	-1009178L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1009178	"Operation not allowed on dbspaces that contain multiple files. %1"
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Probable Cause	The specified operation cannot be applied to a file the contains multiple files

Error 1009179	"The last file in a dbspace may only be removed by DROP DBSPACE. %1"
Constant	EMSG_DBSPACE_CANT_DROP_LAST_FILE
SAP Sybase Error Number	20233
SQL State	QSB75
SQL Code	-1009179L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Probable Cause	A dbspace must contain at least one file. The last file can only be removed by dropping the dbspace that contains it.

Error 1009180	"%2 is not allowed on system dbspace %3. %1"
Constant	EMSG_DBSPACE_NOT_ALLOWED_SYSTEM
SAP Sybase Error Number	20234
SQL State	QSB76
SQL Code	-1009180L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	disallowed command

Error 1009180	"%2 is not allowed on system dbspace %3. %1"
Parameter 3	dbspace name
Probable Cause	The requested DDL operation is not allowed on system dbspaces

Error 1009181	"Multiple FILE clauses are not allowed for this command. %1"
Constant	EMSG_DBSPACE_SINGLE_FILE_CLAUSE
SAP Sybase Error Number	20235
SQL State	QSB77
SQL Code	-1009181L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	Some alter dbspace commands do not allow multiple files to be specified

Error 1009182	"DBFile name %2 is already in use. %1"
Constant	EMSG_DBSPACE_DBFILE_NAME_IN_USE
SAP Sybase Error Number	20236
SQL State	QSB78
SQL Code	-1009182L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	logical filename
Probable Cause	logical filenames must be unique for dbfiles

Error 1009183	"A readwrite dbspace may not be placed offline. %1"
Constant	EMSG_DBSPACE_NO_OFFLINE_RW_DBSPACE
SAP Sybase Error Number	20237
SQL State	QSB79
SQL Code	-1009183L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	A dbspace must be readonly before it can be placed offline

Error 1009184	"Operation not permitted on a READONLY DBSpace. %1"
Constant	EMSG_READONLY_DBSPACE_ILLEGAL_ACCESS
SAP Sybase Error Number	21190
SQL State	QSB80
SQL Code	-1009184L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available..

Error 1009185	"An IO error was encountered while writing a database page in %2 DBSpace. %1. File is readonly."
Constant	EMSG_READONLY_FILE_ILLEGAL_ACCESS
SAP Sybase Error Number	21191
SQL State	QSB81
SQL Code	-1009185L
ODBC 2 State	ERROR

Error 1009185	"An IO error was encountered while writing a database page in %2 DBSpace. %1. File is readonly."
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	dbspace name
Probable Cause	No additional information available..

Messages 1009186 through 1009420

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1009186	"Global Request for freelist failed. %1"
Constant	EMSG_GLOBAL_FL_REQUEST_FAILED
SAP Sybase Error Number	21200
SQL State	QSB82
SQL Code	-1009186L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	Global request for freelist failed.

Error 1009187	"Textindex External Error: Error Code: %2: Error Message: %3. %1"
Constant	EMSG_EXTLIB_ERROR
SAP Sybase Error Number	21205
SQL State	QSB83
SQL Code	-1009187L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1009187	"Textindex External Error: Error Code: %2: Error Message: %3. %1"
Severity Code	<i>14 on page 2</i>
Parameter 1	Error code set by the external library
Parameter 2	Error message from the external library
Parameter 3	location of the exception
Probable Cause	Error from external prefilter or term breaker library.

Error 1009188	"Create shared temporary dbspace not allowed. %1"
Constant	EMSG_DBSPACE_SHARED_TEMP_NOT_ALLOWED
SAP Sybase Error Number	22019
SQL State	QDD1A
SQL Code	-1009188L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Probable Cause	Additional dbspaces may not be created in shared temp store. Shared Temp space may only be added to IQ_SHARED_TEMP.

Error 1009189	"Text document exceeds maximum number of terms. Support up to 4294967295 terms per document. %1"
Constant	EMSG_MAXTERM_ERROR
SAP Sybase Error Number	21210
SQL State	QSB84
SQL Code	-1009189L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>

Error 1009189	"Text document exceeds maximum number of terms. Support up to 4294967295 terms per document. %1"
Parameter 1	location of the exception
Probable Cause	Error from external prefilter or term breaker library.
Error 1009190	"Incorrect %3 Index Version (%2): Index must be dropped and recreated. %1"
Constant	EMSG_TEXTVERSION_ERROR
SAP Sybase Error Number	21211
SQL State	QSB85
SQL Code	-1009190L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Incorrect version of index.
Parameter 3	index type.
Probable Cause	Error from text index.
Error 1009191	"The FORCE READWRITE clause is not allowed on this dbspace. It can be specified for the dbspace IQ_SHARED_TEMP only. %1"
Constant	EMSG_DBSPACE_FORCE_READWRITE_NOT_ALLOWED
SAP Sybase Error Number	22025
SQL State	QSB86
SQL Code	-1009191L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception

Error 1009191	"The FORCE READWRITE clause is not allowed on this dbspace. It can be specified for the dbspace IQ_SHARED_TEMP only. %1"
Probable Cause	The FORCE READWRITE clause can be used with IQ_SHARED_TEMP only.

Error 1009192	"File may not be accessible from one or more multiplex servers. Use sp_iqmpxfilestatus for further diagnosis. %1"
Constant	EMSG_DBSPACE_GLOBAL_FILE_STATUS_INVALID
SAP Sybase Error Number	22026
SQL State	QSB87
SQL Code	-1009192L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	The file must be accessible from all multiplex servers (except those that are excluded) before its mode can be changed to READWRITE. The global file status maintained at the coordinator indicates that file may not be accessible from one or more multiplex servers. Use sp_iqmpxfilestatus for further diagnosis.

Error 1009193	"Insufficient space to accommodate Freelist blocks. Please use a file with at least %2 MB space and turn that file READWRITE. %1"
Constant	EMSG_DBSPACE_INSUFFICIENT_SPACE_FOR_RW
SAP Sybase Error Number	22027
SQL State	QSB88
SQL Code	-1009193L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1009193	"Insufficient space to accommodate Freelist blocks. Please use a file with at least %2 MB space and turn that file READWRITE. %1"
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	Size of the file needed
Probable Cause	There is no READWRITE file in IQ_SHARED_TEMP dbspace at this point in time. While trying to turn the first file READWRITE, the file needs to have enough space to accommodate freelist blocks for all the existing files.

Error 1009194	"Please drop the rest of the files in this dbspace before trying to drop this file. \nThis was the first file to be made READWRITE and can only be dropped if it is the last remaining file. %1"
Constant	EMSG_DBSPACE_LAST_FILE_DROPPED
SAP Sybase Error Number	22028
SQL State	QSB89
SQL Code	-1009194L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Probable Cause	This was the first file to be made READWRITE in IQ_SHARED_TEMP dbspace This file should be the last file in IQ_SHARED_TEMP to be dropped. Please drop rest of the files before trying to drop this file.

Error 1009195	"Cannot open file %2, alter file ReadWrite operation failed. %1"
Constant	EMSG_SDBEXT_SHTEMP_RW_NOT_ALLOWED
SAP Sybase Error Number	22030
SQL State	QSB90

Error 1009195	"Cannot open file %2, alter file ReadWrite operation failed. %1"
SQL Code	-1009195L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	logical filename
Probable Cause	Secondary node cannot make a file in IQ_SHARED_TEMP dbspace READWRITE if it is not accessible.

Error 1009196	"%2: Cannot convert blockmap; bmp={%3}. %1"
Constant	EMSG_BLOCKMAP_CONVERSION_FAILED
SAP Sybase Error Number	22033
SQL State	QSB91
SQL Code	-1009196L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	1) location of the exception
Parameter 2	2) The particular buffer cache throwing the exception.
Parameter 3	3) Information about the blockmap
Probable Cause	Blockmap conversion failed. Blockmap remains unconverted and in read only mode.

Error 1009412	"The INSERT ... LOCATION statement must use a SELECT statement. %1"
Constant	EMSG_SQL_INS_LOC_SEL
SAP Sybase Error Number	21050
SQL State	QCB10

Error 1009412	"The INSERT ... LOCATION statement must use a SELECT statement. %1"
SQL Code	-1009412L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	The INSERT ... LOCATION statement must use a SELECT statement. No other SQL statement is supported here.

Error 1009413	"Secondary server cannot maintain catalog sync. %1"
Constant	EMSG_CAT_MPX_REPLAY_FAIL
SAP Sybase Error Number	21051
SQL State	QCB11
SQL Code	-1009413L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Probable Cause	An error has occurred while applying catalog updates from the coordinator. The secondary server must be restarted or synchronized.

Error 1009414	"Secondary server cannot recover catalog during post-synchronization. %1"
Constant	EMSG_CAT_MPX_POSTSYNC_FAIL
SAP Sybase Error Number	21052
SQL State	QCB12
SQL Code	-1009414L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1009414	"Secondary server cannot recover catalog during post-synchronization. %1"
Severity Code	23 on page 2
Parameter 1	location of the exception
Probable Cause	An error has occurred while reconstituting catalog entries for the IQ Local store. Manual repair is required.

Error 1009415	"CREATE TABLE cannot use IN clause for IQ Local store. %1"
Constant	EMSG_CAT_MPX_NO_LOCAL_INCLAUSE
SAP Sybase Error Number	21053
SQL State	QCB13
SQL Code	-1009415L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	You may not specify the IN clause to create tables in IQ Local store. Without an IN clause, the secondary server create tables in Local store by default.

Error 1009416	"Option '%2' not allowed on a partitioned table. %1"
Constant	EMSG_UNSUPPORTED_PARTITIONED_TABLE_LOAD_OPTION
SAP Sybase Error Number	21054
SQL State	QCB14
SQL Code	-1009416L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2

Error 1009416	"Option '%2' not allowed on a partitioned table. %1"
Parameter 1	location of the exception
Parameter 2	option name
Probable Cause	Certain 'load table' options are not supported on a partitioned table.

Error 1009417	"Updating partition key column on a partitioned table is not allowed. %1"
Constant	EMSG_CANNOT_UPDATE_PARTITION_COLUMN
SAP Sybase Error Number	21055
SQL State	QCB15
SQL Code	-1009417L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	A partition key column cannot be updated.

Error 1009418	"Operation not allowed - partition key column %2 not specified. %1"
Constant	EMSG_PARTITIONING_COLUMN_OMITTED
SAP Sybase Error Number	21056
SQL State	QCB16
SQL Code	-1009418L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	column name
Probable Cause	A partial width insert on a partitioned table is not permitted when at least one of the table's partition key columns is omitted.

Error 1009419	"The width of one or more columns are too large to fit into database's page."
Constant	EMSG_PAGESIZE_TOO_SMALL_FOR_QCP
SAP Sybase Error Number	21159
SQL State	QCB19
SQL Code	-1009419L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	The LOAD Engine cannot fit a column into the page.

Error 1009420	"Value of row's partition-key columns do not fit into any of the table's partitions."
Constant	EMSG_VALUE_DOES_NOT_FIT
SAP Sybase Error Number	21160
SQL State	QCB20
SQL Code	-1009420L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	The value for the partition key columns for a specific row do not fit within any of the table's partitions.

Messages 1010000 through 1010019

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1010000	"The file '%2' already exists. %1"
Constant	EMSG_DATABASE_FILEALREADYEXISTS
SAP Sybase Error Number	20014
SQL State	QXA00

Error 1010000	"The file '%2' already exists. %1"
SQL Code	-1010000L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	dbspace name
Probable Cause	The named dbspace already exists (and it is a raw partition). To proceed, you must first remove it by hand.

Error 1010001	"Cannot use raw partition for dbspace file '%2'. %1"
Constant	EMSG_DATABASE_FILEISRAW
SAP Sybase Error Number	20015
SQL State	QXA01
SQL Code	-1010001L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	dbspace name
Probable Cause	The named dbspace cannot exist on a raw partition.

Error 1010002	"File format mismatch; database %2; Sybase IQ: %3. %1"
Constant	EMSG_DATABASE_FILEFORMAT
SAP Sybase Error Number	20016
SQL State	QXA02
SQL Code	-1010002L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1010002	"File format mismatch; database %2; Sybase IQ: %3. %1"
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	file format of database as found in SYSIQINFO
Parameter 3	file format as known by IQ DLL
Probable Cause	The file format of the database doesn't match the file format as expected by the IQ DLL. The IQ DLL and the database each have a format version. They must match.

Error 1010003	"Catalog format mismatch: database %2; Sybase IQ: %3. %1"
Constant	EMSG_DATABASE_CATALOGFORMAT
SAP Sybase Error Number	20017
SQL State	QXA03
SQL Code	-1010003L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	catalog format of database as found in SYSIQINFO
Parameter 3	catalog format as known by IQ DLL
Probable Cause	The catalog format of the database doesn't match the catalog format as expected by the IQ DLL. The IQ DLL and the ASA catalog each have a format version. They must match.

Error 1010004	"Stored procedure format mismatch: database %2; Sybase IQ: %3. %1"
Constant	EMSG_DATABASE_SPFORMAT
SAP Sybase Error Number	20018
SQL State	QXA04
SQL Code	-1010004L

Error 1010004	"Stored procedure format mismatch: database %2; Sybase IQ: %3. %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	stored procedure of database as found in SYSIQINFO
Parameter 3	stored procedure format as known by IQ DLL
Probable Cause	The stored procedure format of the database doesn't match the stored procedure format as expected by the IQ DLL. The IQ DLL and the database each contain a stored procedure format version. They must match.

Error 1010005	"File format date mismatch: database %2; Sybase IQ: %3. %1"
Constant	EMSG_DATABASE_TIMESTAMP
SAP Sybase Error Number	20019
SQL State	QXA05
SQL Code	-1010005L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	file format date of database as found in SYSIQINFO
Parameter 3	file format as known by IQ DLL
Probable Cause	The file format date of the database doesn't match the file format date as expected by the IQ DLL.

Error 1010006	"Maximum blocks for dbspace '%2' is %3 blocks. %4 blocks were specified. (Database blocksize is %5.) %1"
Constant	EMSG_DATABASE_BLOCKRANGE

Error 1010006	"Maximum blocks for dbspace '%2' is %3 blocks. %4 blocks were specified. (Database blocksize is %5.) %1"
SAP Sybase Error Number	20020
SQL State	QXA06
SQL Code	-1010006L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	dbspace name
Parameter 3	maximum number of blocks for a dbspace given the database's blocksize
Parameter 4	maximum blocks the user specified
Parameter 5	The blocksize of the database.
Probable Cause	Given a database's BLOCK SIZE and the number of blocks specified by the user for the dbspace, the dbspace size (in bytes) would exceed the OS's limit of bytes per file.

Error 1010007	"The number of blocks (%3) for dbspace '%2' must be less than or equal to the number of blocks in the raw partition (%4). %1"
Constant	EMSG_DATABASE_INVALIDNBLOCKS
SAP Sybase Error Number	20980
SQL State	QXA07
SQL Code	-1010007L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	dbspace name

Error 1010007	"The number of blocks (%3) for dbspace '%2' must be less than or equal to the number of blocks in the raw partition (%4). %1"
Parameter 3	user's number of blocks in dbspace
Parameter 4	number of blocks in raw partition
Probable Cause	When creating a dbspace on a raw partition, if the user specifies the dbspace's size, then it must exactly match the size of the raw partition.

Error 1010008	"For an IQ PAGE SIZE of %2, the dbspace '%3' must have at least %4 MB. %1"
Constant	EMSG_DATABASE_DBNBLOCKS
SAP Sybase Error Number	20981
SQL State	QXA08
SQL Code	-1010008L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	page size
Parameter 3	dbspace name
Parameter 4	required minimum size in mega-bytes
Probable Cause	The named dbspace must have the stated minimum size in megabytes.

Error 1010009	"Improper use of cursor - programmer error %1"
Constant	EMSG_CURSOR_PROG_ERROR
SAP Sybase Error Number	21005
SQL State	QXA09
SQL Code	-1010009L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1010009	"Improper use of cursor - programmer error %1"
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	The programmer has misused the internal cursor class(es)

Error 1010010	"An invalid attribute flag was passed to the cursor"
Constant	EMSG_CURSOR_INVALID_ATTRIBUTE
SAP Sybase Error Number	21006
SQL State	QXA10
SQL Code	-1010010L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Probable Cause	A state violation was detected in the cursor

Error 1010011	"Not enough server threads available for this query."
Constant	EMSG_CURSOR_NO_THREADS
SAP Sybase Error Number	21007
SQL State	QXA11
SQL Code	-1010011L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Probable Cause	No thread could be allocated to allow this query to be executed

Error 1010012	"The cursor is in an invalid state %1"
Constant	EMSG_CURSOR_INVALID_STATE
SAP Sybase Error Number	21008
SQL State	QXA12

Error 1010012	"The cursor is in an invalid state %1"
SQL Code	-1010012L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	A state violation was detected in the cursor

Warning 1010013	"IQ cannot support the %1 connections requested by the server.\nRestart the server with -gm %2 on the command line."
Constant	EMSG_CONN_INFO
SAP Sybase Error Number	21024
SQL State	00A13
SQL Code	1010013L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	the number of connections
Parameter 2	the number of supported connections
Probable Cause	Inform the DBA about the number of connection

Error 1010013	"Raw partition %2 is already in use. %1"
Constant	EMSG_RAW_PARTITION_INUSE
SAP Sybase Error Number	21025
SQL State	QXA13
SQL Code	-1010013L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1010013	"Raw partition %2 is already in use. %1"
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	name of the raw partition
Probable Cause	User attempted to create dbspace on a raw partition which is currently in use by the database.

Warning 1010014	"Default cache size is used for command %1."
Constant	EMSG_DEFAULTCACHESIZEUSED
SAP Sybase Error Number	21058
SQL State	QXA14
SQL Code	1010014L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10</i> on page 2
Parameter 1	command type
Probable Cause	warning is issued for the command that uses the default cache size

Error 1010015	"The MAIN store is out of space. Space must be added to the MAIN store first. %1"
Constant	EMSG_DATABASE_MSNOSPACE
SAP Sybase Error Number	21075
SQL State	QXA15
SQL Code	-1010015L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	Location of the exception.
Probable Cause	The MAIN store is out of space. Space must be added to the MAIN store before space can be added to any other store.

Error 1010016	"The TEMPORARY store is out of space. Space must be added to the TEMPORARY store first. %1"
Constant	EMSG_DATABASE_TSNOSPACE
SAP Sybase Error Number	21076
SQL State	QXA16
SQL Code	-1010016L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Probable Cause	The TEMPORARY store is out of space. Space must be added to the TEMPORARY store before space can be added to any other store.

Error 1010017	"You cannot create tables on a secondary server without a readwrite local IQ Store. %1"
Constant	EMSG_DATABASE_MPX_NOLOCAL
SAP Sybase Error Number	21111
SQL State	QXA17
SQL Code	-1010017L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Probable Cause	MPX secondary servers can only create IQ objects in a local store.

Error 1010019	"Cannot modify object %2 on dbspace %3. %1"
Constant	EMSG_DATABASE_MPX_NOROMAIN
SAP Sybase Error Number	21113
SQL State	QXA19
SQL Code	-1010019L

Error 1010019	"Cannot modify object %2 on dbspace %3. %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	Location of the exception.
Parameter 2	object name
Parameter 3	dbspace name
Probable Cause	A generic error indicating error in modifying an object.

Messages 1010020 through 1010040

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1010020	"Backup not allowed on secondary servers. %1"
Constant	EMSG_DATABASE_MPX_NOLOCALFORBU
SAP Sybase Error Number	21114
SQL State	QXA20
SQL Code	-1010020L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	Location of the exception.
Probable Cause	The backup command is not allowed to be executed on a secondary server. Execute the command on the coordinator.

Error 1010021	"Foreign key constraint on a local table cannot reference a shared table. %1"
Constant	EMSG_DATABASE_MPX_NOXKEYS
SAP Sybase Error Number	21115
SQL State	QXA21
SQL Code	-1010021L

Error 1010021	"Foreign key constraint on a local table cannot reference a shared table. %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Probable Cause	Cannot combine main and local tables in a foreign key relationship.

Error 1010022	"Cannot modify main store from a multiplex query server. %1"
Constant	EMSG_DATABASE_MPX_NOMAINRWACCESS
SAP Sybase Error Number	21117
SQL State	QXA22
SQL Code	-1010022L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Probable Cause	The general error when a query server tries to modify the shared main store. There are other more detailed messages for specific cases.

Error 1010023	"Cursor is not updatable: %2. %1"
Constant	EMSG_CURSOR_NOT_UPDATABLE
SAP Sybase Error Number	21121
SQL State	QXA23
SQL Code	-1010023L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of exception.

Error 1010023	"Cursor is not updatable: %2. %1"
Parameter 2	Reason why the cursor is not updatable.
Probable Cause	Cursor is not updatable: there are join/group by/distinct/set, union, olap function, or no updatable columns.

Error 1010024	"Column '%2' is not updatable. %1"
Constant	EMSG_COLUMN_NOT_UPDATABLE
SAP Sybase Error Number	21122
SQL State	QXA24
SQL Code	-1010024L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of exception.
Parameter 2	Column name.
Probable Cause	Column is not updatable if it is long binary/varchar, rowid, (var)binary when ASE_Binary_Display is ON, referenced by other expressions in the select list, identity column, or not in FOR UPDATE of list.

Error 1010025	"Cannot restore to multiplex secondary server. %1"
Constant	EMSG_DATABASE_MPX_NOLOCALFORRESTORE
SAP Sybase Error Number	21125
SQL State	QXA25
SQL Code	-1010025L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Probable Cause	Multiplex secondary server cannot be restored. Only the coordinator can be restored.

Error 1010026	"Only a server in single_node mode can become a coordinator %1"
Constant	EMSG_DATABASE_MPX_CANTBECOMEWRITER
SAP Sybase Error Number	21126
SQL State	QXA26
SQL Code	-1010026L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Probable Cause	Must be in simplex mode to convert to coordinator mode.
Error 1010027	"Only a server in coordinator mode can become a single_node server %1"
Constant	EMSG_DATABASE_MPX_CANTBECOMESPX
SAP Sybase Error Number	21127
SQL State	QXA27
SQL Code	-1010027L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Probable Cause	Must be in coordinator mode to convert to simplex.
Error 1010028	"A secondary server may not drop or alter a domain owned by the coordinator. %1"
Constant	EMSG_DATABASE_MPX_QNODEDOESNOTOWNDOMAIN
SAP Sybase Error Number	21128
SQL State	QXA28
SQL Code	-1010028L

Error 1010028	"A secondary server may not drop or alter a domain owned by the coordinator. %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	Location of the exception.
Probable Cause	Cannot drop a domain on a secondary server unless the secondary server owns the domain.

Error 1010030	"Wrong multiplex mode for this restore. %1"
Constant	EMSG_DATABASE_MPX_WRONGMODEFORRESTORE
SAP Sybase Error Number	21130
SQL State	QXA30
SQL Code	-1010030L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	Location of the exception.
Probable Cause	The mpx mode does not match the restore type.

Error 1010031	"Cannot modify object %2 on dbspace %3. A query server may not modify objects in the main IQ store. %1"
Constant	EMSG_DATABASE_MPX_QUERY_NOWRITE
SAP Sybase Error Number	21131
SQL State	QXA31
SQL Code	-1010031L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	Location of the exception.

Error 1010031	"Cannot modify object %2 on dbspace %3. A query server may not modify objects in the main IQ store. %1"
Parameter 2	object name
Parameter 3	dbspace name
Probable Cause	A query server may not modify objects in the main store.

Error 1010032	"Bad Database Identity block. %1"
Constant	EMSG_DATABASE_MPX_BADDBID
SAP Sybase Error Number	21132
SQL State	QXA32
SQL Code	-1010032L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Probable Cause	The secondary server has too many or too few shared main dbspaces defined.

Error 1010033	"This secondary server was not shut down cleanly before synchronize. Must start with -iqfrec %1"
Constant	EMSG_DATABASE_MPX_READERNOTSHUTDOWNCLEANLY
SAP Sybase Error Number	21133
SQL State	QXA33
SQL Code	-1010033L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Probable Cause	Must start with iqfrec to rebuild freelist.

Error 1010034	"Modifications of the iq main store not allowed in readonly mode. %1"
Constant	EMSG_DATABASE_MPX_NOWRITEIFREADONLY
SAP Sybase Error Number	21134
SQL State	QXA34
SQL Code	-1010034L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Probable Cause	The mpx mode does not match the restore type.
Error 1010035	"The transaction log does not match the mpx mode of this server. %1"
Constant	EMSG_DATABASE_MPX_LOGDBMODEMISMATCH
SAP Sybase Error Number	21135
SQL State	QXA35
SQL Code	-1010035L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Probable Cause	The mpx mode does not match the transaction log.
Error 1010036	"MPX: invalid file_id. Single_node or coordinator using a local or bad fileID. %1"
Constant	EMSG_DATABASE_MPX_BADFILEID
SAP Sybase Error Number	21136
SQL State	QXA36
SQL Code	-1010036L

Error 1010036	"MPX: invalid file_id. Single_node or coordinator using a local or bad fileID. %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	Location of the exception.
Probable Cause	The fileid is not valid for this mpx mode.

Error 1010037	"MPX: invalid local file_id. Secondary server using a bad local fileID. %1"
Constant	EMSG_DATABASE_MPX_BADLOCALFILEID
SAP Sybase Error Number	21137
SQL State	QXA37
SQL Code	-1010037L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	Location of the exception.
Probable Cause	The local fileid is not valid for this mpx mode.

Error 1010038	"MPX: Local stores are not supported. %1"
Constant	EMSG_DATABASE_MPX_NOLOCALFILEID
SAP Sybase Error Number	21138
SQL State	QXA38
SQL Code	-1010038L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	Location of the exception.

Error 1010038	"MPX: Local stores are not supported. %1"
Probable Cause	The local fileid is not valid for this mpx mode.

Error 1010039	"MPX: Inconsistent Transaction Manager Data. %1"
Constant	EMSG_DATABASE_MPX_TXNMGRCHECK
SAP Sybase Error Number	21139
SQL State	QXA39
SQL Code	-1010039L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Probable Cause	The local fileid is not valid for this mpx mode.

Error 1010040	"Cannot restore to multiplex secondary server without a local store. %1"
Constant	EMSG_DATABASE_UNDEFINEDUTILITYCMD
SAP Sybase Error Number	21140
SQL State	QXA40
SQL Code	-1010040L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Probable Cause	A secondary server must have local store dbspaces defined in order to do a restore.

Messages 1010041 through 1010060

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1010041	"Inconsistent data during OpenDatabase. %1"
Constant	EMSG_DATABASE_OPENDBCHECK
SAP Sybase Error Number	21141
SQL State	QXA41
SQL Code	-1010041L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Probable Cause	Open database check failure.

Error 1010042	"\"drop leaks\" is not allowed without executing post-sync secondary server replay. %1"
Constant	EMSG_DBCC_DROPLEAKS_NEED_LOCAL_REPLAY
SAP Sybase Error Number	21142
SQL State	QDB73
SQL Code	-1010042L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Probable Cause	Disallow DBCC to drop leaked blocks on a MPX secondary server without executing post-sync local TLV replay.

Error 1010043	"dbspace %2 is currently not open. %1"
Constant	EMSG_DATABASE_DBSPACE_NOT_OPENED

Error 1010043	"dbspace %2 is currently not open. %1"
SAP Sybase Error Number	21144
SQL State	QXA42
SQL Code	-1010043L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Name of dbpace
Parameter 2	Location of the exception.
Probable Cause	The specified dbspace exists but is not currently open.

Error 1010044	"Plan not available."
Constant	EMSG_QPTCACHE_NOPLAN
SAP Sybase Error Number	21146
SQL State	QXA43
SQL Code	-1010044L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	"User request for the plan and there is no plan in the cache to be returned. cases when this error will be returned :1. User makes a connection and executes select graphical_plan() or select html_plan(). 2. When the the SQL function graphical_plan and html_plan is used to get the plan for an IQ query for which IQ does not generate plan. "

Error 1010045	"Plan not available. Plan type is not supported for Sybase IQ queries."
Constant	EMSG_QPTCACHE_INVALID_PLANTYPE
SAP Sybase Error Number	21147
SQL State	QXA44

Error 1010045	"Plan not available. Plan type is not supported for Sybase IQ queries."
SQL Code	-1010045L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	"IQ supports only graphical_plan and html_plan SQL functions. Other SA plan functions (plan, explanation etc.) are not supported for Sybase IQ."

Error 1010046	"Plan not available. The database option QUERY_PLAN_TEXT_ACCESS is off."
Constant	EMSG_QPTCACHE_ACCESS_NOT_ALLOWED
SAP Sybase Error Number	21148
SQL State	QXA45
SQL Code	-1010046L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	"The plan can be accessed on the client by the user only when DBA sets option QUERY_PLAN_TEXT_ACCESS to ON for the user."

Error 1010047	"%1 is not designated as failover server"
Constant	EMSG_IQMPX_NOT_FAILOVER
SAP Sybase Error Number	21176
SQL State	QXA46
SQL Code	-1010047L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2

Error 1010047	"%1 is not designated as failover server"
Parameter 1	server name
Probable Cause	Failover process is started on a server which is not designated as failover server

Error 1010048	"iqmpx_failover and iqmpx_sn switches cannot be enabled simultaneously"
Constant	EMSG_IQMPX_CANNOT_MIX_FAILOVER_SN
SAP Sybase Error Number	21177
SQL State	QXA47
SQL Code	-1010048L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	While starting an IQ server, both iqmpx_failover and iqmpx_sn command line server switches are ON.

Error 1010049	"Transaction log recovery not allowed during failover. Please restart the server without the failover switch, do a clean shutdown, restart failover"
Constant	EMSG_IQMPX_NO_RECOVERY_IN_FAILOVER
SAP Sybase Error Number	21178
SQL State	QXA48
SQL Code	-1010049L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	The failover process should be started only after clean shutdown of the server. If recovery process is initiated during failover then the server was not shut down cleanly and failover should be restarted after the server is restarted and shut down without the failover switch.

Error 1010050	"Recovery required to complete the last failover process. Please restart the server with failover switch"
Constant	EMSG_IQMPX_START_IN_FAILOVER
SAP Sybase Error Number	21179
SQL State	QXA49
SQL Code	-1010050L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	A previous failover attempt did not finish cleanly. The failover changes must be recovered and to do that restart the server with failover switch.

Error 1010051	"Failover node catalog is not in sync with TLV log. Please restart server without failover switch, run BEGIN TRANSACTION, do a clean shutdown, then restart failover "
Constant	EMSG_IQMPX_FAILOVER_CAT_OUT_OF_SYNC
SAP Sybase Error Number	21180
SQL State	QXA50
SQL Code	-1010051L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	The failover process can be started only if the failover node's catalog is up to date with the TLV log. To fix this, restart the server without the failover switch, run BEGIN TRANSACTION, do a clean shutdown, then restart the server with the failover switch.

Error 1010052	"Only one dbspace file may be added at a time for multiplex servers"
Constant	EMSG_IQMPX_ALTERADD_MULTIPLE_FILES

Error 1010052	"Only one dbspace file may be added at a time for multiplex servers"
SAP Sybase Error Number	21183
SQL State	QXA51
SQL Code	-1010052L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	When using ALTER DBSPACE to add a file to a multiplex server, only one file may be added at a time. Specifying a list of files to add is not supported.

Error 1010053	"DBSPACE command extended syntax not permitted"
Constant	EMSG_DBSPACE_EXTENDED_SYNTAX
SAP Sybase Error Number	21184
SQL State	QXA52
SQL Code	-1010053L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	When using ALTER DBSPACE command, extended syntax is not allowed on a user connection

Error 1010054	"Server option '-iqmpx_ov' only valid when used with '-iqmpx_sn' or '-iqmpx_failover'. %1"
Constant	EMSG_MPX_OV_INVALID_USE
SAP Sybase Error Number	21186
SQL State	QXA53
SQL Code	-1010054L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1010054	"Server option '-iqmpx_ov' only valid when used with '-iqmpx_sn' or '-iqmpx_failover'. %1"
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Probable Cause	Server option '-iqmpx_ov' is permitted on an Multiplex coordinator node or in combination with either '-iqmpx_sn' or '-iqmpx_failover' on any other Multiplex node type.

Error 1010055	"iqmpx_reclaimwriterfreelist server switch can not be used in Simplex or Secondary nodes"
Constant	EMSG_MPX_SWITCH_INVALID_FOR_SPX_OR_SECONDARY
SAP Sybase Error Number	21187
SQL State	QXA54
SQL Code	-1010055L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	iqmpx_reclaimwriterfreelist server switch can only be used on a Coordinator node.

Error 1010056	"Recovery switch '-iqfrec' is allowed on a multiplex server only in single-node operating mode. %1"
Constant	EMSG_MPX_FREQ_INVALID_USE
SAP Sybase Error Number	21188
SQL State	QXA55
SQL Code	-1010056L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception

Error 1010056	"Recovery switch '-iqfrec' is allowed on a multiplex server only in single-node operating mode. %1"
Probable Cause	Recovery switch '-iqfrec' is allowed on a multiplex server only in single-node operating mode.
Error 1010057	""%2' command is not allowed on temp store files, when server started with -iqnotemp switch. %1"
Constant	EMSG_ILLEGAL_ALTER_DBSPACE_NOTEMP
SAP Sybase Error Number	21201
SQL State	QXA56
SQL Code	-1010057L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	alter dbspace command type string
Probable Cause	When the server is running with -iqnotemp switch, certain alter dbspace operations are not allowed. For e.g. alter dbspace add file.
Error 1010058	"Unable to perform forced recovery when database is in read only mode. %1"
Constant	EMSG_FREQ_IN_READ_ONLY
SAP Sybase Error Number	21202
SQL State	QXA57
SQL Code	-1010058L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	Recovery switch '-iqfrec' is allowed on read/write databases only

Error 1010059	"Unable to open the multiplex database. The database can only be opened by starting the Coordinator server using single node mode switch '-iqmpx_sn 1'. %1"
Constant	EMSG_MPX_OPEN_OLDDB_NEED_SINGLE
SAP Sybase Error Number	22023
SQL State	QXA58
SQL Code	-1010059L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	An older version of multiplex database can only be opened by starting the server in single node mode. If you get this error after upgrading the database when the server was started using '-iqro 1', then the database still needs to be opened by starting the coordinator server in single node mode but without '-iqro 1'. This is because the internal IQ on-disk structures could not be upgraded earlier. To complete the upgrade, open the database by starting the coordinator server using single node mode switch '-iqmpx_sn 1', but without '-iqro 1'. After a clean shutdown, the database can then be started normally.

Error 1010060	"Server option -iqmpx_nowr only allowed when there are no writers in multiplex %1"
Constant	EMSG_MPX_NOWR_INVALID_USE
SAP Sybase Error Number	21212
SQL State	QXA60
SQL Code	-1010060L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception

Error 1010060	"Server option -iqmpx_nowr only allowed when there are no writers in multiplex %1"
Probable Cause	Please restart coordinator without -iqmpx_nowr switch to add a writer

Messages 1010061 through 1012005

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1010061	"Server switch -iqmpx_nowr only allowed on coordinator node %1"
Constant	EMSG_MPX_NOWR_INVALID_USE_NOTCNODE
SAP Sybase Error Number	21213
SQL State	QXA61
SQL Code	-1010061L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Probable Cause	Please restart the server without -iqmpx_nowr switch

Error 1010062	"Unable to open the database. Start the coordinator server first, without server option -iqro, to complete the Database Upgrade. %1"
Constant	EMSG_MPX_START_COORD_FIRST
SAP Sybase Error Number	22029
SQL State	QXA62
SQL Code	-1010062L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2

Error 1010062	"Unable to open the database. Start the coordinator server first, without server option -iqro, to complete the Database Upgrade. %1"
Parameter 1	location of the exception
Probable Cause	As IQ store was opened in RO mode when you upgraded the database, some of its internal meta-data information could not be upgraded to new format. Please start the coordinator server first, without server option -iqro, to complete the IQ side upgrade and continue.

Error 1011000	"Vertical Projection Cursor state error %1"
Constant	EMSG_CURSORSTATEERROR
SAP Sybase Error Number	20000
SQL State	QVA00
SQL Code	-1011000L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1011001	"Cannot find index for a given dfe %1"
Constant	EMSG_INDEXNOTFOUND
SAP Sybase Error Number	20001
SQL State	QVA01
SQL Code	-1011001L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	18 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1011002	"The number of existing indexes exceeds the current maximum number of indexes. %1"
Constant	EMSG_EXCEEDEDMAXINDEXES
SAP Sybase Error Number	20002
SQL State	QVA02
SQL Code	-1011002L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.
Error 1011003	"Vertical Projection Cursor does not support AD-HOC joins. %1"
Constant	EMSG_ADHOCJOINREQUIRED
SAP Sybase Error Number	20003
SQL State	QVA03
SQL Code	-1011003L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.
Error 1011004	"Cannot drop primary key or unique constraint because a foreign key still references it."
Constant	EMSG_FKEY_STILL_EXISTS_TO_CKEY
SAP Sybase Error Number	20004
SQL State	QNA27

Error 1011004	"Cannot drop primary key or unique constraint because a foreign key still references it."
SQL Code	-1011004L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	A primary key or unique constraint involved in a referential integrity relationship cannot be dropped until its corresponding foreign key is first dropped.

Error 1011006	"the pattern argument in a like predicate must have string datatype."
Constant	EMSG_INVALIDDATATYPE
SAP Sybase Error Number	20006
SQL State	QVA06
SQL Code	-1011006L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1011007	"the escape argument in a like predicate must be a one byte character."
Constant	EMSG_INVALIDESCAPE
SAP Sybase Error Number	20007
SQL State	QVA07
SQL Code	-1011007L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1011009	"Group (L)"
Constant	EMSG_VPGP_GB_COL_LFS
SAP Sybase Error Number	20009
SQL State	QVA09
SQL Code	-1011009L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1011010	"Group (S)"
Constant	EMSG_VPGP_GB_COL_SFS
SAP Sybase Error Number	20010
SQL State	QVA10
SQL Code	-1011010L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1011011	"Aggregate (L)"
Constant	EMSG_VPGP_AGG_LFS
SAP Sybase Error Number	20011
SQL State	QVA11
SQL Code	-1011011L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1011012	"Aggregate (S)"
Constant	EMSG_VPGP_AGG_SFS
SAP Sybase Error Number	20012
SQL State	QVA12
SQL Code	-1011012L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1011013	"Projection"
Constant	EMSG_VPGP_PROJ
SAP Sybase Error Number	20013
SQL State	QVA13
SQL Code	-1011013L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1012000	"You cannot do a partial restore for database '%2' because it has been updated (%3) since its last backup (%4). %1"
Constant	EMSG_RESTORE_MORE_RECENT_UPDATETIME
SAP Sybase Error Number	20923
SQL State	QUA00
SQL Code	-1012000L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2

Error 1012000	"You cannot do a partial restore for database '%2' because it has been updated (%3) since its last backup (%4). %1"
Parameter 1	location of the exception
Parameter 2	database
Parameter 3	last update
Parameter 4	last backup
Probable Cause	No additional information available.

Error 1012001	"There is already a backup or selective restore in progress. %1"
Constant	EMSG_BACKUP_MULTIPLE_IN_PROGRESS
SAP Sybase Error Number	20924
SQL State	QUA01
SQL Code	-1012001L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1012002	"Unable to write to archive. ('%2') %1"
Constant	EMSG_BACKUP_DEVICE_WRITEERROR
SAP Sybase Error Number	20925
SQL State	QUA02
SQL Code	-1012002L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception

Error 1012002	"Unable to write to archive. ('%2') %1"
Parameter 2	explanation for %2
Probable Cause	No additional information available.

Error 1012003	"You must do a full backup before doing an incremental backup. %1"
Constant	EMSG_BACKUP_NEED_FULL_FIRST
SAP Sybase Error Number	20926
SQL State	QUA03
SQL Code	-1012003L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1012004	"You cannot do incremental backups with this release. %1"
Constant	EMSG_BACKUP_INC_NOT_IMPLEMENTED
SAP Sybase Error Number	20927
SQL State	QUA04
SQL Code	-1012004L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1012005	"Server is reporting no files in the database. %1"
Constant	EMSG_BACKUP_SA_NUMFILES_ZERO
SAP Sybase Error Number	20928

Error 1012005	"Server is reporting no files in the database. %1"
SQL State	QUA05
SQL Code	-1012005L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Messages 1012006 through 1012025

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1012006	"Server reports '%2' files in IQ store, IQ reports '%3'. %1"
Constant	EMSG_BACKUP_SA_IQ_NUMFILES_DISAGREE
SAP Sybase Error Number	20929
SQL State	QUA06
SQL Code	-1012006L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for %2
Parameter 3	explanation for %3
Probable Cause	No additional information available.

Error 1012007	"IQ unable to find all files to back up. %1"
Constant	EMSG_BACKUP_NO_FILES
SAP Sybase Error Number	20930
SQL State	QUA07

Error 1012007	"IQ unable to find all files to back up. %1"
SQL Code	-1012007L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1012008	"Database has changed since last restore. %1"
Constant	EMSG_RESTORE_DBCHANGED
SAP Sybase Error Number	20931
SQL State	QUA08
SQL Code	-1012008L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1012009	"This restore cannot immediately follow the previous restore. %1"
Constant	EMSG_RESTORE_BAD_PREVRESTORE
SAP Sybase Error Number	20932
SQL State	QUA09
SQL Code	-1012009L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception

Error 1012009	"This restore cannot immediately follow the previous restore. %1"
Probable Cause	No additional information available.

Error 1012010	"Unable to read from archive ("%2"). %1"
Constant	EMSG_RESTORE_READ_IOERROR
SAP Sybase Error Number	20933
SQL State	QUA10
SQL Code	-1012010L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for %2
Probable Cause	No additional information available.

Error 1012011	"Header of block to be restored appears to be corrupted. %1"
Constant	EMSG_RESTORE_BAD_BLOCK_HEADER
SAP Sybase Error Number	20934
SQL State	QUA11
SQL Code	-1012011L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1012012	"Media data appears corrupted (bad checksum). %1"
Constant	EMSG_RESTORE_BAD_CRC

Error 1012012	"Media data appears corrupted (bad checksum). %1"
SAP Sybase Error Number	20935
SQL State	QUA12
SQL Code	-1012012L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1012013	"Media meta data appears corrupted (boundary record). %1"
Constant	EMSG_RESTORE_BAD_BOUNDARY_RECORD
SAP Sybase Error Number	20936
SQL State	QUA13
SQL Code	-1012013L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1012014	"Media meta data appear corrupted (multiple begin boundary records). %1"
Constant	EMSG_RESTORE_MULTIPLE_BEGIN_BOUNDARY_RECORDS
SAP Sybase Error Number	20937
SQL State	QUA14
SQL Code	-1012014L
ODBC 2 State	ERROR

Error 1012014	"Media meta data appear corrupted (multiple begin boundary records). %1"
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1012015	"Media meta data appears corrupted (missing begin boundary record). %1"
Constant	EMSG_RESTORE_MISSING_BEGIN_BOUNDARY_RECORD
SAP Sybase Error Number	20938
SQL State	QUA15
SQL Code	-1012015L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1012016	"Restoring database '%2' has failed because not all media required for restoring '%3' were supplied. %1"
Constant	EMSG_RESTORE_INCOMPLETE
SAP Sybase Error Number	20939
SQL State	QUA16
SQL Code	-1012016L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for %2

Error 1012016	"Restoring database '%2' has failed because not all media required for restoring '%3' were supplied. %1"
Parameter 3	explanation for %3
Probable Cause	No additional information available.

Error 1012017	"An I/O write error has occurred on '%2'. The restore query has failed. %1"
Constant	EMSG_RESTORE_WRITE_IOERROR
SAP Sybase Error Number	20940
SQL State	QUA17
SQL Code	-1012017L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for %2
Probable Cause	No additional information available.

Error 1012018	"An I/O read error has occurred on '%2'. The backup query has failed. %1"
Constant	EMSG_BACKUP_READ_IOERROR
SAP Sybase Error Number	20941
SQL State	QUA18
SQL Code	-1012018L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for %2
Probable Cause	No additional information available.

Error 1012019	".db or .log file does not exist. Incremental restore not possible. %1"
Constant	EMSG_RESTORE_SADB_FILE_DOES_NOT_EXIST
SAP Sybase Error Number	20942
SQL State	QUA19
SQL Code	-1012019L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1012020	"Wrong IQ backup tape or file. %1"
Constant	EMSG_RESTORE_WRONG_ARCHIVE
SAP Sybase Error Number	20943
SQL State	QUA20
SQL Code	-1012020L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1012021	"Backup Internal Error. %1"
Constant	EMSG_BACKUP_INTERNAL_ERROR
SAP Sybase Error Number	20944
SQL State	QUA21
SQL Code	-1012021L
ODBC 2 State	ERROR

Error 1012021	"Backup Internal Error. %1"
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1012022	"Restore Internal Error. %1"
Constant	EMSG_RESTORE_INTERNAL_ERROR
SAP Sybase Error Number	20945
SQL State	QUA22
SQL Code	-1012022L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1012023	"Not an IQ backup tape or file. %1"
Constant	EMSG_RESTORE_NOT_IQ_ARCHIVE
SAP Sybase Error Number	20946
SQL State	QUA23
SQL Code	-1012023L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1012024	"Ran out of threads. Start up server with more threads. %1"
Constant	EMSG_RESTORE_OUT_OF_THREADS
SAP Sybase Error Number	20947
SQL State	QUA24
SQL Code	-1012024L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1012025	".db or .log file exists. Full restore will not be done. %1"
Constant	EMSG_RESTORE_SADB_FILE_EXISTS
SAP Sybase Error Number	20948
SQL State	QUA25
SQL Code	-1012025L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Probable Cause	No additional information available.

Messages 1012026 through 1012045

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Warning 1012026	"Number of IQ blocks backed up: %1"
Constant	EMSG_BACKUP_BLOCK_COUNT
SAP Sybase Error Number	20949

Warning 1012026	"Number of IQ blocks backed up: %1"
SQL State	QUA26
SQL Code	1012026L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>1</i> on page 2
Parameter 1	number of blocks
Probable Cause	No additional information available.

Warning 1012027	"Total number of IQ blocks backed Up: %1\n at %2\n\tIQ Blocksize %3\n\tbackup Blocksize %4\n\tblocking factor %5\n\tbuffer size %6"
Constant	EMSG_BACKUP_STATS
SAP Sybase Error Number	20950
SQL State	QUA27
SQL Code	1012027L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>1</i> on page 2
Parameter 1	number of blocks
Parameter 2	time of backup
Parameter 3	IQ Blocksize
Parameter 4	Backup BlockSize
Parameter 5	Blocking Factor
Parameter 6	BufferSize
Probable Cause	No additional information available.

Warning 1012028	"Total number of IQ blocks to be backed up: %1"
Constant	EMSG_TOTAL_BACKUP_BLOCK_COUNT

Warning 1012028	"Total number of IQ blocks to be backed up: %1"
SAP Sybase Error Number	20951
SQL State	QUA28
SQL Code	1012028L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>1</i> on page 2
Parameter 1	number of blocks
Probable Cause	No additional information available.

Error 1012029	"Incremental backups disabled, perhaps due to forced recovery. To enable,\n do a full backup"
Constant	EMSG_BACKUP_INCS_DISABLED
SAP Sybase Error Number	20952
SQL State	QUA29
SQL Code	-1012029L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Probable Cause	No additional information available.

Error 1012030	"for long binary/varchar Column '%2', database page size of (%3) must be greater than %4. %1"
Constant	EMSG_CAT_PAGESIZETOOSMALL
SAP Sybase Error Number	20953
SQL State	QUA30
SQL Code	-1012030L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1012030	"for long binary/varchar Column '%2', database page size of (%3) must be greater than %4. %1"
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	column number
Parameter 3	requested page size
Parameter 4	minimum allowed page size
Probable Cause	The database page size requested by the user for a long binary column is too small.

Error 1012031	"A readonly dbspace does not match this backup. Found: AlterID %2 startBlock %3 numBlocks %4 fileID %5 %1"
Constant	EMSG_RESTORE_BAD_RO_FILE
SAP Sybase Error Number	20954
SQL State	QUA31
SQL Code	-1012031L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	alterID found in the RO dbspace header
Parameter 3	startBlock found in the RO dbspace header
Parameter 4	number of blocks found in the RO dbspace header
Parameter 5	fileID found in the RO dbspace header
Probable Cause	There is a readonly dbspace that does not match the RO dbspaces that existed at the time of the backup.

Error 1012032	"You may either do selective backup of readonly dbspaces or readonly dbfiles with backup type 'full' alone, or do an all-inclusive backup"
Constant	EMSG_BACKUP_RO_WITH_FULL_ALONE

Error 1012032	"You may either do selective backup of readonly dbspaces or readonly dbfiles with backup type 'full' alone, or do an all-inclusive backup"
SAP Sybase Error Number	20955
SQL State	QUA32
SQL Code	-1012032L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	No additional information available.

Error 1012033	"IQ store dbfile %2 must be either readonly or belong to an RO dbspace. %1"
Constant	EMSG_BACKUP_RO_ILLEGAL
SAP Sybase Error Number	20956
SQL State	QUA33
SQL Code	-1012033L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	dbfile to backup
Probable Cause	Dbfile or the dbspace specified in RO selective backup found to be RW

Error 1012034	"IQ store dbspace or dbfile %2 is unavailable. Backup will not be done. %1"
Constant	EMSG_BACKUP_DBSPACE_OFFLINE
SAP Sybase Error Number	20957
SQL State	QUA34
SQL Code	-1012034L

Error 1012034	"IQ store dbspace or dbfile %2 is unavailable. Backup will not be done. %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	dbspace to backup
Probable Cause	dbspace to backup must be online, both in catalog and dynamically

Error 1012035	"You may either do selective restore of readonly dbspaces or readonly dbfiles from a 'full' backup archive, or restore from an all-inclusive backup."
Constant	EMSG_RESTORE_RO_WITH_FULL_ALONE
SAP Sybase Error Number	20958
SQL State	QUA35
SQL Code	-1012035L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	No additional information available.

Error 1012036	"IQ unable to find any file to restore. %1"
Constant	EMSG_RESTORE_NO_FILES
SAP Sybase Error Number	20959
SQL State	QUA36
SQL Code	-1012036L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>

Error 1012036	"IQ unable to find any file to restore. %1"
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1012037	"IQ store dbfile %2 exists. Restore will not be done. %1"
Constant	EMSG_RESTORE_IQDB_FILE_EXISTS
SAP Sybase Error Number	20960
SQL State	QUA37
SQL Code	-1012037L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	dbfile to restore
Probable Cause	File must not exist when restoring from a full backup, unless restore is RO selective or restoring from virtual backup, or the file was created after the dependent backup when restoring from inc backup.

Error 1012038	"IQ store dbfile %2 does not exist. Restore will not be done. %1"
Constant	EMSG_RESTORE_IQDB_FILE_DOES_NOT_EXIST
SAP Sybase Error Number	20961
SQL State	QUA38
SQL Code	-1012038L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	dbfile to restore

Error 1012038	"IQ store dbfile %2 does not exist. Restore will not be done. %1"
Probable Cause	File must exist when restoring from inc backup, unless it was created after the dependant backup, or when restoring from virtual backup.

Error 1012039	"The maximum number of backup devices allowed is %2. %1"
Constant	EMSG_BACKUP_MAX_DEVICES_EXCEEDED
SAP Sybase Error Number	20962
SQL State	QUA39
SQL Code	-1012039L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	the maximum number of backup devices permitted.
Probable Cause	A database can be backed up to a maximum of the stated number of devices.

Error 1012040	"IQ store dbspace %2 is online. Restore will not be done. %1"
Constant	EMSG_RESTORE_DBSPACE_ONLINE
SAP Sybase Error Number	20963
SQL State	QUA40
SQL Code	-1012040L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	dbspace to restore
Probable Cause	dbspace to restore must be offline, both in catalog and dynamically

Error 1012041	"The backup no longer matches the version of the dbspace/dbfile in the database and, therefore, cannot be restored. %1"
Constant	EMSG_RESTORE_VERSIONCHANGED
SAP Sybase Error Number	20964
SQL State	QUA41
SQL Code	-1012041L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Warning 1012042	"(%1) Please mount archive media on '%2'."
Constant	EMSG_RESTORE_MOUNT_NONMASTERMEDIA
SAP Sybase Error Number	20965
SQL State	01A42
SQL Code	1012042L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	explanation of %1
Parameter 2	explanation of %2
Probable Cause	No additional information available.

Warning 1012043	"(%1) Please mount IQ MASTER archive media for database '%2' on '%3'."
Constant	EMSG_RESTORE_MOUNT_MASTERMEDIA
SAP Sybase Error Number	20966
SQL State	01A43

Warning 1012043	"(%1) Please mount IQ MASTER archive media for database '%2' on '%3'."
SQL Code	1012043L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10</i> on page 2
Parameter 1	explanation of %1
Parameter 2	explanation of %2
Parameter 3	explanation of %3
Probable Cause	No additional information available.

Warning 1012044	"(%1) Please mount Backup Server archive media for database '%2' on '%3'."
Constant	EMSG_RESTORE_MOUNT_BACKUPSERVERMEDIA
SAP Sybase Error Number	20967
SQL State	01A44
SQL Code	1012044L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10</i> on page 2
Parameter 1	explanation of %1
Parameter 2	explanation of %2
Parameter 3	explanation of %3
Probable Cause	No additional information available.

Warning 1012045	"(%1) Please mount archive media on '%2'."
Constant	EMSG_BACKUP_MOUNT_NONMASTERMEDIA
SAP Sybase Error Number	20968
SQL State	01A45

Warning 1012045	"(%1) Please mount archive media on '%2'."
SQL Code	1012045L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	explanation of %1
Parameter 2	explanation of %2
Probable Cause	No additional information available.

Messages 1012046 through 1013018

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Warning 1012046	"(%1) Please mount archive media on '%2'. It will be the IQ MASTER archive for database '%3'."
Constant	EMSG_BACKUP_MOUNT_MASTERMEDIA
SAP Sybase Error Number	20969
SQL State	01A46
SQL Code	1012046L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	explanation of %1
Parameter 2	explanation of %2
Parameter 3	explanation of %3
Probable Cause	No additional information available.

Warning 1012047	"(%1) Please mount archive media on '%2'. It will be the Backup Server archive for database '%3'."
Constant	EMSG_BACKUP_MOUNT_BACKUPSERVERMEDIA
SAP Sybase Error Number	20970

Warning 1012047	"(%1) Please mount archive media on '%2'. It will be the Backup Server archive for database '%3'."
SQL State	01A47
SQL Code	1012047L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	explanation of %1
Parameter 2	explanation of %2
Parameter 3	explanation of %3
Probable Cause	No additional information available.

Warning 1012048	"(%1) Archive media mounted on '%2'."
Constant	EMSG_BACKUP_ARCHIVEMEDIA_MOUNTED
SAP Sybase Error Number	20971
SQL State	01U48
SQL Code	1012048L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	explanation of %1
Parameter 2	explanation of %2
Probable Cause	No additional information available.

Warning 1012049	"(%1) Done with archive media on '%2'."
Constant	EMSG_BACKUP_ARCHIVEMEDIA_CLOSED
SAP Sybase Error Number	20972
SQL State	01U49
SQL Code	1012049L

Warning 1012049	"(%1) Done with archive media on '%2'."
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	explanation of %1
Parameter 2	explanation of %2
Probable Cause	No additional information available.

Error 1012050	"Bad opcode detected during restore. Expected opcode is '%2', but '%3' was seen. %1"
Constant	EMSG_HEADER_BADOPCODE
SAP Sybase Error Number	20974
SQL State	QUA50
SQL Code	-1012050L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	explanation of %2
Parameter 3	explanation of %3
Probable Cause	This is an internal error. If this error occurs it should be reported to Sybase.

Error 1012051	"An invalid database segment number (%2, %3) has been detected. %1"
Constant	EMSG_HEADER_BAD_SEGMENTNUMBER
SAP Sybase Error Number	20975
SQL State	QUA51
SQL Code	-1012051L
ODBC 2 State	ERROR

Error 1012051	"An invalid database segment number (%2, %3) has been detected. %1"
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	explanation of %2
Parameter 3	explanation of %3
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1012052	"Programming error: looking for hole '%2', but only have '%3'. %1"
Constant	EMSG_HEADER_HOLE_ERROR
SAP Sybase Error Number	20976
SQL State	QUA52
SQL Code	-1012052L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	explanation of %2
Parameter 3	explanation of %3
Probable Cause	This is an internal error. If this error occurs it should be reported to Sybase.

Error 1012053	"Fatal internal error: looking for segment containing hole {%2,%3}, but none was found. %1"
Constant	EMSG_HEADER_HOLE_LOOKUP_ERROR
SAP Sybase Error Number	20977
SQL State	QUA53
SQL Code	-1012053L

Error 1012053	"Fatal internal error: looking for segment containing hole {%2,%3}, but none was found. %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	explanation of %2
Parameter 3	explanation of %3
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1012054	"Fatal internal error: looking for segment containing block '%2', but none was found. %1"
Constant	EMSG_BACKUP_SEGMENT_NUMBER_ERROR
SAP Sybase Error Number	20978
SQL State	QUA54
SQL Code	-1012054L
ODBC 2 State	ERRORi
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	explanation of %2
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1012055	"RESTORE VERIFY has found errors with the archive. %1"
Constant	EMSG_RESTORE_VERIFY_FAILED_WITH_ERRORS
SAP Sybase Error Number	21207
SQL State	QUA55
SQL Code	-1012055L

Error 1012055	"RESTORE VERIFY has found errors with the archive. %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	The verification of the provided archive has failed. Please check the server log for details of errors which were thrown during the verification process.

Warning 1012056	"Total number of IQ blocks verified: %1/%2 (%3%%)"
Constant	EMSG_RESTORE_VERIFY_PROGRESS
SAP Sybase Error Number	21208
SQL State	QUA56
SQL Code	1012056L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	1 on page 2
Parameter 1	Parameter 1 description
Parameter 2	Parameter 2 description
Parameter 3	Parameter 3 description
Probable Cause	This is an informational message displayed in context with other messages.

Error 1012057	"Command specified for virtual backup failed. %1"
Constant	EMSG_BACKUP_VIRTUAL_CMD_FAILED
SAP Sybase Error Number	21209
SQL State	QUA57
SQL Code	-1012057L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1012057	"Command specified for virtual backup failed. %1"
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	No additional information available.

Error 1012058	"IQ cache dbspace %2 is readonly. Backup will not be done. %1"
Constant	EMSG_BACKUP_DBSPACE_READONLY
SAP Sybase Error Number	22167
SQL State	QUA42
SQL Code	-1012058L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	dbspace to backup
Probable Cause	cache dbspace to backup must be readwrite.

Warning 1013000	*** BlockSize: %2, Block size: Record size: %1"
Constant	EMSG_ISQL_RECORDBLOCKING
SAP Sybase Error Number	20570
SQL State	00A00
SQL Code	1013000L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>1</i> on page 2
Parameter 1	record size
Parameter 2	block size
Probable Cause	No additional information available.

Warning 1013001	**** Record size: variable, Block size: %1"
Constant	EMSG_ISQL_RECORDBLOCKSIZE
SAP Sybase Error Number	20571
SQL State	00A01
SQL Code	1013001L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	1 on page 2
Parameter 1	block size
Probable Cause	No additional information available.

Warning 1013015	"Row Delimiter: %1"
Constant	EMSG_ISQL_PREVIEWROWD
SAP Sybase Error Number	20585
SQL State	00A15
SQL Code	1013015L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	1 on page 2
Parameter 1	row delimiter
Probable Cause	This is the ROW DELIMITER used for the LOAD.

Error 1013015	"Multi-column indexes that are non unique or of more than 5300 bytes in total width are not supported. %1"
Constant	EMSG_SQL_MULTICOLWIDTH
SAP Sybase Error Number	20584
SQL State	QCA15
SQL Code	-1013015L

Error 1013015	"Multi-column indexes that are non unique or of more than 5300 bytes in total width are not supported. %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Probable Cause	Multicolumn indexes that are non unique or of more than 1024 bytes in total width are not supported. The total width is obtained by summing the individual widths of the various columns involved in the multicolumn index.

Error 1013016	"FILLER"
Constant	EMSG_ISQL_FILLERNAME
SAP Sybase Error Number	20586
SQL State	QCA16
SQL Code	-1013016L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Probable Cause	No additional information available.

Error 1013017	"An internal error occurred while calling a method on a db_sql_*_identifier. Object does not have an IIndex Handle. %1"
Constant	EMSG_SQL_NOINDEX
SAP Sybase Error Number	20587
SQL State	QCA17
SQL Code	-1013017L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>23 on page 2</i>

Error 1013017	"An internal error occurred while calling a method on a db_sql_*_identifier. Object does not have an IIndex Handle. %1"
Parameter 1	location of the exception
Probable Cause	This error should not occur during normal operation. It is an internal error. If this error occurs, it should be reported to Sybase.

Error 1013018	"An internal error occurred while calling a method on db_sql_*_identifier. Object does not have an IColumn Handle. %1"
Constant	EMSG_SQL_NOCOLUMN
SAP Sybase Error Number	20588
SQL State	QCA18
SQL Code	-1013018L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Probable Cause	This error should not occur during normal operation. It is an internal error. If this error occurs, it should be reported to Sybase.

1013019 - 1013136

Messages 1013019 through 1013040

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1013019	"CHECK constraint has unsupported component %2. %1"
Constant	EMSG_SQL_IQ_UNSUPPORTED_CONSTRAINT
SAP Sybase Error Number	20589
SQL State	QCA19
SQL Code	-1013019L

Error 1013019	"CHECK constraint has unsupported component %2. %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	details of the constraint
Probable Cause	the CHECK constraints contains either a subquery, a aggregate function, a user defined function, or other components that are not supported by IQ. CHECK constraints are not supported by Sybase IQ.

Error 1013020	"User defined default values are not supported. %1"
Constant	EMSG_SQL_NODEFAULT
SAP Sybase Error Number	20590
SQL State	QCA20
SQL Code	-1013020L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	User defined default values are not supported by Sybase IQ.

Error 1013021	"Multi-column indexes of the specified type are not supported. %1"
Constant	EMSG_SQL_NOCLUSTEREDINDEX
SAP Sybase Error Number	20591
SQL State	QCA21
SQL Code	-1013021L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2

Error 1013021	"Multi-column indexes of the specified type are not supported. %1"
Parameter 1	location of the exception
Probable Cause	Multi-column indexes of the user specified type are not supported by Sybase IQ.

Error 1013022	"Cannot create a duplicate '%2' index '%3'. %1"
Constant	EMSG_SQL_INDEXFOUND
SAP Sybase Error Number	20592
SQL State	QCA22
SQL Code	-1013022L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	indextype
Parameter 3	indexname
Probable Cause	Cannot create duplicate indexes of the same type on a set of columns.

Error 1013023	"Cannot create a unique '%2' index. %1"
Constant	EMSG_SQL_INDEXNOUNIQUE
SAP Sybase Error Number	20593
SQL State	QCA23
SQL Code	-1013023L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Parameter 2	column name

Error 1013023	"Cannot create a unique '%2' index. %1"
Probable Cause	Fast Projection, Low Disk, and High Non Group index types cannot be created as unique.
Error 1013024	"ALTER TABLE MODIFY <column> <datatype> is not supported. %1"
Constant	EMSG_SQL_NOSUPPMODDTYPE
SAP Sybase Error Number	20594
SQL State	QCA24
SQL Code	-1013024L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	Cannot modify the datatype of a column.
Error 1013025	"ALTER TABLE MODIFY <default-value> is not supported. %1"
Constant	EMSG_SQL_NOSUPPMODDEF
SAP Sybase Error Number	20595
SQL State	QCA25
SQL Code	-1013025L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	Cannot modify the default value of a column as defaults are not supported.

Error 1013027	"Number of bytes (%2) for a column from an input file has exceeded the maximum allowed (%3). %1"
Constant	EMSG_DB_RECSCANNER_E_EXCEEDMAX
SAP Sybase Error Number	20597
SQL State	QCA27
SQL Code	-1013027L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	# of bytes.
Parameter 3	maximum number of bytes allowed.
Probable Cause	The number of bytes you are trying to load into a column from an input file has exceeded the maximum number of bytes allowed.

Error 1013028	"An invalid size (too large) was specified for a LOAD option. %1"
Constant	EMSG_SQL_INVALIDSIZE
SAP Sybase Error Number	20598
SQL State	QCA28
SQL Code	-1013028L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Probable Cause	A size too large was specified for a LOAD option. Check the options specified for the LOAD statement.

Error 1013029	"The INSERT...LOCATION statement must have a SELECT statement. %1"
Constant	EMSG_SQL_INS_LOC_SELECT

Error 1013029	"The INSERT...LOCATION statement must have a SELECT statement. %1"
SAP Sybase Error Number	20599
SQL State	QCA29
SQL Code	-1013029L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	The INSERT...LOCATION statement must use a SELECT statement to provide the data for insertion. No other SQL statement type is supported here.

Error 1013031	"An error occurred while calling a method on db_sql_*_identifier. Object does not have an ITable handle. %1"
Constant	EMSG_SQL_NOTABLE
SAP Sybase Error Number	20601
SQL State	QCA31
SQL Code	-1013031L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Probable Cause	This error should not occur during normal operation. It is an internal error. If this error occurs, it should be reported to Sybase.

Error 1013032	"No database is currently in use. %1"
Constant	EMSG_SQL_NODATABASE
SAP Sybase Error Number	20602
SQL State	QCA32

Error 1013032	"No database is currently in use. %1"
SQL Code	-1013032L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1013033	"An error occurred while calling a method on db_sql_*_identifier. Object does not have an IJoinIndex handle. %1"
Constant	EMSG_SQL_NOJOININDEX
SAP Sybase Error Number	20603
SQL State	QCA33
SQL Code	-1013033L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Probable Cause	This is an internal error. If this error occurs, it should be reported to Sybase.

Error 1013034	"Cannot create an index with no columns. %1"
Constant	EMSG_SQL_INDEXNOFIELDS
SAP Sybase Error Number	20604
SQL State	QCA34
SQL Code	-1013034L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1013034	"Cannot create an index with no columns. %1"
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Probable Cause	You cannot create an index with no columns.

Error 1013035	"The number of insert VALUES does not match the column list. %1"
Constant	EMSG_SQL_INSERTNOVALUE
SAP Sybase Error Number	20605
SQL State	QCA35
SQL Code	-1013035L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Probable Cause	The number of columns in the INSERT does not match the number of of VALUES provided.

Error 1013036	"The keyword 'FILLER' is not valid in this context. %1"
Constant	EMSG_SQL_NOFILLER
SAP Sybase Error Number	20606
SQL State	QCA36
SQL Code	-1013036L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14 on page 2</i>
Parameter 1	location of the exception
Probable Cause	You cannot use the 'FILLER' keyword here. No column can be of type 'FILLER' for a VALUES insert.

Error 1013037	"The datatype of column '%2' is not valid. %1"
Constant	EMSG_SQL_DATATYPENOTVALIDFOROP
SAP Sybase Error Number	20607
SQL State	QCA37
SQL Code	-1013037L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	column
Probable Cause	The named column has an invalid datatype. If subsequent examination of the column definition reveals a datatype that is valid, then this error should be reported to Sybase.

Error 1013038	"The number of columns given does not match. %1"
Constant	EMSG_SQL_INSERTNUMBERFIELDS
SAP Sybase Error Number	20608
SQL State	QCA38
SQL Code	-1013038L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	The number of columns to be inserted does not match the number of columns in the insert. If this error persists, it should be reported to Sybase.

Error 1013039	"An internal error occurred while constructing a db_sql_*_identifier. The IColumn handle does not belong to the ITable. %1"
Constant	EMSG_SQL_COLUMNMISMATCH

Error 1013039	"An internal error occurred while constructing a db_sql_*_identifier. The IColumn handle does not belong to the ITable. %1"
SAP Sybase Error Number	20609
SQL State	QCA39
SQL Code	-1013039L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Probable Cause	This error should not occur during normal operation. It is an internal error. If this error occurs, it should be reported to Sybase.

Error 1013040	"Column '%2' in the INSERT list has no matching column in the SELECT list. %1"
Constant	EMSG_SQL_INSERTNOMATCHILIST
SAP Sybase Error Number	20610
SQL State	QCA40
SQL Code	-1013040L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	column
Probable Cause	The named column in the INSERT list does not have a matching column in the SELECT list.

Messages 1013041 through 1013062

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1013041	"Column '%2' in the SELECT list has no matching column in the INSERT list. %1"
Constant	EMSG_SQL_INSERTNOMATCHCLIST
SAP Sybase Error Number	20611
SQL State	QCA41
SQL Code	-1013041L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	column
Probable Cause	The named column in the SELECT list does not have a matching column in the INSERT list.

Error 1013042	"An internal error occurred while constructing a db_sql_*_identifier. The lIndex handle does not belong to the lTable. %1"
Constant	EMSG_SQL_INDEXMISMATCH
SAP Sybase Error Number	20612
SQL State	QCA42
SQL Code	-1013042L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Probable Cause	This error should not occur during normal operation. It is an internal error. If this error occurs it should be reported to Sybase.

Error 1013043	"Unable to convert column '%2' to the requested datatype (%3) from datatype (%4). %1"
Constant	EMSG_SQL_INVALIDCONVERSION
SAP Sybase Error Number	20613
SQL State	QCA43
SQL Code	-1013043L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	column
Parameter 3	requested datatype
Parameter 4	current datatype
Probable Cause	This column cannot be converted to the requested datatype.

Error 1013044	"An internal error occurred. An invalid table type was encountered. %1"
Constant	EMSG_SQL_INVALID_TBL_TYPE
SAP Sybase Error Number	20614
SQL State	QCA44
SQL Code	-1013044L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Probable Cause	This is an internal programming error. The table type was not correctly set to BASE, VIEW, JVT, TMP, LOCAL TMP for its context. If this error occurs it should be reported to Sybase.

Error 1013045	"An invalid file name ('%2') was specified for a LOAD TABLE. The file name has zero length. %1"
Constant	EMSG_SQL_INVALIDFILENAME
SAP Sybase Error Number	20615
SQL State	QCA45
SQL Code	-1013045L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	file name
Probable Cause	A file name of zero length was specified for LOAD TABLE.

Error 1013046	"An internal error occurred. An invalid index type was encountered. %1"
Constant	EMSG_SQL_INVALIDINDEXTYPE
SAP Sybase Error Number	20616
SQL State	QCA46
SQL Code	-1013046L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Probable Cause	This error should not occur during normal operation. It is an internal error and should be reported to Sybase.

Error 1013047	"Cannot alter index '%2'. Only indexes in base tables or global temporary tables can be altered. %1"
Constant	EMSG_SQL_CANNOT_ALTER_INDEX
SAP Sybase Error Number	20617

Error 1013047	"Cannot alter index '%2'. Only indexes in base tables or global temporary tables can be altered. %1"
SQL State	QCA47
SQL Code	-1013047L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Parameter 2	Indexname.
Probable Cause	Only indexes in base tables and global temporary tables listed in SYS.SYSINDEX can be altered.

Warning 1013048	"Warning: Partial input record (%1 bytes) skipped at EOF (O/S %2). %3 rows read."
Constant	EMSG_SQL_INSERTPARTIALRECORD
SAP Sybase Error Number	20618
SQL State	01A48
SQL Code	1013048L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	number of bytes at end of file that were skipped
Parameter 2	operating system error
Parameter 3	number of rows read from the input file
Probable Cause	An incomplete input record was found at the end of the flat file. If the operating system error returned is not zero, you may need to take action as dictated by the error and try the LOAD again.

Warning 1013049	"***** Possible Tape/File Error *****\n\n Bytes Read: %1, O/S errno: %2\n %3 rows read. Input suspended."
Constant	EMSG_SQL_INSERTTAPEERROR

Warning 1013049	***** Possible Tape/File Error *****\n\n Bytes Read: %1, O/S errno: %2\n %3 rows read. Input suspended."
SAP Sybase Error Number	20619
SQL State	01A49
SQL Code	1013049L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	number of bytes read
Parameter 2	operating system error number
Parameter 3	number of rows read
Probable Cause	Take action as dictated by the operating system error and retry the operation.

Error 1013050	"The Temp_Extract_Name1 option is set. The current operation will be rolled back. %1"
Constant	EMSG_SQL_OP_PROHIBITED
SAP Sybase Error Number	20620
SQL State	QCA50
SQL Code	-1013050L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Probable Cause	Certain operations will not be allowed whenever the Temp_Extract_Name1 option is set. They are: INSERT...VALUES, LOAD, DELETE, and INSERT...LOCATION if the table being inserted, SYNCHRONIZE join index. (Which also may be executed as part of CREATE JOIN INDEX.) loaded or deleted from is the top table in a join. INSERT...SELECT. For example, 'insert t1 select * from t2'.

Error 1013052	"The BLOCK FACTOR for LOAD cannot be zero. %1"
Constant	EMSG_SQL_BLOCKFACTOR_IS_ZERO
SAP Sybase Error Number	20622
SQL State	QCA52
SQL Code	-1013052L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	The BLOCK FACTOR for LOAD cannot be zero.

Error 1013054	"Delimiter '%2' must be 1 to %3 characters in length. %1"
Constant	EMSG_SQL_INVALIDDELIMITERSIZE
SAP Sybase Error Number	20624
SQL State	QCA54
SQL Code	-1013054L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	delimiter
Parameter 3	maximum allowable length of column delimiter or row terminator
Probable Cause	The row or column delimiter in a LOAD statement must be 1-4 characters.

Error 1013055	"ON_ERROR = 'CONTINUE' is valid only for a full-width INSERT. %1"
Constant	EMSG_SQL_INVALIDCONTINUE
SAP Sybase Error Number	20625

Error 1013055	"ON_ERROR = 'CONTINUE' is valid only for a full-width INSERT. %1"
SQL State	QCA55
SQL Code	-1013055L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	ON_ERROR = 'CONTINUE' is valid only for a full width insert.

Error 1013056	"FILLER width must be greater than zero. %1"
Constant	EMSG_SQL_INVALIDFILLERWIDTH
SAP Sybase Error Number	20626
SQL State	QCA56
SQL Code	-1013056L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	FILLER width must be greater than zero.

Error 1013057	"ASCII input column width must be greater than zero. %1"
Constant	EMSG_SQL_INVALIDASCIIWIDTH
SAP Sybase Error Number	20627
SQL State	QCA57
SQL Code	-1013057L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2

Error 1013057	"ASCII input column width must be greater than zero. %1"
Parameter 1	location of the exception
Probable Cause	ASCII input column width must be greater than zero.

Error 1013058	"The row delimiter must be distinct from all column delimiters. %1"
Constant	EMSG_SQL_IDENTICALDELIMITERANDROWTERMINATOR
SAP Sybase Error Number	20628
SQL State	QCA58
SQL Code	-1013058L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	The row delimiter cannot be the same as any column delimiter.

Error 1013059	"The BLOCK SIZE option is not valid for a fixed-width input insert. %1"
Constant	EMSG_SQL_INVALIDBLOCKSIZEOPTION
SAP Sybase Error Number	20629
SQL State	QCA59
SQL Code	-1013059L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	You cannot specify BLOCK SIZE for a fixed-width input insert.

Error 1013060	"The BLOCK FACTOR option is not valid for a variable width input insert. %1"
Constant	EMSG_SQL_INVALIDBLOCKFACTOROPTION
SAP Sybase Error Number	20630
SQL State	QCA60
SQL Code	-1013060L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	You cannot specify BLOCK FACTOR for a variable width input insert.

Error 1013061	"Missing row delimiter detected during a row delimited insert. %1"
Constant	EMSG_SQL_MISSINGROWTERMINATOR
SAP Sybase Error Number	20631
SQL State	QCA61
SQL Code	-1013061L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	The input data is missing a row delimiter.

Error 1013062	"Expected '%2' delimited column type on input, but encountered a row delimiter instead. Probable cause is a mismatch between the specified column delimiter and the column delimiter used in the input file. %1"
Constant	EMSG_SQL_EXPECTEDFIELDTYPENOTSEEN

Error 1013062	"Expected '%2' delimited column type on input, but encountered a row delimiter instead. Probable cause is a mismatch between the specified column delimiter and the column delimiter used in the input file. %1"
SAP Sybase Error Number	20632
SQL State	QCA62
SQL Code	-1013062L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	expected datatype of column
Probable Cause	A row delimiter, rather than a column, was encountered during a LOAD. Probable cause is a mismatch between the specified column delimiter and the column delimiter used in the input file.

Messages 1013063 through 1013088

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1013063	"Expected raw-data column type '%2' on input, but no input data exists. %1"
Constant	EMSG_SQL_EXPECTEDRAWFIELDTYPENOTSEEN
SAP Sybase Error Number	20633
SQL State	QCA63
SQL Code	-1013063L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	column datatype

Error 1013063	"Expected raw-data column type '%2' on input, but no input data exists. %1"
Probable Cause	No data was found during a scan of an input file during insert.

Error 1013064	"Row delimiter not seen during scan of input file. At least one of the input rows is missing a terminator. %1"
Constant	EMSG_SQL_ROWTERMINATORNOTSEEN
SAP Sybase Error Number	20634
SQL State	QCA64
SQL Code	-1013064L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	A row delimiter has been omitted from an input file.

Error 1013065	"Row delimiter '%2' and column delimiter '%3' cannot be substrings of each other. %1"
Constant	EMSG_SQL_CANTBESUBSTRING
SAP Sybase Error Number	20635
SQL State	QCA65
SQL Code	-1013065L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	the row delimiter
Parameter 3	the column delimiter
Probable Cause	Row and column delimiters cannot be substrings of each other.

Error 1013066	"The %2 load option can be specified only once. %1"
Constant	EMSG_SQL_MULTIPLE_LOAD_OPTION
SAP Sybase Error Number	20636
SQL State	QCA66
SQL Code	-1013066L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	name of the load option
Probable Cause	The named load option can be specified only once per LOAD statement.

Error 1013067	"Option CONVERSION ERROR must be OFF when IGNORE CONSTRAINT DATA VALUE or ALL is specified. %1"
Constant	EMSG_SQL_DATAVALUE_CVERROR
SAP Sybase Error Number	20637
SQL State	QCA67
SQL Code	-1013067L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	When IGNORE CONSTRAINT DATA VALUE or ALL is given on a load statement, the database option CONVERSION ERROR must be off.

Error 1013068	"Constraint '%2' violated: Invalid value for column '%3' in table '%4'. %1"
Constant	EMSG_SQL_COLUMN_CHECK_CONSTRAINT_VIOLATED

Error 1013068	"Constraint '%2' violated: Invalid value for column '%3' in table '%4'. %1"
SAP Sybase Error Number	20638
SQL State	QCA68
SQL Code	-1013068L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	constraint name
Parameter 3	column name for which the violation occurred
Parameter 4	table name
Probable Cause	The Data being inserted or updated is invalid due to a column check constraint violation.

Error 1013070	"Cannot specify check constraints off and ignore all, ignore check, log all or log check during load. %1"
Constant	EMSG_SQL_IQ_LOAD_CONFLICT
SAP Sybase Error Number	20640
SQL State	QCA70
SQL Code	-1013070L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	when check constraints off is specified during load ignore all, ignore check, log all, log check are not available.

Error 1013071	"Constraint '%2' violated: Invalid value in table '%3'. %1"
Constant	EMSG_SQL_TABLE_CHECK_CONSTRAINT_VIOLATED

Error 1013071	"Constraint '%2' violated: Invalid value in table '%3'. %1"
SAP Sybase Error Number	20641
SQL State	QCA71
SQL Code	-1013071L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	constraint name
Parameter 3	table name on which the table check violation occurred
Probable Cause	The Data being inserted or updated is invalid due to a table check constraint violation.

Error 1013077	"ROW DELIMITED BY is valid only when all columns are delimited or ASCII fixed-width. %1"
Constant	EMSG_SQL_INVALIDUSEOFROWTERMINATOR
SAP Sybase Error Number	20647
SQL State	QCA77
SQL Code	-1013077L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	ROW DELIMITED BY is valid only when all columns are delimited or ASCII fixed-width. You cannot use a row delimiter with PREFIX or BINARY columns.

Error 1013078	"Insert Pass 1 CPU utilization"
Constant	EMSG_FFINSERT_1
SAP Sybase Error Number	20648

Error 1013078	"Insert Pass 1 CPU utilization"
SQL State	QCA78
SQL Code	-1013078L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Probable Cause	This is displayed as part of an informational message during insert.

Error 1013079	"Insert Pass 1 user (%)"
Constant	EMSG_FFINSERT_1U
SAP Sybase Error Number	20649
SQL State	QCA79
SQL Code	-1013079L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Probable Cause	This is displayed as part of an informational message during insert.

Error 1013080	"Insert Pass 1 system (%)"
Constant	EMSG_FFINSERT_1S
SAP Sybase Error Number	20650
SQL State	QCA80
SQL Code	-1013080L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Probable Cause	This is displayed as part of an informational message during insert.

Error 1013081	"Insert Pass 2 CPU utilization"
Constant	EMSG_FFINSERT_2
SAP Sybase Error Number	20651
SQL State	QCA81
SQL Code	-1013081L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	This is displayed as part of an informational message during insert.

Error 1013082	"Insert Pass 2 user (%)"
Constant	EMSG_FFINSERT_2U
SAP Sybase Error Number	20652
SQL State	QCA82
SQL Code	-1013082L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	This is displayed as part of an informational message during insert.

Error 1013083	"Insert Pass 2 system (%)"
Constant	EMSG_FFINSERT_2S
SAP Sybase Error Number	20653
SQL State	QCA83
SQL Code	-1013083L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	This is displayed as part of an informational message during insert.

Error 1013084	"Insert Commit CPU utilization"
Constant	EMSG_FFINSERT_COMMIT
SAP Sybase Error Number	20654
SQL State	QCA84
SQL Code	-1013084L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	This is displayed as part of an informational message during insert.

Error 1013085	"Insert Commit user (%)"
Constant	EMSG_FFINSERT_COMMITU
SAP Sybase Error Number	20655
SQL State	QCA85
SQL Code	-1013085L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	This is displayed as part of an informational message during insert.

Error 1013086	"Insert Commit system (%)"
Constant	EMSG_FFINSERT_COMMITS
SAP Sybase Error Number	20656
SQL State	QCA86
SQL Code	-1013086L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	This is displayed as part of an informational message during insert.

Error 1013087	"Total Insert CPU utilization"
Constant	EMSG_FFINSERT_TOTAL
SAP Sybase Error Number	20657
SQL State	QCA87
SQL Code	-1013087L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	This is displayed as part of an informational message during insert.

Error 1013088	"Insert Total user (%)"
Constant	EMSG_FFINSERT_TOTALU
SAP Sybase Error Number	20658
SQL State	QCA88
SQL Code	-1013088L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	This is displayed as part of an informational message during insert.

Messages 1013089 through 1013111

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1013089	"Insert Total system (%)"
Constant	EMSG_FFINSERT_TOTALS
SAP Sybase Error Number	20659
SQL State	QCA89
SQL Code	-1013089L
ODBC 2 State	ERROR

Error 1013089	"Insert Total system (%)"
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Probable Cause	This is displayed as part of an informational message during insert.

Error 1013090	"Single or double quote mark cannot be the first character of column delimiter or row terminator with QUOTES option ON. %1"
Constant	EMSG_INVALID_COLUMN_DELIM
SAP Sybase Error Number	20979
SQL State	QCA90
SQL Code	-1013090L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Probable Cause	Cannot use single or double quote mark for column/row delimiter with QUOTES option ON.

Error 1013091	"Column pairs %2=%3 could not be matched. %1"
Constant	EMSG_SQL_COLUMNPAIRSNOTFOUND
SAP Sybase Error Number	20983
SQL State	QCA91
SQL Code	-1013091L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	column name
Parameter 3	column name

Error 1013091	"Column pairs %2=%3 could not be matched. %1"
Probable Cause	The columns specified in CREATE JOIN could not be matched in the tables specified.

Error 1013092	"The MONITOR for this database, connection and buffer cache already exists. %1"
Constant	EMSG_SQL_MONITOREXISTS
SAP Sybase Error Number	20984
SQL State	QCA92
SQL Code	-1013092L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	A monitor has already been started for this database, connection and buffer cache.

Warning 1013093	"Insert started: %1\n"
Constant	EMSG_SQL_INSERTSTARTED
SAP Sybase Error Number	20985
SQL State	00A93
SQL Code	1013093L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	1 on page 2
Parameter 1	The table being inserted to.
Probable Cause	This is an informational message displayed during insert.

Error 1013096	"Index %2 could not be created. The datatype does not support an index of %3. %1"
Constant	EMSG_SQL_INDEXTYPEUNSUPPORTED

Error 1013096	"Index %2 could not be created. The datatype does not support an index of %3. %1"
SAP Sybase Error Number	20988
SQL State	QCA96
SQL Code	-1013096L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	indexname
Parameter 3	indextype
Probable Cause	You cannot create an index of the type specified for the column's datatype.

Error 1013098	" The foreign key %2 participates in join %3 and can not be ALTERed. %1"
Constant	EMSG_CAT_JOINFIELDKEYMAT
SAP Sybase Error Number	21004
SQL State	QCA98
SQL Code	-1013098L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	the column of the foreign key
Parameter 3	the name of the join index
Probable Cause	This message is returned during ALTER when a foreign key that is about to be altered, participates in the join of two tables.

Error 1013100	"The ON keyword cannot be used in a NATURAL join. %1"
Constant	EMSG_SQL_JOININVALIDONWITHNATURAL
SAP Sybase Error Number	21020
SQL State	QCB00
SQL Code	-1013100L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	The ON keyword cannot be used in a NATURAL join.

Error 1013102	"User name '%2' does not exist. %1"
Constant	EMSG_SQL_FINDUSERBYNAME
SAP Sybase Error Number	21022
SQL State	QCB02
SQL Code	-1013102L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	the user name specified
Probable Cause	The specified user does not exist.

Error 1013103	"%2 not implemented %1"
Constant	EMSG_SQL_IQMSG_NOT_YET_IMPLEMENTED_IN_ATOM-IC
SAP Sybase Error Number	22001
SQL State	QCC00
SQL Code	-1013103L

Error 1013103	"%2 not implemented %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Parameter 2	Name of the feature
Probable Cause	This feature has not been implemented

Error 1013104	"This operation is not allowed on the dbspace IQ_SYSTEM_TEMP. %1"
Constant	EMSG_DBSPACE_ILLEGAL_TEMP_OP
SAP Sybase Error Number	22012
SQL State	QDD13
SQL Code	-1013104L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	Illegal op for iq_system_temp

Error 1013105	"Use ALTER DBSPACE ALTER FILE for this operation. %1"
Constant	EMSG_DBSPACE_USE_ALTER_FILE
SAP Sybase Error Number	22013
SQL State	QDD14
SQL Code	-1013105L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception

Error 1013105	"Use ALTER DBSPACE ALTER FILE for this operation. %1"
Probable Cause	Must use alter dbspace alter file

Error 1013106	"logical file %2 not part of dbspace %3. %1"
Constant	EMSG_NON_EXISTENT_LOGICAL_FILENAME
SAP Sybase Error Number	22004
SQL State	QDC59
SQL Code	-1013106L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	logical filename that is to be altered
Parameter 3	dbspace named in sql command
Probable Cause	this logical filename is not part of this dbspace

Error 1013107	"MPX: server %2 is not part of the Multiplex configuration. %1"
Constant	EMSG_MPX_BADSERVER_NAME
SAP Sybase Error Number	22008
SQL State	QDD09
SQL Code	-1013107L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	Server name
Probable Cause	This is a multiplex and this server is not part of it.

Error 1013108	"MPX: startup failure message: server '%2' was started on an incorrect host '%3': this server was created with this connection string '%4'. %1"
Constant	EMSG_MPX_START_WRONG_HOST
SAP Sybase Error Number	22009
SQL State	QDD10
SQL Code	-1013108L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	server name
Parameter 3	host server was started on
Parameter 4	this server connection information
Probable Cause	This server cannot be started on this host

Error 1013109	"MPX: coordinator has been started with an incorrect catalog. %1"
Constant	EMSG_MPX_INCORRECT_CATALOG
SAP Sybase Error Number	22010
SQL State	QDD11
SQL Code	-1013109L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	The coordinator has been started with an incorrect catalog

Warning 1013110	"IQ had insufficient memory to create the buffer cache with the size specified with the Main_Cache_Memory_MB or Temp_Cache_Memory_MB options. Instead, the cache will be created using the default size."
Constant	EMSG_IQSTORE_OUTOFMEM_ONOPENDB
SAP Sybase Error Number	21033
SQL State	QSB35
SQL Code	1013110L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	<i>10</i> on page 2
Probable Cause	If we catch an OUTOFMEMORY exception when creating the MAIN or the TEMP buffer cache, we report this warning of our failure and retry to create the cache with the default settings (and NOT the settings in the hos_paramset). This will allow the DBA to re-open a database even if the Main_Cache_Memory_MB or Temp_Cache_Memory_MB options are set so high as to otherwise prevent the re-opening of the database. (QTS 183253.)

Error 1013110	"MPX: server %2 has been started with an incorrect catalog path (expected path: %3). %1"
Constant	EMSG_MPX_INCORRECT_CATALOG_PATH
SAP Sybase Error Number	22011
SQL State	QDD12
SQL Code	-1013110L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	location of the exception
Parameter 2	server name
Parameter 3	expected catalog path
Probable Cause	The coordinator has been started with the incorrect catalog

Warning 1013111	"WARNING***** File '%1' has a length of 0"
Constant	EMSG_SQL_LOAD0LENGTHFILE
SAP Sybase Error Number	22162
SQL State	01A50
SQL Code	1013111L
ODBC 2 State	OK
ODBC 3 State	OK
Severity Code	10 on page 2
Parameter 1	Filename
Probable Cause	An attempt was made to load a file of length 0

Error 1013111	"MPX: This operation is not supported on a MPX secondary node. %1"
Constant	EMSG_MPX_DBSPACE_ILLEGAL_ON_SN
SAP Sybase Error Number	22014
SQL State	QDD15
SQL Code	-1013111L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	Not supported on a mpx secondary node

Messages 1013112 through 1013131

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1013112	"MPX: Striping parameters for IQ_SYSTEM_TEMP are global and may only be altered on the coordinator node. %1"
Constant	EMSG_MPX_DBSPACE_STRIPING_ILLEGAL_ON_SN

Error 1013112	"MPX: Striping parameters for IQ_SYSTEM_TEMP are global and may only be altered on the coordinator node. %1"
SAP Sybase Error Number	22015
SQL State	QDD116
SQL Code	-1013112L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	Change striping for IQ_SYSTEM_TEMP on coordinator only.

Error 1013113	"The multiplex server '%2' is not included in the multiplex. %1"
Constant	EMSG_MPX_SERVER_NOT_INCLUDED
SAP Sybase Error Number	22016
SQL State	QNA49
SQL Code	-1013113L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Exception Location
Parameter 2	server name
Probable Cause	This multiplex server has been excluded

Error 1013114	"To start a Secondary node in single-node mode (-iqmpx_sn 1) the override switch (-iqmpx_ov 1) should be used %1"
Constant	EMSG_MPX_SECONDARY_NEED_OV_START_SINGLE
SAP Sybase Error Number	22017
SQL State	QNA50

Error 1013114	"To start a Secondary node in single-node mode (-iqmpx_sn 1) the override switch (-iqmpx_ov 1) should be used %1"
SQL Code	-1013114L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Probable Cause	Secondary servers are not allowed to start with -iqmpx_sn 1. As the use of -iqmpx_sn 1 makes the server the owner of the IQ database it should not be used unless coordinator restore and failover operations have failed. If it becomes necessary to re-establish ownership of the database by a secondary server you can start the secondary server with -iqmpx_sn 1 only with override (-iqmpx_ov 1)

Error 1013115	"IQ Internal multiplex error. Please report this to Sybase IQ support. %1"
Constant	EMSG_MPX_FATAL_PROGERROR
SAP Sybase Error Number	22018
SQL State	QDD18
SQL Code	-1013115L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Probable Cause	A fatal programming error encountered, server will be aborted.

Error 1013116	"The operation has been cancelled - Mpx_Work_Unit_Timeout exceeded. %2 %1"
Constant	EMSG_MPX_WU_TIMEOUT
SAP Sybase Error Number	22020
SQL State	QDD21
SQL Code	-1013116L

Error 1013116	"The operation has been cancelled - Mpx_Work_Unit_Timeout exceeded. %2 %1"
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	explanation for arg %2 delete if no %2
Probable Cause	The elapsed time to complete a distributed work unit exceed the timeout value.

Error 1013117	"Worker rejected query fragment - %2. %1"
Constant	EMSG_WORKER_REJECTED_QUERY_FRAGMENT
SAP Sybase Error Number	22024
SQL State	QDD24
SQL Code	-1013117L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of exception
Parameter 2	reason for rejecting the fragment.
Probable Cause	Worker node could not execute a remote procedure call.

Error 1013118	"Login denied to logical server '%2', Either the server is not part of the logical server or does not match the node type or login redirection is disabled. %1"
Constant	EMSG_LOGIN_REDIRECTION_ERROR
SAP Sybase Error Number	22031
SQL State	QXA63
SQL Code	-1013118L
ODBC 2 State	ERROR

Error 1013118	"Login denied to logical server '%2', Either the server is not part of the logical server or does not match the node type or login redirection is disabled. %1"
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Parameter 2	logical server id
Probable Cause	This connection attempt failed because the logical server did not match the connection criteria

Error 1013119	"To redirect to the COORDINATOR logical server the connection parameter nodetype should be a 'writer'. %1"
Constant	EMSG_NODETYPE_MUST_BE_WRITER
SAP Sybase Error Number	22032
SQL State	QXA64
SQL Code	-1013119L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	23 on page 2
Parameter 1	location of the exception
Probable Cause	The connection parameter logicalserver = coordinator must ask for a writer node

Error 1013120	"Worker unable to send remote procedure call to leader. - %2. %1"
Constant	EMSG_WORKER_RPC_FAILURE
SAP Sybase Error Number	22035
SQL State	QDD28
SQL Code	-1013120L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1013120	"Worker unable to send remote procedure call to leader. - %2. %1"
Severity Code	<i>14</i> on page 2
Parameter 1	location of exception
Parameter 2	reason for rejecting the fragment.
Probable Cause	The worker node is trying to send a message to the leader node but the leader is no longer available.

Error 1013121	"Cannot truncate partition '%2' of table '%3' - table partitioned incorrectly. %1"
Constant	EMSG_CANNOT_TRUNCATE_PARTITION
SAP Sybase Error Number	22151
SQL State	QDD29
SQL Code	-1013121L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	Location of the exception.
Parameter 2	partition name.
Parameter 3	table name.
Probable Cause	Table must be range partitioned for truncate partition and hash-range partitioned for truncate subpartition

Error 1013122	"Cannot add a partition or subpartition to table %2 %1"
Constant	EMSG_TABLE_CONTAINS_DATA_CANNOT_HASH_PARTITION
SAP Sybase Error Number	22152
SQL State	QDD30
SQL Code	-1013122L
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Error 1013122	"Cannot add a partition or subpartition to table %2 %1"
Severity Code	<i>14</i> on page 2
Parameter 1	Location of the exception.
Parameter 2	table name.
Probable Cause	Alter table add partition hash - not allowed on table that contains data

Error 1013123	"Invalid value for IQ UNIQUE on column %2 %1"
Constant	EMSG_INVALID_IQ_UNIQUE
SAP Sybase Error Number	22153
SQL State	QDD31
SQL Code	-1013123L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	Location of the exception.
Parameter 2	column name.
Probable Cause	Value out of range or datatype does not allow dictionary compression

Error 1013124	"NBIT Column %2 exceeded token limit of %3 %1"
Constant	EMSG_NBIT_LIMIT_EXCEEDED
SAP Sybase Error Number	22154
SQL State	QDD32
SQL Code	-1013124L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	<i>14</i> on page 2
Parameter 1	Location of the exception.
Parameter 2	column name.
Parameter 3	token limit.

Error 1013124	"NBIT Column %2 exceeded token limit of %3 %1"
Probable Cause	Exceeded the IQ UNIQUE(N) limit defined for this column.

Error 1013125	"The optimizer hint ESTIMATED IQ UNIQUE is only allowed on flat FP columns %2 %1"
Constant	EMSG_INVALID_EST_IQ_UNIQUE
SAP Sybase Error Number	22155
SQL State	QDD33
SQL Code	-1013125L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Parameter 2	column name.
Probable Cause	Estimated unique is only allowed on flat columns.

Error 1013126	"Value %3 is less than the current maximum token %4 for column %2 %1"
Constant	EMSG_NBIT_VALUE_TOO_LOW
SAP Sybase Error Number	22156
SQL State	QDD34
SQL Code	-1013126L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Parameter 2	column name.
Parameter 3	new value.
Parameter 4	current number of tokens.

Error 1013126	"Value %3 is less than the current maximum token %4 for column %2 %1"
Probable Cause	The Value is lower than the current number of tokens in the column

Error 1013127	"Create RLV dbspace not allowed in multiplex."
Constant	EMSG_DBSPACE_RLV_MPX_NOT_ALLOWED
SAP Sybase Error Number	22157
SQL State	QRLV1A
SQL Code	-1013127L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	RLV dbspace may not be created in multiplex nodes.

Error 1013128	"The RLV freelist is corrupted."
Constant	EMSG_RLV_FREELIST_CORRUPT
SAP Sybase Error Number	22158
SQL State	QRLV1B
SQL Code	-1013128L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	The RLV freelist is corrupted.

Error 1013129	"RLV Store has run out of memory"
Constant	EMSG_RLV_HEAP_MEMORY_EXHAUSTED
SAP Sybase Error Number	22159
SQL State	QRLV1C
SQL Code	-1013129L
ODBC 2 State	ERROR

Error 1013129	"RLV Store has run out of memory"
ODBC 3 State	ERROR
Severity Code	14 on page 2
Probable Cause	RLV store has exceeded the configured memory limit.

Error 1013130	"All IQ large memory has been used, allocation canceled [size: %2] %1"
Constant	EMSG_LMA_OUTOFMEMORY
SAP Sybase Error Number	22160
SQL State	QBC75
SQL Code	-1013130L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	The size of unable to allocate memory
Probable Cause	iqlm large memory manager reprot error

Error 1013131	"Cannot unpartition a non-empty hash or hash-range partitioned table %2 %1"
Constant	EMSG_TABLE_CONTAINS_DATA_CANNOT_UNPARTITION_HASH_PARTITION
SAP Sybase Error Number	22161
SQL State	QDD35
SQL Code	-1013131L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	Location of the exception.
Parameter 2	table name.

Error 1013131	"Cannot unpartition a non-empty hash or hash-range partitioned table %2 %1"
Probable Cause	Alter table unpartition hash partition hash - not allowed on table that contains data

Messages 1013132 through 1013136

Messages on this page are sorted by Sybase error code. Locate the appropriate code for a full description of the message.

Error 1013132	"A local main cache already exists for the node %2. %1"
Constant	EMSG_DBSPACE_CACHE_CREATION_NOT_ALLOWED
SAP Sybase Error Number	22163
SQL State	QDD36
SQL Code	-1013132L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	server name
Probable Cause	Creation of more than one user defined CACHE dbspace is not allowed per node.

Error 1013133	"%2 is not allowed on cache dbspace %3. %1"
Constant	EMSG_DBSPACE_NOT_ALLOWED_CACHE
SAP Sybase Error Number	22164
SQL State	QDD37
SQL Code	-1013133L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception

Error 1013133	"%2 is not allowed on cache dbspace %3. %1"
Parameter 2	disallowed command
Parameter 3	dbspace name
Probable Cause	The requested DDL operation is not allowed on cache dbspaces

Error 1013134	"Error accessing server '%2': %3 %1"
Constant	EMSG_XT_ACCESS_ERROR
SAP Sybase Error Number	22165
SQL State	QCB88
SQL Code	-1013134L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	server name
Parameter 3	server specific error message
Probable Cause	An error occurred while accessing an external server.

Error 1013135	"Error converting %2 to %3 %1"
Constant	EMSG_XT_CONVERSION_ERROR
SAP Sybase Error Number	22166
SQL State	QCB89
SQL Code	-1013135L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	value
Parameter 3	datatype

Errors and Warnings

Error 1013135	"Error converting %2 to %3 %1"
Probable Cause	Error converting value returned from an external server to target datatype

Error 1013136	"Cannot acquire agent info from server %2. %1"
Constant	EMSG_MPX_AGENT_INFO_NOT_FOUND
SAP Sybase Error Number	21192
SQL State	QDD01
SQL Code	-1013136L
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity Code	14 on page 2
Parameter 1	location of the exception
Parameter 2	server id
Probable Cause	Agent for this server appears to running but failed to get needed info

SQL Preprocessor Errors

Messages 2601 through 2621

Messages on this page are sorted by error number. Locate the appropriate error code in the table below.

Error Code	Type	Message	Possible Cause
2601	Error	Subscript value %1 too large	You have attempted to index a host variable that is an array with a value too large for the array.
2602	Error	Combined pointer and arrays not supported for host types	You have used an array of pointers as a host variable. This is not legal.
2603	Error	Only one-dimensional arrays supported for CHAR type	You have attempted to declare a host variable as an array of character arrays. This is not a legal host variable type
2604	Error	VARCHAR type must have a length	You have attempted to declare a VARCHAR or BINARY host variable using the DECL_VARCHAR or DECL_BINARY macro but have not specified a size for the array.
2605	Error	Arrays of VARCHAR not supported	You have attempted to declare a host variable as an array of VARCHAR or BINARY. This is not a legal host variable type.
2606	Error	VARCHAR host variables cannot be pointers	You have attempted to declare a host variable as a pointer to a VARCHAR or BINARY. This is not a legal host variable type.
2607	Error	Initializer not allowed on VARCHAR host variable	You can not specify a C variable initializer for a host variable of type VARCHAR or BINARY. You must initialize this variable in regular C executable code.

Error Code	Type	Message	Possible Cause
2608	Error	FIXCHAR type must have a length	You have used the DECL_FIXCHAR macro to declare a host variable of type FIXCHAR but have not specified a length.
2609	Error	Arrays of FIXCHAR not supported	You have attempted to declare a host variable as an array of FIXCHAR arrays. This is not a legal host variable type.
2610	Error	Arrays of this type not supported	You have attempted to declare a host variable array of a type that is not supported.
2611	Error	Precision must be specified for decimal type	You must specify the precision when declaring a packed decimal host variable using the DECL_DECIMAL macro. The scale is optional.
2612	Error	Arrays of decimal not allowed	You have attempted to declare a host variable as an array of DECIMAL. This is not a legal host variable type.
2613	Error	Unknown host variable type	You declared a host variable of a type not understood by the SQL preprocessor.
2614	Error	Invalid integer	An integer was required in an Embedded SQL statement (for a fetch offset, or a host variable array index, etc.) and the preprocessor was unable to convert what was supplied into an integer.
2615	Error	'%1' host variable must be a C string type	A C string was required in an Embedded SQL statement (for a cursor name, option name, etc.) and the value supplied was not a C string.
2617	Error	'%1' symbol already defined	You defined a host variable twice.
2618	Error	Invalid type for SQL statement variable	A host variable used as a statement identifier should be of type a_sql_statement_number. You attempted to use a host variable of some other type as a statement identifier.

Error Code	Type	Message	Possible Cause
2619	Error	Cannot find include file '%1'	The specified include file was not found. Note that the preprocessor will use the INCLUDE environment variable to search for include files.
2620	Error	Host variable '%1' is unknown	You have used a host variable in a statement and that host variable has not been declared in a declare section.
2621	Error	Indicator variable '%1' is unknown	You have used an indicator variable in a statement and that indicator variable has not been declared in a declare section.

Messages 2622 through 2649

Messages on this page are sorted by error number. Locate the appropriate error code in the table below.

Error Code	Type	Message	Possible Cause
2622	Error	Invalid type for indicator variable '%1'	Indicator variables must be of type short int. You have used a variable of a different type as an indicator variable.
2623	Error	Invalid host variable type on '%1'	You have used a host variable that is not a string type in a place where the preprocessor was expecting a host variable of a string type.
2625	Error	Host variable '%1' has two different definitions	The same host variable name was defined with two different types within the same module. Note that host variable names are global to a C module.
2626	Error	Statement '%1' not previously prepared	An Embedded SQL statement name has been used (EXECUTE) without first being prepared.

Error Code	Type	Message	Possible Cause
2627	Error	Cursor '%1' not previously declared	An Embedded SQL cursor name has been used (in a FETCH, OPEN, CLOSE, etc.) without first being declared.
2628	Error	Unknown statement '%1'	You attempted to drop an embedded SQL statement that doesn't exist.
2629	Error	Host variables not allowed for this cursor	Host variables are not allowed on the declare statement for the specified cursor. If the cursor name is provided through a host variable, then you should use full dynamic SQL and prepare the statement. A prepared statement may have host variables in it.
2630	Error	Host variables specified twice - on declare and open	You have specified host variables for a cursor on both the declare and the open statements. In the static case, you should specify the host variables on the declare statement. In the dynamic case, specify them on the open.
2631	Error	Must specify a host list or using clause on %1	The specified statement requires host variables to be specified either in a host variable list or from an SQLDA.
2633	Error	No INTO clause on SELECT statement	You specified an embedded static SELECT statement, but you did not specify an INTO clause for the results.
2636	Error	Incorrect Embedded SQL syntax	An Embedded SQL specific statement (OPEN, DECLARE, FETCH, etc.) has a syntax error.
2637	Error	Missing ending quote of string	You have specified a string constant in an Embedded SQL statement, but there is no ending quote before the end of line or end of file.

Error Code	Type	Message	Possible Cause
2639	Error	Token too long	The SQL preprocessor has a maximum token length of 2K. Any token longer than 2K will produce this error. For constant strings in Embedded SQL commands (the main place this error shows up) use string concatenation to make a longer string.
2640	Error	'%1' host variable must be an integer type	You have used a host variable that is not of integer type in a statement where only an integer type host variable is allowed.
2641	Error	Must specify an SQLDA on a DESCRIBE	No additional information available.
2642	Error	Two SQLDAs specified of the same type (INTO or USING)	You have specified two INTO DESCRIPTOR or two USING DESCRIPTOR clauses for this statement.
2646	Error	Cannot describe static cursors	You have described a static cursor. When describing a cursor, the cursor name must be specified in a host variable
2647	Error	Macros cannot be redefined	A preprocessor macro has been defined twice, possibly in a header file.
2648	Error	Invalid array dimension	The array dimension of the variable is negative
2649	Error	Invalid descriptor index	You have allocated less than one variable with the ALLOCATE DESCRIPTOR statement.

Messages 2650 through 2692

Messages on this page are sorted by error number. Locate the appropriate error code in the table below.

Error Code	Type	Message	Possible Cause
2650	Error	Invalid field for SET DESCRIPTOR	An invalid or unknown keyword is present in a SET DESCRIPTOR statement. The keywords can only be TYPE, PRECISION, SCALE, LENGTH, INDICATOR, or DATA.
2651	Error	Field used more than once in SET DESCRIPTOR statement	The same keyword has been used more than once inside a single SET DESCRIPTOR statement.
2652	Error	Data value must be a host variable	The variable used in the SET DESCRIPTOR statement hasn't been declared as a host variable.
2660	Warning	Into clause not allowed on declare cursor - ignored	You have specified an INTO clause on a SELECT statement in a DECLARE CURSOR. Note that the INTO clause will be ignored.
2661	Warning	Unrecognized SQL syntax	You have used a SQL statement that will probably cause a syntax error when the statement is sent to the database server.
2662	Warning	Unknown SQL function '%1'	You have used a SQL function that is unknown to the preprocessor and will probably cause an error when the statement is sent to the database engine.
2663	Warning	Wrong number of arguments to SQL function '%1'	You have used a SQL function with the wrong number of parameters. This will likely cause an error when the statement is sent to the database server.

Error Code	Type	Message	Possible Cause
2664	Warning	Static statement names will not work properly if used by 2 threads	You have used a static statement name and preprocessed with the -r reentrancy switch. Static statement names cause static variables to be generated that are filled in by the database. If two threads use the same statement, contention arises over this var
2665	Warning	Host variable '%1' has been re-defined	You have redefined the same host variable with a different host type. As far as the preprocessor is concerned, host variables are global; two host variables with different types cannot have the same name.
2666	Flag (warning or error)	Disallowed language extension detected in syntax	You have used a feature that is not defined by SQL/92 and preprocessed with the -ee, -ei, -ef, -we, -wi or -wf flagging switch.
2667	Flag (warning or error)	Language extension detected in syntax	You have used a SQL Anywhere feature that is not supported by the current flagging level (set using the -w option).
2668	Flag (warning or error)	Full SQL feature	You have used a full-SQL/92 feature and preprocessed with the -ee, -ei, -we or -wi flagging switch.
2669	Flag (warning or error)	Transact SQL extension	You have used a Sybase Transact SQL feature that is not defined by SQL/92 and preprocessed with the -ee, -ei, -ef, -we, -wi or -wf flagging switch.
2680	Error	No DECLARE SECTION and no INCLUDE SQLCA statement	The EXEC SQL INCLUDE SQLCA statement is missing from the source file.
2681	Error	Unable to open temporary file	An error occurred while attempting to open a temporary file.
2682	Error	Error reading temporary file	An error occurred while reading from a temporary file.
2683	Error	Error writing output file	An error occurred while writing to the output file.

Error Code	Type	Message	Possible Cause
2690	Error	Inconsistent number of host variables for this cursor	You have used a different number of host variables than the number previously used with the cursor. The number of host variables must be consistent for the cursor.
2691	Error	Inconsistent host variable types for this cursor	You have used a host variable with a different type or length than the type or length previously used with the cursor. Host variable types must be consistent for the cursor.
2692	Error	Inconsistent indicator variables for this cursor	You have used an indicator variable when one was not previously used with the cursor, or you have not used an indicator variable when one was previously used with the cursor. Indicator variable usage must be consistent for the cursor.

Messages 2694 through 2701

Messages on this page are sorted by error number. Locate the appropriate error code in the table below.

Error Code	Type	Message	Possible Cause
2694	Error	No OPEN for cursor '%1'	A cursor is declared, and possibly used, but is never opened.
2695	Error	No FETCH or PUT for cursor '%1'	A cursor is declared and opened, but is never used.
2696	Error	Host variable '%1' is in use more than once with different indicators	You have used the same host variable multiple times with different indicator variables in the same statement. This is not supported.
2698	Error	WCHAR and TCHAR host variable types are not supported	You have attempted to declare a host variable as a WCHAR or TCHAR string. These are only supported by UltraLite on Windows platforms.

Error Code	Type	Message	Possible Cause
2699	Error	char, WCHAR, and TCHAR string parameters cannot be mixed	You have attempted to use parameters to one statement that are not all char strings, WCHAR strings or TCHAR strings. String parameters (other than INTO and USING parameters) for one statement must all be the same type of string. Note that literal strings are treated as char strings.
2701	Error	FOR UPDATE or FOR READ ONLY clause must be specified on PREPARE (not on DECLARE CURSOR)	You specified the FOR UPDATE or FOR READ ONLY clause on a DECLARE CURSOR statement. The FOR UPDATE or FOR READ ONLY clause must be specified on the PREPARE statement and not the DECLARE CURSOR statement. For compatibility with previous versions (but with reduced performance), the sqlpp -m HISTORICAL option can be used to allow the FOR UPDATE or FOR READ ONLY clause on the DECLARE CURSOR statement.

