



New Features Summary

Adaptive Server[®] Enterprise

15.7

DOCUMENT ID: DC01165-01-1570-01

LAST REVISED: September 2011

Copyright © 2011 by Sybase, Inc. All rights reserved.

This publication pertains to Sybase software and to any subsequent release until otherwise indicated in new editions or technical notes. Information in this document is subject to change without notice. The software described herein is furnished under a license agreement, and it may be used or copied only in accordance with the terms of that agreement.

To order additional documents, U.S. and Canadian customers should call Customer Fulfillment at (800) 685-8225, fax (617) 229-9845.

Customers in other countries with a U.S. license agreement may contact Customer Fulfillment via the above fax number. All other international customers should contact their Sybase subsidiary or local distributor. Upgrades are provided only at regularly scheduled software release dates. No part of this publication may be reproduced, transmitted, or translated in any form or by any means, electronic, mechanical, manual, optical, or otherwise, without the prior written permission of Sybase, Inc.

Sybase trademarks can be viewed at the Sybase trademarks page at <http://www.sybase.com/detail?id=1011207>. Sybase and the marks listed are trademarks of Sybase, Inc. ® indicates registration in the United States of America.

SAP and other SAP products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of SAP AG in Germany and in several other countries all over the world.

Java and all Java-based marks are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and other countries.

Unicode and the Unicode Logo are registered trademarks of Unicode, Inc.

IBM and Tivoli are registered trademarks of International Business Machines Corporation in the United States, other countries, or both.

All other company and product names mentioned may be trademarks of the respective companies with which they are associated.

Use, duplication, or disclosure by the government is subject to the restrictions set forth in subparagraph (c)(1)(ii) of DFARS 52.227-7013 for the DOD and as set forth in FAR 52.227-19(a)-(d) for civilian agencies.

Sybase, Inc., One Sybase Drive, Dublin, CA 94568.

Contents

New Features in Adaptive Server Version 15.7	1
Application Functionality Configuration Group	1
New Adaptive Server Kernel	1
Compressing Data in Adaptive Server	2
New Security Features	2
End-to-End CIS Kerberos Authentication	3
Dual Control of Encryption Keys and Unattended Startup	3
Securing Logins, Roles, and Password Management Extensions	4
Login Profiles	4
Employee Lifecycle Management	4
External Passwords and Hidden Text	5
Abstract Plans in Cached Statements	5
Shrink Log Space	6
Displaying Currently Set Switches with sysoptions	6
Changes for Large Objects	6
In-Row Off-Row LOB	6
Using Large Object text, unitext, and image Datatypes in Stored Procedures	7
Using LOB Locators in Transact-SQL Statements	7
Extension to where Clause for Large Objects	8
Showing Cached Plans in XML	8
Padding a Character Field Using str	8
Changes to select for update	8
Creating Nonmaterialized, Non-null Columns	9
Sharing Inline Defaults	9
Retain Monitoring Data	9
Analyze Dynamic Parameters	10
Monitor Lock Timeouts	10

- Truncate Trailing Zeros11
- Fully Recoverable DDL11
- Transfer Rows from Source to Target Table Using
merge11
- View Statistics and Histograms with sp_showoptstats
.....11
- Changes to Cursors12
 - Release Cursor Locks at Cursor Close12
 - Enhanced Transaction Support for Cursors12
 - Monitor Cursor Statements12
- Nested select Statement Enhancements13
- Changes to Commands and System Procedures in
Chained Transaction13
- Expanded Variable-Length Rows14
- Changes to like Pattern Matching15
- Changes to Quoted Identifiers15
- Allowing Unicode Noncharacters15
- Reduce Query Processing Latency16
- The sybdiag Utility16
- The Optimizer Diagnostic Utility17
- System Changes in Adaptive Server Version 15.719**
 - Commands19
 - Functions22
 - System Stored Procedures24
 - Configuration Parameters27
 - System Tables29
 - Utilities30
 - Monitoring Table Changes31
 - New Monitoring Tables31
 - Changes to Monitoring Tables31
 - Global Variables38
- New Features in Adaptive Server Version 15.5 Cluster
Edition39**
 - Adaptive Server 15.5 Cluster Edition Feature and
Platform Matrix39

Multiple simultaneous failover	41
Adding space to an archive database	41
Distributed transaction management in the shared-disk cluster	41
System Changes Adaptive Server 15.5 Cluster Edition ...	43
Changed commands	43
Monitoring Tables	43
Configuration Parameters	45
Functions	45
New Features in Adaptive Server® Version 15.5	47
Adaptive Server 15.5 Feature and Platform Matrix	47
In-Memory and Relaxed-Durability Databases	49
Faster Compression for Backups	50
Backup Server Support for the IBM® Tivoli® Storage Manager	50
Deferred Name Resolution for User-Defined Stored Procedures	51
FIPS 140-2 Login Password Encryption	51
Incremental Data Transfer	52
bigdatetime and bigtime Datatypes	52
Creating and Managing tempdb Groups	53
System Changes in Adaptive Server 15.5	55
Datatypes	55
Functions	56
System Stored Procedures	57
Commands	59
Configuration Parameters	61
Monitoring Tables	61
System Tables	62
Utilities	62
Auditing	63
New Features in Adaptive Server 15.0.3	65
SQL Statement Replication	65
Security Enhancements	65
LDAPS User Authentication Enhancement	65

Automatic LDAP User Authentication and Failback	65
Login Mapping of External Authentication	66
Using SSL to Specify a Common Name	66
Concurrent Kerberos Authentication	66
Virtually Hashed Tables	67
Huge Pages	67
Upgrading During a High Availability Configuration	68
Reinstalling System Stored Procedures	68
Distributed Transaction Management (DTM)	68
Adaptive Server Plug-in Updates	69
The Java Interface	70
System Changes in Adaptive Server 15.0.3	71
Functions	71
System Stored Procedures	71
Commands	72
Configuration Parameters	72
Monitoring Tables	73
System Tables	74
New Features in Adaptive Server 15.0.2	75
Encrypted Columns	75
Archive Database Access	76
Finding Slow-Running Queries	77
Deferred Compilation	77
Case-Insensitive Sort Orders for Chinese and Japanese Character Sets	78
Statistical Aggregate Functions	78
Standard Deviation and Variance	79
Eager and Lazy Aggregation	79
Vector and Scalar Aggregation	80
Improved Performance for Data Insertion	80
Using Asynchronous Writes During a Page Split	81
Improving Throughput of tempdb Transactions ..	81
Post-commit Optimization	82

Changes to the Query Processor	83
Deferred Compilation	83
Non-binary Character Set Histogram Interpolation	83
Expression Histogramming Selectivity Estimates	83
Viewing Current Optimizer Settings	84
New Security Features	84
PAM Support in 64-bit Adaptive Server on AIX ...	84
Global Login Triggers Set Automatically	84
SSL Support	85
Improved Password Security	85
Auditing Enhancements	85
High Availability Considerations	86
Installing and Editing Monitoring Tables	86
Monitoring Tables for the Statement Cache	87
Row-Level Locking for System Tables	87
The xmltable() Function	88
Relocated Joins	89
User-Defined SQL Functions	89
instead of Triggers	90
System Changes in Adaptive Server 15.0.2	91
Trace Flags	91
Commands	91
Changes to the set Command	92
Utilities	92
System Stored Procedures	93
System Tables	96
Configuration Parameters	99
Functions	100
Global Variables	101
New Features in Adaptive Server 15.0.1	103
Changes to Abstract Plans	103
New Query-Level Settings	103

Operator Name Alignment for the Abstract Plan and the Optimizer Criteria	104
Extending the Optimizer Criteria Set Syntax	105
Literal Parameterization	105
System Changes in Adaptive Server 15.0.1	107
Functions	107
Configuration Parameters	107
Commands	109
Monitoring Tables	111
New Features in Adaptive Server 15.0	113
Partition Support	113
Row-Locked System Catalogs	114
Query Processor	114
Large Identifiers	115
Computed Columns	115
Differences Between Computed Columns and Function-Based Indexes	116
Differences Between Materialized and Not Materialized Computed Columns	116
Scrollable Cursors	116
unitext Datatype Support	117
big int Datatype Support	117
Unsigned Integer Datatype Support	118
Integer Identity	118
Enhancements to XML Services	119
Adaptive Server Plug-in Enhancements	119
Interactive SQL	120
User-Defined Web Services	120
Very Large Storage Support	120
Automatic Running of update statistics	121
SySAM License Management	121
Query Processing Metrics (qp Metrics)	122
Updates to Abstract Plans	123
showplan Changes	123
Secure Socket Layer Uses FIPS 140-2	124

System Changes in Adaptive Server 15.0	127
Utilities	127
Reserved Words	127
Global Variables	128
Configuration Parameters	129
Functions	130
Commands	132
System Stored Procedures	133
System Tables	134
Monitoring Tables	138
Obtaining Help and Additional Information	141
Index	143

Contents

New Features in Adaptive Server Version 15.7

Adaptive Server® version 15.7 introduces many new features and enhancements.

Application Functionality Configuration Group

Adaptive Server version 15.7 adds the Application Functionality configuration group to the configuration file.

These are the Application Functionality configuration parameters

- `enable functionality group`
- `select for update`
- `streamlined dynamic SQL`
- `enable inline default sharing`
- `enable permissive unicode`
- `quoted identifier enhancements`

Use `enable functionality group` to enable or disable all configuration parameters in this group. Enable or disable individual configuration parameters to overwrite the group value.

See "Setting Configuration Parameters" in the *System Administration Guide, Volume 1*.

New Adaptive Server Kernel

Adaptive Server version 15.7 and later includes two kernels: a threaded kernel and a process kernel.

The kernel for which you configure Adaptive Server determines the mode in which Adaptive Server runs:

- **Threaded mode** – Adaptive Server runs as a single multithreaded operating system process, and processes SQL queries with engines running on threads in thread pools. Threaded mode utilizes threads without engines to manage I/O. Administrators can configure additional thread pools to manage workload.
- **Process mode** – The legacy kernel on which Adaptive Server previously ran. In process mode, Adaptive Server runs as multiple operating system processes that cooperate to work as a single server. Process mode uses engines to manage I/O, and administrators configure engine groups to manage workload.

For many workloads, threaded mode uses significantly less CPU than process mode, delivering the same—or better—performance. Threaded mode does not require as much task-

New Features in Adaptive Server Version 15.7

to-engine affinity, thereby delivering more consistent performance in a mix of I/O- and CPU-intensive workloads.

The threaded kernel allows Adaptive Server to take advantage of parallel hardware and support systems that have more processors, processor cores, and hardware threads than earlier-version kernels. Although version 15.7 changes the kernel, the query processor remains the same. To run in threaded kernel mode, you need not change most scripts written for earlier versions of Adaptive Server, although few commands and stored procedures have changed. Applications are completely compatible with threaded mode.

Threaded mode is the default mode for Adaptive Server, and the mode that Sybase® recommends. Adaptive Server on the Windows platform runs only in threaded mode.

See the *System Administration Guide: Volume 2* for information about configuring Adaptive Server for threaded mode.

Compressing Data in Adaptive Server

Adaptive Server version 15.7 introduces data compression, which lets you use less storage space for the same amount of data, reduce cache memory consumption, and improve performance because of lower I/O demands.

You can compress large object (LOB) and regular data.

After you create a compressed table or partition, Adaptive Server compresses any subsequently inserted or updated data (that is, existing data is not already compressed). If Adaptive Server cannot efficiently compress the inserted data, the original row is retained. If newly inserted or updated LOB data occupies space that is smaller than or equal to a single data page, Adaptive Server does not compress this data.

You need not uncompress data to run queries against it. You can insert, update, and delete compressed data; running **select** or **readtext** statements on the compressed column returns decompressed rows. Because there is less data for Adaptive Server to search, there are fewer I/Os, improving the efficiency of data storage.

Data compression is a separately licensed option. See the *Compression Users Guide*.

New Security Features

Adaptive Server version 15.7 adds these features for security: end-to-end CIS Kerberos authentication, dual control of encryption keys and unattended startup, securing logins, roles and password management extensions, and login profiles.

End-to-End CIS Kerberos Authentication

Adaptive Server version 15.7 includes end-to-end Kerberos authentication support for remote Adaptive Server connections through the component integration system (CIS).

End-to-end (CIS) Kerberos authentication allows a Kerberos V5 user logged in to Adaptive Server using Kerberos authentication to connect to a remote Adaptive Server using the Kerberos unified login authentication when:

- Requesting an RPC to the Adaptive Server
- Issuing CIS passthrough connections
- Issuing general distributed query processing requests to remote Adaptive Servers using CIS

Adaptive Server supports these optional security services for Kerberos connections to remote ASE servers using CIS:

- Message confidentiality
- Message integrity
- Mutual authentication

See the *Security Administration Guide*.

Dual Control of Encryption Keys and Unattended Startup

Adaptive Server version 15.7 adds the dual control of encryption keys and unattended startup features.

Changes for dual control and split knowledge, and unattended startup include:

- The `master` and `dual master` system keys are database-level keys, created by users with the `sso_role` or `keycustodian_role`, and are used as key-encryption keys (KEKs) for user-created encryption keys to achieve better security and split knowledge for data encryption keys. The `master` key replaces the current system encryption password, which Adaptive Server continues to support for backward compatibility purposes. Sybase recommends that users no longer use system encryption passwords to encrypt data encryption keys.
- The ability to supply passwords for the `master` and `dual master` keys with SQL commands and through a private file. Passwords for the master keys are non-persistent: they are not stored in the database.
- The ability to protect all user-created keys through dual control and split knowledge.

See the *Encrypted Columns Users Guide*.

Securing Logins, Roles, and Password Management Extensions

Adaptive Server version 15.7 includes extension for securing logins, roles, and password management.

Adaptive Server improves logins, roles and their passwords through:

- Stronger encryption for role passwords stored on disk.
- Locked roles accounting.
- ISO 8601 duration specification for login, role, and global password policy options.
- Password management extensions such as customizing the Rivest-Shamir-Adleman (RSA) keypair regeneration period, extending password complexity checks to roles passwords, and extending password management support in High Availability environments.
- Auditing enhancements to role definition, activation, role locking due to failed activation attempts, and password management extensions such as RSA keypair regeneration.

See the *Security Administration Guide*.

Login Profiles

Adaptive Server 15.7 adds login profiles, which are SQL-defined containers for login attributes and their values.

Login accounts are defined and governed by attributes. For example, these attributes are associated with login accounts when adding or modifying a login account:

- The database to use
- Which roles to automatically activate
- The language to apply
- The login script to invoke when you log in to Adaptive Server

You can associate some attributes with all login accounts by specifying them in the default login profile, and associate other attributes with a specific set of login accounts by specifying them in a login profile and associating this login profile with login accounts.

See the *Security Administration Guide*.

Employee Lifecycle Management

System security officers or database owners can transfer the ownership of database objects using **alter... modify owner**.

The command provides a way for a database administrator to manage the assignment of objects due to employee changes or to separate the creation ownership of database objects.

External Passwords and Hidden Text

Adaptive Server 15.7 provides strong encryption for external login passwords and hidden text, using the AES-256 symmetric encryption algorithm.

Strong encryption for external passwords applies to passwords for the following:

- Replication Agents – Passwords for replicated databases.
- CIS – Passwords for remote descriptors and logins.
- Job Scheduler – Passwords for Job Scheduler Agent.
- RTMS – Passwords for Real Time Messaging Services.
- Secure Socket Layer (SSL) and Lightweight Directory Access Protocol (LDAP) – Passwords for SSL and LDAP access account. Passwords are administered using stored procedures `sp_ldapadmin` and `sp_ssladmin` can be secured.

Abstract Plans in Cached Statements

Adaptive Server version 15.7 introduces the ability to save abstract plan information in the statement cache.

In this example, which includes an abstract plan, the hash table saves **select * from t1 plan '(use optgoal allows_mix)'**, as shown in the SQL TEXT line:

```

1> select * from t1 plan '(use optgoal allows_mix)'
2> go
1> dbcc prsqlcache
2> go

Start of SSQL Hash Table at 0x0x1474c9050

Memory configured: 1000 2k pages          Memory used: 17 2k pages

Bucket# 243 address 0x0x1474c9f80

SSQL_DESC 0x0x1474cd070
ssql_name *ss0626156152_0290084701ss*
ssql_hashkey 0x0x114a575d          ssql_id 626156152
ssql_suid 1          ssql_uid 1          ssql_dbid 1          ssql_spid 0
ssql_status 0x0xa0          ssql_parallel_deg 1
ssql_isolate 1          ssql_tranmode 32
ssql_keep 0          ssql_usesent 1          ssql_pgcount 6
SQL TEXT: select * from t1 plan '(use optgoal allows_mix)'
```

End of SSQL Hash Table

In versions of Adaptive Server earlier than 15.7, the SQL TEXT line included only the `select * from t1` command, without the plan clause.

See the *Performance and Tuning Series: Query Processing and Abstract Plans*.

Shrink Log Space

In Adaptive Server version 15.7 and later, **alter database** includes the **log off** parameter, which removes unwanted portions of a database log, allowing you to shrink log space and free storage without re-creating the database.

log off may be particularly helpful after running the fully logged option for database operations, such as **select into**, **alter table**, or **reorg rebuild**, when the database ends up with extra allocated space that is no longer needed.

See "Fully Recoverable DDL" in this document and "Creating and Managing User Databases" in the *System Administration Guide, Volume 2*.

Displaying Currently Set Switches with sysoptions

Adaptive Server version 15.7 adds the `number` column to the `sysoptions` table, which contains the switch ID for currently set switches.

`sysoptions` shows these switches:

- Trace flags set in the runserver file with the **-T** flag
- Trace flags set with `dbcc traceon(flag_number)` or **set switch serverwide on**
- Trace flags and switches set for a specific system process ID (spid) with `set switch on`

`sysoptions` shows only the switches that are visible to the user. That is, users cannot see switches set privately by other spids. The value for `number` is Null for all option categories other than switches.

Changes for Large Objects

Adaptive Server version 15.7 includes changes for large objects (LOBs), such as storing in-row LOB columns for small text, image, and untext datatypes, storing declared SQL statements containing LOBs, indirectly referencing a LOB in Transact-SQL statements, and allowing checking for null values of large objects.

In-Row Off-Row LOB

Adaptive Server 15.7 supports the storage of in-row LOB columns for `text`, `image`, and `untext` datatypes when they are small, and subject to available space in the page.

When a LOB expands in size or its space is used for other in-row columns (such as those used for `varchar` and `varbinary` datatypes), Adaptive Server seamlessly migrates the in-row LOB data to off-row storage, automatically replacing the data with an in-row text pointer.

In Adaptive Server 15.7, you can use:

- **create table** to specify in-row storage of LOB columns
- **alter table** to perform modifications of how LOB columns are stored
- **create database** or **alter database** commands to manage database-wide in-row lengths for LOB columns

See "In-Row, Off-Row LOB" in the *Transact-SQL Users Guide*.

Using Large Object text, unitext, and image Datatypes in Stored Procedures

Once they are declared, Adaptive Server stores SQL statements containing LOBs.

In Adaptive Server version 15.7 and later, you can:

- Declare a large object (LOB) `text`, `image`, or `unitext` datatype for a local variable, and pass that variable as an input parameter to a stored procedure.
- Prepare SQL statements that include LOB parameters.

See the *Reference Manual: Building Blocks*.

Using LOB Locators in Transact-SQL Statements

Large object (LOB) locators let you indirectly reference a LOB in Transact-SQL statements rather than referencing the LOB itself.

Because the size of a `text`, `unitext`, or `image` LOB can be many megabytes, using an LOB locator in Transact-SQL statements reduces network traffic between the client and Adaptive Server, and reduces the amount of memory otherwise needed by the client to process the LOB.

Adaptive Server 15.7 allows client applications to send and receive locators as host variables and parameter markers.

When you create a LOB locator, Adaptive Server caches the LOB value in its memory and generates an LOB locator to reference it.

After a LOB locator is created, it remains valid for the duration of the transaction in which it was created. Adaptive Server invalidates the locator when the transaction commits or is rolled back.

LOB locators use three different datatypes

- `text_locator` – for text LOBs
- `unitext_locator` – for unitext LOBs
- `image_locator` – for image LOBs.

See "Using and Creating Datatypes" in the *Transact-SQL Users Guide*.

Extension to where Clause for Large Objects

The `where` clause is extended to allow checking for null values of large objects.

See the *Reference Manual: Commands*.

Showing Cached Plans in XML

The `show_cached_plan_in_xml` function returns a `showplan` output in XML for a statement in cache.

You must enable the statement cache before using `show_cached_plan_in_xml`.

See "Displaying Query Optimization Strategies and Estimates" in the Performance and Tuning Series: *Query Processing and Abstract Plans*

Padding a Character Field Using str

In Adaptive Server version 15.7 the **decimal** parameter of the `str` function has been extended to allow a field to be padded with a specified character or numeric.

See the *Reference Manual: Building Blocks*.

Changes to select for update

Adaptive Server version 15.7 supports **select for update** to exclusively lock rows for subsequent updates within the same transaction, and for updatable cursors. This prevents other concurrent tasks from updating these rows and from blocking the subsequent update. **select for update** is supported at isolation levels 1, 2, and 3.

You can issue **select for update** as a language statement outside of a cursor context. With both language statements and cursors, you must execute **select for update** within a **begin transaction** command or in chained mode.

If you run **select for update** within a cursor context, the cursor **open** and **fetch** statements must be within the context of a transaction, otherwise, Adaptive Server reverts to pre-15.7 functionality.

See "Queries: Selecting Data from a Table" in the *Transact-SQL Users Guide*.

Creating Nonmaterialized, Non-null Columns

Adaptive Server version 15.7 allows you to create nonmaterialized, non-NULL columns.

Nonmaterialized columns exist virtually, but are not physically stored in the row. Use nonmaterialized columns the same as any other column, selecting, updating, and referring to them in SQL queries, or using them as index keys.

Adaptive Server treats nonmaterialized columns similar to the way it treats null columns: if a column is not physically present in the row, Adaptive Server supplies a default. The default for a nullable column is null, but the default for a nonmaterialized column is a user-defined non-NULL value.

See "Adding, Changing, Transferring, and Deleting Data" in the *Transact-SQL Users Guide*.

Sharing Inline Defaults

Adaptive Server 15.7 supports sharing inline defaults between different tables if the tables are in the same database.

Before creating a new inline default, Adaptive Server looks for an existing shareable inline default having the same value in the database belonging to the same user. If Adaptive Server finds an existing shareable default, it binds this object to the column instead of creating a new default. However, if Adaptive Server does not find an existing shareable inline default, it creates a new default.

Adaptive Server cannot share inline defaults in `tempdb`.

See "Defining Defaults and Rules for Data" in the *Transact-SQL Users Guide*.

Retain Monitoring Data

Adaptive Server version 15.7 does not store the descriptors for some objects in the metadata cache. Instead, it retains monitoring data stored in the descriptors, thus improving query performance.

The metadata cache is a limited resource and can hold a limited number of object descriptors. Adding descriptors to the cache may cause other descriptors to be flushed from the cache.

Adaptive Server discards the descriptor for an object that is not already in the cache, instead of consuming resources when you run these functions:

- `data_pages`
- `used_pages`

New Features in Adaptive Server Version 15.7

- reserved_pages
- object_id
- row_count
- datachange
- derived_stat

See the *Reference Manual: Building Blocks*.

Analyze Dynamic Parameters

Adaptive Server version 15.7 allows you to analyze dynamic parameters (which are indicated by question marks) before running a query, helping you avoid inefficient query plans.

Analyze the dynamic parameters using:

- `@@lwpid` global variable – returns the object ID of the most recently prepared lightweight procedure that corresponds to a dynamic SQL prepare statement.
- `@@plwpid` global variable – returns the object ID of the next most recently prepared lightweight procedure that corresponds to a dynamic SQL prepare statement.
- `show_dynamic_params_in_xml` – displays information about parameters in dynamic SQL statements.

Using the value provided by `@@plwpid` as the value for the `show_dynamic_params_in_xml` `object_id` parameter, Adaptive Server displays information about the dynamic parameters in the query. Continue refining the query plan until you determine the parameters that provide you with the best query plan.

See "Displaying Query Optimization Strategies and Estimates" in the *Performance and Tuning Series: Query Processing and Abstract Plans*.

Monitor Lock Timeouts

Adaptive Server version 15.7 allows you to monitor lock timeouts.

Adaptive Server version 15.7 adds this information for tracking locks:

- The `monLockTimeouts` monitoring table provides information about timeout lock requests, such as lock types, owners, locks status, and so on. See the *Reference Manual: Tables*
- These parameters configure Adaptive Server to collect lock wait timeout information and make it available for the `monLockTimeout` table:
 - `lock timeout pipe active`
 - `lock timeout pipe max messages`

See "Setting Configuration Parameters" in the *System Administration Guide, Volume 1*.

Truncate Trailing Zeros

Adaptive Server version 15.7 includes the **disable varbinary truncation** configuration parameter, which enables or disables the truncation of trailing zeros from varbinary and binary null data.

By default, **disable varbinary truncation** is off for the server.

See "Adding, Changing, Transferring, and Deleting Data" in the *Transact-SQL Users Guide*.

Fully Recoverable DDL

Adaptive Server version 15.7 allows you to use **dump transaction** to fully recover the operations that earlier versions of Adaptive Server minimally logged.

These operations are recoverable with **dump transaction**:

- **select into**
- **alter table** commands that require data movement
- **reorg rebuild**

Run **sp_dboption** in the master database to fully log commands that are, by default, minimally logged.

See the *Reference Manual: Commands*.

Transfer Rows from Source to Target Table Using merge

Adaptive Server 15.7 introduces a **merge** command, which allows you to transfer rows from a source table into a target table

See the *Reference Manual: Commands*.

View Statistics and Histograms with sp_showoptstats

sp_showoptstats allows you to extract and display, in an XML document, statistics and histograms for various types of data objects from system tables such as systabstats and sysstatistics.

See the *Reference Manual: Procedures* and "Statistics Tables and Displaying Statistics with optdiag" in the *Performance and Tuning Series: Improving Performance with Statistical Analysis*.

Changes to Cursors

Adaptive Server version 15.7 includes changes to cursor locks, how cursors manage transactions, and how it declares cursor statements.

Release Cursor Locks at Cursor Close

Adaptive Server 15.7 includes the **declare cursor ... release_locks_on_close** option to release cursor locks at isolation levels 2 and 3 when the cursor is closed, even if the transaction is active.

See the *Reference Manual: Commands* and "Cursors: Accessing Data" in the *Transact-SQL Users Guide*.

Enhanced Transaction Support for Cursors

Adaptive Server 15.7 and later changes the way cursors support transactions:

Adaptive Server:

- Does not automatically close an open cursor declared with a **for update** clause if you commit a transaction. To close a read-only cursor when a transaction is committed, set the **close on end tran** option
- Supports **fetch** operations on open cursors after the transaction has been committed

See the *Reference Manual: Commands* and "Cursors: Accessing Data" in the *Transact-SQL Users Guide*.

Monitor Cursor Statements

Adaptive Server version 15.7 monitors cursor statements based information from the monCachedStatement monitoring table.

For example, although you declare the new_cursor cursor (specified by "sq0267364184_1108036110ss"), **sp_cursorinfo** does not display its plan:

```
declare new_cursor cursor for select id from sysroles
go
sp_cursorinfo
go
Cursor name 'new_cursor' is declared on procedure
'*sq0267364184_1108036110ss*'
The cursor is declared as NON-SCROLLABLE cursor.
The cursor id is 983044.
The cursor has been successfully opened 0 times.
The cursor will remain open when a transaction is committed or rolled
back.
The number of rows returned for each FETCH is 1.
The cursor is updatable.
This cursor is declared on a stored procedure. It is presently using
```

```
'860'
bytes. However, the memory usage will increase when the cursor is
opened because
the query plan will be associated with the cursor at that time.
```

Adaptive Server compiles cursors when you open them.

Use the **enable functionality group** configuration parameter to enable and disable monitoring cursor statements.

See "Cursors: Accessing Data" in the *Transact-SQL Users Guide*.

Nested select Statement Enhancements

Adaptive Server 15.7 expands the abilities of the asterisk (*).

In Adaptive Server 15.7 and later, you can use an asterisk in a nested **select** statement that is not an **exists** subquery as long as the asterisk:

- Is the only item in the **select** statement
- Resolves to a single table column for the nested query

In addition, you can:

- Restrict the selected columns in your nested query to only those belonging to a specific table by using the *qualifier.** format, where *qualifier* is one of the tables in the **from** clause.
- Use the asterisk in a nested query that includes a **group by** clause.

When an asterisk resolves to a single table column for the nested query, the query is equivalent to explicitly using a single table column.

See "Queries: Selecting Data from a Table" in the *Transact-SQL Users Guide*.

Changes to Commands and System Procedures in Chained Transaction

Adaptive Server versions 15.7 allows some system procedures to run in sessions that use chained transaction mode.

- These system procedures can run in sessions using chained transaction mode if there are no open transactions:
 - **sp_configure**
 - **sp_engine**
 - **sp_rename**
- These system procedures can run in sessions using chained transactions after you use **sp_procxmode** to change the transaction mode to **anymode**:

- **sp_addengine**
- **sp_dropengine**
- **sp_showplan**
- **sp_sjobcontrol**
- **sp_sjobcmd**
- **sp_sjobcreate**
- **sp_sjobdrop** can run in sessions using chained transaction mode, but fails if you execute it during an open transaction.

When you execute these stored procedures, Adaptive Server implicitly commits the changes performed by these stored procedures when there are no open transactions, so you need not issue a **commit** or **rollback**.

If an open transaction exists when you issue:

- **sp_rename**, **sp_configure**, **sp_engine**, **sp_addengine**, or **sp_dropengine** – the procedures fail with error 17260 because they cannot run within a transaction.
- **sp_sjobcontrol**, **sp_sjobcmd**, **sp_sjobcreate**, **sp_sjobdrop**, or **sp_showplan** – Adaptive Server leaves the transaction open after the procedure executes. You must explicitly issue **commit** or **rollback** for the entire transaction. If these procedures receive an error when they execute, they roll back only the operations performed inside the procedure, but do not roll back the operations performed before they execute, even though the operations are performed in the same transaction.

Use **set chained {on | off}** to set the chained mode for the session.

See the *Reference Manual: Commands* and the *Reference Manual: Procedures*.

Expanded Variable-Length Rows

Adaptive Server version 15.7 redefines data-only locked (DOL) columns to use a row offset of up to 32767 bytes. You must configure Adaptive Server for a logical page size of 16K to create wide, variable-length DOL rows.

By default, Adaptive Server does not use wide, variable-length DOL rows. Enable wide, variable-length DOL rows for each database using:

```
sp_dboption database_name, 'allow wide dol rows', true
```

See "Data Storage" in the *Performance and Tuning Series: Physical Database Tuning*.

Changes to like Pattern Matching

Adaptive Server version 15.7 allows you to treat square brackets individually in the `like` pattern-matching algorithm.

For example, matching a row with `'[XX]'` in earlier versions of Adaptive Server required you to use:

```
select * from t1 where f1 like '[][]XX[]'
```

However, in Adaptive Server 15.7, you can also use:

```
select * from t1 where f1 like '[][]XX'
```

Changes to Quoted Identifiers

In Adaptive Server 15.7 and later, you can use quoted identifiers for tables, views, column names, index names, and system procedure parameters.

In versions earlier than 15.7, Adaptive Server treated “ident” as an identifier that used nonalphanumeric characters delimited with double quotes (quoted identifiers) or square brackets. These identifiers could be used only for table, view, and column names.

See the *Reference Manual: Blocks*.

Allowing Unicode Noncharacters

In Adaptive Server version 15.7, the **enable permissive unicode** configuration parameter, which is a member of **enable functionality group**, allows you to ignore Unicode noncharacters.

When you enable this feature, Unicode noncharacters are not detected in:

- Parameters
 - Presented as `univarchar` and `unitext` (UTF-16) datatypes
 - Presented as `varchar` and `text` (UTF-8) datatypes
 - As parameters to dynamic SQL statements
 - As input to parameterized language statements
 - As input to parameterized language statements
- String literals when the server’s character set is UTF-8
- Escaped string literals (those prefixed with `U&`), regardless of the server’s character set
- Conversion processes between `unichar` (UTF-16) and `varchar` (UTF-8) in either direction

New Features in Adaptive Server Version 15.7

In addition, Unicode noncharacters are acceptable in simple expressions such as comparisons, where they sort higher than legal Unicode characters.

In versions of Adaptive Server earlier than 15.7, the `unichar`, `univarchar`, `unitext`, `char`, `varchar`, and `text` datatypes under the utf-8 default character set did not accept Unicode noncharacters (code points permanently reserved for internal use).

See "Setting Configuration Parameters" and "Configuring Client/Server Character Set Conversions" in the *System Administration Guide, Volume 1*.

Reduce Query Processing Latency

The query processing layer in Adaptive Server 15.7 enables multiple client connections to reuse or share dynamic SQL lightweight procedures (LWPs).

Adaptive Server uses the statement cache to store dynamic SQL statements converted to LWPs. Because the statement cache is shared among all connections, dynamic SQL statements can be reused across connections. These statements are not cached:

- **select into** statements.
- **insert-values** statements with all literal values and no parameters.
- Queries that do not reference any tables
- Individual prepared statements that contain multiple SQL statements. For example

```
statement.prepare('insert t1 values (1) insert
t2 values (3)');
```
- Statements that cause **instead-of** triggers to fire

Use the **streamlined dynamic SQL** or **enable functionality group** configuration parameters to enable this feature.

See "Memory Use and Performance" in the *Performance and Tuning Series: Basics* and "Setting Configuration Parameters" in the *System Administration Guide, Volume 1*.

The sybdiag Utility

Adaptive Server 15.7 adds the **sybdiag** utility, a Java-based tool that collects comprehensive Adaptive Server configuration and environment data. Sybase Technical Support uses this information to diagnose server issues, thus expediting customer cases.

sybdiag connects to an Adaptive Server and executes system procedures such as **sp_configure** and queries to tables like `monLicense`. It collects operating system and platform diagnostic information by executing commands such as **ps**, **vmstat**, and **netstat**.

sybdiag generates a `.zip` output file comprising HTML and data files that can be unzipped and viewed in a Web browser. The information collected includes operating system and

environment data, Adaptive Server configuration and monitoring data, and Adaptive Server files and scripts.

sybdiag does not collect Adaptive Server or operating system data for logins, passwords, or user lists, and does not collect information from application database tables.

See the *Utility Guide*.

The Optimizer Diagnostic Utility

Adaptive Server version 15.7 includes the **sp_opt_querystats** system procedure, which allows you to analyze the query plan generated by the Adaptive Server optimizer and the factors that influenced its choice of a query plan.

This analysis helps determine if elements in the query or the execution environment affect how Adaptive Server executes the query and its performance. You need not run the selected query to perform the analysis.

sp_opt_querystats provides this information:

- The query plan generated by showplan
- Enabled traceflags and switches
- I/O activity for the query generated by set statistics io
- Missing statistics found for any of the tables involved in the query
- The estimated plan cost calculated by the optimizer
- The final plan and cost estimations calculated by the optimizer
- The abstract plan for the query
- The result of the query if the result set is executed (for example, if noexec is not on)
- The logical operator tree for the query generated by set option show
- Query execution time generated by **set statistics time**
- After you execute the query, the query execution time generated by set statistics time

You must install and configure the Job Schedule to run **sp_opt_querystats**.

See "Controlling Optimization" in the *Performance and Tuning Series: Query Processing and Abstract Plans*.

System Changes in Adaptive Server Version 15.7

Adaptive Server 15.7 includes changes to commands, functions, system procedures, configuration parameters, system tables, monitoring tables, and global variables.

Commands

Adaptive Server 15.7 contains new and changed commands.

Table 1. New commands

Command	Description
alter login	Changes the attributes of a login account
alter login profile	Changes the attributes of a login profile
alter...modify owner	Transfers the ownership of database objects from one owner to another
alter thread pool	Alters a thread pool
create login	Creates a login account; specifies a password, a login profile for the account, and user-supplied parameters to be assigned to the account
create login profile	Creates a login profile with specified attributes
create thread pool	Creates a user-defined thread pool
deallocate locator	Deletes a large object (LOB) stored in memory and invalidates its LOB locator
drop login	Drops a login account or list of accounts
drop login profile	Drops a login profile or list of login profiles
drop thread pool	Drops a user-defined pool
merge	Transfers rows from a source table into a target table
select for update	Exclusively locks rows for subsequent update within the same transaction
truncate lob	Truncates a LOB to a specified length

Table 2. Changed commands

Command	Change
alter database changes	<ul style="list-style-type: none"> • allows you to change the compression setting at the database level • alter database .. inrow_LOB_length – allows you to change the length of in-row LOB columns database-wide • alter database ... log off – removes unwanted portions of a database log, allowing you to shrink log space and free storage without re-creating the database
alter encryption key	<ul style="list-style-type: none"> • master and dual master – indicate you are altering a master or dual master encryption key • master key – indicates you are altering the encryption key with the master key • [no] dual_control – indicates whether the new key is encrypted using dual control. • for recovery – indicates the key copy will be used to recover the master key in case of a lost password • for automatic_startup – indicates the key copy will be used to access the master or dual master key after the server starts • regenerate key – replaces the raw key value for the master or dual master keys with a new raw key, and re-encrypts all column encryption keys encrypted by the master or dual master keys
alter table	<ul style="list-style-type: none"> • allows you to change the compression attributes for tables, columns, and partitions. • alter table ... not materialized – indicates you are creating a non-materialized column • alter table ... add lob-colname – allows you to define newly added nullable LOB columns as in-row, and specify its length • alter table ... modify lob-colname - allows you to modify an existing LOB column from off-row to in-row
Concatenation operators	<p>The + and Transact-SQL operators accept LOB locators as expressions for a concatenation operation. The result of a concatenation operation involving one or more locators is a new LOB locator with the same datatype as that referenced by the input locator.</p>

Command	Change
create database	<ul style="list-style-type: none"> • compression = indicates the level of compression to be applied to newly created tables or partitions. • lob_compression = value – Determines the compression level for the newly created table. Selecting off means the table does not use LOB compression. • inrow_lob_length = value – specifies the number of bytes. The range of valid values for inrow_lob_length is 0 through the logical page size of the database.
create encryption key	<ul style="list-style-type: none"> • master and dual master – indicate you are creating a master or dual master encryption key • passwd system_encr_passwd master key – indicates you are using system encryption password or the master key for the password • [no] dual_control – indicates whether the new key is encrypted using dual control.
create table ... [in row [(length)] off row]	allows you to create a compressed table create table lets you specify that the data in a LOB column be kept in the row, instead of stored off-row.
declare cursor ... [release_locks_on_close]	Allows you to configure the lock-releasing behavior of each cursor so that the shared locks can be released when the cursor is closed, even if the transaction is active.
drop encryption key	[dual] master – indicates you are dropping a master or dual master key
dump database ... with shrink_log	Allows you to remove any holes at the end of a database, regardless of whether the database is in a dump sequence.
like clause in a where clause	where clause accepts text and unitext LOB locators, but not image LOB locators, for the <i>variables</i> expression and <i>match_string</i> .
select into ... [in row [(length)] off row]	Sets or changes the in-row characteristics for the text columns in the target table. If you do not specify length, Adaptive Server uses the configured default in-row length.

Command	Change
set	<p>set adds</p> <ul style="list-style-type: none"> • send_locator [on off] – specifies whether Adaptive Server sends the LOB or the locator that references the LOB in a result set sent to the client. • cis_rpc_handling {on off} – makes CIS the remote procedure call (RPC) handling mechanism the default mechanism for Shared Disk Cluster (SDC) handling • encryption passwd <char_literal> for key [dual] master – sets the password for the master or dual master key
where clause extension to support LOBs	where clauses in select, insert, update, and delete statements can include a condition for null large objects (LOBs).

See the *Reference Manual: Commands*.

Functions

Adaptive Server 15.7 contains new and changed functions.

Table 3. New functions

Function	Description
dol_downgrade_check	Returns the number of data-only-locked (DOL) tables in the specified database that contain variable-length columns wider than 8191 bytes
create_locator	Explicitly creates a locator for a specified large object (LOB)
locator_literal	Identifies a binary value as a locator literal
locator_valid	Determines whether a LOB locator is valid
lprofile_id	Returns the login profile ID for the specified login profile name, or the login profile ID for the login profile associated with the current login or specified login name
lprofile_name	Returns the login profile name for the specified login profile ID, or the login profile name for the login profile associated with the current login or specified login name
return_lob	Dereferences a locator, and returns the LOB referenced by that locator
setdata	Overwrites some or all of a LOB

Function	Description
show_cached_plan_in_xml	Displays, in XML, the executing query plan for queries in the statement cache
show_dynamic_params_in_xml	Returns the text of a query in XML format

Table 4. Changed functions

Function	Description
charindex	charindex adds support for the <code>text_locator</code> , <code>unitext_locator</code> , and <code>image_locator</code> LOB locator datatypes and the start option.
charlength	charlength supports the <code>text_locator</code> and <code>unitext_locator</code> datatypes.
datalength	datalength accepts the <code>text_locator</code> , <code>unitext_locator</code> , and <code>image_locator</code> datatypes.
patindex	patindex accepts the <code>text_locator</code> and <code>unitext_locator</code> datatypes.
show_cached_plan_in_xml	show_cached_plan_in_xml expands the scope of the statement_id parameter to accept object IDs that refer to any lightweight procedure, not only those in the statement cache.
str	The decimal parameter of the str function has been expanded to support padding of the output with a character or numeric to the specified length.
textptr	<p>Because the in-row/off-row LOB feature can split or shrink the data page of an allpages-locked table with a clustered index, causing data rows—including in-row LOB columns that reside in those data rows—to move to different pages, the textptr text pointer value of such in-row LOB columns before the split or shrink operation differs from that of the same column after such an operation.</p> <p>For Adaptive Server 15.7 and later, the textptr value returned for an in-row LOB column residing in a data-only-locking data row that is row-forwarded remains unchanged and remains valid after the forwarding.</p>
textvalid	You can use textvalid on the returned text pointer for both in-row and off-row LOBs, returning 1 if the text pointer points to a valid LOB column, and 0 if the LOB column is invalid.

See the *Reference Manual: Building Blocks*.

System Stored Procedures

Adaptive Server 15.7 contains new and changed system procedures.

Table 5. New system stored procedures

System stored procedures	Description
sp_merge_dup_inline_default	Removes existing duplicate inline default objects, converting the unique inline defaults to sharable inline default objects
sp_opt_querystats	Returns a performance analysis for the selected query
sp_securityprofile	Lists the attributes or bindings associated with a login profile
sp_showoptstats	Extracts and displays statistics and histograms for various data objects from system tables such as systabstats and sysstatistics

Table 6. Changed system stored procedures

System stored procedures	Description
sp_dboption	<ul style="list-style-type: none"> • enforce dump tran sequence – prevents operations that disallow a subsequent dump transaction • allow wide rows –configures databases to allow wide, variable-length data-only locked (DOL) rows • full logging for all – fully log commands that are minimally logged by default (select into, alter table, and reorg rebuild)

System stored procedures	Description
sp_displaylogin	<p>Displays</p> <ul style="list-style-type: none"> • The login profile name associated with a login account. • The name of the default login profile if there is no login profile directly associated with the login account but there is a default login profile <p>The login overrides the sp_addlogin and sp_modifylogin default database, default language, authenticate with and login script parameters.</p> <p>If login profiles are ignored, or there is no login profile associated to the login account either directly or through a default login profile, sp_displaylogin displays information in the format of versions earlier than 15.7.</p>
sp_displayroles	<ul style="list-style-type: none"> • When run against the current login, sp_displayroles displays the roles granted to the login profile to which it is associated. sp_displayroles requires the <code>sso_role</code> to view the roles associated with other login profiles. • Displays the roles granted to logins through an associated login profile. A <code>Grantee</code> column in the output indicates the login profile name, as applicable. sp_displayroles displays the <code>Grantee</code> column only if the login has an associated login profile with roles granted to it. • Displays the date when the role was locked, the reason for the lock, and the login ID that locked the role. For password protected roles, sp_displayroles displays the role password encryption version.

System stored procedures	Description
sp_encryption	<ul style="list-style-type: none"> • When run by the SSO, key custodian, or the DBO, reports that a key is protected by dual control • sp_encryption helpkey, master and sp_encryption helpkey, 'dual master' report information about the master and dual master keys, including the existence of a copy encrypted for automatic startup and the existence of a recovery copy • mkey_startup_file [, {<new_path> default_location null} [, {sync_with_mem sync_with_qrm}] – displays or sets the master key startup file name and path • downgrade_kek_size [, {"true" "false"}] – displays or sets downgrade_kek_size configuration for the server
sp_help	Displays compression settings at column, table, and partition level. Displays the in-row LOB settings at the column and table level.
sp_helpconstraint	Updated to display information about shareable inline defaults
sp_helprotect	<ul style="list-style-type: none"> • Accepts 'master key' and 'dual master key' as object names • Accepts 'Set Encryption Passwd' as a valid permission name • Displays dual and master key permissions
sp_helpuser	<i>display_object</i> lists all objects and user-defined datatypes owned by <i>name_in_db</i> in the current database
sp_locklogin	Exempted login accounts are no longer locked because of inactivity.

System stored procedures	Description
sp_passwordpolicy	<ul style="list-style-type: none"> • keypair regeneration period – specifies the date and time to start the first keypair generation and subsequent frequency of keypair regeneration • keypair error retry wait/count – specifies the various configurations you can set for regenerating a key pair after a failed attempt
sp_serveroption	<p>Changes the definition for these options:</p> <ul style="list-style-type: none"> • use message confidentiality – Sets message confidentiality for all connections to the remote server using Kerberos authentication • use message integrity – Sets message integrity for all connections to the remote server using Kerberos authentication

See the *Reference Manual: Procedures*.

Configuration Parameters

Adaptive Server 15.7 introduces new configuration parameters.

Configuration parameter	Description
automatic master key access	Determines Adaptive Server operates in unattended startup mode
capture compression statistics	Enables the monTableCompression monitoring table to begin capturing compression statistics
column default cache size	Determines the size of the cache that Adaptive Server must keep in memory to provide defaults for nonmaterialized columns
compression info pool size	Determines the size of the memory pool used for compression
disable varbinary truncation	Controls whether Adaptive Server includes trailing zeros at the end of varbinary or binary null data

Configuration parameter	Description
enable console logging	Once enabled, Adaptive Server sends messages to the console separately from the error log after startup
enable functionality group	Enables or disables these features in Adaptive Server versions 15.7 and later: <ul style="list-style-type: none"> • Shareable inline defaults • Select for update • Like pattern matching • Quoted identifiers • Unicode noncharacters • Monitor cursor statements • Reduce query processing latency
enable hp posix async i/o	Enables asynchronous I/O on HP-UX 11.31 and later
kernel mode	Determines the mode the Adaptive Server kernel uses, threaded or process
kernel resource memory	Determines the size, in 2K pages, of the kernel resource memory pool from which all thread pools and other kernel resources are allocated memory
lock timeout pipe active	Controls whether Adaptive Server collects lock timeout messages
lock timeout pipe max messages	Determines the number of lock timeout messages Adaptive Server stores, and the amount of memory it allocates for the task
number of disk tasks	Controls the number of tasks dedicated to polling and completing disk I/Os
number of network tasks	Controls the number of tasks dedicated to polling and completing network I/Os

See the *System Administration Guide: Volume 1*

System Tables

Adaptive Server 15.7 contains new and changed system tables.

Table 7. Changed system tables

System table	Column added	Description
sysattributes	<ul style="list-style-type: none"> object_cinfo2 object_date-time 	<ul style="list-style-type: none"> Provides a character description for the object Provides the date and time for the object <i>sysattributes</i> adds the SP object_type, which stores options related to RSA Key pair regeneration and LR object_type, which stores options related to login profiles
sysdatabases		Adds status bits to the <code>status4</code> column to indicate database-wide compression settings
sysoptions	number	Lists the switch ID as an integer
sysobjects	lobcomp_lvl	<ul style="list-style-type: none"> Adds status bits to the <code>status3</code> column to indicate database-wide compression settings <code>lobcomp_lvl</code> – compression level of the columns defined for large objects.
syscolumns	inrowlen	<ul style="list-style-type: none"> Adds status bits to the <code>status2</code> column to indicate if a column is explicitly defined as compressed <code>inrowlen</code> – a nullable column that stores the user-specified, or derived in-row length for LOB columns created as in-row <code>lobcomp_lvl</code> – compression level of the columns defined for large objects.

System Changes in Adaptive Server Version 15.7

System table	Column added	Description
syslogins	crsuid	Server user ID of the creator of login or login profile
syslogins	lpid	Login profile ID
sysrvroles	<ul style="list-style-type: none"> lockdate lockreason locksuid 	<ul style="list-style-type: none"> Date and time a role was locked Reason a role was locked ID of the user who locked the role
sysservers	srvprincipal	Specifies the remote server Kerberos principal name
syscomments	<ul style="list-style-type: none"> syb_syscomm-key_ddddd 	

Adaptive Server version 15.7 adds these system tables, which are views of the master database and provide information about the configuration of data caches and pools.

System table	Description
syscacheinfo	Provides information about data caches.
syspoolinfo	Provides information about cache pools.
syscachepoolinfo	Provides a row for each data cache pool that includes configuration information for the data cache. This view is a join between the <i>syscacheinfo</i> and <i>syspoolinfo</i> views.

See the *Reference Manual: Tables*

Utilities

Adaptive Server 15.7 contains new and changed utilities.

New utilities

Command	Description
sybdiag	sybdiag is a Java-based tool that collects comprehensive Adaptive Server configuration and environment data. Sybase Technical Support uses this information to diagnose server issues, thus expediting customer cases.

Changed utilities

Command	Description
sybperf	The 15.7 version of sybperf exposes a set of Adaptive Server counters that are more useful for monitoring Adaptive Server performance.

Monitoring Table Changes

Adaptive Server version 15.7 contains new and changed monitoring tables.

New Monitoring Tables

Adaptive Server version 15.7 includes new monitoring tables.

Command	Description
monDeviceSpaceUsage	Provides information about the file systems on which database devices are allocated. Space information is available only for file system devices. File system size and free space values are NULL for database devices allocated on raw devices.
monLockTimeout	Provides information about lock timeout requests

See the *Reference Manual: Tables*.

Changes to Monitoring Tables

Adaptive Server version 15.7 includes changes to some monitoring tables.

Changes to monCachePool

Monitoring table	Description
LogicalReads	Number of buffers read from the pool
PhysicalWrites	Number of write operations performed for data in this pool (one write operation may include multiple pages)
APFReads	Number of APF read operations that loaded pages into this pool
APFPercentage	The configured asynchronous prefetch limit for this pool

Monitoring table	Description
WashSize	The wash size, in kilobytes, for a memory pool

Changes to monCachedProcedures

Monitoring table	Description
ExecutionCount	Number of times Adaptive Server executed the stored procedure plan or tree since it was cached
CPUTime	Total number of milliseconds of CPU time used
ExecutionTime	Total amount of elapsed time (in milliseconds) Adaptive Server spent executing the stored procedure plan or tree
PhysicalReads	Number of physical reads performed
LogicalReads	Number of pages read
PhysicalWrites	Number of physical writes performed
PagesWritten	Number of pages written

Changes to monCachedStatement

Monitoring table	Description
OptimizationGoal	Optimization goal stored in the statement cache
OptimizerLevel	Optimizer level stored in the statement cache

Changes to monCachedProcedures

Monitoring table	Description
Status	Status of the cache
Type	Type of cache
CacheSize	Total size of cache, in kilobytes
ReplacementStrategy	Cache replacement strategy
APFReads	Number of asynchronous prefetch (APF) reads for this data cache
Overhead	Cache overhead

Columns added to monDeadLock

Column	Description
HeldClientAppName	Value for the <i>clientapplname</i> property set by the application holding the lock
HeldClientName	Value of the <i>clientname</i> property set by the application holding the lock
HeldClientHostName	Value for the <i>clienthostname</i> property set by the application holding the lock
HeldHostName	Name of the host machine on which the application that executed the query holding the lock is running
HeldNumLocks	Number of locks currently held by holding spid
HeldProcDBName	Name of the database in which the stored procedure was executing the blocking process at the time the deadlock occurred, if applicable
HeldProcedureName	Name of the stored procedure the blocking process was executing at the time the deadlock occurred, if applicable
HeldProgramName	Name of program running the process that holds the lock
HeldStmtNumber	Statement number in the SQL batch of the SQL statement holding the lock
ObjectDBName	Name of the database
ObjectID	Unique identifier for the object
WaitAppName	Name of the application waiting for the lock
WaitBatchID	Identifier of the SQL batch executed by the process waiting for the lock when the lock timeout occurred
WaitClientAppName	Value of the <i>clientapplname</i> property set by the application waiting for the lock
WaitClientHostName	Value of the <i>clienthostname</i> property set by the application waiting for the lock

System Changes in Adaptive Server Version 15.7

Column	Description
WaitClientName	Value of the <i>clientname</i> property set by the application waiting for the lock
WaitCommand	Category of process or command that the process was executing when it was blocked and then timed out
WaitContextID	Unique context identifier for the process waiting for the lock when it was blocked by another process
WaitHostName	Name of the host running the process waiting for the lock
WaitLineNumber	Line number of the SQL statement in the SQL batch or stored procedure waiting for the lock
WaitProcDBID	Unique identifier for the database in which the stored procedure waiting for the lock resides, if applicable
WaitProcDBName	Name for the database where the stored procedure that is waiting for the lock resides, if applicable
WaitProcedureID	ID of the stored procedure waiting for the lock, if applicable
WaitProcedureName	Name for the stored procedure waiting for the lock, if applicable
WaitProgramName	Name of the program running the process
WaitStmtNumber	Line number in SQL batch waiting for the lock
WaitTranName	Name of the transaction in which the lock was requested

Changes to monErrorLog

Adaptive Server version 15.7 and later change the value for stack traces in the `monErrorLog.Severity` column. Earlier versions used 0 as a value for stacktraces. In Adaptive Server version 15.7, all rows representing stack traces have a Severity value of 99.

Changes to monLockTimeout

Monitoring table	Description
HeldProgramName	Removed from monLockTimeout
WaitProgramName	Removed from monLockTimeout
HeldProcedureID	Unique object identifier for the stored procedure that the blocking process was executing when the timeout occurred
WaitProcedureID	Unique object identifier for the stored procedure that is waiting for the lock, if applicable

Changes to monOpenObjectActivity

Monitoring table	Description
SharedLockWaitTime	The total amount of time, in milliseconds, that all tasks spent waiting for a shared lock
ExclusiveLockWaitTime	The total amount of time, in milliseconds, that all tasks spent waiting for an exclusive lock
UpdateLockWaitTime	The total amount of time, in milliseconds, that all tasks spent waiting for an update lock
ObjectCacheDate	Indicates the date and time when the object was added to the cache

Changes to monOpenPartitionActivity

Monitoring table	Description
ObjectCacheDate	Indicates the date and time when the object was added to the cache

Changes to monProcess

Monitoring table	Description
ProgramName	Name of the program on which the process is running
HostName	Name of the host machine on which the application that started the process is running

Monitoring table	Description
ClientName	Value of the <i>clientname</i> property set by the application
ClientHostName	Value of the <i>clienthostname</i> property set by the application
ClientAppName	Value of the <i>clientapplname</i> property set by the application

Changes to monProcessActivity

Monitoring table	Description
ProgramName	Name of the program on which the process is running
HostName	Name of the host machine on which the application that executed the query is running
Application	Name of the application
ClientName	Value of the <i>clientname</i> property set by the application
ClientHostName	Value of the <i>clienthostname</i> property set by the application
ClientAppName	Value of the <i>clientapplname</i> property set by the application

Changes to monProcessLookup

Monitoring table	Description
ProgramName	Name of the program on which the process is running
ClientName	Value of the <i>clientname</i> property set by the application
ClientHostName	Value of the <i>clienthostname</i> property set by the application
ClientAppName	Value of the <i>clientapplname</i> property set by the application

Changes to monProcessProcedures

Monitoring table	Description
ExecutionCount	Number of times Adaptive Server executed this instance of the stored procedure held in the procedure cache
CPUTime	The amount of CPU time, in milliseconds, that Adaptive Server spent executing the instance of this stored procedure held in the procedure cache
ExecutionTime	Total amount of time, in milliseconds, Adaptive Server spent executing the instance of this stored procedure held in the procedure cache
PhysicalReads	Number of physical reads performed by the instance of this stored procedure held in the procedure cache
LogicalReads	Number of logical reads performed by the instance of this stored procedure held in the procedure cache
PhysicalWrites	Number of physical writes performed by the instance of this stored procedure held in the procedure cache
PagesWritten	Number of pages read by the instance of this stored procedure held in the procedure cache

Changes to monTableColumns

monTableColumns includes these changes:

- Adaptive Server versions 15.7 and later include the column's unit of measurement in the Description column of monTableColumns.
- monTableColumn adds the Label column (datatype varchar(50)), which contains a brief description of the data presented in the column. You can use these values in application user interfaces instead of the actual column names.

Changes to monTables, monTableColumns, monWaitEventInfo, and monWaitClassInfo

These monitoring tables add the Language column (datatype varchar(30)), which allows you to specify the language in which Adaptive Server returns the values of the Description column and the monTableColumns.Label column.

See the *Reference Manual: Tables*.

Global Variables

Adaptive Server version 15.7 includes new global variables.

Command	Description
@@plwpid	Returns the object ID of the most recently prepared lightweight procedure
@@lwpid	Returns the object ID of the next most recently run lightweight procedure

See the *Reference Manual: Building Blocks*

New Features in Adaptive Server Version 15.5 Cluster Edition

Adaptive Server® 15.5 Cluster Edition introduces multiple simultaneous failover, distributed transaction management, the **mount** and **unmount** commands, and the ability to use **alter database** to add space to an archived database.

Note: The Cluster Edition does not currently support in-memory databases, relaxed-durability databases, template databases, or minimally-logged DML.

Adaptive Server 15.5 Cluster Edition Feature and Platform Matrix

The feature and platform matrix shows feature availability for supported operating systems in Adaptive Server 15.5 Cluster Edition. A “Y” indicates the feature is supported for that platform.

Adaptive Server Cluster Edition options	HP-UX Itanium 64-bit	IBM AIX 64-bit	Linux Opteron 64-bit	Solaris 64-bit
Security and directory services	Y	Y	Y	Y
Cybersafe Kerberos				Y
Pluggable Authentication Module	Y	Y	Y	Y
Fine-grained access control	Y	Y	Y	Y
LDAP server directory	Y	Y	Y	Y
LDAP user authentication	Y	Y	Y	Y
Platform Native Kerberos				Y
Secure Sockets Layer	Y	Y	Y	Y
MIT Kerberos	Y	Y	Y	Y

Adaptive Server Cluster Edition options	HP-UX Itanium 64-bit	IBM AIX 64-bit	Linux Opteron 64-bit	Solaris 64-bit
Encrypted columns, including fine-grained access control (FGAC)	Y	Y	Y	Y
High availability				
Partitions	Y	Y	Y	Y
In-memory databases				
Tivoli Storage Manager for Backup Server	Y	Y	Y	Y
Active messaging	Y	Y	Y	Y
Enhanced Full-Text Search (EFTS)				
<i>Features included in base Adaptive Server</i>				
Cross-platform dump and load	Y	Y	Y	Y
Job Scheduler	Y	Y	Y	Y
Native XML	Y	Y	Y	Y
IPv6	Y	Y	Y	Y
Java option	Y	Y	Y	Y
Web Services	Y	Y	Y	Y
Distributed transaction management	Y	Y	Y	Y
Content management (external file support)	Y	Y	Y	Y
Archived database access	Y	Y	Y	Y

Multiple simultaneous failover

Adaptive Server Cluster Edition version 15.5 and later support multiple simultaneous instance failures.

Multiple simultaneous failure support occurs when more than one instance fails within a single cluster view, but the cluster remains online and provides the same failover recovery as it does when a single instance fails.

The number of failures cannot be greater than the value for **cluster redundancy level**, a configuration parameter that allows a database administrator to set the maximum number of recoverable simultaneous instance failures for the cluster.

Adding space to an archive database

Adaptive Server Cluster Edition version 15.5 and later supports archive databases. In general, access to an archive database is the same in both a clustered and a nonclustered Adaptive Server. In either scenario, when an archive database runs out of space, use the **alter database** command to add space to the archive database.

In a clustered Adaptive Server, run **alter database** from the same node that is updating the archive database. If you run **alter database** from a different node, Adaptive Server prints an error message with the number of the node that is actually updating the archive database.

Distributed transaction management in the shared-disk cluster

In version 15.5 and later, Adaptive Server supports distributed transaction management (DTM) on its clustered architecture.

The clustered Adaptive Server:

- Is fully compliant with the X/Open XA protocol when it acts as the resource manager (RM), without additional services, such as XA-Server.
- Ensures consistent commit or rollback for transactions that update Adaptive Server data via remote procedure calls (RPCs) and Component Integration Services (CIS).
- Can be part of distributed transactions coordinated by other Adaptive Server installations using the Adaptive Server Transaction Coordination (ASTC) mechanism.
- Can coordinate the distributed transactions across multiple Adaptive Server installations using the ASTC mechanism.

Note: The Cluster Edition does not support the Microsoft Distributed Transaction Coordinator (MSDTC) proprietary protocol.

New Features in Adaptive Server Version 15.5 Cluster Edition

In general, the user interface for distributed transactions is the same in the Adaptive Server clustered environment as in the nonclustered environment. Applications using DTM on a nonclustered Adaptive Server can use the same applications on the clustered Adaptive Server. See *Using Adaptive Server Distributed Transaction Management Features*.

Although the user interface for distributed transactions on the Cluster Edition is the same as that for nonclustered Adaptive Server, support for distributed transactions on the cluster must take into account the cluster-specific issues described in the *Clusters Users Guide*. For example:

- Using the cluster as the resource manager (RM)
- Requests to nonowner instances
- Handling instance failures
- Using transaction coordination with ASTC
- Impact of connection migration
- System configuration

System Changes Adaptive Server 15.5 Cluster Edition

Adaptive Server 15.5 Cluster Edition supports changes to commands, monitoring tables and configuration parameters.

Changed commands

In Adaptive Server Cluster Edition version 15.5 and later, you can use **mount database** and **unmount database** in a shared-disk cluster.

If an instance fails while **mount database** or **unmount database** is in progress, the command may abort. In this case, you must reissue **mount database** or **unmount database** when the instance failover recovery is complete.

Monitoring Tables

Monitoring tables added for Adaptive Server version 15.5.

Adaptive Server Cluster Edition version 15.5 adds these monitoring tables:

- **monTableTransfer** – provides historical transfer information for tables in Adaptive Server active memory.
- **monInmemoryStorage** – used for in-memory databases. For internal purposes only.

The Cluster Edition version 15.0.1 and later include monitoring tables to collect table statistics. These are the monitoring tables included with version 15.5:

- **monCIPC** – provides summary figures for total messaging within the cluster, as viewed from the current instance or all instances.
- **monCIPCEndpoints** – provides a detailed summary, giving traffic data for each subsystem within the cluster instance.
- **monCIPCLinks** – monitors the state of the links between instances in the cluster.
- **monCIPCMesh** – gives summary figures for the mesh of connections, from the current instance to all other instances in the cluster, on a per-instance basis.
- **monCLMObjectActivity** – collects cluster lock information.
- **monClusterCacheManager** – stores diagnostic information about the cluster cache manager daemon running on each instance. **monClusterCacheManager** reports cluster-wide information on a per-instance basis.

- `monCMSFailover` – tracks the time at which the cluster membership service (CMS) detects the failure, gets a new cluster view, resynchronizes the heartbeat, posts the failure event, and completes the failure event. There is a row for each instance.
- `monDBRecovery` – contains rows from all instances in the cluster and contains rows for every database that contributes to recovery.
- `monDBRecoveryLRTypes` – tracks log records seen during recovery. Contains a row for each log record type for which at least one log record was seen by recovery.
- `monFailoverRecovery` – contains aggregated failover recovery diagnostic information for the cluster lock manager (CLM), database recovery, and CMS modules.
- `monLogicalCluster` – displays information about the logical clusters currently configured on the system.
- `monLogicalClusterAction` – shows all administrative actions against local clusters from start-up until these actions are released.
- `monLogicalClusterInstance` – displays information about the many-to-many relationship between instances and logical clusters.
- `monLogicalClusterRoute` – displays information about the configured routes (application, login, and alias bindings). You need not have the `mon_role` role to query this monitor table.
- `monPCM` – tracks the peer coordination module (PCM) client activities in the cluster (for example, the number of fragment that were sent and received), and contains a row for each PCM client.
- `monProcessMigration` – displays information about the connection currently migrating.
- `monSysLoad` – provides trended statistics on a per-engine basis. You need not have the `mon_role` role to query this monitor table.
- `monTempdbActivity` – provides statistics for all open local temporary databases, including global system tempdb when the instance is started in tempdb configuration mode.
- `monWorkload` – displays the workload score for each logical cluster on each instance according to its load profile.
- `monWorkloadPreview` – provides an estimate of how a load profile impacts the workload score without enabling the profile. `monWorkload` includes one row for each logical cluster and instance on which this logical cluster is running.
- `monWorkloadProfile` – displays currently configured workload profiles. You need not have the `mon_role` role to query this monitor table.
- `monWorkloadRaw` – provides the raw workload statistics for each instance. You need not have the `mon_role` to query this monitor table.

Configuration Parameters

New configuration parameter for Adaptive Server Cluster Edition version 15.5 and later.

cluster redundancy level – The maximum number of instances that can fail simultaneously while allowing recovery to proceed concurrently with other activity. The cluster shuts down if the failed number of instances exceeds the maximum.

Functions

New functions for Adaptive Server Cluster Edition versions 15.5 and later.

- **xact_owner_instance** – returns the instance on which an external transaction is running, or 0.
- **xact_conmigrate_check** – determines whether a connection can process an external transaction.

New Features in Adaptive Server® Version 15.5

Adaptive Server 15.5 introduces in-memory and relaxed-durability databases, Backup Server support for IBM Tivoli Storage Manager, faster compression for backups, deferred name resolution for stored procedures, incremental data transfer, support for FIPS 140-2 password encryption, and new datatypes.

Adaptive Server 15.5 Feature and Platform Matrix

The feature and platform matrix shows feature availability for supported operating systems in Adaptive Server 15.5. A “Y” indicates the feature is supported for that platform.

Adaptive Server options	HP-UX Itanium 64-bit	HP-UX PA Risc 64-bit	IBM AIX 64-bit	Linux on Power 64-bit	Linux Opteron 64-bit	Linux x86 32-bit	Solaris 32-bit	Solaris 64-bit	Solaris Opteron 64-bit	Windows Opteron X64	Windows x86 32-bit
Security and directory services	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Cybersafe Kerberos							Y	Y			Y
Pluggable Authentication Module	Y		Y	Y	Y	Y	Y	Y	Y		
Fine-grained access control	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
LDAP server directory	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
LDAP user authentication	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Platform Native Kerberos							Y	Y			
Secure Sockets Layer	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
MIT Kerberos	Y	Y	Y	Y	Y	Y	Y	Y	Y		Y
Encrypted columns, including fine-grained access control (FGAC)	Y	Y	Y		Y	Y	Y	Y	Y	Y	Y

Adaptive Server options	HP-UX Itanium 64-bit	HP-UX PA Risc 64-bit	IBM AIX 64-bit	Linux on Power 64-bit	Linux Opteron 64-bit	Linux x86 32-bit	Solaris 32-bit	Solaris 64-bit	Solaris Opteron 64-bit	Windows Opteron X64	Windows x86 32-bit
High availability	Y	Y	Y		Y	Y	Y	Y			Y
Partitions	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
In-memory databases	Y	Y	Y	Y	Y			Y	Y	Y	
Tivoli Storage Manager for Backup Server	Y		Y		Y			Y	Y	Y	
Active messaging	Y	Y	Y		Y	Y	Y	Y	Y	Y	Y
Enhanced Full-Text Search (EFTS)		Y	Y		Y	Y	Y	Y			Y
<i>Features included in base Adaptive Server</i>											
Cross-platform dump and load	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Job Scheduler	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Native XML	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
IPv6	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Java option	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Web Services	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Distributed transaction management	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Content management (external file support)	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Archived database access	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y

In-Memory and Relaxed-Durability Databases

In-memory and relaxed-durability databases provide enhanced performance.

In-memory databases run entirely in a named cache (that is, in the Adaptive Server memory space), without using disk storage for data or logs. Because an in-memory database does not require I/O, its performance can be much better than a traditional, disk-resident database. In-memory databases are not designed for recovery: their transaction logs are written to the cache and not to disk, and any data changes are lost if the server is restarted. In-memory databases perform transactional logging for runtime rollback, and for other operations, such as firing triggers, deferred mode updates, replication, and so on.

Disk-resident databases perform writes to disk, and ensure that the transactional properties of atomicity, consistency, integrity, and durability (known as the ACID properties) are maintained. Durability refers to the persistence of transactions after they have committed. A traditional Adaptive Server database operates at full durability by writing its transaction log to disk when a transaction commits. This, along with data pages being written periodically to disk, ensures that all committed transactions are durable.

In-memory databases do not write data or log to disk, and trade the guarantee of transaction durability for performance improvements. In the event of a database failure, in-memory databases cannot be recovered. If your applications require data recoverability following a server failure or a normal shutdown, consider using a traditional Adaptive Server database.

With support for relaxed durability, Sybase extends the performance benefits of an in-memory database to disk-resident databases. A traditional disk-resident database guarantees transactional recovery from a server failure. Relaxed-durability databases trade the full durability of committed transactions for enhanced runtime performance for transactional workloads.

The performance benefits of in-memory and relaxed-durability databases include:

- An in-memory database operates entirely in-memory, so it does not wait for I/O.
- Improved buffer and user log cache management, so you need not create an overhead of user log cache flushes and buffer management when Adaptive Server performs concurrent updates to the same data.
- Runtime strategies that may avoid flushing task changes registered in the user-log cache to the transaction log when the transaction commits or aborts. These strategies reduce the contention on in-memory log pages.
- Support for minimally logged DML operations that use in-memory logging techniques improves the performance of large-volume DML operations.

Adaptive Server version 15.5 allows you to create these types of databases:

- Disk-resident databases with durability set to full (this is the default Adaptive Server database)

- User-defined disk-resident temporary databases
- In-memory user databases with durability set to `no_recovery`
- User-defined in-memory temporary databases with durability set to `no_recovery`
- Disk-resident relaxed-durability databases with durability set to `no_recovery` or `at_shutdown`

Adaptive Server supports **dump database** and **load database** for both in-memory and relaxed-durability databases. In addition, you can dump an in-memory database and load it into a disk-resident database, and vice versa. Adaptive Server supports template databases as a way to reinitialize the contents of nonrecoverable databases when the server restarts.

See the *In-Memory Database Users Guide*.

Faster Compression for Backups

New compression levels for dumping databases and transactions provide faster, more complete, and less CPU-intensive compression.

Two new compression levels have been added to the **dump database...compression=** and **dump transaction...compression=** commands: 100 and 101. Compression level 100 provides faster compression; level 101 provides better compression. Both new compression levels are less CPU-intensive than levels 0 – 9.

See the *System Administration Guide* and the *Reference Manual: Commands*.

Backup Server Support for the IBM® Tivoli® Storage Manager

Adaptive Server 15.5 supports IBM Tivoli Storage Manager (TSM) for storage management services in partnership with Backup Server. Support for TSM is a licensed Adaptive Server feature.

The TSM is a third-party client/server program that provides storage management services to licensed users. The Adaptive Server Backup Server supports tape drives and disk files as backup media. TSM works with Backup Server to enable a greater variety of backup media. You can store Adaptive Server backups on any backup media supported by TSM.

Adaptive Server handles the dump and load of databases and transactions to and from TSM; TSM handles storage and retrieval from the storage media. TSM provides storage management services, but you can administer all your Adaptive Server backup and restore operations, including queries for backup objects and deletion of backup objects, from Backup Server.

When you execute the **dump** or **load** commands, Backup Server invokes the Sybase interface with the TSM API, which provides communication with the TSM. When you use the **dump**

command, you specify an object name that is uniquely associated with the backup object. This object name is the same as the TSM object name, and should later be used to specify the same database or transaction dump for the load operation. In general, you can use the same options with the **dump** and **load** commands with TSM as you use with Backup Server when TSM is not configured.

Adaptive Server introduces these stored procedures to support the query and delete of backup objects from TSM:

- **sp_deletesmobj**– deletes some or all of the current server's backup objects from TSM.
- **sp_querysmobj**– retrieves a list of a server's backup objects.

See *Using Backup Server with IBM Tivoli Storage Manager*.

Deferred Name Resolution for User-Defined Stored Procedures

Deferred name resolution lets you create a stored procedure before referenced objects exist.

In versions of Adaptive Server earlier than 15.5, referenced objects were required to already exist before the stored procedure using them could be created. The deferred name resolution feature now allows objects, except for user-defined datatype objects, to be resolved when the stored procedure is executed for the first time.

This feature uses the **deferred name resolution** configuration parameter, which operates at the server level, or a new **set** command, **set deferred_name_resolution**, which operates at the connection level.

See the *Transact-SQL Guide*, the *System Administration Guide: Volume 1*, and the *Reference Manual: Commands*.

FIPS 140-2 Login Password Encryption

Adaptive Server 15.5 supports the FIPS 140-2 validated cryptographic module.

FIPS 140-2 certified Certicom Security Builder GSE encrypts login passwords in a transmitted login packet, in memory and on disk, if you use the configuration parameter **FIPS login password encryption**:

```
sp_configure 'FIPS login password encryption', 1
```

Note: A Security and Directory Services license is required to enable this parameter. If the parameter is not enabled, the OpenSSL security provider performs login password encryption.

See the *Users Guide for Encrypted Columns*.

Incremental Data Transfer

Incremental data transfer lets you transfer data to Adaptive Server or other products.

The **transfer table** command allows you to transfer data incrementally, and, if required, to a different product. In versions of Adaptive Server earlier than 15.5, you could transfer only whole tables from one Adaptive Server to another.

Note: Adaptive Server enables the data transfer feature when you purchase, install, and register the in-memory database license.

Incremental data transfer:

- Lets you export data, including only the data that has changed since a prior transmission, from Adaptive Server tables that are marked for incremental transfer.
- Allows table data to be read without obtaining the usual locks, without guaranteeing any row retrieval order, and without interfering with other ongoing reads or updates.
- Lets you write selected rows to an output file (which can be a named pipe) formatted for a defined receiver: IQ (Sybase IQ), ASE (Adaptive Server Enterprise), bulk copy (**bcp**), or character-coded output. All selected rows are transmitted without encryption, and, by default, any encrypted columns within the row are decrypted before transmittal. The file to which you are writing must be visible to the machine on which Adaptive Server is running (the file can be an NFS file that Adaptive Server can open as a local file).
- Maintains a history of transmissions for eligible tables, and lets you remove transmission history when it is no longer wanted. Exports data from tables declared ineligible for incremental transfer, subject to certain restrictions.
- Transfers entire rows from indicated tables. You cannot currently select certain columns, select a partition within a table, or transfer results from SQL queries.

See Chapter 8, “Adding, Changing, Transferring, and Deleting Data,” in the *Transact-SQL Users Guide*.

bigdatetime and bigtime Datatypes

bigdatetime and *bigtime* provide microsecond precision.

Two new datatypes, *bigdatetime* and *bigtime*, provide a timestamp with microsecond precision that contains the year, month, day, hour, minute, second, and fraction of a second to six decimal places. A *bigdatetime* value requires 8 bytes of storage. A *bigtime* value contains the time of day, containing hour, minute, second, and fraction of a second. The fraction is stored to six decimal places. A *bigtime* value requires 8 bytes of storage.

See the *Adaptive Server Transact-SQL Users Guide*, the *Reference Manual: Building Blocks*, and *Java in Adaptive Server Enterprise*.

Creating and Managing tempdb Groups

Updates for **tempdb** groups for version 15.5

Adaptive Server allows you to create and manage user-created **tempdb** groups in addition to managing the default **tempdb** group. User-created **tempdb** groups can include other user-created temporary databases, and support application and login binding.

You cannot remove the system **tempdb** from the default temporary database group. You cannot add system **tempdb** to any other user-created **tempdb** group.

You can designate and administer user-created **tempdb** groups to contain only disk-resident or in-memory temporary databases. The server does not explicitly impose any such restriction, but by controlling the membership you can assign disk-only or in-memory-only **tempdb** groups to specific logins or applications.

System Changes in Adaptive Server 15.5

Adaptive Server 15.5 supports new and changed datatypes, functions, system procedures, commands, configuration parameters, monitoring tables, system tables, and utilities. New auditing options have also been added.

Datatypes

New *bigtime* and *bigdatetime* datatypes provide precision timestamp information.

Datatypes	Description
<i>bigtime</i>	A <i>bigtime</i> value includes the hour, minute, second, and fraction of a second. The fraction is stored to 6 decimal places.
<i>bigdatetime</i>	A <i>bigdatetime</i> value includes the year, month, day, hour, minute, second, and fraction of a second to 6 decimal places.

Two new functions return *bigtime* and *bigdatetime* values:

- **current_bigtime**
- **current_bigdatetime**

bigtime and *bigdatetime* can be used in these existing functions:

- **datepart**
- **datename**
- **datediff**
- **dateadd**

See the *Reference Manual: Blocks*.

Functions

New and changed functions in Adaptive Server 15.5

Table 8. New functions

Function	Description
db_attr	Returns the durability , dml_logging , and template settings for the specified database.
object_attr	Reports the table's current logging mode, depending on the session-specific, table-wide, and database-wide settings.
cache_usage	Returns cache usage for the cache to which the specified object is bound, as the percentage of the cache which is currently in use by all objects bound to that cache.
current_bigdatetime	Returns a <i>bigdatetime</i> value representing the current date and time with microsecond precision.
current_bigtime	Returns a <i>bigtime</i> value representing the current time with microsecond precision.

Table 9. Changed functions

Function	Description
datepart	Produces the specified <i>datepart</i> argument of the specified date as an integer.
datename	Produces the specified <i>datepart</i> as a character string.
datediff	Calculates the number of date parts between two specified dates or times.
dateadd	Adds an interval to a specified date or time.

See the *Reference Manual: Commands*.

System Stored Procedures

New and changed system stored procedures support Tivoli Storage Manager, and in-memory and relaxed-durability databases.

Table 10. New system stored procedures

System stored procedures	Description
<code>sp_deletesobj</code>	Deletes backup objects from the TSM.
<code>sp_querysmobj</code>	Retrieves a list of backup objects from the TSM.

Table 11. Changed system stored procedures

System stored procedures	Description
<code>sp_addsegment</code>	Updated to manage space in in-memory databases.
<code>sp_addthreshold</code>	Updated to manage space in in-memory databases.
<code>sp_bindcache</code>	You cannot bind objects or databases to in-memory storage caches, and you cannot bind an in-memory database or objects in an in-memory database to any cache.
<code>sp_cacheconfig</code>	Creates, extends the size of, or drops, an in-memory storage cache.
<code>sp_cachestrategy</code>	The prefetch and MRU parameters do not apply to tables and indexes in in-memory databases.
<code>sp_dbextend</code>	Automatic database expansion is currently not supported for in-memory databases.
<code>sp_deviceattr</code>	The directio and dsync device attributes do not apply to in-memory devices.
<code>sp_downgrade</code>	Supports downgrading an Adaptive Server containing in-memory or relaxed-durability databases, or databases using templates or minimal logging.
<code>sp_diskdefault</code>	You cannot use <code>sp_diskdefault</code> to specify in-memory devices as a default devices.

System stored procedures	Description
sp_dropdevice	Drops an in-memory device created from an in-memory storage cache.
sp_dropsegment	Updated to manage space in in-memory databases.
sp_droptreshold	Updated to manage space in in-memory databases.
sp_extendsegment	Updated to manage space in in-memory databases.
sp_help	Reports on properties, such as minimal logging attribute, for a table.
sp_helpcache	Displays properties of the in-memory storage cache, the in-memory database created on it, and details of free space on this cache.
sp_helppdb	Reports on database properties, such as durability, DML logging level, in-memory or not, use, if any, of a template database, or as a template database.
sp_helpdevice	Reports the in-memory device properties created from an in-memory storage cache.
sp_modifythreshold	Updated to manage space in in-memory databases.
sp_plan_dbccdb	Sets up dbccdb for checkstorage execution in an in-memory database.
sp_poolconfig	Large I/O buffer pools are not supported in an in-memory database.
sp_post_xpload	Supports cross-platform operations for in-memory databases.
sp_tempdb	Supports user-created temporary database groups, login or application bindings to temporary database groups and for in-memory databases.
sp_unbindcache, sp_unbindcache_all	You cannot unbind objects in or the in-memory database itself from the host in-memory storage cache.

See the *Reference Manual: Procedures*.

Commands

New and changed commands for Adaptive Server 15.5

Table 12. New commands

Command	Description
transfer table	<p>Initiates an incremental table transfer.</p> <p>A new grant with grant option supports transfer table. It grants a specified user permission to transfer a specified table.</p> <pre>grant transfer table on <i>table_name</i> to <i>user</i> with grant option</pre>

Table 13. Changed commands

Command	Change
alter database	Syntax added to support changing the durability of a database, the level of DML logging, a database's template.
alter table	<p>Syntax added to support changing a table's logging mode for insert, update, and delete (DML) operations.</p> <p>Syntax added to support transfer table:</p> <pre>set transfer table [on off]</pre>
create database	<p>Syntax added to create in-memory and relaxed-durability databases with durability set to full, no_recovery, or at_shutdown.</p> <p>Syntax added to specify DML logging level and template database, if any.</p>
create table	<p>Syntax added to specify DML logging level for tables in in-memory databases.</p> <p>Syntax added to support transfer table:</p> <pre>with transfer table [on off]</pre>
disk init	Syntax added to create in-memory data devices for in-memory databases.
dump database	<p>Syntax added to support the Tivoli Storage Manager (TSM). The keyword syb_tsm invokes the Sybase interface with the TSM API (libsyb_tsm).</p> <pre><i>database_name</i> to "syb_tsm::<i>object_name</i>"</pre>

Command	Change
dump database ... compression=	Syntax added to support faster, less CPU-intensive compression levels 100 and 101.
dump transaction	Syntax added to support TSM. The keyword syb_tsm invokes the Sybase interface with the TSM API (libsyb_tsm). <i>database_name</i> to "syb_tsm:: <i>object_name</i> "
dump transaction ... compression=	Syntax added to support faster, less CPU-intensive compression levels 100 and 101.
load database	Syntax added to support TSM. The keyword syb_tsm invokes the Sybase interface with the TSM API (libsyb_tsm). <i>database_name</i> from "syb_tsm:: [[-S <i>source_server_name</i>] [-D <i>source_database_name</i>]]:: <i>object_name</i> "
load transaction	Syntax added to support TSM. The keyword syb_tsm invokes the Sybase interface with the TSM API (libsyb_tsm). <i>database_name</i> from "syb_tsm:: [[-S <i>source_server_name</i>] [-D <i>source_database_name</i>]]:: <i>object_name</i> "
select into	Syntax added to specify the DML logging level for tables created by selecting into in-memory or relaxed-durability databases.
set	Adds: <ul style="list-style-type: none"> • dml_logging parameter for specifying the amount of logging for a session. • deferred_name_resolution for activating deferred name resolution at the connection level. • builtin_date_strings <i>number</i> Values are: <ul style="list-style-type: none"> • 0 - if a string is given as an argument to a chronological system function, the server interprets it as a <i>datetime</i> value regardless of its apparent precision. This is the default. • 1 - makes the server interpret the argument string as <i>bigdatetime</i>. This affects the result of chronological system functions.

See the *Reference Manual: Commands*.

Configuration Parameters

Adaptive Server 15.5 introduces the **deferred name resolution** configuration parameter.

Configuration parameter	Description
deferred name resolution	Allows you to create procedures using deferred name resolution. Values are: <ul style="list-style-type: none"> • 0 – disables deferred name resolution. This is the default. • 1 – enables deferred name resolution.
builtin date strings	Values are: <ul style="list-style-type: none"> • 0 – causes string literals given to a chronological builtin function as an argument to be interpreted as a datetime type. • 1 – causes string literals given to a chronological builtin function as an argument to be interpreted as a bigdatetime type.

See the *System Administration Guide: Volume 1* and the *Transact-SQL Users Guide*.

Monitoring Tables

Adaptive Server 15.5 introduces the *monTableTransfer* monitoring table.

Monitoring table	Description
<i>monTableTransfer</i>	Provides historical transfer information for tables in the Adaptive Server active memory.

See the *Reference Manual: Tables*.

System Tables

New and changed system tables in Adaptive Server 15.5

Table 14. New system tables

System table	Description
<i>spt_TableTransfer</i>	Stores the results from table transfers.

Table 15. Changed system tables

System table	Change description
<i>sysdevices</i>	Lists the in-memory storage cache under the <i>name</i> and <i>phyname</i> columns. In-memory devices do not include a full path to the disk device, instead, they store the name of the cache on which the in-memory device has been created.
<i>sysdatabases</i>	<p>Adds the <i>durability</i> column, which indicates the durability level of the database. The <i>durability</i> column has the <i>int</i> datatype. Its values are:</p> <ul style="list-style-type: none"> • 1 – full • 5– at_shutdown • 6 – no_recovery

See the *Reference Manual: Tables*.

Utilities

New and changed utilities in Adaptive Server 15.5

Table 16. New utilities

Utility	Description
openssl	Performs all certificate management tasks implemented by certreq, certauth and certpk12. Sybase includes this binary as a convenience, and is not responsible for any issues incurred using the binary. See www.openssl.org for details.

Table 17. Changed utilities

Utility	Change
backupserv	Syntax change supports another verbosity level (V4) for the -V parameter. V4 displays all -V0 messages except “Connection from Server” messages printed for each connection event.

See the *Utility Guide*.

Auditing

Auditing options are added in support of in-memory and relaxed-durability databases, incremental data transfer, and deferred name resolution.

Table 18. Auditing enhancements

Audit option	Command or access to be audited	Event	Information in extrainfo
all, create	transfer table	136	Keywords or options: transfer_table
all, create	alter table	3	If alter table contains set transfer table on , Adaptive Server prints this to extrainfo: SET TRANSFER TABLE ON. If alter table contains set transfer table off , Adaptive Server prints this to extrainfo: SET TRANSFER TABLE OFF.
all, create	create table	12	If create table contains with transfer table on , Adaptive Server prints this to extrainfo: WITH TRANSFER TABLE ON. If create table contains with transfer table off , Adaptive Server prints this to extrainfo: WITH TRANSFER TABLE OFF.
all, create	create database	9	Keywords or options: inmemory
all, create	alter database	2	Keywords or options: inmemory
all, create	create procedure	11	Keywords or options: deferred_name_resolution

New Features in Adaptive Server 15.0.3

Adaptive Server 15.0.3 introduces distributed transaction management, enhancements to the Java interface, virtually hashed tables, huge pages, updates to the Adaptive Server Plug-in, directions for upgrading during a High Availability configuration, and support for SQL statement replication.

SQL Statement Replication

Replication Server 15.2 supports SQL statement replication for Adaptive Server databases

Adaptive Server Enterprise 15.0.3 introduces SQL statement replication, which is supported by Replication Server 15.2 and later.

See the Replication Server documentation.

Security Enhancements

Adaptive Server version 15.0.3 introduces several new security enhancements.

LDAPS User Authentication Enhancement

Modifying the CA trusted root file no longer requires a server restart.

In earlier versions of Adaptive Server, if you modify the Certifying Authority (CA) trusted root file, you must restart Adaptive Server for the modifications to take effect. Adaptive Server version 15.0.3 and later supports modifications to the trusted root file, so that restarting the the server is unnecessary. A new subcommand, **reinit_descriptors**, which unbinds the LDAP server descriptors and reinitializes the user authentication subsystem.

Automatic LDAP User Authentication and Failback

The Adaptive Server housekeeping utility can automatically activate a failed LDAP server

Adaptive Server 15.0.3 provides support for a secondary LDAP server. Previously, after bringing a failed primary LDAP server online, it was necessary to activate the LDAP server manually, in order to authenticate new LDAP logins and move them to the primary LDAP server.

In versions 15.0.3 and later, a new chore has been added to Adaptive Server's housekeeping utility to activate an LDAP server automatically: **'set_failback_interval'**.

After you set the failback interval, the housekeeper task checks for failed LDAP servers each time it sweeps through its chores. When it finds a failed LDAP server, it attempts to activate the LDAP server when the failback time interval expires.

Login Mapping of External Authentication

Adaptive Server can map one unique mapping of an external user to an internal Adaptive Server login

When you configure an external authentication mechanism, if there is exactly one mapping of an external user to an internal Adaptive Server login, and if it is successfully authenticated, Adaptive Server updates the internal login's password to match the external user's password.

For example, under these conditions:

1. USER1 has an Adaptive Server login name of "user_ase" with password "user_password".
2. Another user has an LDAP login name of "user_ldap" with password "user_ldappasswd".
3. Adaptive Server has a one to one mapping for "user_ldap" to "user_ase".
4. User "user_ldap" logs in to Adaptive Server using password "user_ldappasswd". Adaptive Server updates the "user_ase" password to "user_ldappasswd".

Using SSL to Specify a Common Name

Use a fully-qualified domain name for the SSL certificate common name

The server name specified in the directory service entry can be different from the common name the SSL server certificate uses to perform an SSL handshake. This allows you to use a fully-qualified domain name for the SSL certificate common name (for example, `server1.bigcompany.com`).

To add a common name to the interfaces file, use:

```
ase1
  master tcp ether host_name port_number ssl="CN='common_name' "
  query tcp ether host_name port_number ssl="CN='common_name' "
```

When clients use SSL to connect to an Adaptive Server that also uses SSL, the SSL filter is placed after the port number in the `interfaces` file. The directory service includes the common name, which you add either by using `dsedit` or a text editor.

`sp_listener` includes the `CN=common_name` parameter, which allows you to specify a common name for the SSL certificate.

Concurrent Kerberos Authentication

Adaptive Server can establish multiple Kerberos authentication sessions

Adaptive Server version 15.0.3 supports concurrent Kerberos authentication, whereas earlier versions used locking mechanisms during Kerberos authentication to protect internal data structures.

When there are concurrent logins using Kerberos authentication, Adaptive Server now establishes multiple Kerberos authentication sessions.

Version 15.0.3 also resolves an issue with concurrent login sessions, which may be blocked during Kerberos authentication. This concurrency issue occurs when you use prior versions of Adaptive Server with MIT version 1.3.x and 1.4.x Kerberos GSSAPI libraries.

Virtually Hashed Tables

Create virtually hashed tables to efficiently organize tables.

Note: Virtually hashed tables are available only on Linux pSeries.

You can perform hash-based index scans using nonclustered indexes or clustered indexes on data-only-locked tables. During this scan, each worker process navigates the higher levels of the index and reads the leaf-level pages of the index. Each worker process then hashes on either the data page ID or the key value in a separate hash table to determine which data pages or data rows to process.

A virtually hashed table can be a more efficient way to organize a table because it does not require a separate hash table. Instead, it stores the rows so that, using the hash key, the query processor can determine the row ID (based on the row's ordinal number) and the location of the data. Because it does not use a separate hash table to hold the information, it is called a "virtually" hashed table.

For systems that must make more efficient use of their central-processing unit (CPU), the virtually hashed table is a good option.

To create a virtually hashed table, specify the maximum value for the hash region using the **create table** command.

Huge Pages

Enable huge pages to use fewer pages to cover the physical address space.

Note: This feature is available only on Linux pSeries.

The CPU-Cache translation lookaside buffer (TLB) stores information about conversions from an virtual page address to the physical page address, and every byte access to physical memory requires a conversion (called a "cache miss"). Although these cache misses are very expensive, you can improve the TLB hits by enabling "huge pages."

Once enabled, huge pages use fewer pages to cover the physical address space, so the size of "book keeping" (mapping from the virtual to the physical address) decreases, requiring fewer entries in the TLB and improving the system performance.

Adaptive Server version 15.0.3 and later allocates shared memory using huge pages by default. However, if the system does not have enough huge pages—or is not configured for huge pages—Adaptive Server uses regular pages.

To enable huge pages, start Adaptive Server with traceflag 1653. Adaptive Server adjusts its shared memory up to the nearest multiple of 256MB.

Upgrading During a High Availability Configuration

After you have enabled high availability (HA), follow the upgrade instructions in the Adaptive Server installation guide for your platform

The instructions in this section supplement those in the *Installation Guide*.

Reinstalling System Stored Procedures

Reinstall the system stored procedures after enabling high availability

1. Disable HA in the primary server:

```
sp_companion secondary-server-name, 'drop'  
sp_configure 'enable HA', 0
```

2. Disable HA in the secondary server:

```
sp_configure 'enable HA', 0
```

3. Restart the servers.
4. Run the `installmaster` script on both servers.
5. Enable the HA property on both servers:

```
sp_configure 'enable HA', 1
```

6. Restart both servers.
7. Run the `installhasvss` script on both servers. This script is located in `$$SYBASE/$SYBASE_ASE/scripts`.
8. Reestablish companionship:

```
sp_companion [companion_server_name], configure [ ,  
with_proxydb]
```

Distributed Transaction Management (DTM)

Adaptive Serve automatically prevents SQL commands that are intended to execute inside a distributed transaction from executing outside it.

A distributed, or external, transaction is managed by an external transaction coordinator, such as XA Transaction Manager (TM).

In versions of Adaptive Server earlier than 15.0.3, user applications determined whether an external transaction was rolled back while executing DML commands. If Adaptive Server

implicitly aborted an external transaction without the application's knowledge, DML commands that would normally run inside this transaction might instead be executed inside an implicit transaction started by Adaptive Server. This behavior could result in inconsistent business data.

In versions 15.0.3 and later, Adaptive Server does not allow any DML commands to be executed on the connection attached to the external transaction until the transaction manager sends a detach request. The detach request indicates the end of a batch of commands intended for the external transaction.

In versions 15.0.3 and later, Adaptive Server automatically prevents SQL commands that are intended to execute inside a distributed transaction from executing outside it. The user application no longer has to check the global variable before every command; when a transaction is implicitly aborted, an error message (3953) appears, saying "Cannot execute the command because the external transaction has been rolled back." This message disappears when a **detach transaction** command is issued.

Adaptive Server Plug-in Updates

The Adaptive Server Plug-in now runs on Sybase Central 6.00, and contains several new features.

The Adaptive Server Plug-in for Sybase Central manages various Adaptive Server Enterprise products. In versions earlier than 15.0.3, the Adaptive Server Plug-in ran on Sybase Central 4.3. In 15.0.3 the Adaptive Server Plug-in runs on Sybase Central 6.00. These features are new to version 15.0.3, Sybase Central 6.00:

- A Search tool helps you find objects displayed by plug-ins.
- The Connection Profile Description, Import, and Export options allow you to add a text description to a profile connection.
- There is better support for Windows Vista.

These features are new to the version 15.0.3 Adaptive Server plug-in.

- You can create objects by selecting the Add icon from a context-sensitive toolbar.
- Stored procedures and SQLJ procedures are located in the Procedures folder.
- Scalar functions, or user-defined functions, are now supported.
- Utilities items are now accessible from the menu on the context-sensitive toolbar.

DBISQL11, which was previously shipped as part of Adaptive Server Plug-in, is now a separate product, version 11.0, and includes these features:

- The number of multiple result sets is no longer limited to 10.
- The login dialog for Adaptive Server now retains and displays the last five connected server names.

New Features in Adaptive Server 15.0.3

- DBISQL11, or interactive SQL, now supports connection favorites, which are similar to connection profiles.
- The SQL statements pane now contains line numbers.
- The Results pane now shows using **select all**, **insert/update/delete** SQL statements, and sorting and generating, from selected rows.

The Java Interface

Java in Adaptive Server now supports third-party JRE and JVM components such as J2SE.

Adaptive Server version 15.0.3 lets you plug in off-the-shelf Java Runtime environment (JRE) and JVM components, such as J2SE, to Adaptive Server. This Adaptive Server Java framework is called the pluggable component interface (PCI), which includes pluggable component adaptors (PCAs). Any JVM configured for Adaptive Server is called a “plug-in.”

The Adaptive Server Java framework allows you to build on the Java solution in Adaptive Server versions 15.0.2 and earlier without losing significant functionality. Any Java applications you developed using Adaptive Server versions earlier than 15.0.3 should run seamlessly with Java applications you create using the framework in versions 15.0.3 and later.

After you configure Adaptive Server to run with the PCI, you can include any standard JVM that supports Java 6 or later. This separates your Java applications from Adaptive Server, allowing you to change or upgrade your Java applications independent of Adaptive Server and to take advantage of new Java functionality as it becomes available.

See *Java in Adaptive Server Enterprise* for a complete description of the new Adaptive Server Java interface.

System Changes in Adaptive Server 15.0.3

Adaptive Server 15.0.3 introduces new and changed functions, system stored procedures, commands, configuration parameters, and system tables.

Functions

Adaptive Server 15.0.3 introduces the **password_random** and **pssinfo** functions.

Function	Description
password_random	Generates a pseudorandom password that satisfies the global password complexity checks defined on Adaptive Server.
pssinfo	Returns information from the process status structure, with an option that retrieves the transaction isolation level of any spid.

See the *Reference Manual: Commands*.

System Stored Procedures

New and changed system stored procedures in Adaptive Server 15.0.3

Table 19. New system stored procedures

Stored procedure	Description
sp_tabsuspectptn	A range-partitioned table on character-based partition keys can become suspect after a sort-order change, and hash-partitioned tables can become suspect after a cross-platform dump load.
sp_jreconfig	This is a Java stored procedure.

Table 20. Changed System Stored Procedures

Procedure	Change
sp_ldapadmin	Supports the new parameters set_failback_interval and reinit_descriptors .

Procedure	Change
sp_addserver	Supports the filter parameter to add a remote server for remote procedure calls.
sp_passwordpolicy	Supports the validate password options parameter.
sp_pciconfig	Supports Java in the database.
sp_sysmon	Supports additional counters.

See the *Reference Manual: Procedures*.

Commands

Adaptive Server 15.0.3 introduces changes to the **create table** and **update statistics** commands.

Command	Description of change
create table	The table you create with this option is available only to BCP IN and ' alter table unpartition ' operations.
update statistics	Resets the data change counters for global non-clustered indexes.

See the *Reference Manual: Commands*.

Configuration Parameters

New configuration parameters for Adaptive Server 15.0.3

Procedure	Change
enable pci	This is a Java configuration parameter.
maximum nesting level	The maximum nesting level has been increased to 100.

Procedure	Change
<code>mnc_full_index_filter</code>	Prevents Adaptive Server from considering non-covered indexes that do not have a limiting search argument at the server level if there is: <ul style="list-style-type: none"> • A column in the index • A predicate that does not have a histogram
<code>pci memory size</code>	This is a Java configuration parameter

See the *System Administration Guide: Volume 1*.

Monitoring Tables

New and changed monitoring tables for Adaptive Server 15.0.3

Table 21. New monitoring tables

Table	Description
<i>monSQLRepActivity</i>	Provides statistics for all open objects on DML statements replicated using SQL statement replication.
<i>monSQLRepMisses</i>	Provides statistics for replicated operations for which SQL statement replication was not used. The <i>threshold</i> , <i>querylimitation</i> and <i>configuration</i> columns indicate the number of times that one of these factors prevented SQL statement replication for the object

Table 22. Changed monitoring tables

Monitoring table	Description of change
<i>monSysStatement</i> , <i>monSysPlanText</i> , and <i>monSysSQLText</i>	The values of the columns <i>BatchID</i> , <i>ContextID</i> , <i>ProcedureID</i> , and <i>PlanID</i> have been modified.
<i>monSysStatement</i>	Supports two new columns: <i>ProcNestLevel</i> and <i>StatementNumber</i> .

See the *Reference Manual: Tables*.

System Tables

Adaptive Server 15.0.3 adds new columns to several system tables.

Table	Changes
<i>sysqueryplans</i>	<p>New columns:</p> <ul style="list-style-type: none"> • <i>dbid, int null</i> • <i>qptime, datetime null</i> • <i>sprocid, int null</i> • <i>hashkey2, int null</i> • <i>key1, int null</i> • <i>key2, int null</i> • <i>key3, int null</i> • <i>key4, int null</i> <hr/> <p>Note: These columns are reserved for future use.</p>
<i>sysprocedures</i>	<p>New column <i>qp_setting varbinary(6) null</i></p> <hr/> <p>Note: This column is reserved for future use.</p>
<i>sysprocesses</i>	<p>New column <i>clientport</i></p> <ul style="list-style-type: none"> • Displays client port numbers for client processes • Displays 0 for system processes • Datatype: unsigned <i>smallint</i>
<i>sys.servers</i>	<p>The column <i>srvnetname</i> has changed from <i>varchar(32)</i> to <i>varchar(255)</i>.</p>

See the *Reference Manual: Tables*.

New Features in Adaptive Server 15.0.2

Adaptive Server 15.0.2 introduces many new features and enhancements. They include enhancements to security, encrypted columns, and performance. New features include archive database access, deferred compilation, eager and lazy aggregate processing, and user-defined SQL functions.

Encrypted Columns

Adaptive Server Enterprise 15.0.2 provides enhancements to encrypted columns

The new features:

- Protect data from administrator. You can protect keys and encrypted columns with your own password to ensure privacy of data against the power of the DBO or System Administrator.
- Maintain application transparency using key copies protected by login passwords. That is, you can create key copies and assign them to individual users. Users can encrypt their key copies using their login passwords. Once a key copy is associated with a login password, users do not have to supply the key encryption password when they access data encrypted with the key.
- Provide for key recovery. You can recover access to a key after losing a password. The key owner sets up a recovery key copy, which can later be used to reencrypt the key after losing the password.
- Return a default value for users without decrypt permission. You can create or alter a table to allow **select** statements to return specified default values for users who do not have decrypt permission. This allows you to run existing applications and reports without generating a permission error, while keeping private data secure against unauthorized users. Reports generated by unauthorized users do not reveal the encrypted data.
- Restrict automatic decrypt permissions. When the **restricted decrypt permission** configuration parameter is enabled, the System Security Officer explicitly grants decrypt permission, restricting access to data. When **restricted decrypt permission** is enabled:
 - Table owners are not implicitly granted decrypt permission. The schema owner does not have automatic and implicit access to user data, even in systems that rely on the system encryption password to access the keys.
 - Only users with the `sso_role` can grant decrypt permission. The **with grant** option is supported for decrypt permission.
 - Implicit access through ownership chains across view and tables or procedures and tables is restricted.

- Adds datatypes. You can encrypt these additional datatypes: *date*, *time*, *datetime*, *smalldatetime*, *money*, *smallmoney*, *big int*, *unsigned big int*, *bit*, *unichar* and *univarchar*.

Archive Database Access

Validate or selectively recover data from a database dump (an “archive”) by making the dump appear as if it is a traditional, read-only database (an "archive database")

Unlike a traditional database, an archive database uses the actual database dump as its main disk storage device, with a minimum amount of traditional storage to represent new or modified pages that result from the recovery of the database dump. A database dump already contains the images of many (if not most) of the database pages, therefore, an archive database can be loaded without having to use Backup Server to transfer pages from the archive to traditional database storage. Consequently, the load is significantly faster than a traditional database.

Archive database access enables a variety of operations to be performed directly on a database dump.

An archive database does not have to be a complete copy of the original database. Depending on the optimization used when dumping the database using **sp_dumpoptimize**, an archive database may be fully populated (every page in the database is in the database dump), or partially populated (only allocated pages are stored in the database dump).

Because the database dump is presented as a read-only database, a database administrator can query it using familiar tools and techniques such as:

- Running database consistency checks on the most recent copy of a dump made from a production database. These checks can be offloaded to a different server to avoid resource contention in the production environment. If resources are not a concern, the archive can be directly checked in the same server in which it was created. Verification on the archive provides the assurance needed prior to performing a restore operation.
- If the integrity of a database dump is in question, loading it into an archive database can be a quick test for success, and therefore a good tool to identify the appropriate database dump that should be used to restore a traditional database.
- Object-level restoration from the database dump. Lost data is recovered using **select into** to copy the to-be-restored rows from the table within the archive database. The **select into** operation can be performed either directly in the server hosting the archive database, or by using Component Integration Services proxy tables if the archive database is available on a different server than that of the object requiring restoration.

In addition, transaction logs can be loaded into an archive database, thereby providing assurance that the same load sequence can be applied when performing a restore operation.

Finding Slow-Running Queries

Adaptive Server 15.0.2 introduces new **set** commands that collect information about slow-running queries.

These parameters for the **set** command enable you to collect diagnostic information about poorly running queries without having to previously enable **showplan** or other investigatory parameters:

- **tracefile** – saves diagnostics to a trace file
- **show_sqltext** – displays SQL text
- **export_options** – retains session settings

Deferred Compilation

Adaptive Server 15.0.2 introduces deferred compiling. Using deferred compilation, the optimizer can compile stored procedural statements that reference real runtime values.

The optimizer can now perform a runtime compilation of procedural statements that reference local variables and temporary tables, so that the query is optimized with real runtime values, instead of magic numbers.

- Adaptive Server uses deferred compilation for queries that reference local variables and parameters in search clauses, queries where a join is used with a temporary table created in the same procedure, and queries where a subquery references a temporary table.
- A statement qualified for deferred compilation is compiled at the first execution of the stored procedure. Those statements that are not executed the first time the stored procedure is invoked, for example statements omitted due to **IF** clauses, are not compiled until a subsequent execution of the stored procedure actually executes these statements.
- Once a conditional statement is compiled, whether at the first or at a subsequent procedure execution, it is integrated into the query plan and is not recompiled.
- Queries that reference procedure parameters previously were compiled and optimized only with the the value of those parameters upon entry to the stored procedure. In versions 15.0.2 and later, these statements are optimized with the parameter values they had when the query was first executed. If the parameter value alters during the course of the stored procedure execution, the current value is used in optimization.
- You can switch off deferred compilation by starting the server with the global switch - T7730.

Case-Insensitive Sort Orders for Chinese and Japanese Character Sets

This section describes case-insensitive sort orders for these Chinese and Japanese character sets:

- EUC-GB
- GB-18030
- CP-936
- EUC-JIS
- SJIS
- DECKANJI

Table 23. Sort orders available for Simplified Chinese and Japanese

Language or script	Character sets	Sort orders
Simplified Chinese	EUC-GB, GB-18030, CP936	General purpose case-insensitive dictionary ordering
Japanese	EUCJIS, SJIS, DECK-ANJI	General purpose case-insensitive dictionary ordering

Statistical Aggregate Functions

Adaptive Server 15.0.2 introduces statistical aggregate functions to compute variance and standard deviation

Aggregate functions summarize data over a group of rows from the database. The groups are formed using the **group by** clause of the **select** statement.

Simple aggregate functions, such as **sum**, **avg**, **max**, **min**, **count_big**, and **count** are allowed only in the **select** list and in the **having** and **order by** clauses as well as the **compute** clause of a **select** statement. These functions summarize data over a group of rows from the database.

Adaptive Server Enterprise now supports statistical aggregate functions, which permit statistical analysis of numeric data. These functions include **stddev**, **stddev_samp**, **stddev_pop**, **variance**, **var_samp**, and **var_pop**.

These functions, including **stddev** and **variance**, are true aggregate functions in that they can compute values for a group of rows as determined by the query's **group by** clause. As with other basic aggregate functions such as **max** or **min**, their computation ignores null values in the input. Also, regardless of the domain of the expression being analyzed, all variance and standard deviation computation uses IEEE double-precision floating-point standard.

If the input to any variance or standard deviation function is the empty set, then each function returns as its result a null value. If the input to any variance or standard deviation function is a single value, then each function returns 0 as its result.

Standard Deviation and Variance

Learn about the new statistical aggregate functions and their aliases.

- **stddev_pop** (also **stdevp**) – standard deviation of a population. Computes the population standard deviation of the provided value expression evaluated for each row of the group (if **distinct** was specified, then each row that remains after duplicates have been eliminated), defined as the square root of the population variance.
- **stddev_samp** (also **stdev**, **stddev**) – standard deviation of a sample. Computes the population standard deviation of the provided value expression evaluated for each row of the group (if **distinct** was specified, then each row that remains after duplicates have been eliminated), defined as the square root of the sample variance.
- **var_pop** (also **varp**) – variance of a population. Computes the population variance of value expression evaluated for each row of the group (if **distinct** was specified, then each row that remains after duplicates have been eliminated), defined as the sum of squares of the difference of value expression from the mean of value expression, divided by the number of rows in the group.
- **var_samp** (also **var**, **variance**) – variance of a sample. Computes the sample variance of value expression evaluated for each row of the group (if **distinct** was specified, then each row that remains after duplicates have been eliminated), defined as the sum of squares of the difference from the mean of the value expression, divided by one less than the number of rows in the group.

Eager and Lazy Aggregation

Aggregate processing summarizes large amounts of data with an aggregated value.

Aggregate processing is one of the most useful operations in DBMS environments. It summarizes these values:

- The minimum, maximum, sum, or average value of a column in a specified set of rows
- The count of rows that match a condition
- Other statistical functions

In SQL, aggregate processing is performed using the aggregation functions **min()**, **max()**, **count()**, **sum()**, and **avg()**, and **group by** and **having** clauses. The SQL language implements two aggregate processing types, *vector aggregation* and *scalar aggregation*. A **select-project-join** (SPJ) query illustrates these two types of aggregate processing:

```
select r1, s1
from r, s
where r2 = s2
```

Vector and Scalar Aggregation

Adaptive Server 15.0.2 supports vector and scalar aggregation

In vector aggregation, the SPJ result set is grouped on the **group by** clause expressions, and then the **select** clause aggregation functions are applied to each group. The query produces one result row per group:

```
select r1, sum (s1)
from r, s
where r2 = s2
group by r1
```

In scalar aggregation, there is no **group by** clause and the entire SPJ result set is aggregated, as a single group, by the same **select** clause aggregate functions. The query produces a single result row:

```
select sum (s1)
from r, s
where r2 = s2
```

Improved Performance for Data Insertion

Adaptive Server 15.0.2 optimizes performance of data insertion

These 15.0.2 features can enhance performance for data insertion:

- Fast **bcp** can copy data into tables with nonclustered indexes or triggers, improving Adaptive Server's performance for inserting huge volumes of data.
- Adaptive Server version 15.0.2 includes a separate user log cache (ULC) for the session's temporary database, so multidatabase transactions that include a single user database and the session's temporary database do not require ULC flushes when the users switch between the databases or if all of the following conditions are met:
 - Adaptive Server is currently committing the transaction.
 - All the log records are in the ULC
 - There are no post-commit log records.

The configuration option, **session tempdb log cache size**, allows you to configure the size of the ULC, helping to determine how often it needs flushing.

- When Adaptive Server splits an index or data page, it moves some rows from the original pages to the newly created page. The operation of moving the rows is not logged. Adaptive Server version 15.0.2 uses asynchronous writes to disk that do not require the server to block as it waits for the write to complete. Adaptive Server version 15.0.2 uses these asynchronous writes automatically and requires no configuration on your part.
- Improved throughput of tempdb transactions
- Adaptive Server version 15.0.2 provides post-commit optimization. The server performs two scans of the log: the first scan looks for data page deallocation and unreserved pages, the second scan looks for log page deallocation. These scans are an internal optimization,

transparent to users, and are performed automatically; you cannot switch the scans on or off.

With post-commit optimization, Adaptive Server remembers the “next” log page (in the backward direction) containing these log records. During the post-commit phase, Adaptive Server moves to the “next” page requiring post-commit work after processing records from a page. In a concurrent environment, where many users log their transactions to *syslogs* at the same time, post-commit optimization can improve the performance of post commit operation by avoiding reads or scans of unnecessary log pages.

Using Asynchronous Writes During a Page Split

When Adaptive Server splits an index or data page, it moves some rows from the original pages to the newly created page. The operation of moving the rows is not logged. Adaptive Server 15.0.2 uses asynchronous writes to ensure consistency.

To ensure both consistency and durability, Adaptive Server must satisfy these conditions:

- Adaptive Server writes the new page to disk before writing the modified page (with the rows removed) to disk. This ensures that Adaptive Server can restore the previous version of the page if the transaction is undone. Adaptive Server can find these rows on the new page and move them back to the old page even if the rows are missing in the old page, and their row contents were not logged.
- The new page reaches the disk before the transaction commits, which ensures that Adaptive Server cannot lose the committed data. If the transaction was committed, Adaptive Server is not required to redo the transaction for the new page, which would be impossible since the movement of the rows was not logged. In the case of undo, the new page’s allocation is backed out; there’s no page pre-image to restore.

Previous versions of Adaptive Server ensured these two conditions were met by synchronously writing the new page to disk. However, because the server could block until the synchronous write returned, this caused a degradation in performance.

Adaptive Server version 15.0.2 uses asynchronous writes to disk that satisfy the conditions described above and do not require the server to block as it waits for the write to complete.

Adaptive Server version 15.0.2 uses these asynchronous writes automatically and requires no configuration on your part.

Improving Throughput of tempdb Transactions

Earlier versions of Adaptive Server flushed the data pages and single log records (SLRs) because crash recovery was not supported for *tempdb* or any databases not requiring recovery.

SLRs are log records that force a flush of the user log cache (ULC) to *syslogs* immediately after the record is logged. SLRs are created for OAM modifications, and Adaptive Server creates log records affecting allocation pages in a mixed log and data database as SLRs.

New Features in Adaptive Server 15.0.2

- For regular databases, a ULC containing SLRs is flushed immediately to avoid any undetected deadlocks caused during buffer “pinning”. Avoiding a ULC flush for SLRs reduces log semaphore contention, improving the performance.
A ULC flush avoids the deadlock caused by buffer pinning. Because Adaptive Server does not pin the buffers for databases that do not need recovery, it avoids this deadlock and does not have to flush the ULC for SLRs.
- For databases that require recovery, Adaptive Server flushes dirty pages to disk during the checkpoint. This ensures that, if Adaptive Server crashes, all the committed data is saved to disk. However, for databases which do not require recovery, Adaptive Server supports a runtime rollback, but not a crash recovery. This allows it to avoid flushing dirty data pages at a checkpoint and improves performance.
- Adaptive Server does not support write ahead logging on databases that do not require recovery. Write-ahead logging guarantees that data for committed transactions can be recovered by “redoing” the log (reperforming the transactions listed in the log), and “undoing” the changes done by aborted or rolled back transactions to maintain database consistency. Write-ahead logging is implemented by the “buffer pinning” mechanism. Since Adaptive Server does not ensure write-ahead logging on databases not needing recovery, it does not pin buffers for these databases, so it can skip flushing the log when it commits a transaction.

Post-commit Optimization

Adaptive Server version 15.0.2 performs two scans of the log: the first scan looks for data page deallocation and unreserved pages, the second scan looks for log page deallocation. These scans are an internal optimization, transparent to users, and are performed automatically; you cannot switch the scans on or off.

Previous versions of Adaptive Server:

- Used three scans of the log record after a committed transaction, one each for page deallocation, unreserved pages, and log deallocation.
- Performed the backward scan of log pages using page linkages. Some of the pages did not have log records requiring post-commit work.

With post-commit optimization, Adaptive Server remembers the “next” log page (in the backward direction) containing these log records. During the post-commit phase, Adaptive Server moves to the “next” page requiring post-commit work after processing records from a page. In a concurrent environment, where many users log their transactions to *syslogs* at the same time, post-commit optimization can improve the performance of post commit operation by avoiding reads or scans of unnecessary log pages.

The optimization does not show up in any diagnostics.

Changes to the Query Processor

These modifications to the query processor describe behavior changes that can affect query plan selection.

Deferred Compilation

The query processor for Adaptive Server version 15.0.2 defers the optimization of statements in a stored procedure until it executes the statement.

Deferring the optimization of statements benefits the query processor because the values for local variables are available for optimization for their respective statements.

Earlier versions of Adaptive Server used default guesses for selectivity estimates on predicates using local variables.

Non-binary Character Set Histogram Interpolation

Adaptive Server version 15.0.2 allows selectivity estimates to have the same accuracy as the binary character set.

In earlier versions of Adaptive Server, only the default binary character set benefited from histogram interpolation, which is used to estimate the selectivity of range predicates. For all other character sets, Adaptive Server made a selectivity estimate of 50 percent for a histogram cell. This typically required Adaptive Server to use a large number of histogram cells for character column histograms to reduce the error associated with this estimate.

Adaptive Server version 15.0.2 allows selectivity estimates to have the same accuracy as the binary character set, without requiring an excessive number of histogram steps. This benefits queries like the following with range predicates:

```
select * from t1 where charcolumn > "LMC0021" and
charcolumn <= "LMC0029"
```

If ranges specified falls into the same histogram cell, Adaptive Server can much more accurately estimate this selectivity.

Expression Histogramming Selectivity Estimates

Adaptive Server version 15.0.2 applies histogramming estimates to single column predicates if the histogram exists on the column.

Earlier versions of Adaptive Server used default “guesses” for selectivity estimates.

Adaptive Server version 15.0.2 applies histogramming estimates to single column predicates if the histogram exists on the column. This results in more accurate row estimates, and improves the join order selection for query plans.

New Features in Adaptive Server 15.0.2

In this example, if the expression is very selective, it may be better to place table *t1* at the beginning of the join order:

```
select * from t1,t2 where substring(t1.charcol, 1, 3)
= "LMC" and t1.a1 = t2.b
```

Viewing Current Optimizer Settings

A new fake table *sysoptions* and a new stored procedure **sp_options** let you view optimizer settings.

To let you easily view optimizer settings, Adaptive Server version 15.0.2 introduces:

- *sysoptions* – a new fake table that stores information about each **set** option, its category, and its current and default settings. *sysoptions* also contains a bitmap containing further detailed information about the option.
- **sp_options** – a new stored procedure that shows option values.

New Security Features

New security features in Adaptive Server 15.0.2

PAM Support in 64-bit Adaptive Server on AIX

Adaptive Server 15.0.1 supports PAMUA on AIX 5.2.

Adaptive Server version 15.0.2 on AIX 5.2 64-bit supports Pluggable Authentication Module-based User Authentication (PAMUA). Contact your support representative to make sure you have the latest patch for PAM available on your IBM host.

To enable PAMUA in 64-bit Adaptive Server 15.0.2 on AIX 5.2, you must supply the PAM module in `/etc/pam.conf` file. For example:

```
ase auth required /usr/lib/security/pam_aix
```

Global Login Triggers Set Automatically

For Adaptive Server version 15.0.2 and later, any exportable option set or unset in a login trigger takes effect in the login process when the server starts.

Adaptive Server versions 15.0.1, 12.5.4, and earlier required that you start Adaptive Server with trace flag 4073 to enable the options for a login trigger.

Any exportable option set or unset in a login trigger now takes effect in the login process when the server starts

To disable the new behavior, execute **set export_options off** inside the login trigger.

SSL Support

Adaptive Server 15.0.2 supports SSL on Windows 2003 x64 Enterprise Edition.

Adaptive Server version 15.0.2 supports Secure Sockets Layer (SSL) on Windows 2003 X64 Enterprise Edition. Windows 2003 X64 implements SSL functionality using OpenSSL libraries.

SSL functionality is the same as Adaptive Servers on other platforms. It supports the same cipher suites and pre-defined lists as shown in the *System Administration Guide*. OpenSSL libraries for Adaptive Server on Windows 2003 X64 communicates with SSLPlus clients and servers using the same cipher suite names used in SSLPlus. The cipher suite names conform to the Transport Layer Security (TLS). TLS is an enhanced version of SSL 3.0, and is compatible with the SSL version 3.0 Cipher Suites.

Improved Password Security

Adaptive Server 15.0.2 improves password security.

Adaptive Server 15.0.2 adds a higher level of security to the existing password protection mechanisms through:

- Stronger encryption for passwords sent across the network
- Stronger encryption for passwords stored in *syslogins* (on disk) and in memory
- Managing login and password use with new time stamp data and additional account reporting

Auditing Enhancements

Adaptive Server version 15.0.2 introduces two additional auditing security features.

Hiding System Stored Procedure and Command Password Parameters

System stored procedure and command passwords can be replaced with asterisks in audit records.

When auditing is configured and enabled, and the **sp_audit** option '**cmdtext**' is set, system stored procedure and command password parameters are replaced with a fixed length string of asterisks in the audit records contained in the audit logs.

For example, execute:

```
sp_password 'oldpassword', 'newpassword'
```

When auditing is enabled and **sp_audit cmdtext** is set, the results in output are similar to:

```
sp_password '*****', '*****'
```

This protects passwords from being seen by other with access to the audit log.

Monitoring Failed Login Attempts

Monitor failed logins attempts with the **login_locked** audit option.

The new audit option **login_locked** and the event **Locked Login (value 112)** record when a login account is locked due to exceeding the configured number of failed login attempts. This event is enabled when audit option **login_locked** is set. To set **login_locked**, enter:

```
sp_audit "login_locked", "all", "all", "ON"
```

If the audit tables are full and the event cannot be logged, a message with the information is sent to the errorlog.

The hostname and network IP address are included in the audit record. Monitoring the audit logs for the **Locked Login** event (112) helps to identify attacks on login accounts.

High Availability Considerations

The Adaptive Server 15.0.2 password security changes affect High Availability (HA).

HA configuration

The primary and companion servers must have equivalent “**allow password downgrade**” values before they are configured for HA. A new quorum attribute “**allow password downgrade**” has been added to check whether the value of “**allow password downgrade**” is same on both primary and secondary servers. This HA advisory check succeeds when the value for the quorum attribute is the same, and HA advisory check fails when the values are different.

Changed password behavior in syslogins with HA

After upgrading to Adaptive Server 15.0.2 and successful configuring HA, on the first connection to the primary server, the password of the user login is updated on both the primary and companion servers. This synchronizes the login password on primary and companion with the same on-disk encryption format. This is done to avoid password reset or locking when the “**allow password downgrade**” period ends as described in **sp_passwordpolicy** and with password downgrade to earlier Adaptive Server 15.0 versions with **sp_downgrade**. By synchronizing the password encryption format, the login passwords can continue to be used without being reset or locked by **sp_passwordpolicy** or **sp_downgrade**.

Installing and Editing Monitoring Tables

Adaptive Server version 15.0.2 includes new installation and editing features for monitoring tables.

- Installing monitoring table - you no longer need to run the `installmontables` script to install the monitoring tables.

Versions of Adaptive Server earlier than 15.0.2 required you to run the `installmontables` script to install the monitoring tables. Adaptive Server version 15.0.2 includes the monitor tables installation in the `installmaster` script.

- Remotely accessing and editing monitoring tables - Sybase provides `installmontables` as a sample script showing how to remotely access monitoring tables. Run `installmontables` to view the instructions for editing.

Monitoring Tables for the Statement Cache

Two new monitoring tables let you analyze the contents of the statement cache.

The Adaptive Server statement cache stores SQL text of ad-hoc **update**, **delete** and **select** statements and other statements likely to be reused. When the statement cache is enabled, these statements are converted into lightweight procedures and their plans are saved for reuse. When a new statement is issued, Adaptive Server searches the statement cache for a plan to reuse. If Adaptive Server finds a plan to reuse, it avoids recompiling the statement, leading to performance enhancements.

The introduction of literal parameterization in Adaptive Server version 15.0.1 allows it to recognize queries that are the same except for differences in literal values, saving recompiling costs while using statement cache. In addition to performance benefits, literal parameterization leads to enormous space reduction while storing the metrics and statements in the cache.

Adaptive Server version 15.0.2 introduces two new monitoring tables that allow you to easily analyze the contents of the statement cache:

- *monStatementCache* provides a summary snapshot of the statement cache.
- *monCachedStatement* shows detailed information about each statement cached

The columns in each table allow two attributes, “counter” if the column has a counter value, and “reset” if the column can be reset using mechanisms like **sp_sysmon**.

Row-Level Locking for System Tables

Adaptive Server version 15.0.2 uses row-level locking on system tables to enhance performance.

Versions of Adaptive Server earlier than 15.0.2 used exclusive table locks on system tables while executing data definition language (DDL) and utility commands. The set of system tables Adaptive Server locked depended on the type of DDL operation you executed. If another DDL running concurrently tried to take a conflicting exclusive table lock on the same system table, this DDL had to wait to acquire the lock on any system catalogs. These DDL operations were executed serially.

New Features in Adaptive Server 15.0.2

This methodology impeded performance in temporary databases, where their DDL activity is very high also, and consequently their catalog contention is very high. This limited the Adaptive Server throughput for applications using temporary tables.

Adaptive Server version 15.0.2 uses row-level locking to resolve these issues:

- System-table contention, caused a bottleneck for many DDLs and utilities.
- *tempdb* contention. Because the system tables are locked at the row level, Adaptive Server 15.0.2 eliminates *tempdb* contention.
- Shared or exclusive table-level locks while executing DDLs and utilities. Earlier versions converted most system tables to data-only locking (DOL), but still created shared or exclusive table-level locks while executing DDLs and utilities. Using row-level locks for system tables eliminates this contention.

Adaptive Server sets intent locks on catalogs only, which removes potential contention (An intent lock indicates that page-level or row-level locks are currently held on a table.).

- DDLs and utilities blocking each other. Adaptive Server 15.0.2 allows DDLs and utilities to run in parallel.

Earlier versions of Adaptive Server used table locks to achieve system catalog synchronization. Adaptive Server 15.0.2 uses intent locks for table-level synchronization and row locks for row-level synchronization. Earlier releases of Adaptive Server locked the entire system catalog while performing operations on the object, so a single lock request was made. However, Adaptive Server version 15.0.2 requests locks for all applicable rows while performing operations on the object if there are multiple rows corresponding to an object in a system catalog.

This change means that Adaptive Server 15.0.2 requests more locks to perform the same operation than earlier releases, and increases the number of lock resources the system needs. Consequently, you may need to change the **number of locks** configuration option after you upgrade Adaptive Server.

The `xmltable()` Function

`xmltable()` creates a SQL table from elements in an XML table.

`xmltable()` extracts a sequence of multivalued elements from an XML document, and assembles a SQL table of those elements. A single call to **`xmltable()`** replaces a Transact-SQL loop that performs multiple calls to **`xmlextract()`** on each iteration. **`xmltable()`** is invoked as a derived table (a parenthesized subquery specified in the **`from`** clause of a different SQL query). Calling **`xmltable()`** is equivalent to executing a single **`xmlextract()`** expression for each row of the table generated by **`xmltable()`**.

`xmltable()` is a generalization of **`xmlextract()`**. Both functions return data extracted from an XML document that is an argument in the function. The differences are:

- **`xmlextract()`** returns the data identified by a single XPath query.

- **xmltable()** extracts the sequence, or row pattern, of the data identified by an XPath query, and extracts from each element of that sequence the data identified by a list of other XPath queries, the column patterns. It returns all the data in a SQL table.

Relocated Joins

Relocation joins permits joins between local and remote tables to locate to remote server.

Adaptive Server version 15.0.2 introduces relocated joins, which allow joins between local and remote tables to be relocated to a remote server. The remote system executes the join using a dynamically created proxy table referring back to the local table. With the remote system executing the join, a significant amount of network traffic is avoided.

User-Defined SQL Functions

Adaptive Server 15.0.2 introduces user-defined SQL functions.

Use **create function** to create user-defined functions, and **drop function** to remove a user-defined function.

You can include these elements in a scalar function:

- **declare** statements to define data variables and cursors that are local to the function.
- Assigned values to objects local to the function (for example, assigning values to scalar and variables local to a table with **select** or **set** commands).
- Cursor operations that reference local cursors that are declared, opened, closed, and deallocated in the function.
- Control-of-flow statements.
- **set** options (only valid in the scope of the function).

Adaptive Server does not allow **fetch** statements in a scalar function that return data to the client. You cannot include :

- **select** or **fetch** statements that returns data to the client.
- **insert**, **update**, or **delete** statements.
- Utility commands, such as **dbcc**, **dump** and **load** commands.
- **print** statements
- Statement that references **rand**, **rand2**, **getdate**, or **newid**.

You can include **select** or **fetch** statements that assign values only to local variable.

instead of Triggers

Use **instead of** triggers to override default triggering actions.

Views are commonly used to separate logical database schema from physical schema. **instead of** triggers can be defined on a view to replace the standard action of an **update**, **insert**, or **delete** statement. The **instead of** trigger allows all views, including those that are not otherwise updatable, to be updated.

instead of triggers are special stored procedures that override the default action of a triggering statement (**insert**, **update**, and **delete**), and perform user-defined actions.

The **instead of** trigger, like the **for** trigger, executes each time a data modification statement executes on a specific view. A **for** trigger fires after an **insert/update/delete** statement on a table, and is sometimes called an **after** trigger. A single **instead of** trigger can apply to one specific triggering action:

```
instead of update
```

It can also apply to multiple actions, in which the same trigger executes all the actions listed:

```
instead of insert,update,delete
```

Like **for** triggers, **instead of** triggers use the logical **inserted** and **deleted** tables to store modified records while the trigger is active. Each column in these tables maps directly to a column in the base view referenced in the trigger. For example, if a view named V1 contains columns named C1, C2, C3, and C4, the **inserted** and **deleted** tables contain the values for all four columns, even if the trigger modifies only columns C1 and C3. Adaptive Server automatically creates and manages the **inserted** and **deleted** tables as memory-resident objects.

instead of triggers allow views to support updates, and allow implementation of code logic that requires rejecting parts of a batch, while allowing other parts to succeed.

An **instead of** trigger is fired only once per data modification statement. A complex query containing a **while** loop may repeat an **update** or **insert** statement many times, firing the **instead of** trigger each time.

System Changes in Adaptive Server 15.0.2

Changes to commands, functions, utilities, system procedures, system tables, configuration parameters, functions, and global variables in Adaptive Server 15.0.2

Trace Flags

New trace flags in Adaptive Server 15.0.2

- 15340 enables server wide, no matter advanced_aggregation
- 15341 disables server wide, no matter advanced_aggregation

Commands

Changed commands in Adaptive Server 15.0.2

Table 24. Changed commands

Command	Description of change
disk init, disk reinit	Display a warning message if you attempt to create a block device on a platform that Sybase recommends that you not use block device. Sybase recommends that you use block devices as a database device only on the HP-UX, Windows, and Linux platforms.
create proxy table, create table at remote server, and alter table.	Do not support SQL UDF.
disk init, disk resize	When <i>skip_alloc</i> is set to be true, it allows users to avoid initialization of pages with zeros. The default of <i>skip_alloc</i> is false. It is supported for devices created on non-Windows file systems and on Windows raw systems.
dump transaction	dump transaction can now include string and char_variable parameters. However, you cannot supply string and char_variable options to execute begin transaction, commit, connect to, declare cursor, rollback, dbcc, use or nested execute commands.

See the *Reference Manual: Commands*.

Changes to the set Command

Adaptive Server 15.0.2 introduces several changes to the **set** command.

set command change
set advanced_aggregation enables and disables advanced aggregation at the session level.
set switch allows you to set trace flags and switch names locally and server-wide.
The compile-time behavior has changed for some abstract plan set parameters when you use them to create stored procedures or run them in Transact-SQL batches.
The set command can include string and char_variable parameters.

Utilities

Adaptive Server 15.0.2 supports enhancements to the **ddlgen** utility.

Change	Description
ddlgen prompts for password.	In version prior to 15.0.2, failing to include the -P password parameter returned an error. ddlgen now prompts for the password.
ddlgen supports both pre-15.0.2 and 15.0.2 encryption.	Sample syntax: <pre>ddlgen -Usa -P -Sserver -TEK -NSampleKeysDB.dbo.ssn_key</pre>
ddlgen without the -XOD flag	Two things can happen: <ul style="list-style-type: none"> If users do not specify a password when the encryption key is created, ddlgen generates DDL with no password. If users specify a password when the encryption key is created, ddlgen generates a default password.
ddlgen with the -XOD flag	Generates a system encryption password.
Key copy support	ddlgen can generate DDL for key copies and for the base key.

See the *Utility Guide*.

System Stored Procedures

New and changed system procedures in Adaptive Server 15.0.2

Table 25. New system stored procedures

System stored procedure	Description
sp_downgrade	Validates readiness for downgrade to an earlier 15.0.x release. Also downgrades the system catalog changes Adaptive Server 15.0.2 modified.
sp_spaceusage	Reports the space usage for a table, index, or transaction log and estimates the amount of fragmentation for tables and indexes in a database. The estimates are computed using an average row-length for data and index rows, and the number of rows in a table. You can archive the space usage and fragmentation data for future reporting and trends analysis. sp_spaceusage supports a number of actions, including help , display , archive and report , to indicate the current Adaptive Server space usage.

Table 26. Changed system stored procedures

System stored procedure	Description of change
sp_autoformat	Now accepts columns of datatypes <i>int</i> (<i>smallint</i> , <i>bigint</i> , <i>tinyint</i> , <i>unsigned int</i>), <i>numeric</i> , <i>money</i> , <i>date/time</i> , and <i>float</i> , <i>real</i> , and <i>double</i> precision.
sp_changedbowner	Changes the owner of a database. You can now execute it with either <i>sa_role</i> or <i>sso_role</i> privileges. The owner of thresholds for that database is also changed to the specified user.
sp_checksourc	Encrypts the text of user-defined functions.
sp_configure	Now displays non-default value settings.
sp_depends	Checks for any object dependencies for user-defined functions.
sp_deviceattr	Displays a warning message if the dsync option is disabled for a database device on a file system.

System stored procedure	Description of change
sp_displaylogin	<p>includes these changes:</p> <ul style="list-style-type: none"> • supports both a wildcard expression and a server user ID, and displays matching logins: <pre>sp_displaylogin ['user_id' '[loginame wildcard]'</pre> <ul style="list-style-type: none"> • user_id – user ID (<i>suid</i>) of the user whose login you are displaying. • wildcard – wildcard character used for search purposes. <p>Displays the login account for the user with a <i>suid</i> of 56: <pre>sp_displaylogin '56'</pre> <p>Displays the login account information for all users whose logins begin with “st”: <pre>sp_displaylogin 'st%'</pre> </p></p>
sp_droplogin	<p>When sp_droplogin is unable to drop a login due to the existence—in any database—of a user in <i>sysusers</i> referencing the login suid, the names of databases in which the references are found are now displayed in the error message.</p>
sp_help	<p>Displays information about user-defined functions.</p>
sp_helpdevice	<p>The <i>description</i> column of sp_helpdevice displays information about the device type. The device type is one of: <code>raw device</code>, <code>block device</code>, or <code>file system device</code>.</p>
sp_helprotect	<p>The new option, permission_name, in sp_helprotect provides information (grantor name, grantee name, table/column name, and grantability) for any specific permission granted in a given database.</p>
sp_hidetext	<p>Encrypts the text for user-defined functions.</p>
sp_locklogin	<p>The lock option to sp_locklogin, when used with a value for number of inactive days, locks inactive accounts that have not authenticated within that period. The following example locks all login accounts that have not authenticated within the past 60 days.</p>
sp_modifylogin account	<p>A new value for the 'max failed logins' option indicates that the failed login count in the <i>syslogins</i> column login count, is updated whenever an authentication failure occurs, but that the account is not locked.</p>

System stored procedure	Description of change
sp_modifystats	Allows the System Administrator, or any user with permission to execute the procedure and update statistics on the target table, to modify the density values of columns in <i>sysstatistics</i>
sp_monitorconfig	Enhanced to create a table to hold the result set, if the user passes a table name for result_tabl_name that does not already exist.
sp_passwordpolicy	<ul style="list-style-type: none"> The set and clear commands in sp_passwordpolicy are now audited, through audit event 115, "Password Administration." Additional syntax: <pre data-bbox="548 565 1184 899"> sp_passwordpolicy "enable last login updates", "allow password downgrade" "regenerate keypair", "expire login passwords", "[log- in_name wildcard]" "expire role passwords", "[role_name wildcard]" "expire stale login passwords", "da- tetime" "expire stale role passwords", "da- tetime" "maximum failed logins", -1 </pre>
sp_fixindex	Now works on a set of indexes rather than on a single index. sp_fixindex rebuilds the data layer if the target table has a placement or clustered index (it reclaims the unused space in the data layer while working on the placement or clustered index of a system table).
sp_sendmsg	In previous releases, the maximum length for a message sent with this system procedure was 255 characters. For Adaptive Server release 15.0.2, the maximum length of a sp_sendmsg message is 4096 characters.
sp_who	A new column, <i>tempdbname</i> , displays temporary database names of all active sessions.
sp_helptext	Reports the text of user-defined functions, and introduces the numlines and printops parameters.
sp_ldapadmin	Introduces new parameters: set_max_ldapua_desc , set_num_retries , and set_log_interval .
sp_monitor	Enhances the event and help parameters.
sp_tempdb	Introduces the show and who parameters.

See the *Reference Manual: Procedures*.

System Tables

New and changed system tables in Adaptive Server 15.0.2.

Table 27. New system tables

System table	Description
<i>sysoptions</i>	<i>sysoptions</i> is a fake table queried by sp_options . The column names are case-sensitive.

Table 28. Changed system tables

System table	Description of change
<i>sysquerymetrics</i>	Adaptive Server version 15.0.2 increases the number of metrics shared among user IDs. The change reduces the number of entries in <i>sysquerymetrics</i> (a view of <i>sysqueryplans</i>), and automatically aggregates the metrics for identical queries across different user IDs.
<i>syscolumns</i>	Adds a status bit to the <i>status2</i> column that indicates an encrypted column has a <i>decrypt_default</i> attached to it: 0x00001000 (4096) – column has a decrypt default
<i>sysobjects</i>	The <i>type</i> column of <i>sysobjects</i> includes an entry of “DD” for each object that has a decrypt default.
<i>sysaudits</i>	Changes include: <ul style="list-style-type: none"> • The <i>Alter Encryption Key</i> audit event name is changed to <i>AEK As/Not Default</i> • Adaptive Server release 15.0.2 supports these audit events and numbers: <ul style="list-style-type: none"> • 118 – AEK Modify Encryption • 119 – AEK Add Encryption • 120 – AEK Drop Encryption • 121 – AEK Modify Owner • 122 – AEK Key Recovery

System table	Description of change
<i>sysattributes</i>	<p><i>sysattributes</i> includes these changes:</p> <ul style="list-style-type: none"> • Adds two classes: <ul style="list-style-type: none"> • Class 31 <i>allow password downgrade</i> – when set to 1, <i>allow password downgrade</i> enables special handling of login passwords for compatibility with Adaptive Server release 15.0 and earlier. • Class 32 <i>enable last login updates</i> – when set to 1, <i>enable last login updates</i> enables system tables to store the date of the last login. • <i>sysattributes</i> includes information about default decrypt. These are the changes to the columns: <ul style="list-style-type: none"> • <i>attribute</i> – specifies a default decrypt on an encrypted column with a value of 1 (DECRYPT-DEFAULT_ID) for objects with a type of <i>EC</i> and a class of 25. • <i>object</i> – includes the decrypt default ID. • <i>object_info_1</i> – includes the table ID for a table whose encrypted column defines the decrypt default. • <i>object_info2</i> – specifies the colid of the encrypted column that includes the decrypt default.

System table	Description of change
<i>sysencryptkeys</i>	<p>Changes to <i>sysencryptkeys</i> includes</p> <ul style="list-style-type: none"> • New types: <ul style="list-style-type: none"> • <i>EK_KEYCOPY</i> – 0x0010, • <i>EK_KEYBASE</i> – 0x0020 • <i>EK_RECOVERY</i> – 0x0040 • New status bits: <ul style="list-style-type: none"> • <i>EK_KEYRECOVERY</i>(0x00000004) – keys encrypted for lost password protection. • <i>EK_LOGINACCESS</i>(0x00000008) – key encrypted for login access • <i>EK_LOGINPASS</i> (0x00000010) – key encrypted with login password • <i>EK_USERPWD</i>(0x00000100) – keys encrypted with user-encryption passwords • Changes to the description for the <i>uid</i> column – user access or key recovery row. <i>uid</i> contains the user ID (<i>uid</i>) identifying the database user associated with current row. Previous versions of Adaptive Server did not use the <i>uid</i> column.
<i>syslogins</i>	<p>In previous releases the maximum length of the <i>password</i> column was 30 bytes. In Adaptive Server release 15.0.2, the maximum length of the <i>password</i> column is 128 bytes.</p> <p>New columns are: <i>lastlogindate</i>, <i>crdate</i>, <i>locksuid</i>, <i>lockreason</i>, and <i>lockdate</i>.</p>
<i>sysrvroles</i>	<p>In previous releases the maximum length of the <i>password</i> column was 30 bytes. In Adaptive Server release 15.0.2, the maximum length of the <i>password</i> column is 128 bytes.</p>

See the *Reference Manual: Tables*.

Configuration Parameters

New and changed configuration parameters in Adaptive Server 15.0.2

Table 29. New configuration parameters

Configuration parameter	Description
enable merge join	Enables or disables merge joins at the server level.
cost of a logical io	Specifies the cost of a single logical IO.
cost of a physical io	Specifies the cost of a single physical IO.
cost of a cpu unit	Specifies the cost of a single CPU operation.
enable encrypted columns	Enables and disables the encrypted columns feature when encrypted columns is licensed.
max online q engines	Required for MQ series, max online q engines specifies the maximum number of Q engines allowed online.
metrics elap max	If the elapsed time of the query is less than the value of metrics elap max , then the metrics associated with the query are not written to the system tables. enable metrics capture must be on.
metrics exec max	If the execution time of the query is less than the value of metrics exec max , then the metrics associated with the query are not written to the system tables. enable metrics capture must be on.
metrics lio max	If the logical IO time of the query is less than the value of metrics lio max , then the metrics associated with the query are not written to the system tables. enable metrics capture must be on.
metrics pio max	If the physical IO time of the query is less than the value of metrics pio max , then the metrics associated with the query are not written to the system tables. enable metrics capture must be on.
min pages for parallel scan	Lets you scan larger queries in parallel.
not password encryption read	Requires all incoming login authentication requests using Adaptive Server authentication to encrypt the login password when transmitted on the network.

Configuration parameter	Description
number of Q engines at startup	Required for MQ series, specifies the maximum number of Q engines you can have online.
prod-consumer overlap factor	Affects optimization. Adaptive Server changes the group by algorithm, and you cannot use set statistics IO with parallel plans.
send doneinproc tokens	Replaces the dbcc tune option doneinproc .

Table 30. Changed configuration parameters

Configuration parameter	Description of change
max async i/os per engine	The default value has changed from 2147483647 to 1024.
maximum failed logins	The new -1 value indicates that the failed login count in the <i>syslogins</i> column <i>logincount</i> is updated whenever an authentication failure occurs, but that the account is not locked.
print deadlock information	Adds a new parameter value of 2, which lets you print a summary of deadlock information to the error log.

See the *Reference Manual: Tables*.

Functions

New and changed functions in Adaptive Server 15.0.2

Table 31. New functions

Function	Description
authmec()	Returns the authentication method used for a logged-in server process ID session.
index_name()	Returns the name of an index, when you specify the ID of the index and the database, and the object on which the index is defined.
hashbytes()	Produces a fixed-length, hash value expression.

Table 32. Changed functions

Function	Description of change
used_pages()	In all-pages-locked tables with clustered indexes, used_pages() is now passed only the used pages in the data layer, for a value of indid = 0 . When indid = 1 is passed, the used pages at the data layer and at the clustered index layer are returned.
When a function is created, Adaptive Server checks to see if it is a SQL UDF or a SQLJ UDF. If it is a SQLJ UDF, Adaptive Server checks for “sa” permissions. If it is a SQL function, Adaptive Server checks for create function privileges.	

Global Variables

Adaptive Server 15.0.2 introduces the *@@lastlogindate* global variable.

Table 33. New global variables

Global variable	Description
<i>@@lastlogindate</i>	Global T-SQL variable @@lastlogindate is available to each user login session. A <i>datetime</i> datatype, its value is the <i>lastlogindate</i> column for the login account before the current session was established. This variable is specific to each login session and can be used by that session to determine the previous login to the account. If the account has not been used previously or “ sp_passwordpolicy 'set', enable last login updates ” is 0, then the value of @@lastlogindate is NULL.

Table 34. Changed global variables

Global variable	Description of change
@@opttimeoutlimit	<p>Previous version of Adaptive Server user documentation listed @@opttimeout as a server global variable that displays the current optimization timeout limit for query optimization.</p> <p>This is incorrect. The actual name of the global variable that displays the current optimization timeout limit for query optimization is @@optimeoutlimit</p>

New Features in Adaptive Server 15.0.1

Adaptive Server 15.0.1 introduces several enhancements to abstract plans and lets you automatically convert literal values in SQL queries to parameter descriptions.

Changes to Abstract Plans

Adaptive Server 15.0.1 provides enhancements to abstract plans.

The enhancements include:

- The abstract plan syntax has been extended to allow several query level setting that were previously available only at the session level.
- Adaptive Server accepts both the `h_join` and `hash-join` keywords in the extended abstract plan syntax.
- The `set` command supports the `opt_criteria` parameter to turn on and off the current optimization goal setting.

New Query-Level Settings

The abstract plan syntax, used by Adaptive Server Enterprise to force the query plan chosen by the optimizer, has been extended to allow several query level setting that were previously available only at the session level.

The optimization criteria are handled at the session level by the following `set` statements:

```
set
  nl_join|merge_join|hash_join|. .
  0|1
```

The `use ...` abstract plan syntax has been extended to accept any number of use forms before the abstract plan derived table. Previously, the `optgoal` and `opttimeout` could not be in the same abstract plan with a derived table. For example this statement would need to be separate from a `optgoal` statement in a query:

```
select ...
  plan
    "(use opttimeoutlimit 10) (i_scan r)"
```

However, with Adaptive Server 15.0.1, you can include several statements in the same abstract plan in two ways:

- By using several `use` statements, for example:

```
select ...
  plan
    "(use optgoal allrows_dss)
    (use nl_join off) (...)"
```

New Features in Adaptive Server 15.0.1

- By placing several items within one **use** form, for example:

```
select ...
  plan
    "(use (optgoal allows_dss) (nl_join off)) (...)"
```

At the query level, use the optimization goal (**opt_goal**) or timeout (**opttimeout**) setting with the **use ...** abstract plan syntax. At the session level, use these settings with the **set plan ...** syntax:

- Optimization goal
- Optimization timeout

Operator Name Alignment for the Abstract Plan and the Optimizer Criteria

Adaptive Server accepts both the `h_join` and `hash_join` keywords in abstract plans.

The names of algorithms differ between their usage in abstract plans and in the **set** command. For example, a hash join is called `h_join` in abstract plans, but is called `hash_join` in the **set** command. Adaptive Server accepts both keywords in the extended abstract plan syntax. For example:

```
select ...
  plan
    "(h_join (t_scan r) (t_scan s))"
```

is equivalent to:

```
select ...
  plan
    "(hash_join (t_scan r) (t_scan s))"
```

and:

```
select ...
  plan
    "(use h_join on)"
```

and:

```
select ...
  plan
    "(use hash_join on)"
```

When a table abstract plan is present, it takes precedence:

```
select
from r, s, t
...
  plan
    "(use hash_join off)(h_join (t_scan r)
      (t_scan s))"
```

The query uses the `hash_join` for **r** and **s** scans; but for the join with **t** it does not use `hash_join` as specified by the `use` abstract plan form, since it was not specified in the table abstract plan.

Extending the Optimizer Criteria Set Syntax

The **set** command supports the *opt criteria* parameter to turn on and off the current optimization goal setting.

The **set** *<opt criteria>* statement, with a 0 or 1 syntax, accepts on/off/default, where default indicates that you are using the current optimization goal setting for this optimization criteria.

See the *Reference Manual: Commands*).

Literal Parameterization

Adaptive Server version 15.0.1 lets you automatically convert literal values in SQL queries to parameter descriptions (similar to variables).

In earlier versions of Adaptive Server, two queries that were identical except for one or more literal values resulted in the statement cache storing two separate query plans, or two additional rows in *sysqueryplans*. For example, the query plans for these queries were stored separately, even though they are almost identical:

```
select count(*) from titles where total_sales > 100
select count(*) from titles where total_sales > 200
```

Adaptive Server version 15.0.1 allows you to automatically convert literal values in SQL queries to parameter descriptions (similar to variables). A new **sp_configure** option supports this feature, which is called **enable literal autoparam**.

To enable or disable **enable literal autoparam** server-wide, use:

```
sp_configure "enable literal autoparam", [0 | 1]
```

Where 1 automatically converts literals to parameters, and 0 disables the feature. The default is 1.

You can set literal parameterization at the session level with the **set** command:

```
set literal_autoparam [off | on]
```

New Features in Adaptive Server 15.0.1

System Changes in Adaptive Server 15.0.1

Functions

Adaptive Server 15.0.1 introduces three new functions.

Function	Description
isdate	Determines whether an input expression is a valid <i>datetime</i> value.
isnumeric	Determines if an expression is a valid <i>numeric</i> datatype.
partition_object_id	Displays the object ID for a specified partition ID and database ID

See the *Reference Manual: Commands*.

Configuration Parameters

New and changed configuration parameters for Adaptive Server 15.0.1

Table 35. New configuration parameters

Configuration parameter	Description
startup delay	Controls when RepAgent is started during the server start. By default, RepAgent starts at the same time as Adaptive Server. Adaptive Server writes a message to the error log stating the wait time.
enable literal autoparam	Enables and disables literal server-wide parameterization.

Configuration parameter	Description
cis idle connection timeout.	<p>configures Adaptive Server to check for CIS connections to any remote server that have been unused longer than the specified number of seconds. Adaptive Server deletes the unused connections and reallocates their resources.</p> <p>Although the number you specify is in seconds, the housekeeper task wakes up at most once a minute, so idle connections may be idle for much longer than the configured value. Adaptive Server does not drop idle connections if a transaction is active on the connection, and reestablishes the connection automatically if the user executes any command that accesses the connection.</p>
sproc optimize timeout limit	Specifies the amount of time Adaptive Server can spend optimizing a system procedure as a fraction of the estimated execution time.

Table 36. Changed configuration parameters

Configuration parameter	Description of change
optimization timeout limit	The range of values available for optimization timeout limit has changed. With version 15.0.1, it is 0 - 1000. A value of 0 indicates no optimization timeout.
max parallel degree	If max parallel degree is set to 1 (enabled), Adaptive Server forces serial query execution and the optimizer may select plans with a higher parallel degree than if it is disabled.
number of worker processes	If you have not configured number of worker processes for a sufficient number of threads from the worker thread pool, Adaptive Server adjusts query plans at runtime to use fewer worker threads. If Adaptive Server cannot adjust the queries at run-time, the queries recompile serially. However, alter table and execute immediate commands are aborted if they do not have sufficient worker threads.

See the *System Administration Guide: Volume 1*.

Commands

Adaptive Server 15.0.1 introduces syntax and other changes to **alter table**, **create index**, **create existing table**, **update statistics**, and the **set** command.

Table 37. Changed commands

Table	Description of change
alter table	<p>Use the alter table command to drop one or more list or range partitions. You cannot use alter table to drop a hash or round-robin partition.</p> <p>The syntax is:</p> <pre>alter table <i>table_name</i> drop partition <i>partition_name</i> [, <i>partition_name</i>]...</pre>
create index	<p>When you create a unique local index on range-, list-, and hash-partitioned tables, the index key list is a superset of the partition-key list.</p>
create existing table	<p>Includes syntax to determine whether an RPC uses the current or a separate connection:</p> <pre>create existing table (<column_list>) EXTERNAL [non_transactional transactional] PROCEDURE at '<i>location</i>'</pre> <ul style="list-style-type: none"> <code>non_transactional</code> – a separate connection is used to execute the RPC. <code>transactional</code> – the existing connection is used to execute the RPC. <p>The default behavior is transactional.</p>
update statistics	<p>Adaptive Server 15.0.1 adds the ability to run update statistics on a global index.</p> <pre>update table statistics <i>table_name</i> [partition <i>data_partition_name</i>] [<i>index_name</i> [partition <i>index_partition_name</i>]]</pre> <p>Because running update table statistics incurs the I/O cost of running update statistics, use update statistics to generate both column and table statistics.</p> <p>You can create, and then drop, a global index to generate global statistics.</p>

Table 38. New set command options

New set command options	Description
<p>set literal_autoparam on off</p>	<p>Enables and disables literal parameterization at the session level.</p>
<p>set opttimeoutlimit</p>	<p>The range of values for opttimeoutlimit has been changed to 0 – 4000, with 0 indicating no optimization limit.</p>
<p>set index_union on off</p>	<p>When enabled, set index_union limits the scan of a table with an or clause.</p> <p>Index unions (also known as an or strategy) are used for queries that contain or clauses. For example:</p> <pre data-bbox="717 638 1177 713"> select * from titleauthor where au_id = "409-56-7008" or title_id = "PC8888" </pre> <p>If you have enabled index_union, this example uses an index on <i>au_id</i> to find the row IDs (RIDs) of all <i>titleauthor</i> tuples with <i>au_id</i> = "409-56-7008", and uses an index on <i>title_id</i> to find the RIDs of all <i>titleauthor</i> tuples with <i>title_id</i> = "PC8888". Adaptive Server then performs a union on all RIDs to eliminate duplicates. The resulting RIDs are joined with a RidJoin to access the data tuples.</p> <p>If index_union is disabled, Adaptive Server does not use an index union strategy in a query to limit the table scan. Instead, it uses other access paths on the table (in the example above, it would use a table scan for table <i>titleauthor</i>), and applies the or clause as a filter in the scan operator.</p>

See the *Reference Manual: Commands*.

Monitoring Tables

Adaptive Server 15.0.1 introduces two new monitoring tables:

monProcedureCacheMemoryUsage and *monProcedureCacheModuleUsage*.

Monitoring table	Description
<i>monProcedureCacheMemoryUsage</i>	Has one row for each procedure cache allocator. An allocator is identified by an allocator ID, which is internal to Adaptive Server.
<i>monProcedureCacheModuleUsage</i> .	Has one row for each module that allocates memory from procedure cache. A module, which is identified with a module ID, is a functional area classification internal to Adaptive Server procedure cache management.

See the *Performance and Tuning Guide: Monitoring and Analyzing* and the *Reference Manual: Tables*.

System Changes in Adaptive Server 15.0.1

New Features in Adaptive Server 15.0

Adaptive Server 15.0 introduces support for data partitions, row-locked system catalogs, an enhanced query processor, large identifiers, computed columns scollable cursors, new datatype support, XML enhancements, support for interactive SQL, enhancements to SySAM and the Adaptive Server Plug-in, user-defined Web service support, and security enhancements.

Partition Support

Partitioning is useful in managing large tables and indexes by dividing them into smaller, more manageable pieces. Partitions, like a large-scale index, provide faster and easier access to data.

Partitions are database objects and can be managed independently. You can, for example load data, and **create index** cannot be done at a partition level. Yet partitions are transparent to the end user, who can select, insert, and delete data using the same commands whether the table is partitioned or not.

Adaptive Server 15.0 supports horizontal partitioning, in which a selection of table rows can be distributed among partitions on different disk devices. Individual table or index rows are assigned to a partition according to a semantic or to a round-robin partitioning strategy.

Semantic partitioning strategies use the data values in specified, key columns in each row to determine the partition assignment of that row. The round-robin partitioning strategy assigns rows randomly without reference to data values.

Partitioning strategies are:

- *Hash partitioning* (semantic) – a system-supplied hash function determines the partition assignment for each row.
- *List partitioning* (semantic) – values in key columns are compared with sets of user-supplied values specific to each partition. Exact matches determine the partition assignment.
- *Range partitioning* (semantic) – values in key columns are compared with a user-supplied set of upper and lower bounds associated with each partition. Key column values falling within the stated bounds determine the partition assignment.
- *Round-robin partitioning* – rows are assigned randomly to partitions in a round-robin manner so that each partition contains a more or less equal number of rows. This is the default strategy.

You can:

New Features in Adaptive Server 15.0

- Create partitions when you create a table or index using the **create table** and **create index** commands.
- Alter a table's partitioning strategy using the **alter table** command.
- Add a partition to an existing table with **add partition**.
- You can use partitioning to expedite the loading of large amounts of table data—even when the table eventually will be used as an unpartitioned table.

Row-Locked System Catalogs

Many system catalogs can now use a datarows locking scheme.

Adaptive Server version 15.0 converts most system catalogs to a datarows locking scheme. These system catalogs continue to use allpages locking scheme:

- Materialized tables such as *syslocks* and *sysprocesses*. These tables are generated during run-time and their locking schemes are irrelevant for concurrency.
- *sysmessages* and *sysusermessages*, which are read-only tables
- Auditing tables in *sybsecurity*, which are write-once and read many times.

Adaptive Server's internal upgrade process converts the system table locking schemes during an installation, upgrade, or load upgrade.

Because DDLs in Adaptive Server release 15.0 use the same table-level locks as 12.5.x and earlier versions, there is no concurrency improvement when you run DDLs.

Query Processor

Adaptive Server 15.0 provides an enhanced query processor

The Adaptive Server version 15.0 query processor is self-tuning, requiring fewer interventions than earlier versions. This version of Adaptive Server has less reliance on worktables for materialization between steps since the engine supports data flow between steps. However, more worktables could be used in cases where Adaptive Server determines that hash and merge operations are effective.

New features include support for:

- Both vertical and horizontal parallelism for query processing
- Improved index selection, especially for joins with OR clauses and joins and search arguments (SARGs) with mismatched but compatible datatypes
- More efficient algorithms
- Improved costing, using join histograms for joins with data skews in joining columns
- Improved query plan selection that enhances performance through:

- New index union and index intersection strategies for queries with **and/or** predicates on different indexes
- On-the-fly grouping and ordering using in-memory sorting and hashing for queries with **group by** and **order by** clauses
- Cost-based pruning and timeout mechanisms that use permutation search strategies for large, multi-way joins, and for star and snowflake schema joins
- Improved problem diagnosis and resolution using:
 - Searchable XML format trace outputs
 - Diagnostic output from new **set** commands
- Joins involving a large number of tables
- Data and index partitioning, which are especially beneficial for very large data sets

Partitioning is the basic building block for parallelism.

Adaptive Server release 15.0 provides roundrobin partitioning. Round robin partitioning is equivalent to the 12.5 style of partitioning. During the upgrade to Adaptive Server release 15.0, all existing partitioned tables are unpartitioned and automatically converted to 1-way round robin partitioned tables.

Large Identifiers

Adaptive Server 15.0 introduces expanded limits for delimited identifiers

There are new limits for the length of object names or identifiers: 255 bytes for regular identifiers, and 253 bytes for delimited identifiers. The new limit applies to most user-defined identifiers including table name, column name, index name and so on. Due to the expanded limits, some system tables (catalogs) and built-in functions have been expanded.

For variables, “@” count as 1 byte, and the allowed name for the variable is 254 bytes.

Computed Columns

Computed columns and function-based indexes provide easier data manipulation and faster data access.

Computed columns provide easier data manipulation and faster data access by allowing you to create computed columns, computed column indexes, and function-based indexes.

- Computed columns – defined by an expression, whether from regular columns in the same row, functions, arithmetic operators, or path names.
- Indexes on computed columns, or computed column indexes – indexes that contain one or more computed columns as index keys.
- *Function-based indexes – indexes that contain one or more expressions as index keys.*

- Deterministic property – a property assuring that an expression always returns the same results from a specified set of inputs.

Computed columns and function-based indexes similarly allow you to use an expression or a function as the basis for a more complex function.

Differences Between Computed Columns and Function-Based Indexes

Computed columns and function-based indexes differ in some respects.

- A computed column provides both shorthand for an expression and indexability, while a function-based index provides no shorthand; it allows you to index the expression directly.
- A computed column can be either deterministic or nondeterministic, but a function-based index must be deterministic. “Deterministic” means that if the input values in an expression are the same, the return values must also be the same.

Differences Between Materialized and Not Materialized Computed Columns

Computed columns can be materialized or not materialized.

- Columns that are materialized are preevaluated and stored in the table when base columns are inserted or updated. The values associated with them are stored in both the data row and the index row. Any subsequent access to a materialized column does not require reevaluation; its preevaluated result is accessed. Once a column is materialized, each access to it returns the same value.
- Columns that are not materialized are also called virtual columns; virtual columns become materialized when they are accessed. If a column is virtual, or not materialized, its result value must be evaluated each time the column is accessed. This means that if the virtual computed column is expression-based on, or calls a nondeterministic expression, it may return different values each time you access it. You may also encounter run-time exceptions, such as domain errors, when you access virtual computed columns.

Scrollable Cursors

Adaptive Server Enterprise 15.0 supports both scrollable and nonscrollable cursors.

“Scrollable” means that you can scroll through the cursor result set by fetching any, or many, rows, rather than one row at a time; you can also scan the result set repeatedly. You must use Transact-SQL or JDBC to declare a scrollable cursor, and you must have the query engine provided in Adaptive Server 15.0 or later. A scrollable cursor allows you to set the position of the cursor anywhere in the cursor result set for as long as the cursor is open, by specifying the option **first**, **last**, **absolute**, **next**, **prior**, or **relative** in a **fetch** statement.

To fetch the last row in a result set, enter:

```
fetch last [from] <cursor_name>
```

Or, to select a specific row in the result set, in this case the 500th row, enter:

```
fetch absolute 500 [from] <cursor_name>
```

“Insensitive” or “semi-sensitive” refers to the extent to which data changes from outside the cursor are visible to the cursor. A cursor can be semi-sensitive but not scrollable.

All scrollable cursors are read-only. All **update** cursors are nonscrollable.

***unitext* Datatype Support**

Adaptive Server 15.0 supports the variable-length *unitext* datatype.

The variable-length *unitext* datatype can hold up to 1,073,741,823 Unicode characters (2,147,483,646 bytes). You can use *unitext* anywhere you use the *text* datatype, with the same semantics. *unitext* columns are stored in UTF-16 encoding, regardless of the Adaptive Server default character set.

The benefits of *unitext* include:

- Large Unicode character data. Together with *unicar* and *univarchar* datatypes, Adaptive Server provides complete Unicode datatype support, which is best for incremental multilingual applications.
- *unitext* stores data in UTF-16, which is the native encoding datatype for Windows and Java environments.

See the *System Administration Guide*.

***big int* Datatype Support**

Adaptive Server version 15.0 supports the exact numeric datatype *bigint*.

This is the range of numbers allowed by the *bigint* datatype:

Datatype	Range of signed datatypes
<i>bigint</i>	Whole numbers between -2^{63} and $2^{63} - 1$ (from -9,223,372,036,854,775,808 to +9,223,372,036,854,775,807, inclusive).

Adaptive Server *bigint* support also adds the **hextobigint**, **biginttohex**, and **count_big** functions.

See the *Reference Manual: Blocks*.

Unsigned Integer Datatype Support

Adaptive Server 15.0 supports unsigned integer datatypes.

These unsigned integer datatypes allow you to extend the range of the positive numbers for the existing integer types without increasing the required storage size. That is, the signed versions of these datatypes extend both in the negative direction and the positive direction (for example, from -32 to +32). However, the unsigned versions extend only in the positive direction. This is the range for signed and unsigned datatypes:

Datatype	Range of signed datatypes	Range of unsigned datatypes
<i>bigint</i>	Whole numbers between -2^{63} and $2^{63} - 1$ (from -9,223,372,036,854,775,808 to +9,223,372,036,854,775,807, inclusive)	Whole numbers between 0 and 18,446,744,073,709,551,615
<i>int</i>	Whole numbers between -2^{31} and $2^{31} - 1$ (-2,147,483,648 and 2,147,483,647), inclusive	Whole numbers between 0 and 4,294,967,295
<i>smallint</i>	Whole numbers between -2^{15} and $2^{15} - 1$ (-32,768 and 32,767), inclusive	Whole numbers between 0 and 65535

Integer Identity

Adaptive Server 15.0 allows you to use certain datatypes as identity values.

Use these datatypes as identity values:

- *bigint*
- *int*
- *numeric*
- *smallint*
- *tinyint*
- *unsigned bigint*
- *unsigned int*
- *unsigned smallint*

Enhancements to XML Services

XML enhancements in 15.0 include XML schema support, **for xml** clause enhancements, and Unicode (I18N) support.

XML Schema Support

You can validate XML documents against either a DTD or an XML schema. The DTD or schema can be specified either in the **xmlvalidate** command or in the document itself.

You can parse, store, and query XML documents with XML schema declarations.

for xml Enhancements

In Transact-SQL, an expression subquery is a parenthesized subquery. It has a single column, the value of which is the expression subquery result, and must return a single row. You can use an expression subquery almost anywhere you can use an expression.

For more information about subqueries, see the *Transact-SQL® User's Guide*. The **for xml** subqueries feature allows you to use any subquery containing a **for xml** clause as an expression subquery. For the syntax of **for xml** subqueries, see the *XML Services Guide*.

unicode Internationalization (I18N) Support

The I18N extensions fall into three categories:

- I18N support in the **for xml** clause. The columns of the result set you map to XML can contain non-ASCII data. Such data can be represented in the generated SQLX XML document either as plain characters or as numeric character representations (NCRs).
- I18N in **xmlparse** and **xmlvalidate**, to store and validate documents containing non-ASCII data.
- I18N in **xmlextract** and **xmltest**, to process XML documents and queries containing non-ASCII data.

Adaptive Server Plug-in Enhancements

Adaptive Server 15.0 includes enhancements to the Adaptive Server Plug-in.

Enhancements to the Adaptive Server Plug-in improve efficiency and convenience:

- An enterprise view that includes Server Discovery (which enables you to find available servers on the system) and automatic server status.
- The ability to update servers, administrate remote servers, and manage server logs.
- SQL Preview and Job Scheduler integration.
- A graphical query plan viewer.
- The ability to integrate external tools.

Interactive SQL

Interactive SQL allows you to execute SQL statements, build scripts, and display database data to the server.

You can run Interactive SQL individually or from the Adaptive Server Plug-in. It has been integrated in the Adaptive Server Plug-in as the standard query tool. You can use Interactive SQL to:

- Browse the information in a database.
- Test SQL statements that you plan to include in an application.
- Load data into a database and carrying out administrative tasks.

In addition, Interactive SQL can run command files or script files. For example, you can build repeatable scripts to run against a database and then use Interactive SQL to execute these scripts as batches.

User-Defined Web Services

Web Services lets you create Web services and execute SQL in Adaptive Server.

In addition to the Web methods provided by the Adaptive Server Web Services Engine, Web Services lets you create Web services and execute SQL commands in Adaptive Server Enterprise using either a Web browser or a SOAP client. These user-defined Web services use existing security and auditing control inherent in Adaptive Server Enterprise.

You can create a user-defined Web service with the **create service** command, which enables you to specify the SQL to be executed, create a first-class object for which permissions can be controlled with the **grant** command, and control whether the service can be invoked with a Web browser or a SOAP client. The ASE Web Services Engine automatically generates WSDL for user-defined Web services.

See the Adaptive Server Enterprise Web Services *User's Guide*.

Very Large Storage Support

Adaptive Server 15.0 extends the allowable number of disk devices and the allowable number of 2K blocks for each device.

In pre-15.0 versions of Adaptive Server, a virtual page is described internally in a 32-bit integer: the first byte holds the device number (**vdevno**) and the succeeding three bytes describe the page offset within the device in units of 2K bytes (the virtual page number). This architecture limits the number of devices to 256 and the size of each device to 32 gigabytes—for a maximum storage limit of 8 terabytes in the entire server.

With Adaptive Server 15.0, the device number and the page offset are stored in separate 32-bit integers. The new architecture allows you to create up to 2,147,483,647 disk devices, each of which can be as large as 2,147,483,648 2K blocks or 4 terabytes.

Note: Because of schema changes to the *sysdevices* and *sysusages* system tables, you may need to modify scripts and stored procedures that access these tables. The device identifier must now be obtained from the *vdevno* columns of *sysdevices* and *sysusages*. The *high*, *low*, and *vstart* columns of these tables no longer store the device and virtual page number—they store only the virtual page numbers.

Automatic Running of update statistics

Run the **update statistics** command automatically at times that suit your site.

Instead of manually running **update statistics** at a certain time, you can set **update statistics** to run automatically at the time that best suits your site, and avoid running it at times that hamper your system. The best time to run **update statistics** is based on the feedback from the **datachange** function. **datachange** also helps to ensure that you do not unnecessarily run **update statistics**. You can use these templates to determine the objects, schedules, priority, and **datachange** thresholds that trigger **update statistics**, which ensures that critical resources are used only when the query processor generates more efficient plans.

Because it is a resource intensive task, the decision to run **update statistics** should be based on a specific set of criteria. Some of the key parameters that can help you determine a good time to run **update statistics** are:

- How much has the data characteristics changed since you last ran update statistics? This is known as the “datachange” parameter.
- Are there sufficient resources available to run **update statistics**? These include resources such as the number of idle cpu cycles and making sure that critical online activity does not occur during **update statistics**.

Datachange is a key metric that helps you measure the amount of altered data since you last ran **update statistics**, and is tracked by the **datachange** function. Using this metric and the criteria for resource availability, you can automate the process of running **update statistics**. The Job Scheduler provides the mechanism to automatically run update statistics. Job Scheduler includes a set of customizable templates that determine when **update statistics** should be run. These inputs include all parameters to **update statistics**, the **datachange** threshold values, and the time when to run **update statistics**. The Job Scheduler runs update statistics at a low priority so it does not affect critical jobs that are running concurrently.

SySAM License Management

The Sybase Software Asset Management (SySAM) implementation has changed.

The changes include:

New Features in Adaptive Server 15.0

- Asset management and reporting tools are provided with SySAM version 2.0. These tools allow you to monitor license usage and compliance.
- A single installation method supports all Adaptive Server editions.
- SySAM configuration is no longer optional.
- Flexible SySAM configuration options are provided.
- SySAM licenses are no longer shipped along with order fulfillment. You must obtain license certificates from the Sybase Product Download Center (SPDC).
- SySAM license keys include information about the support plan you purchased. You must update these licenses whenever you renew your support plan.
- Licensing policies are strictly and consistently enforced.
- Adaptive Server can function under grace periods if it is not able to obtain a license. These grace periods allow customers reasonable time to respond to the issues causing license failure. Adaptive Server continues to function normally during the grace period. Adaptive Server features or the server itself will shut down at the end of the grace period if the licensing issues are not resolved.
- You can receive real-time e-mail notifications about licensing events.
- Licenses issued from SPDC include information about the host machine where the licenses will be deployed. These licenses cannot be used on another machine without being reissued from SPDC.

These changes affect the Adaptive Server installation and configuration process. See the SySAM Configuration chapter of the *Configuration Guide* for details on SySAM configuration and deployment options. See the *Adaptive Server Installation Guide* for your platform on pre-installation planning and SySAM installation information.

Plan your SySAM deployment before installing Adaptive Server.

Warning! SySAM provides for grace periods when it encounters licensing problems. When Adaptive Server enters such a grace period, the Adaptive Server error log is updated with this information. Optionally, e-mail notifications can be configured for such events. You must fix the problems causing Adaptive Server to go into grace. While Adaptive Server functions normally during this grace period, it may shutdown or disable the licensed features if the problem causing license failure is not fixed within the grace period.

Query Processing Metrics (qp Metrics)

Query processing (QP) metrics identify and compare empirical metric values in query execution. When a query is executed, it is associated with a set of defined metrics that are the basis for comparison in QP metrics.

The metrics captured include:

- CPU execution time – the time, in milliseconds, it takes to execute the query.

- Elapsed time – the difference in milliseconds between the time the command started and the current time, as taken from the operating system clock.
- Logical IO (LIO) reads – the number of Logical IO reads.
- Physical IO (PIO) reads – the number of Physical IO reads.
- Count – the number of times a query is executed.
- Abort count – the number of times a query is aborted by the resource governor due to a resource limit being exceeded.

Each metric has three values: minimum, maximum, and average. Count and abort count are not included.

Updates to Abstract Plans

Adaptive Server 15.0 supports enhancements to the query processor.

For a description of the new and changed abstract plans, see the *Query Processing Guide*.

showplan Changes

The Adaptive Server 15.0 version of **showplan** better represents the steps performed by the query processor.

Adaptive Server changes the format of the **showplan** messages to better convey the shape of the query plan. Instead of the **showplan** messages displayed in a vertical format:

```
delete
from authors
where au_lname = "Willis"
and au_fname = "Max"
```

```
QUERY PLAN FOR STATEMENT 1 (at line 1).
```

```
The type of query is DELETE.
  The update mode is direct.

      FROM TABLE
        authors
      Nested iteration.
      Using Clustered Index.
      Index : au_names_ix
      Forward scan.
      Positioning by key.
      Keys are:
        au_lname  ASC
        au_fname  ASC
      Using I/O Size 2 Kbytes for index leaf pages.
      With LRU Buffer Replacement Strategy for index leaf pages.
      Using I/O Size 2 Kbytes for data pages.
      With LRU Buffer Replacement Strategy for data pages.
```

New Features in Adaptive Server 15.0

```
TO TABLE
authors
```

The Adaptive Server 15.0 version of **showplan** displays a series of “pipes” (the “|” symbol) to distinguish each of the steps performed by the operators.

In the following query, there are three operators, EMIT, DELETE, and SCAN, so this query includes three sets of pipes to display this organization:

```
delete
from authors
where au_lname = "Willis"
and au_fname = "Max"
```

```
QUERY PLAN FOR STATEMENT 1 (at line 1).
2 operator(s) under root
```

The type of query is DELETE.

```
ROOT:EMIT Operator
|DELETE Operator
|  The update mode is direct.
|
| | |SCAN Operator
| | |  FROM TABLE
| | |  authors
| | |  Index : aumind
| | |  Forward Scan.
| | |  Positioning by key.
| | |  Keys are:
| | |    au_lname ASC
| | |    au_fname ASC
| | |  Using I/O Size 8 Kbytes for index leaf pages.
| | |  Using LRU Buffer Replacement Strategy for index leaf pages
| | |  Using I/O Size 8 Kbytes for data pages.
| | |  With LRU Buffer Replacement Strategy for data pages.
|
| TO TABLE
|  authors
|  Using I/O Size 8 Kbytes for data pages.
```

Note: This version of Adaptive Server also includes the ability to display **showplan** messages in XML.

Secure Socket Layer Uses FIPS 140-2

In Adaptive Server 15.0, the SSL uses cryptographic modules validated for FIPS 140-2, level 1.

Secure Socket Layer (SSL) is the standard for securing the transmission of sensitive information – such as credit card numbers, stock trades, and banking transactions – over the Internet. SSL relies on public key and secret key cryptography.

The SSL used in Adaptive Server release 15.0 uses cryptographic modules validated for FIPS 140-2, level 1. The cryptographic modules are Certicom Security Builder GSE for Adaptive Server products running on Windows, Solaris, AIX and HP-UX operating systems. For more information, see validation certificate #542, dated June 2, 2005 at NIST website, <http://csrc.nist.gov/cryptval/140-1/1401val.htm>.

New Features in Adaptive Server 15.0

System Changes in Adaptive Server 15.0

Adaptive Server 15.0 introduces changes in utilities, commands, system tables, functions, stored procedures, reserved words, and monitoring tables.

Utilities

Adaptive Server 15.0 supports changes to the **bcp**, **dataserver**, **sqlsrvr**, **ddlgen**, and **preupgrade** utilities.

Table 39. Changes to utility programs

Utility	Change
bcp	<p>Adds new parameters --sho-fi and --hide-vcc, to support computed columns and functional indexes.</p> <p>Adds new parameter --maxconn to support for parallel loading into partitioned tables.</p> <p>bcp interface has changed to now allow you to run bcp in and bcp out to and from specific partitions.</p>
dataserver	Specifies the -b master_database_size parameter in terabytes.
sqlsrvr	Specifies the -b master_database_size parameter in terabytes.
ddlgen	Adds the WS object type for the -T object_type parameter to support user-defined Web services.
preupgrade	preupgrade includes options to perform incremental checks for various upgrade checks and is enhanced to run on a single database that is undergoing an upgrade using load database

See the *Utility Guide*.

Reserved Words

Adaptive Server 15.0 supports new reserved words in support of scrollable cursors and XML services.

- **insensitive** – supports scrollable cursors
- **xmlextract** – supports XML services
- **xmlparse** – supports XML services

- **xmltest** – supports XML services

You must change all database names that are new reserved words before you can upgrade from an earlier release of the server. You can change table, view, and column names or use delimited identifiers. Once you upgrade to version 15.0, you cannot use database objects whose names are new reserved words until you modify your procedures, SQL scripts, and applications.

See the Reference Manual: Blocks.

Global Variables

Adaptive Server 15.0 introduces new global variables.

Table 40. New global variables

Variable	What it displays	Value
@@rowcount	<p>Enhanced to display the number of rows moved by a cursor, scrollable or nonscrollable.</p> <p>In a nonscrollable cursor, the rows are fetched from the underlying tables to the client.</p> <p>In a scrollable cursor, the rows counted are fetched from the current result set, not from the underlying tables.</p>	<p>The value of the global variable @@rowcount is affected by the specified cursor type.</p> <p>The default, non-scrollable cursor moves forward one row at a time; the maximum value is the number of rows in the result set.</p> <p>In a scrollable cursor the value of continues to increment, whatever the direction of the fetch command; there is no maximum value.</p>
@@fetch_status	<p>The status of a fetch command used for a scrollable cursor.</p>	<p>0 – fetch statement successfully executed.</p> <p>-1 – either the fetch statement failed, or the row requested is outside the result set.</p> <p>-2 – value reserved.</p>

Variable	What it displays	Value
@@cursor_rows	The total number of rows in the cursor result set.	<p>0 – No cursors are open, or no rows qualify for the last open cursor.</p> <p>-1 – Semi-sensitive and scrollable, but the scrolling worktable is not yet populated. The number of rows that qualify the cursor is unknown.</p> <p><i>n</i> – The last opened or fetched cursor result set is fully populated; the value returned is the total number of rows in the result set.</p>

Configuration Parameters

Adaptive Server 15.0 introduces new and changed configuration parameters.

Table 41. New configuration parameters

Function	Description
enable metrics capture	Enables Adaptive Server to capture metrics at the server level.
enable semantic partitioning	Enables semantic (hash-, list-, range-) partitioning of tables and indexes at a licensed site.
enable web services	Enables web services
enable xml	Enables the XML services
max native threads per engine	Defines the maximum number of native threads the server spawns per engine
max partition degree	Configures the amount of dynamic repartitioning Adaptive Server requires, which enables Adaptive Server to use horizontal parallelism
max resource granularity	Sets the maximum percentage of the system's resources a query can use
number of devices	Specifies the number of database devices Adaptive Server can use
number of dump threads	Controls the number of threads that Adaptive Server spawns to perform a memory dump
number of open partitions	Specifies the number of partitions that Adaptive Server can access at one time.

Function	Description
optimization goal	Allows you to configure for three optimization goals, which you can specify at three tiers: server level, session level, and query level
optimization timeout limit	Specifies the amount of time Adaptive Server can spend optimizing a query as a percentage of the total time spent processing the query
rtm thread idle wait period	Defines the time a native thread used by Adaptive Server waits when it has no work to do
sysstatistics flush interval	Determines the length of the interval (in minutes) between flushes of <i>sysstatistics</i>
statement cache size	Increases the server allocation of procedure cache memory and limits the amount of memory from the procedure cache pool used for cached statements. The statement cache feature is enabled server-wide.

Table 42. Changed configuration parameters

Parameter	Change
default network packet size	Previous versions of Adaptive Server used a default network packet size of 512. As of Adaptive Server version 15.0, the default network packet size is 2048.

See the *Administration Guide: Volume 1*.

Functions

New and changed functions for Adaptive Server 15.0

Table 43. New functions

Function	Description
biginttohex	Returns the platform-independent hexadecimal equivalent of the specified integer
count_big	Returns the number of (distinct) non-null values or the number of selected rows as a <i>bigint</i>
datachange	Measures the amount of change in the data distribution since update statistics
data_pages	Returns the number of pages used by the specified table, index, or a specific

Function	Description
hextobigint	Returns the <i>bigint</i> value equivalent of a hexadecimal string
is_quiesced	Returns 1 if the database is quiesced and 0 if it is not.
partition_id	Returns the partition id of the specified data or index partition name.
partition_name	The explicit name of a new partition, <code>partition_name</code> returns the partition name
reserved_pages	Reports the number of pages reserved to a table, index or a specific partition.
row_count	Returns an estimate of the number of rows in the specified table.
showplan_in_xml	Returns the execution plan in XML.
ssel_message	Returns the message text when you specify a message ID.
tran_dumpable_status	Returns a true/false indication of whether dump transaction is allowed.
used_pages	Reports the number of pages used by a table, an index, or a specific partition.
xmlvalidate	Validates XML documents, including those containing non-ASCII characters (I18N). Described in <i>XML Services</i> .

Several function names have been replaced with more readable names.

Table 44. Superseded functions with their new function names

Superseded function name	New function name
data_pgs	data_pages
used_pgs	used_pages
reserved_pgs	reserved_pages
rowcnt	row_count
ptn_data_pgs	data_pages

Commands

New and changed commands in Adaptive Server 15.0

Table 45. New commands

Command	Function
create service	For creating a user-defined Web service.
drop service	For creating a user-defined Web service.
update table statistics	Update <i>systabstats</i> statistics for a table or a partition.

Table 46. New set command options

set Option	Description
set delayed_commit	Allows you to determine when log records are written to disk. With the delayed_commit parameter set to true, the log records are asynchronously written to the disk and control is returned to the client without waiting for the IO to complete
set plan optgoal	Sets the optimization goals at the session level.
set plan opttimeoutlimit	Sets the limit the time taken by long-running and complex queries at the session level.
set metrics_capture on/off	Activates QP metrics at the session level.

Table 47. Changed commands

Command	Change
alter table	Syntax added to support computed and materialized or non-materialized columns. Adds support for partitions.
create index	Enhanced to allow computed columns to be used as index keys, in the same way as regular columns, and to create function-based indexes. Adds support for partitions.
create table	Syntax added to support computed and materialized or non-materialized columns. Adds support for partitions.
dbcc	Adds support for partitions.

Command	Change
declare cursor	Syntax added for scrollable cursors. Syntax added to support semi_sensitive , insensitive , and scrollable cursors.
delete statistics	Adds support for partitions.
disk init	The size parameter can be specified in terabytes. Adds the directio parameter, which allows you to configure Adaptive Server to transfer data directly to disk, bypassing the operating system buffer cache
disk reinit	Adds the directio parameter, which allows you to configure Adaptive Server to transfer data directly to disk, bypassing the operating system buffer cache
fetch	fetch_orientation options added to support scrollable cursors: next , prior , first , last , absolute , and relative .
reorg	Adds support for partitions.
select	for xml clauses added to support XML services. Adds support for partitions.
truncate table	Adds support for partitions.
update all statistics	Adds support for partitions.
update statistics	Adds support for partitions.
update partition statistics	Made obsolete.

System Stored Procedures

New and changed system stored procedures in Adaptive Server 15.0

Table 48. New stored procedures

Stored procedure	Function
sp_helpcomputedcolumn	Reports information on all the computed columns in a specified table
sp_version	Returns the version information of the installation scripts (install-master , installdbccdb , and so on) that was last run and whether it was successful.

Table 49. Changed system stored procedures

Stored procedure	Change
sp_checksource	Checks the existence of computed columns source text.
sp_help	Reports information on computed columns, function-based indexes, and partitions.
sp_helppartition	Adds detailed partition information to its output.
sp_helpindex	Reports information on computed column indexes, function-based indexes, and partitions.
sp_helptext	Displays the source text of computed columns, function-based index definitions, and partitions.
sp_hidetext	Hides the text of computed columns, function-based index keys, and partition condition.
sp_modifylogin	Adds option " enable logins during recovery ".
sp_webservices	Adds addalias , deploy , dropalias , listudws , listalias , and undeploy options to support user-defined Web Services.
sp_monitorconfig	Supports the number of open partitions configuration parameter.
sp_countmetadata	Supports the number of open partitions configuration parameter.
sp_helpsegment	Prints segment bindings for objects and partitions.
sp_objectsegment	Displays segment information for all partitions for an object.
sp_placeobject	Enables future allocations for a partition from a new segment.
sp_dbcc_faultreport	Creates reports for a specific OPID or fault type.
sp_sysmon	Reports information related to open partitions Metadata Cache Management section of the configuration file.

See the *Reference Manual: Procedures*.

System Tables

New and changed system tables in Adaptive Server 15.0

Adaptive Server version 15.0 provides the necessary row-locked catalog infrastructure to support enhanced, multi-user-concurrent data-definition language (DDL) operations. However, this release does not change the catalog locking behavior for DDL operations. Applications that perform heavy multi-user DDL operations (for example, creating or

dropping tables in *tempdb*, will not see any change in behaviour in this release for catalog blocking, or any increased DDL concurrency.

Table 50. New system tables

Table	Description
<i>syspartitions</i>	<i>syspartitions</i> is completely changed from the pre-15.0 version of the table. All columns are new. <i>syspartitions</i> supports both semantic and round-robin partitioning of tables and indexes.
<i>syspartitionkeys</i>	Contains a row for each column in a partition key for each hash-, range-, and list-partitioned table.

Table 51. Changed system tables

Table	Change
<i>syscolumns</i>	<p>New fields:</p> <ul style="list-style-type: none"> • computedcol • status3 <p>New columns:</p> <ul style="list-style-type: none"> • <i>encrtype</i> – Type of encryption • <i>enclen</i> – Length of encrypted column • <i>enrkeyid</i> – Encryption key id • <i>enrkeydb</i> – Database name containing encryption key • <i>enrdate</i> – Date column was encrypted. <p>New bits in <i>status2</i> field:</p> <ul style="list-style-type: none"> • Hex: 0x00000010, Decimal 16 – the column is a computed column. • Hex: 0x00000020, Decimal 32 – the column is a materialized computed column. • Hex: 0x00000040, Decimal 64 – the column is a computed column in a view.
<i>sysconstraints</i>	New internal bit in status field: Hex 0x0100, decimal 265 – indicates a computed column object.

Table	Change
<i>sysdevices</i>	<p>New columns:</p> <ul style="list-style-type: none"> • <i>vdevno</i> – device identification number • <i>crdate</i> – date device created • <i>resizedate</i> – date size of device changed • <i>status2</i> – Additional status2 bits.
<i>sysusages</i>	New column: <i>vdevno</i> – device identification number
<i>sysstatistics</i>	<p>New columns:</p> <ul style="list-style-type: none"> • <i>indid</i> – index ID of the data partition. Always 0. • <i>partitionid</i> – ID of the data partition • <i>ststatus</i> – Internal status bits <p>Unique placement index on <i>id</i>, <i>indid</i>, <i>partitionid</i>, <i>statid</i>, <i>colidarry</i>, <i>formatid</i>, <i>sequence</i></p>
<i>systabstats</i>	<p>New columns:</p> <ul style="list-style-type: none"> • <i>partitionid</i> – ID of data or index partition • <i>statmoddate</i> – Date when statistics were last modified on disk. • <i>unusedpgcnt</i> – Number of unused pages. • <i>oampagecnt</i> – Number of OAM pages for each partition.
<i>syspartitions</i>	<i>syspartitions</i> is completely changed from the pre-15.0 version of the table. All columns are new. <i>syspartitions</i> supports both semantic and round-robin partitioning of tables and indexes.
<i>syscomments</i>	<p>New column: <i>partitionid</i> – ID of data or index partition</p> <p>Table enhanced to store the text of computed column or function-based index key expression.</p>
<i>sysindexes</i>	<p>New columns:</p> <ul style="list-style-type: none"> • <i>partitiontype</i> – partitioning strategy: 1 – range, 2 – hash, 3 – round-robin, 4 – list • <i>conditionid</i> – ID of the partition condition <p>New rows: contains one row for each function-based index or index created on a computed column.</p> <p>One new internal status bit added to the status2 field: Hex 0x8000, decimal 32768 – the index is a function-based index.</p>

Table	Change
<i>syslocks</i>	<p>New columns:</p> <ul style="list-style-type: none"> • <i>nodeid</i> – Reserved for future use. • <i>partitionid</i> – ID of data or index partition. Reserved for future use. Always 0.
<i>sysobjects</i>	<p>New object in <i>type</i> column: <i>N</i> – partition condition</p> <p>New column:</p> <ul style="list-style-type: none"> • <i>identburnmax</i> – For an identity column, maximum burned identity value • <i>spacestates</i> – Number of space states being tracked. (Only applies for DOL tables.) • <i>erlchgts</i> – Timestamp when expected row length was last changed. (Only applies to DOL tables.) <p>New row: one row for each computed column and function-based index key object</p> <ul style="list-style-type: none"> • <i>type</i> field: type “C” added to the type field, when the object is a computed column • <i>status2</i> field: new bit added to indicate that the table contains one or more function-based indexes.
<i>sysprocedures</i>	Stores a sequence tree for each computed column or function-based index definition, in binary form

Table 52. Datatype changes in system table columns

System table	Changed column	Datatype changes	Identifier name
<i>sysattributes</i>	<i>object_cinfo</i> <i>char_info</i>	<i>varchar(30) null</i> to <i>varchar(255) null</i> <i>varchar(255)</i> to <i>varchar(768)</i>	Identifier for the object
<i>sysaudits01</i> – <i>sysaudits08</i>	<i>objname</i>	<i>varchar(30) not null</i> to <i>varchar(255) not null</i>	Object name
<i>syscolumns</i>	<i>name</i>	<i>varchar(30) not null</i> to <i>varchar(255) not null</i>	Column name
	<i>remote_name</i>	<i>varchar(30) null</i> to <i>varchar(255) null</i>	Maps local names to remote names
<i>sysconfigures</i>	<i>name</i>	<i>varchar(80) null</i> to <i>varchar(255) null</i>	

System table	Changed column	Datatype changes	Identifier name
<i>sysindexes</i>	<i>name</i>	<i>varchar(30) null to varchar(255) null</i>	Index for the table name
<i>sysjars</i>	<i>jname</i>	<i>varchar(30) null to varchar(255) null</i>	JAR name
<i>sysobjects</i>	<i>name</i>	<i>varchar(30) not null to varchar(255) not null</i>	Object name
<i>sysprocesses</i>	<i>hostname</i>	<i>char(10) not null to varchar(30) null</i>	Host computer name
	<i>program_name</i>	<i>char(16) not null to varchar(30) null</i>	Name of <i>front_end</i> module
	<i>hostprocess</i>	<i>char(8) not null to varchar(30) null</i>	Host process ID number
	<i>cmd</i>	<i>char (16) not null to varchar(30) null</i>	Command or process currently being executed. Evaluation of a conditional statement, such as an if or while loop, returns.
<i>systimeranges</i>	<i>name</i>	<i>varchar(30) not null to varchar(255) not null</i>	Unique name of the time range
<i>systypes</i>	<i>name</i>	<i>varchar(30) to varchar(255)</i>	Datatype name
<i>sysdatabases</i>	<i>def_remote_loc</i>	<i>varchar(255) null to varchar(349) null.</i>	

See the *Reference Manual: Tables*.

Monitoring Tables

New and enhanced monitoring tables in Adaptive Server 15.0

Table 53. New monitoring tables

Monitoring table	Description
<i>monOpenPartitionActivity</i>	Provides monitoring information for partitions

Table 54. Changed monitoring tables

Monitoring table	Changes
<i>monEngine</i>	New columns for housekeeper GC task
<i>monCachedObject</i>	New columns for partitions
<i>monProcessObject</i>	New columns for partitions

See the *Reference Manual: Tables*.

Obtaining Help and Additional Information

Use the Sybase Getting Started CD, Product Documentation site, and online help to learn more about this product release.

- The Getting Started CD (or download) – contains release bulletins and installation guides in PDF format, and may contain other documents or updated information.
- Product Documentation at <http://sybooks.sybase.com/> – is an online version of Sybase documentation that you can access using a standard Web browser. You can browse documents online, or download them as PDFs. In addition to product documentation, the Web site also has links to EBFs/Maintenance, Technical Documents, Case Management, Solved Cases, Community Forums/Newsgroups, and other resources.
- Online help in the product, if available.

To read or print PDF documents, you need Adobe Acrobat Reader, which is available as a free download from the *Adobe* Web site.

Note: A more recent release bulletin, with critical product or document information added after the product release, may be available from the Product Documentation Web site.

Index

? (question marks) dynamic parameter 10
 @@lastlogindate global variable 101
 @@lwpid global variable 38
 @@lwpid, global variable 10
 @@plwpid global variable 38
 @@plwpid, global variable 10

A

abstract plans 104
 enhancements 103
 query-level settings 103
 saving 5
 updates to 123
 Adaptive Server Plug-in 119
 Interactive SQL 119
 Adaptive Server Plug-in updates 69
 aggregate processing 79
 alter database command 19
 alter encryption key command 19
 alter login command 19
 alter login profile command 19
 alter object modify owner command 4
 alter table 6
 log off parameter 6
 shrinking log 6
 alter...modify owner command 19
 Application Functionality Configuration Group 1
 archive database 41
 archive database access 76
 asterisk (*) in nested select statements 13
 auditing
 changes 63
 failed logins 86
 hidden passwords 85
 authmec() function 100
 automatic master key access configuration
 parameter 27

B

Backup Server 50
 backups
 database 50
 transaction 50

backupserver utility 62
 bcp utility 127
 big int datatype 117
 bigdatetime datatype 55
 biginttohex function 130
 bigtime datatype 55
 builtin date strings configuration parameter 61

C

cache_usage function 56
 chained transactions
 changes to commands and system procedures
 13
 character field, padding with str 8
 character sets, Simplified Chinese and Japanese 78
 charindex function 22
 charlength function 22
 cis idle connection timeout configuration parameter
 107
 Cluster Edition
 archive database 41
 feature and platform matrix 39
 column default cache size configuration parameter
 27
 column names
 quoted identifiers 15
 columns
 creating nonmaterialized, non-NULL 9
 data-only locked (DOL) 14
 row offset 14
 commands
 alter database 19
 alter encryption key 19
 alter login 19
 alter login profile 19
 alter table 11
 alter...modify owner 19
 changes for chained transactions 13
 create database 19
 create encryption key 19
 create login 19
 create login profile 19
 create table ... [in row [(length)] | off row]
 19
 deallocate locator 19

Index

- declare cursor ... [release_locks_on_close] 19
- declare cursor ... release_locks_on_close 12
- drop encryption key 19
- drop login 19
- drop login profile 19
- dump database ... with shrink_log 19
- dump transaction 11
- like 19
- merge 11, 19
- reorg rebuild 11
- select for update 19
- select into 11
- select into ... [in row [(length)] | off row] 19
- set 19
- truncate lob 19
- where 19
- where command 19
- component integration system (CIS)
 - end-to-end Kerberos authentication 3
- compressing data 2
- compression levels 50
- computed columns 115
 - difference between materialized and not materialized 116
 - materialized 116
 - materialized and nonmaterialized 115
 - not materialized 116
 - vs function-based indexes 116
- concatenation operators 19
- configuration parameters
 - automatic master key access 27
 - column default cache size 27
 - disable varbinary truncation 11, 27
 - enable functionality group 1, 12, 15, 16, 27
 - enable hp posix async i/o 27
 - enable inline default sharing 1
 - enable permissive unicode 1
 - kernel mode 27
 - kernel resource memory 27
 - lock timeout pipe active 10, 27
 - lock timeout pipe max messages 10, 27
 - number of disk tasks 27
 - number of network tasks 27
 - quoted identifier enhancements 1
 - select for update 1
 - sp_opt_querystats. 17
 - streamlined dynamic SQL 1, 16
 - unicode noncharacters 15

- cost of a cpu unit configuration parameter 99
- cost of a logical io configuration parameter 99
- cost of a physical io configuration parameter 99
- count_big function 130
- create database 6
- create database command
 - command 19
- create encryption key command 19
- create login command 19
- create login profile command 19
- create service command 132
- create table 6
 - command 67
- create table ... [in row [(length)] | off row] command 19
- create_locator function 22
- cursors
 - locking with select for update 8
 - releasing cursor locks at cursor close 12
 - scrollable 116

D

- data compression
 - large object (LOB) 2
 - regular data. 2
- data_pages function 130
- data-only locked (DOL) columns 14
- database dump 76
- datachange function 130
- datalength function 22
- dataserver utility 127
- datatypes
 - unitext 117
- db_attr function 56
- DDL, fully recoverable 11
- ddlgen utility 92, 127
- deallocate locator command 19
- declare cursor ... [release_locks_on_close] command 19
- defaults, sharing 9
- deferred compilation 77
 - stored procedures 83
- deferred name resolution 51
 - configuration parameter 61
- descriptors, discarding 9
- detach transaction command 68
- disable varbinary truncation configuration parameter 27
- disk devices, very large storage support 120

distributed transaction management (DTM) 68

DOL

See data-only locked (DOL)

dol_downgrade_check function 22

drop encryption key command 19

drop login command 19

drop login profile command 19

drop service command 132

dsedit utility 66

DTM

external rollbacks 68

Transaction Manager 68

dual master system key 3

dump database ... with shrink_log command 19

dump transaction recoverable operations 11

dynamic parameters, analyzing 10

E

employee lifecycle management 4

enable encrypted columns configuration parameter 99

enable functionality group configuration parameter 1, 16, 27

enable functionality group configuration parameter 12

enable hp posix async i/o configuration parameter 27

enable literal autoparm configuration parameter 107

enable merge join configuration parameter 99

enable metrics capture configuration parameter 129

enable semantic partitioning configuration parameter 129

enable web services configuration parameter 129

enable xml configuration parameter 129

encrypted columns, enhancements to 75

end-to-end Kerberos authentication

message confidentiality 3

message integrity 3

mutual authentication 3

exists and select statements 13

external login passwords 5

F

feature and platform matrix 39, 47

feature availability, for supported platforms 39, 47

FIPS 140-2 51

and SSL 124

function-based indexes 115

vs computed columns 116

functions

charindex 22

charlength 22

create_locator 22

datalength 22

dol_downgrade_check 22

locator_literal 22

locator_valid 22

lprofile_id 22

lprofile_name 22

patindex 22

return_lob 22

setdata 22

show_cached_plan_in_xml 22

show_dynamic_params_in_xml 10, 22

str 22

textptr 22

textvalid 22

G

global variables 128

@@lwpid 10, 38

@@plwpid 10, 38

groups, tempdb 53

H

hashbytes() function 100

hashed tables 67

hextobigint function 130

hidden text 5

high availability 68

High Availability 68

and passwords 86

histograms

interpolation 83

selectivity estimates 83

histogramssp_showoptstats

viewing with sp_showoptstats 11

housekeeper task 65

huge pages 67

Index

I

- IBM Tivoli Storage Manager 50
- image datatype, storing 6
- in-memory
 - databases 49
 - system procedures 57
 - temporary databases 49
- in-row LOB columns, storing 6
- incremental data transfer 52
- indent identifier, changes 15
- index names
 - quoted identifiers 15
- index_name() function 100
- inline defaults, sharing 9
- installing system stored procedures 68
- integer identity, datatypes as identity values 118
- Interactive SQL 120
- is_quiesced function 130
- isdate function 107
- isnumeric function 107
- ISO 8601 duration 4

J

- Java in Adaptive Server 70
- joins, relocated 89

K

- Kerberos
 - authentication 66
 - end-to-end authentication 3
 - unified login authentication 3
- kernel
 - and CPUs 1
 - process mode 1
 - thread pools 1
 - threaded mode 1
- kernel mode configuration parameter 27
- kernel resource memory configuration parameter 27
- keywords 127

L

- large identifiers 115
- large object (LOB) data, compressing 2
- large objects (LOBs)
 - in row LOB 6

- LOBs as variables 7
 - off row LOB 6
 - using LOB locators in T-SQL statements 7
 - where clause extension 8
- latency, reducing 16
- LDAP server authentication 65
- LDAPS 65
- like command 19
- like pattern matching 15
- Linux pSeries features 67
- literal parameterization 105
- LOB locators, using in T-SQL statements 7
- locator_literal function 22
- locator_valid function 22
- lock timeout pipe active configuration parameter 27
- lock timeout pipe max messages configuration parameter 27
- lock timeouts, monitoring 10
- locks
 - releasing cursor locks at cursor close 12
- log, shrinking 6
- login triggers 84
- logins
 - mapping 66
 - profiles 4
 - securing 4
- lprofile_id function 22
- lprofile_name function 22

M

- master system key 3
- max native threads per engine configuration parameter 129
- max online q engines configuration parameter 99
- max partition degree configuration parameter 129
- max resource granularity configuration parameter 129
- maximum nesting level configuration parameter 72
- merge command 11, 19
- metadata cache, discarding descriptors 9
- metrics elap max configuration parameter 99
- metrics exec max configuration parameter 99
- metrics lio max configuration parameter 99
- metrics pio max configuration parameter 99
- min pages for parallel scan configuration parameter 99
- mnc_full_index_filter configuration parameter 72
- monCachedProcedures monitoring table 31

monCachedStatement monitoring table 12, 31
 monCachePool monitoring table 31
 monDeadLock monitoring table 31
 monDeviceSpaceUsage monitoring table 31
 monErrorLog monitoring table 31
 monitoring tables 43, 86

- monCachedProcedures 31
- monCachedStatement 12, 31
- monCachePool 31
- monDeadLock 31
- monDeviceSpaceUsage 31
- monErrorLog 31
- monLockTimeout 31
- monLockTimeouts 10
- monOpenObjectActivity 31
- monOpenPartitionActivity 31
- monProcess 31
- monProcessActivity 31
- monProcessLookup 31
- monProcessProcedures 31
- monTableColumns 31
- monTables 31
- monWaitClassInfo 31
- monWaitEventInfo 31
- statement cache 87

 monLockTimeout monitoring table 31
 monLockTimeouts monitoring table 10
 monOpenObjectActivity monitoring table 31
 monOpenPartitionActivity monitoring table 31, 138
 monProcedureCacheMemoryUsage monitoring table 111
 monProcedureCacheModuleUsage. monitoring table 111
 monProcess monitoring table 31
 monProcessActivity monitoring table 31
 monProcessLookup monitoring table 31
 monProcessProcedures monitoring table 31
 monSQLRepActivity monitoring table 73
 monSQLRepMisses monitoring table 73
 monTableColumns monitoring table 31
 monTables monitoring table 31
 monTableTransfer monitoring table 61
 monWaitClassInfo monitoring table 31
 monWaitEventInfo monitoring table 31

N

nested select statements with asterisk (*) 13
 noncharacters, Unicode 15

nonmaterialized, non-NULL columns, creating 9
 number of devices configuration parameter 129
 number of disk tasks configuration parameter 27
 number of dump threads configuration parameter 129
 number of network tasks configuration parameter 27
 number of open partitions configuration parameter 129

O

object descriptors, discarding 9
 object ownership, transferring 4
 object_attr function 56
 off-row columns, storing 6
 openssl utility 62
 optimization goal configuration parameter 129
 optimization timeout limit configuration parameter 129
 optimizer settings, viewing 84
 optimizer, deferred compilation 77

P

parallelism in Adaptive Server 114
 parameters, dynamic 10
 partition_id function 130
 partition_name function 130
 partition_object_id function 107
 partitioning

- and query processor 114
- hash 113
- range 113
- round-robin 113
- support 113

 partitions

- compressing 2

 password_random function 71
 passwords 66

- management 4
- security 85

 patindex function 22
 pattern matching, like 15
 pci memory size configuration parameter 72
 Pluggable Authentication Module (PAM) 84
 preupgrade utility 127
 process mode 1
 profiles, login 4

Index

pssinfo function 71

Q

queries, slow-running 77

query plans 83, 114

analyzing 17

format 123

query processing

latency, reducing 16

metrics 122

query processor 114

question marks, dynamic parameter 10

quoted identifiers 15

R

reinit_descriptors subcommand 65

relaxed-durability databases 49

system procedures 57

Replication Server 65

reserved words 127

reserved_pages function 130

return_job function 22

Rivest-Shamir-Adleman (RSA) keypair
regeneration period 4

roles, securing 4

row_count function 130

row-level locking, system tables 87

row-locked system catalogs 114

rows

transferring 11

variable length 14

rtm thread idle wait period configuration parameter
129

S

scalar aggregation 80

scrollable cursors 116

Secure Socket Layer (SSL) 85

and FIPS 140-2 124

security features

dual control of encryption keys 3

employee lifecycle management 4

encrypted columns 75

end-to-end Kerberos authentication 3

external login passwords and hidden text 5

login profiles 4

securing logins, roles, and password
management 4

transferring object ownership 4

unattended startup 3

select for update

and cursors 8

command 19

locking rows 8

select into ... [in row [(length)] | off row] command
19

select statements, nested 13

send doneinprov tokens configuration parameter
99

set command 19, 77, 92

set...opt critera command 105

setdata function 22

shared memory 67

sharing inline defaults 9

show cached plans in XML 8

show_cached_plan_in_xml function 8, 22

show_dynamic_params_in_xml function 10, 22

showplan changes 123

showplan_in_xml function 130

shrinking log space 6

slow-running queries 77

sort order 78

sp_dboption system procedure 24

sp_deletesmobj stored procedure 57

sp_displaylogin system procedure 24

sp_displayroles system procedure 24

sp_downgrade system procedure 93

sp_encryption system procedure 24

sp_helpcomputedcolumn stored procedure 133

sp_helpconstraint system procedure 24

sp_helpprotect system procedure 24

sp_helpuser system procedure 24

sp_jreconfig system procedure 71

sp_listener stored procedure 66

sp_locklogin system procedure 24

sp_merge_dup_inline_default system procedure 24

sp_opt_querystats configuration parameter 17

sp_opt_querystats system procedure 24

sp_opt_querystats utility 17

sp_passwordpolicy system procedure 24

sp_querysmobj stored procedure 57

sp_securityprofile system procedure 24

sp_serveroption system procedure 24

sp_showoptstats system procedure 24

sp_spaceusage system procedure 93

- sp_tabsuspectptn system procedure 71
 - sp_version stored procedure 133
 - sproc optimize timeout limit configuration parameter 107
 - spt_TableTransfer system table 62
 - SQL
 - lightweight procedurs (LWPs) 16
 - statement replication 65
 - SQL TEXT in abstract plans 5
 - sqlsrvr utility 127
 - square brackets ([]) and like pattern matching 15
 - ssel_message function 130
 - SSL certificate, common name 66
 - SSL support 85
 - standard deviation 79
 - startup delay configuration parameter 107
 - statement cache 8
 - saving abstract plans 5
 - statement cache size configuration parameter 129
 - statistical aggregate functions 78
 - statistics
 - gathering 121
 - viewing with sp_showoptstats 11
 - stored procedures, deferred compilation 77
 - str function 22
 - padding character field 8
 - streamlined dynamic SQL configuration parameter 16
 - switches, view settings 6
 - Sybase Central 119
 - sybdiag utility 16, 30
 - sybperf utility 30
 - SySAM changes 121
 - sysattributes system table 29
 - syscacheinfo system table 29
 - syscachepoolinfo system table 29
 - syscolumns system table 29
 - syscomments system table 29
 - sysdatabases system table 62
 - sysdevices system table 62
 - syslogins system table 29
 - sysoptions 6
 - sysoptions system table 29, 96
 - syspartitionkeys system table 134
 - syspartitions system table 134
 - syspoolinfo system table 29
 - syssservers system table 29
 - sysssrvroles system table 29
 - sysstatistics flush interval configuration parameter 129
 - system encryption password, replaced 3
 - system keys
 - dual master 3
 - master 3
 - system procedures
 - changes for chained transactions 13
 - quoted identifiers 15
 - sp_dboption 11, 24
 - sp_displaylogin 24
 - sp_displayroles 24
 - sp_encryption 24
 - sp_helpconstraint 24
 - sp_helpprotect 24
 - sp_helpuser 24
 - sp_locklogin 24
 - sp_merge_dup_inline_default 24
 - sp_opt_querystats 24
 - sp_passwordpolicy 24
 - sp_securityprofile 24
 - sp_serveroption 24
 - sp_showoptstats 11, 24
 - system tables
 - row-locked 114
 - sysattributes 29
 - syscacheinfo 29
 - syscachepoolinfo 29
 - syscolumns 29
 - syscomments 29
 - syslogins 29
 - sysoptions 29
 - syspoolinfo 29
 - syssservers 29
 - sysssrvroles 29
- ## T
- T-SQL statements, using LOB locators 7
 - tables
 - compressing 2
 - quoted identifiers 15
 - transferring rows 11
 - tempdb groups 53
 - text datatype, storing 6
 - textptr function 22
 - textvalid function 22
 - thread pools 1
 - threaded mode 1

Index

- Tivoli Storage Manager 50
 - system procedures 57
- trace flags, viewing currently set 6
- trailing zeros, truncating 11
- tran_dumpable_status function 130
- transactions
 - chained 13
 - locking with select for update 8
 - mode 13
- transfer table command 59
- transferring
 - data 52
 - rows 11
- triggers, instead of 90
- truncate lob command 19

U

- Unicode
 - enhancements 119
 - noncharacters, ignoring 15
- unitext datatype, storing 6
- unitext support 117
- unsigned integer datatypes 118
- update statistics command 121
- update table statistics command 132
- updates
 - locking with select for update 8
- used_pages function 130
- user-defined functions 89
- utilities
 - sp_opt_querystats 17
 - sybdiag 16, 30
 - sybperf 30

V

- variable-length rows, expanded 14
- variables, using LOBs 7
- variance 79
- vector aggregation 80
- very large storage support (VLSS) 120
- views
 - quoted identifiers 15
- virtually hashed tables 67

W

- Web services 120
- where clause, extension 8
- where command 19

X

- XML
 - enhancements 119
 - internationalization support 119
 - schema support 119
 - showing cached plans 8
 - viewing statistics and histograms 11
- xmltable() function 88
- xmlvalidate function 130

Z

- zeros, truncating 11