



**Supported Hardware and Software**

---

**Sybase Unwired Platform 2.1**

**ESD #1**

DOCUMENT ID: DC01699-01-0211-01

LAST REVISED: December 2011

Copyright © 2011 by Sybase, Inc. All rights reserved.

This publication pertains to Sybase software and to any subsequent release until otherwise indicated in new editions or technical notes. Information in this document is subject to change without notice. The software described herein is furnished under a license agreement, and it may be used or copied only in accordance with the terms of that agreement.

To order additional documents, U.S. and Canadian customers should call Customer Fulfillment at (800) 685-8225, fax (617) 229-9845.

Customers in other countries with a U.S. license agreement may contact Customer Fulfillment via the above fax number. All other international customers should contact their Sybase subsidiary or local distributor. Upgrades are provided only at regularly scheduled software release dates. No part of this publication may be reproduced, transmitted, or translated in any form or by any means, electronic, mechanical, manual, optical, or otherwise, without the prior written permission of Sybase, Inc.

Sybase trademarks can be viewed at the Sybase trademarks page at <http://www.sybase.com/detail?id=1011207>. Sybase and the marks listed are trademarks of Sybase, Inc. ® indicates registration in the United States of America.

SAP and other SAP products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of SAP AG in Germany and in several other countries all over the world.

Java and all Java-based marks are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and other countries.

Unicode and the Unicode Logo are registered trademarks of Unicode, Inc.

All other company and product names mentioned may be trademarks of the respective companies with which they are associated.

Use, duplication, or disclosure by the government is subject to the restrictions set forth in subparagraph (c)(1)(ii) of DFARS 52.227-7013 for the DOD and as set forth in FAR 52.227-19(a)-(d) for civilian agencies.

Sybase, Inc., One Sybase Drive, Dublin, CA 94568.

# Contents

<b>Sybase Mobile SDK Requirements .....</b>	<b>1</b>
Mobile SDK System Requirements .....	1
Supported Mobile Device Platforms .....	1
Object API Applications .....	2
OData SDK Applications .....	3
HTML5/JS Hybrid Apps .....	3
Object API Application Development Environments .....	4
OData Application Development Environments .....	5
<b>Unwired Platform Runtime Requirements .....</b>	<b>6</b>
Unwired Server Requirements .....	6
Data Tier Requirements .....	7
Relay Server Requirements .....	8
Sybase Control Center Requirements .....	9
Supported Afaria Versions .....	9
BlackBerry Enterprise Server .....	10
<b>Enterprise Information Systems (EIS) and Databases .....</b>	<b>10</b>
<b>Index .....</b>	<b>11</b>

# Contents

# Sybase Mobile SDK Requirements

Use the Sybase® Mobile SDK with these operating systems, supported mobile devices, and mobile application development environments.

## Mobile SDK System Requirements

---

Each Sybase Mobile SDK host must meet the requirements for operating system and available disk space.

**Table 1. Host Operating System**

Operating System	Service Pack	CPU
Microsoft Windows XP; Professional	SP2, SP3	32-bit only
Microsoft Windows Vista; Business, Enterprise, or Ultimate	SP2	32- and 64-bit
Microsoft Windows 7; Professional, Enterprise, or Ultimate	SP1	32- and 64-bit

---

**Note:** Windows 64-bit systems are supported using WoW64.

---

**Table 2. Disk Space**

Component	Required Space
Sybase Mobile SDK (including Unwired WorkSpace, Eclipse, and JDK)	1.4GB

## Supported Mobile Device Platforms

---

The mobile application type determines which mobile device platforms and versions are supported.

## **Object API Applications**

You can build native Object API applications for these supported operating systems, mobile device platforms, and versions.

### *Android*

- Android 3.0
- Android 2.3.3
- Android 2.2

### *Apple iOS*

- Apple iOS 4.2
- Apple iOS 4.3
- Apple iOS 5.0

Recommended minimum hardware: iPhone 3GS

### *RIM BlackBerry*

- BlackBerry OS 5.0.x
- BlackBerry OS 6.0.x

Devices are required to be paired with a BES and have the BlackBerry MDS transport enabled to allow connection with the Unwired Platform Runtime and to receive push notifications.

Recommended minimum hardware: 256MB RAM, CPU clock speed greater than 500MHz. Some 5.0 devices do not meet these minimums.

### *Microsoft Windows*

- Windows XP; Professional Edition, SP2 or SP3 (32-bit only)
- Windows Vista; Business, Enterprise, and Ultimate Editions, SP2 (32- and 64-bit)
- Windows 7; Professional, Enterprise, and Ultimate Editions, SP1 (32- and 64-bit)

---

**Note:** Unwired Platform clients must run using WoW64 on any 64-bit Windows operating system. 64-bit native client libraries are not provided.

---

### *Windows Mobile Family*

- Windows Mobile 6.0 Professional
- Windows Mobile 6.0 Standard
- Windows Mobile 6.1 Professional
- Windows Mobile 6.1 Standard
- Windows Mobile 6.5 Professional

- Windows Mobile 6.5 Standard

Recommended minimum hardware: 256MB RAM, CPU clock speed greater than 500MHz.

**See also**

- *Object API Application Development Environments* on page 4

## **OData SDK Applications**

You can develop native OData SDK applications for these supported mobile device platforms and versions.

### *Android*

- Android 3.0
- Android 2.3.3
- Android 2.2

### *Apple iOS*

- Apple iOS 4.2
- Apple iOS 4.3
- Apple iOS 5.0

Recommended minimum hardware: iPhone 3GS

### *RIM BlackBerry*

- BlackBerry OS 5.0.x
- BlackBerry OS 6.0.x

Devices are required to be paired with a BES and have the BlackBerry MDS transport enabled to allow connection with the Unwired Platform Runtime and to receive push notifications.

Recommended minimum hardware: 256MB RAM, CPU clock speed greater than 500MHz. Some 5.0 devices do not meet these minimums.

**See also**

- *OData Application Development Environments* on page 5

## **HTML5/JS Hybrid Apps**

You can develop HTML5/JS Hybrid apps (Mobile Workflow applications) for these supported mobile device platforms and versions.

The Sybase HTML5/JS Hybrid Container application is available on only Windows Mobile Professional, Apple iOS, BlackBerry and Android platforms. For iOS platforms, the Hybrid

## Sybase Mobile SDK Requirements

Web Container application is available in form of a template project with static libraries for easy extensibility and branding.

### *Android*

- Android 3.0
- Android 2.3.3
- Android 2.2

### *Apple iOS*

- Apple iOS 4.2
- Apple iOS 4.3
- Apple iOS 5.0

Recommended minimum hardware: iPhone 3GS

### *RIM BlackBerry*

- BlackBerry OS 5.0.x
- BlackBerry OS 6.0.x

Devices are required to be paired with a BES and have the BlackBerry MDS transport enabled to allow connection with the Unwired Platform Runtime and to receive push notifications.

Recommended minimum hardware: 256MB RAM, CPU clock speed greater than 500MHz. Some 5.0 devices do not meet these minimums.

### *Windows Mobile*

- Windows Mobile 6.0 Professional
- Windows Mobile 6.1 Professional
- Windows Mobile 6.5 Professional

Recommended minimum hardware: 256MB RAM, CPU clock speed greater than 500MHz.

## **Object API Application Development Environments**

---

Sybase Unwired Platform supports these development environments for native Object API applications.

### *Android*

- Android SDK Tools, Revision 15 (android-sdk\_r15-windows.zip)  
<http://developer.android.com/sdk/index.html>
- Android SDK Platform-tools, Revision 5 (included with Android SDK Tools)



- SDK Platform API for specific Android version

#### *Apple iOS*

- Mac OS X 10.6 (Snow Leopard), with Xcode 4.0.2 and iOS SDK 4.3

#### *RIM BlackBerry*

- BlackBerry Java Plug-in for Eclipse v1.3
- BlackBerry Java Development Environment (JDE) v5.0 or v6.0

#### *Windows Mobile*

- Visual Studio 2008, Microsoft .NET Compact Framework 3.5

#### *Windows*

- Visual Studio 2008, Microsoft .NET Framework 3.5

#### **See also**

- *Object API Applications* on page 2

## **OData Application Development Environments**

---

Sybase Unwired Platform supports these development environments for native OData SDK applications.

#### *Android*

- Android SDK Tools, Revision 15 (android-sdk\_r15-windows.zip)  
<http://developer.android.com/sdk/index.html>
- Android SDK Platform-tools, Revision 5 (included with Android SDK Tools)
- SDK Platform API for specific Android version

#### *Apple iOS*

- Mac OS X 10.6 (Snow Leopard)
- Xcode 4.0.2 and 4.3
- iOS SDK 4.3 and 5.0

#### *RIM BlackBerry*

- BlackBerry Java Plug-in for Eclipse v1.3
- BlackBerry Java Development Environment (JDE) v5.0 or v6.0

**See also**

- *OData SDK Applications* on page 3

## Unwired Platform Runtime Requirements

Host systems must be provisioned to meet Unwired Platform runtime requirements before installing Unwired Platform runtime components. Some components require the installation of third-party software.

All Unwired Platform JAVA components require JDK Version 6 Update 26. The JDK is provided with the installation.

## Unwired Server Requirements

---

Each Unwired Server host must meet the following requirements for operating system, hardware, and available disk space.

---

**Note:** Sybase Unwired Platform Enterprise Server edition can be installed only on 64-bit operating systems. The Personal Development Server and Enterprise Development Server editions can be installed on either 32-bit or 64-bit operating systems.

---

**Table 3. Host Operating System**

Operating System	Service Pack
Microsoft Windows XP; Professional (32-bit only)	SP2, SP3
Microsoft Windows Vista; Business, Enterprise, or Ultimate	SP2
Microsoft Windows 7; Professional, Enterprise, or Ultimate	SP1
Microsoft Windows Server 2003; Standard or Enterprise	SP2
Microsoft Windows Server 2008; Standard or Enterprise	SP2
Microsoft Windows Server 2008 R2; Standard or Enterprise	SP1

**Table 4. Hardware (minimum)**

CPU	RAM
Intel Core 2 Duo processor running at 2GHz or higher, or equivalent AMD processor	4GB

**Table 5. Disk Space (minimum)**

Component	Required Space
Unwired Server	1700MB

## Data Tier Requirements

---

Each data tier host must meet the following requirements for operating system, hardware, and available disk space.

**Note:** Sybase Unwired Platform Enterprise Server edition can be installed only on 64-bit operating systems. The Personal Development Server and Enterprise Development Server editions can be installed on either 32-bit or 64-bit operating systems.

---

**Table 6. Host Operating System**

Operating System	Service Pack
Microsoft Windows XP; Professional (32-bit only)	SP2, SP3
Microsoft Windows Vista; Business, Enterprise, or Ultimate	SP2
Microsoft Windows 7; Professional, Enterprise, or Ultimate	SP1
Microsoft Windows Server 2003; Standard or Enterprise	SP2
Microsoft Windows Server 2008; Standard or Enterprise	SP2
Microsoft Windows Server 2008 R2; Standard or Enterprise	SP1

**Table 7. Hardware (minimum)**

CPU	RAM
Intel Core 2 Duo processor running at 2GHz or higher, or equivalent AMD processor	4GB

**Table 8. Disk Space (minimum)**

Component	Required Space
Data tier servers	720MB

## Relay Server Requirements

---

Each Relay Server host must meet the following requirements for operating system, hardware, and available disk space.

**Table 9. Version Required for Sybase Unwired Platform**

Relay Server Version	Support
Relay Server 12.0.1	Binaries and documentation included on Unwired Platform Runtime installation media
Sybase Hosted Relay Service 12.0.1	Supported only for development and test environments

**Note:** Sybase Hosted Relay Service requires no local system resources.

---

**Table 10. Host Operating System**

Operating System	Service Pack
Microsoft Windows Server 2003	SP2
Microsoft Windows Server 2008	SP2
Microsoft Windows Server 2008 R2	SP1
Red Hat Enterprise Linux 5 <ul style="list-style-type: none"> <li>• 32-bit Kernel 2.6.18-8.el5</li> <li>• 64-bit Kernel 2.6.18-92.1.1.el5</li> </ul>	

**Table 11. Web Server Platform**

Web Server	Version
Microsoft Internet Information Services (IIS) on Microsoft Windows	6.0, 7.0, 7.5 (32- and 64-bit)
Apache HTTP Server on RedHat Enterprise Linux 5	2.2.8 (32-bit), 2.2.15 (32- and 64-bit)

**Table 12. Hardware (minimum)**

CPU	RAM
1 or more CPUs, 2GHz or higher	2GB

**Table 13. Disk Space (minimum)**

Component	Required Space
Relay Server 12.0.1	10MB

## Sybase Control Center Requirements

---

Each host used as a Sybase Control Center client must have the required third-party applications installed. Sybase Control Center is supported on Windows only.

**Table 14. Sybase Control Center**

Software	Version
Adobe Flash Player	9.0.124+ or 10.x (recommended)
Internet Explorer	6.0 or later

If Adobe Flash Player is not installed when you connect to a Sybase Control Center server, you may see a message with a link to "Get Flash."

If an outdated version of Adobe Flash Player is installed, you may see a blank page in the browser.

Sybase Unwired Platform installation media includes an installer for Adobe Flash Player in the top-level 3rdParty folder.

---

**Note:** On Microsoft Windows 64-bit operating systems, you must use the 32-bit version of Internet Explorer.

---

## Supported Afaria Versions

---

Each Afaria® server host must meet the requirements for operating system, hardware, and available disk space. See the Afaria documentation for system requirements.

Sybase Unwired Platform supports Afaria Server 6.6, Hot Fix 5.

## BlackBerry Enterprise Server

---

Each RIM BlackBerry Enterprise Server (BES) must meet the requirements for operating system, hardware, and available disk space. See the RIM BES documentation for system requirements.

### *Supported BES Versions*

Sybase Unwired Platform supports the following BES versions.

- BlackBerry Enterprise Server v5.0
- BlackBerry Enterprise Server v4.1

### *Network Communication and Push Notifications*

Devices are required to be paired with a BES and have the BlackBerry MDS transport enabled to allow connection with the Unwired Platform Runtime and to receive push notifications.

## Enterprise Information Systems (EIS) and Databases

Unwired Platform supports connections to several types of EIS and databases, which serve as the back end for mobile applications.

### *SAP Applications*

- SAP® Java Connector (SAP JCo) 3.0.7
- SAP NetWeaver Gateway 2.0 (with Native OData SDK applications only)
- SAP Data Orchestration Engine (with Mobile Gateway 1.1 SP06)

### *Web Services*

- WS-I Basic Profile 1.1
- RESTful services, XML over HTTP(S)

### *Java Database Connectivity (JDBC)*

- SQL Anywhere® 11.x, 12.x
- Adaptive Server® Enterprise 12.5.x, 15.x
- Microsoft SQL Server 2005, 2008
- Oracle 10g, 11g
- IBM DB2 UDB 9.1

# Index

## A

- Afaria versions, supported 9
- Android
  - supported OData SDK devices and versions 3
  - supported versions 2
- Apple iOS
  - supported OData SDK devices and versions 3
  - supported versions 2

## B

- BlackBerry Enterprise Server 10

## D

- data tier requirements 7
- databases, supported 10
- development environments
  - native Object API 4
  - OData SDK 5
- disk space requirements
  - data tier 7
  - Relay Server 8
  - Sybase Mobile SDK 1
  - Unwired Server 6

## H

- HTML5/JS Hybrid apps, supported mobile device platforms 3

## M

- Microsoft .NET Compact Framework 4
- Microsoft Windows
  - operating system requirements 6, 7
  - supported versions 2
- mobile device platforms, supported 1
- mobile devices
  - operating systems supported 2
  - SDKs supported 4
- Mobile Workflow applications, supported mobile device platforms 3

## N

- Native Object API applications, mobile device platforms supported 2

## O

- OData SDK, mobile devices supported 3

## R

- Relay Server
  - disk space requirements 8
  - system requirements 8
- RIM BlackBerry
  - JDE plug-in for Eclipse 4
  - supported OData SDK devices and versions 3
  - supported versions 2

## S

- SAP connectors, supported 10
- Sybase Control Center requirements 9
- Sybase Mobile SDK requirements 1
- system requirements
  - data tier 7
  - Relay Server 8
  - Sybase Control Center client 9
  - Sybase Mobile SDK 1
  - Sybase Unwired Workspace 1
  - Unwired Server 6

## U

- Unwired Platform runtime requirements 6
- Unwired Server requirements 6

## W

- Web services, supported 10
- Windows Mobile family
  - supported versions 2

