Mobile Analytics Kit
Code Examples: HTML5

Sybase Unwired Platform 2.1 ESD #3

Document ID: DC01729-01-0213-01

Last Revised: April 2012

Copyright © 2012 by Sybase, Inc. All rights reserved.

This publication pertains to Sybase software and to any subsequent release until otherwise indicated in new editions or technical notes. Information in this document is subject to change without notice. The software described herein is furnished under a license agreement, and it may be used or copied only in accordance with the terms of that agreement.

Upgrades are provided only at regularly scheduled software release dates. No part of this publication may be reproduced, transmitted, or translated in any form or by any means, electronic, mechanical, manual, optical, or otherwise, without the prior written permission of Sybase, Inc.

Sybase trademarks can be viewed at the Sybase trademarks page at http://www.sybase.com/detail?id=1011207. Sybase and the marks listed are trademarks of Sybase, Inc. ® indicates registration in the United States of America.

SAP and other SAP products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of SAP AG in Germany and in several other countries all over the world.

Java and all Java-based marks are trademarks or registered trademarks of Oracle and/or its affiliates in the U.S. and other countries.

Unicode and the Unicode Logo are registered trademarks of Unicode, Inc.

IBM and Tivoli are registered trademarks of International Business Machines Corporation in the United States, other countries, or both.

All other company and product names mentioned may be trademarks of the respective companies with which they are associated.

Use, duplication, or disclosure by the government is subject to the restrictions set forth in subparagraph (c)(1)(ii) of DFARS 52.227-7013 for the DOD and as set forth in FAR 52.227-19(a)-(d) for civilian agencies.

Sybase, Inc., One Sybase Drive, Dublin, CA 94568.

Contents

Introduction....4

Setting Up Code Examples in Sybase Unwired WorkSpace....4

Adding the MAKit HTML5 Library to the Project....5

Code Examples Walkthrough.... 10

Basic Charts 10

Examples of Chart Configuration.... 10

ChartTypes_Bubble.xml 10

Drilldown Charts.... 13

Example of Drilldown Configuration 14

A drilldown chart renders similarly to other charts in their initial view: 14

Zooming Charts 16

Example of Zooming Chart Configuration.... 17

Dynamic Analytic Panel.... 20

Example of Variable Definition 21

What-If Analysis.... 23

Example of What-If Analysis Configuration 24

MAKit Charts API 27

Example of MAKit Charts API Methods Script 27

Introduction

Mobile Analytics Kit (MAKit) HTML5 is a client-side graphic tool for visualizing and analyzing data through Mobile Web applications on mobile devices (namely tablets) running HTML5 browsers. MAKit HTML5 is delivered as a JavaScript library that can be used with the Sybase® Unwired Platform Hybrid Web Container or any HTML5 Web application.

These code examples demonstrate the core features of MAKit charts: configuring simple charts in normal or full view, configuring drilldown and semantic zooming charts, and applying dynamic analytics and what-if analysis to the charts. MAKit HTML5 also supports default color-theme modifications through the use of custom Cascading Style Sheet (CSS) files.

MAKit HTML5 is metadata-driven development tool that can be easily integrated with any Web application. An XML-based metadata file defines all the runtime behaviors of MAKit charts; this metadata is passed from the application to the MAKit core engine when MAKit is initialized at runtime. MAKit works on any HTML5-compliant browsers both in desktop and mobile devices.

Setting Up Code Examples in Sybase Unwired WorkSpace

Note: These instructions for creating a static Web project are specific to Sybase Unwired WorkSpace. If you are using different tool for Web development, the steps may differ.

1. Start the Sybase Unwired WorkSpace IDE.
2. Select **File** > **New** > **Project.**
3. In the New Project dialog, select **Web** > **Static Web Project**, then click **Next**.
4. Enter `CodeExamples` as the project name, and unselect **Use default location.** Browse to `C:\HTML5` as the location, and click **Next**.
5. Accept the defaults in the next screen by clicking **Finish**.

   The project should look similar to this in the Sybase Unwired WorkSpace IDE:



Adding the MAKit HTML5 Library to the Project

1. In Sybase Unwired WorkSpace, open the CodeExamples project.
2. In the Project Explorer, expand the project folder `CodeExamples`.
3. Right-click **WebContent**, and select **Import.**



4. In the **Import** dialog, select **File System** as the import source under the **General** folder, and click **Next**.



5. For the "From directory," browse to `%SYBASE_UNWIRED_INSTALLLED%\UnwiredPlatform\MobileSDK\MAKit\HTML5`.

6. Click **Select All** and **Overwrite existing resources without warning**. Unselect **Create top-level folder**, then click **Finish**.

This step imports all the code example contents into `WebContent` folder. The project should now look similar to:



By default, when you run HTML5 files on the Sybase Unwired WorkSpace IDE, they are rendered in internal Web browsers within the IDE. To override the default and run the files on Google Chrome or Apple Safari browsers:

a. Verify that your desktop has either Google Chrome or Safari installed.

b. Select **Window** > **Preferences**. In the Preferences dialog, select **General** > **Web Browser.**

c. Select **Use external browser.** If Google Chrome or Safari does not appear, click **New** and follow the onscreen instructions to add an external browser to the list.

d. Select **Google Chrome** or **Safari** and click **OK.**

e. In Project Explorer, expand the `WebContent` folder, right-click **`index.html`** and select **Run As** > **Run on Server.**

f. Click **Choose an existing server** and **HTTP Preview at localhost** and click **Next.** Click **Finish** in the next screen.

Wait for the server to start and load `index.html` in the selected external browser.



This completes setting up the code examples in the Sybase Unwired WorkSpace IDE. Select **MAKit Code Examples using JQuery** to see the available code examples.


HTML5 MAKit Code Examples
Basic Charts
Chart Types
Sales Charts
Energy Charts
Drilldown Charts
Sales Drilldown Example
Energy Drilldown Example
Zooming Charts
Zooming Example 1
Zooming Example 2
Dynamic Analytics
Dynamic Analytics Example 1
Dynamic Analytics Example 2
What-If Analysis
What-If Analysis Chart Example
Charts API
Chart View API
Chart Interaction API
Chart Theme API

Code Examples Walkthrough

Basic Charts

This section demonstrates the chart types supported by the MAKit HTML5 library: column (and stacked column), bar, line, pie, and bubble. Each chart is configured in one XML metadata file.

See the `ChartTypes.html` file to see how the MAKit HTML5 JavaScript library is instantiated and loads the metadata file. `ChartTypes.html` loads six charts in normal mode. Each chart is rendered in one element HTML tag.

Examples of Chart Configuration

ChartTypes_Column.xml

```
<Chart Name="ColumnChart" Title="Region/Product Sales" ChartType="column"
Query="SalesOrder">
       <Category Format="" Column="Region" DisplayName="Region" />
       <Series Format="" Column="Product" DisplayName="Product" />
       <Values>
              <Value Format="currency" Expression="SalesAmount" />
       </Values>
 </Chart>
```

ChartTypes_Bar.xml

```
<Chart Name="BarChart" Title="Salary By Dept/Gender" ChartType="bar" Query="DeptSalary">
       <Category Format="" Column="Department" DisplayName="Department"  />
       <Series Format="" Column="Sex" DisplayName="Sex" />
       <Values>
              <Value Format="round2" Expression="Salary" DisplayName="Salary By Gender" />
       </Values>
 </Chart>
```

ChartTypes_Pie.xml

```
<Chart Name="PieChart" Title="Printer Sales " ChartType="pie" Query="PrinterSales">
       <Category Format="" Column="SalesRep" DisplayName="Sales Rep"  />
       <Values>
              <Value Format="rounded0" Expression="Sales" DisplayName="Units Sold" />
       </Values>
 </Chart>
```

ChartTypes_Bubble.xml

```
<Chart Name="BubbleChart" Title="US Crime Data" ChartType="bubble" Query="CrimeData">
       <Category Format="" Column="State" DisplayName="US State" />
       <Series Format="" Column="CrimeType" DisplayName="CrimeType" />
       <Values>
              <Value Format="rounded2" Expression="Ratio" DisplayName="Crime Ratio" />
       </Values>
</Chart>
```

The charts render in normal mode in supported mobile browsers (or Safari on an iPad):

Click the arrow in the upper-right corner of any chart to load it in full-view mode:

Click the **Table** button to show data table for the chart.



Region	Baseball Cap	Shorts	Sweatshirt	Tee Shirt	Visor
Canada	$3,228.00	$3,240.00	$13,248.00	$8,544.00	$2,688.00
Central	$20,316.00	$26,820.00	$48,960.00	$26,910.00	$11,508.00
Eastern	$20,418.00	$20,880.00	$48,384.00	$31,080.00	$12,600.00
South	$7,630.00	$10,800.00	$17,568.00	$11,472.00	$5,796.00
Western	$4,968.00	$6,300.00	$11,232.00	$6,948.00	$3,528.00

Click **Table** again to return the chart to full-view mode.

Drilldown Charts

MAKit HTML5 lets you drill down by category, or by category and series, on a single chart. You can define any level of drilldown chart in the metadata definition.

You can drill down only when the chart is in full-view mode, by double-tapping a selected category (ByCategory) or by double-tapping individual series in a chart.

Configure the drilldown charts using `<DrillDownGroup>….</DrillDownGroup>` tags; configure individual charts at each level using `<Chart> …. </Chart>` tags.

See the "Drilldown_Resellers.xml" and "Drilldown_OilPrices.xml" metadata files in the code example to see the drilldown configurations.

Example of Drilldown Configuration

```
<DrillDownGroup>
  <Chart Name="ResellerSales" Title="Reseller Sales Summary " ChartType="bar"
                       Query="ResellerSummary" >
      <Category Format="" Column="Region" DisplayName="Region" />
      <Series Format="" Column="ProductCategory" DisplayName="ProductCategory" />
      <Values>
         <Value Format="currency" Expression="SalesAmount"  DisplayName="Sales Amount" />
      </Values>
  </Chart>
  <Chart Name="SalesByCountry" Title="Reseller Sales By Country" ChartType="bar"
                                 Query="ResellerByCountry" >
     <Category Format="" Column="Country" DisplayName="Country" />
     <Series Format="" Column="ProductCategory" DisplayName="Product Category" />
     <Values>
        <Value Format="currency" Expression="SalesAmount"  DisplayName="Sales Amount" />
     </Values>
  </Chart>
  <Chart Name="SalesByCategory" Title="Sales By Product Category " ChartType="bar"
                            Query="ResellerByCategory">
     <Category Format="" Column="ProductSubCategory" DisplayName="Product Sub Category" />
     <Values>
         <Value Format="currency" Expression="SalesAmount"  DisplayName="Sales Amount" />
      </Values>
   </Chart>
</DrillDownGroup>
```

A drilldown chart renders similarly to other charts in their initial view:



Double-tap in the **Europe** region to drill down by category:



Select **Bikes** from the legend, then double-tap in the **France** region:



The chart listing the sales of **Bike Types** in **France**:



Zooming Charts

Semantic zooming lets users view a large data set in different scales. Users can see an overview of a large chart by zooming out, and get every detail by zooming in.

Configure zooming charts and chart behavior at each zooming level in the metadata configuration file.

Like drilldown charts, zooming can be performed only in full-view mode, via hierarchy buttons.

Example of Zooming Chart Configuration

```
<Chart Name="ZoomingChart" Title="Sales By Year" ChartType="Line" Query="ResellerYear" >
    <Category Format="" Column="SalesYear" DisplayName="Sales ByYear-Quarter-Month" />
    <Series Format="" Column="AmountType" DisplayName="Cost Type" />
    <Values>
        <Value Format="Rounded2" Expression="Amount"  DisplayName="Sales Amount" />
     </Values>
     <!-- Zooming Levels Configuration -->
     <ZoomingLevels>
        <ZoomingLevel Query="ResellerYear" CategoryColumn="SalesYear" Title="Year" />
        <ZoomingLevel Query="ResellerQtr" CategoryColumn="Quarter" Title="Quarter" />
        <ZoomingLevel Query="ResellerMonth" CategoryColumn="Month" Title="Month" />
    </ZoomingLevels>
 </Chart>
```

The chart initially renders at the first zooming level configured in the metadata (Sales by Year in this example), and adds hierarchy buttons—one for each level ("Year," "Quarter," and "Month").

Chart at ZoomLevel=1:



Chart at ZoomLevel=2:



Chart at ZoomLevel=3:



Click the **Table** icon to see the hierarchy table for the zooming chart.



		Month	Actual Sales	Mfg Cost
2001	Q3	7	1024062.71	610031.09
		8	3159221.13	1855387.67
		9	2509883.71	1436041.70
	Q4	10	1720634.56	1024347.55
		11	4644432.98	2766430.29
		12	3620106.22	2097321.32
2002	Q1	1	1201072.05	769629.74
		2	3348176.63	2095225.79
		3	2671357.47	1638033.66
	Q2	4	1775997.33	1063264.39
		5	4671203.33	2753596.80

Dynamic Analytic Panel

This section demonstrates the dynamic analytic capabilities of MAKit. Dynamic analytics is a powerful feature that lets you interactively visualize reports by changing some parameters ("what-if" analysis) at runtime, and refreshing charts based on the new values.

The heart of dynamic analytics is the variable definition in the metadata, which constructs the value axis expressions using the variables. When the device user changes the variable value at runtime, MAKit evaluates the value axis expression, and refreshes the charts based on the new value.

Define variables in a separate XML metadata file using `<Variables>……</Variables>` tags.

MAKit automatically generates UI controls to manipulate the values of these variables:

Variable Type	User Interface Generated by MAKit
integer	Slider control
float	PickerView control
boolean	Switch control
enum	PickerView control
datetime	Date Picker control

Example of Variable Definition

DA_Sales_Variables.xml

```
<Variables>
   <Variable Name="$salesdrive" Description="Is Global Sales Promotion ON ?"
                              VariableType="boolean" Value="0" />
   <Variable Name="$region" Description="Sales Promotion in Region "
                     VariableType="enum" Selection="1">
        <Choices>
            <Choice Display="N/A" Value="n/a" />
            <Choice Display="Eastern" Value="Eastern" />
            <Choice Display="Western" Value="Western" />
            <Choice Display="Central" Value="Central" />
            <Choice Display="South" Value="South" />
            <Choice Display="Canada" Value="Canada" />
        </Choices>
    </Variable>
</Variables>
```

The variables defined in the metadata are used in value expressions of chart configuration as shown here.

DA_SalesPerformance_Chart.xml

```
<Chart Name="ProductSales" Title="Region/Product Sales" ChartType="column" Query="SalesOrder">
     <Category Format="" Column="Region" DisplayName="Region" />
     <Series Format="" Column="Product" DisplayName="Product" />
     <Values>
         <Value Format="currency" Expression="if($salesdrive,SalesAmount+(SalesAmount *
0.30),if(Region==$region, SalesAmount+(SalesAmount * 0.80),SalesAmount))"
                  DisplayName="Sales Amount" />
     </Values>
</Chart>
```

When variable values are changed, relevant charts are refreshed based on the expression evaluation.

The Dynamic Analytic panel appears when the chart is in full-view mode:



This figure shows the refreshed chart based on a new variable value ("Western"):



What-If Analysis

What-if analysis is similar to dynamic analytics. Both allow the user to change data behind the chart and immediately see the chart updated; both map the data to UI controls on the screen. However, dynamic analytics changes the variables defined in expressions, while what-if analysis changes data retrieved from the datasource.

Configure what-if analysis in the metadata using what-if columns, which are used in value expressions in the chart configuration.

Configure what-if columns using `<WhatIfColumns>…</WhatIfColumns>` tags.

Example of What-If Analysis Configuration

```
<Chart Name="WhatIfChart" Title="Net Income From Sales" ChartType="Line" Query="ProductSales">
   <Category Format="" Column="Region" DisplayName="Region" />
   <Series Format="" Column="Product" DisplayName="Product" />
   <Values>
       <Value Format="Currency" Expression="((UnitPrice * Quantity) - ((Cost_Of_Revenue * Quantity) +
                           (RD_Cost * Quantity) + (Mkt_Cost * Quantity) + (Admin_Cost * Quantity)))"
                          ValueSequence="1" DisplayName="Net Income" />
  </Values>
  <!-- What If Columns -->
  <WhatIfColumns>
     <Column Name="UnitPrice" Description="Unit Price" VariableType="float" Min="1.0" Max="110.0"
                            Step="1.0" Decimals="2" />
     <Column Name="Cost_Of_Revenue" Description="Cost Of Revenue" VariableType="integer" Min="1"
                           Max="40" />
     <Column Name="RD_Cost" Description="R &amp; D Cost" VariableType="integer" Min="1" Max="18"  />
     <Column Name="Mkt_Cost" Description="Marketing Cost" VariableType="float" Min="1.0" Max="10.0"
                            Step="1.0" Decimals="2" />
  </WhatIfColumns>
</Chart>
```

What-if analysis works only in full-view mode, rendering a UI control for each what-if column in the metadata.

To see what-if analysis behavior, select a category and tap the **What-if** button in the toolbar to display the what-if panel. Tap the button again to close the what-If panel. When the what-if panel is open, changing the values in a what-if column immediately updates the chart for the selected category.

Chart in full-view mode before invoking the what-if panel:



Tap the **What-if** button to invoke the what-if panel for the selected category ("Central" region):



Change the values for the what-if column to update the chart accordingly:



MAKit Charts API

Use the Charts API methods to create or change all chart types and characteristics, including chart selections, drilldown options, chart themes, and whether to hide or show range selectors, toolbars.

Example of MAKit Charts API Methods Script

```
$("#rangeselector").click(function() {
    var chart = $MA("fullChart");
    chart.showRangeSelectorView(!chart.isRangeSelectorViewVisible());
    });

$("#toolbar").click(function() {
    var chart= $MA("fullChart");
    chart.showToolBar(!chart.isToolBarVisible());
    });


$("#table").click(function() {
    var chart= $MA("fullChart");
    chart.showTableView(!chart.isTableViewVisible());
    });
```

Use the Charts API methods to show and hide the toolbar, range selector, table view, and to change the chart type:

For example, use the HideToolBar API to hide the toolbar:

Use the API methods to interact with drilldown charts:



Use the Theme API to change a chart's theme color: