



Error Messages

February 2009

Version 11.0.1

Copyright and trademarks

Copyright © 2009 iAnywhere Solutions, Inc. Portions copyright © 2009 Sybase, Inc. All rights reserved.

This documentation is provided AS IS, without warranty or liability of any kind (unless provided by a separate written agreement between you and iAnywhere).

You may use, print, reproduce, and distribute this documentation (in whole or in part) subject to the following conditions: 1) you must retain this and all other proprietary notices, on all copies of the documentation or portions thereof, 2) you may not modify the documentation, 3) you may not do anything to indicate that you or anyone other than iAnywhere is the author or source of the documentation.

iAnywhere®, Sybase®, and the marks listed at <http://www.sybase.com/detail?id=1011207> are trademarks of Sybase, Inc. or its subsidiaries. ® indicates registration in the United States of America.

All other company and product names mentioned may be trademarks of the respective companies with which they are associated.

Contents

About this book	v
About the SQL Anywhere documentation	vi
SQL Anywhere error messages	1
Introduction to SQL Anywhere error messages	2
SQL Anywhere error messages sorted by SQLCODE	3
SQL Anywhere error messages sorted by SQLSTATE	44
SQL Anywhere error messages sorted by Sybase error code	83
SQL Anywhere error messages sorted by message text (A-C)	128
SQL Anywhere error messages sorted by message text (D-K)	228
SQL Anywhere error messages sorted by message text (L-S)	332
SQL Anywhere error messages sorted by message text (T-Z)	432
SQL Anywhere error messages sorted by message text (special characters)	545
MobiLink server error messages	555
MobiLink server error messages sorted by error code	556
MobiLink server error messages sorted by message text	570
MobiLink server warning messages	653
Introduction to MobiLink server warning messages	654
MobiLink server warning messages sorted by error code	655
MobiLink server warning messages sorted by message text	660
MobiLink communication error messages	685
Introduction to MobiLink communication error messages	686
MobiLink communication error messages sorted by error code	687
MobiLink communication error messages sorted by error constant	694
MobiLink communication error messages sorted by message text	702

SQL preprocessor error messages 743

SQL preprocessor error messages sorted by error code 744

SQL preprocessor error messages sorted by message text 747

About this book

Subject

This book provides a complete listing of SQL Anywhere error messages together with diagnostic information.

Audience

This book is for all users of SQL Anywhere. It is to be used in conjunction with other books in the documentation set.

About the SQL Anywhere documentation

The complete SQL Anywhere documentation is available in four formats that contain identical information.

- **HTML Help** The online Help contains the complete SQL Anywhere documentation, including the books and the context-sensitive help for SQL Anywhere tools.

If you are using a Microsoft Windows operating system, the online Help is provided in HTML Help (CHM) format. To access the documentation, choose **Start » Programs » SQL Anywhere 11 » Documentation » Online Books**.

The administration tools use the same online documentation for their Help features.

- **Eclipse** On Unix platforms, the complete online Help is provided in Eclipse format. To access the documentation, run *sadoc* from the *bin32* or *bin64* directory of your SQL Anywhere 11 installation.
- **DocCommentXchange** DocCommentXchange is a community for accessing and discussing SQL Anywhere documentation.

Use DocCommentXchange to:

- View documentation
- Check for clarifications users have made to sections of documentation
- Provide suggestions and corrections to improve documentation for all users in future releases

Visit <http://dcx.sybase.com>.

- **PDF** The complete set of SQL Anywhere books is provided as a set of Portable Document Format (PDF) files. You must have a PDF reader to view information. To download Adobe Reader, visit <http://get.adobe.com/reader/>.

To access the PDF documentation on Microsoft Windows operating systems, choose **Start » Programs » SQL Anywhere 11 » Documentation » Online Books - PDF Format**.

To access the PDF documentation on Unix operating systems, use a web browser to open *install-dir/documentation/en/pdf/index.html*.

About the books in the documentation set

The SQL Anywhere documentation consists of the following books:

- **SQL Anywhere 11 - Introduction** This book introduces SQL Anywhere 11, a comprehensive package that provides data management and data exchange, enabling the rapid development of database-powered applications for server, desktop, mobile, and remote office environments.
- **SQL Anywhere 11 - Changes and Upgrading** This book describes new features in SQL Anywhere 11 and in previous versions of the software.
- **SQL Anywhere Server - Database Administration** This book describes how to run, manage, and configure SQL Anywhere databases. It describes database connections, the database server, database

files, backup procedures, security, high availability, replication with the Replication Server, and administration utilities and options.

- **SQL Anywhere Server - Programming** This book describes how to build and deploy database applications using the C, C++, Java, PHP, Perl, Python, and .NET programming languages such as Visual Basic and Visual C#. A variety of programming interfaces such as ADO.NET and ODBC are described.
- **SQL Anywhere Server - SQL Reference** This book provides reference information for system procedures, and the catalog (system tables and views). It also provides an explanation of the SQL Anywhere implementation of the SQL language (search conditions, syntax, data types, and functions).
- **SQL Anywhere Server - SQL Usage** This book describes how to design and create databases; how to import, export, and modify data; how to retrieve data; and how to build stored procedures and triggers.
- **MobiLink - Getting Started** This book introduces MobiLink, a session-based relational-database synchronization system. MobiLink technology allows two-way replication and is well suited to mobile computing environments.
- **MobiLink - Client Administration** This book describes how to set up, configure, and synchronize MobiLink clients. MobiLink clients can be SQL Anywhere or UltraLite databases. This book also describes the Dbmlsync API, which allows you to integrate synchronization seamlessly into your C++ or .NET client applications.
- **MobiLink - Server Administration** This book describes how to set up and administer MobiLink applications.
- **MobiLink - Server-Initiated Synchronization** This book describes MobiLink server-initiated synchronization, a feature that allows the MobiLink server to initiate synchronization or perform actions on remote devices.
- **QAnywhere** This book describes QAnywhere, which is a messaging platform for mobile, wireless, desktop, and laptop clients.
- **SQL Remote** This book describes the SQL Remote data replication system for mobile computing, which enables sharing of data between a SQL Anywhere consolidated database and many SQL Anywhere remote databases using an indirect link such as email or file transfer.
- **UltraLite - Database Management and Reference** This book introduces the UltraLite database system for small devices.
- **UltraLite - C and C++ Programming** This book describes UltraLite C and C++ programming interfaces. With UltraLite, you can develop and deploy database applications to handheld, mobile, or embedded devices.
- **UltraLite - M-Business Anywhere Programming** This book describes UltraLite for M-Business Anywhere. With UltraLite for M-Business Anywhere you can develop and deploy web-based database applications to handheld, mobile, or embedded devices, running Palm OS, Windows Mobile, or Windows.
- **UltraLite - .NET Programming** This book describes UltraLite.NET. With UltraLite.NET you can develop and deploy database applications to computers, or handheld, mobile, or embedded devices.
- **UltraLiteJ** This book describes UltraLiteJ. With UltraLiteJ, you can develop and deploy database applications in environments that support Java. UltraLiteJ supports BlackBerry smartphones and Java SE environments. UltraLiteJ is based on the iAnywhere UltraLite database product.

- **Error Messages** This book provides a complete listing of SQL Anywhere error messages together with diagnostic information.

Documentation conventions

This section lists the conventions used in this documentation.

Operating systems

SQL Anywhere runs on a variety of platforms. In most cases, the software behaves the same on all platforms, but there are variations or limitations. These are commonly based on the underlying operating system (Windows, Unix), and seldom on the particular variant (AIX, Windows Mobile) or version.

To simplify references to operating systems, the documentation groups the supported operating systems as follows:

- **Windows** The Microsoft Windows family includes Windows Vista and Windows XP, used primarily on server, desktop, and laptop computers, and Windows Mobile used on mobile devices.

Unless otherwise specified, when the documentation refers to Windows, it refers to all Windows-based platforms, including Windows Mobile.

- **Unix** Unless otherwise specified, when the documentation refers to Unix, it refers to all Unix-based platforms, including Linux and Mac OS X.

Directory and file names

In most cases, references to directory and file names are similar on all supported platforms, with simple transformations between the various forms. In these cases, Windows conventions are used. Where the details are more complex, the documentation shows all relevant forms.

These are the conventions used to simplify the documentation of directory and file names:

- **Uppercase and lowercase directory names** On Windows and Unix, directory and file names may contain uppercase and lowercase letters. When directories and files are created, the file system preserves letter case.

On Windows, references to directories and files are *not* case sensitive. Mixed case directory and file names are common, but it is common to refer to them using all lowercase letters. The SQL Anywhere installation contains directories such as *Bin32* and *Documentation*.

On Unix, references to directories and files *are* case sensitive. Mixed case directory and file names are not common. Most use all lowercase letters. The SQL Anywhere installation contains directories such as *bin32* and *documentation*.

The documentation uses the Windows forms of directory names. In most cases, you can convert a mixed case directory name to lowercase for the equivalent directory name on Unix.

- **Slashes separating directory and file names** The documentation uses backslashes as the directory separator. For example, the PDF form of the documentation is found in *install-dir\Documentation\en\PDF* (Windows form).

On Unix, replace the backslash with the forward slash. The PDF documentation is found in *install-dir/documentation/en/pdf*.

- **Executable files** The documentation shows executable file names using Windows conventions, with a suffix such as *.exe* or *.bat*. On Unix, executable file names have no suffix.

For example, on Windows, the network database server is *dbsrv11.exe*. On Unix, it is *dbsrv11*.

- **install-dir** During the installation process, you choose where to install SQL Anywhere. The environment variable *SQLANY11* is created and refers to this location. The documentation refers to this location as *install-dir*.

For example, the documentation may refer to the file *install-dir/readme.txt*. On Windows, this is equivalent to *%SQLANY11%\readme.txt*. On Unix, this is equivalent to *\$(SQLANY11)/readme.txt* or *\${SQLANY11}/readme.txt*.

For more information about the default location of *install-dir*, see [“SQLANY11 environment variable” \[SQL Anywhere Server - Database Administration\]](#).

- **samples-dir** During the installation process, you choose where to install the samples included with SQL Anywhere. The environment variable *SQLANY11* is created and refers to this location. The documentation refers to this location as *samples-dir*.

To open a Windows Explorer window in *samples-dir*, from the **Start** menu, choose **Programs » SQL Anywhere 11 » Sample Applications And Projects**.

For more information about the default location of *samples-dir*, see [“SQLANY11 environment variable” \[SQL Anywhere Server - Database Administration\]](#).

Command prompts and command shell syntax

Most operating systems provide one or more methods of entering commands and parameters using a command shell or command prompt. Windows command prompts include Command Prompt (DOS prompt) and 4NT. Unix command shells include Korn shell and bash. Each shell has features that extend its capabilities beyond simple commands. These features are driven by special characters. The special characters and features vary from one shell to another. Incorrect use of these special characters often results in syntax errors or unexpected behavior.

The documentation provides command line examples in a generic form. If these examples contain characters that the shell considers special, the command may require modification for the specific shell. The modifications are beyond the scope of this documentation, but generally, use quotes around the parameters containing those characters or use an escape character before the special characters.

These are some examples of command line syntax that may vary between platforms:

- **Parentheses and curly braces** Some command line options require a parameter that accepts detailed value specifications in a list. The list is usually enclosed with parentheses or curly braces. The documentation uses parentheses. For example:

```
-x tcpip(host=127.0.0.1)
```

Where parentheses cause syntax problems, substitute curly braces:

```
-x tcpip{host=127.0.0.1}
```

If both forms result in syntax problems, the entire parameter should be enclosed in quotes as required by the shell:

```
-x "tcPIP(host=127.0.0.1)"
```

- **Quotes** If you must specify quotes in a parameter value, the quotes may conflict with the traditional use of quotes to enclose the parameter. For example, to specify an encryption key whose value contains double-quotes, you might have to enclose the key in quotes and then escape the embedded quote:

```
-ek "my \"secret\" key"
```

In many shells, the value of the key would be my "secret" key.

- **Environment variables** The documentation refers to setting environment variables. In Windows shells, environment variables are specified using the syntax `%ENVVAR%`. In Unix shells, environment variables are specified using the syntax `$ENVVAR` or `${ENVVAR}`.


Graphic icons

The following icons are used in this documentation.


- A client application.



- A database server, such as Sybase SQL Anywhere.



- A database. In some high-level diagrams, the icon may be used to represent both the database and the database server that manages it.



- Replication or synchronization middleware. These assist in sharing data among databases. Examples are the MobiLink server and the SQL Remote Message Agent.



- A programming interface.



Contacting the documentation team

We would like to receive your opinions, suggestions, and feedback on this Help.

To submit your comments and suggestions, send an email to the SQL Anywhere documentation team at iasdoc@sybase.com. Although we do not reply to emails, your feedback helps us to improve our documentation, so your input is welcome.

DocCommentXchange

You can also leave comments directly on help topics using DocCommentXchange. DocCommentXchange (DCX) is a community for accessing and discussing SQL Anywhere documentation. Use DocCommentXchange to:

- View documentation
- Check for clarifications users have made to sections of documentation
- Provide suggestions and corrections to improve documentation for all users in future releases

Visit <http://dcx.sybase.com>.

Finding out more and requesting technical support

Additional information and resources are available at the Sybase iAnywhere Developer Community at <http://www.sybase.com/developer/library/sql-anywhere-techcorner>.

If you have questions or need help, you can post messages to the Sybase iAnywhere newsgroups listed below.

When you write to one of these newsgroups, always provide details about your problem, including the build number of your version of SQL Anywhere. You can find this information by running the following command:
dbeng11 -v.

The newsgroups are located on the *forums.sybase.com* news server.

The newsgroups include the following:

- [sybase.public.sqlanywhere.general](#)
- [sybase.public.sqlanywhere.linux](#)
- [sybase.public.sqlanywhere.mobilink](#)
- [sybase.public.sqlanywhere.product_futures_discussion](#)
- [sybase.public.sqlanywhere.replication](#)
- [sybase.public.sqlanywhere.ultralite](#)
- [ianywhere.public.sqlanywhere.qanywhere](#)

For web development issues, see <http://groups.google.com/group/sql-anywhere-web-development>.

Newsgroup disclaimer

iAnywhere Solutions has no obligation to provide solutions, information, or ideas on its newsgroups, nor is iAnywhere Solutions obliged to provide anything other than a systems operator to monitor the service and ensure its operation and availability.

iAnywhere Technical Advisors, and other staff, assist on the newsgroup service when they have time. They offer their help on a volunteer basis and may not be available regularly to provide solutions and information. Their ability to help is based on their workload.

SQL Anywhere error messages

Contents

Introduction to SQL Anywhere error messages	2
SQL Anywhere error messages sorted by SQLCODE	3
SQL Anywhere error messages sorted by SQLSTATE	44
SQL Anywhere error messages sorted by Sybase error code	83
SQL Anywhere error messages sorted by message text (A-C)	128
SQL Anywhere error messages sorted by message text (D-K)	228
SQL Anywhere error messages sorted by message text (L-S)	332
SQL Anywhere error messages sorted by message text (T-Z)	432
SQL Anywhere error messages sorted by message text (special characters)	545

Introduction to SQL Anywhere error messages

Many of the error messages contain the characters %1, %2, and so on. These are replaced by the parameters to the error message.

Each error has a numeric error code, called the `SQLCODE`. Negative codes are errors, and positive codes are warnings. `SQLCODE 0` indicates successful completion.

- [“Introduction to SQL Anywhere error messages” on page 2](#)
- [“SQL Anywhere error messages sorted by `SQLCODE`” on page 3](#)
- [“SQL Anywhere error messages sorted by `SQLSTATE`” on page 44](#)
- [“SQL Anywhere error messages sorted by Sybase error code” on page 83](#)
- [“SQL Anywhere error messages sorted by message text \(A-C\)” on page 128](#)
- [“SQL Anywhere error messages sorted by message text \(D-K\)” on page 228](#)
- [“SQL Anywhere error messages sorted by message text \(L-S\)” on page 332](#)
- [“SQL Anywhere error messages sorted by message text \(T-Z\)” on page 432](#)
- [“SQL Anywhere error messages sorted by message text \(special characters\)” on page 545](#)

SQL Anywhere error messages sorted by SQLCODE

SQL Anywhere SQLCODE	Message text
-1315	"Script file missing statement \"go\" delimiter on a separate line" on page 400
-1313	"Maximum string length exceeded" on page 341
-1305	"MobiLink communication error; code: %1, parameter: %2, system code %3" on page 345
-1304	"Could not create a new text for this table with the same settings as \"%1\" on page 215
-1303	"Too many MESSAGE ... FOR CONNECTION messages" on page 487
-1288	"\"%1\" statement is not allowed on a mirrored database" on page 552
-1286	"Immediate materialized view definition cannot contain a SUM function over a nullable expression" on page 281
-1283	"A CONTAINS query is not allowed on the view or derived table '%1'" on page 128
-1281	"Another connection has the row in '%1' locked" on page 140
-1280	"Underflow when converting '%1'" on page 517
-1279	"Operation '%1' failed for reason: '%2'" on page 361
-1278	"Operation is not allowed" on page 363
-1277	"Parameter '%1' cannot be null" on page 366
-1276	"Configuration cannot not be modified while in use" on page 205
-1275	"Invalid domain '%1'" on page 300
-1274	"Index '%1' has no columns" on page 284
-1273	"Table '%1' has no columns" on page 433
-1272	"Synchronization is already in progress" on page 423
-1271	"Synchronization download failed to complete" on page 422
-1270	"Must own table '%1' in order to make an immediate view reference it" on page 348

SQL Anywhere SQLCODE	Message text
-1269	“Service statement definition is invalid or unsupported” on page 406
-1268	“The materialized view cannot be changed to immediate because its definition contains an illegal construct” on page 461
-1267	“Event parameter '%1' not found” on page 260
-1266	“No notification within timeout on queue '%1'” on page 353
-1265	“Event object named '%1' already exists” on page 259
-1264	“Event object name '%1' is not valid” on page 259
-1263	“Event notification queue '%1' not found” on page 257
-1262	“This edition of SQL Anywhere is not available on this platform” on page 480
-1261	“This server is not licensed to support '%1' connections” on page 480
-1260	“This server is not licensed to support the '%1' feature” on page 481
-1254	“MERGE statement for table '%1' failed because of a RAISERROR specification in the statement” on page 342
-1253	“The text index %1 needs to be refreshed” on page 475
-1244	“An attempt to decrypt database '%1' failed” on page 136
-1243	“An attempt to encrypt database '%1' failed” on page 137
-1241	“Value-sensitive cursor used after a TRUNCATE” on page 535
-1240	“The provided stoplist is too long” on page 466
-1238	“Passthrough SQL script failed” on page 370
-1237	“Too many columns in procedure result set” on page 483
-1236	“Too many expressions in GROUP BY list” on page 486
-1235	“Too many columns in SELECT list” on page 484
-1233	“The materialized view %1 cannot be changed to immediate because it does not have a unique index on non-nullable columns” on page 459
-1232	“Attempt to start a second snapshot in a transaction” on page 144

SQL Anywhere SQLCODE	Message text
-1231	“Statement timed out: '%1'” on page 418
-1230	“Too many open cursors” on page 487
-1229	“Reorganize table is already being run on table \"%1\” on page 387
-1226	“Foreign key columns do not match the primary key or a uniqueness constraint in \"%1\” on page 270
-1225	“Synchronization profiles are not supported for this database” on page 427
-1224	“Synchronization profile '%1' has invalid parameter '%2'” on page 426
-1223	“Synchronization profile '%1' already exists” on page 426
-1221	“Duplicate options not allowed in the CREATE DATABASE statement” on page 249
-1220	“User cannot be dropped because external logins exist for this user” on page 528
-1219	“Maintenance of dependent immediate materialized view(s) failed” on page 339
-1218	“The materialized view cannot be changed to immediate because it does not have a unique index on non-aggregate non-nullable columns” on page 461
-1217	“Synchronization profile '%1' not found” on page 427
-1216	“The arguments to this procedure must be literal strings” on page 446
-1215	“External library '%1' not loaded” on page 264
-1214	“External library '%1' is in use” on page 263
-1213	“External environment does not support result sets” on page 262
-1212	“Connection disallowed by login policy for this user” on page 206
-1211	“MERGE statement ANSI cardinality violation on table '%1'” on page 342
-1207	“Invalid use of NEAR operator in text query” on page 324
-1206	“External environments are not supported for this database” on page 263
-1205	“External environment '%1' could not be found” on page 261
-1204	“INSERT ... ON EXISTING UPDATE not allowed: immediate materialized view %1 depends on %2” on page 289

SQL Anywhere SQLCODE	Message text
-1203	“WRITETEXT not allowed: immediate materialized view %1 depends on %2” on page 540
-1202	“Operation not allowed on a table with dependent immediate materialized views” on page 363
-1201	“Client library reported an error opening object ('%1') during transfer” on page 195
-1200	“Client library reported a permissions error accessing object ('%1') during transfer” on page 194
-1199	“The materialized view cannot be changed to immediate because COUNT(*) is required to be part of the SELECT list” on page 460
-1198	“User \"%1\" already exists” on page 527
-1197	“Login policy \"%1\" in use” on page 338
-1196	“Login policies are not supported for this database” on page 338
-1195	“Login policy \"%1\" not found” on page 339
-1194	“Login policy \"%1\" already exists” on page 338
-1193	“TRUNCATE TABLE not allowed: initialized immediate materialized view %1 depends on %2” on page 496
-1192	“Cannot update multiple tables immediate materialized view %1 depends on” on page 185
-1191	“LOAD TABLE not allowed: initialized immediate materialized view %1 depends on %2” on page 336
-1190	“LOAD TABLE is not allowed on a materialized view %1” on page 334
-1189	“The UTF-16 endian specified does not match the Byte Order Mark found in the data” on page 476
-1188	“LOAD TABLE error: %1” on page 334
-1187	“Cannot append when using compression or encryption” on page 153
-1186	“Database page validation failed with code: %1” on page 234
-1185	“Index validation failed for table %1, index %2 with code: %3” on page 286

SQL Anywhere SQLCODE	Message text
-1184	“Cannot drop last unique index of an immediate materialized view” on page 166
-1183	“Support for permissions on dbspaces is not available for this database” on page 421
-1182	“Command not allowed on IMMEDIATE REFRESH text index” on page 202
-1181	“The materialized view cannot be changed to immediate because its definition must not contain more than one query block” on page 462
-1180	“Cannot set database option \"%1\" because it is on the options watch list” on page 180
-1179	“Unable to start database server: missing license file” on page 507
-1178	“Transaction log mirroring cannot be used with database mirroring” on page 492
-1177	“No plan. HTML_PLAN function is not supported for this type of statement or database” on page 354
-1176	“Plan not available. NOEXEC Plan can not be generated for this type of statement” on page 375
-1175	“Unable to acquire table locks in specified time” on page 499
-1174	“Cannot create text configuration '%1' because option '%2' has an inappropriate setting” on page 161
-1173	“Client library reported an error accessing data during transfer (%1)” on page 195
-1172	“Client application disallowed the transfer of data (%1)” on page 193
-1171	“Client application does not allow transfer of data (%1)” on page 194
-1170	“The materialized view %1 cannot be changed to immediate because it has already been initialized” on page 460
-1169	“Cannot access a table that is part of a text index” on page 150
-1168	“Cannot alter or drop a text configuration referenced by a text index” on page 153
-1167	“Cannot drop a user that owns text configurations” on page 166
-1166	“Text indexes are not supported for this database” on page 442

SQL Anywhere SQLCODE	Message text
-1165	“Error creating text index \"%1\" on table \"%2\" on page 251
-1164	“Text query parser error: %1” on page 443
-1163	“Invalid collation: \"%1\"” on page 295
-1162	“Term length outside allowed range” on page 440
-1161	“Text configuration \"%1\" already exists” on page 441
-1160	“Text configuration \"%1\".\"%2\" not found” on page 442
-1159	“Non-constant or unknown text query string” on page 355
-1158	“No matching text index” on page 352
-1157	“All column reference arguments must refer to the same table” on page 134
-1156	“Argument \"%1\" must be a column reference” on page 141
-1155	“Unable to close the cursor on table \"%1\". LOAD TABLE cannot be executed” on page 500
-1154	“Traced query (%1, %2) does not exist” on page 490
-1153	“Password has expired but cannot be changed because the database is read-only” on page 373
-1152	“Password has expired” on page 373
-1151	“The logging type ('%1') specified is invalid, not supported or incompatible” on page 457
-1150	“The SQL scripts DLL cannot be loaded” on page 473
-1149	“Database '%1' cannot be started on this platform. See http://iAnywhere.com/developer/product_manuals/sqlanywhere/notes/en/endian_cant_change_platform.html ” on page 228
-1148	“Feature not supported by the client version or the client interface” on page 267
-1147	“Database '%1' cannot be started on this platform. See http://iAnywhere.com/developer/product_manuals/sqlanywhere/notes/en/endian_corruption_warning.html ” on page 229

SQL Anywhere SQLCODE	Message text
-1146	“LOAD TABLE not allowed on temporary table which has foreign key references from another table” on page 335
-1145	“Unable to connect: The server did not accept the requested encryption type” on page 501
-1144	“‘%1’ cannot be used as the encoding specification for ‘%2’ data” on page 547
-1143	“Encryption has not been enabled” on page 251
-1142	“Use of statement ‘%1’, which requires feature ‘%2’, is not allowed” on page 523
-1141	“Unable to start database ‘%1’: NCHAR collation or tailoring not supported on this platform” on page 506
-1140	“Unable to start database ‘%1’: CHAR collation or tailoring not supported on this platform” on page 506
-1139	“The Remote Data Services feature is not supported on this platform” on page 466
-1138	“The mirror ‘%1’ does not match database ‘%2’” on page 463
-1137	“Escape character conflict ‘%1’” on page 255
-1136	“Invalid use of escape character ‘%1’” on page 323
-1135	“Invalid regular expression: %1 in ‘%2’” on page 314
-1134	“Triggers cannot be created on materialized view ‘%1’” on page 495
-1133	“Invalid trigger type for view ‘%1’” on page 321
-1132	“Maximum row size for table ‘%1’ would be exceeded” on page 340
-1131	“The attribute ‘%1’ sets an option ‘%2’ that is incompatible with ‘%3’” on page 447
-1130	“The ‘%1’ attribute is missing a comma within ‘%2’” on page 444
-1129	“The ‘%1’ attribute contains mismatched parentheses within ‘%2’” on page 444
-1128	“Start date/time for non-recurring event ‘%1’ is in the past” on page 414
-1127	“Positioned update operation attempted on a view with an INSTEAD OF trigger” on page 376

SQL Anywhere SQLCODE	Message text
-1126	“Operation failed because table or view '%1' has an INSTEAD OF trigger” on page 362
-1125	“Conflicting INSTEAD OF trigger and WITH CHECK OPTION on view '%1'” on page 205
-1124	“The dbicu library and server versions do not match” on page 452
-1123	“Invalid mime type '%1'” on page 307
-1122	“Exceeded maximum of '%1' allowable parameters” on page 260
-1121	“Not enough free space on device to grow dbspace '%1' by requested amount” on page 357
-1120	“The dbspace '%1' cannot be dropped because it contains tables or indexes” on page 453
-1119	“The '%1' property is no longer supported” on page 445
-1118	“Cannot change the MobiLink remote id when the status of the last upload is unknown” on page 155
-1117	“A row cannot be stored because it exceeds the database page size” on page 130
-1116	“Collation '%1' not supported on this platform” on page 197
-1115	“Table '%1' contains an invalid reference to the ROWID function” on page 432
-1114	“Invalid setting for SOAP header '%1'” on page 318
-1113	“Correlation name '%1' is not valid for use with the ROWID function” on page 212
-1112	“Specified file system volume not found for database '%1'” on page 411
-1111	“Information for synchronization was not provided” on page 287
-1110	“Synchronization process was unable to re-enter synchronization” on page 425
-1109	“Unable to perform requested operation since this database uses keyless encryption” on page 504
-1108	“Unable to access the filesystem on the device” on page 499
-1107	“Too many references to a BLOB” on page 489

SQL Anywhere SQLCODE	Message text
-1106	“Too many publications specified for operation” on page 488
-1104	“Too many users in database” on page 490
-1103	“No partial download was found” on page 353
-1102	“Unable to retry download because upload is not finished” on page 505
-1101	“Column '%1' not part of any indexes in its containing table” on page 201
-1100	“The operation failed because column '%1's type does not support streaming” on page 463
-1099	“Transact-SQL outer joins are currently disabled” on page 491
-1098	“A tracing connection is already active” on page 131
-1097	“ATTACH TRACING could not connect to the tracing database” on page 143
-1096	“The specified http header is malformed” on page 472
-1095	“The specified http header contains illegal or non-ASCII characters” on page 471
-1094	“The http header '%1' is reserved and cannot be modified” on page 454
-1093	“The size of the character column, variable, or value data type exceeds 32767” on page 470
-1092	“The method you attempted to invoke was not enabled for your application” on page 462
-1091	“Constraint '%1' violated: Invalid value in table '%2'” on page 211
-1090	“Function '%1' has invalid parameter '%2' ('%3')” on page 272
-1089	“Invalid commit action for shared temporary table” on page 296
-1088	“ATTACH TRACING TO LOCAL DATABASE cannot be used with a strongly encrypted database” on page 143
-1087	“Could not refresh tracing: volatile_statistics have to be collected in order for %1 specified on row %2 to be collected” on page 221
-1086	“Write access was denied” on page 540

SQL Anywhere SQLCODE	Message text
-1085	"Duplicate key column (%1)" on page 248
-1084	"Use of feature '%1' is not allowed" on page 523
-1083	"Could not refresh tracing: failed to find object %1 on row %2" on page 220
-1082	"Could not refresh tracing: invalid tracing specification on sa_diagnostic_tracing_level row %1" on page 221
-1081	"Could not refresh tracing: at least one enabled tracing level must be specified" on page 220
-1080	"Cannot revoke these permissions while user '%1' is actively replicating transactions" on page 178
-1079	"Backup is unable to open database file '%1'" on page 148
-1078	"Cycle in computed column dependencies" on page 226
-1077	"Cannot use materialized view '%1' because it has not yet been initialized" on page 187
-1076	"dbicu libraries are required but not installed" on page 240
-1075	"Failed to convert from character set '%1' to '%2'" on page 265
-1074	"Login mode '%1' not permitted by login_mode setting" on page 337
-1073	"'%1' cannot be used as the NCHAR collation: only UCA and UTF8BIN may be used" on page 547
-1072	"'%1' is not a valid character set encoding for use with collation '%2'" on page 551
-1071	"The %1 algorithm is not available in FIPS mode" on page 443
-1070	"Kerberos logins are not supported" on page 330
-1069	"Kerberos login failed" on page 330
-1068	"Default dbspace '%1' not found" on page 243
-1066	"File system error: %1" on page 268
-1065	"Attempt to use snapshot isolation in a non-snapshot transaction" on page 144

SQL Anywhere SQLCODE	Message text
-1064	“Update conflict on snapshot transaction” on page 521
-1063	“Unable to start database %1: Cannot use read-only mode if auditing is enabled” on page 505
-1062	“Statement not allowed during snapshot” on page 417
-1061	“Table created or altered after start of snapshot” on page 437
-1060	“Operation conflict with publication type” on page 362
-1057	“BACKUP clause '%1' conflicts with '%2'” on page 146
-1054	“Snapshot isolation disabled or pending” on page 409
-1053	“'%1' is an invalid value for '%2'” on page 548
-1052	“Cannot update materialized view because option '%1' has an inappropriate setting” on page 184
-1051	“Cannot create a materialized view because option '%1' has an inappropriate setting” on page 159
-1050	“Cannot return NULL result as requested data type” on page 178
-1047	“This database does not support encrypted tables” on page 480
-1046	“Illegal column definition: %1” on page 277
-1045	“Invalid backup parameter value” on page 294
-1044	“Invalid password: %1” on page 310
-1043	“Request interrupted due to timeout” on page 388
-1042	“Cannot add a comment to a table declared as LOCAL TEMPORARY” on page 152
-1041	“Materialized View '%1' not found” on page 340
-1040	“Cannot use view '%1' because it is invalid” on page 188
-1039	“Cannot connect to mirror server. Use server name '%1' to find the primary server” on page 156
-1038	“Cannot use view '%1' because it has been disabled” on page 187

SQL Anywhere SQLCODE	Message text
-1037	“Cannot drop or modify object '%1' because at least one other object (%2 '%3') depends upon it” on page 167
-1036	“The DBN/DBF parameters do not match the database for this alternate server name” on page 453
-1035	“LOAD TABLE not permitted on mirrored database” on page 336
-1034	“The '%1' attribute is not valid with procedure type '%2'” on page 445
-1033	“Unable to start database server: Server fatal error” on page 508
-1032	“Syntax error near '%1' -- The materialized view cannot be changed to immediate because its definition contains an illegal construct: '%2'” on page 429
-1031	“Syntax error near '%1' -- Materialized view definition must not use the following construct: '%2'” on page 429
-1030	“Secure HTTP connections are not supported on this platform” on page 401
-1029	“Support for materialized views is not available for this database” on page 421
-1028	“Connection attempting BACKUP has uncommitted transactions” on page 206
-1027	“Service type does not allow '%1' attribute” on page 407
-1026	“USING attribute cannot coexist with FORMAT or GROUP attributes” on page 532
-1025	“Duplicate attribute '%1' in service” on page 247
-1024	“Unsupported property '%1' in service USING attribute” on page 520
-1023	“Missing value for attribute '%1' in service” on page 344
-1022	“Invalid value for attribute '%1' in service” on page 325
-1021	“Invalid backup operation” on page 294
-1020	“Unable to start specified database: Cannot use log file '%1' since it is shorter than expected” on page 513
-1019	“Unable to start specified database: Cannot use log file '%1' since the database file has been used more recently” on page 514

SQL Anywhere SQLCODE	Message text
-1018	“Unable to start specified database: Cannot use log file '%1' since the offsets do not match the offsets in the database file” on page 514
-1017	“Unable to start specified database: '%1': transaction log file not found” on page 512
-1016	“Unable to start specified database: Cannot use log file '%1' since it has been used more recently than the database file” on page 513
-1012	“Unable to start specified database: '%1' must be upgraded to start with this server (capability %2 missing)” on page 511
-1011	“Unable to start specified database: Unknown encryption algorithm” on page 516
-1010	“Unable to start specified database: '%1' not expecting any operations in transaction log” on page 511
-1009	“Unable to start specified database: The transaction log '%1' or its mirror '%2' is invalid” on page 516
-1008	“Unable to start specified database: '%1' is an invalid transaction log mirror” on page 509
-1007	“Unable to start specified database: '%1' is an invalid transaction log” on page 509
-1006	“Unable to start specified database: '%1' is not a valid database file” on page 510
-1005	“Unable to start specified database: '%1' was created by a different version of the software” on page 512
-1004	“Unable to start specified database: '%1' is not a database” on page 510
-1003	“Too many distinct group mappings for integrated user” on page 485
-1002	“The option '%1' is not recognized” on page 465
-1001	“Parameter '%1' in procedure or function '%2' does not have a default value” on page 366
-1000	“Temporary space limit exceeded” on page 440
-999	“Invalid request log format on line %1” on page 314

SQL Anywhere SQLCODE	Message text
-998	“Cannot close a remote JDBC connection that is not the current connection” on page 155
-997	“Local connection ID does not refer to the current database” on page 337
-996	“Specified local connection ID not found” on page 411
-995	“Warning detected when optimizing SELECT INTO is treated as an error” on page 537
-994	“Too many arguments for function or procedure '%1’” on page 483
-993	“LOAD TABLE not allowed on temporary table with ON COMMIT DELETE ROWS” on page 335
-992	“The specified listener could not be registered” on page 472
-991	“Clause '%1’ has invalid attribute '%2’” on page 193
-990	“The secure connection to the remote host failed: %1” on page 468
-989	“NAMESPACE attribute is not valid with procedure type '%1’” on page 349
-988	“Invalid response from the HTTP server” on page 315
-987	“Invalid procedure subtype '%1’ for type '%2’” on page 311
-986	“Invalid procedure type '%1’” on page 312
-985	“The database name 'utility_db' is reserved for the utility database” on page 451
-984	“Could not initialize the encryption DLL: '%1’” on page 217
-983	“HTTP request failed. Status code '%1’” on page 275
-982	“Connection timed out” on page 208
-981	“Unable to connect to the remote host specified by '%1’” on page 501
-980	“The URI '%1’ is invalid” on page 476
-979	“Output file cannot be written” on page 365
-978	“Directory for output file does not exist” on page 244
-976	“Could not load the encryption DLL \"%1\” on page 219

SQL Anywhere SQLCODE	Message text
-975	"Incorrect volume ID for '%1'" on page 283
-974	"File I/O failed for '%1'" on page 268
-973	"The string is too long (%1)" on page 474
-972	"Database page size too small: %1" on page 234
-971	"Checksums are not enabled in this database" on page 192
-970	"Invalid hint specified for table '%1'" on page 303
-969	"Required operators excluded" on page 389
-968	"User '%1' already has EXECUTE permission" on page 524
-967	"Backup file '%1' already exists" on page 147
-966	"Composite ORDER BY not allowed with RANGE" on page 203
-965	"Window function requires ORDER BY" on page 538
-964	"Window function used in predicate" on page 538
-963	"Password contains an illegal character" on page 372
-962	"Argument to GROUPING aggregate must be a grouping column in the GROUP BY clause" on page 142
-961	"Input string is not base64-encoded" on page 288
-960	"Decompression error: %1" on page 242
-959	"Compression error: %1" on page 204
-958	"Password cannot be longer than %1 characters" on page 372
-957	"Invalid preceding or following size in OLAP function" on page 310
-956	"Information for synchronization is incomplete or invalid, check '%1'" on page 287
-955	"This connection already exists" on page 479
-954	"The database '%1' was not found" on page 450
-953	"A schema upgrade is not currently allowed" on page 131

SQL Anywhere SQLCODE	Message text
-952	"The status of the last synchronization upload is unknown" on page 474
-951	"Cannot access schema file '%1'" on page 151
-950	"Frame not allowed for window '%1'" on page 271
-949	"ORDER BY not allowed in window '%1'" on page 364
-948	"PARTITION BY not allowed in reference to window '%1'" on page 370
-947	"Window '%1' not found" on page 538
-946	"Result set not permitted in '%1'" on page 392
-945	"Recursive column %1: conversion from '%2' to '%3' loses precision" on page 384
-944	"Too many expressions in GROUP BY list for ROLLUP, CUBE, or GROUPING SETS operation" on page 486
-943	"No workload capture currently exists" on page 355
-942	"A workload capture (%1) is already in progress" on page 133
-941	"jConnect does not support encryption" on page 328
-940	"Invalid setting for HTTP header '%1'" on page 316
-939	"Invalid setting for HTTP option '%1'" on page 317
-938	"Recursion is not allowed without the RECURSIVE keyword" on page 383
-937	"Invalid reference to or operation on constraint '%1'" on page 313
-936	"Too many constraints in database" on page 485
-935	"Unable to start specified database: Log file error" on page 515
-934	"Unable to start specified database: Server must be upgraded to start database %1" on page 515
-933	"A log is required for IQ databases" on page 129
-931	"Service definition requires a statement when authorization is off" on page 405
-930	"(no message)" on page 553

SQL Anywhere SQLCODE	Message text
-929	"Constraint '%1' not found" on page 209
-928	"Constant expressions must not appear in GROUP BY clause" on page 209
-927	"Service statement definition is inconsistent with service type" on page 406
-926	"Host variable reference in service definition must be named" on page 274
-925	"Invalid service name '%1'" on page 316
-924	"Service '%1' in use" on page 404
-923	"Too many recursive iterations" on page 488
-922	"No column list for recursive query" on page 350
-921	"Invalid recursive query" on page 312
-920	"Service '%1' not found" on page 405
-919	"Service '%1' already exists" on page 404
-918	"A user name must be specified if AUTHORIZATION is Off" on page 132
-916	"'%1' is an unrecognized service type" on page 549
-915	"Service type required for CREATE SERVICE" on page 407
-914	"Cycle in common table expression references" on page 226
-913	"A transaction log file is required for auditing" on page 132
-912	"Insufficient memory for OPENXML query" on page 290
-911	"Control character in XML output" on page 212
-910	"System command failed with return code %1" on page 430
-908	"Invalid operation on a closed object" on page 308
-907	"No name for argument" on page 352
-906	"XMLGEN evaluation failure" on page 542
-905	"Invalid XQuery constructor" on page 325
-904	"Illegal ORDER BY in aggregate function" on page 280

SQL Anywhere SQLCODE	Message text
-903	“CDATA has a name” on page 188
-902	“Too few columns” on page 482
-901	“Undeclared tag ID: '%1’” on page 517
-900	“Parent not open: '%1’” on page 368
-899	“Illegal column name: '%1’” on page 278
-898	“Unknown FOR XML EXPLICIT directive: '%1’” on page 518
-897	“Illegal FOR XML EXPLICIT tag value: '%1’” on page 279
-896	“Cannot delete PUBLIC option '%1' since user settings exist” on page 162
-895	“Encryption error: %1” on page 250
-894	“Plan can not be generated for this type of statement” on page 375
-893	“Illegal flags value passed to OPENXML” on page 279
-892	“XPath parser error: %1” on page 543
-891	“Cannot convert between requested character sets '%1' and '%2’” on page 159
-890	“Statement size or complexity exceeds server limits” on page 417
-889	“Statement contains an illegal usage of the non-deterministic function '%1’” on page 415
-888	“XML parser error: %1” on page 542
-887	“Virtual index creation with more than %1 columns” on page 536
-883	“Character conversion error or warning report is not available when the single-byte converter is used” on page 189
-881	“Character substitution was required when converting from %1 to %2” on page 191
-879	“An invalid multi-byte input character was encountered when converting from %1 to %2” on page 138
-878	“Index '%1' can not be clustered” on page 283
-877	“SETUSER not allowed in procedures, triggers, events, or batches” on page 408

SQL Anywhere SQLCODE	Message text
-876	"Client out of memory" on page 196
-875	"There is no way to join to '%1'" on page 479
-874	"Column must be named: %1" on page 201
-873	"%1 returned multiple result sets" on page 546
-872	"%1 does not return a result set" on page 545
-871	"The database needs to be restarted for this Java related command" on page 452
-870	"Cannot convert between requested character set '%1' and database character set '%2'" on page 158
-869	"Database server cannot convert data from/to character set '%1'" on page 235
-868	"'%1' is an unknown character set encoding label" on page 548
-867	"Cannot change synchronization user_name when status of the last upload is unknown" on page 154
-866	"%1 returned a result set with a different schema than expected" on page 546
-865	"Key constraint between temporary tables requires a primary key (not unique constraint)" on page 331
-864	"Statement contains an illegal usage of the NUMBER(*) function" on page 415
-863	"Grouped query contains more than one distinct aggregate function" on page 274
-862	"The aggregate expression '%1' must appear in either the select list or a HAVING clause subquery" on page 446
-861	"Aggregated expression '%1' contains multiple columns of which one or more are outer references" on page 133
-860	"At least one of the specified dbspaces was not calibrated" on page 142
-858	"CREATE/DROP STATISTICS statement cannot refer to virtual tables" on page 222
-857	"Synchronization failed due to an error on the server: %1" on page 422
-856	"Invalid sqllen field in SQLDA" on page 319

SQL Anywhere SQLCODE	Message text
-855	"Trigger name '%1' is ambiguous" on page 494
-854	"Function or column reference to '%1' in the ORDER BY clause is invalid" on page 272
-853	"Cursor not in a valid state" on page 224
-852	"Table name '%1' is ambiguous" on page 439
-851	"Decryption error: %1" on page 242
-850	"Tables related by key constraint must both be permanent, or both be temporary and not created with ON COMMIT DELETE ROWS. For global temporary tables they must both be shared if one is shared" on page 439
-849	"Referential integrity actions other than RESTRICT not allowed for temporary tables" on page 384
-848	"Exception occurred while loading Java SecurityManager" on page 261
-847	"Java SecurityManager class not found: %1" on page 327
-846	"SET clause for column '%1' used incorrectly" on page 408
-845	"Owner '%1' used in a qualified column reference does not match correlation name '%2'" on page 365
-844	"Cannot find synchronization definition with the name '%1'" on page 169
-843	"Cannot find synchronization user with the name '%1'" on page 170
-842	"JDK '%1' is not a supported JDK" on page 329
-841	"The JDK version in '%1' does not match '%2'" on page 456
-840	"Incorrect or missing encryption key" on page 282
-839	"Download failed because of conflicts with existing rows" on page 246
-838	"TLS initialization on server failed" on page 482
-837	"Trigger or foreign key for table '%1' is no longer valid" on page 494
-836	"Procedure '%1' is no longer valid" on page 378
-835	"Event '%1' in use" on page 256

SQL Anywhere SQLCODE	Message text
-834	"Column '%1' not found in table '%2'" on page 200
-833	"Row in table '%1' was modified or deleted in BEFORE trigger" on page 396
-832	"Connection error: %1" on page 207
-831	"Definition for alias '%1' must appear before its first reference" on page 243
-830	"Alias '%1' is not unique" on page 134
-829	"TLS handshake failure" on page 481
-828	"A conflict with the dbmlsync download phase was detected" on page 128
-827	"Database upgrade not possible; user tables have table ids in system table range" on page 239
-826	"Database upgrade not possible; RowGenerator table not owned by user dbo" on page 238
-825	"Previous error lost prior to RESIGNAL" on page 376
-824	"Illegal reference to correlation name '%1'" on page 280
-823	"Cannot handle expressions involving remote tables inside stored procedures" on page 170
-822	"Table '%1' is already included" on page 434
-821	"Dbospace for table '%1' not found" on page 241
-820	"Invalid scroll position '%1'" on page 315
-819	"Table '%1' is part of a synchronization definition" on page 435
-818	"The external function call is incompatible" on page 454
-817	"Too many temporary tables in connection" on page 489
-816	"Specified database file already in use" on page 410
-815	"Cannot update column '%1' since it does not appear in the SELECT clause" on page 184
-814	"Cannot update column '%1' since it appears in the ORDER BY clause" on page 183

SQL Anywhere SQLCODE	Message text
-813	“FOR UPDATE has been incorrectly specified for a READ ONLY cursor” on page 269
-812	“The select list for the derived table '%1' has no expression to match '%2'” on page 469
-811	“JAR '%1' not found” on page 326
-810	“External object '%1' not found” on page 265
-809	“Synchronization option is too long” on page 425
-808	“An internal error was generated by the test harness” on page 138
-807	“Host variables must not be used within a batch” on page 275
-806	“System event type '%1' not found” on page 431
-805	“Synchronization option '%1' not found” on page 424
-804	“Unable to reenlist transaction; DTC may be down” on page 504
-803	“Unable to enlist transaction; DTC may be down” on page 502
-802	“Cannot enlist in a transaction with uncommitted data pending” on page 168
-801	“Cannot enlist in a transaction while already enlisted in a transaction” on page 168
-800	“Cannot commit or rollback while enlisted in a transaction” on page 156
-799	“DTC transactions are not supported on this platform” on page 247
-797	“Synchronization option '%1' contains semi-colon, equal sign, curly brace, or is null” on page 424
-794	“Synchronization server failed to commit the upload” on page 428
-793	“Invalid start date/time for event '%1'” on page 319
-792	“Invalid time '%1' for event '%2'” on page 321
-791	“Invalid day of week or month '%1' for event '%2'” on page 299
-790	“Cannot register connection to '%1' since automatic label exhausted” on page 177

SQL Anywhere SQLCODE	Message text
-789	“Cannot register '%1' since registration cookie exhausted” on page 175
-788	“Another connection has already registered as '%1’” on page 140
-787	“Current connection is already registered to '%1' as '%2’” on page 223
-786	“Cannot deregister '%1' since active registered connection exists” on page 163
-785	“Cannot deregister application because of invalid cookie” on page 163
-784	“Cannot register connection because of invalid application cookie” on page 176
-783	“Cannot register another '%1' as an exclusive application” on page 176
-782	“Cannot register '%1' since another exclusive instance is running” on page 175
-780	“Cannot update primary key for table '%1' involved in a publica- tion” on page 186
-779	“Cannot create synchronization entry for table '%1' with BLOB primary key” on page 161
-778	“Must include primary key for table '%1' in the synchronization” on page 348
-777	“Cannot synchronize table '%1' since it does not have a primary key” on page 181
-774	“Schedule '%1' for event '%2' already exists” on page 399
-773	“Schedule '%1' for event '%2' not found” on page 400
-772	“Event '%1' already exists” on page 255
-771	“Event '%1' not found” on page 256
-770	“Cannot modify publication entry using ALTER SYNCHRONIZA- TION” on page 173
-769	“Cannot modify synchronization entry using ALTER PUBLICA- TION” on page 173
-768	“Cannot subscribe to '%1’” on page 181
-767	“Cannot find synchronization subscription with the name '%1’” on page 169

SQL Anywhere SQLCODE	Message text
-766	“View references '%1', which is a temporary object. Views can only refer to permanent objects” on page 536
-765	“Synchronization message type '%1' not found” on page 423
-764	“Server not found and unable to autostart” on page 403
-763	“‘%1' is not a public Java reference, and cannot be referenced from SQL” on page 551
-762	“‘%1' is not a public Java class, and cannot be referenced from SQL” on page 550
-761	“Server capability name '%1' could not be found in the database” on page 403
-760	“Invalid SQL identifier” on page 319
-759	“SQLDA data type invalid” on page 412
-758	“The database does not support the Java Virtual Machine” on page 451
-757	“Modifications not permitted for read-only database” on page 345
-756	“Cannot uniquely identify column '%2' of table '%1' in the current JDBC result-set” on page 182
-755	“You cannot synchronize or upgrade with uncommitted transactions” on page 543
-754	“Parse error: %1” on page 369
-753	“The JDBC resultset must be positioned on an insert row in order to use the '%1' function” on page 456
-752	“Cannot call the '%1' function on a JDBC resultset when it is positioned on an insert row” on page 154
-751	“User owns tables in use” on page 530
-750	“User owns procedures in use” on page 530
-749	“Feature not available with UltraLite” on page 266
-748	“Invalid JDBC resultset concurrency” on page 305
-747	“Invalid JDBC resultset type” on page 305

SQL Anywhere SQLCODE	Message text
-746	"Cannot allocate System V resources" on page 152
-745	"Cannot initialize IQ memory manager: %1" on page 171
-744	"Invalid IQ database command line option or parameter value: %1" on page 304
-743	"Seek absolute 0 was attempted on a JDBC SAResultSet" on page 401
-742	"JDBC SAStatement batch execute abandoned" on page 329
-740	"The communications environment could not be created" on page 448
-739	"db_init has not been called or the call to db_init failed" on page 239
-738	"Password must be at least %1 characters" on page 374
-737	"Signature '%1' does not match procedure parameters" on page 409
-736	"The data type of column '%1' is not supported" on page 449
-735	"Invalid parameter" on page 309
-734	"Cannot update or delete an all-NULL row from table '%1'" on page 186
-733	"Number of columns allowing NULLs exceeds limit" on page 359
-732	"Creating remote tables with computed columns is not supported" on page 222
-731	"Cannot drop a user that owns objects involved in replication" on page 165
-730	"Invalid JAR file" on page 304
-729	"The specified foreign key (%1) can not be enforced" on page 471
-728	"Update operation attempted on non-updatable remote query" on page 522
-727	"The optimizer was unable to construct a valid access plan" on page 464
-726	"The table specification '%1' identifies more than one remote table" on page 475
-725	"Identity attribute mismatch for column '%1'" on page 277
-724	"NULL attribute mismatch for column '%1'" on page 358
-723	"The length specified for column '%1' is different than the actual length" on page 457

SQL Anywhere SQLCODE	Message text
-722	"The column '%1' does not exist in the remote table" on page 447
-721	"The data type specified for column '%1' is not compatible with the actual data type" on page 450
-720	"VALIDATE statement must refer to a base table" on page 533
-719	"RESTORE unable to start database '%1'" on page 390
-718	"RESTORE unable to write to file '%1'" on page 391
-717	"RESTORE unable to open file '%1'" on page 390
-716	"Backup file format is invalid" on page 147
-715	"Contents of backup files are inconsistent" on page 211
-714	"Invalid operation on a closed '%1'" on page 308
-713	"An internal error occurred in a '%1'" on page 138
-712	"External login for server '%1' could not be found" on page 264
-711	"Incorrect database store DLL (%1) version" on page 282
-710	"Invalid comparison" on page 297
-709	"Computed columns are not supported in this database" on page 204
-708	"READTEXT or WRITETEXT statement cannot refer to a view" on page 383
-707	"Statement is not allowed in passthrough mode" on page 416
-706	"Remote server does not have the ability to support this statement" on page 386
-705	"Return type of void from procedure '%1' cannot be used in any expression" on page 393
-704	"Cannot create an index on Java class '%1'" on page 160
-703	"Cannot insert or update computed column '%1'" on page 171
-702	"TRUNCATE TABLE statement cannot be used on a view" on page 496
-701	"Cannot access instance member through a class" on page 151
-700	"SQLDA fields inconsistent for a multi-row SQLDA" on page 413

SQL Anywhere SQLCODE	Message text
-699	“Cannot update member fields qualified with \"final\" modifier” on page 185
-698	“The remote server does not support an auto-incrementing data type” on page 467
-697	“Error during backup/restore: %1” on page 252
-696	“Invalid operation on a closed '%1'” on page 307
-695	“An internal error occurred in a '%1'” on page 137
-694	“Could not change an opened prepared statement or callable statement” on page 214
-693	“JDBC feature '%1' not supported” on page 328
-692	“Could not execute backup/restore DLL (%1) entry point” on page 216
-691	“Could not load the backup/restore DLL \"%1\" on page 218
-690	“Return value cannot be set” on page 393
-689	“Input parameter index out of range” on page 288
-688	“Strongly-encrypted database files are not supported in the runtime server” on page 419
-687	“Syntax error, cannot specify IQ specific options without specifying IQ PATH” on page 430
-686	“Insufficient cache to start Java Virtual Machine” on page 290
-685	“Resource governor for '%1' exceeded” on page 389
-684	“Rollback occurred due to deadlock during prefetch” on page 394
-683	“The cursor name '%1' already exists” on page 449
-682	“%1” on page 545
-681	“Invalid join type used with Transact-SQL outer join” on page 306
-680	“Invalid expression in WHERE clause of Transact-SQL outer join” on page 302
-678	“Index name '%1' is ambiguous” on page 285
-677	“Table '%1' has a foreign key with a referential action” on page 432

SQL Anywhere SQLCODE	Message text
-676	"The specified transaction isolation is invalid" on page 473
-675	"External environment could not be started, '%1' could not be found" on page 262
-674	"Statement's size limit is invalid" on page 418
-673	"Database upgrade not possible" on page 238
-672	"Database upgrade failed" on page 237
-671	"Parameter not registered as output parameter" on page 368
-670	"Invalid class byte code" on page 295
-669	"Method '%1' cannot be called at this time" on page 343
-668	"Cursor is restricted to FETCH NEXT operations" on page 224
-667	"Could not access column information for the table '%1'" on page 213
-666	"The remote table '%1' could not be found" on page 467
-665	"Database \"%1\" needs recovery" on page 229
-664	"Database is active" on page 231
-663	"Cannot deserialize Java object" on page 164
-662	"Cannot serialize Java object with class '%1'" on page 179
-661	"Backward scrolling cursors are not supported for remote objects" on page 148
-660	"Server '%1': %2" on page 402
-659	"Remote server '%1' could not be found" on page 385
-658	"Remote server '%1' is currently configured as read-only" on page 386
-657	"Unable to connect, server definition is circular" on page 501
-656	"Unable to connect to server '%1': %2" on page 500
-655	"Error parsing connection parameter string" on page 254
-654	"The connection parameters file could not be found" on page 448

SQL Anywhere SQLCODE	Message text
-653	“Cannot remove class '%1': member of JAR” on page 177
-652	“Could not decompress class '%1' from JAR” on page 215
-651	“An attempt to delete database '%1' failed” on page 136
-650	“Index type specification of '%1' is invalid” on page 286
-649	“Field '%1' of class '%2' cannot be NULL” on page 267
-648	“Cannot create item (%1) in the specified dbspace” on page 160
-647	“Could not execute store DLL (%1) entry point” on page 216
-646	“Could not load the store DLL \"%1\” on page 219
-645	“Database creation failed: %1” on page 231
-644	“Invalid database page size” on page 299
-643	“UNLOAD TABLE cannot be used to unload a view” on page 519
-642	“Invalid SQL descriptor name” on page 318
-641	“Error in assignment” on page 252
-640	“Invalid descriptor index” on page 300
-639	“Parameter name missing in call to procedure '%1'” on page 367
-638	“Right truncation of string data” on page 394
-637	“Duplicate insert column” on page 248
-636	“Duplicate referencing column” on page 249
-635	“GRANT of column permission on view not allowed” on page 274
-634	“Unterminated C string” on page 521
-633	“Update operation attempted on a read-only cursor” on page 522
-632	“WITH CHECK OPTION violated for insert/update on base table '%1'” on page 539
-631	“RAISERROR executed: %1” on page 382

SQL Anywhere SQLCODE	Message text
-630	"Invalid escape sequence '%1'" on page 301
-629	"Invalid escape character '%1'" on page 301
-628	"Division by zero" on page 246
-627	"Disallowed language extension detected in syntax near '%1' on line %2" on page 245
-626	"A thread used internally could not be started" on page 131
-625	"Too many parameters to this external procedure call" on page 487
-624	"Expression has unsupported data type" on page 261
-623	"Data definition statements not allowed in procedures or triggers" on page 228
-622	"Could not allocate resources to call external function" on page 214
-621	"Could not find '%1' in dynamic library '%2'" on page 217
-620	"Could not load dynamic library '%1'" on page 218
-619	"Need a dynamic library name" on page 350
-618	"Mismatch between external function platform specifier and current operating system" on page 344
-617	"Calling functions outside the database server is not supported" on page 149
-616	"Too many columns in table" on page 484
-615	"Parameter '%1' not found in procedure '%2'" on page 367
-614	"Cannot drop a user that owns messages or data types" on page 164
-613	"User-defined type '%1' not found" on page 531
-612	"User message %1 not found" on page 529
-611	"Transact-SQL feature not supported" on page 491
-610	"User message %1 already exists" on page 529
-609	"Invalid data type for column in WRITETEXT or READTEXT" on page 298

SQL Anywhere SQLCODE	Message text
-608	"Invalid TEXTPTR value used with WRITETEXT or READ-TEXT" on page 320
-607	"Cannot stop the database server" on page 180
-606	"The pattern is too long" on page 466
-605	"The server attempted to access a page beyond the end of the maximum allowable dbspace file size" on page 470
-604	"A dbspace has reached its maximum file size" on page 129
-602	"Cannot access file '%1' -- %2" on page 150
-601	"'%1' is not a known file format for loading or unloading tables" on page 550
-313	"The login ID '%1' has not been mapped to any database user ID" on page 458
-312	"User '%1' already has membership in group '%2'" on page 525
-311	"Internal rollback log corrupted" on page 293
-309	"Memory error -- transaction rolled back" on page 341
-308	"Connection was terminated" on page 208
-307	"All threads are blocked" on page 135
-306	"Deadlock detected" on page 241
-305	"I/O error %1 -- transaction rolled back" on page 276
-304	"Disk full '%1' -- transaction rolled back" on page 245
-303	"Disk write failure '%1' -- transaction rolled back" on page 246
-302	"Terminated by user -- transaction rolled back" on page 441
-301	"Internal database error %1 -- transaction rolled back" on page 293
-300	"Run time SQL error -- %1" on page 398
-299	"Statement interrupted by user" on page 416
-298	"Attempted two active database requests" on page 144
-297	"User-defined exception signaled" on page 531

SQL Anywhere SQLCODE	Message text
-296	“Error number %1 for RAISERROR must not be less than 17000” on page 253
-295	“Cannot uniquely identify rows in cursor” on page 182
-294	“Format string argument number %1 is invalid” on page 271
-289	“Multiple consolidated users cannot be defined” on page 347
-288	“Remote statement failed” on page 387
-287	“Passthrough statement inconsistent with current passthrough” on page 371
-286	“Remote message type '%1' not found” on page 385
-285	“User '%1' is not a remote user for this database” on page 526
-284	“User '%1' is already the publisher for this database” on page 526
-283	“Subscription to '%1' for '%2' not found” on page 420
-282	“Subscription to '%1' for '%2' already exists” on page 420
-281	“Table '%1' has publications” on page 434
-280	“Publication '%1' not found” on page 381
-275	“Triggers and procedures not supported in runtime server” on page 495
-274	“Procedure or trigger calls have nested too deeply” on page 381
-273	“COMMIT/ROLLBACK not allowed within trigger actions” on page 202
-272	“Invalid REFERENCES clause in trigger definition” on page 313
-271	“Trigger definition conflicts with existing triggers” on page 493
-270	“Cannot drop a user that owns procedures in runtime server” on page 165
-269	“Cannot delete or rename a column referenced in a trigger definition” on page 162
-268	“Trigger '%1' not found” on page 493
-267	“COMMIT/ROLLBACK not allowed within atomic operation” on page 202
-265	“Procedure '%1' not found” on page 379

SQL Anywhere SQLCODE	Message text
-264	“Wrong number of variables in FETCH” on page 541
-263	“Invalid absolute or relative offset in FETCH” on page 294
-262	“Label '%1' not found” on page 332
-261	“There is already a variable named '%1'” on page 477
-260	“Variable '%1' not found” on page 535
-251	“Foreign key '%1' for table '%2' duplicates an existing foreign key” on page 269
-250	“Identifier '%1' too long” on page 276
-249	“The login ID '%1' is already mapped to user ID '%2'” on page 459
-248	“Cannot map a login ID to the sys or public user ID” on page 172
-247	“The integrated login ID guest can only be mapped to the guest database user ID” on page 455
-246	“Integrated logins are not supported for this database” on page 292
-245	“Integrated login failed” on page 291
-244	“Transaction log was truncated” on page 492
-243	“Unable to delete database file” on page 502
-242	“Incomplete transactions prevent transaction log renaming” on page 281
-241	“Database backup not started” on page 230
-240	“Unknown backup operation” on page 518
-231	“Client/database server version mismatch” on page 196
-230	“sqlpp/dblib version mismatch” on page 413
-222	“Result set not allowed from within an atomic compound statement” on page 391
-221	“ROLLBACK TO SAVEPOINT not allowed” on page 395
-220	“Savepoint '%1' not found” on page 398
-218	“Authentication failed” on page 145

SQL Anywhere SQLCODE	Message text
-217	“The option '%1' cannot be set from within a procedure” on page 465
-216	“The option '%1' can only be set as a temporary option” on page 464
-215	“Procedure in use by '%1’” on page 380
-214	“Table in use” on page 438
-213	“Savepoints require a rollback log” on page 399
-212	“CHECKPOINT statement requires a rollback log” on page 191
-211	“Not allowed while '%1' is using the database” on page 355
-210	“User '%1' has the row in '%2' locked” on page 525
-209	“Constraint '%1' violated: Invalid value for column '%2' in table '%3’” on page 210
-208	“Row has changed since last read -- operation canceled” on page 396
-207	“Wrong number of values for INSERT” on page 541
-206	“Integrated logins are required, standard logins are not permitted” on page 292
-205	“Integrated logins are not permitted” on page 291
-204	“Only the DBA can set the option '%1’” on page 361
-203	“Cannot set a temporary option for user '%1’” on page 179
-202	“Only PUBLIC settings are allowed for option '%1’” on page 360
-201	“Invalid setting for option '%1’” on page 317
-200	“Invalid option '%1' -- no PUBLIC setting exists” on page 308
-199	“INSERT/DELETE on cursor can modify only one table” on page 289
-198	“Primary key for row in table '%1' is referenced by foreign key '%2' in table '%3’” on page 377
-197	“No current row of cursor” on page 350
-196	“Index '%1' for table '%2' would not be unique” on page 284
-195	“Column '%1' in table '%2' cannot be NULL” on page 199

SQL Anywhere SQLCODE	Message text
-194	"No primary key value for foreign key '%1' in table '%2'" on page 354
-193	"Primary key for table '%1' is not unique : Primary key value ('%2')" on page 378
-192	"Update operation attempted on non-updatable query" on page 522
-191	"Cannot modify column '%1' in table '%2'" on page 172
-190	"Cannot update an expression" on page 183
-189	"Unable to find in index '%1' for table '%2'" on page 503
-188	"Not enough values for host variables" on page 358
-187	"Illegal cursor operation attempt" on page 278
-186	"Subquery cannot return more than one row" on page 419
-185	"SELECT returns more than one row" on page 402
-184	"Column '%1' in table '%2' cannot be NULL. The invalid data was supplied to LOAD TABLE in a data file on line %3" on page 199
-183	"Cannot find index named '%1'" on page 168
-182	"Not enough fields allocated in SQLDA" on page 356
-181	"No indicator variable provided for NULL result" on page 351
-180	"Cursor not open" on page 225
-172	"Cursor already open" on page 223
-171	"Error opening cursor" on page 253
-170	"Cursor has not been declared" on page 224
-165	"Java VM heap exhausted at internal function: %1" on page 327
-164	"Namespace heap exhausted at internal function: %1" on page 349
-163	"Derived table '%1' has no name for column %2" on page 244
-162	"Cannot convert %1 to a %2. The bad value was supplied for column '%3' on row %4 of the data file" on page 157

SQL Anywhere SQLCODE	Message text
-161	“Invalid type on DESCRIBE statement” on page 322
-160	“Can only describe a SELECT statement” on page 149
-159	“Invalid column number” on page 296
-158	“Value %1 out of range for destination” on page 533
-157	“Cannot convert %1 to a %2” on page 157
-156	“Invalid expression near '%1’” on page 302
-155	“Invalid host variable” on page 303
-154	“Wrong number of parameters to function '%1’” on page 541
-153	“Select lists in UNION, INTERSECT, or EXCEPT do not match in length” on page 401
-152	“Invalid ORDER BY specification” on page 309
-151	“Subquery allowed only one select list item” on page 419
-150	“Invalid use of an aggregate function” on page 323
-149	“Function or column reference to '%1’ must also appear in a GROUP BY” on page 273
-148	“Unknown function '%1’” on page 519
-147	“There is more than one way to join '%1’ to '%2’” on page 477
-146	“There is no way to join '%1’ to '%2’” on page 478
-145	“Foreign key name '%1’ not found” on page 270
-144	“Column '%1’ found in more than one table -- need a correlation name” on page 198
-143	“Column '%1’ not found” on page 200
-142	“Correlation name '%1’ not found” on page 213
-141	“Table '%1’ not found” on page 436
-140	“User ID '%1’ does not exist” on page 528

SQL Anywhere SQLCODE	Message text
-139	"More than one table is identified as '%1'" on page 347
-138	"DbSPACE '%1' not found" on page 240
-137	"Table '%1' requires a unique correlation name" on page 436
-136	"Table '%1' is in an outer join cycle" on page 435
-135	"Language extension" on page 333
-134	"Feature '%1' not implemented" on page 266
-133	"Invalid prepared statement type" on page 311
-132	"SQL statement error" on page 412
-131	"Syntax error near '%1' %2" on page 428
-130	"Invalid statement" on page 320
-128	"Cannot drop a user that owns tables in runtime system" on page 165
-127	"Cannot alter a column in an index" on page 152
-126	"Table cannot have two primary keys" on page 437
-125	"ALTER clause conflict" on page 135
-124	"More columns are being dropped from table '%1' than are defined" on page 346
-123	"User '%1' is not a user group" on page 527
-122	"Operation would cause a group cycle" on page 363
-121	"Permission denied: %1" on page 374
-120	"User '%1' already has GRANT permission" on page 524
-119	"Primary key column '%1' already defined" on page 377
-118	"Table '%1' has no primary key" on page 433
-116	"Table must be empty" on page 438
-114	"Number of columns defined for the view does not match SELECT statement" on page 360

SQL Anywhere SQLCODE	Message text
-113	“Column '%1' in foreign key has a different definition than primary key” on page 198
-112	“Table already has a primary key” on page 437
-111	“Index name '%1' not unique” on page 285
-110	“Item '%1' already exists” on page 326
-109	“There are still active database connections” on page 477
-108	“Connection not found” on page 207
-107	“Error writing to transaction log file” on page 254
-106	“Cannot open transaction log file -- %1” on page 174
-105	“Database cannot be started -- %1” on page 230
-104	“Invalid user ID or password on preprocessed module” on page 325
-103	“Invalid user ID or password” on page 324
-102	“Database server connection limit exceeded” on page 236
-101	“Not connected to a database” on page 356
-100	“Database server not found” on page 237
-99	“Connections to database have been disabled” on page 209
-98	“Authentication violation” on page 145
-97	“Database page size too big: %1” on page 233
-96	“Database server already running” on page 235
-95	“Parse error: %1” on page 369
-94	“Invalid type for field reference” on page 322
-93	“Class '%1' has no public field '%2’” on page 192
-92	“‘%1' is not a valid class file” on page 552
-91	“Procedure '%1' terminated with unhandled exception '%2’” on page 379

SQL Anywhere SQLCODE	Message text
-90	"Argument %1 of procedure '%2' cannot be NULL" on page 141
-89	"Database server not running in multi-user mode" on page 237
-88	"Client/server communications protocol version mismatch" on page 197
-87	"Database name required to start server" on page 232
-86	"Not enough memory to start" on page 357
-85	"Communication error" on page 203
-84	"Specified database is invalid" on page 410
-83	"Specified database not found" on page 410
-82	"Unable to start specified database: %1" on page 508
-81	"Invalid database server command line" on page 299
-80	"Unable to start database server" on page 507
-79	"Invalid local database option" on page 306
-78	"Dynamic memory exhausted" on page 250
-77	"Database name not unique" on page 232
-76	"Request denied -- no active databases" on page 388
-75	"Request to start/stop database denied" on page 389
-74	"The selected database is currently inactive" on page 469
-72	"No database file specified" on page 351
0	"(no message)" on page 553
100	"Row not found" on page 397
101	"Value truncated" on page 534
102	"Using temporary table" on page 532
103	"Invalid data conversion" on page 297
104	"Row has been updated since last time read" on page 395

SQL Anywhere SQLCODE	Message text
105	“Procedure has completed” on page 380
106	“Value for column '%1' in table '%2' has changed” on page 534
107	“Language extension detected in syntax near '%1' on line %2” on page 333
109	“Null value eliminated in aggregate function” on page 359
110	“Transaction log backup page only partially full” on page 492
111	“Statement cannot be executed” on page 414
112	“More information required” on page 346
113	“Database option '%1' for user '%2' has an invalid setting” on page 233
114	“Character set conversion to '%1' cannot be performed; '%2' is used instead” on page 189
115	“Database server cannot convert data from/to character set '%1', conversion may not be correct” on page 236
116	“Language '%1' is not supported, '%2' will be used” on page 332
117	“Unsupported character set '%1' and unsupported language '%2'; language used is '%3' instead” on page 520
118	“Illegal user selectivity estimate specified” on page 281
119	“Unable to open backup log '%1'” on page 503
120	“‘%1' is an unknown option” on page 549
121	“Cursor option values changed” on page 225
122	“The result returned is non-deterministic” on page 468
124	“Invalid data conversion: NULL was inserted for column '%1' on row %2” on page 298
125	“An invalid multi-byte input character was encountered when converting from %1 to %2” on page 139
127	“Character substitution occurred when converting from %1 to %2” on page 190
129	“Plan may contain virtual indexes” on page 375

SQL Anywhere SQLCODE	Message text
130	"A row was dropped because it could not be converted to the new schema format" on page 130
132	"Cannot output the histogram for string column '%1'" on page 174
133	"UltraLite connection was restored" on page 497
134	"UltraLite cursor (or result set or table) was restored" on page 498
136	"The database was created" on page 452
137	"Row was dropped from table %1 to maintain referential integrity" on page 397
138	"Publication predicates were not evaluated" on page 382
139	"Option '%1' specified more than once" on page 364
140	"Encryption has not been enabled" on page 251
141	"Passthrough SQL script failed" on page 371
142	"UltraLite database state was restored" on page 498
143	"Retrying read of corrupt page (page '%1')" on page 392
144	"Mirror file requires higher checksum_level" on page 343
145	"Two rows with the same primary key have been download for table '%1'" on page 497
146	"Event notification queue '%1' is full, notification discarded" on page 257
147	"Event notifications lost on queue '%1'" on page 258
148	"Event notification queue '%1' not found warning" on page 258
149	"Automatic database upgrade applied" on page 146
200	"Warning: %1" on page 537
201	"The ICU collation '%1' has defaulted to another collation" on page 455

SQL Anywhere error messages sorted by SQLSTATE

SQLSTATE	Message text
00000	“(no message)” on page 553
01000	“Warning: %1” on page 537
01003	“Null value eliminated in aggregate function” on page 359
01004	“Value truncated” on page 534
01005	“Encryption has not been enabled” on page 251
01006	“Passthrough SQL script failed” on page 371
01S02	“Cursor option values changed” on page 225
01W01	“Invalid data conversion: NULL was inserted for column '%1' on row %2” on page 298
01W02	“Using temporary table” on page 532
01W03	“Invalid data conversion” on page 297
01W04	“Row has been updated since last time read” on page 395
01W05	“Procedure has completed” on page 380
01W06	“Value for column '%1' in table '%2' has changed” on page 534
01W07	“Language extension detected in syntax near '%1' on line %2” on page 333
01W08	“Statement cannot be executed” on page 414
01W09	“More information required” on page 346
01W10	“Transaction log backup page only partially full” on page 492
01W11	“Database option '%1' for user '%2' has an invalid setting” on page 233
01W12	“Character set conversion to '%1' cannot be performed; '%2' is used instead” on page 189
01W13	“Database server cannot convert data from/to character set '%1', conversion may not be correct” on page 236
01W14	“Language '%1' is not supported, '%2' will be used” on page 332

SQLSTATE	Message text
01W15	“Unsupported character set '%1' and unsupported language '%2'; language used is '%3' instead” on page 520
01W16	“Illegal user selectivity estimate specified” on page 281
01W17	“‘%1’ is an unknown option” on page 549
01W18	“The result returned is non-deterministic” on page 468
01W20	“Plan may contain virtual indexes” on page 375
01W21	“A row was dropped because it could not be converted to the new schema format” on page 130
01W23	“Cannot output the histogram for string column '%1’” on page 174
01W24	“Row was dropped from table %1 to maintain referential integrity” on page 397
01W25	“Publication predicates were not evaluated” on page 382
01W26	“Option '%1' specified more than once” on page 364
01W27	“Two rows with the same primary key have been download for table '%1’” on page 497
01WC1	“An invalid multi-byte input character was encountered when converting from %1 to %2” on page 139
01WC3	“Character substitution occurred when converting from %1 to %2” on page 190
01WC4	“The ICU collation '%1' has defaulted to another collation” on page 455
02000	“Row not found” on page 397
04W07	“A dbspace has reached its maximum file size” on page 129
04W08	“The server attempted to access a page beyond the end of the maximum allowable dbspace file size” on page 470
07001	“Not enough values for host variables” on page 358
07002	“Not enough fields allocated in SQLDA” on page 356
07003	“Error opening cursor” on page 253
07005	“Can only describe a SELECT statement” on page 149
07009	“Invalid descriptor index” on page 300

SQLSTATE	Message text
07W01	“Invalid type on DESCRIBE statement” on page 322
07W02	“Invalid statement” on page 320
07W03	“Invalid prepared statement type” on page 311
07W04	“SQLDA fields inconsistent for a multi-row SQLDA” on page 413
07W05	“SQLDA data type invalid” on page 412
07W06	“Invalid SQL identifier” on page 319
07W07	“Host variables must not be used within a batch” on page 275
07W08	“Invalid sqllen field in SQLDA” on page 319
08001	“Database cannot be started -- %1” on page 230
08003	“Not connected to a database” on page 356
08004	“User ID '%1' does not exist” on page 528
08005	“Password contains an illegal character” on page 372
08W01	“Database server not found” on page 237
08W02	“Connection not found” on page 207
08W03	“Database server connection limit exceeded” on page 236
08W04	“Connections to database have been disabled” on page 209
08W05	“Cannot open transaction log file -- %1” on page 174
08W06	“There are still active database connections” on page 477
08W07	“Unable to start database server” on page 507
08W08	“Invalid database server command line” on page 299
08W09	“Unable to start specified database: %1” on page 508
08W10	“Specified database not found” on page 410
08W11	“Specified database is invalid” on page 410
08W12	“Communication error” on page 203

SQLSTATE	Message text
08W13	“Not enough memory to start” on page 357
08W14	“Database name required to start server” on page 232
08W15	“Client/server communications protocol version mismatch” on page 197
08W16	“Database server not running in multi-user mode” on page 237
08W17	“Error writing to transaction log file” on page 254
08W18	“sqlpp/dblib version mismatch” on page 413
08W19	“Client/database server version mismatch” on page 196
08W20	“The database name 'utility_db' is reserved for the utility database” on page 451
08W21	“Authentication violation” on page 145
08W22	“Database page size too big: %1” on page 233
08W23	“Database server already running” on page 235
08W24	“Invalid parameter” on page 309
08W25	“Invalid local database option” on page 306
08W26	“Dynamic memory exhausted” on page 250
08W27	“Database name not unique” on page 232
08W28	“Request denied -- no active databases” on page 388
08W29	“Request to start/stop database denied” on page 389
08W30	“The selected database is currently inactive” on page 469
08W32	“Invalid database page size” on page 299
08W33	“Database creation failed: %1” on page 231
08W34	“Could not load the store DLL \"%1\” on page 219
08W35	“Could not execute store DLL (%1) entry point” on page 216
08W36	“Cannot create item (%1) in the specified dbspace” on page 160
08W37	“The connection parameters file could not be found” on page 448

SQLSTATE	Message text
08W38	“Error parsing connection parameter string” on page 254
08W39	“No database file specified” on page 351
08W40	“Database is active” on page 231
08W41	“Database \"%1\" needs recovery” on page 229
08W42	“Database upgrade failed” on page 237
08W43	“Database upgrade not possible” on page 238
08W44	“Could not load the backup/restore DLL \"%1\" on page 218
08W45	“Could not execute backup/restore DLL (%1) entry point” on page 216
08W46	“Error during backup/restore: %1” on page 252
08W47	“Incorrect database store DLL (%1) version” on page 282
08W48	“Authentication failed” on page 145
08W49	“Parse error: %1” on page 369
08W51	“Invalid IQ database command line option or parameter value: %1” on page 304
08W52	“Cannot initialize IQ memory manager: %1” on page 171
08W53	“Cannot allocate System V resources” on page 152
08W54	“Parse error: %1” on page 369
08W55	“Server not found and unable to autostart” on page 403
08W56	“Specified database file already in use” on page 410
08W57	“Database upgrade not possible; RowGenerator table not owned by user dbo” on page 238
08W58	“Database upgrade not possible; user tables have table ids in system table range” on page 239
08W59	“TLS handshake failure” on page 481
08W60	“Connection error: %1” on page 207
08W61	“TLS initialization on server failed” on page 482

SQLSTATE	Message text
08W62	“Incorrect or missing encryption key” on page 282
08W63	“Decryption error: %1” on page 242
08W64	“Database server cannot convert data from/to character set '%1'” on page 235
08W65	“Client out of memory” on page 196
08W66	“Encryption error: %1” on page 250
08W67	“Unable to start specified database: Server must be upgraded to start database %1” on page 515
08W68	“Unable to start specified database: Log file error” on page 515
08W69	“jConnect does not support encryption” on page 328
08W70	“Could not load the encryption DLL \"%1\” on page 219
08W71	“Parameter '%1' in procedure or function '%2' does not have a default value” on page 366
08W72	“Unable to start specified database: '%1' is an invalid transaction log mirror” on page 509
08W73	“Unable to start specified database: The transaction log '%1' or its mirror '%2' is invalid” on page 516
08W74	“Unable to start specified database: '%1' not expecting any operations in transaction log” on page 511
08W75	“Unable to start specified database: Unknown encryption algorithm” on page 516
08W76	“Unable to start specified database: '%1' must be upgraded to start with this server (capability %2 missing)” on page 511
08W80	“Unable to start specified database: Cannot use log file '%1' since it has been used more recently than the database file” on page 513
08W81	“Unable to start specified database: '%1': transaction log file not found” on page 512
08W82	“Unable to start specified database: Cannot use log file '%1' since the offsets do not match the offsets in the database file” on page 514
08W83	“Unable to start specified database: Cannot use log file '%1' since the database file has been used more recently” on page 514

SQLSTATE	Message text
08W84	“Unable to start specified database: Cannot use log file '%1' since it is shorter than expected” on page 513
08W85	“Unable to start specified database: '%1' is not a database” on page 510
08W86	“Unable to start specified database: '%1' was created by a different version of the software” on page 512
08W87	“Unable to start specified database: '%1' is not a valid database file” on page 510
08W88	“Unable to start specified database: '%1' is an invalid transaction log” on page 509
08W89	“Unable to start database server: Server fatal error” on page 508
08W90	“The DBN/DBF parameters do not match the database for this alternate server name” on page 453
08W91	“Cannot connect to mirror server. Use server name '%1' to find the primary server” on page 156
08W93	“Unable to start database %1: Cannot use read-only mode if auditing is enabled” on page 505
08W94	“Function '%1' has invalid parameter '%2' ('%3')” on page 272
08W95	“ATTACH TRACING could not connect to the tracing database” on page 143
08W96	“A tracing connection is already active” on page 131
08W97	“Unable to connect: The server did not accept the requested encryption type” on page 501
08W98	“Database '%1' cannot be started on this platform. See http://iAnywhere.com/developer/product_manuals/sqlanywhere/notes/en/endian_corruption_warning.html ” on page 229
08W99	“Database '%1' cannot be started on this platform. See http://iAnywhere.com/developer/product_manuals/sqlanywhere/notes/en/endian_cant_change_platform.html ” on page 228
08WA0	“Password has expired” on page 373
08WA1	“Password has expired but cannot be changed because the database is read-only” on page 373
08WA2	“Unable to start database server: missing license file” on page 507
09W02	“Illegal cursor operation attempt” on page 278

SQLSTATE	Message text
09W03	“Result set not permitted in '%1’” on page 392
09W04	“INSERT/DELETE on cursor can modify only one table” on page 289
09W05	“Cannot uniquely identify rows in cursor” on page 182
09W06	“Cursor is restricted to FETCH NEXT operations” on page 224
09W07	“Statement's size limit is invalid” on page 418
09W08	“Cannot update or delete an all-NULL row from table '%1’” on page 186
0A000	“Feature '%1' not implemented” on page 266
0A001	“The method you attempted to invoke was not enabled for your application” on page 462
0A002	“This server is not licensed to support the '%1' feature” on page 481
0A003	“This server is not licensed to support '%1' connections” on page 480
0A004	“This edition of SQL Anywhere is not available on this platform” on page 480
0AQ48	“A log is required for IQ databases” on page 129
0AW01	“Language extension” on page 333
0AW02	“Transact-SQL feature not supported” on page 491
0AW03	“Disallowed language extension detected in syntax near '%1' on line %2” on page 245
0AW04	“Triggers and procedures not supported in runtime server” on page 495
0AW05	“Statement is not allowed in passthrough mode” on page 416
0AW06	“Computed columns are not supported in this database” on page 204
0AW07	“Feature not available with UltraLite” on page 266
0AW08	“You cannot synchronize or upgrade with uncommitted transactions” on page 543
0AW09	“Synchronization server failed to commit the upload” on page 428
0AW10	“DTC transactions are not supported on this platform” on page 247
0AW11	“Download failed because of conflicts with existing rows” on page 246
0AW12	“Synchronization failed due to an error on the server: %1” on page 422

SQLSTATE	Message text
0AW13	“Cannot change synchronization user_name when status of the last upload is unknown” on page 154
0AW14	“Plan can not be generated for this type of statement” on page 375
0AW15	“Support for materialized views is not available for this database” on page 421
0AW16	“The %1 algorithm is not available in FIPS mode” on page 443
0AW17	“Cannot change the MobiLink remote id when the status of the last upload is unknown” on page 155
0AW18	“The Remote Data Services feature is not supported on this platform” on page 466
0AW19	“Feature not supported by the client version or the client interface” on page 267
0AW20	“Plan not available. NOEXEC Plan can not be generated for this type of statement” on page 375
0AW21	“No plan. HTML_PLAN function is not supported for this type of statement or database” on page 354
0AW22	“Support for permissions on dbspaces is not available for this database” on page 421
0AW23	“Synchronization download failed to complete” on page 422
0AW24	“Synchronization is already in progress” on page 423
0AWD5	“MobiLink communication error; code: %1, parameter: %2, system code %3” on page 345
0EW00	“Table '%1' has no columns” on page 433
0EW01	“Index '%1' has no columns” on page 284
21000	“SELECT returns more than one row” on page 402
21W01	“Subquery cannot return more than one row” on page 419
22001	“Right truncation of string data” on page 394
22002	“No indicator variable provided for NULL result” on page 351
22003	“Value %1 out of range for destination” on page 533
22005	“Error in assignment” on page 252

SQLSTATE	Message text
2200B	“Escape character conflict '%1'” on page 255
2200C	“Invalid use of escape character '%1'” on page 323
22012	“Division by zero” on page 246
22019	“Invalid escape character '%1'” on page 301
2201B	“Invalid regular expression: %1 in '%2'” on page 314
22024	“Unterminated C string” on page 521
22025	“Invalid escape sequence '%1'” on page 301
22030	“Cannot return NULL result as requested data type” on page 178
22W02	“Row has changed since last read -- operation canceled” on page 396
22W03	“Invalid TEXTPTR value used with WRITETEXT or READTEXT” on page 320
22X13	“Invalid preceding or following size in OLAP function” on page 310
23501	“Column '%1' in table '%2' cannot be NULL. The invalid data was supplied to LOAD TABLE in a data file on line %3” on page 199
23502	“Column '%1' in table '%2' cannot be NULL” on page 199
23503	“No primary key value for foreign key '%1' in table '%2'” on page 354
23504	“Number of columns allowing NULLs exceeds limit” on page 359
23505	“Index '%1' for table '%2' would not be unique” on page 284
23506	“Constraint '%1' violated: Invalid value for column '%2' in table '%3'” on page 210
23507	“The specified foreign key (%1) can not be enforced” on page 471
23508	“Constraint '%1' violated: Invalid value in table '%2'” on page 211
23509	“MERGE statement ANSI cardinality violation on table '%1'” on page 342
23510	“MERGE statement for table '%1' failed because of a RAISERROR specification in the statement” on page 342
23W01	“Primary key for table '%1' is not unique : Primary key value ('%2')” on page 378
23W05	“Primary key for row in table '%1' is referenced by foreign key '%2' in table '%3'” on page 377

SQLSTATE	Message text
24000	“Cursor not in a valid state” on page 224
24001	“Value-sensitive cursor used after a TRUNCATE” on page 535
24501	“Cursor not open” on page 225
24502	“Cursor already open” on page 223
24503	“No current row of cursor” on page 350
24504	“Invalid scroll position '%1’” on page 315
24W01	“Cursor has not been declared” on page 224
26501	“SQL statement error” on page 412
28000	“Invalid user ID or password” on page 324
28W01	“Invalid user ID or password on preprocessed module” on page 325
28W02	“Integrated logins are not permitted” on page 291
28W03	“Integrated logins are required, standard logins are not permitted” on page 292
28W04	“Integrated login failed” on page 291
28W05	“Integrated logins are not supported for this database” on page 292
28W06	“The integrated login ID guest can only be mapped to the guest database user ID” on page 455
28W07	“Cannot map a login ID to the sys or public user ID” on page 172
28W08	“The login ID '%1’ is already mapped to user ID '%2’” on page 459
28W09	“The login ID '%1’ has not been mapped to any database user ID” on page 458
28W10	“Too many distinct group mappings for integrated user” on page 485
28W11	“Invalid password: %1” on page 310
28W12	“Kerberos login failed” on page 330
28W13	“Kerberos logins are not supported” on page 330
28W14	“Login mode '%1’ not permitted by login_mode setting” on page 337
28W15	“Connection disallowed by login policy for this user” on page 206

SQLSTATE	Message text
2D501	“COMMIT/ROLLBACK not allowed within trigger actions” on page 202
33000	“Invalid SQL descriptor name” on page 318
37505	“Wrong number of parameters to function '%1'” on page 541
38W01	“System command failed with return code %1” on page 430
3B001	“Savepoint '%1' not found” on page 398
3B002	“ROLLBACK TO SAVEPOINT not allowed” on page 395
3BW01	“Savepoints require a rollback log” on page 399
3BW02	“Result set not allowed from within an atomic compound statement” on page 391
40000	“Run time SQL error -- %1” on page 398
40001	“Deadlock detected” on page 241
40W01	“Internal database error %1 -- transaction rolled back” on page 293
40W02	“Terminated by user -- transaction rolled back” on page 441
40W03	“Disk full '%1' -- transaction rolled back” on page 245
40W04	“I/O error %1 -- transaction rolled back” on page 276
40W05	“Disk write failure '%1' -- transaction rolled back” on page 246
40W06	“All threads are blocked” on page 135
40W07	“Connection was terminated” on page 208
40W08	“Memory error -- transaction rolled back” on page 341
42501	“Permission denied: %1” on page 374
42R01	“Referential integrity actions other than RESTRICT not allowed for temporary tables” on page 384
42R02	“Tables related by key constraint must both be permanent, or both be temporary and not created with ON COMMIT DELETE ROWS. For global temporary tables they must both be shared if one is shared” on page 439
42R03	“Key constraint between temporary tables requires a primary key (not unique constraint)” on page 331

SQLSTATE	Message text
42R04	“Foreign key columns do not match the primary key or a uniqueness constraint in \"%1\" on page 270
42U00	“View references '%1', which is a temporary object. Views can only refer to permanent objects” on page 536
42U01	“Illegal reference to correlation name '%1'” on page 280
42U02	“Owner '%1' used in a qualified column reference does not match correlation name '%2'” on page 365
42U03	“SET clause for column '%1' used incorrectly” on page 408
42U04	“Constraint '%1' not found” on page 209
42U05	“(no message)” on page 553
42U06	“Invalid reference to or operation on constraint '%1'” on page 313
42U07	“Invalid hint specified for table '%1'” on page 303
42U08	“Duplicate options not allowed in the CREATE DATABASE statement” on page 249
42W01	“User '%1' already has GRANT permission” on page 524
42W02	“Operation would cause a group cycle” on page 363
42W03	“User '%1' is not a user group” on page 527
42W04	“Syntax error near '%1' %2” on page 428
42W05	“Unknown function '%1'” on page 519
42W06	“Invalid use of an aggregate function” on page 323
42W07	“Invalid host variable” on page 303
42W08	“Invalid expression near '%1'” on page 302
42W09	“SETUSER not allowed in procedures, triggers, events, or batches” on page 408
42W13	“Invalid column number” on page 296
42W14	“Variable '%1' not found” on page 535
42W15	“There is already a variable named '%1'” on page 477
42W16	“Invalid option '%1' -- no PUBLIC setting exists” on page 308

SQLSTATE	Message text
42W17	“Invalid setting for option '%1’” on page 317
42W18	“User '%1' has the row in '%2' locked” on page 525
42W19	“Not allowed while '%1' is using the database” on page 355
42W20	“CHECKPOINT statement requires a rollback log” on page 191
42W21	“Table in use” on page 438
42W22	“Attempted two active database requests” on page 144
42W23	“Procedure in use by '%1’” on page 380
42W24	“Label '%1' not found” on page 332
42W25	“Invalid absolute or relative offset in FETCH” on page 294
42W26	“Wrong number of variables in FETCH” on page 541
42W28	“COMMIT/ROLLBACK not allowed within atomic operation” on page 202
42W29	“Procedure or trigger calls have nested too deeply” on page 381
42W30	“Update operation attempted on a read-only cursor” on page 522
42W31	“Update operation attempted on non-updatable query” on page 522
42W32	“Cannot modify column '%1' in table '%2’” on page 172
42W33	“Table '%1' not found” on page 436
42W34	“User '%1' already has membership in group '%2’” on page 525
42W35	“Update operation attempted on non-updatable remote query” on page 522
42W36	“FOR UPDATE has been incorrectly specified for a READ ONLY cursor” on page 269
42W37	“Cannot update column '%1' since it appears in the ORDER BY clause” on page 183
42W38	“Cannot update column '%1' since it does not appear in the SELECT clause” on page 184
42W39	“Conflicting INSTEAD OF trigger and WITH CHECK OPTION on view '%1’” on page 205
42W3A	“Operation failed because table or view '%1' has an INSTEAD OF trigger” on page 362

SQLSTATE	Message text
42W3B	“Positioned update operation attempted on a view with an INSTEAD OF trigger” on page 376
42W3C	“Invalid trigger type for view '%1’” on page 321
42W3D	“Triggers cannot be created on materialized view '%1’” on page 495
42W40	“Duplicate referencing column” on page 249
42W41	“Duplicate insert column” on page 248
42W42	“Parameter name missing in call to procedure '%1’” on page 367
42W43	“Only PUBLIC settings are allowed for option '%1’” on page 360
42W44	“More columns are being dropped from table '%1’ than are defined” on page 346
42W45	“Cannot set a temporary option for user '%1’” on page 179
42W46	“Only the DBA can set the option '%1’” on page 361
42W47	“Parameter '%1’ not found in procedure '%2’” on page 367
42W48	“Syntax error, cannot specify IQ specific options without specifying IQ PATH” on page 430
42W49	“TRUNCATE TABLE statement cannot be used on a view” on page 496
42W50	“READTEXT or WRITETEXT statement cannot refer to a view” on page 383
42W51	“VALIDATE statement must refer to a base table” on page 533
42W52	“The option '%1’ can only be set as a temporary option” on page 464
42W53	“The option '%1’ cannot be set from within a procedure” on page 465
42W54	“Signature '%1’ does not match procedure parameters” on page 409
42W55	“User owns procedures in use” on page 530
42W56	“User owns tables in use” on page 530
42W57	“External object '%1’ not found” on page 265
42W58	“JAR '%1’ not found” on page 326
42W59	“The select list for the derived table '%1’ has no expression to match '%2’” on page 469

SQLSTATE	Message text
42W60	“Alias '%1' is not unique” on page 134
42W61	“Definition for alias '%1' must appear before its first reference” on page 243
42W62	“Row in table '%1' was modified or deleted in BEFORE trigger” on page 396
42W63	“Procedure '%1' is no longer valid” on page 378
42W64	“Trigger or foreign key for table '%1' is no longer valid” on page 494
42W65	“Function or column reference to '%1' in the ORDER BY clause is invalid” on page 272
42W66	“Trigger name '%1' is ambiguous” on page 494
42W67	“CREATE/DROP STATISTICS statement cannot refer to virtual tables” on page 222
42W68	“Aggregated expression '%1' contains multiple columns of which one or more are outer references” on page 133
42W69	“The aggregate expression '%1' must appear in either the select list or a HAVING clause subquery” on page 446
42W70	“Grouped query contains more than one distinct aggregate function” on page 274
42W71	“Statement contains an illegal usage of the NUMBER(*) function” on page 415
42W73	“There is no way to join to '%1'” on page 479
42W74	“Index '%1' can not be clustered” on page 283
42W75	“Synchronization profile '%1' not found” on page 427
42W76	“Synchronization profile '%1' already exists” on page 426
42W77	“Synchronization profile '%1' has invalid parameter '%2'” on page 426
42W78	“Synchronization profiles are not supported for this database” on page 427
42W79	“Statement contains an illegal usage of the non-deterministic function '%1'” on page 415
42W80	“Another connection has the row in '%1' locked” on page 140
42W82	“Cannot delete PUBLIC option '%1' since user settings exist” on page 162
42W83	“Invalid setting for HTTP option '%1'” on page 317
42W84	“Invalid setting for HTTP header '%1'” on page 316

SQLSTATE	Message text
42W85	"'%1' is an invalid value for '%2'" on page 548
42W86	"Invalid setting for SOAP header '%1'" on page 318
42W90	"Illegal ORDER BY in aggregate function" on page 280
42W91	"A transaction log file is required for auditing" on page 132
42W92	"Service type required for CREATE SERVICE" on page 407
42W93	"Cycle in common table expression references" on page 226
42W94	"'%1' is an unrecognized service type" on page 549
42W95	"Invalid service name '%1'" on page 316
42W96	"A user name must be specified if AUTHORIZATION is Off" on page 132
42W97	"Service '%1' already exists" on page 404
42W98	"Service '%1' not found" on page 405
42W99	"Invalid recursive query" on page 312
42W9A	"No column list for recursive query" on page 350
42W9B	"Host variable reference in service definition must be named" on page 274
42W9C	"Service statement definition is inconsistent with service type" on page 406
42W9D	"Constant expressions must not appear in GROUP BY clause" on page 209
42W9E	"Service definition requires a statement when authorization is off" on page 405
42WA0	"Recursion is not allowed without the RECURSIVE keyword" on page 383
42WA1	"Too many expressions in GROUP BY list for ROLLUP, CUBE, or GROUPING SETS operation" on page 486
42WA2	"Recursive column %1: conversion from '%2' to '%3' loses precision" on page 384
42WA3	"Window '%1' not found" on page 538
42WA4	"PARTITION BY not allowed in reference to window '%1'" on page 370
42WA5	"ORDER BY not allowed in window '%1'" on page 364
42WA6	"Frame not allowed for window '%1'" on page 271

SQLSTATE	Message text
42WA7	“Argument to GROUPING aggregate must be a grouping column in the GROUP BY clause” on page 142
42WA8	“Window function used in predicate” on page 538
42WA9	“Window function requires ORDER BY” on page 538
42WAA	“Composite ORDER BY not allowed with RANGE” on page 203
42WAB	“User '%1' already has EXECUTE permission” on page 524
42WAC	“Too many arguments for function or procedure '%1'” on page 483
42WAD	“Invalid value for attribute '%1' in service” on page 325
42WAE	“Missing value for attribute '%1' in service” on page 344
42WAF	“Unsupported property '%1' in service USING attribute” on page 520
42WB0	“Duplicate attribute '%1' in service” on page 247
42WB1	“USING attribute cannot coexist with FORMAT or GROUP attributes” on page 532
42WB2	“Service type does not allow '%1' attribute” on page 407
42WB3	“Syntax error near '%1' -- Materialized view definition must not use the following construct: '%2'” on page 429
42WB4	“Syntax error near '%1' -- The materialized view cannot be changed to immediate because its definition contains an illegal construct: '%2'” on page 429
42WB5	“Materialized View '%1' not found” on page 340
42WB6	“Cannot create a materialized view because option '%1' has an inappropriate setting” on page 159
42WB7	“Cannot update materialized view because option '%1' has an inappropriate setting” on page 184
42WB8	“Table created or altered after start of snapshot” on page 437
42WB9	“Statement not allowed during snapshot” on page 417
42WBA	“Update conflict on snapshot transaction” on page 521
42WBB	“Attempt to use snapshot isolation in a non-snapshot transaction” on page 144

SQLSTATE	Message text
42WBC	“Cannot use materialized view '%1' because it has not yet been initialized” on page 187
42WBD	“Cycle in computed column dependencies” on page 226
42WBE	“Cannot revoke these permissions while user '%1' is actively replicating transactions” on page 178
42WBF	“Correlation name '%1' is not valid for use with the ROWID function” on page 212
42WC0	“Duplicate key column (%1)” on page 248
42WC1	“Table '%1' contains an invalid reference to the ROWID function” on page 432
42WC2	“The '%1' property is no longer supported” on page 445
42WC3	“The materialized view %1 cannot be changed to immediate because it has already been initialized” on page 460
42WC4	“Unable to acquire table locks in specified time” on page 499
42WC5	“The materialized view cannot be changed to immediate because its definition must not contain more than one query block” on page 462
42WC6	“The materialized view cannot be changed to immediate because COUNT(*) is required to be part of the SELECT list” on page 460
42WC7	“The materialized view cannot be changed to immediate because it does not have a unique index on non-aggregate non-nullable columns” on page 461
42WC8	“Maintenance of dependent immediate materialized view(s) failed” on page 339
42WC9	“Attempt to start a second snapshot in a transaction” on page 144
42WCA	“The materialized view %1 cannot be changed to immediate because it does not have a unique index on non-nullable columns” on page 459
42WCB	“The materialized view cannot be changed to immediate because its definition contains an illegal construct” on page 461
42WCC	“Service statement definition is invalid or unsupported” on page 406
42WCD	“Immediate materialized view definition cannot contain a SUM function over a nullable expression” on page 281
42WD3	“Must own table '%1' in order to make an immediate view reference it” on page 348
42Z00	“Write access was denied” on page 540

SQLSTATE	Message text
44000	“WITH CHECK OPTION violated for insert/update on base table '%1'” on page 539
52002	“Column '%1' found in more than one table -- need a correlation name” on page 198
52003	“Column '%1' not found” on page 200
52004	“Derived table '%1' has no name for column %2” on page 244
52005	“Column '%1' not found in table '%2'” on page 200
52009	“Primary key column '%1' already defined” on page 377
52010	“Item '%1' already exists” on page 326
52012	“More than one table is identified as '%1'” on page 347
52W02	“Correlation name '%1' not found” on page 213
52W03	“Cannot find index named '%1'” on page 168
52W04	“Index name '%1' not unique” on page 285
52W05	“Table cannot have two primary keys” on page 437
52W06	“Foreign key '%1' for table '%2' duplicates an existing foreign key” on page 269
52W07	“Foreign key name '%1' not found” on page 270
52W08	“There is more than one way to join '%1' to '%2'” on page 477
52W09	“Procedure '%1' not found” on page 379
52W10	“Trigger '%1' not found” on page 493
52W11	“Trigger definition conflicts with existing triggers” on page 493
52W12	“Invalid REFERENCES clause in trigger definition” on page 313
52W13	“DbSPACE '%1' not found” on page 240
52W14	“Table '%1' is in an outer join cycle” on page 435
52W15	“Table '%1' requires a unique correlation name” on page 436
52W16	“User message %1 already exists” on page 529
52W17	“User message %1 not found” on page 529

SQLSTATE	Message text
52W18	“User-defined type '%1' not found” on page 531
52W19	“DbSPACE for table '%1' not found” on page 241
52W20	“Too many columns in table” on page 484
52W21	“Data definition statements not allowed in procedures or triggers” on page 228
52W22	“GRANT of column permission on view not allowed” on page 274
52W23	“Invalid expression in WHERE clause of Transact-SQL outer join” on page 302
52W24	“Invalid join type used with Transact-SQL outer join” on page 306
52W25	“Invalid comparison” on page 297
52W26	“Invalid commit action for shared temporary table” on page 296
52W40	“Index name '%1' is ambiguous” on page 285
52W41	“Too many temporary tables in connection” on page 489
52W42	“Table name '%1' is ambiguous” on page 439
52W43	“Default dbSPACE '%1' not found” on page 243
53002	“Wrong number of values for INSERT” on page 541
53003	“Function or column reference to '%1' must also appear in a GROUP BY” on page 273
53005	“Invalid ORDER BY specification” on page 309
53011	“Number of columns defined for the view does not match SELECT statement” on page 360
53017	“Cannot convert %1 to a %2. The bad value was supplied for column '%3' on row %4 of the data file” on page 157
53018	“Cannot convert %1 to a %2” on page 157
53019	“Return type of void from procedure '%1' cannot be used in any expression” on page 393
53023	“Subquery allowed only one select list item” on page 419
53026	“Select lists in UNION, INTERSECT, or EXCEPT do not match in length” on page 401
53030	“Column '%1' in foreign key has a different definition than primary key” on page 198

SQLSTATE	Message text
53W01	“ALTER clause conflict” on page 135
53W02	“Cannot update an expression” on page 183
53W04	“There is no way to join '%1' to '%2'” on page 478
53W05	“Cannot alter a column in an index” on page 152
53W06	“Cannot delete or rename a column referenced in a trigger definition” on page 162
53W07	“Error number %1 for RAISERROR must not be less than 17000” on page 253
53W08	“Format string argument number %1 is invalid” on page 271
53W09	“Invalid data type for column in WRITETEXT or READTEXT” on page 298
54003	“Identifier '%1' too long” on page 276
54W01	“Statement size or complexity exceeds server limits” on page 417
54W02	“Too many constraints in database” on page 485
54W03	“Database page size too small: %1” on page 234
54W04	“The specified listener could not be registered” on page 472
54W05	“Temporary space limit exceeded” on page 440
54W06	“The string is too long (%1)” on page 474
54W07	“Password must be at least %1 characters” on page 374
54W08	“Password cannot be longer than %1 characters” on page 372
54W09	“The size of the character column, variable, or value data type exceeds 32767” on page 470
54W10	“Too many users in database” on page 490
54W11	“Too many references to a BLOB” on page 489
54W12	“Too many open cursors” on page 487
54W13	“Too many columns in SELECT list” on page 484
54W14	“Too many expressions in GROUP BY list” on page 486
54W15	“Too many columns in procedure result set” on page 483

SQLSTATE	Message text
54W16	“Too many MESSAGE ... FOR CONNECTION messages” on page 487
54W17	“Maximum string length exceeded” on page 341
54W50	“Virtual index creation with more than %1 columns” on page 536
54W51	“Reorganize table is already being run on table \"%1\” on page 387
54W52	“Invalid domain '%1'” on page 300
55008	“Table '%1' has no primary key” on page 433
55013	“Table already has a primary key” on page 437
55W02	“Table must be empty” on page 438
55W03	“Cannot drop a user that owns tables in runtime system” on page 165
55W04	“Cannot drop a user that owns procedures in runtime server” on page 165
55W05	“Cannot drop a user that owns messages or data types” on page 164
55W06	“Cannot drop a user that owns objects involved in replication” on page 165
55W07	“db_init has not been called or the call to db_init failed” on page 239
55W08	“Modifications not permitted for read-only database” on page 345
55W09	“Cannot commit or rollback while enlisted in a transaction” on page 156
55W10	“Cannot enlist in a transaction while already enlisted in a transaction” on page 168
55W11	“Cannot enlist in a transaction with uncommitted data pending” on page 168
55W12	“Cannot drop a user that owns text configurations” on page 166
55W13	“Strongly-encrypted database files are not supported in the runtime server” on page 419
55W14	“Invalid operation on a closed object” on page 308
55W15	“Service '%1' in use” on page 404
55W16	“Cannot drop or modify object '%1' because at least one other object (%2 '%3') depends upon it” on page 167
55W17	“Cannot use view '%1' because it has been disabled” on page 187
55W18	“Cannot use view '%1' because it is invalid” on page 188

SQLSTATE	Message text
55W19	“Illegal column definition: %1” on page 277
55W20	“This database does not support encrypted tables” on page 480
55W21	“Cannot drop last unique index of an immediate materialized view” on page 166
55W23	“Snapshot isolation disabled or pending” on page 409
55W24	“Could not refresh tracing: at least one enabled tracing level must be specified” on page 220
55W25	“Transact-SQL outer joins are currently disabled” on page 491
55W26	“The dbspace '%1' cannot be dropped because it contains tables or indexes” on page 453
55W27	“Encryption has not been enabled” on page 251
55W28	“Traced query (%1, %2) does not exist” on page 490
55W29	“Cannot update multiple tables immediate materialized view %1 depends on” on page 185
55W30	“TRUNCATE TABLE not allowed: initialized immediate materialized view %1 depends on %2” on page 496
55W31	“Operation not allowed on a table with dependent immediate materialized views” on page 363
55W32	“WRITETEXT not allowed: immediate materialized view %1 depends on %2” on page 540
55W33	“INSERT ... ON EXISTING UPDATE not allowed: immediate materialized view %1 depends on %2” on page 289
55W34	“Configuration cannot not be modified while in use” on page 205
56001	“Table '%1' has a foreign key with a referential action” on page 432
57014	“Statement interrupted by user” on page 416
57015	“Too many recursive iterations” on page 488
57W01	“Request interrupted due to timeout” on page 388
57W02	“Use of feature '%1' is not allowed” on page 523

SQLSTATE	Message text
57W03	“Not enough free space on device to grow dbspace '%1' by requested amount” on page 357
57W04	“Use of statement '%1', which requires feature '%2', is not allowed” on page 523
57W05	“Statement timed out: '%1'” on page 418
5RW01	“Publication '%1' not found” on page 381
5RW02	“Table '%1' has publications” on page 434
5RW03	“Subscription to '%1' for '%2' already exists” on page 420
5RW04	“Subscription to '%1' for '%2' not found” on page 420
5RW05	“User '%1' is already the publisher for this database” on page 526
5RW06	“User '%1' is not a remote user for this database” on page 526
5RW07	“Remote message type '%1' not found” on page 385
5RW08	“Passthrough statement inconsistent with current passthrough” on page 371
5RW09	“Remote statement failed” on page 387
5RW10	“Multiple consolidated users cannot be defined” on page 347
5RW11	“Synchronization message type '%1' not found” on page 423
5RW12	“Cannot find synchronization subscription with the name '%1'” on page 169
5RW13	“Cannot subscribe to '%1'” on page 181
5RW14	“Cannot modify synchronization entry using ALTER PUBLICATION” on page 173
5RW15	“Cannot modify publication entry using ALTER SYNCHRONIZATION” on page 173
5RW16	“Cannot synchronize table '%1' since it does not have a primary key” on page 181
5RW17	“Must include primary key for table '%1' in the synchronization” on page 348
5RW18	“Cannot create synchronization entry for table '%1' with BLOB primary key” on page 161
5RW19	“Cannot update primary key for table '%1' involved in a publication” on page 186
5RW21	“Cannot register '%1' since another exclusive instance is running” on page 175

SQLSTATE	Message text
5RW22	“Cannot register another '%1' as an exclusive application” on page 176
5RW23	“Cannot register connection because of invalid application cookie” on page 176
5RW24	“Cannot deregister application because of invalid cookie” on page 163
5RW25	“Cannot deregister '%1' since active registered connection exists” on page 163
5RW26	“Current connection is already registered to '%1' as '%2'” on page 223
5RW27	“Another connection has already registered as '%1'” on page 140
5RW28	“Cannot register '%1' since registration cookie exhausted” on page 175
5RW29	“Cannot register connection to '%1' since automatic label exhausted” on page 177
5RW32	“Synchronization option '%1' contains semi-colon, equal sign, curly brace, or is null” on page 424
5RW33	“Synchronization option '%1' not found” on page 424
5RW34	“Synchronization option is too long” on page 425
5RW35	“Table '%1' is part of a synchronization definition” on page 435
5RW36	“Table '%1' is already included” on page 434
5RW37	“Cannot find synchronization user with the name '%1'” on page 170
5RW38	“Operation conflict with publication type” on page 362
5RW39	“Cannot find synchronization definition with the name '%1'” on page 169
99999	“User-defined exception signaled” on page 531
WB001	“Unknown backup operation” on page 518
WB002	“Database backup not started” on page 230
WB003	“Incomplete transactions prevent transaction log renaming” on page 281
WB004	“Unable to delete database file” on page 502
WB005	“Transaction log was truncated” on page 492
WB006	“Contents of backup files are inconsistent” on page 211
WB007	“Backup file format is invalid” on page 147

SQLSTATE	Message text
WB008	“RESTORE unable to open file '%1'” on page 390
WB009	“RESTORE unable to write to file '%1'” on page 391
WB010	“RESTORE unable to start database '%1'” on page 390
WB011	“Unable to open backup log '%1'” on page 503
WB012	“Backup file '%1' already exists” on page 147
WB013	“Invalid backup operation” on page 294
WB014	“Connection attempting BACKUP has uncommitted transactions” on page 206
WB015	“Invalid backup parameter value” on page 294
WB016	“BACKUP clause '%1' conflicts with '%2'” on page 146
WB017	“Backup is unable to open database file '%1'” on page 148
WC001	“'%1' is an unknown character set encoding label” on page 548
WC002	“Cannot convert between requested character set '%1' and database character set '%2'” on page 158
WC003	“An invalid multi-byte input character was encountered when converting from %1 to %2” on page 138
WC004	“The UTF-16 endian specified does not match the Byte Order Mark found in the data” on page 476
WC005	“Character substitution was required when converting from %1 to %2” on page 191
WC007	“Character conversion error or warning report is not available when the single-byte converter is used” on page 189
WC008	“Cannot convert between requested character sets '%1' and '%2'” on page 159
WC009	“'%1' is not a valid character set encoding for use with collation '%2'” on page 551
WC010	“'%1' cannot be used as the NCHAR collation: only UCA and UTF8BIN may be used” on page 547
WC011	“Failed to convert from character set '%1' to '%2'” on page 265
WC012	“dbicu libraries are required but not installed” on page 240

SQLSTATE	Message text
WC013	“Collation '%1' not supported on this platform” on page 197
WC014	“The dbicu library and server versions do not match” on page 452
WC015	“Unable to start database \"%1\": CHAR collation or tailoring not supported on this platform” on page 506
WC016	“Unable to start database \"%1\": NCHAR collation or tailoring not supported on this platform” on page 506
WC017	“'%1' cannot be used as the encoding specification for '%2' data” on page 547
WE001	“Event '%1' not found” on page 256
WE002	“Event '%1' already exists” on page 255
WE003	“Schedule '%1' for event '%2' not found” on page 400
WE004	“Schedule '%1' for event '%2' already exists” on page 399
WE005	“Invalid day of week or month '%1' for event '%2'” on page 299
WE006	“Invalid time '%1' for event '%2'” on page 321
WE007	“Invalid start date/time for event '%1'” on page 319
WE008	“System event type '%1' not found” on page 431
WE009	“Event '%1' in use” on page 256
WE010	“Start date/time for non-recurring event '%1' is in the past” on page 414
WE011	“Event notification queue '%1' is full, notification discarded” on page 257
WE012	“Event notifications lost on queue '%1'” on page 258
WE013	“Event notification queue '%1' not found warning” on page 258
WE014	“Event notification queue '%1' not found” on page 257
WE015	“Event object name '%1' is not valid” on page 259
WE016	“Event object named '%1' already exists” on page 259
WE017	“No notification within timeout on queue '%1'” on page 353
WE018	“Event parameter '%1' not found” on page 260

SQLSTATE	Message text
WI002	“Index validation failed for table %1, index %2 with code: %3” on page 286
WI003	“Database page validation failed with code: %1” on page 234
WI004	“Internal rollback log corrupted” on page 293
WI005	“Unable to find in index '%1' for table '%2'” on page 503
WI009	“Cannot serialize Java object with class '%1'” on page 179
WI010	“The optimizer was unable to construct a valid access plan” on page 464
WI011	“Required operators excluded” on page 389
WJ001	“Method '%1' cannot be called at this time” on page 343
WJ002	“Parameter not registered as output parameter” on page 368
WJ003	“The specified transaction isolation is invalid” on page 473
WJ004	“The cursor name '%1' already exists” on page 449
WJ005	“Input parameter index out of range” on page 288
WJ006	“Return value cannot be set” on page 393
WJ007	“JDBC feature '%1' not supported” on page 328
WJ008	“Could not change an opened prepared statement or callable statement” on page 214
WJ009	“An internal error occurred in a '%1'” on page 137
WJ010	“Invalid operation on a closed '%1'” on page 307
WJ011	“Cannot access instance member through a class” on page 151
WJ012	“Cannot update member fields qualified with \"final\" modifier” on page 185
WJ013	“An internal error occurred in a '%1'” on page 138
WJ014	“Invalid operation on a closed '%1'” on page 308
WJ015	“JDBC SASstatement batch execute abandoned” on page 329
WJ016	“Seek absolute 0 was attempted on a JDBC SASResultSet” on page 401
WJ017	“Invalid JDBC resultset type” on page 305

SQLSTATE	Message text
WJ018	“Invalid JDBC resultset concurrency” on page 305
WJ019	“Cannot call the '%1' function on a JDBC resultset when it is positioned on an insert row” on page 154
WJ020	“The JDBC resultset must be positioned on an insert row in order to use the '%1' function” on page 456
WJ021	“Cannot uniquely identify column '%2' of table '%1' in the current JDBC resultset” on page 182
WJ022	“The database does not support the Java Virtual Machine” on page 451
WJ023	“'%1' is not a public Java class, and cannot be referenced from SQL” on page 550
WJ024	“'%1' is not a public Java reference, and cannot be referenced from SQL” on page 551
WJ025	“JDK '%1' is not a supported JDK” on page 329
WJ026	“The JDK version in '%1' does not match '%2'” on page 456
WJ027	“Java SecurityManager class not found: %1” on page 327
WJ028	“Exception occurred while loading Java SecurityManager” on page 261
WJ029	“The database needs to be restarted for this Java related command” on page 452
WJ030	“External environment '%1' could not be found” on page 261
WJ031	“External environment does not support result sets” on page 262
WL001	“'%1' is not a known file format for loading or unloading tables” on page 550
WL002	“Cannot access file '%1' -- %2” on page 150
WL004	“UNLOAD TABLE cannot be used to unload a view” on page 519
WL005	“Unable to enlist transaction; DTC may be down” on page 502
WL006	“Unable to reenlist transaction; DTC may be down” on page 504
WL007	“LOAD TABLE not allowed on temporary table with ON COMMIT DELETE ROWS” on page 335
WL008	“LOAD TABLE not permitted on mirrored database” on page 336

SQLSTATE	Message text
WL009	“LOAD TABLE not allowed on temporary table which has foreign key references from another table” on page 335
WL010	“The logging type ('%1') specified is invalid, not supported or incompatible” on page 457
WL011	“Unable to close the cursor on table \"%1\". LOAD TABLE cannot be executed” on page 500
WL012	“Cannot append when using compression or encryption” on page 153
WL013	“LOAD TABLE error: %1” on page 334
WL014	“LOAD TABLE is not allowed on a materialized view %1” on page 334
WL015	“LOAD TABLE not allowed: initialized immediate materialized view %1 depends on %2” on page 336
WO001	“Unable to connect to server '%1': %2” on page 500
WO002	“Unable to connect, server definition is circular” on page 501
WO003	“Remote server '%1' is currently configured as read-only” on page 386
WO004	“Remote server '%1' could not be found” on page 385
WO005	“Server '%1': %2” on page 402
WO006	“Backward scrolling cursors are not supported for remote objects” on page 148
WO007	“The remote table '%1' could not be found” on page 467
WO008	“Could not access column information for the table '%1'” on page 213
WO010	“%1” on page 545
WO011	“The remote server does not support an auto-incrementing data type” on page 467
WO012	“Remote server does not have the ability to support this statement” on page 386
WO013	“External login for server '%1' could not be found” on page 264
WO014	“Server capability name '%1' could not be found in the database” on page 403
WO015	“The data type specified for column '%1' is not compatible with the actual data type” on page 450

SQLSTATE	Message text
WO016	“The column '%1' does not exist in the remote table” on page 447
WO017	“The length specified for column '%1' is different than the actual length” on page 457
WO018	“NULL attribute mismatch for column '%1'” on page 358
WO019	“Identity attribute mismatch for column '%1'” on page 277
WO020	“The table specification '%1' identifies more than one remote table” on page 475
WO021	“Creating remote tables with computed columns is not supported” on page 222
WO022	“The data type of column '%1' is not supported” on page 449
WO023	“Cannot handle expressions involving remote tables inside stored procedures” on page 170
WO024	“Specified local connection ID not found” on page 411
WO025	“Local connection ID does not refer to the current database” on page 337
WO026	“Cannot close a remote JDBC connection that is not the current connection” on page 155
WO027	“File system error: %1” on page 268
WO028	“User cannot be dropped because external logins exist for this user” on page 528
WP000	“Argument %1 of procedure '%2' cannot be NULL” on page 141
WP001	“Procedure '%1' terminated with unhandled exception '%2'” on page 379
WP002	“'%1' is not a valid class file” on page 552
WP003	“Could not decompress class '%1' from JAR” on page 215
WP004	“Cannot remove class '%1': member of JAR” on page 177
WP005	“Invalid class byte code” on page 295
WP006	“External environment could not be started, '%1' could not be found” on page 262
WP007	“Namespace heap exhausted at internal function: %1” on page 349
WP008	“Java VM heap exhausted at internal function: %1” on page 327
WP009	“Resource governor for '%1' exceeded” on page 389

SQLSTATE	Message text
WP010	“Invalid JAR file” on page 304
WP011	“Previous error lost prior to RESIGNAL” on page 376
WP012	“%1 returned a result set with a different schema than expected” on page 546
WP013	“%1 returned multiple result sets” on page 546
WP014	“%1 does not return a result set” on page 545
WP015	“Insufficient cache to start Java Virtual Machine” on page 290
WP016	“Warning detected when optimizing SELECT INTO is treated as an error” on page 537
WT001	“Argument \"%1\" must be a column reference” on page 141
WT002	“All column reference arguments must refer to the same table” on page 134
WT003	“No matching text index” on page 352
WT004	“Non-constant or unknown text query string” on page 355
WT005	“Text configuration \"%1\".\"%2\" not found” on page 442
WT006	“Text configuration \"%1\" already exists” on page 441
WT007	“Term length outside allowed range” on page 440
WT008	“Invalid collation: \"%1\"” on page 295
WT009	“Text query parser error: %1” on page 443
WT010	“Error creating text index \"%1\" on table \"%2\"” on page 251
WT011	“Text indexes are not supported for this database” on page 442
WT012	“Cannot alter or drop a text configuration referenced by a text index” on page 153
WT013	“Cannot access a table that is part of a text index” on page 150
WT014	“Cannot create text configuration '%1' because option '%2' has an inappropriate setting” on page 161
WT015	“Command not allowed on IMMEDIATE REFRESH text index” on page 202
WT016	“Invalid use of NEAR operator in text query” on page 324
WT017	“The arguments to this procedure must be literal strings” on page 446

SQLSTATE	Message text
WT018	“The provided stoplist is too long” on page 466
WT019	“The text index %1 needs to be refreshed” on page 475
WT020	“A CONTAINS query is not allowed on the view or derived table '%1’” on page 128
WT021	“Could not create a new text for this table with the same settings as \"%1\” on page 215
WW001	“The pattern is too long” on page 466
WW002	“Cannot stop the database server” on page 180
WW003	“Calling functions outside the database server is not supported” on page 149
WW004	“Mismatch between external function platform specifier and current operating system” on page 344
WW005	“Need a dynamic library name” on page 350
WW006	“Could not load dynamic library '%1’” on page 218
WW007	“Could not find '%1' in dynamic library '%2’” on page 217
WW008	“Could not allocate resources to call external function” on page 214
WW009	“Expression has unsupported data type” on page 261
WW010	“Too many parameters to this external procedure call” on page 487
WW011	“A thread used internally could not be started” on page 131
WW012	“RAISERROR executed: %1” on page 382
WW013	“Class '%1' has no public field '%2’” on page 192
WW014	“Invalid type for field reference” on page 322
WW015	“Field '%1' of class '%2' cannot be NULL” on page 267
WW016	“Index type specification of '%1' is invalid” on page 286
WW017	“An attempt to delete database '%1' failed” on page 136
WW018	“Cannot deserialize Java object” on page 164
WW019	“Rollback occurred due to deadlock during prefetch” on page 394
WW020	“Invalid request log format on line %1” on page 314

SQLSTATE	Message text
WW022	“Cannot create an index on Java class '%1'” on page 160
WW023	“Cannot insert or update computed column '%1'” on page 171
WW024	“The communications environment could not be created” on page 448
WW025	“An internal error was generated by the test harness” on page 138
WW026	“The external function call is incompatible” on page 454
WW027	“A conflict with the dbmlsync download phase was detected” on page 128
WW028	“At least one of the specified dbspaces was not calibrated” on page 142
WW029	“A workload capture (%1) is already in progress” on page 133
WW030	“No workload capture currently exists” on page 355
WW031	“Cannot access schema file '%1'” on page 151
WW032	“The status of the last synchronization upload is unknown” on page 474
WW033	“A schema upgrade is not currently allowed” on page 131
WW034	“The database '%1' was not found” on page 450
WW035	“This connection already exists” on page 479
WW036	“Information for synchronization is incomplete or invalid, check '%1'” on page 287
WW037	“Compression error: %1” on page 204
WW038	“Decompression error: %1” on page 242
WW039	“Input string is not base64-encoded” on page 288
WW040	“UltraLite connection was restored” on page 497
WW041	“UltraLite cursor (or result set or table) was restored” on page 498
WW042	“Checksums are not enabled in this database” on page 192
WW043	“File I/O failed for '%1'” on page 268
WW044	“Incorrect volume ID for '%1'” on page 283
WW045	“The operation failed because column '%1's type does not support streaming” on page 463

SQLSTATE	Message text
WW046	“Script file missing statement \"go\" delimiter on a separate line” on page 400
WW047	“Directory for output file does not exist” on page 244
WW048	“Output file cannot be written” on page 365
WW049	“The URI '%1' is invalid” on page 476
WW050	“Unable to connect to the remote host specified by '%1'” on page 501
WW051	“Connection timed out” on page 208
WW052	“HTTP request failed. Status code '%1'” on page 275
WW053	“Could not initialize the encryption DLL: '%1'” on page 217
WW055	“Invalid procedure type '%1'” on page 312
WW056	“Invalid procedure subtype '%1' for type '%2'” on page 311
WW057	“Invalid response from the HTTP server” on page 315
WW058	“NAMESPACE attribute is not valid with procedure type '%1'” on page 349
WW059	“The secure connection to the remote host failed: %1” on page 468
WW060	“Clause '%1' has invalid attribute '%2'” on page 193
WW061	“The database was created” on page 452
WW062	“The option '%1' is not recognized” on page 465
WW063	“Secure HTTP connections are not supported on this platform” on page 401
WW064	“The '%1' attribute is not valid with procedure type '%2'” on page 445
WW065	“Cannot add a comment to a table declared as LOCAL TEMPORARY” on page 152
WW066	“Could not refresh tracing: invalid tracing specification on sa_diagnostic_tracing_level row %1” on page 221
WW067	“Could not refresh tracing: failed to find object %1 on row %2” on page 220
WW068	“Could not refresh tracing: volatile_statistics have to be collected in order for %1 specified on row %2 to be collected” on page 221
WW069	“ATTACH TRACING TO LOCAL DATABASE cannot be used with a strongly encrypted database” on page 143

SQLSTATE	Message text
WW070	“The http header '%1' is reserved and cannot be modified” on page 454
WW071	“The specified http header contains illegal or non-ASCII characters” on page 471
WW072	“The specified http header is malformed” on page 472
WW073	“Column '%1' not part of any indexes in its containing table” on page 201
WW074	“Unable to retry download because upload is not finished” on page 505
WW075	“No partial download was found” on page 353
WW077	“Too many publications specified for operation” on page 488
WW078	“Unable to access the filesystem on the device” on page 499
WW079	“Unable to perform requested operation since this database uses keyless encryption” on page 504
WW080	“Synchronization process was unable to re-enter synchronization” on page 425
WW081	“Information for synchronization was not provided” on page 287
WW082	“Specified file system volume not found for database '%1'” on page 411
WW083	“A row cannot be stored because it exceeds the database page size” on page 130
WW084	“Exceeded maximum of '%1' allowable parameters” on page 260
WW085	“Invalid mime type '%1'” on page 307
WW086	“The '%1' attribute contains mismatched parentheses within '%2'” on page 444
WW087	“The '%1' attribute is missing a comma within '%2'” on page 444
WW088	“The attribute '%1' sets an option '%2' that is incompatible with '%3'” on page 447
WW089	“Maximum row size for table '%1' would be exceeded” on page 340
WW090	“The mirror '%1' does not match database '%2'” on page 463
WW091	“The SQL scripts DLL cannot be loaded” on page 473
WW092	“Client application does not allow transfer of data ('%1')” on page 194
WW093	“Client application disallowed the transfer of data ('%1')” on page 193
WW094	“Client library reported an error accessing data during transfer ('%1')” on page 195

SQLSTATE	Message text
WW095	“Transaction log mirroring cannot be used with database mirroring” on page 492
WW096	“Cannot set database option \"%1\" because it is on the options watch list” on page 180
WW097	“Login policy \"%1\" already exists” on page 338
WW098	“Login policy \"%1\" not found” on page 339
WW099	“Login policies are not supported for this database” on page 338
WW100	“Login policy \"%1\" in use” on page 338
WW101	“User \"%1\" already exists” on page 527
WW102	“Client library reported an error opening object ('%1') during transfer” on page 195
WW103	“Client library reported a permissions error accessing object ('%1') during transfer” on page 194
WW104	“External environments are not supported for this database” on page 263
WW108	“External library '%1' is in use” on page 263
WW109	“External library '%1' not loaded” on page 264
WW112	“Passthrough SQL script failed” on page 370
WW114	“UltraLite database state was restored” on page 498
WW115	“Retrying read of corrupt page (page '%1')” on page 392
WW116	“Mirror file requires higher checksum_level” on page 343
WW118	“An attempt to encrypt database '%1' failed” on page 137
WW119	“An attempt to decrypt database '%1' failed” on page 136
WW120	“'%1' statement is not allowed on a mirrored database” on page 552
WW229	“Parameter '%1' cannot be null” on page 366
WW230	“Operation is not allowed” on page 363
WW231	“Operation '%1' failed for reason: '%2'” on page 361
WW232	“Underflow when converting '%1'” on page 517
WW234	“Automatic database upgrade applied” on page 146

SQLSTATE	Message text
WX001	“Column must be named: %1” on page 201
WX002	“XML parser error: %1” on page 542
WX003	“XPath parser error: %1” on page 543
WX004	“Illegal flags value passed to OPENXML” on page 279
WX005	“Illegal FOR XML EXPLICIT tag value: '%1'” on page 279
WX006	“Unknown FOR XML EXPLICIT directive: '%1'” on page 518
WX007	“Illegal column name: '%1'” on page 278
WX008	“Parent not open: '%1'” on page 368
WX009	“Undeclared tag ID: '%1'” on page 517
WX010	“Too few columns” on page 482
WX011	“CDATA has a name” on page 188
WX012	“Invalid XQuery constructor” on page 325
WX013	“XMLGEN evaluation failure” on page 542
WX014	“No name for argument” on page 352
WX015	“Control character in XML output” on page 212
WX016	“Insufficient memory for OPENXML query” on page 290

SQL Anywhere error messages sorted by Sybase error code

Sybase error code	SQL Anywhere SQLCODE	Message text
0	-631	"RAISERROR executed: %1" on page 382
102	-171	"Error opening cursor" on page 253
102	-199	"INSERT/DELETE on cursor can modify only one table" on page 289
102	-933	"A log is required for IQ databases" on page 129
102	-275	"Triggers and procedures not supported in runtime server" on page 495
102	-273	"COMMIT/ROLLBACK not allowed within trigger actions" on page 202
102	-131	"Syntax error near '%1' %2" on page 428
102	-687	"Syntax error, cannot specify IQ specific options without specifying IQ PATH" on page 430
102	-875	"There is no way to join to '%1'" on page 479
102	-145	"Foreign key name '%1' not found" on page 270
102	-271	"Trigger definition conflicts with existing triggers" on page 493
102	-272	"Invalid REFERENCES clause in trigger definition" on page 313
102	-635	"GRANT of column permission on view not allowed" on page 274
102	-151	"Subquery allowed only one select list item" on page 419
102	-269	"Cannot delete or rename a column referenced in a trigger definition" on page 162
103	-250	"Identifier '%1' too long" on page 276
104	-854	"Function or column reference to '%1' in the ORDER BY clause is invalid" on page 272
108	-152	"Invalid ORDER BY specification" on page 309

Sybase error code	SQL Anywhere SQLCODE	Message text
133	-262	"Label '%1' not found" on page 332
134	-261	"There is already a variable named '%1'" on page 477
137	-260	"Variable '%1' not found" on page 535
154	-623	"Data definition statements not allowed in procedures or triggers" on page 228
155	-200	"Invalid option '%1' -- no PUBLIC setting exists" on page 308
174	-154	"Wrong number of parameters to function '%1'" on page 541
176	-611	"Transact-SQL feature not supported" on page 491
176	-148	"Unknown function '%1'" on page 519
182	-159	"Invalid column number" on page 296
201	-639	"Parameter name missing in call to procedure '%1'" on page 367
201	-615	"Parameter '%1' not found in procedure '%2'" on page 367
201	-737	"Signature '%1' does not match procedure parameters" on page 409
205	-153	"Select lists in UNION, INTERSECT, or EXCEPT do not match in length" on page 401
207	-124	"More columns are being dropped from table '%1' than are defined" on page 346
207	-143	"Column '%1' not found" on page 200
208	-142	"Correlation name '%1' not found" on page 213
209	-144	"Column '%1' found in more than one table -- need a correlation name" on page 198
209	-163	"Derived table '%1' has no name for column %2" on page 244
213	-207	"Wrong number of values for INSERT" on page 541
217	-274	"Procedure or trigger calls have nested too deeply" on page 381
220	-158	"Value %1 out of range for destination" on page 533

Sybase error code	SQL Anywhere SQLCODE	Message text
230	-191	“Cannot modify column '%1' in table '%2'” on page 172
230	-190	“Cannot update an expression” on page 183
233	-195	“Column '%1' in table '%2' cannot be NULL” on page 199
233	-733	“Number of columns allowing NULLs exceeds limit” on page 359
257	-157	“Cannot convert %1 to a %2” on page 157
257	-705	“Return type of void from procedure '%1' cannot be used in any expression” on page 393
262	-121	“Permission denied: %1” on page 374
264	-637	“Duplicate insert column” on page 248
285	-708	“READTEXT or WRITETEXT statement cannot refer to a view” on page 383
301	-147	“There is more than one way to join '%1' to '%2'” on page 477
301	-680	“Invalid expression in WHERE clause of Transact-SQL outer join” on page 302
301	-146	“There is no way to join '%1' to '%2'” on page 478
305	-681	“Invalid join type used with Transact-SQL outer join” on page 306
311	-295	“Cannot uniquely identify rows in cursor” on page 182
314	-122	“Operation would cause a group cycle” on page 363
315	-136	“Table '%1' is in an outer join cycle” on page 435
315	-137	“Table '%1' requires a unique correlation name” on page 436
401	-134	“Feature '%1' not implemented” on page 266
401	-135	“Language extension” on page 333
401	-156	“Invalid expression near '%1'” on page 302
401	-994	“Too many arguments for function or procedure '%1'” on page 483
404	-890	“Statement size or complexity exceeds server limits” on page 417

Sybase error code	SQL Anywhere SQLCODE	Message text
409	109	“Null value eliminated in aggregate function” on page 359
409	–90	“Argument %1 of procedure '%2' cannot be NULL” on page 141
504	–265	“Procedure '%1' not found” on page 379
509	–140	“User ID '%1' does not exist” on page 528
512	–186	“Subquery cannot return more than one row” on page 419
518	103	“Invalid data conversion” on page 297
532	104	“Row has been updated since last time read” on page 395
532	106	“Value for column '%1' in table '%2' has changed” on page 534
538	–627	“Disallowed language extension detected in syntax near '%1' on line %2” on page 245
546	–194	“No primary key value for foreign key '%1' in table '%2'” on page 354
547	–198	“Primary key for row in table '%1' is referenced by foreign key '%2' in table '%3'” on page 377
547	–677	“Table '%1' has a foreign key with a referential action” on page 432
548	–196	“Index '%1' for table '%2' would not be unique” on page 284
548	–209	“Constraint '%1' violated: Invalid value for column '%2' in table '%3'” on page 210
548	–1091	“Constraint '%1' violated: Invalid value in table '%2'” on page 211
549	–729	“The specified foreign key (%1) can not be enforced” on page 471
550	–632	“WITH CHECK OPTION violated for insert/update on base table '%1'” on page 539
553	–264	“Wrong number of variables in FETCH” on page 541
554	–208	“Row has changed since last read -- operation canceled” on page 396
557	–853	“Cursor not in a valid state” on page 224
557	–170	“Cursor has not been declared” on page 224

Sybase error code	SQL Anywhere SQLCODE	Message text
558	-172	"Cursor already open" on page 223
559	-180	"Cursor not open" on page 225
560	100	"Row not found" on page 397
560	-197	"No current row of cursor" on page 350
573	-738	"Password must be at least %1 characters" on page 374
590	111	"Statement cannot be executed" on page 414
601	-642	"Invalid SQL descriptor name" on page 318
708	-80	"Unable to start database server" on page 507
708	-86	"Not enough memory to start" on page 357
708	-1179	"Unable to start database server: missing license file" on page 507
709	-996	"Specified local connection ID not found" on page 411
710	-997	"Local connection ID does not refer to the current database" on page 337
711	-998	"Cannot close a remote JDBC connection that is not the current connection" on page 155
840	-82	"Unable to start specified database: %1" on page 508
840	-87	"Database name required to start server" on page 232
840	-1008	"Unable to start specified database: '%1' is an invalid transaction log mirror" on page 509
840	-1009	"Unable to start specified database: The transaction log '%1' or its mirror '%2' is invalid" on page 516
840	-1010	"Unable to start specified database: '%1' not expecting any operations in transaction log" on page 511
840	-1011	"Unable to start specified database: Unknown encryption algorithm" on page 516

Sybase error code	SQL Anywhere SQLCODE	Message text
840	-1012	“Unable to start specified database: '%1' must be upgraded to start with this server (capability %2 missing)” on page 511
840	-1016	“Unable to start specified database: Cannot use log file '%1' since it has been used more recently than the database file” on page 513
840	-1017	“Unable to start specified database: '%1': transaction log file not found” on page 512
840	-1018	“Unable to start specified database: Cannot use log file '%1' since the offsets do not match the offsets in the database file” on page 514
840	-1019	“Unable to start specified database: Cannot use log file '%1' since the database file has been used more recently” on page 514
840	-1020	“Unable to start specified database: Cannot use log file '%1' since it is shorter than expected” on page 513
840	-1004	“Unable to start specified database: '%1' is not a data-base” on page 510
840	-1005	“Unable to start specified database: '%1' was created by a different version of the software” on page 512
840	-1006	“Unable to start specified database: '%1' is not a valid database file” on page 510
840	-1007	“Unable to start specified database: '%1' is an invalid transaction log” on page 509
840	-1063	“Unable to start database %1: Cannot use read-only mode if auditing is enabled” on page 505
840	-1147	“Database '%1' cannot be started on this platform. See http://iAnywhere.com/developer/product_manuals/sqlanywhere/notes/en/endi-an_corruption_warning.html ” on page 229
840	-1149	“Database '%1' cannot be started on this platform. See http://iAnywhere.com/developer/product_manuals/sqlanywhere/notes/en/endi-an_cant_change_platform.html ” on page 228
911	-83	“Specified database not found” on page 410
924	-816	“Specified database file already in use” on page 410

Sybase error code	SQL Anywhere SQLCODE	Message text
927	-97	"Database page size too big: %1" on page 233
927	-644	"Invalid database page size" on page 299
928	-645	"Database creation failed: %1" on page 231
932	-311	"Internal rollback log corrupted" on page 293
950	-76	"Request denied -- no active databases" on page 388
950	-74	"The selected database is currently inactive" on page 469
1205	-306	"Deadlock detected" on page 241
1205	-307	"All threads are blocked" on page 135
1205	-684	"Rollback occurred due to deadlock during prefetch" on page 394
1601	-102	"Database server connection limit exceeded" on page 236
1602	-85	"Communication error" on page 203
1602	-88	"Client/server communications protocol version mismatch" on page 197
1702	-616	"Too many columns in table" on page 484
1709	-849	"Referential integrity actions other than RESTRICT not allowed for temporary tables" on page 384
1709	-850	"Tables related by key constraint must both be permanent, or both be temporary and not created with ON COMMIT DELETE ROWS. For global temporary tables they must both be shared if one is shared" on page 439
1709	-865	"Key constraint between temporary tables requires a primary key (not unique constraint)" on page 331
1719	-118	"Table '%1' has no primary key" on page 433
1721	-113	"Column '%1' in foreign key has a different definition than primary key" on page 198
1801	-77	"Database name not unique" on page 232

Sybase error code	SQL Anywhere SQLCODE	Message text
1802	-138	“Dbospace '%1' not found” on page 240
1909	-636	“Duplicate referencing column” on page 249
1909	-119	“Primary key column '%1' already defined” on page 377
1909	-251	“Foreign key '%1' for table '%2' duplicates an existing foreign key” on page 269
1921	-111	“Index name '%1' not unique” on page 285
1921	-678	“Index name '%1' is ambiguous” on page 285
1923	-126	“Table cannot have two primary keys” on page 437
1923	-112	“Table already has a primary key” on page 437
2561	-106	“Cannot open transaction log file -- %1” on page 174
2601	-193	“Primary key for table '%1' is not unique : Primary key value ('%2')” on page 378
2706	-141	“Table '%1' not found” on page 436
2715	-613	“User-defined type '%1' not found” on page 531
2727	-189	“Unable to find in index '%1' for table '%2’” on page 503
2732	-296	“Error number %1 for RAISERROR must not be less than 17000” on page 253
2748	-612	“User message %1 not found” on page 529
2749	-294	“Format string argument number %1 is invalid” on page 271
3013	-305	“I/O error %1 -- transaction rolled back” on page 276
3013	-309	“Memory error -- transaction rolled back” on page 341
3206	-240	“Unknown backup operation” on page 518
3206	-241	“Database backup not started” on page 230
3206	-242	“Incomplete transactions prevent transaction log renaming” on page 281

Sybase error code	SQL Anywhere SQLCODE	Message text
3206	-1021	"Invalid backup operation" on page 294
3451	-672	"Database upgrade failed" on page 237
3451	-673	"Database upgrade not possible" on page 238
3618	-302	"Terminated by user -- transaction rolled back" on page 441
3618	-304	"Disk full '%1' -- transaction rolled back" on page 245
3619	-107	"Error writing to transaction log file" on page 254
3621	-299	"Statement interrupted by user" on page 416
3702	-214	"Table in use" on page 438
3702	-215	"Procedure in use by '%1'" on page 380
3702	-750	"User owns procedures in use" on page 530
3702	-751	"User owns tables in use" on page 530
3819	-160	"Can only describe a SELECT statement" on page 149
4001	-105	"Database cannot be started -- %1" on page 230
4001	-84	"Specified database is invalid" on page 410
4001	-72	"No database file specified" on page 351
4002	-103	"Invalid user ID or password" on page 324
4002	-104	"Invalid user ID or password on preprocessed module" on page 325
4224	-108	"Connection not found" on page 207
4224	-99	"Connections to database have been disabled" on page 209
4224	-308	"Connection was terminated" on page 208
4406	-703	"Cannot insert or update computed column '%1'" on page 171
4409	-114	"Number of columns defined for the view does not match SELECT statement" on page 360

Sybase error code	SQL Anywhere SQLCODE	Message text
4412	-766	“View references '%1', which is a temporary object. Views can only refer to permanent objects” on page 536
4708	-702	“TRUNCATE TABLE statement cannot be used on a view” on page 496
4901	-116	“Table must be empty” on page 438
4939	-127	“Cannot alter a column in an index” on page 152
5006	-604	“A dbspace has reached its maximum file size” on page 129
5006	-605	“The server attempted to access a page beyond the end of the maximum allowable dbspace file size” on page 470
5703	107	“Language extension detected in syntax near '%1' on line %2” on page 333
5849	-201	“Invalid setting for option '%1'” on page 317
5849	-1053	“‘%1' is an invalid value for '%2'” on page 548
5864	-81	“Invalid database server command line” on page 299
5864	-735	“Invalid parameter” on page 309
5864	-79	“Invalid local database option” on page 306
5864	-95	“Parse error: %1” on page 369
5864	-754	“Parse error: %1” on page 369
5878	-204	“Only the DBA can set the option '%1'” on page 361
5878	-216	“The option '%1' can only be set as a temporary option” on page 464
5878	-217	“The option '%1' cannot be set from within a procedure” on page 465
6001	-109	“There are still active database connections” on page 477
6004	-75	“Request to start/stop database denied” on page 389
6226	-183	“Cannot find index named '%1'” on page 168
6259	-263	“Invalid absolute or relative offset in FETCH” on page 294

Sybase error code	SQL Anywhere SQLCODE	Message text
6267	-814	“Cannot update column '%1' since it appears in the ORDER BY clause” on page 183
6401	-220	“Savepoint '%1' not found” on page 398
7123	-608	“Invalid TEXTPTR value used with WRITETEXT or READ-TEXT” on page 320
7139	-609	“Invalid data type for column in WRITETEXT or READ-TEXT” on page 298
7201	-155	“Invalid host variable” on page 303
7203	-89	“Database server not running in multi-user mode” on page 237
7301	-192	“Update operation attempted on non-updatable query” on page 522
7301	-813	“FOR UPDATE has been incorrectly specified for a READ ONLY cursor” on page 269
7321	-149	“Function or column reference to '%1' must also appear in a GROUP BY” on page 273
7337	101	“Value truncated” on page 534
7338	-728	“Update operation attempted on non-updatable remote query” on page 522
7364	-139	“More than one table is identified as '%1'” on page 347
7374	-676	“The specified transaction isolation is invalid” on page 473
7705	-630	“Invalid escape sequence '%1'” on page 301
7706	-606	“The pattern is too long” on page 466
7707	-629	“Invalid escape character '%1'” on page 301
7732	-633	“Update operation attempted on a read-only cursor” on page 522
7740	-815	“Cannot update column '%1' since it does not appear in the SELECT clause” on page 184
7950	-100	“Database server not found” on page 237

Sybase error code	SQL Anywhere SQLCODE	Message text
7950	-96	“Database server already running” on page 235
8201	-640	“Invalid descriptor index” on page 300
8205	-641	“Error in assignment” on page 252
8405	-210	“User '%1' has the row in '%2' locked” on page 525
9119	-78	“Dynamic memory exhausted” on page 250
9502	-638	“Right truncation of string data” on page 394
9526	-187	“Illegal cursor operation attempt” on page 278
9819	-268	“Trigger '%1' not found” on page 493
10356	-624	“Expression has unsupported data type” on page 261
11205	-698	“The remote server does not support an auto-incrementing data type” on page 467
11205	-732	“Creating remote tables with computed columns is not supported” on page 222
11205	-736	“The data type of column '%1' is not supported” on page 449
11206	-656	“Unable to connect to server '%1': %2” on page 500
11207	-667	“Could not access column information for the table '%1'” on page 213
11208	-722	“The column '%1' does not exist in the remote table” on page 447
11209	-721	“The data type specified for column '%1' is not compatible with the actual data type” on page 450
11210	-723	“The length specified for column '%1' is different than the actual length” on page 457
11211	-724	“NULL attribute mismatch for column '%1'” on page 358
11212	-725	“Identity attribute mismatch for column '%1'” on page 277
11214	-659	“Remote server '%1' could not be found” on page 385
11214	-666	“The remote table '%1' could not be found” on page 467

Sybase error code	SQL Anywhere SQLCODE	Message text
11215	-726	"The table specification '%1' identifies more than one remote table" on page 475
11221	-712	"External login for server '%1' could not be found" on page 264
11227	-706	"Remote server does not have the ability to support this statement" on page 386
11248	-658	"Remote server '%1' is currently configured as read-only" on page 386
12006	-110	"Item '%1' already exists" on page 326
13075	102	"Using temporary table" on page 532
13204	-150	"Invalid use of an aggregate function" on page 323
13241	-1315	"Script file missing statement \"go\" delimiter on a separate line" on page 400
13243	-1267	"Event parameter '%1' not found" on page 260
13244	-1266	"No notification within timeout on queue '%1'" on page 353
13245	-1265	"Event object named '%1' already exists" on page 259
13246	-1264	"Event object name '%1' is not valid" on page 259
13247	-1263	"Event notification queue '%1' not found" on page 257
13248	148	"Event notification queue '%1' not found warning" on page 258
13249	147	"Event notifications lost on queue '%1'" on page 258
13250	-1269	"Service statement definition is invalid or unsupported" on page 406
13251	-1262	"This edition of SQL Anywhere is not available on this platform" on page 480
13252	-1261	"This server is not licensed to support '%1' connections" on page 480
13253	-1260	"This server is not licensed to support the '%1' feature" on page 481

Sybase error code	SQL Anywhere SQLCODE	Message text
13254	145	“Two rows with the same primary key have been download for table '%1'” on page 497
13259	–1254	“MERGE statement for table '%1' failed because of a RAISERROR specification in the statement” on page 342
13260	–1253	“The text index %1 needs to be refreshed” on page 475
13261	–1151	“The logging type ('%1') specified is invalid, not supported or incompatible” on page 457
13266	–1313	“Maximum string length exceeded” on page 341
13270	–1244	“An attempt to decrypt database '%1' failed” on page 136
13271	–1243	“An attempt to encrypt database '%1' failed” on page 137
13273	–1241	“Value-sensitive cursor used after a TRUNCATE” on page 535
13274	144	“Mirror file requires higher checksum_level” on page 343
13275	143	“Retrying read of corrupt page (page '%1')” on page 392
13276	142	“UltraLite database state was restored” on page 498
13277	–1240	“The provided stoplist is too long” on page 466
13280	–1238	“Passthrough SQL script failed” on page 370
13281	–1237	“Too many columns in procedure result set” on page 483
13282	–1236	“Too many expressions in GROUP BY list” on page 486
13283	–1235	“Too many columns in SELECT list” on page 484
13284	–1233	“The materialized view %1 cannot be changed to immediate because it does not have a unique index on non-nullable columns” on page 459
13285	–1232	“Attempt to start a second snapshot in a transaction” on page 144
13286	–1231	“Statement timed out: '%1'” on page 418
13287	–1230	“Too many open cursors” on page 487
13288	–1229	“Reorganize table is already being run on table \"%1\” on page 387

Sybase error code	SQL Anywhere SQLCODE	Message text
13289	141	“Passthrough SQL script failed” on page 371
13291	–1226	“Foreign key columns do not match the primary key or a uniqueness constraint in \"%1\" on page 270
13292	–1225	“Synchronization profiles are not supported for this database” on page 427
13293	–1224	“Synchronization profile '%1' has invalid parameter '%2'” on page 426
13294	–1223	“Synchronization profile '%1' already exists” on page 426
13296	–1221	“Duplicate options not allowed in the CREATE DATABASE statement” on page 249
13297	–1216	“The arguments to this procedure must be literal strings” on page 446
13298	–1219	“Maintenance of dependent immediate materialized view(s) failed” on page 339
13299	–1218	“The materialized view cannot be changed to immediate because it does not have a unique index on non-aggregate non-nullable columns” on page 461
13300	–1220	“User cannot be dropped because external logins exist for this user” on page 528
13301	–1213	“External environment does not support result sets” on page 262
13302	–1217	“Synchronization profile '%1' not found” on page 427
13303	–1212	“Connection disallowed by login policy for this user” on page 206
13304	–1211	“MERGE statement ANSI cardinality violation on table '%1'” on page 342
13308	–1207	“Invalid use of NEAR operator in text query” on page 324
13309	–1206	“External environments are not supported for this database” on page 263
13310	–1205	“External environment '%1' could not be found” on page 261

Sybase error code	SQL Anywhere SQLCODE	Message text
13311	-1204	“INSERT ... ON EXISTING UPDATE not allowed: immediate materialized view %1 depends on %2” on page 289
13312	-1203	“WRITETEXT not allowed: immediate materialized view %1 depends on %2” on page 540
13313	-1202	“Operation not allowed on a table with dependent immediate materialized views” on page 363
13314	-1201	“Client library reported an error opening object ('%1') during transfer” on page 195
13315	-1200	“Client library reported a permissions error accessing object ('%1') during transfer” on page 194
13316	-1199	“The materialized view cannot be changed to immediate because COUNT(*) is required to be part of the SELECT list” on page 460
13317	-1198	“User \"%1\" already exists” on page 527
13318	-1197	“Login policy \"%1\" in use” on page 338
13319	-1196	“Login policies are not supported for this database” on page 338
13320	-1195	“Login policy \"%1\" not found” on page 339
13321	-1194	“Login policy \"%1\" already exists” on page 338
13322	-1193	“TRUNCATE TABLE not allowed: initialized immediate materialized view %1 depends on %2” on page 496
13323	-1192	“Cannot update multiple tables immediate materialized view %1 depends on” on page 185
13324	-1191	“LOAD TABLE not allowed: initialized immediate materialized view %1 depends on %2” on page 336
13325	-1190	“LOAD TABLE is not allowed on a materialized view %1” on page 334
13326	-1189	“The UTF-16 endian specified does not match the Byte Order Mark found in the data” on page 476
13327	-1188	“LOAD TABLE error: %1” on page 334

Sybase error code	SQL Anywhere SQLCODE	Message text
13328	-1187	"Cannot append when using compression or encryption" on page 153
13329	-1186	"Database page validation failed with code: %1" on page 234
13330	-1185	"Index validation failed for table %1, index %2 with code: %3" on page 286
13331	-1184	"Cannot drop last unique index of an immediate materialized view" on page 166
13332	-1183	"Support for permissions on dbspaces is not available for this database" on page 421
13333	-1182	"Command not allowed on IMMEDIATE REFRESH text index" on page 202
13334	-1181	"The materialized view cannot be changed to immediate because its definition must not contain more than one query block" on page 462
13335	-1180	"Cannot set database option \"%1\" because it is on the options watch list" on page 180
13336	-1178	"Transaction log mirroring cannot be used with database mirroring" on page 492
13337	-1176	"Plan not available. NOEXEC Plan can not be generated for this type of statement" on page 375
13338	-1175	"Unable to acquire table locks in specified time" on page 499
13339	-1174	"Cannot create text configuration '%1' because option '%2' has an inappropriate setting" on page 161
13340	-1173	"Client library reported an error accessing data during transfer (%1)" on page 195
13341	-1172	"Client application disallowed the transfer of data (%1)" on page 193
13342	-1171	"Client application does not allow transfer of data (%1)" on page 194
13343	-1170	"The materialized view %1 cannot be changed to immediate because it has already been initialized" on page 460

Sybase error code	SQL Anywhere SQLCODE	Message text
13344	-1169	“Cannot access a table that is part of a text index” on page 150
13345	-1168	“Cannot alter or drop a text configuration referenced by a text index” on page 153
13346	-1167	“Cannot drop a user that owns text configurations” on page 166
13347	-1166	“Text indexes are not supported for this database” on page 442
13348	-1165	“Error creating text index \"%1\" on table \"%2\" on page 251
13349	-1164	“Text query parser error: %1” on page 443
13350	-1163	“Invalid collation: \"%1\"” on page 295
13351	-1162	“Term length outside allowed range” on page 440
13352	-1161	“Text configuration \"%1\" already exists” on page 441
13353	-1160	“Text configuration \"%1\".\"%2\" not found” on page 442
13354	-1159	“Non-constant or unknown text query string” on page 355
13355	-1158	“No matching text index” on page 352
13356	-1157	“All column reference arguments must refer to the same table” on page 134
13357	-1156	“Argument \"%1\" must be a column reference” on page 141
13358	-1155	“Unable to close the cursor on table \"%1\". LOAD TABLE cannot be executed” on page 500
13359	-1154	“Traced query (%1, %2) does not exist” on page 490
13360	-1153	“Password has expired but cannot be changed because the database is read-only” on page 373
13361	-1152	“Password has expired” on page 373
13362	-1150	“The SQL scripts DLL cannot be loaded” on page 473
13363	-1148	“Feature not supported by the client version or the client interface” on page 267

Sybase error code	SQL Anywhere SQLCODE	Message text
13366	-1146	“LOAD TABLE not allowed on temporary table which has foreign key references from another table” on page 335
13367	-1145	“Unable to connect: The server did not accept the requested encryption type” on page 501
13368	-1144	“‘%1’ cannot be used as the encoding specification for ‘%2’ data” on page 547
13369	140	“Encryption has not been enabled” on page 251
13370	-1143	“Encryption has not been enabled” on page 251
13371	-1142	“Use of statement ‘%1’, which requires feature ‘%2’, is not allowed” on page 523
13372	-1141	“Unable to start database ‘%1’: NCHAR collation or tailoring not supported on this platform” on page 506
13373	-1140	“Unable to start database ‘%1’: CHAR collation or tailoring not supported on this platform” on page 506
13374	-1139	“The Remote Data Services feature is not supported on this platform” on page 466
13375	-1138	“The mirror ‘%1’ does not match database ‘%2’” on page 463
13376	-1137	“Escape character conflict ‘%1’” on page 255
13377	-1136	“Invalid use of escape character ‘%1’” on page 323
13378	-1135	“Invalid regular expression: %1 in ‘%2’” on page 314
13379	-1134	“Triggers cannot be created on materialized view ‘%1’” on page 495
13380	-1133	“Invalid trigger type for view ‘%1’” on page 321
13381	-1132	“Maximum row size for table ‘%1’ would be exceeded” on page 340
13382	-1131	“The attribute ‘%1’ sets an option ‘%2’ that is incompatible with ‘%3’” on page 447
13383	-1130	“The ‘%1’ attribute is missing a comma within ‘%2’” on page 444

Sybase error code	SQL Anywhere SQLCODE	Message text
13384	-1129	“The '%1' attribute contains mismatched parentheses within '%2'” on page 444
13385	-1128	“Start date/time for non-recurring event '%1' is in the past” on page 414
13386	-1127	“Positioned update operation attempted on a view with an INSTEAD OF trigger” on page 376
13387	-1126	“Operation failed because table or view '%1' has an INSTEAD OF trigger” on page 362
13388	-1125	“Conflicting INSTEAD OF trigger and WITH CHECK OPTION on view '%1'” on page 205
13389	-1124	“The dbicu library and server versions do not match” on page 452
13390	-1123	“Invalid mime type '%1'” on page 307
13391	-1122	“Exceeded maximum of '%1' allowable parameters” on page 260
13392	-1121	“Not enough free space on device to grow dbspace '%1' by requested amount” on page 357
13393	-1120	“The dbspace '%1' cannot be dropped because it contains tables or indexes” on page 453
13394	-1119	“The '%1' property is no longer supported” on page 445
13395	-1118	“Cannot change the MobiLink remote id when the status of the last upload is unknown” on page 155
13396	-1117	“A row cannot be stored because it exceeds the database page size” on page 130
13397	201	“The ICU collation '%1' has defaulted to another collation” on page 455
13398	-1116	“Collation '%1' not supported on this platform” on page 197
13399	-1115	“Table '%1' contains an invalid reference to the ROWID function” on page 432
13400	-1114	“Invalid setting for SOAP header '%1'” on page 318

Sybase error code	SQL Anywhere SQLCODE	Message text
13401	-1113	“Correlation name '%1' is not valid for use with the ROWID function” on page 212
13402	-1112	“Specified file system volume not found for database '%1'” on page 411
13403	-1111	“Information for synchronization was not provided” on page 287
13404	-1110	“Synchronization process was unable to re-enter synchronization” on page 425
13405	-1109	“Unable to perform requested operation since this database uses keyless encryption” on page 504
13406	-1108	“Unable to access the filesystem on the device” on page 499
13407	-1107	“Too many references to a BLOB” on page 489
13408	-1106	“Too many publications specified for operation” on page 488
13410	-1104	“Too many users in database” on page 490
13411	-1103	“No partial download was found” on page 353
13412	-1102	“Unable to retry download because upload is not finished” on page 505
13413	-1101	“Column '%1' not part of any indexes in its containing table” on page 201
13414	-1100	“The operation failed because column '%1's type does not support streaming” on page 463
13415	139	“Option '%1' specified more than once” on page 364
13416	-1099	“Transact-SQL outer joins are currently disabled” on page 491
13417	-1098	“A tracing connection is already active” on page 131
13418	-1097	“ATTACH TRACING could not connect to the tracing database” on page 143
13419	-1096	“The specified http header is malformed” on page 472

Sybase error code	SQL Anywhere SQLCODE	Message text
13420	-1095	"The specified http header contains illegal or non-ASCII characters" on page 471
13421	-1094	"The http header '%1' is reserved and cannot be modified" on page 454
13422	-1093	"The size of the character column, variable, or value data type exceeds 32767" on page 470
13423	138	"Publication predicates were not evaluated" on page 382
13424	-1090	"Function '%1' has invalid parameter '%2' ('%3')" on page 272
13425	-1089	"Invalid commit action for shared temporary table" on page 296
13426	-1088	"ATTACH TRACING TO LOCAL DATABASE cannot be used with a strongly encrypted database" on page 143
13427	-1087	"Could not refresh tracing: volatile_statistics have to be collected in order for %1 specified on row %2 to be collected" on page 221
13428	-1086	"Write access was denied" on page 540
13429	-1085	"Duplicate key column (%1)" on page 248
13430	-1084	"Use of feature '%1' is not allowed" on page 523
13431	-1083	"Could not refresh tracing: failed to find object %1 on row %2" on page 220
13432	-1082	"Could not refresh tracing: invalid tracing specification on sa_diagnostic_tracing_level row %1" on page 221
13433	-1081	"Could not refresh tracing: at least one enabled tracing level must be specified" on page 220
13434	-1080	"Cannot revoke these permissions while user '%1' is actively replicating transactions" on page 178
13435	-1079	"Backup is unable to open database file '%1'" on page 148
13436	-1078	"Cycle in computed column dependencies" on page 226
13437	-1077	"Cannot use materialized view '%1' because it has not yet been initialized" on page 187

Sybase error code	SQL Anywhere SQLCODE	Message text
13438	-1076	"dbicu libraries are required but not installed" on page 240
13439	-1075	"Failed to convert from character set '%1' to '%2'" on page 265
13440	-1074	"Login mode '%1' not permitted by login_mode setting" on page 337
13441	-1072	"'%1' is not a valid character set encoding for use with collation '%2'" on page 551
13442	-1092	"The method you attempted to invoke was not enabled for your application" on page 462
13442	-1071	"The %1 algorithm is not available in FIPS mode" on page 443
13442	-1073	"'%1' cannot be used as the NCHAR collation: only UCA and UTF8BIN may be used" on page 547
13444	-1070	"Kerberos logins are not supported" on page 330
13445	-1069	"Kerberos login failed" on page 330
13446	-1068	"Default dbspace '%1' not found" on page 243
13448	-1066	"File system error: %1" on page 268
13449	-1065	"Attempt to use snapshot isolation in a non-snapshot transaction" on page 144
13450	-1064	"Update conflict on snapshot transaction" on page 521
13451	-1062	"Statement not allowed during snapshot" on page 417
13452	-1061	"Table created or altered after start of snapshot" on page 437
13453	-1060	"Operation conflict with publication type" on page 362
13454	-1305	"MobiLink communication error; code: %1, parameter: %2, system code %3" on page 345
13455	-1304	"Could not create a new text for this table with the same settings as \"%1\" on page 215
13456	-1057	"BACKUP clause '%1' conflicts with '%2'" on page 146

Sybase error code	SQL Anywhere SQLCODE	Message text
13457	-1303	"Too many MESSAGE ... FOR CONNECTION messages" on page 487
13459	-1054	"Snapshot isolation disabled or pending" on page 409
13460	-1051	"Cannot create a materialized view because option '%1' has an inappropriate setting" on page 159
13461	-1050	"Cannot return NULL result as requested data type" on page 178
13461	-1052	"Cannot update materialized view because option '%1' has an inappropriate setting" on page 184
13464	-1047	"This database does not support encrypted tables" on page 480
13465	-1046	"Illegal column definition: %1" on page 277
13466	-1045	"Invalid backup parameter value" on page 294
13467	-1044	"Invalid password: %1" on page 310
13468	-1043	"Request interrupted due to timeout" on page 388
13469	-1042	"Cannot add a comment to a table declared as LOCAL TEMPORARY" on page 152
13470	-1041	"Materialized View '%1' not found" on page 340
13471	-1040	"Cannot use view '%1' because it is invalid" on page 188
13472	-1039	"Cannot connect to mirror server. Use server name '%1' to find the primary server" on page 156
13473	-1038	"Cannot use view '%1' because it has been disabled" on page 187
13474	-1037	"Cannot drop or modify object '%1' because at least one other object (%2 '%3') depends upon it" on page 167
13475	-1036	"The DBN/DBF parameters do not match the database for this alternate server name" on page 453
13476	-1035	"LOAD TABLE not permitted on mirrored database" on page 336
13477	-1034	"The '%1' attribute is not valid with procedure type '%2'" on page 445

Sybase error code	SQL Anywhere SQLCODE	Message text
13478	-1033	“Unable to start database server: Server fatal error” on page 508
13479	-1031	“Syntax error near '%1' -- Materialized view definition must not use the following construct: '%2'” on page 429
13480	-1032	“Syntax error near '%1' -- The materialized view cannot be changed to immediate because its definition contains an illegal construct: '%2'” on page 429
13480	-1030	“Secure HTTP connections are not supported on this platform” on page 401
13481	-1029	“Support for materialized views is not available for this database” on page 421
13482	-1028	“Connection attempting BACKUP has uncommitted transactions” on page 206
13483	-1027	“Service type does not allow '%1' attribute” on page 407
13484	-1026	“USING attribute cannot coexist with FORMAT or GROUP attributes” on page 532
13485	-1025	“Duplicate attribute '%1' in service” on page 247
13486	-1024	“Unsupported property '%1' in service USING attribute” on page 520
13487	-1023	“Missing value for attribute '%1' in service” on page 344
13488	-1022	“Invalid value for attribute '%1' in service” on page 325
13489	137	“Row was dropped from table %1 to maintain referential integrity” on page 397
13490	-1003	“Too many distinct group mappings for integrated user” on page 485
13491	-1001	“Parameter '%1' in procedure or function '%2' does not have a default value” on page 366
13492	-1000	“Temporary space limit exceeded” on page 440
13493	-999	“Invalid request log format on line %1” on page 314
13494	136	“The database was created” on page 452

Sybase error code	SQL Anywhere SQLCODE	Message text
13494	-1002	“The option '%1' is not recognized” on page 465
13495	-995	“Warning detected when optimizing SELECT INTO is treated as an error” on page 537
13496	-993	“LOAD TABLE not allowed on temporary table with ON COMMIT DELETE ROWS” on page 335
13497	-992	“The specified listener could not be registered” on page 472
13498	-991	“Clause '%1' has invalid attribute '%2’” on page 193
13499	-990	“The secure connection to the remote host failed: %1” on page 468
13500	-989	“NAMESPACE attribute is not valid with procedure type '%1’” on page 349
13501	-988	“Invalid response from the HTTP server” on page 315
13502	-987	“Invalid procedure subtype '%1' for type '%2’” on page 311
13503	-986	“Invalid procedure type '%1’” on page 312
13504	-985	“The database name 'utility_db' is reserved for the utility database” on page 451
13505	-984	“Could not initialize the encryption DLL: '%1’” on page 217
13506	-983	“HTTP request failed. Status code '%1’” on page 275
13507	-982	“Connection timed out” on page 208
13508	-981	“Unable to connect to the remote host specified by '%1’” on page 501
13509	-980	“The URI '%1' is invalid” on page 476
13510	-979	“Output file cannot be written” on page 365
13511	-978	“Directory for output file does not exist” on page 244
13513	-976	“Could not load the encryption DLL \"%1\” on page 219
13515	-973	“The string is too long (%1)” on page 474
13516	-972	“Database page size too small: %1” on page 234

Sybase error code	SQL Anywhere SQLCODE	Message text
13517	-971	"Checksums are not enabled in this database" on page 192
13518	134	"UltraLite cursor (or result set or table) was restored" on page 498
13519	133	"UltraLite connection was restored" on page 497
13520	-970	"Invalid hint specified for table '%1'" on page 303
13521	-969	"Required operators excluded" on page 389
13522	-968	"User '%1' already has EXECUTE permission" on page 524
13523	-967	"Backup file '%1' already exists" on page 147
13524	-966	"Composite ORDER BY not allowed with RANGE" on page 203
13525	-965	"Window function requires ORDER BY" on page 538
13526	-964	"Window function used in predicate" on page 538
13527	-962	"Argument to GROUPING aggregate must be a grouping column in the GROUP BY clause" on page 142
13528	-963	"Password contains an illegal character" on page 372
13528	-961	"Input string is not base64-encoded" on page 288
13529	-959	"Compression error: %1" on page 204
13530	-958	"Password cannot be longer than %1 characters" on page 372
13530	-960	"Decompression error: %1" on page 242
13531	-957	"Invalid preceding or following size in OLAP function" on page 310
13532	-956	"Information for synchronization is incomplete or invalid, check '%1'" on page 287
13533	-955	"This connection already exists" on page 479
13534	-954	"The database '%1' was not found" on page 450
13535	-953	"A schema upgrade is not currently allowed" on page 131
13536	-952	"The status of the last synchronization upload is unknown" on page 474

Sybase error code	SQL Anywhere SQLCODE	Message text
13537	-951	“Cannot access schema file '%1'” on page 151
13538	-950	“Frame not allowed for window '%1'” on page 271
13539	-949	“ORDER BY not allowed in window '%1'” on page 364
13540	-948	“PARTITION BY not allowed in reference to window '%1'” on page 370
13541	-947	“Window '%1' not found” on page 538
13542	-946	“Result set not permitted in '%1'” on page 392
13543	-945	“Recursive column %1: conversion from '%2' to '%3' loses precision” on page 384
13544	-944	“Too many expressions in GROUP BY list for ROLLUP, CUBE, or GROUPING SETS operation” on page 486
13545	-943	“No workload capture currently exists” on page 355
13546	-942	“A workload capture (%1) is already in progress” on page 133
13547	-940	“Invalid setting for HTTP header '%1'” on page 316
13548	-941	“jConnect does not support encryption” on page 328
13548	-939	“Invalid setting for HTTP option '%1'” on page 317
13549	-938	“Recursion is not allowed without the RECURSIVE keyword” on page 383
13550	-937	“Invalid reference to or operation on constraint '%1'” on page 313
13551	-936	“Too many constraints in database” on page 485
13552	-934	“Unable to start specified database: Server must be upgraded to start database %1” on page 515
13553	-935	“Unable to start specified database: Log file error” on page 515
13554	-931	“Service definition requires a statement when authorization is off” on page 405
13555	-930	“(no message)” on page 553

Sybase error code	SQL Anywhere SQLCODE	Message text
13556	-929	“Constraint '%1' not found” on page 209
13557	-928	“Constant expressions must not appear in GROUP BY clause” on page 209
13558	-927	“Service statement definition is inconsistent with service type” on page 406
13559	-926	“Host variable reference in service definition must be named” on page 274
13560	-925	“Invalid service name '%1’” on page 316
13561	-923	“Too many recursive iterations” on page 488
13562	-922	“No column list for recursive query” on page 350
13563	-921	“Invalid recursive query” on page 312
13564	-920	“Service '%1' not found” on page 405
13565	-919	“Service '%1' already exists” on page 404
13566	-918	“A user name must be specified if AUTHORIZATION is Off” on page 132
13567	-924	“Service '%1' in use” on page 404
13568	-916	“'%1' is an unrecognized service type” on page 549
13569	-915	“Service type required for CREATE SERVICE” on page 407
13570	-914	“Cycle in common table expression references” on page 226
13571	-913	“A transaction log file is required for auditing” on page 132
13572	-912	“Insufficient memory for OPENXML query” on page 290
13573	-911	“Control character in XML output” on page 212
13574	-910	“System command failed with return code %1” on page 430
13575	-908	“Invalid operation on a closed object” on page 308
13576	-907	“No name for argument” on page 352

Sybase error code	SQL Anywhere SQLCODE	Message text
13577	-906	“XMLGEN evaluation failure” on page 542
13578	-905	“Invalid XQuery constructor” on page 325
13579	-904	“Illegal ORDER BY in aggregate function” on page 280
13580	-901	“Undeclared tag ID: '%1’” on page 517
13580	-903	“CDATA has a name” on page 188
13581	-900	“Parent not open: '%1’” on page 368
13581	-902	“Too few columns” on page 482
13582	-899	“Illegal column name: '%1’” on page 278
13583	-898	“Unknown FOR XML EXPLICIT directive: '%1’” on page 518
13584	-897	“Illegal FOR XML EXPLICIT tag value: '%1’” on page 279
13585	132	“Cannot output the histogram for string column '%1’” on page 174
13587	-896	“Cannot delete PUBLIC option '%1' since user settings exist” on page 162
13588	130	“A row was dropped because it could not be converted to the new schema format” on page 130
13589	-895	“Encryption error: %1” on page 250
13589	-894	“Plan can not be generated for this type of statement” on page 375
13590	-893	“Illegal flags value passed to OPENXML” on page 279
13591	-892	“XPath parser error: %1” on page 543
13592	-891	“Cannot convert between requested character sets '%1' and '%2’” on page 159
13593	-657	“Unable to connect, server definition is circular” on page 501
13594	-889	“Statement contains an illegal usage of the non-deterministic function '%1’” on page 415
13595	-888	“XML parser error: %1” on page 542

Sybase error code	SQL Anywhere SQLCODE	Message text
13596	129	“Plan may contain virtual indexes” on page 375
13597	–887	“Virtual index creation with more than %1 columns” on page 536
13600	0	“(no message)” on page 553
13601	–690	“Return value cannot be set” on page 393
13602	–693	“JDBC feature '%1' not supported” on page 328
13603	–694	“Could not change an opened prepared statement or callable statement” on page 214
13604	–695	“An internal error occurred in a '%1’” on page 137
13605	–696	“Invalid operation on a closed '%1’” on page 307
13606	–699	“Cannot update member fields qualified with \"final\" modifier” on page 185
13607	–701	“Cannot access instance member through a class” on page 151
13608	–713	“An internal error occurred in a '%1’” on page 138
13609	–714	“Invalid operation on a closed '%1’” on page 308
13613	114	“Character set conversion to '%1' cannot be performed; '%2' is used instead” on page 189
13614	115	“Database server cannot convert data from/to character set '%1', conversion may not be correct” on page 236
13615	116	“Language '%1' is not supported, '%2' will be used” on page 332
13616	117	“Unsupported character set '%1' and unsupported language '%2'; language used is '%3' instead” on page 520
13617	118	“Illegal user selectivity estimate specified” on page 281
13618	105	“Procedure has completed” on page 380
13619	200	“Warning: %1” on page 537
13620	–98	“Authentication violation” on page 145
13621	–218	“Authentication failed” on page 145

Sybase error code	SQL Anywhere SQLCODE	Message text
13622	-101	“Not connected to a database” on page 356
13623	-125	“ALTER clause conflict” on page 135
13624	-610	“User message %1 already exists” on page 529
13625	-120	“User '%1' already has GRANT permission” on page 524
13626	-123	“User '%1' is not a user group” on page 527
13627	-312	“User '%1' already has membership in group '%2’” on page 525
13628	-130	“Invalid statement” on page 320
13629	-132	“SQL statement error” on page 412
13630	-133	“Invalid prepared statement type” on page 311
13631	-707	“Statement is not allowed in passthrough mode” on page 416
13632	-614	“Cannot drop a user that owns messages or data types” on page 164
13633	-731	“Cannot drop a user that owns objects involved in replication” on page 165
13634	-161	“Invalid type on DESCRIBE statement” on page 322
13635	-181	“No indicator variable provided for NULL result” on page 351
13636	-182	“Not enough fields allocated in SQLDA” on page 356
13637	-185	“SELECT returns more than one row” on page 402
13638	-188	“Not enough values for host variables” on page 358
13640	-267	“COMMIT/ROLLBACK not allowed within atomic operation” on page 202
13641	-270	“Cannot drop a user that owns procedures in runtime server” on page 165
13642	-280	“Publication '%1' not found” on page 381
13643	-281	“Table '%1' has publications” on page 434
13644	-282	“Subscription to '%1' for '%2' already exists” on page 420

Sybase error code	SQL Anywhere SQLCODE	Message text
13645	-283	"Subscription to '%1' for '%2' not found" on page 420
13646	-284	"User '%1' is already the publisher for this database" on page 526
13647	-285	"User '%1' is not a remote user for this database" on page 526
13648	-286	"Remote message type '%1' not found" on page 385
13649	-287	"Passthrough statement inconsistent with current pass-through" on page 371
13650	-288	"Remote statement failed" on page 387
13652	-211	"Not allowed while '%1' is using the database" on page 355
13653	-212	"CHECKPOINT statement requires a rollback log" on page 191
13654	-221	"ROLLBACK TO SAVEPOINT not allowed" on page 395
13655	-222	"Result set not allowed from within an atomic compound statement" on page 391
13656	-213	"Savepoints require a rollback log" on page 399
13657	-230	"sqlpp/dblib version mismatch" on page 413
13658	-231	"Client/database server version mismatch" on page 196
13660	-243	"Unable to delete database file" on page 502
13661	-244	"Transaction log was truncated" on page 492
13662	-297	"User-defined exception signaled" on page 531
13663	-298	"Attempted two active database requests" on page 144
13664	-300	"Run time SQL error -- %1" on page 398
13665	-301	"Internal database error %1 -- transaction rolled back" on page 293
13666	-1288	"'%1' statement is not allowed on a mirrored database" on page 552
13668	-1286	"Immediate materialized view definition cannot contain a SUM function over a nullable expression" on page 281

Sybase error code	SQL Anywhere SQLCODE	Message text
13669	-601	"'%1' is not a known file format for loading or unloading tables" on page 550
13670	-602	"Cannot access file '%1' -- %2" on page 150
13672	-643	"UNLOAD TABLE cannot be used to unload a view" on page 519
13673	-607	"Cannot stop the database server" on page 180
13674	-617	"Calling functions outside the database server is not supported" on page 149
13675	-618	"Mismatch between external function platform specifier and current operating system" on page 344
13676	-619	"Need a dynamic library name" on page 350
13677	-620	"Could not load dynamic library '%1'" on page 218
13678	-621	"Could not find '%1' in dynamic library '%2'" on page 217
13679	-622	"Could not allocate resources to call external function" on page 214
13680	-625	"Too many parameters to this external procedure call" on page 487
13681	-626	"A thread used internally could not be started" on page 131
13682	-634	"Unterminated C string" on page 521
13683	110	"Transaction log backup page only partially full" on page 492
13684	149	"Automatic database upgrade applied" on page 146
13685	-202	"Only PUBLIC settings are allowed for option '%1'" on page 360
13686	112	"More information required" on page 346
13687	-203	"Cannot set a temporary option for user '%1'" on page 179
13688	113	"Database option '%1' for user '%2' has an invalid setting" on page 233
13689	-205	"Integrated logins are not permitted" on page 291
13690	-206	"Integrated logins are required, standard logins are not permitted" on page 292

Sybase error code	SQL Anywhere SQLCODE	Message text
13691	-245	"Integrated login failed" on page 291
13694	-246	"Integrated logins are not supported for this database" on page 292
13695	-247	"The integrated login ID guest can only be mapped to the guest database user ID" on page 455
13696	-248	"Cannot map a login ID to the sys or public user ID" on page 172
13697	-249	"The login ID '%1' is already mapped to user ID '%2'" on page 459
13698	-313	"The login ID '%1' has not been mapped to any database user ID" on page 458
13699	-646	"Could not load the store DLL \"%1\" on page 219
13700	-647	"Could not execute store DLL (%1) entry point" on page 216
13701	-711	"Incorrect database store DLL (%1) version" on page 282
13702	-648	"Cannot create item (%1) in the specified dbspace" on page 160
13703	-93	"Class '%1' has no public field '%2'" on page 192
13704	-650	"Index type specification of '%1' is invalid" on page 286
13705	-651	"An attempt to delete database '%1' failed" on page 136
13706	-654	"The connection parameters file could not be found" on page 448
13707	-655	"Error parsing connection parameter string" on page 254
13708	-664	"Database is active" on page 231
13709	-665	"Database \"%1\" needs recovery" on page 229
13710	-668	"Cursor is restricted to FETCH NEXT operations" on page 224
13711	-669	"Method '%1' cannot be called at this time" on page 343
13712	-671	"Parameter not registered as output parameter" on page 368
13713	-674	"Statement's size limit is invalid" on page 418
13714	-683	"The cursor name '%1' already exists" on page 449

Sybase error code	SQL Anywhere SQLCODE	Message text
13715	-685	“Resource governor for '%1' exceeded” on page 389
13717	-689	“Input parameter index out of range” on page 288
13718	-691	“Could not load the backup/restore DLL \"%1\” on page 218
13719	-692	“Could not execute backup/restore DLL (%1) entry point” on page 216
13720	-697	“Error during backup/restore: %1” on page 252
13721	-700	“SQLDA fields inconsistent for a multi-row SQLDA” on page 413
13722	-709	“Computed columns are not supported in this database” on page 204
13723	-761	“Server capability name '%1' could not be found in the database” on page 403
13724	-715	“Contents of backup files are inconsistent” on page 211
13725	-716	“Backup file format is invalid” on page 147
13726	-717	“RESTORE unable to open file '%1'” on page 390
13727	-718	“RESTORE unable to write to file '%1'” on page 391
13728	-719	“RESTORE unable to start database '%1'” on page 390
13729	-720	“VALIDATE statement must refer to a base table” on page 533
13730	-727	“The optimizer was unable to construct a valid access plan” on page 464
13731	-128	“Cannot drop a user that owns tables in runtime system” on page 165
13732	-660	“Server '%1': %2” on page 402
13733	-661	“Backward scrolling cursors are not supported for remote objects” on page 148
13734	-682	“%1” on page 545
13735	-91	“Procedure '%1' terminated with unhandled exception '%2'” on page 379

Sybase error code	SQL Anywhere SQLCODE	Message text
13736	-92	"%1' is not a valid class file" on page 552
13737	-730	"Invalid JAR file" on page 304
13738	-94	"Invalid type for field reference" on page 322
13739	-164	"Namespace heap exhausted at internal function: %1" on page 349
13740	-165	"Java VM heap exhausted at internal function: %1" on page 327
13741	-649	"Field '%1' of class '%2' cannot be NULL" on page 267
13742	-652	"Could not decompress class '%1' from JAR" on page 215
13743	-653	"Cannot remove class '%1': member of JAR" on page 177
13744	-662	"Cannot serialize Java object with class '%1'" on page 179
13745	-663	"Cannot deserialize Java object" on page 164
13746	-670	"Invalid class byte code" on page 295
13747	-675	"External environment could not be started, '%1' could not be found" on page 262
13748	-704	"Cannot create an index on Java class '%1'" on page 160
13749	-710	"Invalid comparison" on page 297
13750	-734	"Cannot update or delete an all-NULL row from table '%1'" on page 186
13751	120	"%1' is an unknown option" on page 549
13752	-739	"db_init has not been called or the call to db_init failed" on page 239
13753	-740	"The communications environment could not be created" on page 448
13754	-1270	"Must own table '%1' in order to make an immediate view reference it" on page 348
13755	-742	"JDBC SAStatement batch execute abandoned" on page 329
13756	-743	"Seek absolute 0 was attempted on a JDBC SAResult-Set" on page 401

Sybase error code	SQL Anywhere SQLCODE	Message text
13757	-744	"Invalid IQ database command line option or parameter value: %1" on page 304
13758	-745	"Cannot initialize IQ memory manager: %1" on page 171
13759	-746	"Cannot allocate System V resources" on page 152
13760	-747	"Invalid JDBC resultset type" on page 305
13761	-748	"Invalid JDBC resultset concurrency" on page 305
13762	-749	"Feature not available with UltraLite" on page 266
13763	-752	"Cannot call the '%1' function on a JDBC resultset when it is positioned on an insert row" on page 154
13764	-753	"The JDBC resultset must be positioned on an insert row in order to use the '%1' function" on page 456
13765	-755	"You cannot synchronize or upgrade with uncommitted transactions" on page 543
13766	-756	"Cannot uniquely identify column '%2' of table '%1' in the current JDBC resultset" on page 182
13767	-289	"Multiple consolidated users cannot be defined" on page 347
13768	-757	"Modifications not permitted for read-only database" on page 345
13769	-758	"The database does not support the Java Virtual Machine" on page 451
13770	-759	"SQLDA data type invalid" on page 412
13771	-760	"Invalid SQL identifier" on page 319
13772	-762	"'%1' is not a public Java class, and cannot be referenced from SQL" on page 550
13773	-763	"'%1' is not a public Java reference, and cannot be referenced from SQL" on page 551
13774	-764	"Server not found and unable to autostart" on page 403
13775	-765	"Synchronization message type '%1' not found" on page 423

Sybase error code	SQL Anywhere SQLCODE	Message text
13776	119	“Unable to open backup log '%1'” on page 503
13777	–767	“Cannot find synchronization subscription with the name '%1'” on page 169
13778	–768	“Cannot subscribe to '%1'” on page 181
13779	–769	“Cannot modify synchronization entry using ALTER PUBLICATION” on page 173
13780	–770	“Cannot modify publication entry using ALTER SYNCHRONIZATION” on page 173
13781	–771	“Event '%1' not found” on page 256
13782	–772	“Event '%1' already exists” on page 255
13783	–773	“Schedule '%1' for event '%2' not found” on page 400
13784	–774	“Schedule '%1' for event '%2' already exists” on page 399
13785	146	“Event notification queue '%1' is full, notification discarded” on page 257
13786	–1268	“The materialized view cannot be changed to immediate because its definition contains an illegal construct” on page 461
13787	–777	“Cannot synchronize table '%1' since it does not have a primary key” on page 181
13788	–778	“Must include primary key for table '%1' in the synchronization” on page 348
13789	–779	“Cannot create synchronization entry for table '%1' with BLOB primary key” on page 161
13790	–780	“Cannot update primary key for table '%1' involved in a publication” on page 186
13791	–1283	“A CONTAINS query is not allowed on the view or derived table '%1'” on page 128
13792	–782	“Cannot register '%1' since another exclusive instance is running” on page 175

Sybase error code	SQL Anywhere SQLCODE	Message text
13793	-783	“Cannot register another '%1' as an exclusive application” on page 176
13794	-784	“Cannot register connection because of invalid application cookie” on page 176
13795	-785	“Cannot deregister application because of invalid cookie” on page 163
13796	-786	“Cannot deregister '%1' since active registered connection exists” on page 163
13797	-787	“Current connection is already registered to '%1' as '%2'” on page 223
13798	-788	“Another connection has already registered as '%1'” on page 140
13799	-789	“Cannot register '%1' since registration cookie exhausted” on page 175
13800	-790	“Cannot register connection to '%1' since automatic label exhausted” on page 177
13801	-791	“Invalid day of week or month '%1' for event '%2'” on page 299
13802	-792	“Invalid time '%1' for event '%2'” on page 321
13803	-793	“Invalid start date/time for event '%1'” on page 319
13804	-794	“Synchronization server failed to commit the upload” on page 428
13805	-1281	“Another connection has the row in '%1' locked” on page 140
13806	-1280	“Underflow when converting '%1'” on page 517
13807	-797	“Synchronization option '%1' contains semi-colon, equal sign, curly brace, or is null” on page 424
13808	-1279	“Operation '%1' failed for reason: '%2'” on page 361
13809	-799	“DTC transactions are not supported on this platform” on page 247
13810	-800	“Cannot commit or rollback while enlisted in a transaction” on page 156

Sybase error code	SQL Anywhere SQLCODE	Message text
13811	-801	"Cannot enlist in a transaction while already enlisted in a transaction" on page 168
13812	-802	"Cannot enlist in a transaction with uncommitted data pending" on page 168
13813	-803	"Unable to enlist transaction; DTC may be down" on page 502
13814	-804	"Unable to reenlist transaction; DTC may be down" on page 504
13815	-805	"Synchronization option '%1' not found" on page 424
13816	-806	"System event type '%1' not found" on page 431
13817	-807	"Host variables must not be used within a batch" on page 275
13818	-808	"An internal error was generated by the test harness" on page 138
13819	-809	"Synchronization option is too long" on page 425
13820	-810	"External object '%1' not found" on page 265
13821	-811	"JAR '%1' not found" on page 326
13822	-812	"The select list for the derived table '%1' has no expression to match '%2'" on page 469
13823	-817	"Too many temporary tables in connection" on page 489
13824	-818	"The external function call is incompatible" on page 454
13825	-819	"Table '%1' is part of a synchronization definition" on page 435
13826	-820	"Invalid scroll position '%1'" on page 315
13827	-821	"DbSPACE for table '%1' not found" on page 241
13828	-822	"Table '%1' is already included" on page 434
13829	-823	"Cannot handle expressions involving remote tables inside stored procedures" on page 170
13830	-824	"Illegal reference to correlation name '%1'" on page 280
13831	-825	"Previous error lost prior to RESIGNAL" on page 376

Sybase error code	SQL Anywhere SQLCODE	Message text
13832	-826	“Database upgrade not possible; RowGenerator table not owned by user dbo” on page 238
13833	-827	“Database upgrade not possible; user tables have table ids in system table range” on page 239
13834	-828	“A conflict with the dbmlsync download phase was detected” on page 128
13835	-829	“TLS handshake failure” on page 481
13836	-830	“Alias '%1' is not unique” on page 134
13837	-831	“Definition for alias '%1' must appear before its first reference” on page 243
13838	-832	“Connection error: %1” on page 207
13839	-833	“Row in table '%1' was modified or deleted in BEFORE trigger” on page 396
13840	-834	“Column '%1' not found in table '%2'” on page 200
13841	-835	“Event '%1' in use” on page 256
13842	-836	“Procedure '%1' is no longer valid” on page 378
13843	-837	“Trigger or foreign key for table '%1' is no longer valid” on page 494
13844	-838	“TLS initialization on server failed” on page 482
13845	-839	“Download failed because of conflicts with existing rows” on page 246
13846	-1278	“Operation is not allowed” on page 363
13847	-841	“The JDK version in '%1' does not match '%2'” on page 456
13848	-842	“JDK '%1' is not a supported JDK” on page 329
13849	-843	“Cannot find synchronization user with the name '%1'” on page 170
13850	-844	“Cannot find synchronization definition with the name '%1'” on page 169

Sybase error code	SQL Anywhere SQLCODE	Message text
13851	-845	“Owner '%1' used in a qualified column reference does not match correlation name '%2’” on page 365
13852	-846	“SET clause for column '%1' used incorrectly” on page 408
13853	-847	“Java SecurityManager class not found: %1” on page 327
13854	-848	“Exception occurred while loading Java SecurityManager” on page 261
13855	-851	“Decryption error: %1” on page 242
13856	-852	“Table name '%1' is ambiguous” on page 439
13857	121	“Cursor option values changed” on page 225
13858	-855	“Trigger name '%1' is ambiguous” on page 494
13859	-856	“Invalid sqllen field in SQLDA” on page 319
13860	-857	“Synchronization failed due to an error on the server: %1” on page 422
13861	-858	“CREATE/DROP STATISTICS statement cannot refer to virtual tables” on page 222
13862	-1277	“Parameter '%1' cannot be null” on page 366
13863	-1276	“Configuration cannot not be modified while in use” on page 205
13864	-860	“At least one of the specified dbspaces was not calibrated” on page 142
13865	-861	“Aggregated expression '%1' contains multiple columns of which one or more are outer references” on page 133
13866	-862	“The aggregate expression '%1' must appear in either the select list or a HAVING clause subquery” on page 446
13867	-863	“Grouped query contains more than one distinct aggregate function” on page 274
13868	-303	“Disk write failure '%1' -- transaction rolled back” on page 246

Sybase error code	SQL Anywhere SQLCODE	Message text
13869	-864	"Statement contains an illegal usage of the NUMBER(*) function" on page 415
13870	-866	"%1 returned a result set with a different schema than expected" on page 546
13871	-867	"Cannot change synchronization user_name when status of the last upload is unknown" on page 154
13872	-868	"'%1' is an unknown character set encoding label" on page 548
13873	-869	"Database server cannot convert data from/to character set '%1'" on page 235
13874	-870	"Cannot convert between requested character set '%1' and database character set '%2'" on page 158
13875	-871	"The database needs to be restarted for this Java related command" on page 452
13876	-872	"%1 does not return a result set" on page 545
13877	-873	"%1 returned multiple result sets" on page 546
13878	-686	"Insufficient cache to start Java Virtual Machine" on page 290
13879	-688	"Strongly-encrypted database files are not supported in the runtime server" on page 419
13880	-874	"Column must be named: %1" on page 201
13881	-1275	"Invalid domain '%1'" on page 300
13882	-876	"Client out of memory" on page 196
13883	122	"The result returned is non-deterministic" on page 468
13884	-1274	"Index '%1' has no columns" on page 284
13885	-184	"Column '%1' in table '%2' cannot be NULL. The invalid data was supplied to LOAD TABLE in a data file on line %3" on page 199
13886	124	"Invalid data conversion: NULL was inserted for column '%1' on row %2" on page 298

Sybase error code	SQL Anywhere SQLCODE	Message text
13887	-162	"Cannot convert %1 to a %2. The bad value was supplied for column '%3' on row %4 of the data file" on page 157
13888	-877	"SETUSER not allowed in procedures, triggers, events, or batch-es" on page 408
13889	-878	"Index '%1' can not be clustered" on page 283
13890	-879	"An invalid multi-byte input character was encountered when converting from %1 to %2" on page 138
13891	-1273	"Table '%1' has no columns" on page 433
13892	125	"An invalid multi-byte input character was encountered when converting from %1 to %2" on page 139
13893	-1272	"Synchronization is already in progress" on page 423
13894	-881	"Character substitution was required when converting from %1 to %2" on page 191
13895	-1215	"External library '%1' not loaded" on page 264
13896	127	"Character substitution occurred when converting from %1 to %2" on page 190
13897	-1214	"External library '%1' is in use" on page 263
13898	-883	"Character conversion error or warning report is not available when the single-byte converter is used" on page 189
13899	-1271	"Synchronization download failed to complete" on page 422
13959	-974	"File I/O failed for '%1'" on page 268
13960	-975	"Incorrect volume ID for '%1'" on page 283
16846	-840	"Incorrect or missing encryption key" on page 282
36007	-628	"Division by zero" on page 246
1333336	-1177	"No plan. HTML_PLAN function is not supported for this type of statement or database" on page 354

SQL Anywhere error messages sorted by message text (A-C)

A conflict with the dbmlsync download phase was detected

Error constant	SQLE_RECORDING_CONFLICT_DETECTED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	11
SQLCODE	-828
SQLSTATE	WW027
Sybase error code	13834

Probable cause

Dbmlsync uses this error to detect download phase conflicts with rows modified by other connections.

A CONTAINS query is not allowed on the view or derived table '%1'

Error constant	SQLE_TEXT_INVALID_VIEW_FOR_CONTAINS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the view or derived table that cannot be queried with CONTAINS.
Severity	16
SQLCODE	-1283
SQLSTATE	WT020
Sybase error code	13791

Probable cause

A view or derived table can only be queried using CONTAINS if it does not use TOP, FIRST, DISTINCT, GROUP BY, or FOR XML. In addition, the list of columns to search must all come from a single base table

in the FROM clause of the view. They cannot come from multiple tables, or from another view or derived table in the FROM clause.

A dbspace has reached its maximum file size

Error constant	SQLE_DBSpace_FULL
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-604
SQLSTATE	04W07
Sybase error code	5006

Probable cause

A dbspace has grown to its maximum number of disk pages, which is usually limited by the maximum operating system file size. This is a fatal error.

A log is required for IQ databases

Error constant	SQLE_IQ_LOG_REQUIRED
ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	-933
SQLSTATE	0AQ48
Sybase error code	102

Probable cause

IQ databases require the use of a transaction log file.

A row cannot be stored because it exceeds the database page size

Error constant	SQLE_ROW_EXCEEDS_PAGE_SIZE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1117
SQLSTATE	WW083
Sybase error code	13396

Probable cause

You attempted to insert or update a row which is too large to be stored on a database page. For UltraLite, with the exception of BLOB columns, a row must fit entirely on a single database page. Larger page sizes may be used to accommodate larger rows.

A row was dropped because it could not be converted to the new schema format

Error constant	SQLE_ROW_DROPPED_DURING_SCHEMA_UPGRADE
ODBC 2 State	OK
ODBC 3 State	OK
Severity	10
SQLCODE	130
SQLSTATE	01W21
Sybase error code	13588

Probable cause

A row that was valid in the old schema is no longer valid. This could be because a column domain changed and the old value can not be cast to the new domain. Rows are also dropped if a uniqueness or foreign key constraint cannot be satisfied.

A schema upgrade is not currently allowed

Error constant	SQLE_SCHEMA_UPGRADE_NOT_ALLOWED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-953
SQLSTATE	WW033
Sybase error code	13535

Probable cause

A schema upgrade cannot proceed because of concurrent use of the database. For example, all cursors must be closed before a schema upgrade can occur.

A thread used internally could not be started

Error constant	SQLE_THREAD_START_FAILURE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	19
SQLCODE	-626
SQLSTATE	WW011
Sybase error code	13681

Probable cause

This is a Windows 95 specific error. An operating system thread could not be started that is required to execute external functions.

A tracing connection is already active

Error constant	SQLE_TRACING_ALREADY_ATTACHED
----------------	-------------------------------

ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1098
SQLSTATE	08W96
Sybase error code	13417

Probable cause

This database is already participating in a tracing connection, either as the sender (the database being traced) or as the receiver (the tracing database). A database can only send or receive one stream of tracing data at a time.

A transaction log file is required for auditing

Error constant	SQL_E_AUDITING_WITHOUT_TRANSACTION_LOG
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-913
SQLSTATE	42W91
Sybase error code	13571

Probable cause

This database is running without a transaction log file. You must use the Transaction Log utility (dblog) to create a transaction log file before using auditing.

A user name must be specified if AUTHORIZATION is Off

Error constant	SQL_E_SERVICE_REQUIRES_USER_NAME
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Severity	16
SQLCODE	–918
SQLSTATE	42W96
Sybase error code	13566

Probable cause

A valid user name must be specified if AUTHORIZATION is Off.

A workload capture (%1) is already in progress

Error constant	SQLE_WORKLOAD_CAPTURE_ALREADY_EXISTS
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	The name of the workload capture that is already in progress.
Severity	16
SQLCODE	–942
SQLSTATE	WW029
Sybase error code	13546

Probable cause

You have tried to initiate a workload capture when one is already in progress. You need to wait for the other capture to complete.

Aggregated expression '%1' contains multiple columns of which one or more are outer references

Error constant	SQLE_MULTIPLE_AGGREGATE_COLUMNS
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	The aggregated expression in error.

Severity	15
SQLCODE	–861
SQLSTATE	42W68
Sybase error code	13865

Probable cause

A subselect within the nested query contains an aggregate function whose parameters include an outer reference. In such cases, the outer reference must be the only column referenced in the expression.

Alias '%1' is not unique

Error constant	SQLE_ALIAS_NOT_UNIQUE
ODBC 2 State	37000
ODBC 3 State	ERROR
Parameter 1	Name of the alias.
Severity	15
SQLCODE	–830
SQLSTATE	42W60
Sybase error code	13836

Probable cause

The same alias is used more than once in a select list.

All column reference arguments must refer to the same table

Error constant	SQLE_TEXT_TOO_MANY_TABLE_REFERENCES
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	–1157

SQLSTATE	WT002
Sybase error code	13356

Probable cause

All column references in a CONTAINS query must refer to the same table.

All threads are blocked

Error constant	SQLE_THREAD_DEADLOCK
ODBC 2 State	40001
ODBC 3 State	40001
Severity	13
SQLCODE	-307
SQLSTATE	40W06
Sybase error code	1205

Probable cause

You attempted to read or write a row and it is locked by another user. Also, all other threads (see the -gn server option) are blocked waiting for a lock to be released. This is a deadlock situation and your transaction has been chosen as the one to rollback.

ALTER clause conflict

Error constant	SQLE_ALTER_CLAUSE_CONFLICT
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	15
SQLCODE	-125
SQLSTATE	53W01
Sybase error code	13623

Probable cause

A primary key clause, foreign key clause, or a uniqueness clause must be the only clause of an ALTER TABLE statement.

An attempt to decrypt database '%1' failed

Error constant	SQLE_DECRYPT_DATABASE_FAILED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the database that could not be decrypted.
Severity	16
SQLCODE	-1244
SQLSTATE	WW119
Sybase error code	13270

Probable cause

Your attempt to decrypt a database file failed.

An attempt to delete database '%1' failed

Error constant	SQLE_DROP_DATABASE_FAILED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the database that could not be deleted.
Severity	16
SQLCODE	-651
SQLSTATE	WW017
Sybase error code	13705

Probable cause

Your attempt to delete a database file failed. You may have attempted to delete a running database. Some parts of the database may have been deleted before failure.

An attempt to encrypt database '%1' failed

Error constant	SQLE_ENCRYPT_DATABASE_FAILED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the database that could not be encrypted.
Severity	16
SQLCODE	-1243
SQLSTATE	WW118
Sybase error code	13271

Probable cause

Your attempt to encrypt a database file failed.

An internal error occurred in a '%1'

Error constant	SQLE_JDBC_OBJ_INTERNAL_ERR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Java class of the object in error.
Severity	20
SQLCODE	-695
SQLSTATE	WJ009
Sybase error code	13604

Probable cause

This is an internal JDBC object error. If it can be reproduced, it should be reported to iAnywhere.

An internal error occurred in a '%1'

Error constant	SQLE_JNAT_OBJ_INTERNAL_ERR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Java class of the object in error.
Severity	20
SQLCODE	-713
SQLSTATE	WJ013
Sybase error code	13608

Probable cause

This is an internal native Java object error. If it can be reproduced, it should be reported to iAnywhere.

An internal error was generated by the test harness

Error constant	SQLE_TEST_HARNESS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	18
SQLCODE	-808
SQLSTATE	WW025
Sybase error code	13818

Probable cause

An internal error was generated by the test harness.

An invalid multi-byte input character was encountered when converting from %1 to %2

Error constant	SQLE_ILLEGAL_MULTIBYTE_ERROR
----------------	------------------------------

ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The character set of the input string.
Parameter 2	The character set of the output string.
Severity	16
SQLCODE	-879
SQLSTATE	WC003
Sybase error code	13890

Probable cause

While the server was performing character set conversion on an input string, an invalid multi-byte character was encountered. The operation was aborted.

An invalid multi-byte input character was encountered when converting from %1 to %2

Error constant	SQLE_ILLEGAL_MULTIBYTE_WARNING
ODBC 2 State	01000
ODBC 3 State	01000
Parameter 1	The character set of the input string.
Parameter 2	The character set of the output string.
Severity	10
SQLCODE	125
SQLSTATE	01WC1
Sybase error code	13892

Probable cause

While the server was performing character set conversion on an input string, an invalid multi-byte character was encountered. The illegal character was directly copied without conversion. Data following the illegal character may be misinterpreted. See `on_charset_conversion_failure` option.

Another connection has already registered as '%1'

Error constant	SQLE_NOT_UNIQUE_CONN_REG_LABEL
ODBC 2 State	42000
ODBC 3 State	42S02
Parameter 1	Registered connection label.
Severity	16
SQLCODE	-788
SQLSTATE	5RW27
Sybase error code	13798

Probable cause

You attempted to register a connection with a label already in use for the same application.

Another connection has the row in '%1' locked

Error constant	SQLE_ROW_LOCKED
ODBC 2 State	40001
ODBC 3 State	40001
Parameter 1	Table that generates the error.
Severity	21
SQLCODE	-1281
SQLSTATE	42W80
Sybase error code	13805

Probable cause

You attempted modify or delete a row that is locked by another connection. The row will be unlocked once that connection commits or rolls back.

Argument %1 of procedure '%2' cannot be NULL

Error constant	SQLE_ARGUMENT_CANNOT_BE_NULL
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The argument number that cannot be NULL.
Parameter 2	The name of the procedure that cannot receive the NULL parameter.
Severity	16
SQLCODE	-90
SQLSTATE	WP000
Sybase error code	409

Probable cause

You passed a NULL value to a procedure expecting a scalar argument. For example, a Java procedure that has an 'int' argument cannot receive a NULL value.

Argument \"%1\" must be a column reference

Error constant	SQLE_TEXT_BAD_COLUMN_REFERENCE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The argument number.
Severity	16
SQLCODE	-1156
SQLSTATE	WT001
Sybase error code	13357

Probable cause

The CONTAINS argument must be a column reference.

Argument to GROUPING aggregate must be a grouping column in the GROUP BY clause

Error constant	SQLE_INVALID_GROUPING_AGGREGATE
ODBC 2 State	37000
ODBC 3 State	42000
Severity	15
SQLCODE	-962
SQLSTATE	42WA7
Sybase error code	13527

Probable cause

Only a grouping column is permitted as an argument to the GROUPING aggregate function. An argument that contains anything other than a single grouping column expression will not be accepted.

At least one of the specified dbspaces was not calibrated

Error constant	SQLE_DBSPACE_NOT_CALIBRATED
ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	-860
SQLSTATE	WW028
Sybase error code	13864

Probable cause

You attempted to calibrate a dbspace that was not open or was too small.

ATTACH TRACING could not connect to the tracing database

Error constant	SQLE_ATTACH_TRACING_FAILED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1097
SQLSTATE	08W95
Sybase error code	13418

Probable cause

A connection to the tracing database could not be established. Check your connection string and verify that other clients can connect. Note that if you are trying to attach tracing to another server, it is possible that the connection is being blocked by a firewall.

ATTACH TRACING TO LOCAL DATABASE cannot be used with a strongly encrypted database

Error constant	SQLE_NO_LOCAL_CONNECTIONS_TO_ENCRYPTED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1088
SQLSTATE	WW069
Sybase error code	13426

Probable cause

The local database is strongly encrypted, so you cannot use the LOCAL DATABASE clause of the ATTACH TRACING statement. You must specify a connection string with the encryption key for the database.

Attempt to start a second snapshot in a transaction

Error constant	SQLE_SNAPSHOT_ALREADY_STARTED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1232
SQLSTATE	42WC9
Sybase error code	13285

Probable cause

A transaction tried to start a snapshot (e.g., see BEGIN SNAPSHOT statement) while another snapshot was already active.

Attempt to use snapshot isolation in a non-snapshot transaction

Error constant	SQLE_NON_SNAPSHOT_TRANSACTION
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1065
SQLSTATE	42WBB
Sybase error code	13449

Probable cause

A transaction tried to use snapshot isolation but did not begin with snapshot isolation.

Attempted two active database requests

Error constant	SQLE_DOUBLE_REQUEST
----------------	---------------------

ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-298
SQLSTATE	42W22
Sybase error code	13663

Probable cause

In embedded SQL, you attempted to submit a database request while you have another request in progress. You should either use a separate SQLCA and connection for each thread accessing the database, or use thread synchronization calls to ensure that a SQLCA is only accessed by one thread at a time.

Authentication failed

Error constant	SQLE_AUTHENTICATION_FAILED
ODBC 2 State	08001
ODBC 3 State	08001
Severity	16
SQLCODE	-218
SQLSTATE	08W48
Sybase error code	13621

Probable cause

You set the database_authentication or connection_authentication option incorrectly.

Authentication violation

Error constant	SQLE_AUTHENTICATION_VIOLATION
ODBC 2 State	08001
ODBC 3 State	08001

Severity	16
SQLCODE	-98
SQLSTATE	08W21
Sybase error code	13620

Probable cause

You attempted to connect to a server that has been authenticated for exclusive use with a specific application.

Automatic database upgrade applied

Error constant	SQLE_DATABASE_UPGRADE_WARNING
ODBC 2 State	OK
ODBC 3 State	OK
Severity	10
SQLCODE	149
SQLSTATE	WW234
Sybase error code	13684

Probable cause

The database is from an older version of the software. Automatic database upgrade occurs during startup. Subsequently the database can no longer be opened with the older version of the software.

BACKUP clause '%1' conflicts with '%2'

Error constant	SQLE_INVALID_BACKUP_STATEMENT
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	First BACKUP clause.
Parameter 2	Second BACKUP clause.
Severity	16

SQLCODE	-1057
SQLSTATE	WB016
Sybase error code	13456

Probable cause

Clauses specified in the BACKUP STATEMENT are mutually exclusive.

Backup file '%1' already exists

Error constant	SQLE_BACKUP_FILE_EXISTS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the file.
Severity	16
SQLCODE	-967
SQLSTATE	WB012
Sybase error code	13523

Probable cause

A file that would normally be created by this BACKUP statement already exists.

Backup file format is invalid

Error constant	SQLE_RESTORE_INVALID_FORMAT
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	21
SQLCODE	-716
SQLSTATE	WB007

Sybase error code	13725
-------------------	-------

Probable cause

The format of an archive file to be used during a RESTORE is invalid.

Backup is unable to open database file '%1'

Error constant	SQLE_BACKUP_UNABLE_TO_OPEN_FILE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the file.
Severity	16
SQLCODE	-1079
SQLSTATE	WB017
Sybase error code	13435

Probable cause

The database file can not be opened by the backup. It may have been erased or otherwise corrupted.

Backward scrolling cursors are not supported for remote objects

Error constant	SQLE_OMNI_BACKWARDS_CURSOR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-661
SQLSTATE	WO006
Sybase error code	13733

Probable cause

Backward scrolling cursors are not supported for remote objects. Use forward scrolling cursors only.

Calling functions outside the database server is not supported

Error constant	SQLE_EXTERNAL_CALLS_NOT_SUPPORTED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-617
SQLSTATE	WW003
Sybase error code	13674

Probable cause

You attempted to call a stored procedure that, in turn, calls a function in a dynamically loaded module. The operating system on which this stored procedure was called does not support such an action.

Can only describe a SELECT statement

Error constant	SQLE_DESCRIBE_NONSELECT
ODBC 2 State	OK
ODBC 3 State	OK
Severity	16
SQLCODE	-160
SQLSTATE	07005
Sybase error code	3819

Probable cause

In the C language interface, you attempted to describe the select list of a statement other than a SELECT statement. In UltraLite this error can result from trying to retrieve the schema of any statement other than a SELECT.

Cannot access a table that is part of a text index

Error constant	SQLE_TEXT_CANNOT_USE_TEXT_INDEX
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1169
SQLSTATE	WT013
Sybase error code	13344

Probable cause

It is not possible to directly manipulate tables created as part of a text index.

Cannot access file '%1' -- %2

Error constant	SQLE_CANNOT_ACCESS_FILE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The file name.
Parameter 2	The cause of the error.
Severity	19
SQLCODE	-602
SQLSTATE	WL002
Sybase error code	13670

Probable cause

A file cannot be accessed. For example, a file referenced by LOAD TABLE does not exist or cannot be read. The message will contain the reason for the error.

Cannot access instance member through a class

Error constant	SQLE_CANNOT_ACCESS_INSTANCE_MEMBER
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-701
SQLSTATE	WJ011
Sybase error code	13607

Probable cause

Non-static fields or methods must be accessed through an object instance.

Cannot access schema file '%1'

Error constant	SQLE_CANNOT_ACCESS_SCHEMA_FILE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the file or indication that no name was given.
Severity	16
SQLCODE	-951
SQLSTATE	WW031
Sybase error code	13537

Probable cause

UltraLite requires a schema file to perform the current operation. Either no schema file was specified or the one specified was not accessible or was corrupt.

Cannot add a comment to a table declared as LOCAL TEMPORARY

Error constant	SQLLE_COMMENT_NOT_ALLOWED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	11
SQLCODE	-1042
SQLSTATE	WW065
Sybase error code	13469

Probable cause

You attempted to add a comment to a table that has been declared as LOCAL TEMPORARY. This is not allowed.

Cannot allocate System V resources

Error constant	SQLLE_IQ_SYSTEM_V_FAILURE
ODBC 2 State	08001
ODBC 3 State	08001
Severity	18
SQLCODE	-746
SQLSTATE	08W53
Sybase error code	13759

Probable cause

IQ was unable to allocate System V resources. Delete unused System V semaphores and shared memory segments or increase operating system configuration values for these resources.

Cannot alter a column in an index

Error constant	SQLLE_COLUMN_IN_INDEX
----------------	-----------------------

ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-127
SQLSTATE	53W05
Sybase error code	4939

Probable cause

You may have attempted to delete or modify the definition of a column that is part of a primary or foreign key. You may have attempted to delete a column that has an index on it. In this case, DROP the index or key, perform the ALTER statement, and then add the index or key again.

Cannot alter or drop a text configuration referenced by a text index

Error constant	SQLE_TEXT_CANNOT_ALTER_CONFIG
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1168
SQLSTATE	WT012
Sybase error code	13345

Probable cause

It is not possible to alter or drop a text configuration referenced by a populated text index or currently being used by a text procedure. Either copy the configuration and alter the copy, or close all cursors on text procedures and truncate all indexes that use the configuration.

Cannot append when using compression or encryption

Error constant	SQLE_UNLOAD_CANNOT_APPEND
----------------	---------------------------

ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1187
SQLSTATE	WL012
Sybase error code	13328

Probable cause

The UNLOAD statement cannot append to a file when using compression or encryption. Either the compressed or encrypted keywords were specified, or the file being appended to is compressed or encrypted.

Cannot call the '%1' function on a JDBC resultset when it is positioned on an insert row

Error constant	SQL_E_JDBC_INVALID_OPER_ON_INSERT_ROW
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the resultset function being called.
Severity	16
SQLCODE	-752
SQLSTATE	WJ019
Sybase error code	13763

Probable cause

Some resultset functions such as updateRow and deleteRow are invalid when the cursor of the resultset is positioned at the insert row.

Cannot change synchronization user_name when status of the last upload is unknown

Error constant	SQL_E_CANNOT_CHANGE_USER_NAME
----------------	-------------------------------

ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	-867
SQLSTATE	0AW13
Sybase error code	13871

Probable cause

The MobiLink server uses the user_name to track synchronizations. If the status of the previous upload is unknown then you must resolve this condition before changing the user.

Cannot change the MobiLink remote id when the status of the last upload is unknown

Error constant	SQLE_CANNOT_CHANGE_ML_REMOTE_ID
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1118
SQLSTATE	0AW17
Sybase error code	13395

Probable cause

The MobiLink server uses the remote id to track synchronization progress. If the status of the previous upload is unknown then you must resolve this condition before changing the remote id.

Cannot close a remote JDBC connection that is not the current connection

Error constant	SQLE_CANNOT_CLOSE_JDBC_CONNECTION
ODBC 2 State	ERROR

ODBC 3 State	ERROR
Severity	16
SQLCODE	-998
SQLSTATE	WO026
Sybase error code	711

Probable cause

When attempting to close a remote JDBC connection, the specified connection must be the local connection.

Cannot commit or rollback while enlisted in a transaction

Error constant	SQL_E_CANNOT_COMMIT_OR_ROLLBACK_WHILE_ENLISTED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-800
SQLSTATE	55W09
Sybase error code	13810

Probable cause

You tried to explicitly commit or rollback on a connection that is enlisted in a transaction. You must use the Commit/Abort protocol of the transaction instead.

Cannot connect to mirror server. Use server name '%1' to find the primary server

Error constant	SQL_E_CONNECTED_TO_MIRROR_SERVER
ODBC 2 State	08001
ODBC 3 State	08001
Parameter 1	The server name for the mirroring system.

Severity	11
SQLCODE	-1039
SQLSTATE	08W91
Sybase error code	13472

Probable cause

You have attempted to connect to the mirror server in a mirroring system. You should change your connection string or DSN to use the server name for the mirroring system.

Cannot convert %1 to a %2

Error constant	SQLE_CONVERSION_ERROR
ODBC 2 State	07006
ODBC 3 State	07006
Parameter 1	The value that could not be converted.
Parameter 2	The name of the type for the conversion.
Severity	16
SQLCODE	-157
SQLSTATE	53018
Sybase error code	257

Probable cause

An error occurred while trying to convert a value to another data type.

Cannot convert %1 to a %2. The bad value was supplied for column '%3' on row %4 of the data file

Error constant	SQLE_CONVERSION_ERROR_LOAD_TABLE
ODBC 2 State	07006
ODBC 3 State	07006

Parameter 1	Value that could not be converted.
Parameter 2	Destination data type.
Parameter 3	Name of the column where the value was to be inserted.
Parameter 4	Line number of the data file where the invalid data occurred.
Severity	16
SQLCODE	-162
SQLSTATE	53017
Sybase error code	13887

Probable cause

The data file supplied to LOAD TABLE contains a value that cannot be converted to the required data type.

Cannot convert between requested character set '%1' and database character set '%2'

Error constant	SQL_E_FAILED_TO_START_CONVERTER
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the requested character set encoding.
Parameter 2	The name of the database character set encoding.
Severity	16
SQLCODE	-870
SQLSTATE	WC002
Sybase error code	13874

Probable cause

The server is unable to convert between the connection character set that was specified and the database character set. This could happen when the dbicu and dbicudt DLLs are not installed.

Cannot convert between requested character sets '%1' and '%2'

Error constant	SQLE_FAILED_TO_START_CONVERTER_2_CHARSETS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the first requested character set encoding.
Parameter 2	The name of the second requested character set encoding.
Severity	16
SQLCODE	-891
SQLSTATE	WC008
Sybase error code	13592

Probable cause

The server is unable to convert between the two specified character sets. This could happen when the dbicu and dbicudt DLLs are not installed.

Cannot create a materialized view because option '%1' has an inappropriate setting

Error constant	SQLE_CANNOT_CREATE_MATVIEW
ODBC 2 State	42000
ODBC 3 State	ERROR
Parameter 1	Name of the option with the incorrect setting.
Severity	14
SQLCODE	-1051
SQLSTATE	42WB6
Sybase error code	13460

Probable cause

You attempted to create a materialized view, but one of the database options is currently set to a value not permitted while creating a materialized view.

Cannot create an index on Java class '%1'

Error constant	SQLE_CANNOT_INDEX_ON_JAVA_CLASS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the class.
Severity	16
SQLCODE	-704
SQLSTATE	WW022
Sybase error code	13748

Probable cause

An operation requiring an index was attempted in which an attempt was made to create an index on a Java class type.

Cannot create item (%1) in the specified dbspace

Error constant	SQLE_INVALID_DBSPACE_FOR_CREATE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the item that could not be created.
Severity	16
SQLCODE	-648
SQLSTATE	08W36
Sybase error code	13702

Probable cause

The specified dbspace is invalid. For example, an index must be created in a dbspace of the same type as the underlying table.

Cannot create synchronization entry for table '%1' with BLOB primary key

Error constant	SQLE_BLOB_IN_SYNC_TABLE_PK
ODBC 2 State	42000
ODBC 3 State	42S02
Parameter 1	Name of the table.
Severity	16
SQLCODE	-779
SQLSTATE	5RW18
Sybase error code	13789

Probable cause

You attempted to create a synchronization entry on a table with a BLOB primary key.

Cannot create text configuration '%1' because option '%2' has an inappropriate setting

Error constant	SQLE_TEXT_BAD_OPTION
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the configuration.
Parameter 2	Name of the option with the incorrect setting.
Severity	16
SQLCODE	-1174
SQLSTATE	WT014

Sybase error code	13339
-------------------	-------

Probable cause

You attempted an operation that needs to create or alter the database options settings for a text configuration, but one of the options is currently set to a value not permitted for a text configuration.

Cannot delete or rename a column referenced in a trigger definition

Error constant	SQLE_COLUMN_IN_TRIGGER
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	15
SQLCODE	-269
SQLSTATE	53W06
Sybase error code	102

Probable cause

You attempted to delete or rename a column referenced in a trigger definition. Drop the trigger before performing the ALTER statement.

Cannot delete PUBLIC option '%1' since user settings exist

Error constant	SQLE_UNSET_PUBLIC_ID
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Name of the option.
Severity	15
SQLCODE	-896
SQLSTATE	42W82
Sybase error code	13587

Probable cause

You tried to delete a PUBLIC option, but there are user settings for the same option. The user settings must be deleted before the PUBLIC option is deleted.

Cannot deregister '%1' since active registered connection exists

Error constant	SQLE_DEREG_APP_IN_USE
ODBC 2 State	42000
ODBC 3 State	42S02
Parameter 1	Name of the application.
Severity	16
SQLCODE	-786
SQLSTATE	5RW25
Sybase error code	13796

Probable cause

You attempted to deregister an application while there are still active connections registered to that application.

Cannot deregister application because of invalid cookie

Error constant	SQLE_DEREG_APP_NOT_FOUND
ODBC 2 State	42000
ODBC 3 State	42S02
Severity	16
SQLCODE	-785
SQLSTATE	5RW24
Sybase error code	13795

Probable cause

The application has not been registered successfully or it was previously deregistered.

Cannot deserialize Java object

Error constant	SQLE_JAVA_DESERIALIZATION_ERROR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	–663
SQLSTATE	WW018
Sybase error code	13745

Probable cause

The persistent Java object cannot be read from the database column. Possibly, the class of the object has been removed or modified.

Cannot drop a user that owns messages or data types

Error constant	SQLE_USER_OWNS_MESSAGES_OR_DATATYPES
ODBC 2 State	42000
ODBC 3 State	42000
Severity	16
SQLCODE	–614
SQLSTATE	55W05
Sybase error code	13632

Probable cause

You attempted to drop a user that is the creator of a message or user-defined data type. The message or user-defined data type must be dropped first.

Cannot drop a user that owns objects involved in replication

Error constant	SQLE_USER_OWNS_REPLICATED_OBJECTS
ODBC 2 State	42000
ODBC 3 State	42000
Severity	16
SQLCODE	-731
SQLSTATE	55W06
Sybase error code	13633

Probable cause

You attempted to drop a user that is the creator of a database object involved in replication. For example, the user may own a table that is part of a publication.

Cannot drop a user that owns procedures in runtime server

Error constant	SQLE_USER_OWNS_PROCEDURES
ODBC 2 State	42000
ODBC 3 State	42000
Severity	16
SQLCODE	-270
SQLSTATE	55W04
Sybase error code	13641

Probable cause

You attempted to drop a user that owns procedures while using the runtime server. This operation would result in dropping procedures. The runtime server cannot drop procedures. Use the full server.

Cannot drop a user that owns tables in runtime system

Error constant	SQLE_USER_OWNS_TABLES
----------------	-----------------------

ODBC 2 State	42000
ODBC 3 State	42000
Severity	16
SQLCODE	-128
SQLSTATE	55W03
Sybase error code	13731

Probable cause

You attempted to drop a user that owns tables while running the runtime server. This operation would result in dropping tables. The runtime server cannot drop tables. Use the full server.

Cannot drop a user that owns text configurations

Error constant	SQL_E_USER_OWNS_TEXT_CONFIG
ODBC 2 State	42000
ODBC 3 State	42000
Severity	16
SQLCODE	-1167
SQLSTATE	55W12
Sybase error code	13346

Probable cause

You attempted to drop a user that is the creator of a text configuration. The text configuration must be dropped first.

Cannot drop last unique index of an immediate materialized view

Error constant	SQL_E_DELETE_UPDATABLE_MATVIEW_INDEX_ERR
ODBC 2 State	42000
ODBC 3 State	ERROR

Severity	16
SQLCODE	-1184
SQLSTATE	55W21
Sybase error code	13331

Probable cause

You attempted to drop the last unique index on non-nullable columns of an immediate materialized view. Immediate materialized view needs at least one unique index on non-nullable columns in order to be valid.

Cannot drop or modify object '%1' because at least one other object (%2 '%3') depends upon it

Error constant	SQLE_OBJECT_HAS_DEPENDENTS
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	The name of the object that could not be dropped or modified.
Parameter 2	The type of the object that depends on the object that could not be dropped or modified.
Parameter 3	The name of the object that depends on the object that could not be dropped or modified.
Severity	16
SQLCODE	-1037
SQLSTATE	55W16
Sybase error code	13474

Probable cause

You attempted to drop or modify an object, such as a table or a column, that is used by another object, such as a materialized view, that cannot be automatically invalidated. The dependent object must be disabled or dropped before a drop or modification can be permitted.

Cannot enlist in a transaction while already enlisted in a transaction

Error constant	SQLE_CANNOT_ENLIST_WHILE_ALREADY_ENLISTED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-801
SQLSTATE	55W10
Sybase error code	13811

Probable cause

You tried to enlist a second transaction on a connection that is already enlisted in a transaction.

Cannot enlist in a transaction with uncommitted data pending

Error constant	SQLE_CANNOT_ENLIST_WITH_UNCOMMITTED_DATA
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-802
SQLSTATE	55W11
Sybase error code	13812

Probable cause

You tried to enlist a transaction on a connection that has pending uncommitted data.

Cannot find index named '%1'

Error constant	SQLE_INDEX_NOT_FOUND
----------------	----------------------

ODBC 2 State	S0012
ODBC 3 State	42S12
Parameter 1	Name of the index that cannot be found.
Severity	16
SQLCODE	-183
SQLSTATE	52W03
Sybase error code	6226

Probable cause

You attempted to perform an operation using an index that does not exist. Check for spelling errors. Check whether the index name must be qualified with a user ID.

Cannot find synchronization definition with the name '%1'

Error constant	SQLE_SYNC_DEFINITION_NOT_FOUND
ODBC 2 State	S0002
ODBC 3 State	42S02
Parameter 1	Name of the synchronization definition.
Severity	16
SQLCODE	-844
SQLSTATE	5RW39
Sybase error code	13850

Probable cause

You misspelled the name of a synchronization definition or you did not qualify it correctly with a user name.

Cannot find synchronization subscription with the name '%1'

Error constant	SQLE_SYNCHRONIZATION_NOT_FOUND
----------------	--------------------------------

ODBC 2 State	S0002
ODBC 3 State	42S02
Parameter 1	Name of the subscription.
Severity	16
SQLCODE	-767
SQLSTATE	5RW12
Sybase error code	13777

Probable cause

You misspelled the name of a synchronization subscription or you did not qualify it correctly with a user name.

Cannot find synchronization user with the name '%1'

Error constant	SQLE_SYNC_SITE_NOT_FOUND
ODBC 2 State	S0002
ODBC 3 State	42S02
Parameter 1	Name of the synchronization user.
Severity	16
SQLCODE	-843
SQLSTATE	5RW37
Sybase error code	13849

Probable cause

You misspelled the name of a synchronization site or you did not qualify it correctly with a user name.

Cannot handle expressions involving remote tables inside stored procedures

Error constant	SQLE_OMNI_EXPRESSION_IN_PROC
----------------	------------------------------

ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	12
SQLCODE	-823
SQLSTATE	WO023
Sybase error code	13829

Probable cause

The server encountered an expression involving remote tables inside a stored procedure. The expression was too complicated to process.

Cannot initialize IQ memory manager: %1

Error constant	SQLE_IQ_MEMORY_MANAGER_FAILED
ODBC 2 State	08001
ODBC 3 State	08001
Parameter 1	A message describing the error that occurred.
Severity	18
SQLCODE	-745
SQLSTATE	08W52
Sybase error code	13758

Probable cause

System V shared memory was requested but could not be allocated.

Cannot insert or update computed column '%1'

Error constant	SQLE_COMPUTED_COLUMN_WRITE_ATTEMPTED
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Parameter 1	The name of the column.
Severity	16
SQLCODE	-703
SQLSTATE	WW023
Sybase error code	4406

Probable cause

Computed column values cannot be modified explicitly. Their value is determined implicitly from the computed expression value.

Cannot map a login ID to the sys or public user ID

Error constant	SQLE_LOGON_SYSMAP
ODBC 2 State	28000
ODBC 3 State	28000
Severity	16
SQLCODE	-248
SQLSTATE	28W07
Sybase error code	13696

Probable cause

You attempted to map a login ID to either SYS or PUBLIC.

Cannot modify column '%1' in table '%2'

Error constant	SQLE_CANNOT_MODIFY
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	Name of the column that cannot be changed.
Parameter 2	Name of the table containing the column.

Severity	14
SQLCODE	-191
SQLSTATE	42W32
Sybase error code	230

Probable cause

You may have tried to modify a column that you do not have permission to modify. You may have tried to modify a column defined as an expression (such as column1+column2) in a view.

Cannot modify publication entry using ALTER SYNCHRONIZATION

Error constant	SQLE_CANNOT_MODIFY_PUB_AS_SYNC
ODBC 2 State	42000
ODBC 3 State	42S02
Severity	16
SQLCODE	-770
SQLSTATE	5RW15
Sybase error code	13780

Probable cause

You attempted to modify a publication entry using an ALTER SYNCHRONIZATION statement.

Cannot modify synchronization entry using ALTER PUBLICATION

Error constant	SQLE_CANNOT_MODIFY_SYNC_AS_PUB
ODBC 2 State	42000
ODBC 3 State	42S02
Severity	16

SQLCODE	-769
SQLSTATE	5RW14
Sybase error code	13779

Probable cause

You attempted to modify a synchronization entry using an ALTER PUBLICATION statement.

Cannot open transaction log file -- %1

Error constant	SQLE_CANNOT_OPEN_LOG
ODBC 2 State	08003
ODBC 3 State	08003
Parameter 1	Reason why transaction log file cannot be opened.
Severity	16
SQLCODE	-106
SQLSTATE	08W05
Sybase error code	2561

Probable cause

The database server was unable to open the named transaction log file. The log file name may include an invalid device or directory. If this is the case, you can use the Transaction Log utility (dblog) to find out where the transaction log should be and perhaps change it.

Cannot output the histogram for string column '%1'

Error constant	SQLE_CANNOT_DUMP_STRING_HISTOGRAM
ODBC 2 State	OK
ODBC 3 State	OK
Parameter 1	Name of the column containing string data.
Severity	10

SQLCODE	132
SQLSTATE	01W23
Sybase error code	13585

Probable cause

You tried to get the histogram for a column containing strings. Histograms on string information cannot be output in a readable format; as a result, no information was retrieved. Consider using the `ESTIMATE` function to get information on a specific value or range in the column.

Cannot register '%1' since another exclusive instance is running

Error constant	SQLE_SAME_EXCLUSIVE_APP_RUNNING
ODBC 2 State	42000
ODBC 3 State	42S02
Parameter 1	Name of the application.
Severity	16
SQLCODE	-782
SQLSTATE	5RW21
Sybase error code	13792

Probable cause

You attempted to start an application but another exclusive instance of the same application is already registered.

Cannot register '%1' since registration cookie exhausted

Error constant	SQLE_APP_REG_COOKIE_EXHAUSTED
ODBC 2 State	42000
ODBC 3 State	42S02
Parameter 1	Name of the application.

Severity	16
SQLCODE	-789
SQLSTATE	5RW28
Sybase error code	13799

Probable cause

Cannot register the application until one is unregistered.

Cannot register another '%1' as an exclusive application

Error constant	SQLE_SAME_APP_RUNNING
ODBC 2 State	42000
ODBC 3 State	42S02
Parameter 1	Name of the application.
Severity	16
SQLCODE	-783
SQLSTATE	5RW22
Sybase error code	13793

Probable cause

You attempted to register an exclusive application but another instance of the same application is already registered.

Cannot register connection because of invalid application cookie

Error constant	SQLE_CANNOT_REG_CONN
ODBC 2 State	42000
ODBC 3 State	42S02
Severity	16

SQLCODE	-784
SQLSTATE	5RW23
Sybase error code	13794

Probable cause

Application registration cannot be found for the given cookie.

Cannot register connection to '%1' since automatic label exhausted

Error constant	SQLE_CONN_REG_AUTO_LABEL_EXHAUSTED
ODBC 2 State	42000
ODBC 3 State	42S02
Parameter 1	Name of the application.
Severity	16
SQLCODE	-790
SQLSTATE	5RW29
Sybase error code	13800

Probable cause

You may register using a specified label instead.

Cannot remove class '%1': member of JAR

Error constant	SQLE_CLASS_MEMBER_OF_JAR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the class file that cannot be removed.
Severity	16
SQLCODE	-653

SQLSTATE	WP004
Sybase error code	13743

Probable cause

You attempted to remove a class file that is still part of a JAR. (It must be removed with the JAR.)

Cannot return NULL result as requested data type

Error constant	SQL_E_VALUE_IS_NULL
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1050
SQLSTATE	22030
Sybase error code	13461

Probable cause

You tried to retrieve a value from the database that was NULL and assign it to a variable that cannot be NULL.

Cannot revoke these permissions while user '%1' is actively replicating transactions

Error constant	SQL_E_MUST_NOT_BE_REPLICATING
ODBC 2 State	40001
ODBC 3 State	40001
Parameter 1	The name of the user.
Severity	16
SQLCODE	-1080
SQLSTATE	42WBE

Sybase error code	13434
-------------------	-------

Probable cause

You attempted to revoke permissions from a user while there are transactions currently being replicated for that user. This is not allowed.

Cannot serialize Java object with class '%1'

Error constant	SQLE_JAVA_SERIALIZATION_ERROR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The class of the value that cannot be serialized.
Severity	16
SQLCODE	-662
SQLSTATE	WI009
Sybase error code	13744

Probable cause

The Java object cannot be serialized as a persistent database column.

Cannot set a temporary option for user '%1'

Error constant	SQLE_TEMPORARY_NOT_ALLOWED
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	User ID whose option was to be changed.
Severity	16
SQLCODE	-203
SQLSTATE	42W45
Sybase error code	13687

Probable cause

TEMPORARY options are set on a connection basis, and only for specific options known to the database server. To change an option for another user, do not specify TEMPORARY in the SET OPTION statement.

Cannot set database option \"%1\" because it is on the options watch list

Error constant	SQLE_OPTION_ON_WATCH_LIST
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the option.
Severity	16
SQLCODE	-1180
SQLSTATE	WW096
Sybase error code	13335

Probable cause

An attempt was made to set a database option that is on the options watch list. The options watch list is used to help find references to options that have been removed or deprecated.

Cannot stop the database server

Error constant	SQLE_CANNOT_STOP_SERVER
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-607
SQLSTATE	WW002
Sybase error code	13673

Probable cause

The server has determined that it cannot be shut down at this time. Normally, this error should not occur.

Cannot subscribe to '%1'

Error constant	SQLE_CANNOT_SUBSCRIBE
ODBC 2 State	42000
ODBC 3 State	42S02
Parameter 1	Name of the publication.
Severity	16
SQLCODE	-768
SQLSTATE	5RW13
Sybase error code	13778

Probable cause

Some publications cannot be subscribed to, such as a synchronization publication.

Cannot synchronize table '%1' since it does not have a primary key

Error constant	SQLE_CANNOT_SYNC_TABLE_WITHOUT_PK
ODBC 2 State	42000
ODBC 3 State	42S02
Parameter 1	Name of the table.
Severity	16
SQLCODE	-777
SQLSTATE	5RW16
Sybase error code	13787

Probable cause

Tables being synchronized must contain a primary key.

Cannot uniquely identify column '%2' of table '%1' in the current JDBC resultset

Error constant	SQLE_JDBC_TBL_COL_NOT_FOUND_IN_RESULTSET
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Table name.
Parameter 2	Column name.
Severity	16
SQLCODE	-756
SQLSTATE	WJ021
Sybase error code	13766

Probable cause

Failed to identify a column in a JDBC resultset with the given table name and column name. This can happen if the given names are not found or if they are ambiguous.

Cannot uniquely identify rows in cursor

Error constant	SQLE_CANNOT_UNIQUELY_IDENTIFY_ROWS
ODBC 2 State	42000
ODBC 3 State	42000
Severity	16
SQLCODE	-295
SQLSTATE	09W05
Sybase error code	311

Probable cause

You opened a UNIQUE cursor on a SELECT statement for which a set of columns uniquely identifying each row cannot be generated. One of the tables may not be defined with a primary key or uniqueness constraint, or the SELECT statement may involve a UNION, INTERSECT, EXCEPT, or GROUP BY.

Cannot update an expression

Error constant	SQLE_NON_UPDATEABLE_COLUMN
ODBC 2 State	37000
ODBC 3 State	42000
Severity	14
SQLCODE	-190
SQLSTATE	53W02
Sybase error code	230

Probable cause

You tried to update a column in a query that is a database expression rather than a column in a table.

Cannot update column '%1' since it appears in the ORDER BY clause

Error constant	SQLE_CANNOT_UPDATE_ORDER_BY_COLUMN
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	Name of the column that appears in the ORDER BY clause.
Severity	15
SQLCODE	-814
SQLSTATE	42W37
Sybase error code	6267

Probable cause

You attempted to update a column that appears in the ORDER BY clause. The ansi_update_constraints option controls whether this update is allowed.

Cannot update column '%1' since it does not appear in the SELECT clause

Error constant	SQLE_UPDATE_NOT_IN_SELECT
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	Name of the column that does not appear in the SELECT clause.
Severity	15
SQLCODE	-815
SQLSTATE	42W38
Sybase error code	7740

Probable cause

You attempted to update a column that does not explicitly appear in the select list. The ansi_update_constraints option controls whether this update is allowed.

Cannot update materialized view because option '%1' has an inappropriate setting

Error constant	SQLE_CANNOT_UPDATE_MATVIEW
ODBC 2 State	42000
ODBC 3 State	ERROR
Parameter 1	Name of the option with the incorrect setting.
Severity	14
SQLCODE	-1052
SQLSTATE	42WB7

Sybase error code	13461
-------------------	-------

Probable cause

You attempted to update/refresh a materialized view but one of the database options is currently set to a value that is not permitted while updating a materialized view, or, the option's setting does not match the value when the view was created.

Cannot update member fields qualified with \"final\" modifier

Error constant	SQLE_CANNOT_UPDATE_FINAL_FIELD
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-699
SQLSTATE	WJ012
Sybase error code	13606

Probable cause

An attempt was made to modify a Java member that was qualified with the "final" modifier. Such members are constant and cannot be modified.

**Cannot update multiple tables immediate materialized view
%1 depends on**

Error constant	SQLE_CANNOT_UPDATE_TWO_TABLES_IMV
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the view that depends on two or more tables in the update statement.
Severity	16
SQLCODE	-1192

SQLSTATE	55W29
Sybase error code	13323

Probable cause

You attempted to simultaneously update two or more tables initialized immediate materialized view depends on. No more than one base table an immediate materialized view depends on can be updated in a statement.

Cannot update or delete an all-NULL row from table '%1'

Error constant	SQLE_CANNOT_UPDATE_NULL_ROW
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	The name of the table that cannot be modified.
Severity	16
SQLCODE	-734
SQLSTATE	09W08
Sybase error code	13750

Probable cause

You attempted to modify or delete a row in the specified table, which is part of the NULL-supplying side of an outer join. However, the cursor is currently positioned on a derived row that contains an all-NULL row for this table, which is the result of the failure of one or more ON conditions to evaluate to TRUE. Verify that the UPDATE or DELETE statement is correct.

Cannot update primary key for table '%1' involved in a publication

Error constant	SQLE_ARTICLE_PK_CANNOT_BE_UPDATED
ODBC 2 State	42000
ODBC 3 State	42S02
Parameter 1	Name of the table.

Severity	16
SQLCODE	-780
SQLSTATE	5RW19
Sybase error code	13790

Probable cause

The primary key of a table involved in a publication cannot be updated. The database option prevent_article_pkey_update can be set to 'off' to allow updates to the primary key of the table involved in the publication.

Cannot use materialized view '%1' because it has not yet been initialized

Error constant	SQLE_CANNOT_USE_MATVIEW
ODBC 2 State	42000
ODBC 3 State	ERROR
Parameter 1	Name of the materialized view.
Severity	14
SQLCODE	-1077
SQLSTATE	42WBC
Sybase error code	13437

Probable cause

You attempted to use a materialized view but it has not yet been initialized. In order for a materialized view to become available for first use after being created or enabled, it must be initialized at least once using the REFRESH MATERIALIZED VIEW statement.

Cannot use view '%1' because it has been disabled

Error constant	SQLE_VIEW_DISABLED
ODBC 2 State	42000

ODBC 3 State	42000
Parameter 1	The name of the view.
Severity	16
SQLCODE	-1038
SQLSTATE	55W17
Sybase error code	13473

Probable cause

You attempted to reference a view that has been disabled. The view must be enabled before it can be used again.

Cannot use view '%1' because it is invalid

Error constant	SQLE_VIEW_INVALID
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	The name of the view.
Severity	16
SQLCODE	-1040
SQLSTATE	55W18
Sybase error code	13471

Probable cause

You attempted to reference an invalid view. The view must be enabled before it can be used again.

CDATA has a name

Error constant	SQLE_FOR_XML_EXPLICIT_NAMED_CDATA
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Severity	16
SQLCODE	–903
SQLSTATE	WX011
Sybase error code	13580

Probable cause

A CDATA directive in a FOR XML EXPLICIT query must not be given a name.

Character conversion error or warning report is not available when the single-byte converter is used

Error constant	SQLE_CHARACTER_CONVERSION_REPORT_NOT_AVAILABLE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	–883
SQLSTATE	WC007
Sybase error code	13898

Probable cause

You attempted to set the `on_charset_conversion_failure` option to produce either a warning or error report. This setting is not available when the single-byte to single-byte converter is used.

Character set conversion to '%1' cannot be performed; '%2' is used instead

Error constant	SQLE_CANNOT_PERFORM_CHAR_TRANSLATION
ODBC 2 State	01000
ODBC 3 State	01000
Parameter 1	Name of character set the application requested.

Parameter 2	Name of character set the database will be using.
Severity	10
SQLCODE	114
SQLSTATE	01W12
Sybase error code	13613

Probable cause

The server is unable to perform a character conversion from the character set the database is using to the character set the application requested.

Character substitution occurred when converting from %1 to %2

Error constant	SQL_SIMPLE_SUBSTITUTION_WARNING
ODBC 2 State	01000
ODBC 3 State	01000
Parameter 1	The character set of the input string.
Parameter 2	The character set of the output string.
Severity	10
SQLCODE	127
SQLSTATE	01WC3
Sybase error code	13896

Probable cause

While the server was performing character set conversion on an input string, some characters could not be represented in the database character set. Those characters were substituted. See `on_charset_conversion_failure` option.

Character substitution was required when converting from %1 to %2

Error constant	SQLE_SIMPLE_SUBSTITUTION_ERROR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The character set of the input string.
Parameter 2	The character set of the output string.
Severity	16
SQLCODE	-881
SQLSTATE	WC005
Sybase error code	13894

Probable cause

While the server was performing character set conversion on an input string, some characters could not be represented in the database character set. The operation was aborted. See `on_charset_conversion_failure` option.

CHECKPOINT statement requires a rollback log

Error constant	SQLE_CHECKPOINT_REQUIRES_UNDO
ODBC 2 State	40001
ODBC 3 State	40001
Severity	16
SQLCODE	-212
SQLSTATE	42W20
Sybase error code	13653

Probable cause

You cannot use a CHECKPOINT statement when the database server is running in bulk mode without a rollback log.

Checksums are not enabled in this database

Error constant	SQLE_CHECKSUMS_NOT_ENABLED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-971
SQLSTATE	WW042
Sybase error code	13517

Probable cause

An attempt was made to perform checksum validation but the database does not have checksums enabled.

Class '%1' has no public field '%2'

Error constant	SQLE_FIELD_NOT_FOUND
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the class in which the named field could not be found.
Parameter 2	The name of the field that could not be found.
Severity	16
SQLCODE	-93
SQLSTATE	WW013
Sybase error code	13703

Probable cause

An expression referenced a field that either does not exist or is not public.

Clause '%1' has invalid attribute '%2'

Error constant	SQLE_INVALID_PROCEDURE_ATTRIBUTE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The attribute on the procedure.
Parameter 2	The attribute value or cause of failure.
Severity	16
SQLCODE	-991
SQLSTATE	WW060
Sybase error code	13498

Probable cause

The attribute value specified on the procedure is not valid.

Client application disallowed the transfer of data ('%1')

Error constant	SQLE_CLIENT_TRANSFER_DISALLOWED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the object being transferred to/from the application.
Severity	16
SQLCODE	-1172
SQLSTATE	WW093
Sybase error code	13341

Probable cause

The client application rejected the transfer of server initiated data. In order to allow transfer of server initiated data, the application registered a validation callback which rejected the transfer of requested data.

Client application does not allow transfer of data ('%1')

Error constant	SQLE_CLIENT_TRANSFER_NO_VALIDATION
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the object being transferred to/from the application.
Severity	16
SQLCODE	-1171
SQLSTATE	WW092
Sybase error code	13342

Probable cause

The client application does not allow the transfer of server initiated data. In order to allow transfer of server initiated data, the application must register a validation callback mechanism with the client library.

Client library reported a permissions error accessing object ('%1') during transfer

Error constant	SQLE_CLIENT_TRANSFER_PERMS_ERROR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the object being transferred to/from the application.
Severity	16
SQLCODE	-1200
SQLSTATE	WW103
Sybase error code	13315

Probable cause

The client application reported a permissions error while attempting to access the object for a data transfer request from the server. The client application likely does not have the necessary operating system authorization required to access the object.

Client library reported an error accessing data during transfer ('%1')

Error constant	SQLE_CLIENT_TRANSFER_ACCESS_ERROR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the object being transferred to/from the application.
Severity	16
SQLCODE	-1173
SQLSTATE	WW094
Sybase error code	13340

Probable cause

The client application reported an error while attempting to access the data for a transfer request from the server. Reasons could include the client application lacking permissions to the data object or other operating system reported errors.

Client library reported an error opening object ('%1') during transfer

Error constant	SQLE_CLIENT_TRANSFER_OPEN_ERROR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the object being transferred to/from the application.
Severity	16
SQLCODE	-1201
SQLSTATE	WW102
Sybase error code	13314

Probable cause

The client application reported an error while attempting to open the object for a data transfer request from the server. Reasons could include an invalid name for the object or a missing object.

Client out of memory

Error constant	SQLE_CLIENT_OUT_OF_MEMORY
ODBC 2 State	S1001
ODBC 3 State	HY001
Severity	17
SQLCODE	-876
SQLSTATE	08W65
Sybase error code	13882

Probable cause

A failure occurred when the database client was trying to allocate memory.

Client/database server version mismatch

Error constant	SQLE_DBLIB_ENGINE_MISMATCH
ODBC 2 State	08001
ODBC 3 State	08001
Severity	21
SQLCODE	-231
SQLSTATE	08W19
Sybase error code	13658

Probable cause

Your executable uses a database interface library that does not match the version number of the database server.

Client/server communications protocol version mismatch

Error constant	SQLE_PROTOCOL_MISMATCH
ODBC 2 State	08S01
ODBC 3 State	08S01
Severity	21
SQLCODE	-88
SQLSTATE	08W15
Sybase error code	1602

Probable cause

The connection failed because the protocol versions of the client and the server do not match. Ensure the client and server software are the same version.

Collation '%1' not supported on this platform

Error constant	SQLE_COLLATION_NOT_SUPPORTED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The collation that is not supported.
Severity	16
SQLCODE	-1116
SQLSTATE	WC013
Sybase error code	13398

Probable cause

The specified collation is not supported on the current platform.

Column '%1' found in more than one table -- need a correlation name

Error constant	SQLE_COLUMN_AMBIGUOUS
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Name of the ambiguous column.
Severity	16
SQLCODE	-144
SQLSTATE	52002
Sybase error code	209

Probable cause

You have not put a correlation name on a column that is found in more than one of the tables referenced in a query. You need to add a correlation name to the reference.

Column '%1' in foreign key has a different definition than primary key

Error constant	SQLE_INVALID_FOREIGN_KEY_DEF
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	Name of the problem column.
Severity	16
SQLCODE	-113
SQLSTATE	53030
Sybase error code	1721

Probable cause

The data type of the column in the foreign key is not the same as the data type of the column in the primary key. Change the definition of one of the columns using ALTER TABLE.

Column '%1' in table '%2' cannot be NULL

Error constant	SQLE_COLUMN_CANNOT_BE_NULL
ODBC 2 State	23000
ODBC 3 State	23000
Parameter 1	Name of the column that cannot be NULL.
Parameter 2	Name of the table containing the column.
Severity	16
SQLCODE	-195
SQLSTATE	23502
Sybase error code	233

Probable cause

You have not supplied a value where a value is required. The column definition prohibits NULL values or the column is part of a NOT NULL foreign key.

Column '%1' in table '%2' cannot be NULL. The invalid data was supplied to LOAD TABLE in a data file on line %3

Error constant	SQLE_COLUMN_CANNOT_BE_NULL_LOAD_TABLE
ODBC 2 State	23000
ODBC 3 State	23000
Parameter 1	Name of the column that cannot be NULL.
Parameter 2	Name of the table containing the column.
Parameter 3	The line number of the data file containing the invalid data.
Severity	16
SQLCODE	-184
SQLSTATE	23501
Sybase error code	13885

Probable cause

You either have not supplied a value where a value is required or a data conversion was necessary that resulted in a NULL value. The column definition prohibits NULL values or the column is part of a NOT NULL foreign key.

Column '%1' not found

Error constant	SQLE_COLUMN_NOT_FOUND
ODBC 2 State	S0002
ODBC 3 State	42S22
Parameter 1	Name of the column that could not be found.
Severity	16
SQLCODE	-143
SQLSTATE	52003
Sybase error code	207

Probable cause

You misspelled the name of a column, or the column you are looking for is in a different table.

Column '%1' not found in table '%2'

Error constant	SQLE_COLUMN_NOT_FOUND_IN_TABLE
ODBC 2 State	S0002
ODBC 3 State	42S22
Parameter 1	Name of the column that could not be found.
Parameter 2	Name of the table that was supposed to contain the column.
Severity	11
SQLCODE	-834
SQLSTATE	52005
Sybase error code	13840

Probable cause

You misspelled the name of a column, or the column you are looking for is in a different table.

Column '%1' not part of any indexes in its containing table

Error constant	SQLE_COLUMN_NOT_INDEXED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the column not found in any index.
Severity	16
SQLCODE	-1101
SQLSTATE	WW073
Sybase error code	13413

Probable cause

The specified column is not part of any indexes belonging to the containing table.

Column must be named: %1

Error constant	SQLE_NO_XML_IDENTIFIER
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Number of the column that must be named.
Severity	16
SQLCODE	-874
SQLSTATE	WX001
Sybase error code	13880

Probable cause

Unnamed columns cannot be used as XML element or attribute names. Name unnamed columns in the select list using AS.

Command not allowed on IMMEDIATE REFRESH text index

Error constant	SQLE_TEXT_IMMEDIATE_NOT_ALLOWED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1182
SQLSTATE	WT015
Sybase error code	13333

Probable cause

You cannot use REFRESH TEXT INDEX or TRUNCATE TEXT INDEX on an index that is created with immediate refresh. You cannot alter a text index to use or stop using immediate refresh.

COMMIT/ROLLBACK not allowed within atomic operation

Error constant	SQLE_ATOMIC_OPERATION
ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	-267
SQLSTATE	42W28
Sybase error code	13640

Probable cause

You attempted a COMMIT or ROLLBACK statement while executing within an atomic operation.

COMMIT/ROLLBACK not allowed within trigger actions

Error constant	SQLE_INVALID_TRIGGER_STATEMENT
ODBC 2 State	37000

ODBC 3 State	42000
Severity	15
SQLCODE	-273
SQLSTATE	2D501
Sybase error code	102

Probable cause

You attempted to execute a statement that is not allowed while performing a trigger action. COMMIT and ROLLBACK statements cannot be executed from a trigger.

Communication error

Error constant	SQLE_COMMUNICATIONS_ERROR
ODBC 2 State	08S01
ODBC 3 State	08S01
Severity	21
SQLCODE	-85
SQLSTATE	08W12
Sybase error code	1602

Probable cause

There is a communication problem between the application and the server.

Composite ORDER BY not allowed with RANGE

Error constant	SQLE_ILLEGAL_COMPOSITE_ORDERBY
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-966

SQLSTATE	42WAA
Sybase error code	13524

Probable cause

Window functions that use the RANGE keyword may only ORDER BY a single column.

Compression error: %1

Error constant	SQLE_COMPRESSION_ERROR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Error message.
Severity	16
SQLCODE	-959
SQLSTATE	WW037
Sybase error code	13529

Probable cause

An error occurred during compression.

Computed columns are not supported in this database

Error constant	SQLE_COMPUTED_COLUMNS_NOT_SUPPORTED
ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	-709
SQLSTATE	0AW06
Sybase error code	13722

Probable cause

The current database is an older database and does not have catalog support for computed (materialized) columns. To use this feature, upgrade your database to the most recent version.

Configuration cannot not be modified while in use

Error constant	SQLE_CONFIG_IN_USE
ODBC 2 State	ERROR
ODBC 3 State	42000
Severity	16
SQLCODE	-1276
SQLSTATE	55W34
Sybase error code	13863

Probable cause

You attempted to modify a configuration object that is in use by an open connection.

Conflicting INSTEAD OF trigger and WITH CHECK OPTION on view '%1'

Error constant	SQLE_CHECK_TRIGGER_CONFLICT
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	Name of the view with an INSTEAD OF trigger
Severity	15
SQLCODE	-1125
SQLSTATE	42W39
Sybase error code	13388

Probable cause

You attempted an operation that involves a WITH CHECK OPTION clause that conflicts with an INSTEAD OF trigger. A view defined with the WITH CHECK OPTION clause cannot refer to a view (possibly nested) with an INSTEAD OF trigger.

Connection attempting BACKUP has uncommitted transactions

Error constant	SQLE_BACKUP_HAS_UNCOMMITTED_TRANS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1028
SQLSTATE	WB014
Sybase error code	13482

Probable cause

A connection attempting to perform a BACKUP ... WAIT BEFORE START or BACKUP ... WAIT AFTER END has uncommitted transactions. A COMMIT or ROLLBACK must be performed before executing the backup.

Connection disallowed by login policy for this user

Error constant	SQLE_CONNECTION_DISALLOWED_BY_LOGIN_POLICY
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1212
SQLSTATE	28W15
Sybase error code	13303

Probable cause

A connection attempt was disallowed based on the login policy for the user. It may be necessary for a user with DBA authority to reset this user via the ALTER USER statement.

Connection error: %1

Error constant	SQLE_CONNECTION_ERROR
ODBC 2 State	08001
ODBC 3 State	08001
Parameter 1	Description of the connection error.
Severity	16
SQLCODE	-832
SQLSTATE	08W60
Sybase error code	13838

Probable cause

An error occurred while attempting to establish a connection with the database server, but before attempting to connect to a database. Failure to initialize a communication link during the connection attempt is an example of this error. Creating a debug log file using the LogFile connection parameter may provide more information.

Connection not found

Error constant	SQLE_CONNECTION_NOT_FOUND
ODBC 2 State	08003
ODBC 3 State	08003
Severity	16
SQLCODE	-108
SQLSTATE	08W02
Sybase error code	4224

Probable cause

The specified connection name on a DISCONNECT or SET CONNECTION statement is invalid.

Connection timed out

Error constant	SQLE_REMOTE_CONNECTION_TIMED_OUT
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	19
SQLCODE	-982
SQLSTATE	WW051
Sybase error code	13507

Probable cause

The connection to the remote host timed out due to inactivity.

Connection was terminated

Error constant	SQLE_CONNECTION_TERMINATED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-308
SQLSTATE	40W07
Sybase error code	4224

Probable cause

Your database connection has been terminated and your transaction has been rolled back. The connection may have been terminated because a DBA executed a DROP CONNECTION statement, or because the database server was shut down, or because your network connection to the database server was interrupted.

Connections to database have been disabled

Error constant	SQLE_CONNECTIONS_DISABLED
ODBC 2 State	08005
ODBC 3 State	08005
Severity	16
SQLCODE	-99
SQLSTATE	08W04
Sybase error code	4224

Probable cause

Connections to the network database server have been disabled. You will receive this error until connections have been enabled.

Constant expressions must not appear in GROUP BY clause

Error constant	SQLE_NO_CONSTANTS_IN_GROUP_BY
ODBC 2 State	37000
ODBC 3 State	42000
Severity	15
SQLCODE	-928
SQLSTATE	42W9D
Sybase error code	13557

Probable cause

You used a constant in the GROUP BY clause. Constants must not appear in the GROUP BY clause for a query. References to columns in a view that are constant are permitted in a GROUP BY clause. Also, expressions that use a view column that is constant are permitted.

Constraint '%1' not found

Error constant	SQLE_CONSTRAINT_NOT_FOUND
----------------	---------------------------

ODBC 2 State	S0002
ODBC 3 State	42S23
Parameter 1	Name of the constraint that could not be found.
Severity	16
SQLCODE	-929
SQLSTATE	42U04
Sybase error code	13556

Probable cause

You misspelled the name of a constraint, or the constraint you are looking for is on a different table.

Constraint '%1' violated: Invalid value for column '%2' in table '%3'

Error constant	SQLE_INVALID_COLUMN_VALUE
ODBC 2 State	42000
ODBC 3 State	23000
Parameter 1	Name of the constraint (if defined) that was violated by an invalid value.
Parameter 2	Name of the column that was assigned an invalid value.
Parameter 3	Name of the table containing the column.
Severity	16
SQLCODE	-209
SQLSTATE	23506
Sybase error code	548

Probable cause

You attempted an insert or update that violates a CHECK constraint. A CHECK constraint is violated if it evaluates to FALSE; it is deemed to hold if the condition evaluates to TRUE or UNKNOWN.

Constraint '%1' violated: Invalid value in table '%2'

Error constant	SQLE_TABLE_CONSTRAINT_VIOLATED
ODBC 2 State	42000
ODBC 3 State	23000
Parameter 1	Name of the constraint (if defined) that was violated by an invalid value.
Parameter 2	Name of the table containing the column.
Severity	16
SQLCODE	-1091
SQLSTATE	23508
Sybase error code	548

Probable cause

You attempted an insert or update that violates a CHECK constraint. A CHECK constraint is violated if it evaluates to FALSE; it is deemed to hold if the condition evaluates to TRUE or UNKNOWN.

Contents of backup files are inconsistent

Error constant	SQLE_RESTORE_INCONSISTENT
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	23
SQLCODE	-715
SQLSTATE	WB006
Sybase error code	13724

Probable cause

During a RESTORE, the contents of a backup that was done to two or more disk or tape devices were found to be inconsistent.

Control character in XML output

Error constant	SQLE_CONTROL_CHARACTER_IN_XML_OUTPUT
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-911
SQLSTATE	WX015
Sybase error code	13573

Probable cause

A non-space character less than hex 20 was encountered while generating XML content. Consider base64 encoding strings that contain control characters before using them as XML content. This can be accomplished in a FOR XML query or SQLX function by casting the string to a type such as LONG BINARY.

Correlation name '%1' is not valid for use with the ROWID function

Error constant	SQLE_INVALID_CORRELATION_FOR_ROWID
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the invalid correlation name.
Severity	15
SQLCODE	-1113
SQLSTATE	42WBF
Sybase error code	13401

Probable cause

The correlation name used was not valid for the ROWID function. Only the correlation names of base tables, temporary tables, global temporary tables or proxy tables may be used with the ROWID function. The argument of a ROWID function should not refer to a view, derived table, common table expression, or a procedure.

Correlation name '%1' not found

Error constant	SQLE_CORRELATION_NAME_NOT_FOUND
ODBC 2 State	S0002
ODBC 3 State	42S02
Parameter 1	Name of the invalid correlation name.
Severity	16
SQLCODE	-142
SQLSTATE	52W02
Sybase error code	208

Probable cause

You misspelled a correlation name, or you used a table name instead of the correlation name.

Could not access column information for the table '%1'

Error constant	SQLE_OMNI_RMT_COLUMNS_NOTFOUND
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The complete name of the remote table.
Severity	11
SQLCODE	-667
SQLSTATE	WO008
Sybase error code	11207

Probable cause

Column information for the table could not be accessed. Check permissions for the table.

Could not allocate resources to call external function

Error constant	SQLE_ERROR_CALLING_FUNCTION
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	19
SQLCODE	-622
SQLSTATE	WW008
Sybase error code	13679

Probable cause

The external function could not be called due to a shortage of operating system resources. If the operating system supports threads, the maximum thread count should be increased.

Could not change an opened prepared statement or callable statement

Error constant	SQLE_CANNOT_CHANGE_OPENED_STATEMENT
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-694
SQLSTATE	WJ008
Sybase error code	13603

Probable cause

You attempted to change the SQL statement of an open prepared statement or callable statement. Prepared statements and callable statements must be closed before attempting such changes.

Could not create a new text for this table with the same settings as \"%1\

Error constant	SQLE_TEXT_INDEX_SAME_SETTING_IDX
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the other text index with the same settings.
Severity	16
SQLCODE	-1304
SQLSTATE	WT021
Sybase error code	13455

Probable cause

Two text indexes with the same column list and configuration settings cannot be created for a table.

Could not decompress class '%1' from JAR

Error constant	SQLE_CANNOT_DECOMPRESS_CLASS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the class file in the JAR.
Severity	16
SQLCODE	-652
SQLSTATE	WP003
Sybase error code	13742

Probable cause

The Java runtime library must be installed to extract class files from ZIP or JAR files.

Could not execute backup/restore DLL (%1) entry point

Error constant	SQLE_BACKUP_ENTRY_NOT_FOUND
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the entry point that could not be found.
Severity	19
SQLCODE	-692
SQLSTATE	08W45
Sybase error code	13719

Probable cause

An attempt to locate or execute the backup/restore DLL entry point failed.

Could not execute store DLL (%1) entry point

Error constant	SQLE_STORE_ENTRY_NOT_FOUND
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the store DLL where the entry point failed.
Severity	19
SQLCODE	-647
SQLSTATE	08W35
Sybase error code	13700

Probable cause

An attempt to locate or execute the store DLL entry point failed.

Could not find '%1' in dynamic library '%2'

Error constant	SQLE_COULD_NOT_FIND_FUNCTION
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the function that could not be found.
Parameter 2	Name of the dynamic library in which the function could not be found.
Severity	19
SQLCODE	-621
SQLSTATE	WW007
Sybase error code	13678

Probable cause

The external function could not be found in the dynamic library.

Could not initialize the encryption DLL: '%1'

Error constant	SQLE_ENCRYPTION_INITIALIZATION_FAILED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Reason the initialization failed, if known.
Severity	19
SQLCODE	-984
SQLSTATE	WW053
Sybase error code	13505

Probable cause

An attempt to initialize the encryption DLL failed.

Could not load dynamic library '%1'

Error constant	SQLE_COULD_NOT_LOAD_LIBRARY
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the dynamic library that could not be loaded.
Severity	19
SQLCODE	-620
SQLSTATE	WW006
Sybase error code	13677

Probable cause

This error is usually caused by a failure to load a dynamic library named in an external function call.

Could not load the backup/restore DLL \"%1\

Error constant	SQLE_BACKUP_NOT_LOADED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the DLL that could not be loaded.
Severity	19
SQLCODE	-691
SQLSTATE	08W44
Sybase error code	13718

Probable cause

An attempt to load the backup/restore DLL failed.

Could not load the encryption DLL \"%1\

Error constant	SQLE_MISSING_ENCRYPTION_DLL
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the encryption DLL that could not be loaded.
Severity	19
SQLCODE	-976
SQLSTATE	08W70
Sybase error code	13513

Probable cause

An attempt to load the encryption DLL failed.

Could not load the store DLL \"%1\

Error constant	SQLE_STORE_NOT_LOADED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the store DLL that could not be loaded.
Severity	19
SQLCODE	-646
SQLSTATE	08W34
Sybase error code	13699

Probable cause

An attempt to load the store DLL failed.

Could not refresh tracing: at least one enabled tracing level must be specified

Error constant	SQLE_NO_TRACING_LEVELS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1081
SQLSTATE	55W24
Sybase error code	13433

Probable cause

Table sa_diagnostic_tracing_level contains no rows (tracing levels) or no tracing levels are enabled.

Could not refresh tracing: failed to find object %1 on row %2

Error constant	SQLE_TRACING_OBJ_NOT_FOUND
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The specified name of the object.
Parameter 2	The primary key of the row on which the check failed.
Severity	11
SQLCODE	-1083
SQLSTATE	WW067
Sybase error code	13431

Probable cause

You misspelled the object name, or you did not qualify the name with user (and, possibly, table) name. For example, you might have referred to Employees instead of DBA"."Employees", or you might have referred to Employees_trigger instead of "DBA"."Employees"."Employees_trigger".

Could not refresh tracing: invalid tracing specification on sa_diagnostic_tracing_level row %1

Error constant	SQLE_INVALID_TRACING_SPEC
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The primary key of the row that is invalid.
Severity	16
SQLCODE	-1082
SQLSTATE	WW066
Sybase error code	13432

Probable cause

You specified an invalid combination of values for the tracing level. Some invalid combinations are: specified condition is not valid for the tracing type, or specified tracing type is not valid for the scope.

Could not refresh tracing: volatile_statistics have to be collected in order for %1 specified on row %2 to be collected

Error constant	SQLE_NO_VOLATILE_LEVEL_SPEC
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The tracing level that caused the error.
Parameter 2	The primary key of the row on which the check failed.
Severity	16
SQLCODE	-1087
SQLSTATE	WW068
Sybase error code	13427

Probable cause

Volatile statistics have to be collected in order for the non-volatile and connection statistics to be collected.

CREATE/DROP STATISTICS statement cannot refer to virtual tables

Error constant	SQLE_HISTOGRAMS_NOT_SUPPORTED_ON_OBJECT
ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	-858
SQLSTATE	42W67
Sybase error code	13861

Probable cause

You attempted to use CREATE/DROP STATISTICS to create/drop one or more histograms on a virtual database object, such as a view or remote table. The CREATE STATISTICS and DROP STATISTICS statements can only refer to base tables, local temporary tables, or global temporary tables in the SQL Anywhere database that you are connected to.

Creating remote tables with computed columns is not supported

Error constant	SQLE_OMNI_COMPUTED_NOT_SUPPORTED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	12
SQLCODE	-732
SQLSTATE	WO021
Sybase error code	11205

Probable cause

Computed columns are not supported in CREATE TABLE statements that specify a remote location.

Current connection is already registered to '%1' as '%2'

Error constant	SQLE_CONN_ALREADY_REGISTERED
ODBC 2 State	42000
ODBC 3 State	42S02
Parameter 1	Name of the application.
Parameter 2	Registered connection label.
Severity	16
SQLCODE	-787
SQLSTATE	5RW26
Sybase error code	13797

Probable cause

You attempted to register this connection more than once.

Cursor already open

Error constant	SQLE_CURSOR_ALREADY_OPEN
ODBC 2 State	24000
ODBC 3 State	24000
Severity	16
SQLCODE	-172
SQLSTATE	24502
Sybase error code	558

Probable cause

You attempted to OPEN a cursor that is already open.

Cursor has not been declared

Error constant	SQLE_CURSOR_NOT_DECLARED
ODBC 2 State	24000
ODBC 3 State	24000
Severity	16
SQLCODE	-170
SQLSTATE	24W01
Sybase error code	557

Probable cause

You attempted to OPEN a cursor that has not been declared.

Cursor is restricted to FETCH NEXT operations

Error constant	SQLE_NO_SCROLL_CURSOR
ODBC 2 State	S1106
ODBC 3 State	HY106
Severity	16
SQLCODE	-668
SQLSTATE	09W06
Sybase error code	13710

Probable cause

An illegal FETCH operation has been detected for a NO SCROLL cursor. For a forward-only cursor the only permitted FETCH operations are FETCH RELATIVE 0 and FETCH NEXT (FETCH RELATIVE 1).

Cursor not in a valid state

Error constant	SQLE_CURSOR_INVALID_STATE
ODBC 2 State	24000

ODBC 3 State	24000
Severity	16
SQLCODE	-853
SQLSTATE	24000
Sybase error code	557

Probable cause

You attempted to use a cursor that is not in a valid state for the attempted operation. For example, the cursor may have encountered an error.

Cursor not open

Error constant	SQLE_CURSOR_NOT_OPEN
ODBC 2 State	34000
ODBC 3 State	34000
Severity	16
SQLCODE	-180
SQLSTATE	24501
Sybase error code	559

Probable cause

You attempted to use a cursor that has not been opened.

Cursor option values changed

Error constant	SQLE_CURSOR_OPTIONS_CHANGED
ODBC 2 State	01S02
ODBC 3 State	01S02
Severity	10
SQLCODE	121

SQLSTATE	01S02
Sybase error code	13857

Probable cause

The database server could not support the requested cursor option values for the associated query. Similar option settings were substituted.

Cycle in common table expression references

Error constant	SQLE_COMMON_TABLE_EXPRESSION_CYCLE
ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	-914
SQLSTATE	42W93
Sybase error code	13570

Probable cause

Cycles involving multiple common table expressions are not allowed.

Cycle in computed column dependencies

Error constant	SQLE_COMPUTED_COLUMN_CYCLE
ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	-1078
SQLSTATE	42WBD
Sybase error code	13436

Probable cause

The table has a cycle in the dependencies between its computed columns. Cycles are not allowed.

SQL Anywhere error messages sorted by message text (D-K)

Data definition statements not allowed in procedures or triggers

Error constant	SQLE_DDL_NOT_ALLOWED_IN_PROCEDURES
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	15
SQLCODE	-623
SQLSTATE	52W21
Sybase error code	154

Probable cause

The procedure or trigger definition contains a data definition statement (such as CREATE, DROP, GRANT, REVOKE, or ALTER). These statements are not allowed within procedures or triggers.

Database '%1' cannot be started on this platform. See http://iAnywhere.com/developer/product_manuals/sqlanywhere/notes/en/Endian_cant_change_platform.html

Error constant	SQLE_DATABASE_ENDIAN_FAILURE
ODBC 2 State	08001
ODBC 3 State	08001
Parameter 1	The name of the database.
Severity	11
SQLCODE	-1149
SQLSTATE	08W99
Sybase error code	840

Probable cause

It was determined that the database cannot be started on the current platform because doing so could possibly cause an endian related database file corruption. It will continue to start without problems on a platform with the opposite endian. More information and instructions on how to proceed are available at: http://ianywhere.com/developer/product_manuals/sqlanywhere/notes/en/endian_cant_change_platform.html

Database '%1' cannot be started on this platform. See http://ianywhere.com/developer/product_manuals/sqlanywhere/notes/en/endian_corruption_warning.html

Error constant	SQLE_POSSIBLE_DATABASE_CORRUPTION
ODBC 2 State	08001
ODBC 3 State	08001
Parameter 1	The name of the database.
Severity	11
SQLCODE	-1147
SQLSTATE	08W98
Sybase error code	840

Probable cause

It was determined that the database may be corrupt. More information and instructions on how to proceed are available at: http://ianywhere.com/developer/product_manuals/sqlanywhere/notes/en/endian_corruption_warning.html

Database \"%1\" needs recovery

Error constant	SQLE_DATABASE_NEEDS_RECOVERY
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The file name of the database that needs recovery.
Severity	21
SQLCODE	-665

SQLSTATE	08W41
Sybase error code	13709

Probable cause

The database quit abnormally the last time it was used. Database recovery must be performed before proceeding.

Database backup not started

Error constant	SQL_E_BACKUP_NOT_STARTED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	20
SQLCODE	-241
SQLSTATE	WB002
Sybase error code	3206

Probable cause

A database backup could not be started. Either a backup is already running, or you do not have the required authority (BACKUP, DBA, or REMOTE DBA).

Database cannot be started -- %1

Error constant	SQL_E_UNABLE_TO_CONNECT
ODBC 2 State	08001
ODBC 3 State	08001
Parameter 1	Reason that database cannot be started.
Severity	11
SQLCODE	-105
SQLSTATE	08001

Sybase error code	4001
-------------------	------

Probable cause

The specified database cannot be started. Either it does not exist, it is not a database, it is corrupt, or it is an older, unsupported format.

Database creation failed: %1

Error constant	SQLE_DATABASE_NOT_CREATED
ODBC 2 State	08004
ODBC 3 State	08004
Parameter 1	Reason that the database was not created.
Severity	14
SQLCODE	-645
SQLSTATE	08W33
Sybase error code	928

Probable cause

Your attempt to initialize a file for a database failed.

Database is active

Error constant	SQLE_DATABASE_ACTIVE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-664
SQLSTATE	08W40
Sybase error code	13708

Probable cause

The attempted operation (CREATE ENCRYPTED, CREATE DECRYPTED, ALTER DATABASE) cannot be performed while the database is running. Stop the database to perform the operation.

Database name not unique

Error constant	SQLE_ALIAS_CLASH
ODBC 2 State	08001
ODBC 3 State	08001
Severity	16
SQLCODE	-77
SQLSTATE	08W27
Sybase error code	1801

Probable cause

The database cannot be started as its name conflicts with a previously started database.

Database name required to start server

Error constant	SQLE_DATABASE_NAME_REQUIRED
ODBC 2 State	08001
ODBC 3 State	08001
Severity	17
SQLCODE	-87
SQLSTATE	08W14
Sybase error code	840

Probable cause

You did not supply a database name. A database name is required to start a database server.

Database option '%1' for user '%2' has an invalid setting

Error constant	SQLE_INVALID_OPTION_ON_CONNECT
ODBC 2 State	01000
ODBC 3 State	01000
Parameter 1	Name of the database option that has the invalid value.
Parameter 2	Name of the user attempting to connect.
Severity	10
SQLCODE	113
SQLSTATE	01W11
Sybase error code	13688

Probable cause

Upon processing a connection request for a specific user, the server processed a database option that has an invalid setting. The server will use the default option value.

Database page size too big: %1

Error constant	SQLE_PAGE_SIZE_TOO_BIG
ODBC 2 State	08004
ODBC 3 State	08004
Parameter 1	Database name.
Severity	14
SQLCODE	-97
SQLSTATE	08W22
Sybase error code	927

Probable cause

You attempted to start a database with a page size that exceeds the maximum page size of the running server. Either restart the server and include this database name on the command line, or restart the server with the required page size.

Database page size too small: %1

Error constant	SQLE_PAGE_SIZE_TOO_SMALL
ODBC 2 State	08004
ODBC 3 State	08004
Parameter 1	Database name.
Severity	14
SQLCODE	-972
SQLSTATE	54W03
Sybase error code	13516

Probable cause

You attempted to load statistics that were too large for the current database page size. Rebuilding this database with a larger page size could prevent this error.

Database page validation failed with code: %1

Error constant	SQLE_CORRUPT_ULTRALITE_DATABASE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The specific kind of corruption that was found.
Severity	23
SQLCODE	-1186
SQLSTATE	WI003
Sybase error code	13329

Probable cause

UltraLite database validation failed while validating the database pages. The code provides more specific information on the validation failure.

Database server already running

Error constant	SQLE_ENGINE_ALREADY_RUNNING
ODBC 2 State	S1000
ODBC 3 State	HY000
Severity	18
SQLCODE	–96
SQLSTATE	08W23
Sybase error code	7950

Probable cause

The database server was not able to start because a server with the same name was already running.

Database server cannot convert data from/to character set '%1'

Error constant	SQLE_UNSUPPORTED_CHARACTER_SET_ERROR
ODBC 2 State	08S01
ODBC 3 State	08S01
Parameter 1	Name of the requested character set.
Severity	21
SQLCODE	–869
SQLSTATE	08W64
Sybase error code	13873

Probable cause

The database server cannot convert character data from/to the character set requested by the application because the character set is not supported. The connection fails.

Database server cannot convert data from/to character set '%1', conversion may not be correct

Error constant	SQLE_UNSUPPORTED_CHARACTER_SET_WARNING
ODBC 2 State	01000
ODBC 3 State	01000
Parameter 1	Name of the requested character set.
Severity	10
SQLCODE	115
SQLSTATE	01W13
Sybase error code	13614

Probable cause

The database server cannot convert character data from/to the character set requested by the application because the character set is not supported. The connection succeeds, but character conversion may not be correct for all characters.

Database server connection limit exceeded

Error constant	SQLE_TOO_MANY_CONNECTIONS
ODBC 2 State	08004
ODBC 3 State	08004
Severity	21
SQLCODE	-102
SQLSTATE	08W03
Sybase error code	1601

Probable cause

You exceeded the number of computers allowed to connect to the server. If you are running the network database server, the limit is spelled out in your license agreement. The server may be running low on cache such that it cannot accept any more database connections. The personal database server is restricted to 10 connections.

Database server not found

Error constant	SQLE_ENGINE_NOT_RUNNING
ODBC 2 State	08001
ODBC 3 State	08001
Severity	16
SQLCODE	-100
SQLSTATE	08W01
Sybase error code	7950

Probable cause

The database server is not running, or is in the process of starting up or shutting down, or the interface library is unable to find it.

Database server not running in multi-user mode

Error constant	SQLE_ENGINE_NOT_MULTUSER
ODBC 2 State	08001
ODBC 3 State	08001
Severity	17
SQLCODE	-89
SQLSTATE	08W16
Sybase error code	7203

Probable cause

The database server was started for bulk loading (the -b option) and cannot be used as a network server. Stop the database server, and start again without -b.

Database upgrade failed

Error constant	SQLE_DATABASE_UPGRADE_FAILED
----------------	------------------------------

ODBC 2 State	08004
ODBC 3 State	08004
Severity	20
SQLCODE	-672
SQLSTATE	08W42
Sybase error code	3451

Probable cause

Your attempt to upgrade a database failed. This could be caused by a failure to locate one of the SQL script files used to define the system table changes.

Database upgrade not possible

Error constant	SQLE_DATABASE_UPGRADE_NOT_POSSIBLE
ODBC 2 State	08004
ODBC 3 State	08004
Severity	21
SQLCODE	-673
SQLSTATE	08W43
Sybase error code	3451

Probable cause

An attempt to upgrade a database failed. The database is too old to be upgraded.

Database upgrade not possible; RowGenerator table not owned by user dbo

Error constant	SQLE_DBO_DOES_NOT_OWN_ROWGENERATOR
ODBC 2 State	08004
ODBC 3 State	08004

Severity	21
SQLCODE	–826
SQLSTATE	08W57
Sybase error code	13832

Probable cause

An attempt to upgrade a database failed. The RowGenerator table is not owned by user dbo.

Database upgrade not possible; user tables have table ids in system table range

Error constant	SQLE_USER_TABLES_IN_SYSTEM_RANGE
ODBC 2 State	08004
ODBC 3 State	08004
Severity	21
SQLCODE	–827
SQLSTATE	08W58
Sybase error code	13833

Probable cause

An attempt to upgrade a database failed. The RowGenerator table is not owned by user dbo.

db_init has not been called or the call to db_init failed

Error constant	SQLE_DB_INIT_NOT_CALLED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	–739
SQLSTATE	55W07

Sybase error code	13752
-------------------	-------

Probable cause

The SQLCA passed to a dblib entry point has not been initialized by a call to db_init or the call to db_init failed.

dbicu libraries are required but not installed

Error constant	SQLLE_ICU_NOT_AVAILABLE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1076
SQLSTATE	WC012
Sybase error code	13438

Probable cause

The server is unable to load ICU components that are required by this database. Ensure that the dbicu and dbicudt DLLs are installed.

Dbospace '%1' not found

Error constant	SQLLE_DBSPACE_NOT_FOUND
ODBC 2 State	S0002
ODBC 3 State	42S02
Parameter 1	Name of the dbspace that could not be found.
Severity	11
SQLCODE	-138
SQLSTATE	52W13
Sybase error code	1802

Probable cause

You tried to access a dbspace that the database server could not find.

Dbospace for table '%1' not found

Error constant	SQLE_DBSPACE_FOR_TABLE_UNAVAILABLE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the table whose dbspace could not be found.
Severity	11
SQLCODE	-821
SQLSTATE	52W19
Sybase error code	13827

Probable cause

You tried to access a table in a dbspace that the database server could not find. You may need to change the file name associated with the dbspace using the ALTER DBSPACE statement.

Deadlock detected

Error constant	SQLE_DEADLOCK
ODBC 2 State	40001
ODBC 3 State	40001
Severity	13
SQLCODE	-306
SQLSTATE	40001
Sybase error code	1205

Probable cause

You attempted to read or write a row and it is locked by another user. Also, the other user is blocked directly or indirectly on your own transaction. This is a deadlock situation and your transaction has been chosen as the one to rollback.

Decompression error: %1

Error constant	SQLE_DECOMPRESSION_ERROR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Error message.
Severity	16
SQLCODE	–960
SQLSTATE	WW038
Sybase error code	13530

Probable cause

An error occurred during decompression.

Decryption error: %1

Error constant	SQLE_DECRYPT_ERROR
ODBC 2 State	08001
ODBC 3 State	08001
Parameter 1	Description of the error that occurred.
Severity	11
SQLCODE	–851
SQLSTATE	08W63
Sybase error code	13855

Probable cause

An error occurred during decryption.

Default dbspace '%1' not found

Error constant	SQLE_DEFAULT_DBSPACE_NOT_FOUND
ODBC 2 State	S0002
ODBC 3 State	42S02
Parameter 1	Name of the default dbspace that could not be found.
Severity	11
SQLCODE	-1068
SQLSTATE	52W43
Sybase error code	13446

Probable cause

You tried to create a table with the default_dbspace option set to a dbspace that could not be found.

Definition for alias '%1' must appear before its first reference

Error constant	SQLE_ALIAS_NOT_YET_DEFINED
ODBC 2 State	37000
ODBC 3 State	ERROR
Parameter 1	Name of the alias.
Severity	15
SQLCODE	-831
SQLSTATE	42W61
Sybase error code	13837

Probable cause

An expression contains a reference to an alias, but the alias is defined later in the select list. The alias definition must appear before its first reference.

Derived table '%1' has no name for column %2

Error constant	SQLE_NO_COLUMN_NAME
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Name of the derived table.
Parameter 2	Number of the column for which there is no name.
Severity	16
SQLCODE	-163
SQLSTATE	52004
Sybase error code	209

Probable cause

The specified column of the derived table has no column name. Use a select list alias in the query specification or use a derived columns specifier.

Directory for output file does not exist

Error constant	SQLE_DIRECTORY_INACCESSIBLE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	20
SQLCODE	-978
SQLSTATE	WW047
Sybase error code	13511

Probable cause

The file cannot be written because the directory does not exist.

Disallowed language extension detected in syntax near '%1' on line %2

Error constant	SQLE_INVALID_SYNTAX_EXTENSION
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The word or symbol where the syntax has been detected.
Parameter 2	Line number.
Severity	16
SQLCODE	-627
SQLSTATE	0AW03
Sybase error code	538

Probable cause

The statement you are trying to execute contains syntax that is not allowed with the current setting of the option `sql_flagger_error_level`. Modify the offending statement or set the `sql_flagger_error_level` option to a different value.

Disk full '%1' -- transaction rolled back

Error constant	SQLE_DEVICE_FULL
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the file that could not be written to the disk.
Severity	17
SQLCODE	-304
SQLSTATE	40W03
Sybase error code	3618

Probable cause

Your hard disk is out of space. A ROLLBACK statement has been automatically executed.

Disk write failure '%1' -- transaction rolled back

Error constant	SQLE_DISK_WRITE_FAILED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the file that could not be written.
Severity	21
SQLCODE	-303
SQLSTATE	40W05
Sybase error code	13868

Probable cause

A disk write failed. A ROLLBACK statement has been automatically executed.

Division by zero

Error constant	SQLE_DIV_ZERO_ERROR
ODBC 2 State	22012
ODBC 3 State	22012
Severity	16
SQLCODE	-628
SQLSTATE	22012
Sybase error code	36007

Probable cause

A division by zero operation was detected.

Download failed because of conflicts with existing rows

Error constant	SQLE_DOWNLOAD_CONFLICT
----------------	------------------------

ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	-839
SQLSTATE	0AW11
Sybase error code	13845

Probable cause

You attempted a download-only synchronization with modified rows in the UltraLite database. There was a conflict between one or more rows in the download stream and rows in the UltraLite database.

DTC transactions are not supported on this platform

Error constant	SQLE_DTC_TRANSACTIONS_NOT_SUPPORTED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-799
SQLSTATE	0AW10
Sybase error code	13809

Probable cause

You tried to enlist a DTC transaction on a platform that does not support this feature.

Duplicate attribute '%1' in service

Error constant	SQLE_SERVICE_PARM_DUPLICATE_PROPERTY
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the duplicate attribute.

Severity	16
SQLCODE	-1025
SQLSTATE	42WB0
Sybase error code	13485

Probable cause

The service definition contains a duplicate attribute.

Duplicate insert column

Error constant	SQLE_DUPLICATE_INSERT_COLUMN
ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	-637
SQLSTATE	42W41
Sybase error code	264

Probable cause

You supplied a duplicate column name in the list of insert columns.

Duplicate key column (%1)

Error constant	SQLE_DUPLICATE_KEY_COLUMN
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	The name of the duplicate column.
Severity	16
SQLCODE	-1085

SQLSTATE	42WC0
Sybase error code	13429

Probable cause

You supplied a duplicate column name in the list of columns for the key of a primary key, foreign key, or unique constraint, or an index.

Duplicate options not allowed in the CREATE DATABASE statement

Error constant	SQL_E_DUPLICATE_CREATE_DB_OPTION
ODBC 2 State	S0002
ODBC 3 State	ERROR
Severity	11
SQLCODE	-1221
SQLSTATE	42U08
Sybase error code	13296

Probable cause

You have specified one of the options more than once when executing the CREATE DATABASE statement.

Duplicate referencing column

Error constant	SQL_E_DUPLICATE_REFERENCING_COLUMN
ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	-636
SQLSTATE	42W40
Sybase error code	1909

Probable cause

You supplied a duplicate column name in the list of referencing columns.

Dynamic memory exhausted

Error constant	SQLE_DYNAMIC_MEMORY_EXHAUSTED
ODBC 2 State	S1001
ODBC 3 State	HY001
Severity	17
SQLCODE	-78
SQLSTATE	08W26
Sybase error code	9119

Probable cause

A failure occurred when the database server was trying to allocate dynamic memory.

Encryption error: %1

Error constant	SQLE_ENCRYPT_ERROR
ODBC 2 State	08001
ODBC 3 State	08001
Parameter 1	Description of the error that occurred.
Severity	11
SQLCODE	-895
SQLSTATE	08W66
Sybase error code	13589

Probable cause

An error occurred during encryption.

Encryption has not been enabled

Error constant	SQLE_ENCRYPTION_NOT_ENABLED_WARNING
ODBC 2 State	OK
ODBC 3 State	OK
Severity	10
SQLCODE	140
SQLSTATE	01005
Sybase error code	13369

Probable cause

An encryption key was provided, but encryption has not been enabled, nor is the database encrypted.

Encryption has not been enabled

Error constant	SQLE_ENCRYPTION_NOT_ENABLED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1143
SQLSTATE	55W27
Sybase error code	13370

Probable cause

You attempted to use encryption without first enabling it. Call `ULEnableStrongEncryption` to enable encryption.

Error creating text index \"%1\" on table \"%2\"

Error constant	SQLE_TEXT_INDEX_CREATION_ERROR
ODBC 2 State	ERROR

ODBC 3 State	ERROR
Parameter 1	The name of the text index.
Parameter 2	The name of the table.
Severity	16
SQLCODE	-1165
SQLSTATE	WT010
Sybase error code	13348

Probable cause

There was an internal error creating a text index.

Error during backup/restore: %1

Error constant	SQLE_BACKUP_ERROR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	A message describing the error that occurred.
Severity	21
SQLCODE	-697
SQLSTATE	08W46
Sybase error code	13720

Probable cause

An error occurred during a BACKUP or RESTORE statement.

Error in assignment

Error constant	SQLE_ERROR_IN_ASSIGNMENT
ODBC 2 State	22005

ODBC 3 State	22018
Severity	20
SQLCODE	-641
SQLSTATE	22005
Sybase error code	8205

Probable cause

In a GET DESCRIPTOR statement, the data type of the host variable must correspond to the data type of the descriptor item.

Error number %1 for RAISERROR must not be less than 17000

Error constant	SQLE_ERROR_NUMBER_OUT_OF_RANGE
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Error number.
Severity	16
SQLCODE	-296
SQLSTATE	53W07
Sybase error code	2732

Probable cause

You supplied an invalid error number in a RAISERROR statement. The number must be greater than or equal to 17000.

Error opening cursor

Error constant	SQLE_OPEN_CURSOR_ERROR
ODBC 2 State	24000
ODBC 3 State	24000

Severity	15
SQLCODE	-171
SQLSTATE	07003
Sybase error code	102

Probable cause

You attempted to open a cursor on a statement that is not SELECT, CALL or EXEC.

Error parsing connection parameter string

Error constant	SQLE_GEN_PARSE_ERROR
ODBC 2 State	08001
ODBC 3 State	08001
Severity	16
SQLCODE	-655
SQLSTATE	08W38
Sybase error code	13707

Probable cause

The connection string could not be parsed. The string or connection parameter file contains a syntax error.

Error writing to transaction log file

Error constant	SQLE_ERROR_WRITING_LOG
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	17
SQLCODE	-107
SQLSTATE	08W17

Sybase error code	3619
-------------------	------

Probable cause

The database server got an I/O error writing the transaction log file. The disk may be full or the log file name could be invalid.

Escape character conflict '%1'

Error constant	SQLE_ESCAPE_CHARACTER_CONFLICT
ODBC 2 State	S1000
ODBC 3 State	2200B
Parameter 1	The escape character that is invalid.
Severity	16
SQLCODE	-1137
SQLSTATE	2200B
Sybase error code	13376

Probable cause

The specified escape character cannot be used.

Event '%1' already exists

Error constant	SQLE_EVENT_ALREADY_EXISTS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the event that already exists.
Severity	16
SQLCODE	-772
SQLSTATE	WE002
Sybase error code	13782

Probable cause

You have attempted to create an event with a name that already exists in the database.

Event '%1' in use

Error constant	SQLE_EVENT_IN_USE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the event that is in use.
Severity	16
SQLCODE	-835
SQLSTATE	WE009
Sybase error code	13841

Probable cause

You have attempted to drop an event that is currently in use.

Event '%1' not found

Error constant	SQLE_EVENT_NOT_FOUND
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the event that could not be found.
Severity	11
SQLCODE	-771
SQLSTATE	WE001
Sybase error code	13781

Probable cause

You have attempted to reference an event with a name that does not exist in the database.

Event notification queue '%1' is full, notification discarded

Error constant	SQLE_EVENT_NOTIFICATION_QUEUE_FULL
ODBC 2 State	OK
ODBC 3 State	OK
Parameter 1	The name of the event notification queue
Severity	10
SQLCODE	146
SQLSTATE	WE011
Sybase error code	13785

Probable cause

The named queue is full and will not receive any event notifications until notifications are read from the queue. The pending notification has been discarded.

Event notification queue '%1' not found

Error constant	SQLE_EVENT_NOTIFICATION_QUEUE_NOT_FOUND
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the event notification queue
Severity	11
SQLCODE	-1263
SQLSTATE	WE014
Sybase error code	13247

Probable cause

The named event notification queue was not found. The operation failed.

Event notification queue '%1' not found warning

Error constant	SQLE_EVENT_NOTIFICATION_QUEUE_NOT_FOUND_WARN
ODBC 2 State	OK
ODBC 3 State	OK
Parameter 1	The name of the event notification queue
Severity	10
SQLCODE	148
SQLSTATE	WE013
Sybase error code	13248

Probable cause

The named event notification queue was not found. The operation will be skipped.

Event notifications lost on queue '%1'

Error constant	SQLE_EVENT_NOTIFICATIONS_LOST
ODBC 2 State	OK
ODBC 3 State	OK
Parameter 1	The name of the event notification queue
Severity	10
SQLCODE	147
SQLSTATE	WE012
Sybase error code	13249

Probable cause

Event notifications have been lost on the named queue. This occurs if there are pending notifications when the queue is destroyed. The notifications are discarded.

Event object name '%1' is not valid

Error constant	SQLE_INVALID_EVENT_OBJECT_NAME
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the event object
Severity	16
SQLCODE	-1264
SQLSTATE	WE015
Sybase error code	13246

Probable cause

The given name is not valid for an event object (notification queue or user event). Names are limited in length to 32 characters (bytes), and may not contain certain characters, like '*' or '@'.

Event object named '%1' already exists

Error constant	SQLE_EVENT_OBJECT_ALREADY_EXISTS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the event object
Severity	16
SQLCODE	-1265
SQLSTATE	WE016
Sybase error code	13245

Probable cause

An event object (notification queue or user event) with the given name already exists.

Event parameter '%1' not found

Error constant	SQLE_EVENT_PARAMETER_NOT_FOUND
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the event parameter
Severity	11
SQLCODE	-1267
SQLSTATE	WE018
Sybase error code	13243

Probable cause

The named event parameter was not found in the event notification.

Exceeded maximum of '%1' allowable parameters

Error constant	SQLE_INVALID_MAXIMUM_PARAMETERS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The maximum number of allowable parameters
Severity	16
SQLCODE	-1122
SQLSTATE	WW084
Sybase error code	13391

Probable cause

The maximum allowable parameters for the given web client procedure or function has been exceeded .

Exception occurred while loading Java SecurityManager

Error constant	SQLE_JAVA_SECMGR_EXCEPTION
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-848
SQLSTATE	WJ028
Sybase error code	13854

Probable cause

A Java exception occurred while loading the Java SecurityManager for this connection.

Expression has unsupported data type

Error constant	SQLE_DATATYPE_NOT_ALLOWED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	14
SQLCODE	-624
SQLSTATE	WW009
Sybase error code	10356

Probable cause

Either an external function or Java method is declared to have a parameter or result data type that is not supported, or a Java field reference with an unsupported result type was attempted.

External environment '%1' could not be found

Error constant	SQLE_EXTERN_ENV_NOT_FOUND
ODBC 2 State	ERROR

ODBC 3 State	ERROR
Parameter 1	Name of the external environment.
Severity	11
SQLCODE	-1205
SQLSTATE	WJ030
Sybase error code	13310

Probable cause

You attempted to define an object for an external environment that has not been added.

External environment could not be started, '%1' could not be found

Error constant	SQLE_EXTENV_NOT_STARTED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The component (executable or file) that could not be found and is needed to run the VM.
Severity	16
SQLCODE	-675
SQLSTATE	WP006
Sybase error code	13747

Probable cause

A problem was encountered starting the External Environment. A component that is needed to run the environment could not be found.

External environment does not support result sets

Error constant	SQLE_EXTERN_ENV_NO_RESULT_SET_SUPPORT
ODBC 2 State	ERROR

ODBC 3 State	ERROR
Severity	11
SQLCODE	-1213
SQLSTATE	WJ031
Sybase error code	13301

Probable cause

You attempted to define dynamic result sets for an external environment that does not support result sets.

External environments are not supported for this database

Error constant	SQLE_EXTERN_ENV_UPGRADE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1206
SQLSTATE	WW104
Sybase error code	13309

Probable cause

The current database does not have catalog support for external environments. To use this feature, upgrade your database to the most recent version.

External library '%1' is in use

Error constant	SQLE_EXTERNAL_LIBRARY_IN_USE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The external library that is in use
Severity	16

SQLCODE	-1214
SQLSTATE	WW108
Sybase error code	13897

Probable cause

The external library cannot be unloaded as it is currently in use.

External library '%1' not loaded

Error constant	SQLE_EXTERNAL_LIBRARY_NOT_LOADED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The external library that is not loaded
Severity	16
SQLCODE	-1215
SQLSTATE	WW109
Sybase error code	13895

Probable cause

The external library cannot be unloaded as it is not current loaded.

External login for server '%1' could not be found

Error constant	SQLE_OMNI_EXTLOGIN_NOT_FOUND
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the remote server.
Severity	11
SQLCODE	-712

SQLSTATE	WO013
Sybase error code	11221

Probable cause

An external login for the server and user does not exist.

External object '%1' not found

Error constant	SQLE_EXTENV_OBJECT_NOT_FOUND
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	Name of the Java class or external object.
Severity	16
SQLCODE	-810
SQLSTATE	42W57
Sybase error code	13820

Probable cause

The Java class or external object with this name does not exist in the database.

Failed to convert from character set '%1' to '%2'

Error constant	SQLE_FAILED_TO_CONVERT_CHARSET
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The character set of the input string.
Parameter 2	The character set of the output string.
Severity	16
SQLCODE	-1075

SQLSTATE	WC011
Sybase error code	13439

Probable cause

The server failed to convert between the two specified character sets. This could happen when the dbicu and dbicudt DLLs are not installed.

Feature '%1' not implemented

Error constant	SQLE_NOT_IMPLEMENTED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The unimplemented feature.
Severity	16
SQLCODE	-134
SQLSTATE	0A000
Sybase error code	401

Probable cause

You attempted to carry out an operation or use a feature that is not implemented in this version of SQL Anywhere.

Feature not available with UltraLite

Error constant	SQLE_NOT_SUPPORTED_IN_ULTRALITE
ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	-749
SQLSTATE	0AW07

Sybase error code	13762
-------------------	-------

Probable cause

You attempted to execute a statement or use a feature that is not supported in an UltraLite database.

Feature not supported by the client version or the client interface

Error constant	SQLE_NOT_SUPPORTED_BY_CLIENT
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1148
SQLSTATE	0AW19
Sybase error code	13363

Probable cause

You have attempted to use a feature which the server supports but the client does not. In order to use the feature, you must upgrade the client library or use a different client interface. Some features are not supported by the JConnect or Open Client client interfaces.

Field '%1' of class '%2' cannot be NULL

Error constant	SQLE_FIELD_CANNOT_BE_NULL
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the field that cannot be NULL.
Parameter 2	The name of the class that has the field.
Severity	16
SQLCODE	-649
SQLSTATE	WW015

Sybase error code	13741
-------------------	-------

Probable cause

An attempt was made to store a SQL NULL value in a Java object field that has a Java type that cannot be NULL. For example, the Java 'int' type cannot be NULL.

File I/O failed for '%1'

Error constant	SQLE_DEVICE_IO_FAILED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The file name.
Severity	16
SQLCODE	-974
SQLSTATE	WW043
Sybase error code	13959

Probable cause

An error occurred while trying to access the file. If the file is located on a removable media card, the card may have been removed.

File system error: %1

Error constant	SQLE_OMNI_FILE_SYSTEM_ERROR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Error description.
Severity	12
SQLCODE	-1066
SQLSTATE	WO027

Sybase error code	13448
-------------------	-------

Probable cause

This error results from an error in the underlying file system that was encountered while accessing a file directory as a proxy table.

FOR UPDATE has been incorrectly specified for a READ ONLY cursor

Error constant	SQLE_NON_UPDATEABLE_CURSOR
ODBC 2 State	42000
ODBC 3 State	42000
Severity	15
SQLCODE	-813
SQLSTATE	42W36
Sybase error code	7301

Probable cause

You attempted to declare a cursor FOR UPDATE on a query that is not updatable. Queries that contain DISTINCT, GROUP BY, HAVING, INTERSECT, EXCEPT, or UNION, or that contain aggregate functions are read-only. If the ansi_update_constraints option is on, then queries that contain a join are read-only. If the query references a view then the view may be non-updatable.

Foreign key '%1' for table '%2' duplicates an existing foreign key

Error constant	SQLE_DUPLICATE_FOREIGN_KEY
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	The role name of the new foreign key.
Parameter 2	The table containing the foreign key.
Severity	16

SQLCODE	-251
SQLSTATE	52W06
Sybase error code	1909

Probable cause

You attempted to define a foreign key that already exists.

Foreign key columns do not match the primary key or a uniqueness constraint in \"%1\

Error constant	SQLE_NO_MATCHING_INDEX
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the primary table.
Severity	16
SQLCODE	-1226
SQLSTATE	42R04
Sybase error code	13291

Probable cause

An attempt was made to create a foreign key, but the columns specified do not match the primary key or a uniqueness constraint for the referenced table.

Foreign key name '%1' not found

Error constant	SQLE_FOREIGN_KEY_NAME_NOT_FOUND
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Name of the non-existing foreign key.
Severity	15

SQLCODE	-145
SQLSTATE	52W07
Sybase error code	102

Probable cause

You misspelled the name of a foreign key, or the foreign key does not exist.

Format string argument number %1 is invalid

Error constant	SQLE_INVALID_FORMAT_STRING_ARG_NUM
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Argument number.
Severity	16
SQLCODE	-294
SQLSTATE	53W08
Sybase error code	2749

Probable cause

You supplied an invalid argument number in the format string for a PRINT or RAISERROR statement. The number must be between 1 and 20 and must not exceed the number of arguments provided.

Frame not allowed for window '%1'

Error constant	SQLE_FRAME_NOT_ALLOWED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the window or function.
Severity	16
SQLCODE	-950

SQLSTATE	42WA6
Sybase error code	13538

Probable cause

Frames are not allowed on rank functions or on windows referenced from inline window specifications.

Function '%1' has invalid parameter '%2' ('%3')

Error constant	SQLE_INVALID_PARAMETER_W_PARM
ODBC 2 State	08004
ODBC 3 State	08004
Parameter 1	The name of the function.
Parameter 2	The name of the parameter.
Parameter 3	Information about the parameter that caused the error.
Severity	18
SQLCODE	-1090
SQLSTATE	08W94
Sybase error code	13424

Probable cause

An error occurred while evaluating a parameter.

Function or column reference to '%1' in the ORDER BY clause is invalid

Error constant	SQLE_INVALID_ORDERBY_COLUMN
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Name of the column referenced directly, or in an expression, in the ORDER BY clause.

Severity	15
SQLCODE	–854
SQLSTATE	42W65
Sybase error code	104

Probable cause

You specified a function or column reference in the ORDER BY clause that is semantically invalid. For example, for DISTINCT queries the ORDER BY clause may only refer to items in the query's select list.

Function or column reference to '%1' must also appear in a GROUP BY

Error constant	SQLE_INVALID_GROUP_SELECT
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Name of the column referenced directly, or in an expression, that must be in the GROUP BY clause.
Severity	15
SQLCODE	–149
SQLSTATE	53003
Sybase error code	7321

Probable cause

You used a non-aggregate function or column reference in the select list or in a nested query block that does not appear in the GROUP BY clause. In a query using GROUP BY, select list items that are not aggregate functions must also appear in the GROUP BY clause. If the select list item is a column reference or an alias, you may add the column name or alias to the GROUP BY clause. If the select list item is a scalar function, ensure that the function's arguments in the GROUP BY clause match exactly with those in the select list. In some cases, you may want to use the MAX function on the column name (or another aggregate function) instead of adding the column to the GROUP BY clause.

GRANT of column permission on view not allowed

Error constant	SQLE_NO_COLUMN_PERMS_FOR_VIEWS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	15
SQLCODE	–635
SQLSTATE	52W22
Sybase error code	102

Probable cause

You cannot grant permissions on columns for views.

Grouped query contains more than one distinct aggregate function

Error constant	SQLE_INVALID_DISTINCT_AGGREGATE
ODBC 2 State	37000
ODBC 3 State	42000
Severity	15
SQLCODE	–863
SQLSTATE	42W70
Sybase error code	13867

Probable cause

Two or more DISTINCT aggregate functions were specified in the same grouped query. This is only permitted if the Hash Group By operator is available. Any query block can only contain at most one DISTINCT aggregate function if the Hash Group By operator is not available.

Host variable reference in service definition must be named

Error constant	SQLE_HOSTVAR_MUST_BE_NAMED
----------------	----------------------------

ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-926
SQLSTATE	42W9B
Sybase error code	13559

Probable cause

You have attempted to create a service with an unnamed host variable reference.

Host variables must not be used within a batch

Error constant	SQLE_HOSTVARS_IN_BATCH
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	15
SQLCODE	-807
SQLSTATE	07W07
Sybase error code	13817

Probable cause

You have attempted to execute a batch that contains host variable references. Host variables are not supported within a batch.

HTTP request failed. Status code '%1'

Error constant	SQLE_HTTP_REQUEST_FAILED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The HTTP status code.

Severity	19
SQLCODE	–983
SQLSTATE	WW052
Sybase error code	13506

Probable cause

The HTTP request returned a status code that indicated failure.

I/O error %1 -- transaction rolled back

Error constant	SQLE_DEVICE_ERROR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	A message describing the error that occurred.
Severity	24
SQLCODE	–305
SQLSTATE	40W04
Sybase error code	3013

Probable cause

SQL Anywhere has detected a problem with your hard disk. A ROLLBACK statement has been automatically executed.

Identifier '%1' too long

Error constant	SQLE_IDENTIFIER_TOO_LONG
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	The identifier that is too long.
Severity	15

SQLCODE	-250
SQLSTATE	54003
Sybase error code	103

Probable cause

An identifier was specified is longer than 128 bytes.

Identity attribute mismatch for column '%1'

Error constant	SQLE_OMNI_IDENTITY_MISMATCH
ODBC 2 State	OK
ODBC 3 State	OK
Parameter 1	The name of the column.
Severity	16
SQLCODE	-725
SQLSTATE	WO019
Sybase error code	11212

Probable cause

The identity attribute of the column specified in the CREATE EXISTING statement differs from the identity attribute of the actual column.

Illegal column definition: %1

Error constant	SQLE_ILLEGAL_COLUMN_DEFINITION
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	A message describing the error that occurred.
Severity	16
SQLCODE	-1046

SQLSTATE	55W19
Sybase error code	13465

Probable cause

You are attempting to define a column in a way that is not allowed.

Illegal column name: '%1'

Error constant	SQLE_BAD_FOR_XML_EXPLICIT_COLUMN_NAME
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The reason the column name was illegal.
Severity	16
SQLCODE	-899
SQLSTATE	WX007
Sybase error code	13582

Probable cause

FOR XML EXPLICIT column names can consist of up to four fields separated by exclamation marks. The first two columns must be named Tag and Parent.

Illegal cursor operation attempt

Error constant	SQLE_CURSOROP_NOT_ALLOWED
ODBC 2 State	07005
ODBC 3 State	07005
Severity	16
SQLCODE	-187
SQLSTATE	09W02
Sybase error code	9526

Probable cause

You attempted an illegal cursor operation. For example, you may be attempting to OPEN a cursor for a statement that is neither a SELECT nor a BATCH.

Illegal flags value passed to OPENXML

Error constant	SQLE_BAD_OPENXML_FLAG
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-893
SQLSTATE	WX004
Sybase error code	13590

Probable cause

The flags value passed to OPENXML as the third argument must be either 1 (attribute-centric mapping), or 2 (element-centric mapping).

Illegal FOR XML EXPLICIT tag value: '%1'

Error constant	SQLE_BAD_FOR_XML_EXPLICIT_TAG
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The illegal tag value.
Severity	16
SQLCODE	-897
SQLSTATE	WX005
Sybase error code	13584

Probable cause

FOR XML EXPLICIT tag values must be greater than 0 and less than 256. Also, NULL values are not allowed in the Tag column.

Illegal ORDER BY in aggregate function

Error constant	SQLE_INVALID_ORDERBY_IN_AGGREGATE
ODBC 2 State	37000
ODBC 3 State	42000
Severity	15
SQLCODE	-904
SQLSTATE	42W90
Sybase error code	13579

Probable cause

An ORDER BY can be used in an aggregate function only if there are no DISTINCT aggregates in the select list, or there is a single DISTINCT aggregate with the DISTINCT column equal to the first column of the ORDER BY. Also, multiple ordered aggregates cannot be used in the same select list unless they have the exact same ORDER BY clause.

Illegal reference to correlation name '%1'

Error constant	SQLE_INVALID_CORRELATION_NAME_REFERENCE
ODBC 2 State	S0002
ODBC 3 State	42S02
Parameter 1	The correlation name that is incorrectly referenced.
Severity	15
SQLCODE	-824
SQLSTATE	42U01
Sybase error code	13830

Probable cause

Your query contains a reference in a table expression to a correlation name that is not contained in that table expression.

Illegal user selectivity estimate specified

Error constant	SQLE_INVALID_USER_ESTIMATE
ODBC 2 State	01000
ODBC 3 State	01000
Severity	10
SQLCODE	118
SQLSTATE	01W16
Sybase error code	13617

Probable cause

You specified a user selectivity estimate that is either not a literal constant or is outside the range 0.0 to 100.0 (estimates are specified as percentages). The estimate has been ignored.

Immediate materialized view definition cannot contain a SUM function over a nullable expression

Error constant	SQLE_UPDATABLE_MATVIEW_SUM_NULL_EXPR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	15
SQLCODE	-1286
SQLSTATE	42WCD
Sybase error code	13668

Probable cause

You attempted to change the refresh type to immediate for a materialized view whose definition contains a SUM function over a nullable expression.

Incomplete transactions prevent transaction log renaming

Error constant	SQLE_BACKUP_CANNOT_RENAME_LOG_YET
----------------	-----------------------------------

ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	20
SQLCODE	-242
SQLSTATE	WB003
Sybase error code	3206

Probable cause

The last page in the transaction log was read by a call to `db_backup`. One or more currently active connections have partially completed transactions, preventing the transaction log file from being renamed. Reissue the `db_backup` call.

Incorrect database store DLL (%1) version

Error constant	SQLE_STORE_VERSION_MISMATCH
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the database store DLL.
Severity	19
SQLCODE	-711
SQLSTATE	08W47
Sybase error code	13701

Probable cause

The database store DLL and server DLL versions do not match.

Incorrect or missing encryption key

Error constant	SQLE_BAD_ENCRYPTION_KEY
ODBC 2 State	08001

ODBC 3 State	08001
Severity	21
SQLCODE	-840
SQLSTATE	08W62
Sybase error code	16846

Probable cause

The database is encrypted with a key. There was no key given to start the database, or the key given was incorrect.

Incorrect volume ID for '%1'

Error constant	SQLE_INCORRECT_VOLUME_ID
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The file name.
Severity	16
SQLCODE	-975
SQLSTATE	WW044
Sybase error code	13960

Probable cause

The file can be accessed, but the volume ID has changed. Please insert the original removable media card.

Index '%1' can not be clustered

Error constant	SQLE_CLUSTERED_INDEX_NOT_ALLOWED
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	Name of the index that could not be made clustered.

Severity	16
SQLCODE	-878
SQLSTATE	42W74
Sybase error code	13889

Probable cause

You attempted to create a clustered index (including key indexes) but the new index cannot be created, for example, because the table already has a clustered index.

Index '%1' for table '%2' would not be unique

Error constant	SQLE_INDEX_NOT_UNIQUE
ODBC 2 State	23000
ODBC 3 State	23000
Parameter 1	Name of the index that would not be unique.
Parameter 2	Name of the table that contains the index.
Severity	16
SQLCODE	-196
SQLSTATE	23505
Sybase error code	548

Probable cause

You attempted to insert or update a row that has the same value as another row in some column, and there is a constraint that does not allow two rows to have the same value in that column.

Index '%1' has no columns

Error constant	SQLE_INDEX_HAS_NO_COLUMNS
ODBC 2 State	37000
ODBC 3 State	42000

Parameter 1	The name of the index.
Severity	16
SQLCODE	-1274
SQLSTATE	0EW01
Sybase error code	13884

Probable cause

You attempted to create an index without columns.

Index name '%1' is ambiguous

Error constant	SQLE_AMBIGUOUS_INDEX_NAME
ODBC 2 State	S0011
ODBC 3 State	42S11
Parameter 1	Name of the ambiguous index.
Severity	16
SQLCODE	-678
SQLSTATE	52W40
Sybase error code	1921

Probable cause

A statement has referred to an index name that is not unique. Preface the index name with the table and/or owner name.

Index name '%1' not unique

Error constant	SQLE_INDEX_NAME_NOT_UNIQUE
ODBC 2 State	S0011
ODBC 3 State	42S11
Parameter 1	Name of the invalid index.

Severity	16
SQLCODE	-111
SQLSTATE	52W04
Sybase error code	1921

Probable cause

You attempted to create an index with the same name as an existing index.

Index type specification of '%1' is invalid

Error constant	SQLE_INVALID_INDEX_TYPE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The index type specification that is invalid.
Severity	16
SQLCODE	-650
SQLSTATE	WW016
Sybase error code	13704

Probable cause

IQ index types can be specified for IQ indexes only. In UltraLite, you cannot specify indexes on LONG column types.

Index validation failed for table %1, index %2 with code: %3

Error constant	SQLE_CORRUPT_ULTRALITE_INDEX
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the table.
Parameter 2	The name of the index.

Parameter 3	The specific kind of corruption that was found.
Severity	23
SQLCODE	-1185
SQLSTATE	WI002
Sybase error code	13330

Probable cause

UltraLite database validation failed while validating the specified index. The code provides more specific information on the validation failure.

Information for synchronization is incomplete or invalid, check '%1'

Error constant	SQLE_SYNC_INFO_INVALID
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the parameter not properly initialized.
Severity	16
SQLCODE	-956
SQLSTATE	WW036
Sybase error code	13532

Probable cause

Information for synchronization is incomplete or invalid. Correct the indicated parameter before attempting to synchronize again. If init_verify is indicated, the UInitSynchInfo function was not called.

Information for synchronization was not provided

Error constant	SQLE_SYNC_INFO_REQUIRED
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Severity	16
SQLCODE	-1111
SQLSTATE	WW081
Sybase error code	13403

Probable cause

You must supply information for synchronization, either directly in the synchronization call or by using the SetSynchInfo call before synchronizing. In the Palm HotSync conduit, this error occurs during synchronization if you have not used the SetSynchInfo call in your application before exiting, or if the SetSynchInfo call failed.

Input parameter index out of range

Error constant	SQLE_BAD_PARAM_INDEX
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-689
SQLSTATE	WJ005
Sybase error code	13717

Probable cause

The range for valid parameters is from 1 up to the number of host variables specified in the prepared/callable statement.

Input string is not base64-encoded

Error constant	SQLE_BASE64_DECODING_ERROR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16

SQLCODE	-961
SQLSTATE	WW039
Sybase error code	13528

Probable cause

An error occurred during base64 decoding.

INSERT ... ON EXISTING UPDATE not allowed: immediate materialized view %1 depends on %2

Error constant	SQLE_UPDATE_ON_EXISTING_DEP_IMV
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of dependent immediate materialized view.
Parameter 2	The name of the base table into which the insert was performed.
Severity	16
SQLCODE	-1204
SQLSTATE	55W33
Sybase error code	13311

Probable cause

Insert statement with ON EXISTING clause is not permitted on a base table if the base table has dependent initialized immediate materialized view.

INSERT/DELETE on cursor can modify only one table

Error constant	SQLE_ONLY_ONE_TABLE
ODBC 2 State	37000
ODBC 3 State	42000
Severity	15

SQLCODE	-199
SQLSTATE	09W04
Sybase error code	102

Probable cause

You attempted to insert into a cursor and have specified values for more than one table, or you attempted to delete from a cursor that involves a join. Insert into one table at a time. For DELETE, use the FROM clause to specify the table you want to delete from.

Insufficient cache to start Java Virtual Machine

Error constant	SQLE_JAVA_VM_INSUFFICIENT_CACHE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-686
SQLSTATE	WP015
Sybase error code	13878

Probable cause

Insufficient cache was available to start the Java Virtual Machine. Restart the database server with a larger cache size.

Insufficient memory for OPENXML query

Error constant	SQLE_XQUERY_MEMORY_ERROR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	17
SQLCODE	-912
SQLSTATE	WX016

Sybase error code	13572
-------------------	-------

Probable cause

The memory used by an OPENXML query may be proportional to the maximum distance between elements or attributes returned by a single row. For example, a query where some row uses the value from both the first and last element in the document may use memory proportional to the size of the document. One solution is to increase the cache size. Another is to break a query that refers to distant elements into several queries that refer to nearby elements and join the results.

Integrated login failed

Error constant	SQLE_INTEGRATED_LOGON_FAILED
ODBC 2 State	28000
ODBC 3 State	28000
Severity	16
SQLCODE	-245
SQLSTATE	28W04
Sybase error code	13691

Probable cause

The integrated login failed. You may not have a system account on the server machine.

Integrated logins are not permitted

Error constant	SQLE_INVALID_STANDARD_LOGON
ODBC 2 State	28000
ODBC 3 State	28000
Severity	16
SQLCODE	-205
SQLSTATE	28W02
Sybase error code	13689

Probable cause

The login_mode database option is set to Standard, and you attempted an integrated login. Change the option setting or supply an explicit user ID.

Integrated logins are not supported for this database

Error constant	SQLE_INTEGRATED_LOGON_UNSUPPORTED
ODBC 2 State	28000
ODBC 3 State	28000
Severity	16
SQLCODE	-246
SQLSTATE	28W05
Sybase error code	13694

Probable cause

The current database is an older database and does not have the information to map integrated login IDs to database user IDs. You must upgrade your database to use integrated logins.

Integrated logins are required, standard logins are not permitted

Error constant	SQLE_INVALID_INTEGRATED_LOGON
ODBC 2 State	28000
ODBC 3 State	28000
Severity	16
SQLCODE	-206
SQLSTATE	28W03
Sybase error code	13690

Probable cause

The login_mode database option is set to Integrated, and you attempted a standard login. Change the option setting or use an integrated login.

Internal database error %1 -- transaction rolled back

Error constant	SQLE_DATABASE_ERROR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Identification of the error.
Severity	18
SQLCODE	-301
SQLSTATE	40W01
Sybase error code	13665

Probable cause

An internal database error occurred. If it can be reproduced, it should be reported to iAnywhere. A ROLLBACK statement has been automatically executed.

Internal rollback log corrupted

Error constant	SQLE_LOG_CORRUPTED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	22
SQLCODE	-311
SQLSTATE	WI004
Sybase error code	932

Probable cause

While processing a COMMIT or ROLLBACK, corruption was found in the internal rollback log. This is a fatal internal error.

Invalid absolute or relative offset in FETCH

Error constant	SQLE_INVALID_FETCH_POSITION
ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	-263
SQLSTATE	42W25
Sybase error code	6259

Probable cause

You specified an offset in a FETCH that was invalid or NULL.

Invalid backup operation

Error constant	SQLE_INVALID_BACKUP_OPERATION
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1021
SQLSTATE	WB013
Sybase error code	3206

Probable cause

The specified backup operation is not valid because of previous backup operation(s).

Invalid backup parameter value

Error constant	SQLE_INVALID_BACKUP_PARM_VALUE
ODBC 2 State	ERROR

ODBC 3 State	ERROR
Severity	16
SQLCODE	-1045
SQLSTATE	WB015
Sybase error code	13466

Probable cause

One or more of the parameters supplied to the backup operation has an invalid value.

Invalid class byte code

Error constant	SQLE_BAD_CLASS_BYTE_CODE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-670
SQLSTATE	WP005
Sybase error code	13746

Probable cause

A binary expression passed to the INSTALL JAVA statement was not a valid Java class.

Invalid collation: \"%1\"

Error constant	SQLE_TEXT_BAD_COLLATION
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The invalid collation string.
Severity	16

SQLCODE	-1163
SQLSTATE	WT008
Sybase error code	13350

Probable cause

The collation was not found, or the tailoring options were invalid.

Invalid column number

Error constant	SQL_INVALID_COLUMN_NUMBER
ODBC 2 State	42000
ODBC 3 State	42000
Severity	15
SQLCODE	-159
SQLSTATE	42W13
Sybase error code	182

Probable cause

You gave an invalid column number, or the column you are looking for is in a different table.

Invalid commit action for shared temporary table

Error constant	SQL_INVALID_SHARED_COMMIT_ACTION
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1089
SQLSTATE	52W26
Sybase error code	13425

Probable cause

A global shared temporary table must be declared as ON COMMIT PRESERVE ROWS or NOT TRANSACTIONAL.

Invalid comparison

Error constant	SQLE_INVALID_COMPARISON
ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	-710
SQLSTATE	52W25
Sybase error code	13749

Probable cause

An attempt was made to compare two arguments that do not support comparison. For example, it is not valid to compare a Java object with another Java object, unless the class of the object supports a valid compareTo method.

Invalid data conversion

Error constant	SQLE_CANNOT_CONVERT
ODBC 2 State	01S01
ODBC 3 State	01S01
Severity	10
SQLCODE	103
SQLSTATE	01W03
Sybase error code	518

Probable cause

The database could not convert a value to the required type. The value being converted was either supplied to the database on an insert, update, or as a host bind variable, or was a value retrieved from the database into a host variable or SQLDA.

Invalid data conversion: NULL was inserted for column '%1' on row %2

Error constant	SQLE_CANNOT_CONVERT_LOAD_TABLE
ODBC 2 State	07006
ODBC 3 State	07006
Parameter 1	Name of the column where NULL was inserted.
Parameter 2	Row number in the data file where the invalid data conversion took place.
Severity	10
SQLCODE	124
SQLSTATE	01W01
Sybase error code	13886

Probable cause

The database could not convert a value to the required type. The value being converted was supplied to the database in a data file and inserted using LOAD TABLE. A NULL value has been inserted into the column.

Invalid data type for column in WRITETEXT or READTEXT

Error constant	SQLE_INVALID_TEXT_IMAGE_DATATYPE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-609
SQLSTATE	53W09
Sybase error code	7139

Probable cause

You referenced a column in a WRITETEXT or READTEXT statement that is not defined for storing text or image data.

Invalid database page size

Error constant	SQLE_PAGE_SIZE_INVALID
ODBC 2 State	42000
ODBC 3 State	42000
Severity	14
SQLCODE	-644
SQLSTATE	08W32
Sybase error code	927

Probable cause

You attempted to create a database with an invalid page size. The page size for a SQL Anywhere database must be either 2048, 4096, 8192, 16384, or 32768 bytes. The page size for an UltraLite database must be either 1024, 2048, 4096, 8192, or 16384 bytes.

Invalid database server command line

Error constant	SQLE_INVALID_COMMAND_LINE
ODBC 2 State	08001
ODBC 3 State	08001
Severity	18
SQLCODE	-81
SQLSTATE	08W08
Sybase error code	5864

Probable cause

It was not possible to start the database server because the command line was invalid.

Invalid day of week or month '%1' for event '%2'

Error constant	SQLE_INVALID_EVENT_DAY
----------------	------------------------

ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Day-of-week name or day-of-month number.
Parameter 2	Name of the event being scheduled.
Severity	15
SQLCODE	-791
SQLSTATE	WE005
Sybase error code	13801

Probable cause

You have attempted to create a schedule with an invalid day-of-week name or day-of-month number.

Invalid descriptor index

Error constant	SQLE_INVALID_DESCRIPTOR_INDEX
ODBC 2 State	S1002
ODBC 3 State	07009
Severity	26
SQLCODE	-640
SQLSTATE	07009
Sybase error code	8201

Probable cause

The index number used with respect to a descriptor area is out of range.

Invalid domain '%1'

Error constant	SQLE_INVALID_DOMAIN
ODBC 2 State	ERROR

ODBC 3 State	42000
Parameter 1	The invalid domain specification.
Severity	16
SQLCODE	-1275
SQLSTATE	54W52
Sybase error code	13881

Probable cause

You attempted to create an invalid domain. The size/scale/precision is invalid.

Invalid escape character '%1'

Error constant	SQLE_INVALID_ESCAPE_CHAR
ODBC 2 State	S1000
ODBC 3 State	22019
Parameter 1	The escape character that is invalid.
Severity	16
SQLCODE	-629
SQLSTATE	22019
Sybase error code	7707

Probable cause

The escape character string length must be exactly one.

Invalid escape sequence '%1'

Error constant	SQLE_INVALID_ESCAPE_SEQ
ODBC 2 State	S1000
ODBC 3 State	22025

Parameter 1	The escaped character.
Severity	16
SQLCODE	–630
SQLSTATE	22025
Sybase error code	7705

Probable cause

A LIKE pattern contains an invalid use of the escape character. The escape character may only precede the special characters '%', '_', '[', and the escape character itself.

Invalid expression in WHERE clause of Transact-SQL outer join

Error constant	SQLE_INVALID_TSQL_OJ_EXPRESSION
ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	–680
SQLSTATE	52W23
Sybase error code	301

Probable cause

An expression in the WHERE clause of a query that uses Transact-SQL syntax contains a comparison of a column from the NULL-supplying table with a subquery or an expression that references a column from another table.

Invalid expression near '%1'

Error constant	SQLE_EXPRESSION_ERROR
ODBC 2 State	37000
ODBC 3 State	42000

Parameter 1	The invalid expression.
Severity	16
SQLCODE	–156
SQLSTATE	42W08
Sybase error code	401

Probable cause

You supplied an expression that the database server cannot understand. For example, you may have tried to add two dates.

Invalid hint specified for table '%1'

Error constant	SQLE_INVALID_HINT
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	The name of the table for which the hint was specified.
Severity	15
SQLCODE	–970
SQLSTATE	42U07
Sybase error code	13520

Probable cause

A hint was specified for the current statement is not valid in this context. In a single statement, all references to a table must specify the same hint or none at all.

Invalid host variable

Error constant	SQLE_VARIABLE_INVALID
ODBC 2 State	37000
ODBC 3 State	42000

Severity	17
SQLCODE	-155
SQLSTATE	42W07
Sybase error code	7201

Probable cause

You supplied an invalid host variable to the database using the C language interface. You may have supplied the variable as a host variable or through a SQLDA.

Invalid IQ database command line option or parameter value: %1

Error constant	SQLE_IQ_INVALID_COMMAND_LINE
ODBC 2 State	08001
ODBC 3 State	08001
Parameter 1	The command line option that is invalid.
Severity	18
SQLCODE	-744
SQLSTATE	08W51
Sybase error code	13757

Probable cause

An invalid command line option was used. The option began with -iq, but is either invalid or contained a bad parameter.

Invalid JAR file

Error constant	SQLE_BAD_JAR_FILE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16

SQLCODE	-730
SQLSTATE	WP010
Sybase error code	13737

Probable cause

A file passed to the INSTALL JAVA statement was not a valid JAR file.

Invalid JDBC resultset concurrency

Error constant	SQLE_JDBC_INVALID_RESULTSET_CONCURRENCY
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-748
SQLSTATE	WJ018
Sybase error code	13761

Probable cause

An invalid resultset concurrency was used when creating a JDBC statement.

Invalid JDBC resultset type

Error constant	SQLE_JDBC_INVALID_RESULTSET_TYPE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-747
SQLSTATE	WJ017
Sybase error code	13760

Probable cause

An invalid resultset type was used when creating a JDBC statement.

Invalid join type used with Transact-SQL outer join

Error constant	SQLE_INVALID_TSQL_JOIN_TYPE
ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	-681
SQLSTATE	52W24
Sybase error code	305

Probable cause

An invalid join type was used with a query that contains Transact-SQL outer join comparison operators.

Invalid local database option

Error constant	SQLE_INVALID_LOCAL_OPTION
ODBC 2 State	08001
ODBC 3 State	08001
Severity	18
SQLCODE	-79
SQLSTATE	08W25
Sybase error code	5864

Probable cause

An invalid database option was found in the DBS (DatabaseSwitches) connection parameter.

Invalid mime type '%1'

Error constant	SQLE_INVALID_MIMETYPE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the mime type
Severity	16
SQLCODE	-1123
SQLSTATE	WW085
Sybase error code	13390

Probable cause

The mime type specifier is invalid.

Invalid operation on a closed '%1'

Error constant	SQLE_JDBC_OBJ_CLOSED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Java class of the closed object.
Severity	16
SQLCODE	-696
SQLSTATE	WJ010
Sybase error code	13605

Probable cause

An illegal attempt was made to access a closed JDBC object.

Invalid operation on a closed '%1'

Error constant	SQLE_JNAT_OBJ_CLOSED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Java class of the closed object.
Severity	16
SQLCODE	-714
SQLSTATE	WJ014
Sybase error code	13609

Probable cause

An illegal attempt was made to access a closed native Java object.

Invalid operation on a closed object

Error constant	SQLE_ULTRALITE_OBJ_CLOSED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-908
SQLSTATE	55W14
Sybase error code	13575

Probable cause

An illegal attempt was made to access a closed UltraLite object.

Invalid option '%1' -- no PUBLIC setting exists

Error constant	SQLE_INVALID_OPTION
----------------	---------------------

ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Name of the invalid option.
Severity	15
SQLCODE	-200
SQLSTATE	42W16
Sybase error code	155

Probable cause

You may have misspelled the name of an option in the SET OPTION statement. You can only define an option for a user if the database administrator has supplied a PUBLIC value for that option.

Invalid ORDER BY specification

Error constant	SQLE_INVALID_ORDER
ODBC 2 State	37000
ODBC 3 State	42000
Severity	15
SQLCODE	-152
SQLSTATE	53005
Sybase error code	108

Probable cause

Either you used an integer in an ORDER BY list and the integer is larger than the number of columns in the select list, or you specified an ORDER BY expression that is semantically invalid. For example, with UNION queries you can only use integers to specify an ordering of the result.

Invalid parameter

Error constant	SQLE_INVALID_PARAMETER
ODBC 2 State	08004

ODBC 3 State	08004
Severity	18
SQLCODE	-735
SQLSTATE	08W24
Sybase error code	5864

Probable cause

An error occurred while evaluating a parameter.

Invalid password: %1

Error constant	SQLE_INVALID_NEW_PASSWORD
ODBC 2 State	28000
ODBC 3 State	28000
Parameter 1	Reason the password is invalid, or the reason attempting to call the function to verify the password failed.
Severity	16
SQLCODE	-1044
SQLSTATE	28W11
Sybase error code	13467

Probable cause

The attempt to create a new user ID or change a password failed. The function specified by the `verify_password_function` option disallowed the password.

Invalid preceding or following size in OLAP function

Error constant	SQLE_INVALID_FRAME_BOUNDARY
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Severity	16
SQLCODE	–957
SQLSTATE	22X13
Sybase error code	13531

Probable cause

The expression for the preceding or following size evaluated to NULL or a negative value.

Invalid prepared statement type

Error constant	SQLE_INVALID_STATEMENT_TYPE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	–133
SQLSTATE	07W03
Sybase error code	13630

Probable cause

This is an internal error. If it can be reproduced, it should be reported to iAnywhere.

Invalid procedure subtype '%1' for type '%2'

Error constant	SQLE_INVALID_PROCEDURE_SUBTYPE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The procedure subtype.
Parameter 2	The procedure type.
Severity	16

SQLCODE	-987
SQLSTATE	WW056
Sybase error code	13502

Probable cause

A procedure or function was specified with an invalid subtype for the given procedure type.

Invalid procedure type '%1'

Error constant	SQLE_INVALID_PROCEDURE_TYPE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The procedure type.
Severity	16
SQLCODE	-986
SQLSTATE	WW055
Sybase error code	13503

Probable cause

A procedure or function was specified with an invalid type.

Invalid recursive query

Error constant	SQLE_INVALID_RECURSION
ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	-921
SQLSTATE	42W99

Sybase error code	13563
-------------------	-------

Probable cause

A recursive query must consist of the UNION ALL of an initial query and an iteration query. The only set operation allowed in the iteration query is UNION ALL. A recursive reference to the name of the common table expression can only appear in the iteration query, and must not be in a SELECT that uses DISTINCT, ORDER BY, or an aggregate function. A recursive reference also cannot appear on the NULL-supplying side of an outer join, or in a subquery.

Invalid reference to or operation on constraint '%1'

Error constant	SQLE_INVALID_CONSTRAINT_REF
ODBC 2 State	S0002
ODBC 3 State	42S23
Parameter 1	Name of the constraint can not be used for the specified purpose.
Severity	16
SQLCODE	-937
SQLSTATE	42U06
Sybase error code	13550

Probable cause

You specified an invalid operation on a constraint. For example, you tried to alter a primary key constraint.

Invalid REFERENCES clause in trigger definition

Error constant	SQLE_INVALID_TRIGGER_COL_REFS
ODBC 2 State	37000
ODBC 3 State	42000
Severity	15
SQLCODE	-272
SQLSTATE	52W12

Sybase error code	102
-------------------	-----

Probable cause

You supplied an invalid REFERENCES clause in a trigger definition. You may have specified an OLD correlation name in a BEFORE INSERT trigger, or a NEW correlation name in an AFTER DELETE trigger. In both cases, the values do not exist and cannot be referenced.

Invalid regular expression: %1 in '%2'

Error constant	SQL_INVALID_REGULAR_EXPRESSION
ODBC 2 State	S1000
ODBC 3 State	2201B
Parameter 1	The reason the regular expression is invalid.
Parameter 2	The invalid regular expression.
Severity	16
SQLCODE	-1135
SQLSTATE	2201B
Sybase error code	13378

Probable cause

The specified regular expression is invalid.

Invalid request log format on line %1

Error constant	SQL_INVALID_REQUEST_LOG_FORMAT
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The line number in the log file.
Severity	16
SQLCODE	-999

SQLSTATE	WW020
Sybase error code	13493

Probable cause

The request log file format is invalid. The request log may have been created with an older version of the software.

Invalid response from the HTTP server

Error constant	SQLE_INVALID_HTTP_RESPONSE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	19
SQLCODE	-988
SQLSTATE	WW057
Sybase error code	13501

Probable cause

The response from the remote HTTP server was invalid. It may have been empty, malformed, missing header information, and so on.

Invalid scroll position '%1'

Error constant	SQLE_INVALID_POSITION
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The scroll position that is invalid.
Severity	16
SQLCODE	-820
SQLSTATE	24504

Sybase error code	13826
-------------------	-------

Probable cause

You attempted to scroll to a position that is not supported. Scroll positions must be between -2147483647 and 2147483646.

Invalid service name '%1'

Error constant	SQLE_INVALID_SERVICE_NAME
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the service.
Severity	16
SQLCODE	-925
SQLSTATE	42W95
Sybase error code	13560

Probable cause

You have attempted to create a service with an invalid name. The name may contain characters that are not allowed, or it may conflict with the URL PATH setting specified for the service.

Invalid setting for HTTP header '%1'

Error constant	SQLE_INVALID_HTTP_HEADER_SETTING
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Name of the invalid HTTP header.
Severity	16
SQLCODE	-940
SQLSTATE	42W84

Sybase error code	13547
-------------------	-------

Probable cause

You supplied an invalid value for an HTTP header.

Invalid setting for HTTP option '%1'

Error constant	SQLE_INVALID_HTTP_OPTION_SETTING
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Name of the invalid HTTP option.
Severity	16
SQLCODE	-939
SQLSTATE	42W83
Sybase error code	13548

Probable cause

You supplied an invalid value for an HTTP option. Some options allow only numeric values, while other options allow only the values On and Off.

Invalid setting for option '%1'

Error constant	SQLE_INVALID_OPTION_SETTING
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Name of the invalid option.
Severity	16
SQLCODE	-201
SQLSTATE	42W17
Sybase error code	5849

Probable cause

You supplied an invalid value for an option in the SET statement. Some options allow only numeric values, while other options allow only the values On and Off.

Invalid setting for SOAP header '%1'

Error constant	SQLE_INVALID_SOAP_HEADER_SETTING
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Name of the invalid SOAP header.
Severity	16
SQLCODE	-1114
SQLSTATE	42W86
Sybase error code	13400

Probable cause

You supplied an invalid value for a SOAP header.

Invalid SQL descriptor name

Error constant	SQLE_INVALID_DESCRIPTOR_NAME
ODBC 2 State	33000
ODBC 3 State	33000
Severity	21
SQLCODE	-642
SQLSTATE	33000
Sybase error code	601

Probable cause

You attempted to deallocate a descriptor that has not been allocated.

Invalid SQL identifier

Error constant	SQLE_INVALID_SQL_IDENTIFIER
ODBC 2 State	07001
ODBC 3 State	07W06
Severity	16
SQLCODE	-760
SQLSTATE	07W06
Sybase error code	13771

Probable cause

An invalid identifier was supplied through the C language interface. For example, you may have supplied a NULL string for a cursor name.

Invalid sqlen field in SQLDA

Error constant	SQLE_INVALID_SQLLEN
ODBC 2 State	HY090
ODBC 3 State	HY090
Severity	16
SQLCODE	-856
SQLSTATE	07W08
Sybase error code	13859

Probable cause

An invalid length was specified in a SQLDA sqlen field. All variable length types must have a non-negative length. The DT_BINARY and DT_VARCHAR types must have length greater than one.

Invalid start date/time for event '%1'

Error constant	SQLE_INVALID_EVENT_START
----------------	--------------------------

ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the event being scheduled.
Severity	15
SQLCODE	-793
SQLSTATE	WE007
Sybase error code	13803

Probable cause

You have specified an event starting date that is invalid.

Invalid statement

Error constant	SQLE_INVALID_STATEMENT
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-130
SQLSTATE	07W02
Sybase error code	13628

Probable cause

The statement identifier generated by a PREPARE passed to the database for a further operation is invalid.

Invalid TEXTPTR value used with WRITETEXT or READTEXT

Error constant	SQLE_INVALID_TEXTPTR_VALUE
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Severity	16
SQLCODE	-608
SQLSTATE	22W03
Sybase error code	7123

Probable cause

You supplied an invalid value as the TEXTPTR for a WRITETEXT or READTEXT statement.

Invalid time '%1' for event '%2'

Error constant	SQLE_INVALID_EVENT_TIME
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Time value.
Parameter 2	Name of the event being scheduled.
Severity	15
SQLCODE	-792
SQLSTATE	WE006
Sybase error code	13802

Probable cause

You have attempted to create a schedule with an invalid start or stop time.

Invalid trigger type for view '%1'

Error constant	SQLE_INVALID_TRIGGER_VIEW
ODBC 2 State	42000
ODBC 3 State	ERROR
Parameter 1	Name of the view

Severity	14
SQLCODE	-1133
SQLSTATE	42W3C
Sybase error code	13380

Probable cause

You attempted to create a trigger on a view, but the type of trigger is supported on base tables only. Only INSTEAD OF triggers can be created on views.

Invalid type for field reference

Error constant	SQLE_INVALID_FIELD_REFERENCE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-94
SQLSTATE	WW014
Sybase error code	13738

Probable cause

An expression attempted to reference a field or a method of a non-Java value. Field references via . and >> are only valid when applied to Java objects.

Invalid type on DESCRIBE statement

Error constant	SQLE_INVALID_DESCRIBE_TYPE
ODBC 2 State	OK
ODBC 3 State	OK
Severity	16
SQLCODE	-161

SQLSTATE	07W01
Sybase error code	13634

Probable cause

A Java type specified on a DESCRIBE statement has no corresponding SQL type.

Invalid use of an aggregate function

Error constant	SQLE_AGGREGATES_NOT_ALLOWED
ODBC 2 State	37000
ODBC 3 State	42000
Severity	15
SQLCODE	-150
SQLSTATE	42W06
Sybase error code	13204

Probable cause

You attempted to use an aggregate function inappropriately. For example, a SELECT statement cannot contain an aggregate function within a predicate in the WHERE clause unless the aggregate function constitutes an outer reference. Other invalid uses include specifying an aggregate function in the SET clause of an UPDATE statement, or using an aggregate function in a CHECK constraint.

Invalid use of escape character '%1'

Error constant	SQLE_INVALID_USE_OF_ESCAPE_CHARACTER
ODBC 2 State	S1000
ODBC 3 State	2200C
Parameter 1	The escape character that is invalid.
Severity	16
SQLCODE	-1136
SQLSTATE	2200C

Sybase error code	13377
-------------------	-------

Probable cause

The specified escape character cannot be used.

Invalid use of NEAR operator in text query

Error constant	SQLE_TEXT_INVALID_NEAR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1207
SQLSTATE	WT016
Sybase error code	13308

Probable cause

Only terms, prefixes, or other NEAR operators are allowed as arguments to a NEAR operator.

Invalid user ID or password

Error constant	SQLE_INVALID_LOGON
ODBC 2 State	28000
ODBC 3 State	28000
Severity	14
SQLCODE	-103
SQLSTATE	28000
Sybase error code	4002

Probable cause

You supplied an invalid user ID or an incorrect password.

Invalid user ID or password on preprocessed module

Error constant	SQLE_INVALID_MODULE_LOGON
ODBC 2 State	28000
ODBC 3 State	28000
Severity	14
SQLCODE	-104
SQLSTATE	28W01
Sybase error code	4002

Probable cause

You specified an invalid user ID or password when a module was preprocessed.

Invalid value for attribute '%1' in service

Error constant	SQLE_SERVICE_PARM_INVALID_VALUE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the invalid attribute.
Severity	16
SQLCODE	-1022
SQLSTATE	42WAD
Sybase error code	13488

Probable cause

The service definition contains a USING, FORMAT, or GROUP attribute with an invalid value.

Invalid XQuery constructor

Error constant	SQLE_INVALID_XQUERY_CONSTRUCTOR
----------------	---------------------------------

ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-905
SQLSTATE	WX012
Sybase error code	13578

Probable cause

The XQuery constructor passed as the first argument to XMLGEN was not valid.

Item '%1' already exists

Error constant	SQLE_NAME_NOT_UNIQUE
ODBC 2 State	S0001
ODBC 3 State	42S01
Parameter 1	Name of the item that already exists.
Severity	16
SQLCODE	-110
SQLSTATE	52010
Sybase error code	12006

Probable cause

You attempted to create a file, table, view, column, constraint, foreign key, or publication with the same name as an existing one.

JAR '%1' not found

Error constant	SQLE_JAR_NOT_FOUND
ODBC 2 State	42000
ODBC 3 State	42000

Parameter 1	Name of the JAR.
Severity	16
SQLCODE	-811
SQLSTATE	42W58
Sybase error code	13821

Probable cause

The JAR with this name does not exist in the database.

Java SecurityManager class not found: %1

Error constant	SQLE_JAVA_SECMGR_NOT_FOUND
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The class name of the Java SecurityManager.
Severity	16
SQLCODE	-847
SQLSTATE	WJ027
Sybase error code	13853

Probable cause

The class specified is either not a SecurityManager subclass or cannot be found.

Java VM heap exhausted at internal function: %1

Error constant	SQLE_JAVA_VM_HEAP_EXHAUSTED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The internal function is for debugging purposes.

Severity	16
SQLCODE	–165
SQLSTATE	WP008
Sybase error code	13740

Probable cause

The amount of space allocated for the Java VM is insufficient to continue allocating new objects. Increase the size by using: SET OPTION PUBLIC.java_heap_size = nnnnnnnn.

jConnect does not support encryption

Error constant	SQLE_NO_ENCRYPTION_FOR_JCONNECT
ODBC 2 State	08004
ODBC 3 State	08004
Severity	18
SQLCODE	–941
SQLSTATE	08W69
Sybase error code	13548

Probable cause

You supplied an encryption type for a connection using jConnect. jConnect does not support encryption.

JDBC feature '%1' not supported

Error constant	SQLE_UNSUPPORTED_JDBC_FEATURE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the attempted feature.
Severity	16
SQLCODE	–693

SQLSTATE	WJ007
Sybase error code	13602

Probable cause

An attempt was made to use a feature of JDBC that is not supported.

JDBC SAStatement batch execute abandoned

Error constant	SQLE_JDBC_BATCH_EXECUTE_ABANDONED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-742
SQLSTATE	WJ015
Sybase error code	13755

Probable cause

An error occurred when executing a statement in the batch. The rest of the statements in the batch will be abandoned.

JDK '%1' is not a supported JDK

Error constant	SQLE_UNSUPPORTED_JDK
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	A JDK version string.
Severity	16
SQLCODE	-842
SQLSTATE	WJ025
Sybase error code	13848

Probable cause

Either the JDK version specified in the CREATE DATABASE statement is unsupported or the version in the manifest file of the JDK JAR file is unsupported.

Kerberos login failed

Error constant	SQLE_KERBEROS_LOGON_FAILED
ODBC 2 State	28000
ODBC 3 State	28000
Severity	16
SQLCODE	-1069
SQLSTATE	28W12
Sybase error code	13445

Probable cause

The Kerberos login failed due to a failure of the client to authenticate the user's principal with the KDC or a failure of the server to authenticate the client. The most likely causes are the Kerberos principal may not be signed in, the principal's ticket may have expired, or the client, server, or KDC's system time are not within a few minutes of each other. The LogFile connection parameter or the server's -z option may provide more information.

Kerberos logins are not supported

Error constant	SQLE_KERBEROS_LOGONS_UNSUPPORTED
ODBC 2 State	28000
ODBC 3 State	28000
Severity	16
SQLCODE	-1070
SQLSTATE	28W13
Sybase error code	13444

Probable cause

The client and/or server does not support Kerberos logins. Kerberos may not be supported by the platform, the Kerberos client software including the GSS-API runtime may not be installed or found on the client, or Kerberos was not enabled on the server. The LogFile connection parameter or the server's -z option may provide more information.

Key constraint between temporary tables requires a primary key (not unique constraint)

Error constant	SQLE_INVALID_FOREIGN_KEY_INDEX
ODBC 2 State	42000
ODBC 3 State	42000
Severity	16
SQLCODE	-865
SQLSTATE	42R03
Sybase error code	1709

Probable cause

The key constraint between temporary tables requires a primary key (not a UNIQUE constraint) if the database uses combined indexes. Change the definition of the primary table using ALTER TABLE or rebuild the database.

SQL Anywhere error messages sorted by message text (L-S)

Label '%1' not found

Error constant	SQLE_LABEL_NOT_FOUND
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Name of the label that could not be found.
Severity	15
SQLCODE	-262
SQLSTATE	42W24
Sybase error code	133

Probable cause

You reference a label in a LEAVE statement, but the label could not be found.

Language '%1' is not supported, '%2' will be used

Error constant	SQLE_UNSUPPORTED_LANGUAGE
ODBC 2 State	01000
ODBC 3 State	01000
Parameter 1	Name of the language that was requested by the client.
Parameter 2	Name of the language that the server will use to send message strings.
Severity	10
SQLCODE	116
SQLSTATE	01W14
Sybase error code	13615

Probable cause

The language that the application requested is not supported by the server to which the application is connecting. Instead, the server will send message strings in the language stated.

Language extension

Error constant	SQLE_LANGUAGE_EXTENSION
ODBC 2 State	37000
ODBC 3 State	ERROR
Severity	16
SQLCODE	-135
SQLSTATE	0AW01
Sybase error code	401

Probable cause

You used a SQL statement that may be valid in some versions of SQL, but not in SQL Anywhere.

Language extension detected in syntax near '%1' on line %2

Error constant	SQLE_SYNTAX_EXTENSION_WARNING
ODBC 2 State	01000
ODBC 3 State	01000
Parameter 1	The word or symbol where the syntax has been detected.
Parameter 2	Line number.
Severity	10
SQLCODE	107
SQLSTATE	01W07
Sybase error code	5703

Probable cause

The statement you are executing contains syntax that is not allowed with the current setting of the option `SQL_FLAGGER_WARNING_LEVEL`. Modify the offending statement or set the `SQL_FLAGGER_WARNING_LEVEL` option to a different value.

LOAD TABLE error: %1

Error constant	SQLE_LOAD_TABLE_ERROR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Description of the failure encountered
Severity	16
SQLCODE	-1188
SQLSTATE	WL013
Sybase error code	13327

Probable cause

The `LOAD TABLE` statement failed. The message specifies the actual problem that occurred.

LOAD TABLE is not allowed on a materialized view %1

Error constant	SQLE_LOAD_TABLE_ON_MATVIEW_ERROR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the materialized view on which load was attempted.
Severity	16
SQLCODE	-1190
SQLSTATE	WL014
Sybase error code	13325

Probable cause

LOAD TABLE statement is not allowed on a materialized view.

LOAD TABLE not allowed on temporary table which has foreign key references from another table

Error constant	SQL_E_INVALID_LOAD_TABLE_WITH_FOREIGN_KEY
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1146
SQLSTATE	WL009
Sybase error code	13366

Probable cause

The LOAD TABLE statement removes all rows in a temporary table upon failure. If a temporary table being loaded caused an error then the foreign rows would be orphaned.

LOAD TABLE not allowed on temporary table with ON COMMIT DELETE ROWS

Error constant	SQL_E_INVALID_TEMP_TABLE_COMMIT_ACTION
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-993
SQLSTATE	WL007
Sybase error code	13496

Probable cause

The LOAD TABLE statement automatically commits at completion. If a temporary table being loaded was declared with ON COMMIT DELETE ROWS, the rows are discarded at completion.

LOAD TABLE not allowed: initialized immediate materialized view %1 depends on %2

Error constant	SQL_LOAD_TABLE_WITH_IMV
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the dependent initialized immediate materialized view.
Parameter 2	Name of the table on which load was performed.
Severity	16
SQLCODE	-1191
SQLSTATE	WL015
Sybase error code	13324

Probable cause

LOAD TABLE is not permitted on any table that has dependent initialized immediate materialized views.

LOAD TABLE not permitted on mirrored database

Error constant	SQL_LOAD_TABLE_ON_MIRRORED_DB
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1035
SQLSTATE	WL008
Sybase error code	13476

Probable cause

LOAD TABLE statements are not permitted when a database is being mirrored, since the file being loaded might not be accessible by the other server.

Local connection ID does not refer to the current database

Error constant	SQLE_LOCAL_CONNECTION_NOT_TO_CURRENT_DB
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-997
SQLSTATE	WO025
Sybase error code	710

Probable cause

The specified connection ID is for a connection to a database other than the current database.

Login mode '%1' not permitted by login_mode setting

Error constant	SQLE_LOGON_MODE_NOT_PERMITTED
ODBC 2 State	28000
ODBC 3 State	28000
Parameter 1	Name of the login mode not included in the current login_mode database option setting.
Severity	16
SQLCODE	-1074
SQLSTATE	28W14
Sybase error code	13440

Probable cause

You attempted to connect using a login mode not included in the current login_mode database option setting. Change the option setting or connect using a different login mode.

Login policies are not supported for this database

Error constant	SQLE_LOGIN_POLICY_UPGRADE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1196
SQLSTATE	WW099
Sybase error code	13319

Probable cause

The current database does not have catalog support for login policies. To use this feature, upgrade your database to the most recent version.

Login policy \"%1\" already exists

Error constant	SQLE_LOGIN_POLICY_ALREADY_EXISTS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the login policy.
Severity	16
SQLCODE	-1194
SQLSTATE	WW097
Sybase error code	13321

Probable cause

An attempt was made to create a login policy that already exists in the database.

Login policy \"%1\" in use

Error constant	SQLE_LOGIN_POLICY_IN_USE
----------------	--------------------------

ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the login policy.
Severity	16
SQLCODE	-1197
SQLSTATE	WW100
Sybase error code	13318

Probable cause

The named login policy is associated with a user in the database. Any users associated with the login policy must be assigned a different login policy before the named login policy can be dropped.

Login policy \"%1\" not found

Error constant	SQLE_LOGIN_POLICY_NOT_FOUND
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the login policy.
Severity	16
SQLCODE	-1195
SQLSTATE	WW098
Sybase error code	13320

Probable cause

The named login policy was not found in the database.

Maintenance of dependent immediate materialized view(s) failed

Error constant	SQLE_MAINTENANCE_OF_IMV_FAILED
----------------	--------------------------------

ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1219
SQLSTATE	42WC8
Sybase error code	13298

Probable cause

Maintenance of immediate materialized view(s) dependent on the base table failed.

Materialized View '%1' not found

Error constant	SQLE_MATVIEW_NOT_FOUND
ODBC 2 State	S0002
ODBC 3 State	42S02
Parameter 1	Name of the materialized view that could not be found.
Severity	11
SQLCODE	-1041
SQLSTATE	42WB5
Sybase error code	13470

Probable cause

You misspelled the name of a materialized view, or you did not qualify a materialized view name with a user name. For example, you might have referred to "Employees" instead of DBA"."Employees".

Maximum row size for table '%1' would be exceeded

Error constant	SQLE_MAX_ROW_SIZE_EXCEEDED
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Parameter 1	Table name.
Severity	16
SQLCODE	-1132
SQLSTATE	WW089
Sybase error code	13381

Probable cause

You tried to create or alter a table with a maximum row size greater than 64KB. In UltraLite, tables must be defined such that the maximum row size (the sum of the bytes required to store each column) is less than 64KB.

Maximum string length exceeded

Error constant	SQLE_MAX_STRING_LENGTH_EXCEEDED
ODBC 2 State	37000
ODBC 3 State	54000
Severity	15
SQLCODE	-1313
SQLSTATE	54W17
Sybase error code	13266

Probable cause

A string operation attempted to create a string longer than the maximum allowed by the server.

Memory error -- transaction rolled back

Error constant	SQLE_MEMORY_ERROR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	24

SQLCODE	-309
SQLSTATE	40W08
Sybase error code	3013

Probable cause

The UltraLite runtime has received an unexpected error from the system calls being used to store the UltraLite database. For example, a write to persistent memory failed. This is an internal error and indicates faulty or corrupt persistent storage on the device. A ROLLBACK statement has been automatically executed.

MERGE statement ANSI cardinality violation on table '%1'

Error constant	SQL_E_MERGE_CARDINALITY_VIOLATION
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the table being updated
Severity	16
SQLCODE	-1211
SQLSTATE	23509
Sybase error code	13304

Probable cause

You have attempted to execute the MERGE statement and the same row is the target of a WHEN MATCHED clause more than once

MERGE statement for table '%1' failed because of a RAISERROR specification in the statement

Error constant	SQL_E_MERGE_USER_SPECIFIED_ERROR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the table being merged into

Severity	16
SQLCODE	-1254
SQLSTATE	23510
Sybase error code	13259

Probable cause

You have attempted to execute a MERGE statement that contains the RAISERROR clause in one or more merge operation branches and one of the input rows satisfies the conditions for one of these branches

Method '%1' cannot be called at this time

Error constant	SQLE_METHOD_CANNOT_BE_CALLED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the method.
Severity	16
SQLCODE	-669
SQLSTATE	WJ001
Sybase error code	13711

Probable cause

The method cannot be called at this time. Check that the method is not being called out of order.

Mirror file requires higher checksum_level

Error constant	SQLE_MIRROR_FILE_REQUIRES_CHECKSUMS
ODBC 2 State	OK
ODBC 3 State	OK
Severity	10
SQLCODE	144

SQLSTATE	WW116
Sybase error code	13274

Probable cause

To effectively protect against media failures, page checksums must be enabled when using the mirror file. Specify the checksum_level database creation option.

Mismatch between external function platform specifier and current operating system

Error constant	SQLE_EXTERNAL_PLATFORM_FAILURE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-618
SQLSTATE	WW004
Sybase error code	13675

Probable cause

A call to an external entry point in a dynamically loaded module was qualified by an operating system that was not the operating system on which the server is currently executing.

Missing value for attribute '%1' in service

Error constant	SQLE_SERVICE_PARM_MISSING_VALUE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the invalid attribute.
Severity	16
SQLCODE	-1023
SQLSTATE	42WAE

Sybase error code	13487
-------------------	-------

Probable cause

The service definition contains a USING, FORMAT, or GROUP attribute with a missing value.

MobiLink communication error; code: %1, parameter: %2, system code %3

Error constant	SQLE_MOBILINK_COMMUNICATIONS_ERROR
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	The stream error code.
Parameter 2	The parameter to the stream error if one exists
Parameter 3	The system error code
Severity	16
SQLCODE	-1305
SQLSTATE	0AWD5
Sybase error code	13454

Probable cause

An error was encountered while communicating with a MobiLink server.

Modifications not permitted for read-only database

Error constant	SQLE_READ_ONLY_DATABASE
ODBC 2 State	42000
ODBC 3 State	42000
Severity	14
SQLCODE	-757
SQLSTATE	55W08

Sybase error code	13768
-------------------	-------

Probable cause

You attempted an update operation on a database that was declared as read-only.

More columns are being dropped from table '%1' than are defined

Error constant	SQLE_TOO_MANY_COLUMNS_DELETED
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Name of the table from which the columns could not be dropped.
Severity	16
SQLCODE	-124
SQLSTATE	42W44
Sybase error code	207

Probable cause

The number of columns in a table can never fall below one. Your ALTER TABLE has more drop/delete column clauses than the current number of columns in the table.

More information required

Error constant	SQLE_MORE_INFO
ODBC 2 State	37000
ODBC 3 State	OK
Severity	10
SQLCODE	112
SQLSTATE	01W09
Sybase error code	13686

Probable cause

More information is required to complete the request. This is used internally in the database interface library to process a unified login. It should not be returned to an application.

More than one table is identified as '%1'

Error constant	SQLE_CORRELATION_NAME_AMBIGUOUS
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Ambiguous correlation name.
Severity	16
SQLCODE	-139
SQLSTATE	52012
Sybase error code	7364

Probable cause

You identified two tables in the same FROM clause with the same correlation name.

Multiple consolidated users cannot be defined

Error constant	SQLE_CONSOLIDATED_USER_ALREADY_EXISTS
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity	16
SQLCODE	-289
SQLSTATE	5RW10
Sybase error code	13767

Probable cause

You attempted to grant consolidated permissions when your database already has a consolidated user, or attempted to grant consolidated permissions to multiple users in a single statement.

Must include primary key for table '%1' in the synchronization

Error constant	SQLE_PK_NOT_IN_SYNC_ARTICLE
ODBC 2 State	42000
ODBC 3 State	42S02
Parameter 1	Name of the table.
Severity	16
SQLCODE	-778
SQLSTATE	5RW17
Sybase error code	13788

Probable cause

The primary key of the table must be included in the synchronization entry.

Must own table '%1' in order to make an immediate view reference it

Error constant	SQLE_NO_PERMS_FOR_IMV
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the table
Severity	16
SQLCODE	-1270
SQLSTATE	42WD3
Sybase error code	13754

Probable cause

You have attempted to change the refresh type of a materialized view to immediate and the view references a table that is not owned by you. In order to perform this operation, you must either own all the tables referenced by the materialized view or have DBA privileges.

NAMESPACE attribute is not valid with procedure type '%1'

Error constant	SQLE_INVALID_NAMESPACE_ATTRIBUTE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The NAMESPACE attribute on the procedure.
Severity	16
SQLCODE	-989
SQLSTATE	WW058
Sybase error code	13500

Probable cause

The NAMESPACE attribute is only applicable to procedures of type SOAP.

Namespace heap exhausted at internal function: %1

Error constant	SQLE_NAMESPACE_HEAP_EXHAUSTED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The internal function is for debugging purposes.
Severity	16
SQLCODE	-164
SQLSTATE	WP007
Sybase error code	13739

Probable cause

The amount of space allocated for the Java Namespace is insufficient to continue loading Java classes. Increase the size by using: SET OPTION PUBLIC.java_namespace_size = nnnnnnnn.

Need a dynamic library name

Error constant	SQLE_REQUIRE_DLL_NAME
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	19
SQLCODE	-619
SQLSTATE	WW005
Sybase error code	13676

Probable cause

You must provide a library name specifier in the name of the external function to call.

No column list for recursive query

Error constant	SQLE_NO_RECURSIVE_COLUMN_LIST
ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	-922
SQLSTATE	42W9A
Sybase error code	13562

Probable cause

A common table expression defining a recursive query must have a column list.

No current row of cursor

Error constant	SQLE_NO_CURRENT_ROW
ODBC 2 State	24000

ODBC 3 State	24000
Severity	16
SQLCODE	-197
SQLSTATE	24503
Sybase error code	560

Probable cause

You attempted to perform an operation on the current row of a cursor, but the cursor is not positioned on a row. The cursor is before the first row of the cursor, after the last row, or is on a row that has since been deleted.

No database file specified

Error constant	SQLE_NO_DATABASE_FILE
ODBC 2 State	08001
ODBC 3 State	08001
Severity	11
SQLCODE	-72
SQLSTATE	08W39
Sybase error code	4001

Probable cause

The database server was started but there was no specified database file. The server is stopped.

No indicator variable provided for NULL result

Error constant	SQLE_NO_INDICATOR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16

SQLCODE	-181
SQLSTATE	22002
Sybase error code	13635

Probable cause

You tried to retrieve a value from the database that was NULL, but you did not provide an indicator variable for that value.

No matching text index

Error constant	SQLTEXT_NO_MATCHING_INDEX
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1158
SQLSTATE	WT003
Sybase error code	13355

Probable cause

A single text index must exist on all columns referenced in a CONTAINS query.

No name for argument

Error constant	SQL_NO_SQLX_ARGUMENT_NAME
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-907
SQLSTATE	WX014
Sybase error code	13576

Probable cause

Unnamed arguments cannot be used as XML element or attribute names. Name unnamed items in the argument list using AS.

No notification within timeout on queue '%1'

Error constant	SQLE_EVENT_NOTIFICATION_QUEUE_TIMEOUT
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the event notification queue
Severity	16
SQLCODE	-1266
SQLSTATE	WE017
Sybase error code	13244

Probable cause

The pending get-notification operation has timed out. No notification arrived before the given timeout elapsed.

No partial download was found

Error constant	SQLE_PARTIAL_DOWNLOAD_NOT_FOUND
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1103
SQLSTATE	WW075
Sybase error code	13411

Probable cause

A partial download was not found for the synchronizing user. This error could occur if trying to resume from a non-existent partial download or trying to rollback a non-existent partial download.

No plan. HTML_PLAN function is not supported for this type of statement or database

Error constant	SQLE_HTML_PLAN_NOT_SUPPORTED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	15
SQLCODE	-1177
SQLSTATE	0AW21
Sybase error code	1333336

Probable cause

You tried to get the HTML plan for a query which is either a SQL Anywhere query or an OMNI/CIS decomposed query. HTML_PLAN is supported for a pure IQ query.

No primary key value for foreign key '%1' in table '%2'

Error constant	SQLE_INVALID_FOREIGN_KEY
ODBC 2 State	23000
ODBC 3 State	23000
Parameter 1	Name of the foreign key.
Parameter 2	Name of the table with the foreign key.
Severity	16
SQLCODE	-194
SQLSTATE	23503
Sybase error code	546

Probable cause

You attempted to insert or update a row that has a foreign key for another table. The value for the foreign key is not NULL and there is not a corresponding value in the primary key

No workload capture currently exists

Error constant	SQLE_WORKLOAD_CAPTURE_DOES_NOT_EXIST
ODBC 2 State	42000
ODBC 3 State	42000
Severity	16
SQLCODE	-943
SQLSTATE	WW030
Sybase error code	13545

Probable cause

You have tried to stop, pause, resume, or get the status of a workload capture, but no workload captures exist.

Non-constant or unknown text query string

Error constant	SQLE_TEXT_QUERY_NOT_KNOWN
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1159
SQLSTATE	WT004
Sybase error code	13354

Probable cause

The query string argument to a CONTAINS query must be a constant, or a non-null value in a variable.

Not allowed while '%1' is using the database

Error constant	SQLE_MUST_BE_ONLY_CONNECTION
ODBC 2 State	40001

ODBC 3 State	40001
Parameter 1	Name of the connection that is using the database.
Severity	16
SQLCODE	-211
SQLSTATE	42W19
Sybase error code	13652

Probable cause

You attempted a data definition language operation that cannot be completed while another user is connected.

Not connected to a database

Error constant	SQLE_NOT_CONNECTED
ODBC 2 State	08003
ODBC 3 State	08003
Severity	16
SQLCODE	-101
SQLSTATE	08003
Sybase error code	13622

Probable cause

You are not connected to a database, or you executed the DISCONNECT statement and have not connected to a database again.

Not enough fields allocated in SQLDA

Error constant	SQLE_SQLDA_TOO_SMALL
ODBC 2 State	07001
ODBC 3 State	07002
Severity	16

SQLCODE	-182
SQLSTATE	07002
Sybase error code	13636

Probable cause

There are not enough fields in the SQLDA to retrieve all of the values requested.

Not enough free space on device to grow dbspace '%1' by requested amount

Error constant	SQLE_NO_ROOM_TO_GROW_DBSPACE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the dbspace
Severity	16
SQLCODE	-1121
SQLSTATE	57W03
Sybase error code	13392

Probable cause

You attempted to grow a dbspace using the ALTER DBSPACE statement, but there is not enough free space on the device to grow by the amount specified.

Not enough memory to start

Error constant	SQLE_NO_MEMORY
ODBC 2 State	S1001
ODBC 3 State	HY001
Severity	17
SQLCODE	-86

SQLSTATE	08W13
Sybase error code	708

Probable cause

The database server started, but stopped because there was not enough memory.

Not enough values for host variables

Error constant	SQLE_NOT_ENOUGH_HOST_VARS
ODBC 2 State	07002
ODBC 3 State	07002
Severity	16
SQLCODE	-188
SQLSTATE	07001
Sybase error code	13638

Probable cause

You have not provided enough host variables for either the number of bind variables, or the statement, or the number of select list items.

NULL attribute mismatch for column '%1'

Error constant	SQLE_OMNI_NULL_MISMATCH
ODBC 2 State	OK
ODBC 3 State	OK
Parameter 1	The name of the column.
Severity	16
SQLCODE	-724
SQLSTATE	WO018
Sybase error code	11211

Probable cause

The NULL attribute of the column specified in the CREATE EXISTING statement differs from the NULL attribute of the actual column.

Null value eliminated in aggregate function

Error constant	SQLE_NULL_VALUE_ELIMINATED
ODBC 2 State	01000
ODBC 3 State	01003
Severity	10
SQLCODE	109
SQLSTATE	01003
Sybase error code	409

Probable cause

The expression argument of the aggregate function evaluated to NULL for one or more rows.

Number of columns allowing NULLs exceeds limit

Error constant	SQLE_TOO_MANY_NULL_COLUMNS
ODBC 2 State	23000
ODBC 3 State	23000
Severity	16
SQLCODE	-733
SQLSTATE	23504
Sybase error code	233

Probable cause

You attempted to create or modify a table definition such that the number of columns that allow NULLS is now more than the limit on such columns. The limit is a function of database page size and is approximately $8 * (\text{page-size} - 30)$.

Number of columns defined for the view does not match SELECT statement

Error constant	SQLE_VIEW_DEFINITION_ERROR
ODBC 2 State	21S02
ODBC 3 State	21S02
Severity	20
SQLCODE	-114
SQLSTATE	53011
Sybase error code	4409

Probable cause

You attempted to create a view, but the column list specified as part of the CREATE VIEW statement does not correspond to the list of items in the view's SELECT statement.

Only PUBLIC settings are allowed for option '%1'

Error constant	SQLE_NOT_PUBLIC_ID
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	Name of the option.
Severity	16
SQLCODE	-202
SQLSTATE	42W43
Sybase error code	13685

Probable cause

The option specified in the SET OPTION statement is PUBLIC only. You cannot define this option for any other user.

Only the DBA can set the option '%1'

Error constant	SQLE_OPTION_REQUIRES_DBA
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	Name of the option that could not be set.
Severity	14
SQLCODE	-204
SQLSTATE	42W46
Sybase error code	5878

Probable cause

The option specified in the SET OPTION statement can only be set by a user with DBA authority.

Operation '%1' failed for reason: '%2'

Error constant	SQLE_ULTRALITEJ_OPERATION_FAILED
ODBC 2 State	ERROR
ODBC 3 State	42000
Parameter 1	The name of the operation.
Parameter 2	The cause of the failure.
Severity	16
SQLCODE	-1279
SQLSTATE	WW231
Sybase error code	13808

Probable cause

The requested operation failed.

Operation conflict with publication type

Error constant	SQLE_CONFLICTING_PUB_TYPE
ODBC 2 State	42000
ODBC 3 State	42S02
Severity	16
SQLCODE	-1060
SQLSTATE	5RW38
Sybase error code	13453

Probable cause

You attempted to perform an operation not applicable to the type of publication. For example, you applied operations specific to a scripted upload publication to a logscan publication.

Operation failed because table or view '%1' has an INSTEAD OF trigger

Error constant	SQLE_INSTEAD_TRIGGER
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	Name of the view or table with an INSTEAD OF trigger
Severity	15
SQLCODE	-1126
SQLSTATE	42W3A
Sybase error code	13387

Probable cause

You attempted an operation that cannot succeed because an INSTEAD OF trigger is defined on a target table or view (possibly nested in another view).

Operation is not allowed

Error constant	SQLE_ULTRALITEJ_OPERATION_NOT_ALLOWED
ODBC 2 State	ERROR
ODBC 3 State	42000
Severity	16
SQLCODE	-1278
SQLSTATE	WW230
Sybase error code	13846

Probable cause

The requested operation is not allowed while schema is being modified.

Operation not allowed on a table with dependent immediate materialized views

Error constant	SQLE_INVALID_OPERATION_FOR_TBL_WITH_IMV
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1202
SQLSTATE	55W31
Sybase error code	13313

Probable cause

Requested operation cannot be applied to a table with dependent immediate materialized views.

Operation would cause a group cycle

Error constant	SQLE_GROUP_CYCLE
ODBC 2 State	37000

ODBC 3 State	42000
Severity	16
SQLCODE	-122
SQLSTATE	42W02
Sybase error code	314

Probable cause

You attempted to add a member to group that would result in a member belonging to itself. The membership may be direct or indirect.

Option '%1' specified more than once

Error constant	SQLE_DUPLICATE_OPTION
ODBC 2 State	OK
ODBC 3 State	OK
Parameter 1	The name of the duplicated option.
Severity	10
SQLCODE	139
SQLSTATE	01W26
Sybase error code	13415

Probable cause

A particular option has been specified multiple times. Only the last instance of the option is used; the previous ones are ignored.

ORDER BY not allowed in window '%1'

Error constant	SQLE_ORDERBY_NOT_ALLOWED
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Parameter 1	The name of the window.
Severity	16
SQLCODE	–949
SQLSTATE	42WA5
Sybase error code	13539

Probable cause

When an existing window name is referenced from an inline window specification, either the inline window or the referenced window may have an ORDER BY, but not both.

Output file cannot be written

Error constant	SQLE_CANNOT_WRITE_FILE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	20
SQLCODE	–979
SQLSTATE	WW048
Sybase error code	13510

Probable cause

Unable to create or write an output file. The file may be locked or read-only.

Owner '%1' used in a qualified column reference does not match correlation name '%2'

Error constant	SQLE_INVALID_COLUMN_QUALIFICATION
ODBC 2 State	S0002
ODBC 3 State	42S02
Parameter 1	The owner name specified in the column reference.

Parameter 2	The correlation name that is incorrectly referenced.
Severity	15
SQLCODE	–845
SQLSTATE	42U02
Sybase error code	13851

Probable cause

Your query contains a qualified column reference to a table name, but either a correlation name has been used for that table, or the owner of the table does not match the owner name specified in the column reference. Remove the owner qualification, and qualify column references only by correlation name.

Parameter '%1' cannot be null

Error constant	SQLE_PARAMETER_CANNOT_BE_NULL
ODBC 2 State	ERROR
ODBC 3 State	42000
Parameter 1	Name of the parameter.
Severity	16
SQLCODE	–1277
SQLSTATE	WW229
Sybase error code	13862

Probable cause

The specified parameter cannot be null.

Parameter '%1' in procedure or function '%2' does not have a default value

Error constant	SQLE_NO_DEFAULT_FOR_PARM
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Parameter 1	The name of the parameter.
Parameter 2	The name of the procedure or function.
Severity	16
SQLCODE	-1001
SQLSTATE	08W71
Sybase error code	13491

Probable cause

An attempt was made to use DEFAULT as a procedure or function argument, but the corresponding parameter does not have a default value.

Parameter '%1' not found in procedure '%2'

Error constant	SQLE_INVALID_PARAMETER_NAME
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Name of the parameter that was not found.
Parameter 2	Name of the procedure where the parameter was not found.
Severity	16
SQLCODE	-615
SQLSTATE	42W47
Sybase error code	201

Probable cause

You supplied a procedure parameter name that does not match a parameter for this procedure. Check the spelling of the parameter name.

Parameter name missing in call to procedure '%1'

Error constant	SQLE_PARAMETER_NAME_MISSING
----------------	-----------------------------

ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	The name of the procedure.
Severity	16
SQLCODE	–639
SQLSTATE	42W42
Sybase error code	201

Probable cause

Positional parameters were specified after named parameters in a call to this procedure.

Parameter not registered as output parameter

Error constant	SQLE_PARAM_NOT_REGISTERED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	–671
SQLSTATE	WJ002
Sybase error code	13712

Probable cause

The parameter must be registered as an output parameter before the value of the parameter can be obtained.

Parent not open: '%1'

Error constant	SQLE_EXPLICIT_TAG_NOT_OPEN
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Parameter 1	The parent tag ID that is not among the open tags.
Severity	16
SQLCODE	–900
SQLSTATE	WX008
Sybase error code	13581

Probable cause

FOR XML EXPLICIT requires the parent tag for a row to be opened when that row is read. Check the order of the rows returned by the query with the FOR XML EXPLICIT clause removed.

Parse error: %1

Error constant	SQLE_INVALID_PARSE_PARAMETER
ODBC 2 State	08004
ODBC 3 State	08004
Parameter 1	Description of the parsing error.
Severity	18
SQLCODE	–95
SQLSTATE	08W49
Sybase error code	5864

Probable cause

An error occurred while parsing a connection string.

Parse error: %1

Error constant	SQLE_INVALID_DSN_NAME
ODBC 2 State	08004
ODBC 3 State	08004
Parameter 1	The invalid data source name.

Severity	18
SQLCODE	-754
SQLSTATE	08W54
Sybase error code	5864

Probable cause

An invalid data source name was used in the connection string.

PARTITION BY not allowed in reference to window '%1'

Error constant	SQLE_PARTITIONBY_NOT_ALLOWED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the window.
Severity	16
SQLCODE	-948
SQLSTATE	42WA4
Sybase error code	13540

Probable cause

When an existing window name is referenced from an inline window specification, the inline specification must not have a PARTITION BY clause.

Passthrough SQL script failed

Error constant	SQLE_PASSTHROUGH_SQL_SCRIPT_FAILED_E
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1238

SQLSTATE	WW112
Sybase error code	13280

Probable cause

A passthrough SQL script has failed with an unknown error. Sync your database to report the error to MobiLink. You may need to contact the server administrator.

Passthrough SQL script failed

Error constant	SQLE_PASSTHROUGH_SQL_SCRIPT_FAILED_W
ODBC 2 State	OK
ODBC 3 State	OK
Severity	10
SQLCODE	141
SQLSTATE	01006
Sybase error code	13289

Probable cause

A passthrough SQL script has failed. Sync your database to report the error to MobiLink. You may need to contact the server administrator.

Passthrough statement inconsistent with current passthrough

Error constant	SQLE_PASSTHROUGH_INCONSISTENT
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity	16
SQLCODE	-287
SQLSTATE	5RW08
Sybase error code	13649

Probable cause

Passthrough is additive, in that subsequent PASSTHROUGH statements add to the list of users receiving passthrough. The PASSTHROUGH statements must all be PASSTHROUGH ONLY or none should be PASSTHROUGH ONLY.

Password cannot be longer than %1 characters

Error constant	SQLE_PASSWORD_TOO_LONG
ODBC 2 State	37000
ODBC 3 State	54000
Parameter 1	Maximum length of password.
Severity	15
SQLCODE	-958
SQLSTATE	54W08
Sybase error code	13530

Probable cause

The password is longer than that allowed by the server.

Password contains an illegal character

Error constant	SQLE_ILLEGAL_PASSWORD
ODBC 2 State	28000
ODBC 3 State	28000
Severity	11
SQLCODE	-963
SQLSTATE	08005
Sybase error code	13528

Probable cause

The specified password contains an illegal character.

Password has expired

Error constant	SQLE_PASSWORD_EXPIRED
ODBC 2 State	28000
ODBC 3 State	28000
Severity	16
SQLCODE	-1152
SQLSTATE	08WA0
Sybase error code	13361

Probable cause

You attempted to connect using a valid user ID, but with an expired password. You can change your password by supplying the NewPassword connection parameter along with the current expired password.

Password has expired but cannot be changed because the database is read-only

Error constant	SQLE_PASSWORD_EXPIRED_READONLY_DB
ODBC 2 State	28000
ODBC 3 State	28000
Severity	16
SQLCODE	-1153
SQLSTATE	08WA1
Sybase error code	13360

Probable cause

You attempted to connect to a read-only database using a valid user ID, but with an expired password. The password cannot be changed unless the database is started without the -r option on the database server command line. Removing -r will permit modifications to the database.

Password must be at least %1 characters

Error constant	SQLE_PASSWORD_TOO_SHORT
ODBC 2 State	37000
ODBC 3 State	54000
Parameter 1	Minimum length of password.
Severity	14
SQLCODE	-738
SQLSTATE	54W07
Sybase error code	573

Probable cause

The password is shorter than that allowed by the current min_password_length option setting.

Permission denied: %1

Error constant	SQLE_PERMISSION_DENIED
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	Description of the type of permission required.
Severity	16
SQLCODE	-121
SQLSTATE	42501
Sybase error code	262

Probable cause

You do not have the required permission to perform the specified action. The message specifies the actual permission required and the object being acted upon.

Plan can not be generated for this type of statement

Error constant	SQLE_STMT_NOT_ALLOWED_IN_PLAN
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	15
SQLCODE	-894
SQLSTATE	0AW14
Sybase error code	13589

Probable cause

You tried to get the execution plan for a statement type that is not supported.

Plan may contain virtual indexes

Error constant	SQLE_USING_VIRTUAL_INDEXES
ODBC 2 State	01S01
ODBC 3 State	01S01
Severity	10
SQLCODE	129
SQLSTATE	01W20
Sybase error code	13596

Probable cause

Virtual indexes are currently enabled in this connection. Any plans that are generated may contain virtual indexes.

Plan not available. NOEXEC Plan can not be generated for this type of statement

Error constant	SQLE_STMT_NOT_ALLOWED_FOR_NOEXEC_PLAN
----------------	---------------------------------------

ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	15
SQLCODE	-1176
SQLSTATE	0AW20
Sybase error code	13337

Probable cause

You tried to get the NOEXEC plan for a statement type for which IQ cannot generate a NOEXEC plan.

Positioned update operation attempted on a view with an INSTEAD OF trigger

Error constant	SQLE_INSTEAD_TRIGGER_POSITIONED
ODBC 2 State	42000
ODBC 3 State	42000
Severity	15
SQLCODE	-1127
SQLSTATE	42W3B
Sybase error code	13386

Probable cause

You attempted a positioned update, positioned delete, put, or wide insert operation that would involve an INSTEAD OF trigger on a view (possibly nested). These operations are not supported with INSTEAD OF triggers on views.

Previous error lost prior to RESIGNAL

Error constant	SQLE_PREVIOUS_ERROR_LOST
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Severity	16
SQLCODE	-825
SQLSTATE	WP011
Sybase error code	13831

Probable cause

A RESIGNAL statement in an exception handler of a stored procedure was executed but the context of the previous error was unavailable. A possible cause of this error is a SELECT statement that returns a result set in the exception handler.

Primary key column '%1' already defined

Error constant	SQLE_PRIMARY_KEY_COLUMN_DEFINED
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	Name of the column that is already in the primary key.
Severity	16
SQLCODE	-119
SQLSTATE	52009
Sybase error code	1909

Probable cause

You listed the same column name twice in the definition of a primary key.

Primary key for row in table '%1' is referenced by foreign key '%2' in table '%3'

Error constant	SQLE_PRIMARY_KEY_VALUE_REF
ODBC 2 State	23000
ODBC 3 State	23000
Parameter 1	The name of the table containing the row being modified.

Parameter 2	The name of the foreign index (or role) of the referencing table.
Parameter 3	The name of the foreign table referencing the primary row.
Severity	16
SQLCODE	-198
SQLSTATE	23W05
Sybase error code	547

Probable cause

You attempted to delete or modify a row whose primary key value is referenced elsewhere in the database.

Primary key for table '%1' is not unique : Primary key value ('%2')

Error constant	SQL_E_PRIMARY_KEY_NOT_UNIQUE
ODBC 2 State	23000
ODBC 3 State	23000
Parameter 1	Name of the table where the problem was detected.
Parameter 2	Duplicate primary key values that caused the error.
Severity	14
SQLCODE	-193
SQLSTATE	23W01
Sybase error code	2601

Probable cause

You attempted to add a new row to a table, but the new row has the same primary key as an existing row. The database has not added the incorrect row to the database. For example, you might have added a student with student number 86004 and there is already a row for a student with that number.

Procedure '%1' is no longer valid

Error constant	SQL_E_PROCEDURE_NO_LONGER_VALID
----------------	---------------------------------

ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Name of the procedure.
Severity	15
SQLCODE	-836
SQLSTATE	42W63
Sybase error code	13842

Probable cause

A procedure definition cannot be loaded from the catalog. Check for tables or columns that have been renamed or that may be reserved words.

Procedure '%1' not found

Error constant	SQLE_PROCEDURE_NOT_FOUND
ODBC 2 State	S0002
ODBC 3 State	42S02
Parameter 1	Name of the procedure that could not be found.
Severity	11
SQLCODE	-265
SQLSTATE	52W09
Sybase error code	504

Probable cause

You misspelled the name of a procedure, or you did not qualify a procedure name with a user name.

Procedure '%1' terminated with unhandled exception '%2'

Error constant	SQLE_UNHANDLED_EXTENV_EXCEPTION
ODBC 2 State	ERROR

ODBC 3 State	ERROR
Parameter 1	The name of the procedure that returned the unhandled exception.
Parameter 2	The fully qualified Java class name of the unhandled exception.
Severity	16
SQLCODE	-91
SQLSTATE	WP001
Sybase error code	13735

Probable cause

A Java procedure terminated with an active exception, and this exception is reflected in SQL as an error status.

Procedure has completed

Error constant	SQLPROCEDURE_COMPLETE
ODBC 2 State	OK
ODBC 3 State	OK
Severity	10
SQLCODE	105
SQLSTATE	01W05
Sybase error code	13618

Probable cause

There are no more result sets available for this procedure. An OPEN or a RESUME statement may have caused the procedure to execute to completion.

Procedure in use by '%1'

Error constant	SQLPROCEDURE_IN_USE
ODBC 2 State	40001

ODBC 3 State	40001
Parameter 1	Name of user.
Severity	16
SQLCODE	-215
SQLSTATE	42W23
Sybase error code	3702

Probable cause

You attempted to DROP a procedure that is being used by other active users of the database.

Procedure or trigger calls have nested too deeply

Error constant	SQLE_NESTING_TOO_DEEP
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-274
SQLSTATE	42W29
Sybase error code	217

Probable cause

You may have defined a procedure or trigger that causes unlimited recursion.

Publication '%1' not found

Error constant	SQLE_PUBLICATION_NOT_FOUND
ODBC 2 State	S0002
ODBC 3 State	42S02
Parameter 1	Name of the publication that could not be found.

Severity	16
SQLCODE	-280
SQLSTATE	5RW01
Sybase error code	13642

Probable cause

You misspelled the name of a publication, or you did not qualify a publication name with a user name.

Publication predicates were not evaluated

Error constant	SQLE_PUBLICATION_PREDICATE_IGNORED
ODBC 2 State	OK
ODBC 3 State	OK
Severity	10
SQLCODE	138
SQLSTATE	01W25
Sybase error code	13423

Probable cause

Publication predicates were not evaluated because UltraLite was initialized without SQL support. The table will be uploaded as if no publication predicate was specified for the table.

RAISERROR executed: %1

Error constant	SQLE_RAISERROR_STMT
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	RAISERROR message string.
Severity	16
SQLCODE	-631

SQLSTATE	WW012
Sybase error code	0

Probable cause

A RAISERROR statement has been executed. The string associated with the RAISERROR statement is included in the text of the error message.

READTEXT or WRITETEXT statement cannot refer to a view

Error constant	SQLE_TEXT_OPERATION_ON_VIEW
ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	-708
SQLSTATE	42W50
Sybase error code	285

Probable cause

A Transact-SQL READTEXT or WRITETEXT statement cannot refer to text columns in a view. Replace the view reference with the name of a base table.

Recursion is not allowed without the RECURSIVE keyword

Error constant	SQLE_RECURSIVE_KEYWORD_REQUIRED
ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	-938
SQLSTATE	42WA0
Sybase error code	13549

Probable cause

The common table expressions for a recursive query must be defined using a WITH RECURSIVE clause.

Recursive column %1: conversion from '%2' to '%3' loses precision

Error constant	SQLE_BAD_RECURSIVE_COLUMN_CONVERSION
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Column number of the recursive subquery.
Parameter 2	Type converted from.
Parameter 3	Type converted to.
Severity	16
SQLCODE	-945
SQLSTATE	42WA2
Sybase error code	13543

Probable cause

Every column in the recursive subquery must be convertible to the type of the corresponding column in the initial subquery without loss of precision. Try casting the column in the initial subquery to an appropriate type.

Referential integrity actions other than RESTRICT not allowed for temporary tables

Error constant	SQLE_INVALID_FOREIGN_KEY_ACTION
ODBC 2 State	42000
ODBC 3 State	42000
Severity	16
SQLCODE	-849

SQLSTATE	42R01
Sybase error code	1709

Probable cause

You attempted to specify an unsupported referential integrity action for a temporary table.

Remote message type '%1' not found

Error constant	SQLE_NOT_REMOTE_TYPE
ODBC 2 State	S0002
ODBC 3 State	42S02
Parameter 1	Name of remote message type.
Severity	16
SQLCODE	-286
SQLSTATE	5RW07
Sybase error code	13648

Probable cause

You referred to a remote message type that is not defined in this database. Use CREATE REMOTE TYPE to define remote message types.

Remote server '%1' could not be found

Error constant	SQLE_OMNI_SERVER_NOT_FOUND
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the remote server.
Severity	11
SQLCODE	-659
SQLSTATE	WO004

Sybase error code	11214
-------------------	-------

Probable cause

You attempted to define an object on a server that has not been added. Use CREATE SERVER to add the remote server definition.

Remote server '%1' is currently configured as read-only

Error constant	SQLE_OMNI_READONLY
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the remote server.
Severity	16
SQLCODE	-658
SQLSTATE	WO003
Sybase error code	11248

Probable cause

You attempted to perform an update on an object located on a server that is configured as read-only. Use ALTER SERVER to reconfigure the remote server to be updatable.

Remote server does not have the ability to support this statement

Error constant	SQLE_OMNI_SERVER_NOT_CAPABLE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-706
SQLSTATE	WO012
Sybase error code	11227

Probable cause

You attempted to execute a statement that requires a capability that is not supported by a remote server.

Remote statement failed

Error constant	SQLE_REMOTE_STATEMENT_FAILED
ODBC 2 State	S0002
ODBC 3 State	42S02
Severity	16
SQLCODE	-288
SQLSTATE	5RW09
Sybase error code	13650

Probable cause

This SQLSTATE can be signaled within a trigger to prevent the SQL Remote Message Agent (dbremote) from displaying an error message in the output. This exception will only occur when a trigger or procedure signals it. This is useful for ignoring replication errors that are permitted by design.

Reorganize table is already being run on table \"%1\

Error constant	SQLE_REORG_ALREADY_IN_PROGRESS
ODBC 2 State	54000
ODBC 3 State	54000
Parameter 1	The name of the table.
Severity	16
SQLCODE	-1229
SQLSTATE	54W51
Sybase error code	13288

Probable cause

There is already a REORGANIZE TABLE statement being run on this table. Only one such statement can be executing on a table at any time.

Request denied -- no active databases

Error constant	SQLE_REQUEST_DENIED_NO_DATABASES
ODBC 2 State	08004
ODBC 3 State	08004
Severity	14
SQLCODE	-76
SQLSTATE	08W28
Sybase error code	950

Probable cause

The server has denied your request as there are currently no running databases.

Request interrupted due to timeout

Error constant	SQLE_REQUEST_TIMEOUT
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1043
SQLSTATE	57W01
Sybase error code	13468

Probable cause

The current request was canceled during its execution since it ran for longer than the request_timeout database option value. The database was able to stop the operation without doing a rollback. If the statement is INSERT, UPDATE, or DELETE, any changes made by the statement will be canceled. If the statement is a data definition statement (for example CREATE TABLE), the statement will be canceled, but the COMMIT that was done as a side effect will not be canceled.

Request to start/stop database denied

Error constant	SQLE_START_STOP_DATABASE_DENIED
ODBC 2 State	42000
ODBC 3 State	42000
Severity	14
SQLCODE	-75
SQLSTATE	08W29
Sybase error code	6004

Probable cause

You do not have permission to start or stop a database. The required permission is determined on the server command line.

Required operators excluded

Error constant	SQLE_REQUIRED_OPERATORS_EXCLUDED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	18
SQLCODE	-969
SQLSTATE	WI011
Sybase error code	13521

Probable cause

The database server was unable to construct a valid access plan for the given request because required data flow operators were excluded by the `exclude_operators` option. Re-enable the required operators to execute the statement.

Resource governor for '%1' exceeded

Error constant	SQLE_RESOURCE_GOVERNOR_EXCEEDED
----------------	---------------------------------

ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The resource whose limit has been exceeded.
Severity	19
SQLCODE	-685
SQLSTATE	WP009
Sybase error code	13715

Probable cause

The resource governor for the stated resource has determined that the usage of the resource has exceeded its limit.

RESTORE unable to open file '%1'

Error constant	SQLLE_RESTORE_UNABLE_TO_OPEN
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	File name of database file.
Severity	21
SQLCODE	-717
SQLSTATE	WB008
Sybase error code	13726

Probable cause

RESTORE was unable to open one of the database files.

RESTORE unable to start database '%1'

Error constant	SQLLE_RESTORE_UNABLE_TO_START
ODBC 2 State	ERROR

ODBC 3 State	ERROR
Parameter 1	File name of database file.
Severity	21
SQLCODE	-719
SQLSTATE	WB010
Sybase error code	13728

Probable cause

After a RESTORE, the resulting database could not be started.

RESTORE unable to write to file '%1'

Error constant	SQLE_RESTORE_UNABLE_TO_WRITE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	File name of database file.
Severity	21
SQLCODE	-718
SQLSTATE	WB009
Sybase error code	13727

Probable cause

RESTORE was unable to write to one of the database files.

Result set not allowed from within an atomic compound statement

Error constant	SQLE_RESULT_NOT_ALLOWED
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Severity	16
SQLCODE	-222
SQLSTATE	3BW02
Sybase error code	13655

Probable cause

You used a SELECT statement with no INTO clause or a RESULT CURSOR statement within an atomic compound statement.

Result set not permitted in '%1'

Error constant	SQLE_RESULT_SET_NOT_PERMITTED
ODBC 2 State	07005
ODBC 3 State	07005
Parameter 1	Name of object containing the invalid statement.
Severity	16
SQLCODE	-946
SQLSTATE	09W03
Sybase error code	13542

Probable cause

You attempted to execute a SELECT statement in a context where a result set is not permitted.

Retrying read of corrupt page (page '%1')

Error constant	SQLE_CORRUPT_PAGE_READ_RETRY
ODBC 2 State	OK
ODBC 3 State	OK
Parameter 1	The page id
Severity	10

SQLCODE	143
SQLSTATE	WW115
Sybase error code	13275

Probable cause

UltraLite detected a corrupt database page and will attempt the read operation again. If a mirror file is enabled, it is used for the retry. If the retry fails, an error will be signaled.

Return type of void from procedure '%1' cannot be used in any expression

Error constant	SQLE_PROCEDURE_RETURNS_VOID
ODBC 2 State	07006
ODBC 3 State	07006
Parameter 1	Name of the procedure.
Severity	16
SQLCODE	-705
SQLSTATE	53019
Sybase error code	257

Probable cause

The Java type void does not map onto any SQL type, hence a procedure returning void cannot be used in any SQL expression.

Return value cannot be set

Error constant	SQLE_RETVAL_CANNOT_BE_SET
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-690

SQLSTATE	WJ006
Sybase error code	13601

Probable cause

Setting a value for the return parameter of a callable statement is not allowed.

Right truncation of string data

Error constant	SQLLE_STRING_RIGHT_TRUNCATION
ODBC 2 State	22001
ODBC 3 State	22001
Severity	16
SQLCODE	-638
SQLSTATE	22001
Sybase error code	9502

Probable cause

Non-space characters were truncated upon the assignment of string data.

Rollback occurred due to deadlock during prefetch

Error constant	SQLLE_ROLLBACK_ON_PREFETCH
ODBC 2 State	40001
ODBC 3 State	40001
Severity	13
SQLCODE	-684
SQLSTATE	WW019
Sybase error code	1205

Probable cause

One of the cursors that was opened with prefetch enabled was performing fetch operations, and a deadlock occurred during a prefetch. This is a deadlock situation and your transaction has been chosen as the one to rollback. The request that received this error was not executed, unless the request was to close the cursor, in which case the cursor was closed.

ROLLBACK TO SAVEPOINT not allowed

Error constant	SQLE_ROLLBACK_NOT_ALLOWED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-221
SQLSTATE	3B002
Sybase error code	13654

Probable cause

You attempted a ROLLBACK TO SAVEPOINT within an atomic operation to a savepoint established before the atomic operation.

Row has been updated since last time read

Error constant	SQLE_ROW_UPDATED_WARNING
ODBC 2 State	OK
ODBC 3 State	OK
Severity	10
SQLCODE	104
SQLSTATE	01W04
Sybase error code	532

Probable cause

You fetched a row from a SCROLL cursor. The row was previously fetched from the same cursor, and one or more columns in the row has been updated since the previous fetch. The column(s) updated may or may

not be fetched by the cursor; this warning just indicates that the row from the table has been updated. If the cursor involves more than one table, a row from one or more of the tables has been updated.

Row has changed since last read -- operation canceled

Error constant	SQLE_ROW_UPDATED_SINCE_READ
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-208
SQLSTATE	22W02
Sybase error code	554

Probable cause

You attempted an UPDATE (positioned) or DELETE (positioned) operation on a cursor declared as a SCROLL cursor, and the row you are changing has been updated since you read it. This error prevents the "lost update" problem.

Row in table '%1' was modified or deleted in BEFORE trigger

Error constant	SQLE_ROW_REMODIFIED_OR_DELETED
ODBC 2 State	37000
ODBC 3 State	ERROR
Parameter 1	Name of the table.
Severity	16
SQLCODE	-833
SQLSTATE	42W62
Sybase error code	13839

Probable cause

A BEFORE trigger has updated or deleted the row that caused the trigger to fire, preventing the original operation from completing. The trigger must be re-written so that it does not attempt to change the row via UPDATE or DELETE statements.

Row not found

Error constant	SQLE_NOTFOUND
ODBC 2 State	OK
ODBC 3 State	OK
Severity	16
SQLCODE	100
SQLSTATE	02000
Sybase error code	560

Probable cause

You positioned a cursor beyond the beginning or past the end of the query. There is no row at that position.

Row was dropped from table %1 to maintain referential integrity

Error constant	SQLE_ROW_DELETED_TO_MAINTAIN_REFERENTIAL_INTEGRITY
ODBC 2 State	OK
ODBC 3 State	OK
Parameter 1	The name of the table.
Severity	10
SQLCODE	137
SQLSTATE	01W24
Sybase error code	13489

Probable cause

A delete of a primary row during download forced its foreign row(s) to be deleted as well to maintain referential integrity

Run time SQL error -- %1

Error constant	SQLE_ERROR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Identification of the error.
Severity	18
SQLCODE	-300
SQLSTATE	40000
Sybase error code	13664

Probable cause

An internal database error occurred. If it can be reproduced, it should be reported to iAnywhere. You may be able to work around this problem by modifying the associated query statement.

Savepoint '%1' not found

Error constant	SQLE_SAVEPOINT_NOTFOUND
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of savepoint.
Severity	16
SQLCODE	-220
SQLSTATE	3B001
Sybase error code	6401

Probable cause

You attempted to rollback to a savepoint that does not exist.

Savepoints require a rollback log

Error constant	SQLE_SAVEPOINTS_REQUIRE_UNDO
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-213
SQLSTATE	3BW01
Sybase error code	13656

Probable cause

You cannot use savepoints when the database server is running in bulk mode without a rollback log.

Schedule '%1' for event '%2' already exists

Error constant	SQLE_SCHEDULE_ALREADY_EXISTS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the schedule that already exists.
Parameter 2	Name of the event being scheduled.
Severity	16
SQLCODE	-774
SQLSTATE	WE004
Sybase error code	13784

Probable cause

You have attempted to create a schedule with a name that already exists in the database for the named event.

Schedule '%1' for event '%2' not found

Error constant	SQLE_SCHEDULE_NOT_FOUND
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the schedule that could not be found.
Parameter 2	Name of the event being scheduled.
Severity	11
SQLCODE	-773
SQLSTATE	WE003
Sybase error code	13783

Probable cause

You have attempted to reference a schedule with a name that does not exist in the database for the named event.

Script file missing statement \"go\" delimiter on a separate line

Error constant	SQLE_SCRIPT_MISSING_DELIMITER
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	15
SQLCODE	-1315
SQLSTATE	WW046
Sybase error code	13241

Probable cause

For UltraLite, all non-comment SQL statements in a script file (including the final one) must be followed by "go" on a line by itself. For strings, you can use "\"ngo" to end a statement.

Secure HTTP connections are not supported on this platform

Error constant	SQLE_SECURE_CONNECTION_UNAVAILABLE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	19
SQLCODE	-1030
SQLSTATE	WW063
Sybase error code	13480

Probable cause

A Secure HTTP connection was attempted, but is not supported on this platform.

Seek absolute 0 was attempted on a JDBC SAResultSet

Error constant	SQLE_JDBC_RESULTSET_SEEK_ABSOLUTE_ZERO
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-743
SQLSTATE	WJ016
Sybase error code	13756

Probable cause

There is no row zero on JDBC resultSets. The valid row numbers are 1, 2, ..., -2, -1.

Select lists in UNION, INTERSECT, or EXCEPT do not match in length

Error constant	SQLE_INVALID_UNION
----------------	--------------------

ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	-153
SQLSTATE	53026
Sybase error code	205

Probable cause

You specified a UNION, INTERSECT, or EXCEPT but the SELECT statements involved in the operation do not have the same number of columns in the select list.

SELECT returns more than one row

Error constant	SQLE_TOO_MANY_RECORDS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-185
SQLSTATE	21000
Sybase error code	13637

Probable cause

You tried to use a SELECT statement without a cursor, but the statement cursor returns more than one row. Only a single row SELECT statement can be used in this context.

Server '%1': %2

Error constant	SQLE_OMNI_REMOTE_ERROR
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Parameter 1	The name of the remote server.
Parameter 2	The message from the remote server.
Severity	16
SQLCODE	–660
SQLSTATE	WO005
Sybase error code	13732

Probable cause

A message was generated by a remote server. The message text is included.

Server capability name '%1' could not be found in the database

Error constant	SQLE_CAPABILITY_NOT_FOUND
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of server capability.
Severity	16
SQLCODE	–761
SQLSTATE	WO014
Sybase error code	13723

Probable cause

An ALTER SERVER statement was attempted on a capability that was not defined.

Server not found and unable to autostart

Error constant	SQLE_UNABLE_TO_CONNECT_OR_START
ODBC 2 State	08001
ODBC 3 State	08001

Severity	11
SQLCODE	-764
SQLSTATE	08W55
Sybase error code	13774

Probable cause

Could not connect to a server, and was unable to autostart a server. Autostart may have failed because no database file was supplied.

Service '%1' already exists

Error constant	SQLLE_SERVICE_ALREADY_EXISTS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the service that already exists.
Severity	16
SQLCODE	-919
SQLSTATE	42W97
Sybase error code	13565

Probable cause

You have attempted to create a service with a name that already exists in the database.

Service '%1' in use

Error constant	SQLLE_SERVICE_IN_USE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the service that is in use.
Severity	16

SQLCODE	-924
SQLSTATE	55W15
Sybase error code	13567

Probable cause

You have attempted to drop a service that is currently in use.

Service '%1' not found

Error constant	SQLE_SERVICE_NOT_FOUND
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the specified service that could not be found.
Severity	16
SQLCODE	-920
SQLSTATE	42W98
Sybase error code	13564

Probable cause

You have attempted to reference a service with a name that does not exist in the database.

Service definition requires a statement when authorization is off

Error constant	SQLE_SERVICE_AUTH_REQUIRED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-931
SQLSTATE	42W9E

Sybase error code	13554
-------------------	-------

Probable cause

The service definition for the specified service type requires a statement to be specified when authorization is set to Off.

Service statement definition is inconsistent with service type

Error constant	SQLE_SERVICE_STATEMENT_MISMATCH
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-927
SQLSTATE	42W9C
Sybase error code	13558

Probable cause

Either no statement was provided for a service whose type requires one, or a statement was provided when the service type does not allow one to be defined.

Service statement definition is invalid or unsupported

Error constant	SQLE_SERVICE_STATEMENT_INVALID
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1269
SQLSTATE	42WCC
Sybase error code	13250

Probable cause

Either the statement provided is invalid or it is unsupported within the context of a service.

Service type does not allow '%1' attribute

Error constant	SQLE_SERVICE_ATTR_NOT_ALLOWED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the attribute that is not allowed.
Severity	16
SQLCODE	-1027
SQLSTATE	42WB2
Sybase error code	13483

Probable cause

The service definition for the specified service type does not allow the given attribute to be specified

Service type required for CREATE SERVICE

Error constant	SQLE_SERVICE_TYPE_REQUIRED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-915
SQLSTATE	42W92
Sybase error code	13569

Probable cause

The CREATE SERVICE statement requires a service type to be specified.

SET clause for column '%1' used incorrectly

Error constant	SQLE_INVALID_SET_CLAUSE
ODBC 2 State	S0002
ODBC 3 State	42S03
Parameter 1	The SET clause that is invalid.
Severity	15
SQLCODE	-846
SQLSTATE	42U03
Sybase error code	13852

Probable cause

Your UPDATE statement contains an invalid SET clause, for example, there are multiple SET clauses for the same column.

SETUSER not allowed in procedures, triggers, events, or batches

Error constant	SQLE_SETUSER_NOT_IN_PROCEDURES
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-877
SQLSTATE	42W09
Sybase error code	13888

Probable cause

The SETUSER statement is not allowed in stored procedures, triggers, event handlers, or batches, and cannot be called from an EXECUTE IMMEDIATE statement.

Signature '%1' does not match procedure parameters

Error constant	SQLE_SIGNATURE_MISMATCH
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	The value of the signature.
Severity	16
SQLCODE	-737
SQLSTATE	42W54
Sybase error code	201

Probable cause

The number of types in the signature must match the number of procedure parameters. If a DYNAMIC RESULT SETS clause was specified, the number of dynamic result sets must match the quantity found in the signature.

Snapshot isolation disabled or pending

Error constant	SQLE_SNAPSHOT_ISOLATION_DISABLED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1054
SQLSTATE	55W23
Sybase error code	13459

Probable cause

Snapshot isolation is disabled or its activation is still pending. You must enable snapshot isolation before using it.

Specified database file already in use

Error constant	SQLE_FILE_IN_USE
ODBC 2 State	08001
ODBC 3 State	08001
Severity	14
SQLCODE	-816
SQLSTATE	08W56
Sybase error code	924

Probable cause

The database server could not start the specified database because the file is already in use.

Specified database is invalid

Error constant	SQLE_INVALID_DATABASE
ODBC 2 State	08001
ODBC 3 State	08001
Severity	11
SQLCODE	-84
SQLSTATE	08W11
Sybase error code	4001

Probable cause

The database file you specified is invalid. The database server is stopped.

Specified database not found

Error constant	SQLE_DATABASE_NOT_FOUND
ODBC 2 State	08001

ODBC 3 State	08001
Severity	16
SQLCODE	-83
SQLSTATE	08W10
Sybase error code	911

Probable cause

The database server was unable to find the specified database. The database server may be attempting to start a database file that cannot be opened or that cannot be found on the network. You may be attempting to connect to a database name that is not running.

Specified file system volume not found for database '%1'

Error constant	SQLE_FILE_VOLUME_NOT_FOUND
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the database.
Severity	16
SQLCODE	-1112
SQLSTATE	WW082
Sybase error code	13402

Probable cause

The file system volume you specified in the database file name was not found. Check the volume name or ordinal.

Specified local connection ID not found

Error constant	SQLE_LOCAL_CONNECTION_NOT_FOUND
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Severity	16
SQLCODE	–996
SQLSTATE	WO024
Sybase error code	709

Probable cause

There is no connection with the specified connection ID.

SQL statement error

Error constant	SQLE_STATEMENT_ERROR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	–132
SQLSTATE	26501
Sybase error code	13629

Probable cause

The statement identifier (generated by PREPARE) passed to the database for a further operation is invalid.

SQLDA data type invalid

Error constant	SQLE_SQLDA_INVALID_DATATYPE
ODBC 2 State	07001
ODBC 3 State	07W05
Severity	16
SQLCODE	–759
SQLSTATE	07W05

Sybase error code	13770
-------------------	-------

Probable cause

The data type specified for a SQLDA variable is invalid.

SQLDA fields inconsistent for a multi-row SQLDA

Error constant	SQLE_SQLDA_INCONSISTENT
ODBC 2 State	07001
ODBC 3 State	07W04
Severity	16
SQLCODE	-700
SQLSTATE	07W04
Sybase error code	13721

Probable cause

Not all of the rows in a multi-row SQLDA have been defined identically for an array operation (insert, fetch, or execute). A given column must be defined the same (type and length) in each row.

sqlpp/dblib version mismatch

Error constant	SQLE_PP_DBLIB_MISMATCH
ODBC 2 State	08801
ODBC 3 State	08001
Severity	21
SQLCODE	-230
SQLSTATE	08W18
Sybase error code	13657

Probable cause

Your executable has Embedded SQL source files that were preprocessed with a version of sqlpp that does not match the database interface library.

Start date/time for non-recurring event '%1' is in the past

Error constant	SQLE_EVENT_START_TIME_IN_PAST
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the event being scheduled.
Severity	15
SQLCODE	-1128
SQLSTATE	WE010
Sybase error code	13385

Probable cause

You have specified an event starting date or time that has already passed, and the event is not recurring.

Statement cannot be executed

Error constant	SQLE_CANNOT_EXECUTE_STMT
ODBC 2 State	OK
ODBC 3 State	OK
Severity	10
SQLCODE	111
SQLSTATE	01W08
Sybase error code	590

Probable cause

You specified a SQL statement for the PREPARE ... WITH EXECUTE statement that cannot be executed. If you specified an output SQLDA, it may contain a DESCRIBE of the prepared statement.

Statement contains an illegal usage of the non-deterministic function '%1'

Error constant	SQLE_NONDETERMINISTIC_FUNCTION
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	The name of the non-deterministic user-defined function used in error.
Severity	15
SQLCODE	-889
SQLSTATE	42W79
Sybase error code	13594

Probable cause

Non-deterministic functions cannot appear in a CHECK constraint, or any other type of integrity constraint. They may appear anywhere within a query, view, or derived table. However, if an aliased select list expression contains a non-deterministic function, that alias cannot be referred to elsewhere in the query.

Statement contains an illegal usage of the NUMBER(*) function

Error constant	SQLE_INVALID_NUMBER
ODBC 2 State	37000
ODBC 3 State	42000
Severity	15
SQLCODE	-864
SQLSTATE	42W71
Sybase error code	13869

Probable cause

The NUMBER and IDENTITY functions can only appear in the select list of the outer-most SELECT block. It cannot be used in any subquery or in a predicate.

Statement interrupted by user

Error constant	SQLE_INTERRUPTED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-299
SQLSTATE	57014
Sybase error code	3621

Probable cause

You canceled a statement during its execution. The database was able to stop the operation without doing a rollback. If the statement is INSERT, UPDATE, or DELETE, any changes made by the statement will be canceled. If the statement is a data definition statement (for example CREATE TABLE), the statement will be canceled, but the COMMIT that was done as a side effect will not be canceled.

Statement is not allowed in passthrough mode

Error constant	SQLE_STMT_NOT_ALLOWED_IN_PASSTHROUGH
ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	-707
SQLSTATE	0AW05
Sybase error code	13631

Probable cause

You tried to execute a statement that cannot be executed while in passthrough mode. For example, you may have executed a batch statement.

Statement not allowed during snapshot

Error constant	SQLE_STATEMENT_NOT_ALLOWED_IN_SNAPSHOT
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1062
SQLSTATE	42WB9
Sybase error code	13451

Probable cause

A connection with an outstanding snapshot attempted to use CREATE INDEX, DROP INDEX, ALTER INDEX or ALTER TABLE. Make sure all cursors for the connection are closed.

Statement size or complexity exceeds server limits

Error constant	SQLE_SYNTACTIC_LIMIT
ODBC 2 State	37000
ODBC 3 State	54000
Severity	19
SQLCODE	-890
SQLSTATE	54W01
Sybase error code	404

Probable cause

The statement contains one or more constructs whose size make it impossible to process. Increasing the maximum cache size, page size, or stack size may resolve this error. Consider rewriting the query so that the internal limit is not exceeded. For example, if the query contains a large IN-list, consider inserting the IN-list's values into a temporary table. Then rewrite the query to join this temporary table to the other table(s) in the original statement.

Statement timed out: '%1'

Error constant	SQLE_STATEMENT_TIMEOUT
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Statement type
Severity	16
SQLCODE	-1231
SQLSTATE	57W05
Sybase error code	13286

Probable cause

The statement failed because it did not complete within the allotted or specified time.

Statement's size limit is invalid

Error constant	SQLE_INVALID_CURSOR_RANGE
ODBC 2 State	42000
ODBC 3 State	42000
Severity	15
SQLCODE	-674
SQLSTATE	09W07
Sybase error code	13713

Probable cause

FIRST or TOP n are used in a SELECT statement to limit the size of a result. The size limit must be a constant integer greater than 0 and less than 32767.

Strongly-encrypted database files are not supported in the runtime server

Error constant	SQLE_NO_ENCRYPTION_IN_RUNTIME
ODBC 2 State	42000
ODBC 3 State	42000
Severity	16
SQLCODE	-688
SQLSTATE	55W13
Sybase error code	13879

Probable cause

You attempted to start a strongly-encrypted database with the runtime server. Use the full server.

Subquery allowed only one select list item

Error constant	SQLE_SUBQUERY_SELECT_LIST
ODBC 2 State	37000
ODBC 3 State	42000
Severity	15
SQLCODE	-151
SQLSTATE	53023
Sybase error code	102

Probable cause

You entered a subquery that has more than one column in the select list. Change the select list to have only one column.

Subquery cannot return more than one row

Error constant	SQLE_SUBQUERY_RESULT_NOT_UNIQUE
----------------	---------------------------------

ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	-186
SQLSTATE	21W01
Sybase error code	512

Probable cause

You used a subquery that returns more than one row, in a context where only a single row can be used. If the subquery is in the WHERE clause, you might be able to use the IN keyword.

Subscription to '%1' for '%2' already exists

Error constant	SQL_E_SUBSCRIPTION_NOT_UNIQUE
ODBC 2 State	S0002
ODBC 3 State	42S02
Parameter 1	Name of the publication.
Parameter 2	Name of the user.
Severity	16
SQLCODE	-282
SQLSTATE	5RW03
Sybase error code	13644

Probable cause

You attempted to create a subscription that already exists.

Subscription to '%1' for '%2' not found

Error constant	SQL_E_SUBSCRIPTION_NOT_FOUND
ODBC 2 State	S0002

ODBC 3 State	42S02
Parameter 1	Name of the publication.
Parameter 2	Name of the user.
Severity	16
SQLCODE	-283
SQLSTATE	5RW04
Sybase error code	13645

Probable cause

You attempted to drop, start, or synchronize a subscription that does not exist.

Support for materialized views is not available for this database

Error constant	SQLE_MAT_VIEWS_NOT_SUPPORTED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	15
SQLCODE	-1029
SQLSTATE	0AW15
Sybase error code	13481

Probable cause

The statement being executed requires support for materialized views, but the database being used does not have the materialized view capability.

Support for permissions on dbspaces is not available for this database

Error constant	SQLE_DBSPACE_PERMS_NOT_SUPPORTED
----------------	----------------------------------

ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	15
SQLCODE	-1183
SQLSTATE	0AW22
Sybase error code	13332

Probable cause

The statement being executed requires support for permissions on dbspaces, but the database being used does not have this capability. The database must be recreated or upgraded using a version of the server that supports permissions on dbspaces.

Synchronization download failed to complete

Error constant	SQLE_INCOMPLETE_SYNCHRONIZATION
ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	-1271
SQLSTATE	0AW23
Sybase error code	13899

Probable cause

You attempted to synchronize an UltraLite database. During the synchronization session, an incomplete download stream was received from the consolidated database. The reason for the upload failure can be found in the synchronization log file.

Synchronization failed due to an error on the server: %1

Error constant	SQLE_SERVER_SYNCHRONIZATION_ERROR
ODBC 2 State	37000

ODBC 3 State	42000
Parameter 1	The error number from the server.
Severity	16
SQLCODE	-857
SQLSTATE	0AW12
Sybase error code	13860

Probable cause

Synchronization failed at the server. More details can be found in the synchronization log file.

Synchronization is already in progress

Error constant	SQLE_SYNCHRONIZATION_IN_PROGRESS
ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	-1272
SQLSTATE	0AW24
Sybase error code	13893

Probable cause

You attempted to synchronize an UltraLite database but this database is being synchronized on another thread.

Synchronization message type '%1' not found

Error constant	SQLE_NOT_SYNC_TYPE
ODBC 2 State	S0002
ODBC 3 State	42S02
Parameter 1	Name of synchronization message type.

Severity	16
SQLCODE	-765
SQLSTATE	5RW11
Sybase error code	13775

Probable cause

You referred to a synchronization message type that is not defined in this database.

Synchronization option '%1' contains semi-colon, equal sign, curly brace, or is null

Error constant	SQLE_BAD_SYNC_OPTION_VALUE
ODBC 2 State	42000
ODBC 3 State	42S02
Parameter 1	The name of the synchronization option.
Severity	16
SQLCODE	-797
SQLSTATE	5RW32
Sybase error code	13807

Probable cause

You attempted to set a synchronization option with an invalid value.

Synchronization option '%1' not found

Error constant	SQLE_SYNC_OPTION_NOT_FOUND
ODBC 2 State	42000
ODBC 3 State	42S02
Parameter 1	The name of the synchronization option.
Severity	16

SQLCODE	–805
SQLSTATE	5RW33
Sybase error code	13815

Probable cause

You attempted to delete an undefined synchronization option.

Synchronization option is too long

Error constant	SQLE_SYNC_OPTION_TOO_LONG
ODBC 2 State	42000
ODBC 3 State	42S02
Severity	16
SQLCODE	–809
SQLSTATE	5RW34
Sybase error code	13819

Probable cause

Synchronization option list cannot be longer than the database page size.

Synchronization process was unable to re-enter synchronization

Error constant	SQLE_SYNC_NOT_REENTRANT
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	–1110
SQLSTATE	WW080
Sybase error code	13404

Probable cause

Synchronization was unable to be re-entered by the sync process. This could be caused by two different threads trying to make a synchronize call at the same time.

Synchronization profile '%1' already exists

Error constant	SQLE_SYNC_PROFILE_ALREADY_EXISTS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the synchronization profile.
Severity	16
SQLCODE	-1223
SQLSTATE	42W76
Sybase error code	13294

Probable cause

You tried to create a synchronization profile that already exists.

Synchronization profile '%1' has invalid parameter '%2'

Error constant	SQLE_SYNC_PROFILE_INVALID
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the synchronization profile that is invalid.
Parameter 2	Name of the parameter in the profile that has the problem.
Severity	16
SQLCODE	-1224
SQLSTATE	42W77
Sybase error code	13293

Probable cause

You tried to create or alter a synchronization profile using a string containing an invalid parameter setting.

Synchronization profile '%1' not found

Error constant	SQLE_SYNC_PROFILE_NOT_FOUND
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the synchronization profile.
Severity	16
SQLCODE	-1217
SQLSTATE	42W75
Sybase error code	13302

Probable cause

You tried to access a synchronization profile that the database could not find.

Synchronization profiles are not supported for this database

Error constant	SQLE_SYNC_PROFILE_UPGRADE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1225
SQLSTATE	42W78
Sybase error code	13292

Probable cause

The current database does not have catalog support for synchronization profiles. To use this feature, upgrade your database to the most recent version.

Synchronization server failed to commit the upload

Error constant	SQLE_UPLOAD_FAILED_AT_SERVER
ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	-794
SQLSTATE	0AW09
Sybase error code	13804

Probable cause

You attempted to synchronize an UltraLite database. During the synchronization session, a complete upload stream was sent that could not be committed to the consolidated database. The reason for the upload failure can be found in the synchronization log file.

Syntax error near '%1' %2

Error constant	SQLE_SYNTAX_ERROR
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	The word or symbol where the syntax error has been detected.
Parameter 2	Line number.
Severity	15
SQLCODE	-131
SQLSTATE	42W04
Sybase error code	102

Probable cause

The database server cannot understand the statement you are trying to execute. If you used a keyword (such as DATE) for a column name, try enclosing the keyword in quotation marks ("DATE").

Syntax error near '%1' -- Materialized view definition must not use the following construct: '%2'

Error constant	SQLE_MATVIEW_SYNTAX_ERROR
ODBC 2 State	42000
ODBC 3 State	ERROR
Parameter 1	Location of the feature used that is not permitted.
Parameter 2	The feature used that is not permitted.
Severity	15
SQLCODE	-1031
SQLSTATE	42WB3
Sybase error code	13479

Probable cause

You attempted to create a materialized view whose definition violates one of the restrictions.

Syntax error near '%1' -- The materialized view cannot be changed to immediate because its definition contains an illegal construct: '%2'

Error constant	SQLE_UPDATABLE_MATVIEW_SYNTAX_ERROR
ODBC 2 State	42000
ODBC 3 State	ERROR
Parameter 1	Location of the feature used that is not permitted.
Parameter 2	The feature used that is not permitted.
Severity	15
SQLCODE	-1032
SQLSTATE	42WB4
Sybase error code	13480

Probable cause

You attempted to change the refresh type to immediate for a materialized view whose definition violates one of the restrictions.

Syntax error, cannot specify IQ specific options without specifying IQ PATH

Error constant	SQLE_IQ_PATH_SYNTAX_ERROR
ODBC 2 State	37000
ODBC 3 State	42000
Severity	15
SQLCODE	-687
SQLSTATE	42W48
Sybase error code	102

Probable cause

The database server cannot understand the statement you are trying to execute. If you used a keyword (such as DATE) for a column name, try enclosing the keyword in quotation marks ("DATE").

System command failed with return code %1

Error constant	SQLE_SYSTEM_COMMAND_FAILED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Return code value.
Severity	16
SQLCODE	-910
SQLSTATE	38W01
Sybase error code	13574

Probable cause

A non-zero return code resulted when executing a system command.

System event type '%1' not found

Error constant	SQLE_EVENT_TYPE_NOT_FOUND
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the system event type that could not be found.
Severity	11
SQLCODE	-806
SQLSTATE	WE008
Sybase error code	13816

Probable cause

You have attempted to create an event with a system event type name that does not exist in the database.

SQL Anywhere error messages sorted by message text (T-Z)

Table '%1' contains an invalid reference to the ROWID function

Error constant	SQLE_INVALID_ROWID_PLACEMENT
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the table that contains the invalid reference.
Severity	15
SQLCODE	-1115
SQLSTATE	42WC1
Sybase error code	13399

Probable cause

The ROWID function cannot be used in a computed column expression or in a CHECK constraint.

Table '%1' has a foreign key with a referential action

Error constant	SQLE_TABLE_HAS_REFACTION
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the table with the referential action.
Severity	16
SQLCODE	-677
SQLSTATE	56001
Sybase error code	547

Probable cause

The table could not be renamed as it has a foreign key with a referential action. To rename the table, first drop the foreign key constraints.

Table '%1' has no columns

Error constant	SQLE_TABLE_HAS_NO_COLUMNS
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	The name of the table.
Severity	16
SQLCODE	-1273
SQLSTATE	0EW00
Sybase error code	13891

Probable cause

You attempted to create a table without columns.

Table '%1' has no primary key

Error constant	SQLE_NO_PRIMARY_KEY
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	Name of the table that does not have a primary key.
Severity	16
SQLCODE	-118
SQLSTATE	55008
Sybase error code	1719

Probable cause

You attempted an operation that required the referenced table to have a primary key. Examples of these operations include adding a foreign key, or using the ON EXISTING clause of an INSERT statement, while referring to a table that does not have a primary key. You must add a primary key to the referenced table.

Table '%1' has publications

Error constant	SQLLE_TABLE_HAS_PUBLICATIONS
ODBC 2 State	S0002
ODBC 3 State	42S02
Parameter 1	Name of the table that has publications.
Severity	16
SQLCODE	-281
SQLSTATE	5RW02
Sybase error code	13643

Probable cause

You attempted to drop a table that has publications defined.

Table '%1' is already included

Error constant	SQLLE_TABLE_ALREADY_INCLUDED
ODBC 2 State	42000
ODBC 3 State	42S02
Parameter 1	The name of the table.
Severity	16
SQLCODE	-822
SQLSTATE	5RW36
Sybase error code	13828

Probable cause

You attempted to add or modify a publication or synchronization definition such that the same table is included twice.

Table '%1' is in an outer join cycle

Error constant	SQLE_OUTER_JOIN_CYCLE
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Name of a table in the cycle.
Severity	16
SQLCODE	-136
SQLSTATE	52W14
Sybase error code	315

Probable cause

You specified outer joins that create a cycle of tables.

Table '%1' is part of a synchronization definition

Error constant	SQLE_SYNC_CONTAINS_TABLE
ODBC 2 State	42000
ODBC 3 State	42S02
Parameter 1	The name of the table.
Severity	16
SQLCODE	-819
SQLSTATE	5RW35
Sybase error code	13825

Probable cause

A table belonging to a synchronization definition cannot be dropped or altered except using dbmlsync.

Table '%1' not found

Error constant	SQLE_TABLE_NOT_FOUND
ODBC 2 State	S0002
ODBC 3 State	42S02
Parameter 1	Name of the table that could not be found.
Severity	11
SQLCODE	-141
SQLSTATE	42W33
Sybase error code	2706

Probable cause

You misspelled the name of a table, or you did not qualify a table name with the owner name. For example, you might have referred to "Employees" instead of DBA"."Employees".

Table '%1' requires a unique correlation name

Error constant	SQLE_CORRELATION_NAME_NEEDED
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Name of the table that needs a unique correlation name.
Severity	16
SQLCODE	-137
SQLSTATE	52W15
Sybase error code	315

Probable cause

You specified a join that joins a table to itself. You need to use unique correlation names in order to have multiple instances of a table.

Table already has a primary key

Error constant	SQLE_EXISTING_PRIMARY_KEY
ODBC 2 State	42000
ODBC 3 State	42000
Severity	16
SQLCODE	-112
SQLSTATE	55013
Sybase error code	1923

Probable cause

You attempted to add a primary key on a table that already has a primary key defined. You must delete the current primary key before adding a new one.

Table cannot have two primary keys

Error constant	SQLE_PRIMARY_KEY_TWICE
ODBC 2 State	42000
ODBC 3 State	42000
Severity	16
SQLCODE	-126
SQLSTATE	52W05
Sybase error code	1923

Probable cause

You specified the primary key twice in a CREATE TABLE statement.

Table created or altered after start of snapshot

Error constant	SQLE_SNAPSHOT_TABLE_CHANGED
ODBC 2 State	ERROR

ODBC 3 State	ERROR
Severity	16
SQLCODE	-1061
SQLSTATE	42WB8
Sybase error code	13452

Probable cause

A snapshot transaction attempted to use a table that was created or altered after the transaction began.

Table in use

Error constant	SQLE_TABLE_IN_USE
ODBC 2 State	40001
ODBC 3 State	40001
Severity	16
SQLCODE	-214
SQLSTATE	42W21
Sybase error code	3702

Probable cause

You attempted to ALTER or DROP a table that is being used by other active users of the database.

Table must be empty

Error constant	SQLE_TABLE_MUST_BE_EMPTY
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-116

SQLSTATE	55W02
Sybase error code	4901

Probable cause

You attempted to modify a table, and the database server can only perform the change if there are no rows in the table.

Table name '%1' is ambiguous

Error constant	SQLE_AMBIGUOUS_TABLE_NAME
ODBC 2 State	S0013
ODBC 3 State	42S13
Parameter 1	Name of an ambiguous table.
Severity	16
SQLCODE	-852
SQLSTATE	52W42
Sybase error code	13856

Probable cause

A statement has referred to a table name that is not unique. Preface the table name by an owner name.

Tables related by key constraint must both be permanent, or both be temporary and not created with ON COMMIT DELETE ROWS. For global temporary tables they must both be shared if one is shared

Error constant	SQLE_INVALID_FOREIGN_KEY_TABLE
ODBC 2 State	42000
ODBC 3 State	42000
Severity	16

SQLCODE	-850
SQLSTATE	42R02
Sybase error code	1709

Probable cause

Tables involved in a key constraint relationship must both be permanent user tables or both be temporary tables not created with ON COMMIT DELETE ROWS. Change the definition of one or both tables using ALTER TABLE.

Temporary space limit exceeded

Error constant	SQLE_TEMP_SPACE_LIMIT
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	19
SQLCODE	-1000
SQLSTATE	54W05
Sybase error code	13492

Probable cause

The connection has exceeded its temporary-space usage limit. This limit is based in part on the amount of free-space remaining on the drive containing the temporary file. Try deleting unused files from the drive, or placing the temporary file on a drive with more space available. See the -dt server option to specify a directory for temporary files.

Term length outside allowed range

Error constant	SQLE_TEXT_BAD_TERM_LENGTH
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1162

SQLSTATE	WT007
Sybase error code	13351

Probable cause

The minimum and maximum term lengths must both be greater than 0 and less than or equal to 60 characters.

Terminated by user -- transaction rolled back

Error constant	SQLE_TERMINATED_BY_USER
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-302
SQLSTATE	40W02
Sybase error code	3618

Probable cause

You canceled a statement while the database was executing. A ROLLBACK statement has been automatically executed.

Text configuration \"%1\" already exists

Error constant	SQLE_TEXT_CONFIG_ALREADY_EXISTS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The text configuration name.
Severity	16
SQLCODE	-1161
SQLSTATE	WT006
Sybase error code	13352

Probable cause

The specified text configuration name already exists.

Text configuration \"%1\".\"%2\" not found

Error constant	SQLE_TEXT_CONFIG_NOT_FOUND
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The text configuration creator.
Parameter 2	The text configuration name.
Severity	16
SQLCODE	-1160
SQLSTATE	WT005
Sybase error code	13353

Probable cause

The specified text configuration does not exist.

Text indexes are not supported for this database

Error constant	SQLE_TEXT_UPGRADE_REQUIRED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1166
SQLSTATE	WT011
Sybase error code	13347

Probable cause

The current database does not have catalog support for text indexes. To use this feature, upgrade your database to the most recent version.

Text query parser error: %1

Error constant	SQLE_TEXT_PARSER_ERROR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The error message returned by the text query parser.
Severity	16
SQLCODE	-1164
SQLSTATE	WT009
Sybase error code	13349

Probable cause

The text query could not be parsed.

The %1 algorithm is not available in FIPS mode

Error constant	SQLE_FIPS_NOT_AVAILABLE
ODBC 2 State	ERROR
ODBC 3 State	08001
Parameter 1	Name of the algorithm.
Severity	19
SQLCODE	-1071
SQLSTATE	0AW16
Sybase error code	13442

Probable cause

The specified algorithm is not available when the server is running in FIPS mode.

The '%1' attribute contains mismatched parentheses within '%2'

Error constant	SQLE_INVALID_ATTRIBUTE_MISMATCH_BRACES
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The attribute on the procedure.
Parameter 2	The value of the attribute.
Severity	16
SQLCODE	-1129
SQLSTATE	WW086
Sybase error code	13384

Probable cause

The value of the attribute is not valid due to mismatched parenthesis (or possibly braces if specifying a port option).

The '%1' attribute is missing a comma within '%2'

Error constant	SQLE_INVALID_ATTRIBUTE_MISSING_COMMA
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The attribute on the procedure.
Parameter 2	The value of the attribute.
Severity	16
SQLCODE	-1130
SQLSTATE	WW087
Sybase error code	13383

Probable cause

The value of the attribute is not valid due to a missing comma.

The '%1' attribute is not valid with procedure type '%2'

Error constant	SQLE_INVALID_ATTRIBUTE_WITH_TYPE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The attribute on the procedure.
Parameter 2	The procedure type.
Severity	16
SQLCODE	-1034
SQLSTATE	WW064
Sybase error code	13477

Probable cause

This attribute is not applicable to the given procedure type.

The '%1' property is no longer supported

Error constant	SQLE_UNSUPPORTED_PROPERTY
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the invalid property.
Severity	16
SQLCODE	-1119
SQLSTATE	42WC2
Sybase error code	13394

Probable cause

The specified property is not supported in the current release.

The aggregate expression '%1' must appear in either the select list or a HAVING clause subquery

Error constant	SQLE_INVALID_AGGREGATE_PLACEMENT
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	The aggregated expression in error.
Severity	15
SQLCODE	-862
SQLSTATE	42W69
Sybase error code	13866

Probable cause

An aggregated expression containing an outer reference must either appear in a select list expression (a subselect), or in a HAVING clause subquery in the query whose FROM clause contains the table with the column being aggregated.

The arguments to this procedure must be literal strings

Error constant	SQLE_TEXT_NEED_CONSTANT_ARGUMENT
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1216
SQLSTATE	WT017
Sybase error code	13297

Probable cause

This procedure only accepts literal strings as arguments.

The attribute '%1' sets an option '%2' that is incompatible with '%3'

Error constant	SQLE_INVALID_ATTRIBUTE_OPTIONS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The attribute on the procedure.
Parameter 2	The first option of the attribute.
Parameter 3	The second option of the attribute.
Severity	16
SQLCODE	-1131
SQLSTATE	WW088
Sybase error code	13382

Probable cause

The options specified for this attribute are not compatible.

The column '%1' does not exist in the remote table

Error constant	SQLE_OMNI_NOSUCH_COLUMN
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the column.
Severity	11
SQLCODE	-722
SQLSTATE	WO016

Sybase error code	11208
-------------------	-------

Probable cause

The column specified in the CREATE EXISTING statement does not exist in the remote table.

The communications environment could not be created

Error constant	SQLE_FAILED_TO_CREATE_STREAMS_ENV
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-740
SQLSTATE	WW024
Sybase error code	13753

Probable cause

The communications environment could not be created. Either there are insufficient resources to create the environment or the language resource file cannot be found.

The connection parameters file could not be found

Error constant	SQLE_NO_PROFILE_FILE
ODBC 2 State	08001
ODBC 3 State	08001
Severity	16
SQLCODE	-654
SQLSTATE	08W37
Sybase error code	13706

Probable cause

An attempt was made to parse a connection string containing a connection profile but the connection parameters file could not be found.

The cursor name '%1' already exists

Error constant	SQLE_DUPLICATE_CURSOR_NAME
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the cursor.
Severity	16
SQLCODE	-683
SQLSTATE	WJ004
Sybase error code	13714

Probable cause

You attempted to declare a cursor with a name that already exists. Cursor names must be unique within a connection.

The data type of column '%1' is not supported

Error constant	SQLE_OMNI_UNSUPPORTED_DATATYPE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the column.
Severity	12
SQLCODE	-736
SQLSTATE	WO022
Sybase error code	11205

Probable cause

The column is defined with a data type that is not supported for remote tables.

The data type specified for column '%1' is not compatible with the actual data type

Error constant	SQLE_OMNI_DATATYPE_MISMATCH
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the column.
Severity	12
SQLCODE	-721
SQLSTATE	WO015
Sybase error code	11209

Probable cause

The data type of the column specified in the CREATE EXISTING statement is not compatible with the actual data type of the column in the remote table.

The database '%1' was not found

Error constant	SQLE_ULTRALITE_DATABASE_NOT_FOUND
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the database specified or the default database name.
Severity	16
SQLCODE	-954
SQLSTATE	WW034
Sybase error code	13534

Probable cause

The named database was not found. Ensure your connection string properly names the desired database.

The database does not support the Java Virtual Machine

Error constant	SQLE_NO_JAVA_SUPPORT
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-758
SQLSTATE	WJ022
Sybase error code	13769

Probable cause

The Java Virtual Machine could not be started because the database does not have the proper support. It may be that the database was created with an older version of the software, or was created with the Java support disabled. If the database was created with an older version of the software the database should be upgraded to the most recent version. If the database was created with Java support disabled, then the instjava.sql script should be run against the database to enable Java support.

The database name 'utility_db' is reserved for the utility database

Error constant	SQLE_DB_ALIAS_RESERVED_UTILDB
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	19
SQLCODE	-985
SQLSTATE	08W20
Sybase error code	13504

Probable cause

You are attempting to start a database with the name "utility_db". This name is reserved for the utility database.

The database needs to be restarted for this Java related command

Error constant	SQLE_JAVA_DB_RESTART_NEEDED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-871
SQLSTATE	WJ029
Sybase error code	13875

Probable cause

Java support in the database requires a database restart after some Java related commands are performed, for example, some Java commands like ALTER DATABASE UPGRADE JAVA ON require a restart before one performs any Java related commands that load a Java class into the database.

The database was created

Error constant	SQLE_DATABASE_CREATED
ODBC 2 State	OK
ODBC 3 State	OK
Severity	10
SQLCODE	136
SQLSTATE	WW061
Sybase error code	13494

Probable cause

The specified UltraLite database was created using the specified schema when the connection was opened.

The dbicu library and server versions do not match

Error constant	SQLE_ICU_DLL_VERSION_MISMATCH
----------------	-------------------------------

ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1124
SQLSTATE	WC014
Sybase error code	13389

Probable cause

The server is unable to load ICU components that are required by this database. Ensure that the correct version of the dbicu libraries are installed.

The DBN/DBF parameters do not match the database for this alternate server name

Error constant	SQLE_WRONG_DB_ON_ALT_SERVER_NAME
ODBC 2 State	08001
ODBC 3 State	08001
Severity	11
SQLCODE	-1036
SQLSTATE	08W90
Sybase error code	13475

Probable cause

The DBN or DBF parameters specified do not match the database using the specified alternate server name.

The dbspace '%1' cannot be dropped because it contains tables or indexes

Error constant	SQLE_DBSPACE_CONTAINS_TABLES
ODBC 2 State	ERROR

ODBC 3 State	ERROR
Parameter 1	Name of the dbspace
Severity	16
SQLCODE	-1120
SQLSTATE	55W26
Sybase error code	13393

Probable cause

You attempted to drop the named dbspace, but it contains tables or indexes. You must drop the tables and/or indexes before dropping the dbspace.

The external function call is incompatible

Error constant	SQLE_INCOMPATIBLE_EXTERNAL_CALL
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-818
SQLSTATE	WW026
Sybase error code	13824

Probable cause

You attempted to call an external function. An attempt to load the attempted library failed because of incompatibility with the server. Incompatibility may arise because the dynamic library is using an external function API that is either not supported by the server or is newer than the one supported by the server.

The http header '%1' is reserved and cannot be modified

Error constant	SQLE_HTTP_HEADER_ATTRIBUTE_RESERVED_XXX
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Parameter 1	The header causing the failure.
Severity	16
SQLCODE	-1094
SQLSTATE	WW070
Sybase error code	13421

Probable cause

The specified http header is reserved and cannot be modified.

The ICU collation '%1' has defaulted to another collation

Error constant	SQLE_COLLATION_DEFAULT_WARNING
ODBC 2 State	01000
ODBC 3 State	01000
Parameter 1	The ICU collation specifier.
Severity	10
SQLCODE	201
SQLSTATE	01WC4
Sybase error code	13397

Probable cause

The specified ICU collation is not available. Another collation was substituted, which may or may not produce suitable results. Due to the structure of ICU, the collation that was used is not known, but was the best alternative to the specified collation. If this database is used on another platform, a different collation may be chosen and the operation may generate different results.

The integrated login ID guest can only be mapped to the guest database user ID

Error constant	SQLE_INTEGRATED_LOGON_GUESTMAP
ODBC 2 State	28000

ODBC 3 State	28000
Severity	16
SQLCODE	-247
SQLSTATE	28W06
Sybase error code	13695

Probable cause

You attempted to map the guest login ID to something other than guest.

The JDBC resultset must be positioned on an insert row in order to use the '%1' function

Error constant	SQLE_JDBC_MUST_OPER_ON_INSERT_ROW
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the resultset function being called.
Severity	16
SQLCODE	-753
SQLSTATE	WJ020
Sybase error code	13764

Probable cause

Resultset functions such as insertRow can only be called when the resultset is positioned on the insert row.

The JDK version in '%1' does not match '%2'

Error constant	SQLE_JDK_VERSION_MISMATCH
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	A JDK JAR file name.

Parameter 2	A JDK version string.
Severity	16
SQLCODE	-841
SQLSTATE	WJ026
Sybase error code	13847

Probable cause

The JDK version specified in the CREATE DATABASE statement does not match the JDK version in the JDK JAR file.

The length specified for column '%1' is different than the actual length

Error constant	SQLE_OMNI_LENGTH_MISMATCH
ODBC 2 State	OK
ODBC 3 State	OK
Parameter 1	The name of the column.
Severity	16
SQLCODE	-723
SQLSTATE	WO017
Sybase error code	11210

Probable cause

The length of the column specified in the CREATE EXISTING statement is different than the length of the column in the remote table.

The logging type ('%1') specified is invalid, not supported or incompatible

Error constant	SQLE_INVALID_LOAD_LOGGING_TYPE
ODBC 2 State	ERROR

ODBC 3 State	ERROR
Parameter 1	The specified logging type.
Severity	19
SQLCODE	-1151
SQLSTATE	WL010
Sybase error code	13261

Probable cause

The logging type specified for LOAD TABLE is not supported for the version of the database being used, is incompatible with other specifications of the statement or is not supported for the specific table being loaded into.

The login ID '%1' has not been mapped to any database user ID

Error constant	SQLE_LOGON_UNMAPPED
ODBC 2 State	28000
ODBC 3 State	28000
Parameter 1	Name of the login ID that is not mapped.
Severity	16
SQLCODE	-313
SQLSTATE	28W09
Sybase error code	13698

Probable cause

You attempted to connect using a login ID that is not mapped to a database user ID and there is no guest database user ID, or you attempted to revoke a login ID that has not been mapped. This can also occur when attempting to connect using an integrated login ID that is a member of more than one mapped group.

The login ID '%1' is already mapped to user ID '%2'

Error constant	SQLE_LOGON_MAPPED
ODBC 2 State	28000
ODBC 3 State	28000
Parameter 1	Name of the login ID that is already mapped.
Parameter 2	Name of the user ID that the login ID is already mapped to.
Severity	16
SQLCODE	-249
SQLSTATE	28W08
Sybase error code	13697

Probable cause

You attempted to map a login ID twice.

The materialized view %1 cannot be changed to immediate because it does not have a unique index on non-nullable columns

Error constant	SQLE_IMMEDIATE_MV_NO_UNIQUE_INDEX
ODBC 2 State	42000
ODBC 3 State	ERROR
Parameter 1	Name of the materialized view.
Severity	14
SQLCODE	-1233
SQLSTATE	42WCA
Sybase error code	13284

Probable cause

You attempted to change the refresh type to immediate for a materialized view which does not have a unique index on non-nullable columns. Create a unique index on the materialized view before changing the refresh type.

The materialized view %1 cannot be changed to immediate because it has already been initialized

Error constant	SQLE_IMMEDIATE_MV_REFRESH_NOT_ALLOWED
ODBC 2 State	42000
ODBC 3 State	ERROR
Parameter 1	Name of the materialized view.
Severity	14
SQLCODE	-1170
SQLSTATE	42WC3
Sybase error code	13343

Probable cause

You attempted to change the refresh type to immediate for a materialized view which is already in an initialized state. Truncate the view before changing the refresh type.

The materialized view cannot be changed to immediate because COUNT(*) is required to be part of the SELECT list

Error constant	SQLE_UPDATABLE_MATVIEW_MISSING_COUNT
ODBC 2 State	42000
ODBC 3 State	ERROR
Severity	15
SQLCODE	-1199
SQLSTATE	42WC6
Sybase error code	13316

Probable cause

You attempted to change the refresh type to immediate for a materialized view whose definition does not include COUNT(*) in the SELECT list.

The materialized view cannot be changed to immediate because it does not have a unique index on non-aggregate non-nullable columns

Error constant	SQLE_UPDATABLE_MATVIEW_NON_AGGR_INDEX
ODBC 2 State	42000
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1218
SQLSTATE	42WC7
Sybase error code	13299

Probable cause

You attempted to change the refresh type to immediate for a materialized view which does not have a unique index on non-aggregate non-nullable columns. Create a unique index on the materialized view before changing the refresh type.

The materialized view cannot be changed to immediate because its definition contains an illegal construct

Error constant	SQLE_UPDATABLE_MATVIEW_ERR
ODBC 2 State	42000
ODBC 3 State	ERROR
Severity	15
SQLCODE	-1268
SQLSTATE	42WCB
Sybase error code	13786

Probable cause

You attempted to change the refresh type to immediate for a materialized view whose definition contains an illegal construct.

The materialized view cannot be changed to immediate because its definition must not contain more than one query block

Error constant	SQLC_UPDATABLE_MATVIEW_MULTIPLE_BLOCK_ERR
ODBC 2 State	42000
ODBC 3 State	ERROR
Severity	15
SQLCODE	-1181
SQLSTATE	42WC5
Sybase error code	13334

Probable cause

You attempted to change the refresh type to immediate for a materialized view whose definition contains more than one query block.

The method you attempted to invoke was not enabled for your application

Error constant	SQLC_FEATURE_NOT_ENABLED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1092
SQLSTATE	0A001
Sybase error code	13442

Probable cause

You attempted to call a method or use a feature that has not been enabled. In UltraLite features are enabled using ULEnable functions or by using ULEnableDatabaseManager instead of ULEnableDatabaseManagerNoSQL.

The mirror '%1' does not match database '%2'

Error constant	SQLE_MIRROR_FILE_MISMATCH
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the mirror file
Parameter 2	The name of the database file
Severity	16
SQLCODE	-1138
SQLSTATE	WW090
Sybase error code	13375

Probable cause

The named mirror file does not correspond to the database file. This could happen if the database was not shut down properly, or if the wrong mirror file was specified. The mirror file must be moved or discarded before proceeding, or a different mirror specified.

The operation failed because column '%1's type does not support streaming

Error constant	SQLE_COLUMN_NOT_STREAMABLE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The number of the column whose type is invalid.
Severity	16
SQLCODE	-1100
SQLSTATE	WW045

Sybase error code	13414
-------------------	-------

Probable cause

The only column types that support streaming are: BINARY, LONG BINARY, VARCHAR and LONG VARCHAR. This error could also occur when allocating a stream object twice on the same column.

The optimizer was unable to construct a valid access plan

Error constant	SQLC_CANNOT_OPTIMIZE_QUERY
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	18
SQLCODE	-727
SQLSTATE	WI010
Sybase error code	13730

Probable cause

The database server was unable to construct a valid access plan for the given request. This is a SQL Anywhere internal error. If it can be reproduced, it should be reported to iAnywhere. You may be able to work around this problem by modifying the query statement.

The option '%1' can only be set as a temporary option

Error constant	SQLC_OPTION_IS_TEMP_ONLY
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	Name of the option that could not be set.
Severity	14
SQLCODE	-216
SQLSTATE	42W52
Sybase error code	5878

Probable cause

The option specified in the SET OPTION statement can only be set as a temporary option.

The option '%1' cannot be set from within a procedure

Error constant	SQLE_OPTION_IN_PROCEDURE
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	Name of the option that could not be set.
Severity	14
SQLCODE	-217
SQLSTATE	42W53
Sybase error code	5878

Probable cause

The option specified in the SET OPTION statement cannot be set from within a procedure.

The option '%1' is not recognized

Error constant	SQLE_UNRECOGNIZED_OPTION
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the option.
Severity	16
SQLCODE	-1002
SQLSTATE	WW062
Sybase error code	13494

Probable cause

The specified option was not recognized. The option may have been spelled incorrectly.

The pattern is too long

Error constant	SQLE_PATTERN_TOO_LONG
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-606
SQLSTATE	WW001
Sybase error code	7706

Probable cause

The pattern for the LIKE operator is too long. All patterns of 126 characters or less are supported. Some patterns as long as 254 characters are supported, depending on their contents. Patterns longer than 254 characters are not supported.

The provided stoplist is too long

Error constant	SQLE_TEXT_STOPLIST_TOO_LONG
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1240
SQLSTATE	WT018
Sybase error code	13277

Probable cause

A text configuration stop list must be less than 8000 bytes.

The Remote Data Services feature is not supported on this platform

Error constant	SQLE_OMNI_FEATURE_NOT_SUPPORTED
----------------	---------------------------------

ODBC 2 State	37000
ODBC 3 State	42000
Severity	15
SQLCODE	-1139
SQLSTATE	0AW18
Sybase error code	13374

Probable cause

You attempted to use a Remote Data Services feature, however, Remote Data Services are not supported on this platform.

The remote server does not support an auto-incrementing data type

Error constant	SQLE_OMNI_AUTOINC_NOT_SUPPORTED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	12
SQLCODE	-698
SQLSTATE	WO011
Sybase error code	11205

Probable cause

Auto-incrementing data types can only be supported in a proxy table when the remote server supports this feature.

The remote table '%1' could not be found

Error constant	SQLE_OMNI_RMT_TABLE_NOTFOUND
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Parameter 1	The complete name of the remote table.
Severity	11
SQLCODE	-666
SQLSTATE	WO007
Sybase error code	11214

Probable cause

The table could not be found on the remote server. Check the remote table name and the user privileges on that table.

The result returned is non-deterministic

Error constant	SQL_NONDETERMINISTIC_RESULT
ODBC 2 State	01000
ODBC 3 State	01000
Severity	10
SQLCODE	122
SQLSTATE	01W18
Sybase error code	13883

Probable cause

FIRST or TOP n are used in a SELECT statement to limit the size of a result. The statement must also have an ORDER BY if the result is to be well-defined. If it does not have an ORDER BY, then the server is free to return any subset of the result that has the requested number of rows.

The secure connection to the remote host failed: %1

Error constant	SQL_SECURE_CONNECTION_FAILED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	A message describing the error that occurred.

Severity	19
SQLCODE	-990
SQLSTATE	WW059
Sybase error code	13499

Probable cause

The server was unable to initiate a secure connection with the remote host.

The select list for the derived table '%1' has no expression to match '%2'

Error constant	SQLE_NO_MATCHING_SELECT_ITEM
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Name of the derived table.
Parameter 2	Name of the alias for which there is no matching expression.
Severity	15
SQLCODE	-812
SQLSTATE	42W59
Sybase error code	13822

Probable cause

The specified alias from the derived table's AS clause has no matching expression from the SELECT statement for that derived table. Ensure that each select list item has a matching alias in the derived table's AS clause, and vice-versa.

The selected database is currently inactive

Error constant	SQLE_DATABASE_NOT_ACTIVE
ODBC 2 State	08001
ODBC 3 State	08001

Severity	14
SQLCODE	-74
SQLSTATE	08W30
Sybase error code	950

Probable cause

The selected database is in an inactive state. The database may be in the process of being started or shut down.

The server attempted to access a page beyond the end of the maximum allowable dbspace file size

Error constant	SQL_ACCESS_BEYOND_END_OF_MAX_DBSPACE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-605
SQLSTATE	04W08
Sybase error code	5006

Probable cause

The database attempted to access a page whose page number is beyond the maximum possible number of disk pages. This is a fatal internal error.

The size of the character column, variable, or value data type exceeds 32767

Error constant	SQL_CHAR_FIELD_SIZE_EXCEEDED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	19

SQLCODE	–1093
SQLSTATE	54W09
Sybase error code	13422

Probable cause

The declaration or conversion has specified a character type with byte length greater than 32767.

The specified foreign key (%1) can not be enforced

Error constant	SQLE_UNENFORCEABLE_FOREIGN_KEY
ODBC 2 State	23000
ODBC 3 State	23000
Parameter 1	Name of the foreign key.
Severity	16
SQLCODE	–729
SQLSTATE	23507
Sybase error code	549

Probable cause

You attempted to create a foreign key that cannot be enforced. In order to be enforceable, the primary and foreign table for the specified key must exist on the same server. You can use the UNENFORCED keyword to create a foreign key specification that is not to be enforced.

The specified http header contains illegal or non-ASCII characters

Error constant	SQLE_HTTP_HEADER_ATTRIBUTE_ASCII
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	–1095

SQLSTATE	WW071
Sybase error code	13420

Probable cause

Http headers must contain printable ASCII characters.

The specified http header is malformed

Error constant	SQLE_HTTP_HEADER_ATTRIBUTE_MALFORMED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1096
SQLSTATE	WW072
Sybase error code	13419

Probable cause

The http header is missing the colon delimiter or a folding construct is malformed.

The specified listener could not be registered

Error constant	SQLE_CANNOT_REGISTER_LISTENER
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	17
SQLCODE	-992
SQLSTATE	54W04
Sybase error code	13497

Probable cause

The specified listener could not be registered because the maximum number of listeners has been reached, the class name is already in use, or system resources are not available.

The specified transaction isolation is invalid

Error constant	SQLE_INVALID_TRANSACTION_ISOLATION
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	15
SQLCODE	-676
SQLSTATE	WJ003
Sybase error code	7374

Probable cause

The specified transaction isolation is invalid.

The SQL scripts DLL cannot be loaded

Error constant	SQLE_INVALID_SCRIPT_DLL
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1150
SQLSTATE	WW091
Sybase error code	13362

Probable cause

The SQL scripts DLL cannot be loaded. The DLL might be missing or the version found might not match the version of the database server being used.

The status of the last synchronization upload is unknown

Error constant	SQLE_SYNC_STATUS_UNKNOWN
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-952
SQLSTATE	WW032
Sybase error code	13536

Probable cause

The status of the last synchronization upload is unknown. The current operation cannot proceed until a successful upload is synchronized.

The string is too long (%1)

Error constant	SQLE_STRING_PARM_TOO_LONG
ODBC 2 State	37000
ODBC 3 State	54000
Parameter 1	The string that is longer than that allowed by the server.
Severity	15
SQLCODE	-973
SQLSTATE	54W06
Sybase error code	13515

Probable cause

The string is longer than that allowed by the server.

The table specification '%1' identifies more than one remote table

Error constant	SQLE_OMNI_RMT_TABLE_NOTUNIQUE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The complete name of the remote table.
Severity	11
SQLCODE	-726
SQLSTATE	WO020
Sybase error code	11215

Probable cause

More than one table was found on the remote server for the given table specification. Add a database or owner name to the specification.

The text index %1 needs to be refreshed

Error constant	SQLE_TEXT_MATCHING_INDEX_NOT_REFRESHED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the text index that needs to be refreshed.
Severity	16
SQLCODE	-1253
SQLSTATE	WT019
Sybase error code	13260

Probable cause

There is a text index that matches the query, but it needs to be refreshed before it is used.

The URI '%1' is invalid

Error constant	SQLE_INVALID_URI
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The invalid URI.
Severity	16
SQLCODE	-980
SQLSTATE	WW049
Sybase error code	13509

Probable cause

The specified URI is not valid.

The UTF-16 endian specified does not match the Byte Order Mark found in the data

Error constant	SQLE_UTF16_ENDIAN_MISMATCH
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1189
SQLSTATE	WC004
Sybase error code	13326

Probable cause

The specified UTF-16 encoding explicitly specifies the expected endian of the data; however, the Byte Order Mark found at the beginning of the data indicates that the data is encoded in the opposite endian.

There are still active database connections

Error constant	SQLE_STILL_ACTIVE_CONNECTIONS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-109
SQLSTATE	08W06
Sybase error code	6001

Probable cause

You attempted to shut down a database that still has active connections.

There is already a variable named '%1'

Error constant	SQLE_VARIABLE_EXISTS
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Name of the variable that already exists.
Severity	15
SQLCODE	-261
SQLSTATE	42W15
Sybase error code	134

Probable cause

You attempted to create a variable with the name of another variable that already exists.

There is more than one way to join '%1' to '%2'

Error constant	SQLE_AMBIGUOUS_JOIN
----------------	---------------------

ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Name of first table that cannot be joined.
Parameter 2	Name of second table that cannot be joined.
Severity	16
SQLCODE	-147
SQLSTATE	52W08
Sybase error code	301

Probable cause

You are attempting to KEY JOIN two tables, and there are two or more foreign keys relating the two tables. There may be two foreign keys from the first table to the second table. It may be that each table has a foreign key to the other table. You must use a correlation name for the primary key table that is the same as the role name of the desired foreign key relationship.

There is no way to join '%1' to '%2'

Error constant	SQLC_CANNOT_JOIN
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Name of first table that cannot be joined.
Parameter 2	Name of second table that cannot be joined.
Severity	16
SQLCODE	-146
SQLSTATE	53W04
Sybase error code	301

Probable cause

You may have attempted a KEY JOIN between two tables and there is no foreign key on one of the tables that references the primary key of the other table. You may have attempted a NATURAL JOIN between two tables that have no common column names.

There is no way to join to '%1'

Error constant	SQLE_CANNOT_JOIN_TABEXPR
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Name of table or view that cannot be joined.
Severity	15
SQLCODE	-875
SQLSTATE	42W73
Sybase error code	102

Probable cause

The server cannot discover a valid join condition involving this table. If the join is an outer join, you may be missing an ON clause. If the join is a KEY JOIN, the server cannot discover a foreign key-primary key relationship with this table that can be used to generate the join condition. If the join is a NATURAL JOIN, the table has no common column names with the table expression it is being joined to.

This connection already exists

Error constant	SQLE_CONNECTION_ALREADY_EXISTS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-955
SQLSTATE	WW035
Sybase error code	13533

Probable cause

A connection with the given SQLCA and name (or no name) already exists. Before connecting you must disconnect the existing connection, or specify a different connection name.

This database does not support encrypted tables

Error constant	SQLE_ENCRYPTED_TABLES_NOT_SUPPORTED
ODBC 2 State	42000
ODBC 3 State	42000
Severity	16
SQLCODE	-1047
SQLSTATE	55W20
Sybase error code	13464

Probable cause

You tried to create an encrypted table in a database that does not support them.

This edition of SQL Anywhere is not available on this platform

Error constant	SQLE_PLATFORM_NOT_LICENSED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1262
SQLSTATE	0A004
Sybase error code	13251

Probable cause

This edition of SQL Anywhere is not available on this platform. You must use a different license key to use SQL Anywhere on this platform.

This server is not licensed to support '%1' connections

Error constant	SQLE_CONNECTION_PROTOCOL_NOT_LICENSED
----------------	---------------------------------------

ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The unlicensed connection type.
Severity	16
SQLCODE	-1261
SQLSTATE	0A003
Sybase error code	13252

Probable cause

You attempted to use a connection protocol or api that is not licensed in this edition of SQL Anywhere.

This server is not licensed to support the '%1' feature

Error constant	SQLE_FEATURE_NOT_LICENSED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The unlicensed feature.
Severity	16
SQLCODE	-1260
SQLSTATE	0A002
Sybase error code	13253

Probable cause

You attempted to carry out an operation or use a feature that is not licensed in this edition of SQL Anywhere.

TLS handshake failure

Error constant	SQLE_TLS_HANDSHAKE_FAILED
ODBC 2 State	08S01

ODBC 3 State	08S01
Severity	21
SQLCODE	-829
SQLSTATE	08W59
Sybase error code	13835

Probable cause

The connection failed because of a failure in the TLS handshaking process.

TLS initialization on server failed

Error constant	SQLE_TLS_INIT_FAILED_ON_SRV
ODBC 2 State	08S01
ODBC 3 State	08S01
Severity	21
SQLCODE	-838
SQLSTATE	08W61
Sybase error code	13844

Probable cause

The connection failed because the initialization of the TLS library on the server failed.

Too few columns

Error constant	SQLE_FOR_XML_EXPLICIT_TOO_FEW_COLUMNS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-902

SQLSTATE	WX010
Sybase error code	13581

Probable cause

FOR XML EXPLICIT requires at least three columns: the tag column, the parent column, and one or more data columns.

Too many arguments for function or procedure '%1'

Error constant	SQLE_TOO_MANY_ARGUMENTS
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	The name of the function or procedure.
Severity	16
SQLCODE	-994
SQLSTATE	42WAC
Sybase error code	401

Probable cause

You supplied an argument list that the database server cannot handle. This can happen if the argument list of the function or stored procedure is too long. Rebuilding the database with a larger page size could prevent this error.

Too many columns in procedure result set

Error constant	SQLE_TOO_MANY_COLUMNS_IN_PROC_RES
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1237
SQLSTATE	54W15

Sybase error code	13281
-------------------	-------

Probable cause

You executed a statement with too many expressions in the GROUP BY list. The number of expressions within a GROUP BY list is limited to 60000. You executed a CREATE PROCEDURE or ALTER PROCEDURE statement. The resulting number of columns in the result set of the procedure would exceed the server's limit.

Too many columns in SELECT list

Error constant	SQL_E_TOO_MANY_COLUMNS_IN_SELECT
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1235
SQLSTATE	54W13
Sybase error code	13283

Probable cause

You executed a statement with too many expressions in the SELECT list. The number of expressions within a SELECT list is limited to 60000.

Too many columns in table

Error constant	SQL_E_TOO_MANY_COLUMNS_IN_TABLE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-616
SQLSTATE	52W20
Sybase error code	1702

Probable cause

You executed a CREATE TABLE or ALTER TABLE statement that attempted to add a column to a table. The resulting number of columns in the table would exceed the limit for the current database page size.

Too many constraints in database

Error constant	SQLE_TOO_MANY_CONSTRAINTS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-936
SQLSTATE	54W02
Sybase error code	13551

Probable cause

An attempt to create a new constraint failed because the corresponding system table is full. Reloading the database will reclaim any unused space.

Too many distinct group mappings for integrated user

Error constant	SQLE_INTEGRATED_LOGON_TOO_MANY_MAPPINGS
ODBC 2 State	28000
ODBC 3 State	28000
Severity	16
SQLCODE	-1003
SQLSTATE	28W10
Sybase error code	13490

Probable cause

The integrated user does not have an explicit mapping in the database but does have group mappings. There are too many distinct group mappings. You must either reduce the number of distinct group mappings or add an explicit mapping for the user.

Too many expressions in GROUP BY list

Error constant	SQLE_TOO_MANY_COLUMNS_IN_GROUPBY
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1236
SQLSTATE	54W14
Sybase error code	13282

Probable cause

You executed a statement with too many expressions in the GROUP BY list. The number of expressions within a GROUP BY list is limited to 60000.

Too many expressions in GROUP BY list for ROLLUP, CUBE, or GROUPING SETS operation

Error constant	SQLE_TOO_MANY_GROUPING_EXPRESSIONS
ODBC 2 State	37000
ODBC 3 State	42000
Severity	15
SQLCODE	-944
SQLSTATE	42WA1
Sybase error code	13544

Probable cause

You specified too many expressions in the GROUP BY list for the requested ROLLUP, CUBE, or GROUPING SETS operation. The current environment where SQL Anywhere is executing cannot support this number of expressions in the GROUP BY list for the requested operation.

Too many MESSAGE ... FOR CONNECTION messages

Error constant	SQLE_CONNECTION_MESSAGE_QUEUE_FULL
ODBC 2 State	37000
ODBC 3 State	54000
Severity	19
SQLCODE	-1303
SQLSTATE	54W16
Sybase error code	13457

Probable cause

You executed a MESSAGE ... FOR CONNECTION statement and the maximum number of messages for the connection have already been queued.

Too many open cursors

Error constant	SQLE_TOO_MANY_CURSORS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	17
SQLCODE	-1230
SQLSTATE	54W12
Sybase error code	13287

Probable cause

You exceeded the number of cursors allowed to be open on a single UltraLite database. Check to ensure you are freeing statements when you are done with them.

Too many parameters to this external procedure call

Error constant	SQLE_TOO_MANY_PARAMETERS
----------------	--------------------------

ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	19
SQLCODE	-625
SQLSTATE	WW010
Sybase error code	13680

Probable cause

There is a maximum of 256 parameters to an external function call in 32-bit Windows.

Too many publications specified for operation

Error constant	SQLE_TOO_MANY_PUBLICATIONS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1106
SQLSTATE	WW077
Sybase error code	13408

Probable cause

You have specified too many publications for the required operation. For example, when retrieving the last download timestamp, you are only allowed to select one publication.

Too many recursive iterations

Error constant	SQLE_TOO_MANY_RECURSIVE_ITERATIONS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16

SQLCODE	-923
SQLSTATE	57015
Sybase error code	13561

Probable cause

A recursive query ran for more iterations than allowed by the current max_recursive_iterations option setting.

Too many references to a BLOB

Error constant	SQLE_TOO_MANY_BLOB_REFS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1107
SQLSTATE	54W11
Sybase error code	13407

Probable cause

You have exceeded the maximum number of references to a particular BLOB. In UltraLite you may have at most 256 references to any one particular BLOB.

Too many temporary tables in connection

Error constant	SQLE_TOO_MANY_TEMP_TABLES
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-817
SQLSTATE	52W41
Sybase error code	13823

Probable cause

A CREATE TABLE or DECLARE TABLE statement attempted to create a temporary table, but the resulting number of distinct table ids used for temporary tables in the current connection would exceed the limit.

Too many users in database

Error constant	SQLE_TOO_MANY_USERS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1104
SQLSTATE	54W10
Sybase error code	13410

Probable cause

You have exceeded the maximum number of users permitted to access the database. The maximum number of users that are allowed granted access to a single UltraLite database is four.

Traced query (%1, %2) does not exist

Error constant	SQLE_INVALID_TRACED_PLAN
ODBC 2 State	28000
ODBC 3 State	28000
Parameter 1	The specified logging session id.
Parameter 2	The specified query id.
Severity	16
SQLCODE	-1154
SQLSTATE	55W28
Sybase error code	13359

Probable cause

You attempted to generate a graphical plan for a query saved by diagnostic tracing, identified by a logging_session_id and query id. However, no such query exists in this database. If it was traced, it was sent to a different database.

Transact-SQL feature not supported

Error constant	SQLE_TSQL_FEATURE_NOT_SUPPORTED
ODBC 2 State	37000
ODBC 3 State	42000
Severity	15
SQLCODE	-611
SQLSTATE	0AW02
Sybase error code	176

Probable cause

You attempted to use a Transact-SQL feature that is not supported in SQL Anywhere.

Transact-SQL outer joins are currently disabled

Error constant	SQLE_TSQL_OUTER_JOINS_DISABLED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	15
SQLCODE	-1099
SQLSTATE	55W25
Sybase error code	13416

Probable cause

The ability to specify a Transact-SQL outer join in a query is currently disabled by the setting of the tsq_outer_joins connection option. Transact-SQL outer joins are deprecated in this release of SQL Anywhere.

Transaction log backup page only partially full

Error constant	SQLE_BACKUP_PAGE_INCOMPLETE
ODBC 2 State	OK
ODBC 3 State	OK
Severity	10
SQLCODE	110
SQLSTATE	01W10
Sybase error code	13683

Probable cause

A DB_LOG_BACKUP_READ_WAIT was issued against the transaction log and the page returned was not full. The application should reissue the request for the same page.

Transaction log mirroring cannot be used with database mirroring

Error constant	SQLE_MIRROR_LOG_WITH_DB_MIRROR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1178
SQLSTATE	WW095
Sybase error code	13336

Probable cause

Transaction log mirroring cannot be used with database mirroring. Use the DBLOG utility to disable transaction log mirroring.

Transaction log was truncated

Error constant	SQLE_LOG_TRUNCATED
----------------	--------------------

ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-244
SQLSTATE	WB005
Sybase error code	13661

Probable cause

An operation was being performed on the transaction log such as SQL Remote or Replication Agent processing and the transaction log was truncated by an independent backup during that operation.

Trigger '%1' not found

Error constant	SQLE_TRIGGER_NOT_FOUND
ODBC 2 State	S0002
ODBC 3 State	42S02
Parameter 1	Name of the trigger that could not be found.
Severity	11
SQLCODE	-268
SQLSTATE	52W10
Sybase error code	9819

Probable cause

You misspelled the name of a trigger, or you did not qualify a trigger name with a user name.

Trigger definition conflicts with existing triggers

Error constant	SQLE_TRIGGER_DEFN_CONFLICT
ODBC 2 State	S0002
ODBC 3 State	42S01

Severity	15
SQLCODE	-271
SQLSTATE	52W11
Sybase error code	102

Probable cause

You attempted to create a trigger, but a trigger with the same name already exists.

Trigger name '%1' is ambiguous

Error constant	SQLE_AMBIGUOUS_TRIGGER_NAME
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Name of the ambiguous trigger.
Severity	16
SQLCODE	-855
SQLSTATE	42W66
Sybase error code	13858

Probable cause

A statement has referred to a trigger name that is not unique. Qualify the trigger name with the table and/or owner name.

Trigger or foreign key for table '%1' is no longer valid

Error constant	SQLE_TRIGGER_NO_LONGER_VALID
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Name of the table.
Severity	15

SQLCODE	-837
SQLSTATE	42W64
Sybase error code	13843

Probable cause

A trigger definition cannot be loaded from the catalog. Check for tables or columns that have been renamed or that may be reserved words. The trigger may be a system-generated trigger to enforce the referential actions of a foreign key.

Triggers and procedures not supported in runtime server

Error constant	SQLE_PROCEDURES_NOT_IN_DESKTOP
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	15
SQLCODE	-275
SQLSTATE	0AW04
Sybase error code	102

Probable cause

You attempted to call a stored procedure or have modified a row in a table on which a trigger is defined and you are using the runtime server. Triggers and stored procedures are not supported in the runtime server. You must run the full server to use these features.

Triggers cannot be created on materialized view '%1'

Error constant	SQLE_INVALID_TRIGGER_MATVIEW
ODBC 2 State	42000
ODBC 3 State	ERROR
Parameter 1	Name of the materialized view
Severity	14

SQLCODE	-1134
SQLSTATE	42W3D
Sybase error code	13379

Probable cause

You attempted to create a trigger on a materialized view. A materialized view is not a valid target for a trigger.

TRUNCATE TABLE not allowed: initialized immediate materialized view %1 depends on %2

Error constant	SQLE_TRUNCATE_TABLE_WITH_IMV
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the dependent initialized immediate materialized view.
Parameter 2	Name of the table on which TRUNCATE TABLE was performed.
Severity	16
SQLCODE	-1193
SQLSTATE	55W30
Sybase error code	13322

Probable cause

TRUNCATE TABLE is not permitted on any table that has dependent initialized immediate materialized views.

TRUNCATE TABLE statement cannot be used on a view

Error constant	SQLE_CANNOT_TRUNCATE_VIEW
ODBC 2 State	37000
ODBC 3 State	42000
Severity	16

SQLCODE	-702
SQLSTATE	42W49
Sybase error code	4708

Probable cause

You attempted to use TRUNCATE TABLE on a view, which is not permitted.

Two rows with the same primary key have been download for table '%1'

Error constant	SQLE_DUPLICATE_ROW_FOUND_IN_DOWNLOAD
ODBC 2 State	01000
ODBC 3 State	01000
Parameter 1	Name of the table being downloaded.
Severity	10
SQLCODE	145
SQLSTATE	01W27
Sybase error code	13254

Probable cause

The synchronization scripts are producing duplicate rows with the same primary key in your download. Generally this indicates a problem with the synchronization scripts. No guarantees are made about which of the downloaded rows will be applied to the database.

UltraLite connection was restored

Error constant	SQLE_CONNECTION_RESTORED
ODBC 2 State	OK
ODBC 3 State	OK
Severity	10
SQLCODE	133

SQLSTATE	WW040
Sybase error code	13519

Probable cause

The connection attempt completed successfully and the transaction was restored from a suspended state.

UltraLite cursor (or result set or table) was restored

Error constant	SQLE_CURSOR_RESTORED
ODBC 2 State	OK
ODBC 3 State	OK
Severity	10
SQLCODE	134
SQLSTATE	WW041
Sybase error code	13518

Probable cause

The cursor (or result set or table) was opened successfully and the cursor position was restored from the suspended state.

UltraLite database state was restored

Error constant	SQLE_DATABASE_STATE_RESTORED
ODBC 2 State	OK
ODBC 3 State	OK
Severity	10
SQLCODE	142
SQLSTATE	WW114
Sybase error code	13276

Probable cause

The database state was restored from the temporary file. This includes suspended connections, transactions, and cursors.

Unable to access the filesystem on the device

Error constant	SQLE_CANNOT_ACCESS_FILESYSTEM
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1108
SQLSTATE	WW078
Sybase error code	13406

Probable cause

On a Palm device, you have tried to utilize the VFS filesystem, but that feature has not been enabled on the device.

Unable to acquire table locks in specified time

Error constant	SQLE_LOCK_TIMEOUT
ODBC 2 State	40001
ODBC 3 State	40001
Severity	21
SQLCODE	-1175
SQLSTATE	42WC4
Sybase error code	13338

Probable cause

The LOCK TABLE command could not acquire all the locks in specified time period

Unable to close the cursor on table \"%1\". LOAD TABLE cannot be executed

Error constant	SQLE_CANNOT_LOAD_TEMP_WITH_CURSOR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the table.
Severity	16
SQLCODE	-1155
SQLSTATE	WL011
Sybase error code	13358

Probable cause

You cannot perform LOAD TABLE on a temporary table that has an open cursor on it. An attempt to close the cursor failed. A failed LOAD TABLE would cause all of the rows in the temporary table to be deleted thereby invalidating the cursor.

Unable to connect to server '%1': %2

Error constant	SQLE_OMNI_CONNECT_ERROR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the server that could not be connected to.
Parameter 2	A more specific reason returned from the server class driver.
Severity	16
SQLCODE	-656
SQLSTATE	WO001
Sybase error code	11206

Probable cause

You attempted to connect to a remote server. Check that the remote server is running.

Unable to connect to the remote host specified by '%1'

Error constant	SQLE_UNABLE_TO_CONNECT_TO_HOST
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The URI referencing the remote host.
Severity	19
SQLCODE	-981
SQLSTATE	WW050
Sybase error code	13508

Probable cause

A connection could not be initiated to the remote server.

Unable to connect, server definition is circular

Error constant	SQLE_OMNI_CIRCULAR_CONNECT
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-657
SQLSTATE	WO002
Sybase error code	13593

Probable cause

You attempted to connect to a remote server that maps to the local database.

Unable to connect: The server did not accept the requested encryption type

Error constant	SQLE_ENCRYPTION_TYPE_NOT_ACCEPTED
----------------	-----------------------------------

ODBC 2 State	08001
ODBC 3 State	08001
Severity	16
SQLCODE	-1145
SQLSTATE	08W97
Sybase error code	13367

Probable cause

The server only accepts certain encryption types, and the connection's encryption type is not one of the accepted types. The -ec server option is used to configure the encryption types that the server accepts.

Unable to delete database file

Error constant	SQLE_BACKUP_UNABLE_TO_DELETE_FILE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-243
SQLSTATE	WB004
Sybase error code	13660

Probable cause

You attempted to delete a database file, but it could not be deleted. The file name should not be the same as any database file that is currently in use.

Unable to enlist transaction; DTC may be down

Error constant	SQLE_FAILED_TO_ENLIST
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Severity	17
SQLCODE	-803
SQLSTATE	WL005
Sybase error code	13813

Probable cause

You tried to enlist a transaction but DTC does not seem to be available at this time.

Unable to find in index '%1' for table '%2'

Error constant	SQLE_NOT_FOUND_IN_INDEX
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of invalid index.
Parameter 2	Name of table containing the invalid index.
Severity	11
SQLCODE	-189
SQLSTATE	WI005
Sybase error code	2727

Probable cause

This is an internal error. If it can be reproduced, it should be reported to iAnywhere. You should be able to work around the error by dropping and recreating the index.

Unable to open backup log '%1'

Error constant	SQLE_UNABLE_TO_OPEN_BACKUP_LOG
ODBC 2 State	OK
ODBC 3 State	OK
Parameter 1	Backup log file name.

Severity	10
SQLCODE	119
SQLSTATE	WB011
Sybase error code	13776

Probable cause

The server was unable to open the backup log to record the execution of a BACKUP or RESTORE statement. Check the settings of the environment variables used to locate the backup log file. The directory to contain the log must already exist.

Unable to perform requested operation since this database uses keyless encryption

Error constant	SQLE_KEYLESS_ENCRYPTION
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1109
SQLSTATE	WW079
Sybase error code	13405

Probable cause

The operation you requested on the encryption key failed since the UltraLite database uses keyless encryption. This can occur when you try to change the encryption key for a keyless encrypted database.

Unable to reenlist transaction; DTC may be down

Error constant	SQLE_FAILED_TO_REENLIST
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	17

SQLCODE	-804
SQLSTATE	WL006
Sybase error code	13814

Probable cause

You tried to recover a transaction but DTC does not seem to be available at this time.

Unable to retry download because upload is not finished

Error constant	SQLE_DOWNLOAD_RESTART_FAILED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1102
SQLSTATE	WW074
Sybase error code	13412

Probable cause

The MobiLink server could not restart the download because the MobiLink server has not received the entire upload stream.

Unable to start database %1: Cannot use read-only mode if auditing is enabled

Error constant	SQLE_AUDITING_DB_READ_ONLY
ODBC 2 State	08001
ODBC 3 State	08001
Parameter 1	Name of the database.
Severity	11
SQLCODE	-1063

SQLSTATE	08W93
Sybase error code	840

Probable cause

The specified database has auditing enabled, and cannot be started read-only.

Unable to start database \"%1\": CHAR collation or tailoring not supported on this platform

Error constant	SQLE_CHAR_COLLATION_NOT_SUPPORTED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The database name.
Severity	16
SQLCODE	-1140
SQLSTATE	WC015
Sybase error code	13373

Probable cause

The specified CHAR collation is not supported on the current platform.

Unable to start database \"%1\": NCHAR collation or tailoring not supported on this platform

Error constant	SQLE_NCHAR_COLLATION_NOT_SUPPORTED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The database name.
Severity	16
SQLCODE	-1141

SQLSTATE	WC016
Sybase error code	13372

Probable cause

The specified NCHAR collation is not supported on the current platform.

Unable to start database server

Error constant	SQLE_UNABLE_TO_START_ENGINE
ODBC 2 State	08001
ODBC 3 State	08001
Severity	17
SQLCODE	-80
SQLSTATE	08W07
Sybase error code	708

Probable cause

It was not possible to start the database server. There may not be enough memory to run the database server. It may be that the executable cannot be found.

Unable to start database server: missing license file

Error constant	SQLE_UNABLE_TO_START_ENGINE_MISSING_LICENSE
ODBC 2 State	08001
ODBC 3 State	08001
Severity	17
SQLCODE	-1179
SQLSTATE	08WA2
Sybase error code	708

Probable cause

It was not possible to start the database server because the server license file was not found. The server license file has the same name as the server executable with the extension ".lic".

Unable to start database server: Server fatal error

Error constant	SQLE_UNABLE_TO_START_ENGINE_FATAL_ERROR
ODBC 2 State	08001
ODBC 3 State	08001
Severity	17
SQLCODE	-1033
SQLSTATE	08W89
Sybase error code	13478

Probable cause

The database server failed to start because a fatal error or assertion failure occurred. More information may be available in the Windows event log or Unix system log or by manually starting the database server.

Unable to start specified database: %1

Error constant	SQLE_UNABLE_TO_START_DATABASE
ODBC 2 State	08001
ODBC 3 State	08001
Parameter 1	Reason the database could not be started, if known.
Severity	11
SQLCODE	-82
SQLSTATE	08W09
Sybase error code	840

Probable cause

The database server was unable to start the specified database. Check the server window messages area for more details. If the server was being autostarted, using the server -o option or manually starting the server may give more details.

Unable to start specified database: '%1' is an invalid transaction log

Error constant	SQLE_CORRUPT_REDO
ODBC 2 State	08001
ODBC 3 State	08001
Parameter 1	The name of the transaction log file.
Severity	11
SQLCODE	-1007
SQLSTATE	08W88
Sybase error code	840

Probable cause

The specified file is not a valid transaction log.

Unable to start specified database: '%1' is an invalid transaction log mirror

Error constant	SQLE_CORRUPT_REDO_MIRROR
ODBC 2 State	08001
ODBC 3 State	08001
Parameter 1	The name of the transaction log mirror file.
Severity	11
SQLCODE	-1008
SQLSTATE	08W72

Sybase error code	840
-------------------	-----

Probable cause

The specified file is not a valid transaction log mirror.

Unable to start specified database: '%1' is not a database

Error constant	SQLE_FILE_NOT_DB
ODBC 2 State	08001
ODBC 3 State	08001
Parameter 1	The name of the database file.
Severity	11
SQLCODE	-1004
SQLSTATE	08W85
Sybase error code	840

Probable cause

The specified file is not a valid database file.

Unable to start specified database: '%1' is not a valid database file

Error constant	SQLE_FILE_BAD_DB
ODBC 2 State	08001
ODBC 3 State	08001
Parameter 1	The name of the database file.
Severity	11
SQLCODE	-1006
SQLSTATE	08W87
Sybase error code	840

Probable cause

The specified file is not a valid database.

Unable to start specified database: '%1' must be upgraded to start with this server (capability %2 missing)

Error constant	SQLE_UPGRADE_DATABASE
ODBC 2 State	08001
ODBC 3 State	08001
Parameter 1	The name of the database file.
Parameter 2	The capability that is missing from the database file.
Severity	11
SQLCODE	-1012
SQLSTATE	08W76
Sybase error code	840

Probable cause

The specified database must be upgraded to start with this server.

Unable to start specified database: '%1' not expecting any operations in transaction log

Error constant	SQLE_EXPECTING_NO_REDO
ODBC 2 State	08001
ODBC 3 State	08001
Parameter 1	The name of the transaction log file.
Severity	11
SQLCODE	-1010
SQLSTATE	08W74

Sybase error code	840
-------------------	-----

Probable cause

The transaction log contains operations, but the database server was not expecting any.

Unable to start specified database: '%1' was created by a different version of the software

Error constant	SQLE_FILE_WRONG_VERSION
ODBC 2 State	08001
ODBC 3 State	08001
Parameter 1	The name of the database file.
Severity	11
SQLCODE	-1005
SQLSTATE	08W86
Sybase error code	840

Probable cause

The specified database file was created by a different version of the software, and it can not be read by this version.

Unable to start specified database: '%1': transaction log file not found

Error constant	SQLE_LOG_NOT_FOUND
ODBC 2 State	08001
ODBC 3 State	08001
Parameter 1	The name of the transaction log file.
Severity	11
SQLCODE	-1017

SQLSTATE	08W81
Sybase error code	840

Probable cause

The transaction log file was not found.

Unable to start specified database: Cannot use log file '%1' since it has been used more recently than the database file

Error constant	SQLE_LOG_NEWER_THAN_DB
ODBC 2 State	08001
ODBC 3 State	08001
Parameter 1	The name of the transaction log mirror file.
Severity	11
SQLCODE	-1016
SQLSTATE	08W80
Sybase error code	840

Probable cause

The transaction log file has been used more recently than the database file.

Unable to start specified database: Cannot use log file '%1' since it is shorter than expected

Error constant	SQLE_LOG_TOO_SHORT
ODBC 2 State	08001
ODBC 3 State	08001
Parameter 1	The name of the transaction log file.
Severity	11
SQLCODE	-1020

SQLSTATE	08W84
Sybase error code	840

Probable cause

The transaction log file is shorter than expected.

Unable to start specified database: Cannot use log file '%1' since the database file has been used more recently

Error constant	SQLLE_LOG_OLDER_THAN_DB
ODBC 2 State	08001
ODBC 3 State	08001
Parameter 1	The name of the transaction log file.
Severity	11
SQLCODE	-1019
SQLSTATE	08W83
Sybase error code	840

Probable cause

The database file has been used more recently than the transaction log file.

Unable to start specified database: Cannot use log file '%1' since the offsets do not match the offsets in the database file

Error constant	SQLLE_LOG_OFFSETS_DONT_MATCH
ODBC 2 State	08001
ODBC 3 State	08001
Parameter 1	The name of the transaction log file.
Severity	11

SQLCODE	-1018
SQLSTATE	08W82
Sybase error code	840

Probable cause

The transaction log file has an offset that does not match the offset expected by the database file.

Unable to start specified database: Log file error

Error constant	SQLE_UNABLE_TO_START_DATABASE_LOG_ERROR
ODBC 2 State	08001
ODBC 3 State	08001
Severity	11
SQLCODE	-935
SQLSTATE	08W68
Sybase error code	13553

Probable cause

The database server was unable to start the database since the log file is missing, for a different database, or some other reason. Check the server window messages area for more details.

Unable to start specified database: Server must be upgraded to start database %1

Error constant	SQLE_UNABLE_TO_START_DATABASE_VER_NEWER
ODBC 2 State	08001
ODBC 3 State	08001
Parameter 1	Name of the database that could not be started, if known.
Severity	11
SQLCODE	-934

SQLSTATE	08W67
Sybase error code	13552

Probable cause

The database server was unable to start the database since the database version is newer than the server version. The server must be upgraded to at least the version of the database to be able to start the database.

Unable to start specified database: The transaction log '%1' or its mirror '%2' is invalid

Error constant	SQLE_CORRUPT_REDO_OR_MIRROR
ODBC 2 State	08001
ODBC 3 State	08001
Parameter 1	The name of the transaction log file.
Parameter 2	The name of the transaction log mirror file.
Severity	11
SQLCODE	-1009
SQLSTATE	08W73
Sybase error code	840

Probable cause

The transaction log differs from the transaction log mirror. Either the transaction log or its mirror is invalid.

Unable to start specified database: Unknown encryption algorithm

Error constant	SQLE_UNKNOWN_ENCRYPTION_ALGORITHM
ODBC 2 State	08001
ODBC 3 State	08001
Severity	11

SQLCODE	-1011
SQLSTATE	08W75
Sybase error code	840

Probable cause

The database is encrypted with an algorithm not supported by this server.

Undeclared tag ID: '%1'

Error constant	SQLE_UNDECLARED_FOR_XML_EXPLICIT_TAG
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The value of the undeclared tag ID.
Severity	16
SQLCODE	-901
SQLSTATE	WX009
Sybase error code	13580

Probable cause

Every value appearing in the Tag column of the table must be declared in the TagNumber field of at least one column name.

Underflow when converting '%1'

Error constant	SQLE_UNDERFLOW
ODBC 2 State	ERROR
ODBC 3 State	42000
Parameter 1	The type being converted.
Severity	16
SQLCODE	-1280

SQLSTATE	WW232
Sybase error code	13806

Probable cause

An underflow occurred when converting the specified type. The source type may be too small (for example zero length binary) or value may be too small to be represented by the destination type.

Unknown backup operation

Error constant	SQLE_UNKNOWN_BACKUP_OPERATION
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	20
SQLCODE	-240
SQLSTATE	WB001
Sybase error code	3206

Probable cause

You specified an invalid backup statement operation in a call to db_backup.

Unknown FOR XML EXPLICIT directive: '%1'

Error constant	SQLE_BAD_FOR_XML_EXPLICIT_DIRECTIVE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The unknown directive.
Severity	16
SQLCODE	-898
SQLSTATE	WX006
Sybase error code	13583

Probable cause

Legal FOR XML EXPLICIT directives are: id, idref, idrefs, hide, element, xml, cdata.

Unknown function '%1'

Error constant	SQLE_UNKNOWN_FUNC
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Function name that is not a database function.
Severity	15
SQLCODE	-148
SQLSTATE	42W05
Sybase error code	176

Probable cause

You misspelled the name of a database function (such as MAXIMUM instead of MAX) in a query definition or in a query column name.

UNLOAD TABLE cannot be used to unload a view

Error constant	SQLE_CANNOT_UNLOAD_A_VIEW
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-643
SQLSTATE	WL004
Sybase error code	13672

Probable cause

UNLOAD TABLE was specified with the name of a view. UNLOAD TABLE may only be used to unload tables.

Unsupported character set '%1' and unsupported language '%2'; language used is '%3' instead

Error constant	SQLE_UNSUPPORTED_CHARSET_AND_LANGUAGE
ODBC 2 State	01000
ODBC 3 State	01000
Parameter 1	Name of the character set that could not be supported.
Parameter 2	Name of the language that could not be supported.
Parameter 3	Name of the language that the server will use to send language strings.
Severity	10
SQLCODE	117
SQLSTATE	01W15
Sybase error code	13616

Probable cause

The character set that the application requested is not supported by the server to which the application is connecting. The language that the application requested is not supported either. Language strings will be sent in the language specified.

Unsupported property '%1' in service USING attribute

Error constant	SQLE_SERVICE_PARM_UNSUPPORTED_PROPERTY
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the unsupported property.
Severity	16
SQLCODE	-1024
SQLSTATE	42WAF
Sybase error code	13486

Probable cause

The service definition contains a USING attribute with an unsupported property.

Unterminated C string

Error constant	SQLE_UNTERMINATED_C_STR
ODBC 2 State	22024
ODBC 3 State	22024
Severity	16
SQLCODE	-634
SQLSTATE	22024
Sybase error code	13682

Probable cause

The last byte of a C string host variable must contain the null character.

Update conflict on snapshot transaction

Error constant	SQLE_SNAPSHOT_UPDATE_CONFLICT
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1064
SQLSTATE	42WBA
Sybase error code	13450

Probable cause

A snapshot transaction attempted to update or delete a row that was changed by another transaction after the snapshot began.

Update operation attempted on a read-only cursor

Error constant	SQLE_READ_ONLY_CURSOR
ODBC 2 State	S1009
ODBC 3 State	HY092
Severity	16
SQLCODE	-633
SQLSTATE	42W30
Sybase error code	7732

Probable cause

You attempted an update operation on a cursor that was explicitly declared as read-only.

Update operation attempted on non-updatable query

Error constant	SQLE_NON_UPDATEABLE_VIEW
ODBC 2 State	42000
ODBC 3 State	42000
Severity	15
SQLCODE	-192
SQLSTATE	42W31
Sybase error code	7301

Probable cause

You attempted an insert, update, or delete operation on a query that is implicitly read-only. Queries that contain DISTINCT, GROUP BY, HAVING, EXCEPT, INTERSECT or UNION, or that contain aggregate functions, or that involve a join, are implicitly read-only. If the query references a view then the view may be non-updatable.

Update operation attempted on non-updatable remote query

Error constant	SQLE_NON_UPDATEABLE_EXT_TAB
----------------	-----------------------------

ODBC 2 State	42000
ODBC 3 State	42000
Severity	15
SQLCODE	-728
SQLSTATE	42W35
Sybase error code	7338

Probable cause

You attempted an update or delete operation on a remote table that is currently not implemented. Examples of such operations include positioned updates and updates that require building of work tables.

Use of feature '%1' is not allowed

Error constant	SQLE_SECURE_FEATURE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the SQL statement or feature.
Severity	14
SQLCODE	-1084
SQLSTATE	57W02
Sybase error code	13430

Probable cause

You have attempted to use a feature that was disabled by the server administrator when the database server was started.

Use of statement '%1', which requires feature '%2', is not allowed

Error constant	SQLE_SECURE_STATEMENT
ODBC 2 State	ERROR

ODBC 3 State	ERROR
Parameter 1	Name of the SQL statement.
Parameter 2	Name of the feature.
Severity	14
SQLCODE	-1142
SQLSTATE	57W04
Sybase error code	13371

Probable cause

You have attempted to use a statement which requires a feature that was disabled by the server administrator when the database server was started.

User '%1' already has EXECUTE permission

Error constant	SQLLE_ALREADY_HAS_EXEC_PERMS
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	Name of the user ID that already has EXECUTE permission.
Severity	16
SQLCODE	-968
SQLSTATE	42WAB
Sybase error code	13522

Probable cause

You attempted to give EXECUTE permission on a stored procedure to a user that already has EXECUTE permission on that procedure.

User '%1' already has GRANT permission

Error constant	SQLLE_ALREADY_HAS_GRANT_PERMS
----------------	-------------------------------

ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	Name of the user ID that already has GRANT permission.
Severity	16
SQLCODE	-120
SQLSTATE	42W01
Sybase error code	13625

Probable cause

You attempted to give GRANT OPTION permission to a user that already has it.

User '%1' already has membership in group '%2'

Error constant	SQLE_ALREADY_HAS_GROUP_MEMBERSHIP
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	Name of the user ID that already has membership.
Parameter 2	Name of the group.
Severity	16
SQLCODE	-312
SQLSTATE	42W34
Sybase error code	13627

Probable cause

You attempted to give a membership in a group to a user that already has such membership.

User '%1' has the row in '%2' locked

Error constant	SQLE_LOCKED
----------------	-------------

ODBC 2 State	40001
ODBC 3 State	40001
Parameter 1	Name of another user.
Parameter 2	Table that generates the error.
Severity	21
SQLCODE	-210
SQLSTATE	42W18
Sybase error code	8405

Probable cause

You attempted to read or write a row that is locked by another user, while the database option 'blocking' is set to Off.

User '%1' is already the publisher for this database

Error constant	SQL_E_ONLY_ONE_PUBLISHER
ODBC 2 State	S0002
ODBC 3 State	42S02
Parameter 1	Name of the publisher.
Severity	16
SQLCODE	-284
SQLSTATE	5RW05
Sybase error code	13646

Probable cause

You attempted to GRANT PUBLISH to a user ID, when a publisher already exists.

User '%1' is not a remote user for this database

Error constant	SQL_E_NOT_REMOTE_USER
----------------	-----------------------

ODBC 2 State	S0002
ODBC 3 State	42S02
Parameter 1	Name of user.
Severity	16
SQLCODE	-285
SQLSTATE	5RW06
Sybase error code	13647

Probable cause

You attempted to execute a CREATE SUBSCRIPTION or PASSTHROUGH for a user that is not a remote user of this database. You must GRANT REMOTE or GRANT CONSOLIDATE for this user before proceeding with this operation.

User '%1' is not a user group

Error constant	SQLE_NOT_A_GROUP
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	Name of user you thought was a group.
Severity	16
SQLCODE	-123
SQLSTATE	42W03
Sybase error code	13626

Probable cause

You attempted to add a member to group, but the user ID specified as a group has not been granted GROUP permission.

User \"%1\" already exists

Error constant	SQLE_USER_ALREADY_EXISTS
----------------	--------------------------

ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the user.
Severity	16
SQLCODE	-1198
SQLSTATE	WW101
Sybase error code	13317

Probable cause

An attempt was made to create a user that already exists in the database.

User cannot be dropped because external logins exist for this user

Error constant	SQLE_USER_HAS_EXTERNLOGINS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	11
SQLCODE	-1220
SQLSTATE	WO028
Sybase error code	13300

Probable cause

The user cannot be dropped while an external login for the user still exists.

User ID '%1' does not exist

Error constant	SQLE_UNKNOWN_USERID
ODBC 2 State	28000
ODBC 3 State	28000

Parameter 1	Name of the user ID that could not be found.
Severity	11
SQLCODE	-140
SQLSTATE	08004
Sybase error code	509

Probable cause

You used a user ID that does not exist.

User message %1 already exists

Error constant	SQLE_MESSAGE_ALREADY_EXISTS
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	Error number of the user message that exists in the database.
Severity	16
SQLCODE	-610
SQLSTATE	52W16
Sybase error code	13624

Probable cause

The message with this error number already exists in the database.

User message %1 not found

Error constant	SQLE_MESSAGE_NOT_FOUND
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	Message number.

Severity	16
SQLCODE	-612
SQLSTATE	52W17
Sybase error code	2748

Probable cause

The message with this error number does not exist in the database.

User owns procedures in use

Error constant	SQLE_USER_OWNS_PROCEDURES_IN_USE
ODBC 2 State	40001
ODBC 3 State	40001
Severity	16
SQLCODE	-750
SQLSTATE	42W55
Sybase error code	3702

Probable cause

You attempted to drop a user that owns a procedure being used by other active users of the database.

User owns tables in use

Error constant	SQLE_USER_OWNS_TABLES_IN_USE
ODBC 2 State	40001
ODBC 3 State	40001
Severity	16
SQLCODE	-751
SQLSTATE	42W56

Sybase error code	3702
-------------------	------

Probable cause

You attempted to REVOKE CONNECT from a user that owns a table being used by other active users of the database.

User-defined exception signaled

Error constant	SQLE_USER_DEFINED_EXCEPTION
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-297
SQLSTATE	99999
Sybase error code	13662

Probable cause

A stored procedure or trigger signaled a user-defined exception. This error state is reserved for use within stored procedures or triggers that contain exception handlers, as a way of signaling an exception that can be guaranteed to not have been caused by the database server. Valid SQLSTATE values range from 99000 to 99999 and are set by the user when executing the signal SQL statement.

User-defined type '%1' not found

Error constant	SQLE_USER_TYPE_NOT_FOUND
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	Name of the user-defined type.
Severity	16
SQLCODE	-613
SQLSTATE	52W18

Sybase error code	2715
-------------------	------

Probable cause

The user-defined type with this name does not exist in the database.

USING attribute cannot coexist with FORMAT or GROUP attributes

Error constant	SQLE_SERVICE_ATTR_COEXIST
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-1026
SQLSTATE	42WB1
Sybase error code	13484

Probable cause

The service definition for the specified service type cannot specify a USING attribute along with a FORMAT or GROUP attribute.

Using temporary table

Error constant	SQLE_TEMPORARY_TABLE
ODBC 2 State	01000
ODBC 3 State	01000
Severity	10
SQLCODE	102
SQLSTATE	01W02
Sybase error code	13075

Probable cause

A temporary table has been created in order to satisfy the query. This warning can only occur on an OPEN statement.

VALIDATE statement must refer to a base table

Error constant	SQLE_CANNOT_VALIDATE_OBJECT
ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	-720
SQLSTATE	42W51
Sybase error code	13729

Probable cause

The VALIDATE statement must refer to a local base table; it cannot refer to a view, an IQ table, or an object on a remote server.

Value %1 out of range for destination

Error constant	SQLE_OVERFLOW_ERROR
ODBC 2 State	22003
ODBC 3 State	22003
Parameter 1	The value that caused the overflow.
Severity	16
SQLCODE	-158
SQLSTATE	22003
Sybase error code	220

Probable cause

You supplied to or fetched from the database a value that is out of range for the destination column or host variable. For example, the value 10 may have been supplied for a DECIMAL(3,2) field.

Value for column '%1' in table '%2' has changed

Error constant	SQLE_COLUMN_VALUE_CHANGED
ODBC 2 State	OK
ODBC 3 State	OK
Parameter 1	Name of the column whose value has changed.
Parameter 2	Name of the table containing the column.
Severity	10
SQLCODE	106
SQLSTATE	01W06
Sybase error code	532

Probable cause

A replicated UPDATE has found a value in an updated column that does not match the value when the original UPDATE was made.

Value truncated

Error constant	SQLE_TRUNCATED
ODBC 2 State	01004
ODBC 3 State	01004
Severity	10
SQLCODE	101
SQLSTATE	01004
Sybase error code	7337

Probable cause

You may have fetched data into a host variable or SQLDA variable not large enough to receive the value.

Value-sensitive cursor used after a TRUNCATE

Error constant	SQLE_HOLD_CURSOR_AFTER_TRUNCATE
ODBC 2 State	24000
ODBC 3 State	24000
Severity	16
SQLCODE	-1241
SQLSTATE	24001
Sybase error code	13273

Probable cause

You attempted to use a value-sensitive cursor opened WITH HOLD after a TRUNCATE or after a COMMIT removed all rows from a temporary table declared as ON COMMIT DELETE ROWS.

Variable '%1' not found

Error constant	SQLE_VARIABLE_NOT_FOUND
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Name of the variable that could not be found.
Severity	15
SQLCODE	-260
SQLSTATE	42W14
Sybase error code	137

Probable cause

You attempted to DROP or SET the value of a SQL variable that was not created or was previously dropped.

View references '%1', which is a temporary object. Views can only refer to permanent objects

Error constant	SQLE_VIEW_OVER_TEMP_OBJECT
ODBC 2 State	42000
ODBC 3 State	42000
Parameter 1	Temporary object name.
Severity	16
SQLCODE	-766
SQLSTATE	42U00
Sybase error code	4412

Probable cause

Views must refer only to permanent objects, not to temporary objects such as local temporary tables.

Virtual index creation with more than %1 columns

Error constant	SQLE_TOO_MANY_VIRTUAL_INDEX_COLUMNS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The maximum number of virtual index columns.
Severity	16
SQLCODE	-887
SQLSTATE	54W50
Sybase error code	13597

Probable cause

You attempted to create a virtual index with more than the maximum number of columns.

Warning detected when optimizing SELECT INTO is treated as an error

Error constant	SQLE_SELECT_INTRO_WARNING_TREATED_AS_ERROR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-995
SQLSTATE	WP016
Sybase error code	13495

Probable cause

The SELECT ... INTO #TEMPTABLE statement cannot proceed if a warning is detected while optimizing the query. To fix the problem, test the query by removing the INTO clause, and resolve the reported warning.

Warning: %1

Error constant	SQLE_WARNING
ODBC 2 State	OK
ODBC 3 State	OK
Parameter 1	Warning message.
Severity	10
SQLCODE	200
SQLSTATE	01000
Sybase error code	13619

Probable cause

A warning has occurred. The message indicates the condition that caused the warning.

Window '%1' not found

Error constant	SQLE_WINDOW_NOT_FOUND
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the window that could not be found.
Severity	16
SQLCODE	-947
SQLSTATE	42WA3
Sybase error code	13541

Probable cause

You have attempted to reference a window name that is not defined in the window list of the SELECT statement.

Window function requires ORDER BY

Error constant	SQLE_ORDERBY_REQUIRED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-965
SQLSTATE	42WA9
Sybase error code	13525

Probable cause

Rank functions and window functions that use the RANGE keyword must specify an ORDER BY clause.

Window function used in predicate

Error constant	SQLE_ILLEGAL_WINDOW_PREDICATE
----------------	-------------------------------

ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	16
SQLCODE	-964
SQLSTATE	42WA8
Sybase error code	13526

Probable cause

A window function was used in the WHERE or HAVING clause of a SELECT statement. Consider making the SELECT into a derived table, putting the window function in the select list of the derived table, and changing the predicate to reference the derived column.

WITH CHECK OPTION violated for insert/update on base table '%1'

Error constant	SQL_E_WITH_CHECK_OPTION_VIOLATION
ODBC 2 State	S1000
ODBC 3 State	44000
Parameter 1	Name of the base table being updated.
Severity	16
SQLCODE	-632
SQLSTATE	44000
Sybase error code	550

Probable cause

You attempted an insert or update operation on the indicated base table through a view (possibly nested). However, one or more values in the modified row(s) triggered a WITH CHECK OPTION violation. This violation occurs when a modified value causes one or more rows to fall outside the range of the view by making the view's WHERE clause evaluate to FALSE or UNKNOWN for that row.

Write access was denied

Error constant	SQLE_ULTRALITE_WRITE_ACCESS_DENIED
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Severity	14
SQLCODE	-1086
SQLSTATE	42Z00
Sybase error code	13428

Probable cause

A write attempt to an UltraLite database in read-only mode was denied. Note that UltraLite databases cannot be modified while sending an upload to MobiLink.

WRITETEXT not allowed: immediate materialized view %1 depends on %2

Error constant	SQLE_WRITETEXT_TABLE_WITH_IMV
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the dependent immediate materialized view.
Parameter 2	Name of the base table.
Severity	16
SQLCODE	-1203
SQLSTATE	55W32
Sybase error code	13312

Probable cause

WRITETEXT is not allowed on base tables that have dependent initialized immediate materialized views. No operation that does not fire triggers is allowed on base tables with dependent initialized immediate materialized views.

Wrong number of parameters to function '%1'

Error constant	SQLE_WRONG_PARAMETER_COUNT
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	Name of the function.
Severity	15
SQLCODE	-154
SQLSTATE	37505
Sybase error code	174

Probable cause

You supplied an incorrect number of parameters to a database function.

Wrong number of values for INSERT

Error constant	SQLE_WRONG_NUM_OF_INSERT_COLS
ODBC 2 State	21S01
ODBC 3 State	21S01
Severity	16
SQLCODE	-207
SQLSTATE	53002
Sybase error code	213

Probable cause

The number of values you are trying to insert does not match the number of columns specified in the INSERT statement, or the number of columns in the table if no columns are specified.

Wrong number of variables in FETCH

Error constant	SQLE_WRONG_NUM_OF_FETCH_VARIABLES
----------------	-----------------------------------

ODBC 2 State	S1002
ODBC 3 State	07009
Severity	16
SQLCODE	-264
SQLSTATE	42W26
Sybase error code	553

Probable cause

You specified a number of variables in a FETCH statement that does not match the number of select list items.

XML parser error: %1

Error constant	SQLE_XML_PARSER_ERROR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The error message returned by the XML parser.
Severity	16
SQLCODE	-888
SQLSTATE	WX002
Sybase error code	13595

Probable cause

An XML instance will only parse correctly if it is well-formed as defined by the XML 1.0 specification.

XMLGEN evaluation failure

Error constant	SQLE_XMLGEN_EVALUATION_FAILURE
ODBC 2 State	ERROR
ODBC 3 State	ERROR

Severity	16
SQLCODE	–906
SQLSTATE	WX013
Sybase error code	13577

Probable cause

One of the variables referenced in the XQuery constructor was not found in the list of arguments.

XPath parser error: %1

Error constant	SQLE_XQUERY_PARSER_ERROR
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The error message returned by the XPath parser.
Severity	16
SQLCODE	–892
SQLSTATE	WX003
Sybase error code	13591

Probable cause

The XPath expression is illegal or uses features that are not currently supported.

You cannot synchronize or upgrade with uncommitted transactions

Error constant	SQLE_UNCOMMITTED_TRANSACTIONS
ODBC 2 State	37000
ODBC 3 State	42000
Severity	16
SQLCODE	–755

SQLSTATE	0AW08
Sybase error code	13765

Probable cause

You attempted to synchronize or upgrade the schema of an UltraLite database and there are changes in the UltraLite database that have not been committed.

SQL Anywhere error messages sorted by message text (special characters)

%1

Error constant	SQLE_OMNI_DEBUG
ODBC 2 State	OK
ODBC 3 State	OK
Parameter 1	The debug message for the console.
Severity	16
SQLCODE	-682
SQLSTATE	WO010
Sybase error code	13734

Probable cause

This message is used for displaying component integration services debug messages on the console.

%1 does not return a result set

Error constant	SQLE_NO_RESULT_SET
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the procedure.
Severity	16
SQLCODE	-872
SQLSTATE	WP014
Sybase error code	13876

Probable cause

A procedure called in the FROM clause of a SELECT statement must return a result set.

%1 returned a result set with a different schema than expected

Error constant	SQLE_BAD_RESULT_SET
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the procedure that returned the incorrect result set.
Severity	12
SQLCODE	-866
SQLSTATE	WP012
Sybase error code	13870

Probable cause

When calling a procedure in the FROM clause of a SELECT statement, the expected schema of the result is taken from the WITH clause. If no WITH clause is given, the expected schema is taken from the system catalog. The result set returned from the call must match the expected schema or it must be possible to convert every column so that it matches.

%1 returned multiple result sets

Error constant	SQLE_TOO_MANY_RESULT_SETS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Name of the procedure.
Severity	16
SQLCODE	-873
SQLSTATE	WP013
Sybase error code	13877

Probable cause

A procedure called in the FROM clause of a SELECT statement cannot return multiple result sets.

'%1' cannot be used as the encoding specification for '%2' data

Error constant	SQLE_INVALID_OPENSTRING_ENCODING
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The encoding that has been specified
Parameter 2	The data type for which the encoding has been specified
Severity	16
SQLCODE	-1144
SQLSTATE	WC017
Sybase error code	13368

Probable cause

The specified encoding cannot be used for interpreting the given data. For CHAR data, the encoding must be the database's CHAR character encoding and for NCHAR data, it must be the database's NCHAR character encoding.

'%1' cannot be used as the NCHAR collation: only UCA and UTF8BIN may be used

Error constant	SQLE_INVALID_NCHAR_COLLATION
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The collation that can not be used as the NCHAR collation.
Severity	16
SQLCODE	-1073
SQLSTATE	WC010
Sybase error code	13442

Probable cause

The specified collation cannot be used as the NCHAR collation. NCHAR always uses UTF-8, so the collation must be either UCA or UTF8BIN.

'%1' is an invalid value for '%2'

Error constant	SQLE_INVALID_OPTION_VALUE
ODBC 2 State	37000
ODBC 3 State	42000
Parameter 1	The invalid value.
Parameter 2	Name of the option.
Severity	16
SQLCODE	–1053
SQLSTATE	42W85
Sybase error code	5849

Probable cause

You supplied an invalid value for an option. Some options only allow numeric values and some options only allow true or false. Also, many options do not permit the empty string as a value.

'%1' is an unknown character set encoding label

Error constant	SQLE_UNKNOWN_CHARSET
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The character set encoding label that is not recognized.
Severity	16
SQLCODE	–868
SQLSTATE	WC001
Sybase error code	13872

Probable cause

The specified character set label is not recognized, so conversion from/to that character set is not possible.

'%1' is an unknown option

Error constant	SQLE_UNKNOWN_OPTION
ODBC 2 State	01000
ODBC 3 State	01000
Parameter 1	The option that is unknown to the server.
Severity	10
SQLCODE	120
SQLSTATE	01W17
Sybase error code	13751

Probable cause

You attempted to set the value of an option that is not known to the server.

'%1' is an unrecognized service type

Error constant	SQLE_UNKNOWN_SERVICE_TYPE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The service type that is unrecognized.
Severity	16
SQLCODE	-916
SQLSTATE	42W94
Sybase error code	13568

Probable cause

An unrecognized service type was specified.

'%1' is not a known file format for loading or unloading tables

Error constant	SQLE_UNSUPPORTED_LOAD_FORMAT
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The specified format.
Severity	19
SQLCODE	-601
SQLSTATE	WL001
Sybase error code	13669

Probable cause

An unsupported file format was specified for LOAD TABLE or UNLOAD TABLE.

'%1' is not a public Java class, and cannot be referenced from SQL

Error constant	SQLE_NON_PUBLIC_JAVA_CLASS
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Java class name.
Severity	16
SQLCODE	-762
SQLSTATE	WJ023
Sybase error code	13772

Probable cause

Only public Java classes installed into the database are accessible from SQL.

'%1' is not a public Java reference, and cannot be referenced from SQL

Error constant	SQLE_UNKNOWN_JAVA_REF
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	A dotted expression.
Severity	16
SQLCODE	-763
SQLSTATE	WJ024
Sybase error code	13773

Probable cause

The dotted expression is neither a public Java class nor a Java variable.

'%1' is not a valid character set encoding for use with collation '%2'

Error constant	SQLE_INVALID_ENCODING_FOR_COLLATION
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The character set encoding that is invalid.
Parameter 2	The collation for which the character set encoding is invalid.
Severity	16
SQLCODE	-1072
SQLSTATE	WC009
Sybase error code	13441

Probable cause

The specified character set cannot be used with the specified collation.

'%1' is not a valid class file

Error constant	SQLE_BAD_CLASS_FILE
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	The name of the invalid file.
Severity	16
SQLCODE	-92
SQLSTATE	WP002
Sybase error code	13736

Probable cause

A file passed to the INSTALL JAVA statement was not a valid Java class file.

'%1' statement is not allowed on a mirrored database

Error constant	SQLE_STMT_NOT_ALLOWED_WITH_MIRRORING
ODBC 2 State	ERROR
ODBC 3 State	ERROR
Parameter 1	Statement that generates the error.
Severity	16
SQLCODE	-1288
SQLSTATE	WW120
Sybase error code	13666

Probable cause

You attempted to execute a statement that is not allowed when using a mirrored database.

(no message)

Error constant	SQLE_AMBIGUOUS_CONSTRAINT
ODBC 2 State	S0002
ODBC 3 State	42S24
Severity	16
SQLCODE	-930
SQLSTATE	42U05
Sybase error code	13555

Probable cause

You have asked for an unnamed column constraint to be altered, but there is at least one named constraint.

(no message)

Error constant	SQLE_NOERROR
ODBC 2 State	00000
ODBC 3 State	00000
Severity	10
SQLCODE	0
SQLSTATE	00000
Sybase error code	13600

Probable cause

This code indicates that there was no error or warning.

MobiLink server error messages

Contents

MobiLink server error messages sorted by error code	556
MobiLink server error messages sorted by message text	570

MobiLink server error messages sorted by error code

Error code	Message text
0	“No error or unknown error” on page 598
–10001	“Protocol error: %1” on page 602
–10002	“Consolidated database server or ODBC error: %1” on page 580
–10003	“Memory allocation failed, attempted to allocate %1 bytes” on page 597
–10004	“Protocol version mismatch -- expecting %1 but received %2” on page 602
–10013	“Version '%1' not found in the ml_script_version table. Cannot synchronize” on page 651
–10016	“Cannot convert '%1' to Unicode” on page 578
–10017	“Protocol error: there is no publication that contains table '%1’” on page 602
–10018	“Error fetching connection script %1” on page 584
–10019	“Error fetching table script %1.%2” on page 585
–10020	“Unable to flush scripts” on page 635
–10021	“Unable to retry the current transaction after deadlock in the consolidated database. The retry limit has been reached” on page 645
–10022	“The synchronization sequence number stored in ml_subscription.progress is negative. Set this value to zero (0) to re-enable synchronizations for remote ID '%1’” on page 620
–10023	“The remote database may have been restored from backup, or perhaps remote ID '%1' is being used by different remote databases. Set ml_subscription.progress to zero to re-enable synchronizations for this remote database” on page 615
–10024	“Unrecognized domain id %1” on page 649
–10028	“Unable to connect to the consolidated database. Aborting the synchronization” on page 630
–10029	“Attempt to set non-null column to null” on page 577
–10030	“A network read failed. Unable to read data from the remote client” on page 573
–10031	“An error occurred when trying to store progress information in the consolidated database” on page 573

Error code	Message text
-10032	“Upload failed with client error %1” on page 650
-10033	“The row is too big. The size (%1 bytes) exceeds the maximum allowable size (%2 bytes)” on page 616
-10034	“No download confirmation from remote database” on page 598
-10035	“Download failed with client error %1” on page 584
-10038	“A downloaded value for table '%1' (column #%2) was either too big or invalid for the remote schema type” on page 572
-10039	“Scripts cannot be defined as NULL” on page 606
-10041	“INTERNAL ERROR: occurred while retrieving a BLOB -- read” on page 591
-10047	“Expecting %1 parameters in script, but only found %2: %3” on page 589
-10048	“Expecting at least %1 parameters in script, but only found %2: %3” on page 589
-10050	“Expecting %1 columns in cursor, but found %2” on page 588
-10051	“Internal error: wrong function '%1' called. Please contact technical support” on page 591
-10052	“The %1 script returned %2” on page 608
-10054	“Unable to insert user name '%1' into the ml_user table” on page 637
-10055	“Unable to authenticate user %1” on page 628
-10056	“User name '%1' not found in the ml_user table” on page 650
-10057	“Invalid password for user %1” on page 594
-10058	“Unable to open %1” on page 641
-10060	“Memory allocation failed” on page 597
-10061	“An error occurred while uploading an insert row into table '%1'. The inserted column values are as follows:” on page 574
-10062	“An error occurred while uploading a deleted row into table '%1'. The deleted column values are as follows:” on page 573
-10063	“An error occurred while uploading an updated row into table '%1'. The updated column values are as follows:” on page 574

Error code	Message text
-10064	“Unable to ROLLBACK transaction: %1” on page 645
-10065	“Unable to COMMIT transaction: %1 -- Attempting to ROLLBACK” on page 629
-10066	“Unable to initialize ODBC” on page 636
-10067	“Unable to allocate a connection” on page 627
-10071	“Unable to fetch from table '%1' using %2” on page 633
-10072	“Unable to insert into table '%1' using %2” on page 636
-10073	“Unable to delete from table '%1' using %2” on page 632
-10074	“Unable to update table '%1' using %2” on page 648
-10075	“Required ODBC function %1 is not supported by the driver” on page 603
-10076	“The MobiLink server was unable to calculate the timestamp precision on the consolidated database using the ml_scripts_modified table. Timestamp precision related warnings will not be generated” on page 612
-10077	“The MobiLink server was unable to modify the error message using the modify_error_message script” on page 612
-10081	“The MobiLink server DLL or shared object version does not match the data layer DLL or shared object version” on page 611
-10083	“Unable to delete user name '%1' from the ml_user_table” on page 632
-10084	“LANG: %1 - Failed to attach thread” on page 596
-10085	“LANG: %1 - Failed to allocate database connection” on page 596
-10086	“Cannot load DLL or shared object: '%1' for Script Language: '%2’” on page 578
-10087	“Version mismatch with DLL or shared object: '%1' Expected version: %2 got version: %3” on page 651
-10088	“Unable to load entry points from DLL: '%1’” on page 639
-10089	“Client is unable to process truncate table request for table '%1’” on page 579
-10090	“The client cannot find the consolidated progress offset from the client transaction log(s)” on page 610
-10091	“This connection will be abandoned due to previous errors” on page 622

Error code	Message text
-10092	“There is no upload data script defined for table '%1'. If you want to be able to synchronize anyway, with the risk of potentially losing upload data, use the -fr command line option” on page 622
-10093	“There is no download data script defined for table '%1'. If you want to be able to synchronize anyway, with the risk of potentially losing download data, use the -fr command line option” on page 622
-10094	“Expecting %1 authentication parameter(s) from client, but received %2 for script %3” on page 588
-10099	“Unable to load UNILIB collation %1: %2” on page 640
-10100	“The MobiLink system table '%1' is missing or a table column is missing” on page 613
-10105	“Bad stream specification: %1” on page 577
-10106	“Bad stream type: %1” on page 577
-10107	“Unable to load DLL or shared object: %1” on page 639
-10108	“Unable to load DLL or shared object %1 for stream %2: %3” on page 638
-10109	“One or more invalid parameters prevented startup” on page 600
-10110	“Unable to initialize communications stream %1: %2” on page 635
-10112	“Unable to create the background thread” on page 632
-10117	“Stream Error: %1” on page 607
-10118	“Caught JAVA exception with type: %1. Exception message: %2” on page 579
-10119	“Unable to dump exception information. Received exception while processing exception” on page 633
-10120	“%1 is an unknown subclass of ScriptExecutionException” on page 570
-10121	“Unable to load the Java VM due to a version error” on page 639
-10122	“Unable to load the Java VM due to a memory error” on page 639
-10123	“Unable to load the Java VM due to an unknown error” on page 640
-10124	“The following non-daemon threads were destroyed: %1” on page 610
-10125	“Unable to parse class and method name from script: %1” on page 642

Error code	Message text
-10126	“Error while attaching thread to Java VM” on page 585
-10127	“Failed to load necessary Java class: %1” on page 590
-10128	“Failed to load necessary method: '%1' for Java class: %2” on page 590
-10130	“Not enough arguments to execute script: '%1.%2'. %3 arguments are needed but only %4 are provided” on page 599
-10131	“Expected <void> or an object, but a primitive of type '%1' was returned instead” on page 587
-10132	“Returned class '%1' not a subclass of ianywhere.ml.script.RowReader or java.lang.String” on page 603
-10133	“%1” on page 570
-10134	“Expected an instance of java.lang.String or subclass, but found class '%1' instead” on page 587
-10135	“Expected an instance of ianywhere.ml.script.RowReader or subclass, but found class '%1' instead” on page 587
-10136	“Invalid line found in the JVM config file: %1 All lines must begin with either '#' or '-'” on page 593
-10137	“Invalid line found in the JVM config file: %1. Line is too long” on page 593
-10138	“There are no entries in the JVM config file: %1” on page 620
-10139	“The options '%1' and '%2' must not be used together” on page 614
-10140	“The option '%1' needs a path” on page 613
-10141	“The classpath '%1' is too long” on page 609
-10142	“Unable to find the JAR file: '%1' in install directory or classpath” on page 634
-10143	“Unable to find shared components directory. JRE location is not specified in options. JRE location is unknown” on page 634
-10144	“Shared install directory is incorrect: %1” on page 606
-10145	“Unable to access the JRE at: %1” on page 626
-10146	“Too many options sent to Java VM” on page 625

Error code	Message text
-10147	“There are too many entries in the JVM config file: %1” on page 621
-10148	“Java exception” on page 596
-10149	“Exception thrown in initializer of class: '%1'. Error description: '%2'. Stack trace: '%3'” on page 586
-10150	“Linkage error while loading class: '%1' Error description: '%2'” on page 596
-10151	“No public methods found in script class: '%1'” on page 598
-10152	“Unable to resolve script. Two methods with name: '%1' found in class: '%2'” on page 644
-10153	“No suitable constructor found in class: '%1'” on page 599
-10154	“Exception thrown in constructor of class: '%1'. Error description: '%2'. Stack trace: '%3'” on page 586
-10155	“System exception thrown in constructor of class: '%1'. Error description: '%2'” on page 607
-10156	“Internal error: '%1'” on page 592
-10157	“Could not call method: '%1' with arguments of type '%2'” on page 581
-10158	“Exception thrown in method: '%1'. Error description: '%2'. Stack trace: '%3'” on page 586
-10159	“Unable to create new database connection” on page 631
-10160	“Unable to attach JDBC connection” on page 628
-10161	“No valid constructor was found for class '%1'” on page 599
-10162	“Option '%1' was previously defined on the MobiLink command line with value '%2'” on page 601
-10163	“Option '%1' is invalid or was not specified correctly on MobiLink command line” on page 601
-10164	“Unable to load .NET Framework CLR Version %1” on page 638
-10165	“Unable to load .NET CLR Host DLL” on page 637
-10166	“Unable to find file '%1'” on page 634

Error code	Message text
-10167	“.NET CLR Host encountered unexpected error” on page 570
-10168	“Unable to attach thread to .NET runtime” on page 628
-10169	“Unable to detach worker from VM” on page 633
-10170	“Unable to allocate memory needed for script execution” on page 627
-10171	“Assembly '%1' was compiled against version %2 of '%3'. Please recompile against version %4” on page 575
-10172	“Assembly '%1' does not contain '%2'” on page 574
-10173	“Script '%1' returns a '%2' object, but only return types of 'System.Void' and 'System.String' are supported” on page 605
-10174	“The .NET scripting VM requires version %1 of the MobiLink ODBC Bridge DLL, but was supplied version %2 instead” on page 608
-10175	“The .NET scripting VM requires version %1 of the MobiLink Script DLL, but was supplied version %2 instead” on page 608
-10176	“.NET Domain Configuration File is corrupt” on page 571
-10177	“The name '%1' is not a valid name for a .NET start class” on page 613
-10178	“Domain '%1' was not specified in Domain configuration file” on page 584
-10179	“No Assembly in domain '%1' contains type '%2'” on page 598
-10180	“Unable to shutdown .NET scripting VM” on page 646
-10181	“Unable to shutdown .NET scripting VM. %1 workers still attached” on page 647
-10182	“Invalid format used for script '%1'” on page 592
-10183	“Only one domain can be used per script version. Domain '%1' was in use when script '%2' attempted to use domain '%3'” on page 600
-10184	“Script '%1' requires %2 parameters, but %3 parameters were supplied” on page 605
-10185	“Script '%1' returned an object of type '%2', which is not a subtype of 'System.Void' or 'System.String'” on page 605
-10186	“Script '%1' reported a synchronization error” on page 604
-10187	“Failed to load .NET start class '%1'” on page 589

Error code	Message text
-10188	“Script '%1' reported a server error” on page 604
-10189	“Script '%1' encountered an error” on page 603
-10190	“Script '%1' reported a fatal error” on page 604
-10191	“Unable to locate .NET Domain Configuration File '%1'” on page 640
-10192	“Could not create domain '%1'” on page 582
-10193	“Unable to load Assembly '%1' into domain '%2'” on page 638
-10194	“Attempt to prepare SQL statement '%1' after MLDBCommand.Close() was called” on page 576
-10195	“Attempt to prepare null SQL statement. Set value of MLDBCommand.CommandText before calling MLDBCommand.Prepare()” on page 576
-10196	“Attempt to execute null SQL statement. Set value of MLDBCommand.CommandText before calling a MLDBCommand.Execute method” on page 575
-10197	“Attempt to execute SQL statement '%1' after MLDBCommand.Close() was called” on page 576
-10198	“The prepared SQL statement '%1' requires %2 parameters, but parameter %3 was not supplied” on page 615
-10199	“Attempt to execute a SQL statement with bound parameters before MLDBCommand.Prepare() was called” on page 575
-10200	“The prepared SQL statement '%1' requires %2 parameters, but %3 parameters were supplied” on page 614
-10201	“Binding of parameter %1 requires value to be of type '%2', but a '%3' was supplied” on page 578
-10202	“Transactions on this connection cannot be committed or rolled back” on page 625
-10203	“Attempt to use a connection with an invalid handle” on page 577
-10204	“Script '%1' is a member of '%2', but only %3 classes are permitted per script version” on page 603
-10205	“Failure executing script '%1'” on page 590
-10206	“'%1'” on page 570

Error code	Message text
-10207	“Unrecognized event name: %1” on page 650
-10209	“Unable to load the Java VM shared library. Make sure that the shared library path is set correctly and that LD_PRELOAD is set correctly and supported by your version of the dynamic loader” on page 640
-10211	“A downloaded value for table '%1' (column #%2) contains character data that cannot be converted” on page 571
-10212	“Unable to open temporary file '%1'” on page 642
-10213	“Unable to convert the string %1 to a numeric value” on page 630
-10214	“Invalid return value (%2) from the %1 script. Using the default action code (%3)” on page 594
-10215	“Invalid parameter '%1'” on page 594
-10216	“A downloaded value for table '%1' (column #%2) was an invalid unique identifier string” on page 572
-10217	“Invalid stream parameter %1 for stream %2: %3” on page 595
-10218	“Invalid value %1 stream parameter %2 for stream %3: %4” on page 595
-10219	“Invalid context for stream parameter %1 for stream %2: %3” on page 592
-10220	“Only one of upload_fetch and upload_fetch_columns scripts may be defined for table '%1'” on page 600
-10221	“Unable to allocate memory for the DownloadData instance” on page 627
-10222	“Unable to allocate memory for the UploadData instance” on page 627
-10223	“The handle_UploadData event script must be void or return null” on page 610
-10224	“Column-level conflict detection is not available for table '%1', because it contains BLOBs” on page 580
-10225	“Failure occurred while executing user supplied code in the server” on page 590
-10226	“Invalid named parameter (too short or long) for script '%1'” on page 593
-10227	“Unknown system parameter '%1' for script '%2'” on page 649
-10228	“Invalid system parameter '%1' for script '%2'” on page 595

Error code	Message text
-10229	“System parameter %1 has been set to NULL” on page 607
-10230	“Parameter %1 has been set to NULL” on page 601
-10231	“The script '%1' can not process row data” on page 616
-10232	“Column names must be set in the ml_column table in order to use named row parameters” on page 580
-10233	“Table '%1' does not have a column named '%2'” on page 607
-10234	“The script '%1' can not process pre-image row data” on page 616
-10235	“The script '%1' contains an invalid character in a named parameter” on page 617
-10236	“The script '%1' contains invalid syntax for using named parameters” on page 618
-10237	“The script '%1' references the in out parameter '%2' more than one time” on page 619
-10238	“The remote database identified by remote ID '%1' is already synchronizing. Concurrent synchronizations using the same remote ID are not allowed” on page 615
-10239	“The script '%1' contains an invalid parameter reference: '%2'” on page 617
-10240	“The script '%1' contains an invalid user parameter: '%2'” on page 617
-10241	“The script '%1' references table '%2' column %3, but there are only %4 columns” on page 618
-10242	“The script '%1' references authentication parameter %2 but there are only %3” on page 618
-10243	“The script '%1' references unknown authentication parameter '%2'” on page 619
-10244	“The MobiLink server has encountered an error and the synchronization has been aborted” on page 612
-10245	“The upload table '%1' (column #%2) has the data type '%3', but your ODBC driver doesn't support '%4'” on page 620
-10246	“Unable to retry the current transaction after conflict-update with snapshot isolation in the consolidated database. The retry limit has been reached” on page 645
-10247	“Unable to set transaction isolation level to snapshot” on page 646
-10248	“Cursor-based upload is no longer supported. The scripts for table '%1' must be changed to use statement-based upload” on page 583

Error code	Message text
-10249	“Could not find file transfer root directory: '%1'” on page 582
-10250	“Could not transfer requested file. The transfer root was not set” on page 583
-10251	“Could not find requested file '%1' for user '%2'” on page 582
-10252	“Could not open file for transfer: '%1'” on page 583
-10253	“Could not read file for transfer: '%1'” on page 583
-10254	“Could not add script version: '%1'” on page 581
-10255	“Unable to start the restartable synchronization” on page 647
-10256	“This synchronization was canceled due to a new synchronization <%1> with the same remote id” on page 624
-10257	“This synchronization was paused due to an existing synchronization <%1> with the same remote id” on page 625
-10258	“Unable to create an I/O completion port (system error %1)” on page 631
-10259	“Network address '%1' is not local” on page 597
-10260	“Unable to create listener socket (system error %1)” on page 631
-10261	“Unable to bind listener socket to port (system error %1)” on page 629
-10262	“Unable to listen on port (system error %1)” on page 637
-10263	“Could not associate socket with completion port (system error %1)” on page 581
-10264	“Unable to create connection socket (system error %1)” on page 631
-10265	“Unable to start accepting connections (system error %1)” on page 647
-10266	“Unable to perform a hard close on a socket '%1'” on page 642
-10267	“Unable to post socket deletion request to completion queue (system error %1)” on page 643
-10268	“Unable to perform a hard close on a listener socket” on page 642
-10269	“Unable to post listener deletion request to completion queue (system error %1)” on page 643
-10270	“Unable to wait on completion port (system error %1)” on page 649

Error code	Message text
-10271	“Unable to close socket (system error %1)” on page 629
-10272	“Unable to create unix pipe for socket selector notification (system error %1)” on page 632
-10273	“Unable to reuse address (system error %1)” on page 645
-10274	“Unable to poll sockets (system error %1)” on page 643
-10275	“Unable to notify (system error %1)” on page 641
-10276	“Unable to accept an incoming connection (system error %1)” on page 626
-10277	“Error in reading from notification pipe (system error %1)” on page 585
-10278	“Error on notification pipe” on page 585
-10279	“Connection was dropped due to lack of network activity” on page 580
-10280	“The number of columns in client table '%1' does not agree with the number defined in ml_column” on page 613
-10281	“In table '%1', the column named '%2' in the ml_column table has an index greater than the number of remote columns” on page 591
-10282	“Unable to create a shared memory file” on page 630
-10283	“Unable to resolve host name '%1' (error: '%2')” on page 644
-10284	“This Synchronization is using a blocking download ack but has nonblocking download ack events defined” on page 624
-10285	“When using QAnywhere the only supported mode is nonblocking download ack” on page 651
-10286	“Unable to get the DTC transaction manager -- system error: '%1'” on page 635
-10287	“Unable to initialize a distributed transaction -- system error: '%1'” on page 635
-10288	“Unable to enlist the database in the Distributed Transaction Coordinator” on page 633
-10289	“Unable to commit the distributed transaction (event: %1) -- system error: '%2'” on page 629
-10290	“Unable to abort the distributed transaction (event: %1) -- system error: '%2'” on page 626

Error code	Message text
-10291	“A corrupt or invalid subscription list was received from the client” on page 571
-10292	“Unable to accept new connections on network listener port” on page 626
-10293	“The MobiLink server (farm version '%1') cannot run, because another MobiLink server with a different version is currently running in the MobiLink server farm” on page 611
-10294	“Unable to register the MobiLink server with name '%1'” on page 644
-10295	“The MobiLink server and client implementation IDs mismatch” on page 611
-10296	“Unable to support MLSD” on page 648
-10297	“Unable to send SQL Passthrough script due to an unknown script flag: '%1'” on page 646
-10298	“Unable to update SQL Passthrough script ID during SQL Passthrough repair” on page 648
-10299	“There is an invalid SQL Passthrough repair action '%1' for this user. SQL Passthrough for this user has been halted” on page 621
-10300	“SQL Passthrough protocol error: '%1'. Please contact technical support” on page 606
-10301	“Unable to initialize server shared state” on page 636
-10302	“There has been an internal error in the server shared state. '%1'” on page 621
-10303	“Unable to maintain shared server state liveness” on page 641
-10304	“Unable to start with shared server state because no server name has been set. Use the -zs option to set a server name” on page 647
-10305	“A local server connect string has been specified but shared server state is not enabled. Enable shared server state using the 'ml_server_farm' MobiLink property” on page 572
-10306	“The character set (%1) used by the remote client cannot be mapped by the MobiLink server” on page 609
-10307	“The character set (%1) used by the remote client cannot be mapped by the MobiLink server” on page 609
-10308	“Upload data for column %1 of table '%2' is invalid” on page 650
-10309	“This server is not licensed to connect to a consolidated database of the following type: %1” on page 623

Error code	Message text
-10310	“Unable to authenticate the user” on page 628
-10311	“This server does not have shared server state enabled but other servers connected to this consolidated database have shared server state enabled” on page 623
-10312	“This server is not licensed to use the direct row API” on page 624
-10313	“This server is not licensed to use QAnywhere” on page 624
-10314	“This server is not licensed to use dbmlsync” on page 623
-10315	“Cannot skip generating the next last download timestamp without having the modify_next_last_download_timestamp script” on page 579

MobiLink server error messages sorted by message text

%1

Error code	-10133
Error constant	EL_JAVA_GENERIC_ERROR
Parameter 1	Message string.

Probable cause

A generic error for Java synchronization logic. The details are in the message.

%1 is an unknown subclass of ScriptExecutionException

Error code	-10120
Error constant	EL_JAVA_UNKNOWN_SCRIPTEXECUTIONEXCEPTION
Parameter 1	Class name.

Probable cause

The given class name is an unknown subclass of ScriptExecutionException. Expected subclass names include 'SynchronizationException' and 'ServerException'.

'%1'

Error code	-10206
Error constant	EL_DNET_WRITE_STREAM_ERROR
Parameter 1	An error message.

Probable cause

Generic error message generated by the .Net CLR or by a method invoked during synchronization.

.NET CLR Host encountered unexpected error

Error code	-10167
------------	--------

Error constant	EL_DNET_SERVER_ERROR_FAIL
----------------	---------------------------

Probable cause

MobiLink received an error while performing a routine .NET call. Please examine your .NET installation.

.NET Domain Configuration File is corrupt

Error code	-10176
Error constant	EL_DNET_DOMAIN_CONFIG_FILE_CORRUPT

Probable cause

Examine the contents of the .NET configuration file for errors.

A corrupt or invalid subscription list was received from the client

Error code	-10291
Error constant	CORRUPT_MLSUBS_DATA

Probable cause

MobiLink server has received corrupt data from the client. Please contact technical support.

A downloaded value for table '%1' (column #%2) contains character data that cannot be converted

Error code	-10211
Error constant	DOWNLOAD_DATA_TRANS_ERROR
Parameter 1	Table name.
Parameter 2	Column index.

Probable cause

Character data originating from the consolidated database needs to be converted to the client character set before being sent to the client. However the MobiLink server was not able to convert the data.

A downloaded value for table '%1' (column #%2) was an invalid unique identifier string

Error code	-10216
Error constant	INVALID_UUID_STRING
Parameter 1	Table name.
Parameter 2	Column index.

Probable cause

The MobiLink server cannot convert the string to a unique identifier. Please use a CHAR or VARCHAR data type in the non-SQL Anywhere consolidated database to map UNIQUEIDENTIFIER in the remote database and make sure the string in the consolidated database is a valid unique identifier.

A downloaded value for table '%1' (column #%2) was either too big or invalid for the remote schema type

Error code	-10038
Error constant	STRING_TOO_BIG
Parameter 1	Table name.
Parameter 2	Column index.

Probable cause

The column width for the given table may not be defined consistently in the consolidated and remote databases. Please check the table definition.

A local server connect string has been specified but shared server state is not enabled. Enable shared server state using the 'ml_server_farm' MobiLink property

Error code	-10305
Error constant	SHARED_STATE_CONN_INFO_WITHOUT_DB_PROP

Probable cause

A local server connect string should only be specified when using shared server state. Use the 'ml_server_farm' MobiLink property to enable shared server state.

A network read failed. Unable to read data from the remote client

Error code	-10030
Error constant	STREAM_READ_ERROR

Probable cause

The MobiLink server was unable to complete a network read. Please check the network.

An error occurred when trying to store progress information in the consolidated database

Error code	-10031
Error constant	TXN_LOG_COOKIE_UPDATE_ERROR

Probable cause

The MobiLink server is unable to save the synchronization status into the consolidated database. Please make sure that the database server is running and the network is okay.

An error occurred while uploading a deleted row into table '%1'. The deleted column values are as follows:

Error code	-10062
Error constant	DELETED_ROW_ERROR
Parameter 1	The script name.

Probable cause

A failure occurred when the MobiLink server was uploading a deleted row into the given table in the consolidated database.

An error occurred while uploading an insert row into table '%1'. The inserted column values are as follows:

Error code	-10061
Error constant	INSERTED_ROW_ERROR
Parameter 1	The script name.

Probable cause

A failure occurred when the MobiLink server was uploading an inserted row into the given table in the consolidated database.

An error occurred while uploading an updated row into table '%1'. The updated column values are as follows:

Error code	-10063
Error constant	UPDATED_ROW_ERROR
Parameter 1	The script name.

Probable cause

A failure occurred when the MobiLink server was uploading an updated row into the given table in the consolidated database.

Assembly '%1' does not contain '%2'

Error code	-10172
Error constant	EL_DNET_SCRIPT_NOT_IN_ASM
Parameter 1	The assembly name.
Parameter 2	The missing method name.

Probable cause

If the method is implemented but the name is wrong, change it. If the method is missing, you must add it to the assembly.

Assembly '%1' was compiled against version %2 of '%3'. Please recompile against version %4

Error code	-10171
Error constant	EL_DNET_SCRIPT_VER_MISMATCH
Parameter 1	The assembly name.
Parameter 2	The assembly version.
Parameter 3	The DLL name.
Parameter 4	The desired assembly version.

Probable cause

Please fix the version mismatch displayed and run again.

Attempt to execute a SQL statement with bound parameters before MLDBCommand.Prepare() was called

Error code	-10199
Error constant	EL_DNET_NO_STMT_PREPARED_ON_BIND

Probable cause

An attempt was made to bind a parameter to a statement that was not prepared. Please prepare the statement before binding parameters.

Attempt to execute null SQL statement. Set value of MLDBCommand.CommandText before calling a MLDBCommand.Execute method

Error code	-10196
Error constant	EL_DNET_NO_EXECUTE_ON_NULL

Probable cause

A null SQL statement is being executed. Make sure the SQL statement is non-null before executing it.

Attempt to execute SQL statement '%1' after MLDBCommand.Close() was called

Error code	-10197
Error constant	EL_DNET_NO_EXECUTE_ON_CLOSED
Parameter 1	The SQL statement.

Probable cause

The SQL statement is being executed when the database connection is closed. Make sure the database connection is open before executing a statement.

Attempt to prepare null SQL statement. Set value of MLDBCommand.CommandText before calling MLDBCommand.Prepare()

Error code	-10195
Error constant	EL_DNET_NO_PREPARE_ON_NULL

Probable cause

A null SQL statement is being prepared. Make sure the SQL statement is non-null before preparing it.

Attempt to prepare SQL statement '%1' after MLDBCommand.Close() was called

Error code	-10194
Error constant	EL_DNET_NO_PREPARE_ON_CLOSED
Parameter 1	The SQL statement.

Probable cause

The SQL statement is being prepared when the database connection is closed. Make sure the database connection is open before preparing a statement.

Attempt to set non-null column to null

Error code	-10029
Error constant	NULL_FOR_NONNULL

Probable cause

The MobiLink server attempted to download a null into a non-nullable column.

Attempt to use a connection with an invalid handle

Error code	-10203
Error constant	EL_DNET_INVALID_CONN_HANDLE

Probable cause

Make sure the connection handle is valid before using it.

Bad stream specification: %1

Error code	-10105
Error constant	BAD_STREAM_SPEC
Parameter 1	The stream name.

Probable cause

The stream name was specified incorrectly. Please consult the documentation for the -x and -xo switches.

Bad stream type: %1

Error code	-10106
Error constant	BAD_STREAM_TYPE
Parameter 1	The stream type.

Probable cause

The given stream type is unrecognized. Valid names include 'tcpip', 'http', 'tls', and 'https'.

Binding of parameter %1 requires value to be of type '%2', but a '%3' was supplied

Error code	-10201
Error constant	EL_DNET_PARAM_TYPE_MISMATCH
Parameter 1	The parameter number.
Parameter 2	The expected type.
Parameter 3	The supplied type.

Probable cause

The supplied parameter type is incorrect. Change the parameter to the proper type.

Cannot convert '%1' to Unicode

Error code	-10016
Error constant	ERROR_CANNOT_CONVERT_TO_UNICODE
Parameter 1	String to be converted.

Probable cause

The MobiLink server was not able to convert the given string to Unicode using Unilib.

Cannot load DLL or shared object: '%1' for Script Language: '%2'

Error code	-10086
Error constant	EL_UNABLE_TO_LOAD_LANG_DLL
Parameter 1	The DLL or shared object name.
Parameter 2	The script language name.

Probable cause

Please make sure that the script language is valid. Currently the script languages supported by the MobiLink server are SQL (sql), Java (java) and .NET (dnet).

Cannot skip generating the next last download timestamp without having the modify_next_last_download_timestamp script

Error code	-10315
Error constant	CANNOT_SKIP_GEN_NLDT_WITHOUT_MOD_NLDT

Probable cause

The MobiLink server will rely on the user-defined prepare_for_download and modify_next_last_download_timestamp scripts to generate the next last download timestamp that will be used to create the download stream in the next synchronization.

Caught JAVA exception with type: %1. Exception message: %2

Error code	-10118
Error constant	EL_JAVA_CAUGHT_JAVA_EXCEPTION_WITH_TYPE
Parameter 1	Class name.
Parameter 2	Error message.

Probable cause

A Java script caused the given exception. Either correct the condition that caused the exception, or change the code to avoid the exception.

Client is unable to process truncate table request for table '%1'

Error code	-10089
Error constant	CLIENT_TOO_OLD_FOR_TRUNCATE
Parameter 1	Table name.

Probable cause

The download_delete_cursor script is requesting that the table be truncated. The client needs to be updated to a newer version in order to process this action.

Column names must be set in the ml_column table in order to use named row parameters

Error code	-10232
Error constant	NO_COLUMN_NAMES

Probable cause

The remote column names to be used in scripts must be defined in the ml_column table for the named parameter feature to be used.

Column-level conflict detection is not available for table '%1', because it contains BLOBs

Error code	-10224
Error constant	COLUMN_CONFLICT_DET_WITH_BLOB
Parameter 1	Table name.

Probable cause

The column-level conflict detection is not available for tables that contain BLOBs. Please use the row-level conflict detection script, upload_fetch for any tables that contain BLOBs.

Connection was dropped due to lack of network activity

Error code	-10279
Error constant	CONNECTION_DROPPED_DUE_TO_IDLE_TIMEOUT

Probable cause

The MobiLink server has dropped this connection because of lack of activity. The remote may have lost network connectivity.

Consolidated database server or ODBC error: %1

Error code	-10002
Error constant	ERROR_SQL_ERROR

Parameter 1	The actual error message sent by the database server or ODBC driver.
-------------	--

Probable cause

This may be a SQL error such as a syntax error.

Could not add script version: '%1'

Error code	-10254
Error constant	UNABLE_TO_ADD_VERSION
Parameter 1	Version string.

Probable cause

The server was unable to automatically add the given script version. This error usually happens when connecting the Monitor, which uses the script version called for_ML_Monitor_only. Check database permissions or add the script version directly.

Could not associate socket with completion port (system error %1)

Error code	-10263
Error constant	UNABLE_TO_ASSOCIATE_SOCKET_WITH_COMPL_PORT
Parameter 1	System error.

Probable cause

Please contact technical support.

Could not call method: '%1' with arguments of type '%2'

Error code	-10157
Error constant	EL_JAVA_WRONG_PARM_TYPE
Parameter 1	The method name.
Parameter 2	The type name.

Probable cause

Please refer to the MobiLink documentation to determine what argument types MobiLink expects for this call.

Could not create domain '%1'

Error code	-10192
Error constant	EL_DNET_CREATE_DOMAIN_FAIL
Parameter 1	The domain name.

Probable cause

The .NET CLR refused to create the indicated domain. Fix the domain configuration and try again.

Could not find file transfer root directory: '%1'

Error code	-10249
Error constant	FILETRANSFER_ROOT_DIR_NOT_FOUND
Parameter 1	Root path specified by user.

Probable cause

The server could not find the specified path. Please check that the path given is correct.

Could not find requested file '%1' for user '%2'

Error code	-10251
Error constant	FILETRANSFER_FILE_NOT_FOUND
Parameter 1	File name.
Parameter 2	User name.

Probable cause

The server could not find the file requested for transfer.

Could not open file for transfer: '%1'

Error code	-10252
Error constant	FILETRANSFER_OPEN_FAILED
Parameter 1	File name.

Probable cause

The server found the file requested for transfer but was unable to open the file. Check file permissions.

Could not read file for transfer: '%1'

Error code	-10253
Error constant	FILETRANSFER_READ_FAILED
Parameter 1	File name.

Probable cause

The server found the file requested for transfer but was unable to read the file. Check file permissions.

Could not transfer requested file. The transfer root was not set

Error code	-10250
Error constant	FILETRANSFER_ROOT_DIR_NOT_SET

Probable cause

The server received a client file transfer request but the transfer root directory has not been set on the server.

Cursor-based upload is no longer supported. The scripts for table '%1' must be changed to use statement-based upload

Error code	-10248
Error constant	CURSORED_UPLOAD_NOT_SUPPORTED_XXX
Parameter 1	Table name.

Probable cause

The MobiLink server no longer supports cursor-based upload. Please rewrite your upload table scripts to use statement-based upload.

Domain '%1' was not specified in Domain configuration file

Error code	-10178
Error constant	EL_DNET_DOMAIN_NOT_FOUND
Parameter 1	The domain name.

Probable cause

The event script domain name does not match any of the domains that have been configured.

Download failed with client error %1

Error code	-10035
Error constant	DOWNLOAD_FAILED_WITH_ERROR
Parameter 1	An error number sent by the client.

Probable cause

The MobiLink server aborts the synchronization when the client indicates there is a problem on the remote site during download.

Error fetching connection script %1

Error code	-10018
Error constant	ERROR_FETCHING_CONNECTION_SCRIPT
Parameter 1	Connection script name.

Probable cause

The MobiLink server was not able to refresh connection scripts. Please make sure that the database server is running and the network is okay.

Error fetching table script %1.%2

Error code	-10019
Error constant	ERROR_FETCHING_TABLE_SCRIPT
Parameter 1	Table name.
Parameter 2	Script name.

Probable cause

The MobiLink server was not able to refresh table scripts. Please make sure that the database server is running and the network is okay.

Error in reading from notification pipe (system error %1)

Error code	-10277
Error constant	ERROR_IN_READ_FROM_NOTIFICATION_PIPE
Parameter 1	System error.

Probable cause

Please contact technical support.

Error on notification pipe

Error code	-10278
Error constant	ERROR_ON_NOTIFICATION_PIPE

Probable cause

Please contact technical support.

Error while attaching thread to Java VM

Error code	-10126
Error constant	EL_JAVA_THREAD_ATTACH_ERROR

Probable cause

This is an internal startup error. Please consult technical support.

Exception thrown in constructor of class: '%1'. Error description: '%2'. Stack trace: '%3'

Error code	-10154
Error constant	EL_JAVA_USER_EXCEPTION_IN_CONSTRUCTOR
Parameter 1	The class name.
Parameter 2	The error text.
Parameter 3	The stack trace.

Probable cause

A user exception was thrown when invoking the constructor of a user class. Please examine the stack trace and fix the error.

Exception thrown in initializer of class: '%1'. Error description: '%2'. Stack trace: '%3'

Error code	-10149
Error constant	EL_JAVA_USER_EXCEPTION_IN_INIT
Parameter 1	The class name.
Parameter 2	The error text.
Parameter 3	The stack trace.

Probable cause

The stack initializers in a user supplied class have thrown an exception. Please examine the Stack trace and fix the problem.

Exception thrown in method: '%1'. Error description: '%2'. Stack trace: '%3'

Error code	-10158
------------	--------

Error constant	EL_JAVA_USER_EXCEPTION_IN_METHOD
Parameter 1	The method name.
Parameter 2	The error text.
Parameter 3	The stack trace.

Probable cause

An error has occurred in user supplied code. Please examine the Exception information and fix the error.

Expected <void> or an object, but a primitive of type '%1' was returned instead

Error code	-10131
Error constant	EL_JAVA_EXPECTED_RETURN_OBJECT
Parameter 1	Class name.

Probable cause

Methods implementing Java synchronization logic must return <void> or an object.

Expected an instance of ianywhere.ml.script.RowReader or subclass, but found class '%1' instead

Error code	-10135
Error constant	EL_JAVA_EXPECTED_ROWREADER
Parameter 1	Class name.

Probable cause

Examine your JAVA code and make sure that the object returned can be cast to a RowReader.

Expected an instance of java.lang.String or subclass, but found class '%1' instead

Error code	-10134
------------	--------

Error constant	EL_JAVA_EXPECTED_STRING
Parameter 1	Class name.

Probable cause

Methods implementing Java synchronization logic to return SQL scripts must return a java.lang.String object or a subclass.

Expecting %1 authentication parameter(s) from client, but received %2 for script %3

Error code	-10094
Error constant	WRONG_AUTH_PARM_COUNT
Parameter 1	The number of parameters expected.
Parameter 2	The number of parameters passed up from the client.
Parameter 3	The script that needs the parameters.

Probable cause

The number of authentication parameters received from the client does not match the number expected. The number of client parameters should be two less than the number required by the authenticate_parameters script.

Expecting %1 columns in cursor, but found %2

Error code	-10050
Error constant	ODBC_WRONG_NUM_COLUMNS
Parameter 1	The number of columns expected.
Parameter 2	The number of columns found.

Probable cause

The number of parameters found in the upload or download script does not match the number of columns or the number of primary key columns for the given table. Please check the number of parameters for the given script.

Expecting %1 parameters in script, but only found %2: %3

Error code	-10047
Error constant	ODBC_WRONG_NUM_PARAMETERS
Parameter 1	The number of parameters expected.
Parameter 2	The number of parameters found.
Parameter 3	The script name.

Probable cause

There are too many parameters found in the given script. Please check the number of parameters for the given script.

Expecting at least %1 parameters in script, but only found %2: %3

Error code	-10048
Error constant	ODBC_WRONG_NUM_PARAMETERS_AT_LEAST
Parameter 1	The minimum number of parameters expected.
Parameter 2	The number of parameters found.
Parameter 3	The script name.

Probable cause

There are not enough parameters found in the given script. Please check the number of parameters for the given script.

Failed to load .NET start class '%1'

Error code	-10187
Error constant	EL_DNET_STARTCLASS_LOAD_FAIL
Parameter 1	The class name.

Probable cause

MobiLink server was unable to load the given class on startup.

Failed to load necessary Java class: %1

Error code	-10127
Error constant	EL_JAVA_BOOT_CLASS_LOAD_ERR
Parameter 1	Class name.

Probable cause

This is an internal startup error. Please consult technical support.

Failed to load necessary method: '%1' for Java class: %2

Error code	-10128
Error constant	EL_JAVA_BOOT_CLASS_METH_LOAD_ERR
Parameter 1	Method name.
Parameter 2	Class name.

Probable cause

This is an internal startup error. Please consult technical support.

Failure executing script '%1'

Error code	-10205
Error constant	EL_DNET_SCRIPT_EXEC_FAIL
Parameter 1	The script.

Probable cause

MobiLink server was unable to invoke the given script. Check for previous errors in the MobiLink server log.

Failure occurred while executing user supplied code in the server

Error code	-10225
------------	--------

Error constant	EL_FAILURE_IN_USER_CODE
----------------	-------------------------

Probable cause

A failure occurred while attempting to execute user supplied code. Examine the server log and fix the user supplied code.

In table '%1', the column named '%2' in the ml_column table has an index greater than the number of remote columns

Error code	-10281
Error constant	INVALID_REF_TO_ML_COLUMN_NAME
Parameter 1	Name of table.
Parameter 2	Name of column from the ml_column table.

Probable cause

A synchronization script has an invalid named parameter reference. Check the ml_column table for this script version and table, to make sure the number and order of columns match the number and order coming up from the remote. The most likely cause is either an invalid column named in the named parameter, or invalid entries in the ml_column table prior to the valid column entry.

INTERNAL ERROR: occurred while retrieving a BLOB -- read

Error code	-10041
Error constant	BLOB_READ_ERROR

Probable cause

The MobiLink server cannot retrieve the upload data from memory or a temporary file. This is an internal error. Please contact technical support.

Internal error: wrong function '%1' called. Please contact technical support

Error code	-10051
Error constant	INTERNAL_ERR_WRONG_FUNC_IS_CALLED

Parameter 1	The function name.
-------------	--------------------

Probable cause

This is an internal error. Please contact technical support.

Internal error: '%1'

Error code	-10156
Error constant	EL_JAVA_INTERNAL_ERROR
Parameter 1	The error text.

Probable cause

MobiLink experienced a JAVA internal error. Please examine the error information printed and try to fix the problem.

Invalid context for stream parameter %1 for stream %2: %3

Error code	-10219
Error constant	BAD_STREAM_PARM_CONTEXT
Parameter 1	Parameter name.
Parameter 2	Stream number.
Parameter 3	Stream specification.

Probable cause

The given parameter is not valid for this stream. Some parameters may be specified in a server environment but not for a client.

Invalid format used for script '%1'

Error code	-10182
Error constant	EL_DNET_INVALID_SCRIPT_NAME
Parameter 1	The script.

Probable cause

The script format is invalid. The proper format is either myDomain:myClass.myMethod or just myClass.myMethod.

Invalid line found in the JVM config file: %1 All lines must begin with either '#' or '-'

Error code	-10136
Error constant	EL_JAVA_INVALID_LINE_IN_JVM_CFG
Parameter 1	Config file name.

Probable cause

MobiLink was unable to parse the jvm.cfg config file. Please check that the contents of this file are valid.

Invalid line found in the JVM config file: %1. Line is too long

Error code	-10137
Error constant	EL_JAVA_LINE_TOO_LONG_IN_JVM_CFG
Parameter 1	Config file name.

Probable cause

MobiLink was unable to parse the jvm.cfg config file. A line exceeded the maximum line length. Please check that the contents of this file are valid.

Invalid named parameter (too short or long) for script '%1'

Error code	-10226
Error constant	INVALID_NAMED_PARAMETER_LENGTH
Parameter 1	Name of script.

Probable cause

A named parameter was encountered where there was no name or the name length was too long.

Invalid parameter '%1'

Error code	-10215
Error constant	INVALID_STREAM_PARAMETER
Parameter 1	Name of the invalid parameter.

Probable cause

One or more invalid parameters were detected in the communication protocol. Please check the command line options and make sure all the protocol options valid.

Invalid password for user %1

Error code	-10057
Error constant	USER_BAD_PASSWORD
Parameter 1	The user name.

Probable cause

The password sent up from the remote is invalid for the given user. Please note: passwords are case sensitive.

Invalid return value (%2) from the %1 script. Using the default action code (%3)

Error code	-10214
Error constant	ERROR_HANDLER_BAD_RETURN
Parameter 1	Name of the script returning the bad value.
Parameter 2	Action value return from script.
Parameter 3	Action value to be used.

Probable cause

The error handler script called returned a value outside of the allowable range. The default value will be used.

Invalid stream parameter %1 for stream %2: %3

Error code	-10217
Error constant	BAD_STREAM_PARM
Parameter 1	Parameter name.
Parameter 2	Stream number.
Parameter 3	Stream specification.

Probable cause

The given parameter is not valid for this stream. Check for misspelling.

Invalid system parameter '%1' for script '%2'

Error code	-10228
Error constant	INVALID_NAMED_SYSTEM_PARAMETER
Parameter 1	Name of invalid system parameter.
Parameter 2	Name of script.

Probable cause

The named system parameter cannot be used with the given script.

Invalid value %1 stream parameter %2 for stream %3: %4

Error code	-10218
Error constant	BAD_STREAM_PARM_VALUE
Parameter 1	Parameter value.
Parameter 2	Parameter name.
Parameter 3	Stream number.
Parameter 4	Stream specification.

Probable cause

The value for the given parameter is not valid for this stream.

Java exception

Error code	-10148
Error constant	EL_JAVA_EXCEPTION

Probable cause

Examine the MobiLink log error message adjacent to this error for more information.

LANG: %1 - Failed to allocate database connection

Error code	-10085
Error constant	EL_FAILED_TO_ALLOCATE_CONNECTION
Parameter 1	The name of the script language.

Probable cause

A connection cannot be made to the database server.

LANG: %1 - Failed to attach thread

Error code	-10084
Error constant	EL_FAILED_TO_ATTACH_THREAD
Parameter 1	The name of the script language.

Probable cause

A MobiLink server thread could not attach itself to the DLL or shared object used to process the given script language. Please make sure that the MobiLink server installation contains all of the required DLLs or shared objects.

Linkage error while loading class: '%1' Error description: '%2'

Error code	-10150
Error constant	EL_JAVA_LINKAGE_ERROR
Parameter 1	The class name.

Parameter 2	The error text.
-------------	-----------------

Probable cause

The Java VM was unable to load a class. Please examine the Error description printed and fix the problem.

Memory allocation failed

Error code	-10060
Error constant	OUT_OF_MEMORY

Probable cause

Your system is running out of memory. You may need to close some applications or add more memory to your system.

Memory allocation failed, attempted to allocate %1 bytes

Error code	-10003
Error constant	MEMORY_ALLOCATION_FAILED
Parameter 1	The number of bytes it was trying to allocate.

Probable cause

Your system is running out of memory. You may need to close some applications or add more memory to your system.

Network address '%1' is not local

Error code	-10259
Error constant	NOT_LOCAL_IP_ADDRESS
Parameter 1	Host name.

Probable cause

The network address provided does not resolve to a network adapter on this machine.

No Assembly in domain '%1' contains type '%2'

Error code	-10179
Error constant	EL_DNET_NO_ASM_CONTAINS_TYPE
Parameter 1	The domain name.
Parameter 2	The type name.

Probable cause

Make sure the type is defined in the given domain.

No download confirmation from remote database

Error code	-10034
Error constant	NO_CONFIRMATION

Probable cause

The client was supposed to send a confirmation status to the MobiLink server after download. The MobiLink server did not receive this confirmation. This could happen if the synchronization is interrupted or if there is a network problem.

No error or unknown error

Error code	0
Error constant	NONE

Probable cause

This code indicates there was either no error or an unknown error. The MobiLink server did not assign an error number.

No public methods found in script class: '%1'

Error code	-10151
Error constant	EL_JAVA_NO_PUBLIC_METHODS
Parameter 1	The class name.

Probable cause

A script class must have public methods so that MobiLink can call its methods. Please supply a fixed class.

No suitable constructor found in class: '%1'

Error code	-10153
Error constant	EL_JAVA_NO_SUITABLE_CONSTRUCTOR
Parameter 1	The class name.

Probable cause

Please make sure that the user supplied class has a public constructor that MobiLink can invoke in order to create an instance.

No valid constructor was found for class '%1'

Error code	-10161
Error constant	EL_DNET_NO_VALID_CONSTRUCTOR_ERROR
Parameter 1	The class name.

Probable cause

MobiLink server was unable to find a valid constructor for the given class.

Not enough arguments to execute script: '%1.%2'. %3 arguments are needed but only %4 are provided

Error code	-10130
Error constant	EL_JAVA_NOT_ENOUGH_PARMS
Parameter 1	Class name.
Parameter 2	Method name.
Parameter 3	Number of parameters expected.
Parameter 4	Number of parameters provided.

Probable cause

Consult the documentation for the event associated with this script.

One or more invalid parameters prevented startup

Error code	-10109
Error constant	NETIO_INVALID_PARAMETERS

Probable cause

The application could not be started due to invalid command-line parameters. Consult the documentation for the application command line.

Only one domain can be used per script version. Domain '%1' was in use when script '%2' attempted to use domain '%3'

Error code	-10183
Error constant	EL_DNET_ONE_DOMAIN_PER_VERSION
Parameter 1	The domain name.
Parameter 2	The script.
Parameter 3	The extra domain name.

Probable cause

The script is of the form myDomain:myClass.myMethod, and another script in the same script version used a different domain name. Make sure all scripts for the same script version use the same domain.

Only one of upload_fetch and upload_fetch_columns scripts may be defined for table '%1'

Error code	-10220
Error constant	MULTIPLE_UPLOAD_FETCH_SCRIPTS
Parameter 1	Table name.

Probable cause

MobiLink server uses one of these scripts for conflict detection. Please only define one of these two scripts.

Option '%1' is invalid or was not specified correctly on MobiLink command line

Error code	-10163
Error constant	EL_DNET_INVALID_OPTION
Parameter 1	The option name.

Probable cause

The given option is improperly specified.

Option '%1' was previously defined on the MobiLink command line with value '%2'

Error code	-10162
Error constant	EL_DNET_OPTION_DEFINED
Parameter 1	The option name.
Parameter 2	The extra option value.

Probable cause

The given option may not be specified more than once.

Parameter %1 has been set to NULL

Error code	-10230
Error constant	PARAMETER_N_NULL
Parameter 1	Number of parameter

Probable cause

Parameter may be modified but not set to NULL.

Protocol error: there is no publication that contains table '%1'

Error code	-10017
Error constant	INVALID_TABLE_PUBLICATION_COUNT_XX
Parameter 1	Table name.

Probable cause

A table is requested for synchronization by the client. However the table is not in any publication. Please make sure that the table was not dropped in the remote database.

Protocol error: %1

Error code	-10001
Error constant	PROTOCOL_ERROR
Parameter 1	The error number.

Probable cause

The MobiLink server does not understand the request sent by the client. This could happen if the client is newer than the MobiLink server. Please contact technical support

Protocol version mismatch -- expecting %1 but received %2

Error code	-10004
Error constant	STREAM_INCORRECT_VERSION
Parameter 1	The maximum version accepted.
Parameter 2	The version as sent from the client.

Probable cause

The MobiLink server is communicating with the client using different protocol versions. If the client sends a version that is not supported by the MobiLink server, it will give this error. Please make sure that you are not using a newer client (DBMLSync or an UltraLite application) to talk to an older version of the MobiLink server.

Required ODBC function %1 is not supported by the driver

Error code	-10075
Error constant	ODBC_MISSING_REQUIRED_FUNCTION
Parameter 1	The ODBC function name.

Probable cause

The MobiLink server was not able to find the function from the ODBC driver. Please start the MobiLink server with the recommended ODBC drivers.

Returned class '%1' not a subclass of anywhere.ml.script.RowReader or java.lang.String

Error code	-10132
Error constant	EL_JAVA_INVALID_RETURN_OBJECT
Parameter 1	Class name.

Probable cause

Change the class so it returns one of the proper types.

Script '%1' encountered an error

Error code	-10189
Error constant	EL_DNET_USER_SCRIPT_ERROR
Parameter 1	The script.

Probable cause

When invoked, the script triggered a ScriptExecutionException.

Script '%1' is a member of '%2', but only %3 classes are permitted per script version

Error code	-10204
------------	--------

Error constant	EL_DNET_TOO_MANY_CLASSES_PER_VERSION
Parameter 1	The method name.
Parameter 2	The class name.
Parameter 3	The number of classes permitted.

Probable cause

A script version cannot explicitly reference more than the given number of classes. If you encounter this error, create a wrapper class containing all of the methods used by different events.

Script '%1' reported a fatal error

Error code	-10190
Error constant	EL_DNET_FATAL_ERROR
Parameter 1	The script.

Probable cause

When invoked, the script triggered a FatalException.

Script '%1' reported a server error

Error code	-10188
Error constant	EL_DNET_SERVER_ERROR
Parameter 1	The script.

Probable cause

When invoked, the script triggered a ServerException.

Script '%1' reported a synchronization error

Error code	-10186
Error constant	EL_DNET_SYNC_ERROR
Parameter 1	The script.

Probable cause

When invoked, the script triggered a SynchronizationException.

Script '%1' requires %2 parameters, but %3 parameters were supplied

Error code	-10184
Error constant	EL_DNET_NUM_PARAMS_MISMATCH
Parameter 1	The script.
Parameter 2	The required number of method parameters.
Parameter 3	The supplied number of method parameters.

Probable cause

The method invoked by the script must accept the given number of parameters. Change the method accordingly.

Script '%1' returned an object of type '%2', which is not a subtype of 'System.Void' or 'System.String'

Error code	-10185
Error constant	EL_DNET_INVALID_RETURN_OBJ
Parameter 1	The method name.
Parameter 2	The returned object type.

Probable cause

When invoked, the script returned an object of unexpected type. Change your method to always return an object of the correct type.

Script '%1' returns a '%2' object, but only return types of 'System.Void' and 'System.String' are supported

Error code	-10173
Error constant	EL_DNET_INVALID_RETURN_TYPE

Parameter 1	The method name.
Parameter 2	The returned object type.

Probable cause

The method is declared to return a type that is unexpected. Change your method to return the correct type.

Scripts cannot be defined as NULL

Error code	-10039
Error constant	CURSOR_SCRIPTS_MUST_BE_NON_NULL

Probable cause

Scripts cannot be defined as NULL or empty string. Please check the script definitions to make sure that no script is defined as NULL or empty string.

Shared install directory is incorrect: %1

Error code	-10144
Error constant	EL_JAVA_SHARED_LOCATION_INCORRECT
Parameter 1	SQL Anywhere shared directory.

Probable cause

Please fix the shared components environment variable so that it points to the correct location.

SQL Passthrough protocol error: '%1'. Please contact technical support

Error code	-10300
Error constant	SQL_PASSTHROUGH_PROTOCOL_ERROR

Probable cause

Please contact technical support. Include the MobiLink server log.

Stream Error: %1

Error code	-10117
Error constant	STREAM_ERROR
Parameter 1	Error message.

Probable cause

A generic stream error. The details of the error are in the message.

System exception thrown in constructor of class: '%1'. Error description: '%2'

Error code	-10155
Error constant	EL_JAVA_SYSTEM_EXCEPTION_IN_CONSTRUCTOR
Parameter 1	The class name.
Parameter 2	The error text.

Probable cause

An system exception was thrown when invoking the constructor of a user class. Please examine the stack trace and fix the error.

System parameter %1 has been set to NULL

Error code	-10229
Error constant	SYSTEM_PARAMETER_NULL
Parameter 1	Name of system parameter.

Probable cause

System parameters may be modified but not set to NULL.

Table '%1' does not have a column named '%2'

Error code	-10233
------------	--------

Error constant	UNKNOWN_TABLE_COLUMN
Parameter 1	Name of table.
Parameter 2	Name of column.

Probable cause

The column name referenced in the script does not appear in the list of column names for the table.

The %1 script returned %2

Error code	-10052
Error constant	GENERIC_ERROR_HANDLER_RETURN
Parameter 1	The user authentication script name.
Parameter 2	The script returning value.

Probable cause

The user authentication script returned a value greater than 3000.

The .NET scripting VM requires version %1 of the MobiLink ODBC Bridge DLL, but was supplied version %2 instead

Error code	-10174
Error constant	EL_DNET_ODBC_VER_MISMATCH
Parameter 1	The required version.
Parameter 2	The supplied version.

Probable cause

This is likely an install problem. Please contact technical support.

The .NET scripting VM requires version %1 of the MobiLink Script DLL, but was supplied version %2 instead

Error code	-10175
------------	--------

Error constant	EL_DNET_SCRIPT_DLL_VER_MISMATCH
Parameter 1	The required version.
Parameter 2	The supplied version.

Probable cause

This is likely an install problem. Please contact technical support.

The character set (%1) used by the remote client cannot be mapped by the MobiLink server

Error code	-10306
Error constant	UNKNOWN_CID
Parameter 1	Character set ID.

Probable cause

The character data supplied by the remote cannot be translated into the character set required by the consolidated database.

The character set (%1) used by the remote client cannot be mapped by the MobiLink server

Error code	-10307
Error constant	UNKNOWN_CHARSET
Parameter 1	Character set label.

Probable cause

The character data supplied by the remote cannot be translated into the character set required by the consolidated database.

The classpath '%1' is too long

Error code	-10141
Error constant	EL_JAVA_CLASSPATH_TOO_LONG

Parameter 1	Classpath.
-------------	------------

Probable cause

The classpath is too long. Please fix the classpath in order to shorten its length.

The client cannot find the consolidated progress offset from the client transaction log(s)

Error code	-10090
Error constant	CANNOT_FIND_PROG_OFFSET

Probable cause

When the progress offsets in the consolidated and the remote databases are different, the MobiLink server may ask the client to redo the synchronization again with the progress offset from the consolidated database. However the requested consolidated progress offset cannot be found in the transaction log(s) of the remote database because the old transaction logs have been deleted or the requested offset has not been created yet. Please find the source that caused this problem, and then rerun dbmlsync using the -ra or -rb option.

The following non-daemon threads were destroyed: %1

Error code	-10124
Error constant	EL_JAVA_THREADS_DESTROYED
Parameter 1	The list of thread identifiers.

Probable cause

The given Java threads were forcibly destroyed during shutdown. Use the ShutdownListener interface to destroy threads gracefully during MobiLink server shutdown.

The handle_UploadData event script must be void or return null

Error code	-10223
Error constant	HANDLE_UPLOAD_DATA_SHOULD_BE_VOID

Probable cause

Rewrite this handle_UploadData script so that it has a void return type or returns null.

The MobiLink server (farm version '%1') cannot run, because another MobiLink server with a different version is currently running in the MobiLink server farm

Error code	-10293
Error constant	FARM_VERSION_MISMATCH
Parameter 1	Version number.

Probable cause

The MobiLink server has refused to start up, because another MobiLink server with a different version is currently running against the same consolidated database. Please make sure all the MobiLink servers have the same version, when they are running against the same database server.

The MobiLink server and client implementation IDs mismatch

Error code	-10295
Error constant	MISMATCH_IMPLEMENTATION_ID

Probable cause

The MobiLink server was not able to accept the synchronization request due to the server and client implementation IDs mismatch.

The MobiLink server DLL or shared object version does not match the data layer DLL or shared object version

Error code	-10081
Error constant	DL_VERSION_MISMATCH

Probable cause

The MobiLink server DLL or shared object that processes the upload and download data is not consistent with the version of the data layer DLL or shared object (ODBC) that is used to interact with the databases. Please check your MobiLink server installation.

The MobiLink server has encountered an error and the synchronization has been aborted

Error code	-10244
Error constant	DEFAULT_SERVER_ERROR

Probable cause

An error has occurred in the MobiLink server. Please see the MobiLink server message log for more details about this error.

The MobiLink server was unable to calculate the timestamp precision on the consolidated database using the ml_scripts_modified table. Timestamp precision related warnings will not be generated

Error code	-10076
Error constant	UNKNOWN_CONSOLIDATED_TIMESTAMP_PRECISION

Probable cause

The MobiLink server must calculate the maximum timestamp precision of the consolidated database in order to properly synchronize all time-related values. This error typically comes up when a non-recommended ODBC driver is used. Please start the MobiLink server with a recommended ODBC driver.

The MobiLink server was unable to modify the error message using the modify_error_message script

Error code	-10077
Error constant	ERROR_MODIFY_ERROR_MSG_SCRIPT

Probable cause

An error occurred during synchronization, but the MobiLink server was unable to modify the error message using the given script. Please check your modify_error_message script.

The MobiLink system table '%1' is missing or a table column is missing

Error code	-10100
Error constant	ML_TABLE_OR_COLUMN_MISSING
Parameter 1	Table name.

Probable cause

The table or table column cannot be found in the consolidated database. The MobiLink tables may not have been installed or an upgrade may be required.

The name '%1' is not a valid name for a .NET start class

Error code	-10177
Error constant	EL_DNET_INVALID_STARTCLASS_NAME
Parameter 1	The start class name.

Probable cause

The start class name is not well formed please fix the name and run again.

The number of columns in client table '%1' does not agree with the number defined in ml_column

Error code	-10280
Error constant	INVALID_NUMBER_OF_CLIENT_COLUMNS
Parameter 1	Name of table.

Probable cause

The number of columns sent for the table from the client is greater than the number as defined in ml_column. Ensure that ml_column is up to date.

The option '%1' needs a path

Error code	-10140
------------	--------

Error constant	EL_JAVA_FLAG_NEEDS_PATH
Parameter 1	Option name.

Probable cause

The given option must be followed by a path.

The options '%1' and '%2' must not be used together

Error code	-10139
Error constant	EL_JAVA_EXCLUSIVE_FLAGS
Parameter 1	Option name.
Parameter 2	Option name.

Probable cause

Consider using one option or the other, or neither, but not both.

The prepared SQL statement '%1' requires %2 parameters, but %3 parameters were supplied

Error code	-10200
Error constant	EL_DNET_NUM_BOUND_PARAM_MISMATCH
Parameter 1	The SQL statement.
Parameter 2	The expected number of parameters.
Parameter 3	The supplied number of parameters.

Probable cause

The statement was executed with the wrong number of parameters. Please supply the correct number of parameters before executing the statement.

The prepared SQL statement '%1' requires %2 parameters, but parameter %3 was not supplied

Error code	-10198
Error constant	EL_DNET_PARAM_NOT_BOUND
Parameter 1	The SQL statement.
Parameter 2	The expected number of parameters.
Parameter 3	The supplied number of parameters.

Probable cause

The statement was executed too few parameters. Please supply the correct number of parameters before executing the statement.

The remote database identified by remote ID '%1' is already synchronizing. Concurrent synchronizations using the same remote ID are not allowed

Error code	-10238
Error constant	REMOTEID_ALREADY_IN_USE
Parameter 1	The remote ID.

Probable cause

The given remote database identified by the remote ID is already synchronizing. Please try the synchronization later.

The remote database may have been restored from backup, or perhaps remote ID '%1' is being used by different remote databases. Set ml_subscription.progress to zero to re-enable synchronizations for this remote database

Error code	-10023
Error constant	SEQUENCE_NUMBER_TOO_SMALL

Parameter 1	Remote ID.
-------------	------------

Probable cause

Before doing synchronization, the MobiLink server compares the sequence number sent by the client with that stored in the consolidated database to see if they match. If a remote database is restored from a backup or the last synchronization was interrupted, the sequence number may be less than that in the consolidated. Please set ml_subscription.progress to zero to re-enable synchronizations for this remote database.

The row is too big. The size (%1 bytes) exceeds the maximum allowable size (%2 bytes)

Error code	-10033
Error constant	ROW_TOO_BIG
Parameter 1	The actual row size to be downloaded.
Parameter 2	The maximum row size the client is willing to accept.

Probable cause

An UltraLite application may have a row size limit. If the row size in the synchronization table in the consolidated database has exceeded this limit, the table cannot be downloaded. Please redesign your synchronization table.

The script '%1' can not process pre-image row data

Error code	-10234
Error constant	SCRIPT_NO_OLD_ROW_DATA
Parameter 1	Name of script.

Probable cause

Only scripts that process pre-image row data may use named parameters that reference pre-image row data.

The script '%1' can not process row data

Error code	-10231
Error constant	SCRIPT_NO_ROW_DATA

Parameter 1	Name of script.
-------------	-----------------

Probable cause

Only scripts that process row data may use named parameters that reference row data.

The script '%1' contains an invalid character in a named parameter

Error code	-10235
Error constant	INVALID_NAMED_PARAMETER_CHAR
Parameter 1	Name of script.

Probable cause

The rules for naming a SQL Anywhere identifier must be followed.

The script '%1' contains an invalid parameter reference: '%2'

Error code	-10239
Error constant	INVALID_NAMED_PARAMETER_NUMBER
Parameter 1	Name of script.
Parameter 2	Number of parameter.

Probable cause

The script contains a numeric reference to a parameter which is either zero or too large.

The script '%1' contains an invalid user parameter: '%2'

Error code	-10240
Error constant	INVALID_NAMED_USER_PARAMETER
Parameter 1	Name of script.
Parameter 2	Number of parameter.

Probable cause

The script contains a numeric reference to a user parameter.

The script '%1' contains invalid syntax for using named parameters

Error code	-10236
Error constant	INVALID_NAMED_PARAMETER_SCRIPT
Parameter 1	Name of script.

Probable cause

The script does not contain a properly formed named parameter sequence. To reference a script parameter by name, enclose the parameter in curly braces and prefix it with ml, as in {ml parameter}. For example, {ml s.action_code}.

The script '%1' references authentication parameter %2 but there are only %3

Error code	-10242
Error constant	INVALID_AUTH_PARM_NUMBER
Parameter 1	Name of script.
Parameter 2	Number of parameter.
Parameter 3	Number of parameters.

Probable cause

The script contains a reference to an authentication parameter which does not exist.

The script '%1' references table '%2' column %3, but there are only %4 columns

Error code	-10241
Error constant	INVALID_TABLE_COLUMN
Parameter 1	Name of script.

Parameter 2	Name of table.
Parameter 3	Number of parameter.
Parameter 4	Number of table columns.

Probable cause

The script contains a reference to a parameter which is either zero or too large.

The script '%1' references the in out parameter '%2' more than one time

Error code	-10237
Error constant	MULTI_USE_INOUT_PARAMETER
Parameter 1	Name of script.
Parameter 2	Name of parameter.

Probable cause

In out parameters may only be passed to a script once.

The script '%1' references unknown authentication parameter '%2'

Error code	-10243
Error constant	UNKNOWN_AUTH_PARM
Parameter 1	Name of script.
Parameter 2	Name of parameter.

Probable cause

The script contains a reference to a authentication parameter which does not exist.

The synchronization sequence number stored in ml_subscription.progress is negative. Set this value to zero (0) to re-enable synchronizations for remote ID '%1'

Error code	-10022
Error constant	NEGATIVE_SEQUENCE_NUMBER_IN_CONSOLIDATED
Parameter 1	Remote ID.

Probable cause

The sequence number stored in the ml_subscription table in the consolidated database is negative. This number is maintained by the MobiLink server. In most cases, please do not directly modify this number.

The upload table '%1' (column #'%2') has the data type '%3', but your ODBC driver doesn't support '%4'

Error code	-10245
Error constant	DATATYPE_NOT_SUPPORTED_BY_DRIVER
Parameter 1	Table name.
Parameter 2	Column index.
Parameter 3	SQL Anywhere data type.
Parameter 4	ODBC data type.

Probable cause

The upload table contains a column with a data type that is not supported by your ODBC driver. Please make sure that the MobiLink server is using a recommended ODBC driver.

There are no entries in the JVM config file: %1

Error code	-10138
Error constant	EL_JAVA_NO_ENTRIES_IN_JVM_CFG
Parameter 1	Config file name.

Probable cause

If a jvm.cfg file is found it is expected to have at least one line. Please remove or populate the jvm.cfg.

There are too many entries in the JVM config file: %1

Error code	-10147
Error constant	EL_JAVA_TOO_MANY_ENTRIES_IN_JVM_CFG
Parameter 1	The config file.

Probable cause

The jvm.cfg is probably corrupt. Please check the contents of the jvm.cfg file.

There has been an internal error in the server shared state. '%1'

Error code	-10302
Error constant	SHARED_STATE_INTERNAL_ERROR

Probable cause

MobiLink has experienced an error in the server shared state. Examine the server configuration and consolidated database for configuration issues.

There is an invalid SQL Passthrough repair action '%1' for this user. SQL Passthrough for this user has been halted

Error code	-10299
Error constant	UNKNOWN_PASSTHROUGH_REPAIR_ACTION

Probable cause

Fix the unknown SQL Passthrough repair action that has been specified for this failed SQL Passthrough script.

There is no download data script defined for table '%1'. If you want to be able to synchronize anyway, with the risk of potentially losing download data, use the -fr command line option

Error code	-10093
Error constant	NO_DOWNLOAD_DATA_SCRIPT
Parameter 1	Table name.

Probable cause

If there is no download data script for a table and synchronization is download only, there is a risk of potentially losing the download data. To prevent this situation, the synchronization is aborted. If you do not care about losing download data, you can use -fr to force the synchronization to continue.

There is no upload data script defined for table '%1'. If you want to be able to synchronize anyway, with the risk of potentially losing upload data, use the -fr command line option

Error code	-10092
Error constant	NO_UPLOAD_DATA_SCRIPT
Parameter 1	Table name.

Probable cause

If there is no upload data script for a table, there is a risk of potentially losing the upload data. To prevent this situation, the synchronization is aborted. If you do not care about losing upload data, you can use -fr to force the synchronization to continue.

This connection will be abandoned due to previous errors

Error code	-10091
Error constant	CONNECTION_ABANDONED

Probable cause

Due to the severity of error(s) encountered processing the upload stream, further work will be futile. This is probably due to an I/O error or a protocol problem.

This server does not have shared server state enabled but other servers connected to this consolidated database have shared server state enabled

Error code	-10311
Error constant	SHARED_STATE_OTHERS_IN_SHARED_MODE

Probable cause

All servers connected to the same consolidated database must have shared server state enabled. Use the '-ss' option when starting this server.

This server is not licensed to connect to a consolidated database of the following type: %1

Error code	-10309
Error constant	UNLICENSED_FOR_THIS_CONSOLIDATED_TYPE
Parameter 1	Consolidated database type.

Probable cause

Some MobiLink server licenses are restricted to specific consolidated database types. Use a DSN that connects to a consolidated database type you are licensed for.

This server is not licensed to use dbmlsync

Error code	-10314
Error constant	UNLICENSED_FOR_MLSYNC

Probable cause

Some MobiLink server licenses are not allowed to use dbmlsync. You may not use dbmlsync to sync with this server.

This server is not licensed to use QAnywhere

Error code	-10313
Error constant	UNLICENSED_FOR_QANYWHERE

Probable cause

Some MobiLink server licenses are not allowed to use QAnywhere. You may not use the -m option.

This server is not licensed to use the direct row API

Error code	-10312
Error constant	UNLICENSED_FOR_DIRECT_ROW_API

Probable cause

Some MobiLink server licenses are not allowed to use the direct row API. You may not have any handle_UploadData or handle_DownloadData scripts.

This Synchronization is using a blocking download ack but has nonblocking download ack events defined

Error code	-10284
Error constant	NONBLOCKING_EVENTS_FOR_BLOCKING_ACK

Probable cause

The events nonblocking_download_ack and publication_nonblocking_download_ack may not be defined for a synchronization which is using a blocking download ack. Please check your -nba flag setting or remove the events.

This synchronization was canceled due to a new synchronization <%1> with the same remote id

Error code	-10256
Error constant	SYNC_STOPPED_FOR_NEW_SYNC_WITH_REMOTE_ID
Parameter 1	Synchronization ID.

Probable cause

A new synchronization from the same remote as this synchronization has started. The server has canceled this connection since the remote must have disconnected.

This synchronization was paused due to an existing synchronization <%1> with the same remote id

Error code	-10257
Error constant	SYNC_PAUSED_FOR_OLD_SYNC_WITH_REMOTE_ID
Parameter 1	Synchronization ID.

Probable cause

A new synchronization from the same remote as an existing synchronization <%1!d!> has started. The server has canceled the existing synchronization and temporarily paused this synchronization.

Too many options sent to Java VM

Error code	-10146
Error constant	EL_JAVA_TOO_MANY_OPTIONS

Probable cause

The number of options passed to the Java VM is exceedingly large. Please reduce the number of command line arguments.

Transactions on this connection cannot be committed or rolled back

Error code	-10202
Error constant	EL_DNET_TRANSACTS_NOT_ALLOWED

Probable cause

An attempt was made to commit or roll back a transaction on a database connection that MobiLink server controls. Do not attempt to commit or roll back a MobiLink server database connection from a method invoked as a script.

Unable to abort the distributed transaction (event: %1) -- system error: '%2'

Error code	-10290
Error constant	DTC_UNABLE_TO_ABORT

Probable cause

The MobiLink server was not able to abort the distributed transaction.

Unable to accept an incoming connection (system error %1)

Error code	-10276
Error constant	UNABLE_TO_ACCEPT_INCOMING_CONNECTION
Parameter 1	System error.

Probable cause

Please contact technical support.

Unable to accept new connections on network listener port

Error code	-10292
Error constant	UNABLE_TO_ACCEPT_ON_LISTEN_PORT

Probable cause

The MobiLink server was unable to accept an incoming connection. Please contact technical support.

Unable to access the JRE at: %1

Error code	-10145
Error constant	EL_JAVA_JRE_PATH_INCORRECT
Parameter 1	The JRE path.

Probable cause

Please fix the argument to the -jrepath option so that MobiLink may load the required JAVA virtual machine.

Unable to allocate a connection

Error code	-10067
Error constant	ODBC_UNABLE_TO_ALLOCATE_A_CONNECTION

Probable cause

The MobiLink server was not able to allocate a connection. Please make sure that there is enough memory to start the MobiLink server. Also, make sure that the database server is running, and that the user ID and password are valid.

Unable to allocate memory for the DownloadData instance

Error code	-10221
Error constant	EL_JAVA_FAILED_ALLOC_DOWNLOAD_DATA

Probable cause

The JAVA VM has run out of memory. Try increasing the amount of memory available to the Java VM.

Unable to allocate memory for the UploadData instance

Error code	-10222
Error constant	EL_JAVA_FAILED_ALLOC_UPLOADED_TRANSACTION

Probable cause

The JAVA VM has run out of memory. Try increasing the amount of memory available to the Java VM.

Unable to allocate memory needed for script execution

Error code	-10170
Error constant	EL_DNET_MEM_ALLOC_FAIL

Probable cause

Consider adding more RAM, or shutting down other programs, or reducing the memory required by the .NET synchronization scripts.

Unable to attach JDBC connection

Error code	-10160
Error constant	EL_JAVA_JDBC_UNABLE_TO_ATTACH

Probable cause

MobiLink was unable to wrap an ODBC connection in order to create a JDBC connection.

Unable to attach thread to .NET runtime

Error code	-10168
Error constant	EL_DNET_WORKER_ATTACH_FAIL

Probable cause

This is an internal startup error. Please contact technical support.

Unable to authenticate the user

Error code	-10310
Error constant	UNABLE_TO_AUTH_USER

Probable cause

The MobiLink server was not able to authenticate the user. Please check the MobiLink server message log for more details.

Unable to authenticate user %1

Error code	-10055
Error constant	ERROR_AUTHENTICATING
Parameter 1	The user name.

Probable cause

The MobiLink server was not able to authenticate the given user.

Unable to bind listener socket to port (system error %1)

Error code	-10261
Error constant	UNABLE_TO_BIND_LISTENER_PORT
Parameter 1	System error.

Probable cause

Please contact technical support.

Unable to close socket (system error %1)

Error code	-10271
Error constant	UNABLE_TO_CLOSE_SOCKET
Parameter 1	System error.

Probable cause

Please contact technical support.

Unable to commit the distributed transaction (event: %1) -- system error: '%2'

Error code	-10289
Error constant	DTC_UNABLE_TO_COMMIT

Probable cause

The MobiLink server was not able to commit the distributed transaction.

Unable to COMMIT transaction: %1 -- Attempting to ROLLBACK

Error code	-10065
Error constant	UNABLE_TO_COMMIT
Parameter 1	The script name.

Probable cause

The MobiLink server was not able to commit the transaction for the given script. Writing scripts to avoid deadlocks is always a good practice.

Unable to connect to the consolidated database. Aborting the synchronization

Error code	-10028
Error constant	UNABLE_TO_CONNECT_TO_CONSOLIDATED

Probable cause

The MobiLink server was not able to make a connection to the consolidated database server. Please make sure that the database server is running and the network is okay.

Unable to convert the string %1 to a numeric value

Error code	-10213
Error constant	UNABLE_TO_CONVERT_STR_TO_NUMERIC
Parameter 1	String to be converted.

Probable cause

The MobiLink server cannot convert the string to a numeric value. This is an internal error. Please contact technical support.

Unable to create a shared memory file

Error code	-10282
Error constant	UNABLE_TO_CREATE_SHARED_MEMORY

Probable cause

The MobiLink server was not able to create a shared memory file using the given MobiLink server name. Please check if a MobiLink server with the same name is currently running on the local machine.

Unable to create an I/O completion port (system error %1)

Error code	-10258
Error constant	CANNOT_CREATE_COMPLETION_PORT
Parameter 1	System error.

Probable cause

Please contact technical support.

Unable to create connection socket (system error %1)

Error code	-10264
Error constant	UNABLE_TO_CREATE_CONNECT_SOCKET
Parameter 1	System error.

Probable cause

Please contact technical support.

Unable to create listener socket (system error %1)

Error code	-10260
Error constant	UNABLE_TO_CREATE_LISTENER_SOCKET
Parameter 1	System error.

Probable cause

Please contact technical support.

Unable to create new database connection

Error code	-10159
Error constant	EL_JAVA_JDBC_UNABLE_TO_CONNECT

Probable cause

MobiLink was unable to create a new ODBC connection needed to create a new JDBC wrapper.

Unable to create the background thread

Error code	-10112
Error constant	UNABLE_TO_CREATE_BACKGROUND_THREAD

Probable cause

MobiLink server was unable to create a thread for background processing. The most likely cause is insufficient memory.

Unable to create unix pipe for socket selector notification (system error %1)

Error code	-10272
Error constant	UNABLE_TO_CREATE_UNIX_PIPE
Parameter 1	System error.

Probable cause

Please contact technical support.

Unable to delete from table '%1' using %2

Error code	-10073
Error constant	DELETE_FROM
Parameter 1	Table name.
Parameter 2	Script name.

Probable cause

A failure occurred when the MobiLink server was deleting row(s) from the given table in the consolidated database.

Unable to delete user name '%1' from the ml_user_table

Error code	-10083
Error constant	ERROR_DELETING_USER

Parameter 1	The name of the user to be deleted.
-------------	-------------------------------------

Probable cause

Please check if the MobiLink user is valid and is not currently in use by other threads.

Unable to detach worker from VM

Error code	-10169
Error constant	EL_DNET_WORKER_DETACH_FAIL

Probable cause

This is an internal shutdown error. Please contact technical support.

Unable to dump exception information. Received exception while processing exception

Error code	-10119
Error constant	EL_JAVA_EXCEPTION_WHILE_PROCESSING_EXCEPTION

Probable cause

A Java script caused an exception, but MobiLink server could not display the exception information because of a subsequent exception.

Unable to enlist the database in the Distributed Transaction Coordinator

Error code	-10288
Error constant	DTC_UNABLE_TO_ENLIST_TRANS

Probable cause

The MobiLink server was not able to enlist the database in the Distributed Transaction Coordinator.

Unable to fetch from table '%1' using %2

Error code	-10071
------------	--------

Error constant	FETCH_FROM
Parameter 1	Table name.
Parameter 2	Script name.

Probable cause

A failure occurred when the MobiLink server was retrieving row(s) from the given table in the consolidated database.

Unable to find file '%1'

Error code	-10166
Error constant	EL_DNET_MDGHOST_DLL_NOT_FOUND
Parameter 1	The filename.

Probable cause

MobiLink was unable to find one of the files it needs to start .NET scripting. Please check your installation and environment variables.

Unable to find shared components directory. JRE location is not specified in options. JRE location is unknown

Error code	-10143
Error constant	EL_JAVA_COULD_NOT_FIND_JRE

Probable cause

Set the shared components environment variable or specify a JRE location using the -jrepath option.

Unable to find the JAR file: '%1' in install directory or classpath

Error code	-10142
Error constant	EL_JAVA_JAR_NOT_FOUND
Parameter 1	JAR file name.

Probable cause

Install the missing JAR file.

Unable to flush scripts

Error code	-10020
Error constant	ERROR_FLUSH_SCRIPTS

Probable cause

The MobiLink server always updates its cached scripts at the beginning of each synchronization by connecting to the consolidated database server and querying the ml_scripts_modified table. The MobiLink server encountered a problem flushing the scripts.

Unable to get the DTC transaction manager -- system error: '%1'

Error code	-10286
Error constant	DTC_UNABLE_TO_GET_TRANS_MANAGER

Probable cause

The MobiLink server was not able to get the transaction manager. Please make sure the service of the Distributed Transaction Coordinator (DTC) is running on the local computer.

Unable to initialize a distributed transaction -- system error: '%1'

Error code	-10287
Error constant	DTC_UNABLE_TO_START_TRANS

Probable cause

The MobiLink server was not able to initialize a distributed transaction. Please make sure the transaction log of the database is not full.

Unable to initialize communications stream %1: %2

Error code	-10110
------------	--------

Error constant	UNABLE_TO_CREATE_STREAM
Parameter 1	Stream number.
Parameter 2	Stream specification.

Probable cause

The given stream could not be initialized. Ensure that the stream name and stream options are valid.

Unable to initialize ODBC

Error code	-10066
Error constant	ODBC_UNABLE_TO_INITIALIZE

Probable cause

The MobiLink server was not able to initialize the ODBC layer. Please make sure that there is enough memory to start the MobiLink server and then start the MobiLink server with a recommended ODBC driver.

Unable to initialize server shared state

Error code	-10301
Error constant	SHARED_STATE_INITIALIZATION_ERROR

Probable cause

MobiLink server was unable to initialize the server shared state. Please examine your consolidated database setup.

Unable to insert into table '%1' using %2

Error code	-10072
Error constant	INSERT_INTO
Parameter 1	Table name.
Parameter 2	Script name.

Probable cause

A failure occurred when the MobiLink server was inserting row(s) into the given table in the consolidated database.

Unable to insert user name '%1' into the ml_user table

Error code	-10054
Error constant	ERROR_ADDING_USER
Parameter 1	The user name.

Probable cause

The MobiLink server was not able to add the given user into the ml_user table. Please verify that the consolidated database server is running and that the MobiLink user has permission to modify the ml_user table.

Unable to listen on port (system error %1)

Error code	-10262
Error constant	UNABLE_TO_LISTEN_ON_PORT
Parameter 1	System error.

Probable cause

Please contact technical support.

Unable to load .NET CLR Host DLL

Error code	-10165
Error constant	EL_DNET_HOST_LOAD_FAIL

Probable cause

The .NET CLR refused to load. Please use the .NET CLR utilities for logging binding and loading activity to determine the problem.

Unable to load .NET Framework CLR Version %1

Error code	-10164
Error constant	EL_DNET_CLR_LOAD_FAIL
Parameter 1	The CLR version.

Probable cause

Make sure the given CLR version is installed.

Unable to load Assembly '%1' into domain '%2'

Error code	-10193
Error constant	EL_DNET_ASM_LOAD_FAIL
Parameter 1	The assembly name.
Parameter 2	The domain name.

Probable cause

The named assembly could not be loaded. Please use the .NET CLR utilities for logging binding and loading activity to determine the problem.

Unable to load DLL or shared object %1 for stream %2: %3

Error code	-10108
Error constant	CANNOT_LOAD_DLL_FOR_STREAM
Parameter 1	The DLL or shared object name.
Parameter 2	Stream type.
Parameter 3	Stream name.

Probable cause

The given DLL or shared object could not be loaded for the given stream. Ensure the correct version of the DLL or shared object is present and in the proper location.

Unable to load DLL or shared object: %1

Error code	-10107
Error constant	CANNOT_LOAD_DLL
Parameter 1	The DLL or shared object name.

Probable cause

The given DLL or shared object could not be loaded. Ensure the correct version of the DLL or shared object is present and in the proper location.

Unable to load entry points from DLL: '%1'

Error code	-10088
Error constant	EL_UNABLE_TO_LOAD_ENTRY_POINTS
Parameter 1	The DLL or shared object name.

Probable cause

Please check your MobiLink server installation.

Unable to load the Java VM due to a memory error

Error code	-10122
Error constant	EL_JAVA_VM_MEM_ERROR

Probable cause

MobiLink server was unable to load the Java VM. Consider increasing RAM or freeing up memory by shutting down other processes.

Unable to load the Java VM due to a version error

Error code	-10121
Error constant	EL_JAVA_VM_VER_ERROR

Probable cause

MobiLink server was unable to load the Java VM. Ensure the correct Java VM is installed.

Unable to load the Java VM due to an unknown error

Error code	-10123
Error constant	EL_JAVA_VM_LOAD_ERROR

Probable cause

MobiLink server was unable to load the Java VM. The reason is likely displayed in previous output.

Unable to load the Java VM shared library. Make sure that the shared library path is set correctly and that LD_PRELOAD is set correctly and supported by your version of the dynamic loader

Error code	-10209
Error constant	EL_JAVA_VM_HP_ERROR

Probable cause

The MobiLink server was not able to load the Java VM shared library. Please make sure that the Java VM shared library is installed, the path is set correctly, and the LD_PRELOAD is set correctly and supported by your version of the dynamic loader

Unable to load UNILIB collation %1: %2

Error code	-10099
Error constant	UNABLE_TO_LOAD_CID2
Parameter 1	Unilib charset ID.
Parameter 2	Unilib error string.

Probable cause

The MobiLink server cannot initialize the Unilib converter. The installation may be damaged or the required collation is unavailable.

Unable to locate .NET Domain Configuration File '%1'

Error code	-10191
------------	--------

Error constant	EL_DNET_DOMAIN_CONFIG_FILE_MISSING
Parameter 1	The filename.

Probable cause

The domain configuration file specified could not be found. Please check the file location and configuration file setting.

Unable to maintain shared server state liveness

Error code	-10303
Error constant	SHARED_STATE_FAILED_PERFORM_LIVENESS

Probable cause

MobiLink server was unable to maintain server shared state liveness. Please check for consolidated database connectivity.

Unable to notify (system error %1)

Error code	-10275
Error constant	UNABLE_TO_NOTIFY
Parameter 1	System error.

Probable cause

Please contact technical support.

Unable to open %1

Error code	-10058
Error constant	UNABLE_TO_OPEN_TABLE_SCRIPT
Parameter 1	The script name.

Probable cause

The MobiLink server failed to execute the given table script. Please make sure that the script contains valid SQL.

Unable to open temporary file '%1'

Error code	-10212
Error constant	CANNOT_OPEN_TEMP_FILE
Parameter 1	File name.

Probable cause

The MobiLink server may use temporary files to store intermediate data. Please make sure the MobiLink server has permission to create temporary files.

Unable to parse class and method name from script: %1

Error code	-10125
Error constant	EL_JAVA_SCRIPT_FORMAT_ERROR
Parameter 1	Script name.

Probable cause

The proper format for Java synchronization scripts is 'myPackage.myClass.myMethod'.

Unable to perform a hard close on a listener socket

Error code	-10268
Error constant	UNABLE_TO_CLOSE_LISTENER_SOCKET

Probable cause

Please contact technical support.

Unable to perform a hard close on a socket '%1'

Error code	-10266
Error constant	UNABLE_TO_PERFORM_HARD_CLOSE_ON_SOCKET
Parameter 1	Socket.

Probable cause

Please contact technical support.

Unable to poll sockets (system error %1)

Error code	-10274
Error constant	UNABLE_TO_POLL_SOCKET
Parameter 1	System error.

Probable cause

Please contact technical support.

Unable to post listener deletion request to completion queue (system error %1)

Error code	-10269
Error constant	UNABLE_TO_POST_LISTENER_DELETION_REQUEST
Parameter 1	System error.

Probable cause

Please contact technical support.

Unable to post socket deletion request to completion queue (system error %1)

Error code	-10267
Error constant	UNABLE_TO_POST_SOCKET_DELETION_REQUEST
Parameter 1	System error.

Probable cause

Please contact technical support.

Unable to register the MobiLink server with name '%1'

Error code	-10294
Error constant	FARM_CANT_REGISTER
Parameter 1	Server name.

Probable cause

The MobiLink server was not able to register its server name in the MobiLink server farm. Please make sure the MobiLink server name is unique across the MobiLink server farm.

Unable to resolve host name '%1' (error: '%2')

Error code	-10283
Error constant	UNABLE_TO_RESOLVE_HOST_NAME
Parameter 1	Host name.
Parameter 2	Error number.

Probable cause

The host name specified could not be resolved. An OS-specific error number is given.

Unable to resolve script. Two methods with name: '%1' found in class: '%2'

Error code	-10152
Error constant	EL_JAVA_DUPLICATE_METHODS
Parameter 1	The method name.
Parameter 2	The class name.

Probable cause

If MobiLink is given a method name to call in a user supplied class that class must have only one method with that name. Method overloading is not supported. Please alter the class.

Unable to retry the current transaction after conflict-update with snapshot isolation in the consolidated database. The retry limit has been reached

Error code	-10246
Error constant	CANNOT_RETRY_AFTER_CONFLICT_UPDATE

Probable cause

The MobiLink server has retried the current transaction, but the conflict-update problem still occurred. Please commit all open transactions running against the consolidated database and try to run the synchronization again.

Unable to retry the current transaction after deadlock in the consolidated database. The retry limit has been reached

Error code	-10021
Error constant	CANNOT_RETRY_AFTER_DEADLOCK

Probable cause

The MobiLink server has retried the current transaction, but the deadlock problem still occurred. Please redesign your synchronization logic or use the -r MobiLink server command line option.

Unable to reuse address (system error %1)

Error code	-10273
Error constant	UNABLE_TO_REUSE_ADDRESS
Parameter 1	System error.

Probable cause

Please contact technical support.

Unable to ROLLBACK transaction: %1

Error code	-10064
Error constant	UNABLE_TO_ROLLBACK

Parameter 1	The script name.
-------------	------------------

Probable cause

The MobiLink server was not able to roll back the transaction.

Unable to send SQL Passthrough script due to an unknown script flag: '%1'

Error code	-10297
Error constant	UNKNOWN_PASSTHROUGH_SCRIPT_FLAG

Probable cause

MobiLink server found an unknown SQL Passthrough script flag for this user. Check the scripts for this user.

Unable to set transaction isolation level to snapshot

Error code	-10247
Error constant	UNABLE_TO_SET_SNAPSHOT_ISOLATION

Probable cause

The MobiLink server was not able to set the transaction isolation level to snapshot. Please make sure the userid used to connect the MobiLink server to the consolidated database has the permission to change the isolation level and the database allows snapshot isolation.

Unable to shutdown .NET scripting VM

Error code	-10180
Error constant	EL_DNET_VM_FINI_FAIL

Probable cause

MobiLink server was unable to shut down the .NET scripting VM. Shutdown actions performed by start classes may not complete properly.

Unable to shutdown .NET scripting VM. %1 workers still attached

Error code	-10181
Error constant	EL_DNET_WORKERS_NOT_DETACHED
Parameter 1	The number of worker threads.

Probable cause

MobiLink server was unable to shutdown the .NET scripting VM because there are worker threads still attached. There may be a start class that is not respecting the shutdown, or is delaying its response to the shutdown.

Unable to start accepting connections (system error %1)

Error code	-10265
Error constant	UNABLE_TO_START_ACCEPTING_CONNECT
Parameter 1	System error.

Probable cause

Please contact technical support.

Unable to start the restartable synchronization

Error code	-10255
Error constant	UNABLE_TO_RESTART_SYNC

Probable cause

The MobiLink server was unable to start the restartable synchronization requested by the client because the synchronization may already have been completed or the MobiLink server may have been restarted.

Unable to start with shared server state because no server name has been set. Use the -zs option to set a server name

Error code	-10304
------------	--------

Error constant	SHARED_STATE_SERVER_NAME_NOT_SPECIFIED
----------------	--

Probable cause

A server name must be specified when using server shared state. Use the -zs option to set the server name.

Unable to support MLSD

Error code	-10296
Error constant	MLSD_NOT_SUPPORTED

Probable cause

The MobiLink server was not able to support its system objects stored in a database other than the consolidated database, because the ODBC driver for this database server doesn't support the Microsoft Distributed Transactions. Please install the MobiLink server system objects on the consolidated database and remove the -cs option from the command line.

Unable to update SQL Passthrough script ID during SQL Passthrough repair

Error code	-10298
Error constant	UNABLE_TO_UPDATE_SQL_PASSTHROUGH_SCRIPT_ID

Probable cause

MobiLink server encountered a database error while attempting to repair a SQL Passthrough script. Examine the database error in order to find a solution.

Unable to update table '%1' using %2

Error code	-10074
Error constant	UPDATE
Parameter 1	Table name.
Parameter 2	Script name.

Probable cause

A failure occurred when the MobiLink server was updating row(s) for the given table in the consolidated database.

Unable to wait on completion port (system error %1)

Error code	-10270
Error constant	UNABLE_TO_WAIT_ON_COMPLETION_PORT
Parameter 1	System error.

Probable cause

Please contact technical support.

Unknown system parameter '%1' for script '%2'

Error code	-10227
Error constant	UNKNOWN_NAMED_SYSTEM_PARAMETER
Parameter 1	Name of unknown system parameter.
Parameter 2	Name of script.

Probable cause

The named system parameter is not in the list of valid system parameters.

Unrecognized domain id %1

Error code	-10024
Error constant	ERROR_UNSUPPORTED_DOMAIN_ID
Parameter 1	Domain ID.

Probable cause

The client-requested domain ID (datatype) is not supported. Please make sure that your MobiLink server is up-to-date.

Unrecognized event name: %1

Error code	-10207
Error constant	UNKNOWN_EVENT
Parameter 1	The name of the unrecognized event.

Probable cause

The MobiLink server only recognizes a set of connection and table events and these events are stored in the tables of ml_connection_script and ml_table_script. Please make sure all the connection and table events are valid.

Upload data for column %1 of table '%2' is invalid

Error code	-10308
Error constant	INVALID_TABLE_DATA
Parameter 1	Column index.
Parameter 2	Table name.

Probable cause

The data uploaded from the client cannot be processed, either it is out of range or cannot be translated.

Upload failed with client error %1

Error code	-10032
Error constant	UPLOAD_FAILED
Parameter 1	An error number sent by the client.

Probable cause

The MobiLink server aborted the synchronization because the client indicates there is a problem on the remote site during upload.

User name '%1' not found in the ml_user table

Error code	-10056
------------	--------

Error constant	USER_NOT_FOUND
Parameter 1	The user name.

Probable cause

The MobiLink server could not find the user from the ml_user table. Please add this user to the ml_user table using mluser or start the MobiLink server with the -zu+ option.

Version '%1' not found in the ml_script_version table. Cannot synchronize

Error code	-10013
Error constant	VERSION_NOT_FOUND
Parameter 1	Version string.

Probable cause

The client-specified version does not exist in the consolidated database. Please create a script version.

Version mismatch with DLL or shared object: '%1' Expected version: %2 got version: %3

Error code	-10087
Error constant	EL_WRONG_LANG_DLL_VERSION
Parameter 1	The DLL or shared object name.
Parameter 2	The expected version number.
Parameter 3	The supplied version number.

Probable cause

Please check your MobiLink server installation.

When using QAnywhere the only supported mode is nonblocking download ack

Error code	-10285
------------	--------

Error constant	QANYWHERE_FORCES_NONBLOCKING_MODE
----------------	-----------------------------------

Probable cause

Remove the -nba- option from the MobiLink command line.

MobiLink server warning messages

Contents

Introduction to MobiLink server warning messages	654
MobiLink server warning messages sorted by error code	655
MobiLink server warning messages sorted by message text	660

Introduction to MobiLink server warning messages

The warning messages are written to the MobiLink server message log.

Each warning is assigned a level between 1 and 5. The following table explains each level:

Level	Description
1	Server or high level ODBC warnings when a MobiLink server starts or shuts down.
2	Synchronization and user level warnings when a synchronization starts and ends.
3	Schema level (including publications and tables) warnings.
4	Script and lower level ODBC warnings.
5	Table and row level warnings.

MobiLink server warning messages sorted by error code

Error code	Level	Message text
10001	1	“Maximum number of database connections set to %1 (must be at least the number of database worker threads plus one)” on page 666
10003	1	“ODBC Isolation level (%1) is not supported” on page 668
10004	1	“ODBC function %1 is not supported by the driver” on page 668
10005	1	“ODBC statement option %1 has changed from %2 (%3) to %4 (%5)” on page 669
10006	1	“ODBC statement option %1 has changed from %2 to %3” on page 669
10007	2	“Retrying the begin_connection transaction after deadlock in the consolidated database” on page 671
10009	2	“MobiLink table '%1' is damaged” on page 667
10010	2	“No handle_error script is defined. The default action code (%1) will decide the error behavior” on page 668
10012	2	“The consolidated and remote databases disagree on when the last synchronization took place. The remote is being asked to send a new upload that starts at the last known synchronization point” on page 674
10014	4	“Expecting at most %1 parameter(s) in cursor, but found %2” on page 664
10015	3	“Table '%1' has at least one timestamp column. Due to a timestamp precision mismatch, uploaded timestamps can lose precision, defeating download filtering” on page 673
10016	3	“Table '%1' has at least one timestamp column. Due to a timestamp precision mismatch, downloaded timestamps can lose precision, resulting in inconsistent data” on page 672
10017	3	“The consolidated and remote databases have different timestamp precisions. Consolidated database timestamps are precise to %1 digit(s) in the fractional second while the remote database timestamps are precise to %2 digit(s)” on page 675

Error code	Level	Message text
10018	3	“Resolve the timestamp precision mismatch by setting the SQL Anywhere DE-Fault_TIMESTAMP_INCREMENT option on the remote database to %1 and TRUNCATE_TIMESTAMP_VALUES to 'On'. UltraLite remotes must set the TIMESTAMP_INCREMENT option to %1” on page 670
10019	3	“The remote database is not capable of matching the timestamp precision of the consolidated database. Your application, schema, and scripts must contain logic that copes with the precision mismatch” on page 676
10020	3	“The timestamp precision mismatch may affect upload conflict detection. Use the -zp option to cause the MobiLink server to use the lowest timestamp precision for conflict detection purposes” on page 677
10021	3	“The remote and consolidated databases have different timestamp precisions, and a timestamp value with a precision higher than the lower-precision side was used for conflict detection purposes. Consider using the -zp option” on page 676
10022	3	“Publication '%1' is not referenced by any table” on page 670
10023	3	“The upload will be rolled back and the synchronization aborted. The next time this remote synchronizes, it will ask what happened to the previous upload” on page 678
10024	3	“Table '%1' has no entry in the ml_table table” on page 673
10032	2	“Unable to open the file to store the client synchronization logs. The filename is '%1'” on page 681
10033	2	“An error occurred reading the remote client's synchronization log” on page 663
10034	2	“Unable to write to the local file that contains remote synchronization logs” on page 681
10035	2	“The remote client's synchronization log ended prematurely, and was probably truncated” on page 676
10036	2	“Client synchronization logs will be shown in the MobiLink server message log file or the MobiLink server messages window” on page 663
10037	5	“Ignoring updated row (new values)” on page 664
10038	5	“Ignoring updated row (old values)” on page 665
10039	2	“Error detected during multi-row operation, performing rollback before retrying in single row mode” on page 663

Error code	Level	Message text
10040	2	“%1 row(s) were ignored in uploading data into table %2” on page 660
10041	2	“The upload will be committed and the synchronization aborted. The next time this remote synchronizes, it will ask what happened to the previous upload” on page 678
10043	4	“Unable to determine current timestamp from consolidated database” on page 680
10044	5	“A row in table '%1' could not be updated because it no longer exists in the consolidated database” on page 661
10045	2	“Retrying the upload after deadlock in the consolidated database” on page 672
10048	2	“Retrying the begin_synchronization transaction after deadlock in the consolidated database” on page 671
10049	2	“Retrying the end_synchronization transaction after deadlock in the consolidated database” on page 671
10050	4	“%1” on page 660
10051	1	“Unrecognized ODBC driver '%1'. The functionality and quality of ODBC drivers varies greatly. This driver may lack functionality required for successful synchronizations. Use at your own risk” on page 682
10055	2	“The client has provided %1 authentication parameter(s), but no authenticate_parameters script exists” on page 673
10056	4	“There is no download data script defined for table: %1. Synchronization has the risk of potentially losing download data” on page 678
10057	4	“There is no upload data script defined for table: %1. Synchronization has the risk of potentially losing upload data” on page 679
10064	1	“Unknown users will be added automatically (when there is no authenticate_user script)” on page 682
10066	1	“mlstop will not be able to stop this server” on page 666
10068	5	“%1” on page 660
10069	5	“All insert rows for table '%1' will be ignored because there is no upload_insert script for this table” on page 662
10070	5	“All update rows for table '%1' will be ignored because there is no upload_update script for this table” on page 662

Error code	Level	Message text
10071	5	“All delete rows for table '%1' will be ignored because there is no upload_delete script for this table” on page 662
10072	5	“The update row for table '%1' is a conflict update and this row is ignored” on page 677
10073	1	“Windows XP Firewall is enabled, and the MobiLink server is not in the exception list. Clients on remote machines may not be able to connect to this server” on page 682
10074	4	“Unable to fetch the download timestamp from the consolidated database” on page 680
10075	1	“Unable to access ORACLE table 'v_\$transaction'. Access is needed in order to ensure no data is missed if using timestamp-based downloads” on page 680
10076	5	“A conflict detection script is defined for table '%1', but there is no conflict resolution script” on page 661
10077	1	“You are using a DSN created using an out-of-date ODBC driver '%1'. Please use a DSN created with a recommended driver described at http://www.sybase.com/detail?id=1011880 ” on page 683
10078	1	“Unable to access Microsoft SQL Server virtual table 'sys.dm_tran_active_transactions'. The MobiLink server will not use snapshot isolation” on page 679
10079	1	“The command line option '%1' is ignored” on page 674
10080	5	“Retrying the upload after conflicting update in the consolidated database” on page 671
10081	3	“Unable to retrieve the column data types for table '%1' from the consolidated database” on page 681
10082	1	“MobiLink server has swapped data pages to disk out:%1 in:%2 concurrently used pages:%3” on page 667
10083	1	“MobiLink server has suspended network reads on this synchronization due to a limit on concurrent synchronizations” on page 666
10084	1	“MobiLink server restarted network reads on this synchronization due to a drop in the number of concurrent synchronizations” on page 667
10085	1	“For table '%1', the number of entries in the ml_column table is greater than the number of columns in the remote table” on page 664

Error code	Level	Message text
10086	1	“The ODBC driver '%1' is deprecated” on page 675
10087	1	“Unable to access ASE table 'master..systransactions'. The MobiLink server will use system time for download” on page 679
10088	5	“The current SQL statement has been running for too long in the consolidated database. The connection ID is %1” on page 675
10089	1	“Performance warning -- database connections have been recycled at a rate of %1%” on page 669
10090	1	“Invalid liveness value '%1' -- the minimum value is '%2'. Now the MobiLink server uses the default value '%2'” on page 665
10091	2	“A passthrough script failed at the remote client. run_order:'%1' script_id:'%2' error_code:'%3' error_text:'%4'” on page 661
10092	2	“Invalid log verbosity options: '%1'” on page 665

MobiLink server warning messages sorted by message text

%1

Error code	10050
Error constant	WARN_SQL_SUCCESS_WITH_INFO
Parameter 1	A message from the ODBC driver.

Probable cause

The MobiLink server made a successful ODBC call, but the ODBC driver displayed a warning message. Avoiding this message depends on the specific warning.

%1 row(s) were ignored in uploading data into table %2

Error code	10040
Error constant	IGNORED_ROWS_FOR_TABLE
Parameter 1	The total number of ignored rows.
Parameter 2	Table name.

Probable cause

The MobiLink server counts all the upload rows that were not applied to the consolidated database as ignored rows. This can happen if there are upload inserts/updates/deletes from the client, but there is no upload_insert/upload_update/upload_delete script for the listed table in the consolidated database or errors occurred during uploading data into this table, but the handle_error/handle_odbc_error returned 1000.

'%1'

Error code	10068
Error constant	EL_DNET_WRITE_STREAM_WARNING
Parameter 1	A warning message.

Probable cause

Warning messages generated by .Net CLR.

A conflict detection script is defined for table '%1', but there is no conflict resolution script

Error code	10076
Error constant	NO_CONFLICT_RESOLVE_SCRIPT
Parameter 1	Table name.

Probable cause

MobiLink server will not invoke the conflict detection script for a given table, if there is no conflict resolution script for this table. Please define conflict resolution scripts or remove the conflict detection script for this table.

A passthrough script failed at the remote client. run_order:'%1' script_id:'%2' error_code:'%3' error_text:'%4'

Error code	10091
Error constant	PASSTHROUGH_SCRIPT_FAILED
Parameter 1	The run_order of the failed passthrough script.
Parameter 2	The script_id of the failed passthrough script.
Parameter 3	The error_code of the failed passthrough script.
Parameter 4	The error_text of the failed passthrough script.

Probable cause

Examine the error code and text and create a repair action for this script.

A row in table '%1' could not be updated because it no longer exists in the consolidated database

Error code	10044
Error constant	UPDATE_NO_ROW
Parameter 1	Table name.

Probable cause

An update statement failed because the table in the consolidated database doesn't contain the original row.

All delete rows for table '%1' will be ignored because there is no upload_delete script for this table

Error code	10071
Error constant	NO_SCRIPT_IGNORE_DELETE
Parameter 1	Table name.

Probable cause

The MobiLink server will issue this warning message, if the client sends delete rows for the given table, but there is no corresponding upload_delete script defined in the consolidated database.

All insert rows for table '%1' will be ignored because there is no upload_insert script for this table

Error code	10069
Error constant	NO_SCRIPT_IGNORE_INSERT
Parameter 1	Table name.

Probable cause

The MobiLink server will issue this warning message, if the client sends insert rows for the given table, but there is no corresponding upload_insert script defined in the consolidated database.

All update rows for table '%1' will be ignored because there is no upload_update script for this table

Error code	10070
Error constant	NO_SCRIPT_IGNORE_UPDATE
Parameter 1	Table name.

Probable cause

The MobiLink server will issue this warning message, if the client sends update rows for the given table, but there is no corresponding upload_update script defined in the consolidated database.

An error occurred reading the remote client's synchronization log

Error code	10033
Error constant	ERROR_READING_ERROR_LOG

Probable cause

The MobiLink server was unable to get the remote error log from the client. To avoid this warning, please do not kill the client when it is running and also make sure the network connection is okay.

Client synchronization logs will be shown in the MobiLink server message log file or the MobiLink server messages window

Error code	10036
Error constant	ERROR_LOG_TO_OUTPUT_LOG

Probable cause

If an error occurs on the client side during synchronization, the client may send its output file to the server and the server will store this output file to a file specified using the server command line option -e or -et. However, if the MobiLink server could not open this file for writing, it will show this warning message and will write the remote log into its message log file or messages window. To avoid this warning, please make sure the MobiLink server has the privilege to write the file.

Error detected during multi-row operation, performing rollback before retrying in single row mode

Error code	10039
Error constant	RETRY_AFTER_MULTIPLE_ROW

Probable cause

Errors were detected when the MobiLink server applied the upload stream using multi-row mode. It will roll back the upload stream and retry the upload transaction in single-row mode.

Expecting at most %1 parameter(s) in cursor, but found %2

Error code	10014
Error constant	ODBC_EXTRA_PARAMETERS
Parameter 1	The maximum number of parameter(s) expected.
Parameter 2	The number of parameter(s) found.

Probable cause

There is a maximum number of parameters for every cursor script in the MobiLink server. If the number of parameters for the given cursor script is larger than the maximum number of parameters, the server will show this warning.

For table '%1', the number of entries in the ml_column table is greater than the number of columns in the remote table

Error code	10085
Error constant	TOO_MANY_ML_COLUMN_ENTRIES
Parameter 1	Table name.

Probable cause

This warning tells you that you have extra column entries in the ml_column table for the given table. This is only a problem if (i) your synchronization scripts reference the column names via named parameters, and (ii) they reference a column name whose index is greater than the number of columns in the table. In this case, an error will be issued after this warning.

Ignoring updated row (new values)

Error code	10037
Error constant	IGNORING_UPDATED_ROW_NEW_VALUES

Probable cause

There is a conflict-update, but there is no upload_new_row_insert script defined in the consolidated database for the table.

Ignoring updated row (old values)

Error code	10038
Error constant	IGNORING_UPDATED_ROW_OLD_VALUES

Probable cause

There is a conflict-update, but there is no upload_old_row_insert script defined in the consolidated database for the table.

Invalid liveness value '%1' -- the minimum value is '%2'. Now the MobiLink server uses the default value '%2'

Error code	10090
Error constant	INVALID_LIVENESS
Parameter 1	Liveness value in the ml_property table.
Parameter 2	Acceptable minimum liveness value.
Parameter 3	Default liveness value.

Probable cause

The MobiLink server retrieves the liveness value from the ml_property table and this value must be greater than or equal to a certain value. If this value is too small, it may degrade the server performance, then the server will use the default liveness value.

Invalid log verbosity options: '%1'

Error code	10092
Error constant	INVALID_LOG_VERBOSITY
Parameter 1	Verbosity options.

Probable cause

The log verbosity options in the ml_property table are not valid. The valid verbosity options can be found from the MobiLink server usage window.

Maximum number of database connections set to %1 (must be at least the number of database worker threads plus one)

Error code	10001
Error constant	MAX_DB_CONNECTIONS_SET_TO
Parameter 1	Maximum number of connections.

Probable cause

The MobiLink server makes one connection for each database worker thread and an extra connection for managing state. Therefore, the maximum number of connections must be at least the number of database worker threads plus one.

mlstop will not be able to stop this server

Error code	10066
Error constant	NO_DBMLSTOP

Probable cause

The MobiLink server cannot be stopped by mlstop because another server with the same name is currently running.

MobiLink server has suspended network reads on this synchronization due to a limit on concurrent synchronizations

Error code	10083
Error constant	PLACED_SYNCHRONIZATION_IN_BACKLOG

Probable cause

The MobiLink server will suspend any new synchronization connections when the maximum number of concurrent synchronizations has been exceeded. This limit is set using the -sm option.

MobiLink server has swapped data pages to disk out:%1 in:%2 concurrently used pages:%3

Error code	10082
Error constant	SWAPPED_LOTS_OF_PAGES
Parameter 1	Total count of pages swapped out.
Parameter 2	Total count of pages swapped in.
Parameter 3	Count of concurrently used disk pages.

Probable cause

The MobiLink server may write data out to disk that can not fit in its cache memory. The server prints warning message to the log when this happens so that the user may determine if this is a performance problem. The -cm option controls the server cache memory size.

MobiLink server restarted network reads on this synchronization due to a drop in the number of concurrent synchronizations

Error code	10084
Error constant	RESTARTED_SYNCHRONIZATION_IN_BACKLOG

Probable cause

The MobiLink server will restart reads on a synchronization that was stopped due to a limit on concurrent synchronizations. This limit is set using the -sm option.

MobiLink table '%1' is damaged

Error code	10009
Error constant	TABLE_DAMAGED
Parameter 1	The MobiLink system table name.

Probable cause

The MobiLink server was unable to get information from the listed table. Please make sure the table does exist and the database server is running.

No handle_error script is defined. The default action code (%1) will decide the error behavior

Error code	10010
Error constant	NO_ERROR_HANDLER
Parameter 1	The error action code.

Probable cause

An error occurred in the MobiLink server during synchronization. However there is no handle_error script defined in the consolidated database. The server will take the default action for the error. To avoid this warning, please define a handle_error script.

ODBC function %1 is not supported by the driver

Error code	10004
Error constant	ODBC_MISSING_FUNCTION
Parameter 1	ODBC function name.

Probable cause

This function is required for the MobiLink server to operate. Update your ODBC driver.

ODBC Isolation level (%1) is not supported

Error code	10003
Error constant	ODBC_MISSING_REQUIRED_ISOLATION_LEVEL
Parameter 1	The required isolation level.

Probable cause

The required isolation level is not supported by the consolidated database. Determine if another level is suitable.

ODBC statement option %1 has changed from %2 (%3) to %4 (%5)

Error code	10005
Error constant	OPTION_CHANGED_1
Parameter 1	Name of the ODBC statement option.
Parameter 2	Original name of the setting.
Parameter 3	Original value of the setting.
Parameter 4	New name of the setting.
Parameter 5	New value of the setting.

Probable cause

The option has been changed by the ODBC driver. This may not be desirable.

ODBC statement option %1 has changed from %2 to %3

Error code	10006
Error constant	OPTION_CHANGED_2
Parameter 1	Name of the ODBC statement option.
Parameter 2	Original value of the setting.
Parameter 3	New value of the setting.

Probable cause

The option has been changed by the ODBC driver. This may not be desirable.

Performance warning -- database connections have been recycled at a rate of %1%%

Error code	10089
Error constant	CONN_THRASHING
Parameter 1	Connection recycle rate.

Probable cause

The MobiLink server maintains a pool of connections to the consolidated database to improve performance. Each pooled connection is associated with a script version. If the pool is full and there are no connection available for the requested version, then a pooled connection will be reconnected to get the required version. Please see the -cn switch for more information.

Publication '%1' is not referenced by any table

Error code	10022
Error constant	WARN_PUB_NO_TABLE
Parameter 1	Publication name.

Probable cause

The MobiLink synchronization client sends an upload stream that includes upload data as well as upload tables, publications, and so on. All these publications must be referenced by at least one of the upload tables. If there are any publications that are not referenced by any upload table, the server will show this warning. If this happens, please contact technical support.

Resolve the timestamp precision mismatch by setting the SQL Anywhere DEFAULT_TIMESTAMP_INCREMENT option on the remote database to %1 and TRUNCATE_TIMESTAMP_VALUES to 'On'. UltraLite remotes must set the TIMESTAMP_INCREMENT option to %1

Error code	10018
Error constant	REMOTE_MAY_MATCH_CONSOLIDATE_TIMESTAMP_PRECISION
Parameter 1	Timestamp precision of the consolidated database in terms of number of decimal digits in the fractional second.

Probable cause

This is an advisory on how to align timestamp precision by adjusting timestamp precision on the SQL Anywhere client database or the SQL Anywhere reference database for UltraLite clients. UltraLite clients need to be regenerated after the precision is adjusted.

Retrying the begin_connection transaction after deadlock in the consolidated database

Error code	10007
Error constant	RETRY_BC_AFTER_DEADLOCK

Probable cause

Deadlock occurred in the transaction of begin_transaction in the consolidated database. To avoid this warning, please rewrite your begin_connection script to avoid deadlocks.

Retrying the begin_synchronization transaction after deadlock in the consolidated database

Error code	10048
Error constant	RETRY_BS_AFTER_DEADLOCK

Probable cause

Deadlock occurred when the MobiLink server executed the begin_synchronization script. It will roll back the transaction and retry this script.

Retrying the end_synchronization transaction after deadlock in the consolidated database

Error code	10049
Error constant	RETRY_ES_AFTER_DEADLOCK

Probable cause

Deadlock occurred when the MobiLink server executed the end_synchronization script. It will roll back the transaction and retry this script.

Retrying the upload after conflicting update in the consolidated database

Error code	10080
Error constant	RETRY_AFTER_CONFLICT_UPDATE

Probable cause

A conflicting update occurred when the MobiLink server was applying the upload stream with snapshot isolation. It will roll back the transaction and retry this script. To avoid this warning, please commit all the open transactions in all other applications that are connecting to this consolidated database.

Retrying the upload after deadlock in the consolidated database

Error code	10045
Error constant	RETRY_AFTER_DEADLOCK

Probable cause

Deadlock occurred when the MobiLink server was applying the upload stream. It will roll back the transaction and retry this script. Avoid this warning by removing contention between synchronization scripts. There can also be contention between synchronization scripts and other applications.

Table '%1' has at least one timestamp column. Due to a timestamp precision mismatch, downloaded timestamps can lose precision, resulting in inconsistent data

Error code	10016
Error constant	LOSING_DOWNLOAD_TIMESTAMP_PRECISION
Parameter 1	Table name.

Probable cause

A remote database is synchronizing a table with at least one timestamp column while the timestamp precision of the remote database is lower than that of the consolidated database. The downloaded value will lose precision after being stored into the remote database. This situation creates a virtual difference in the synchronized timestamp data between the consolidated database and the remote database. To avoid this data inconsistency problem, you should align timestamp precision across all databases involved in your synchronization system.

Table '%1' has at least one timestamp column. Due to a timestamp precision mismatch, uploaded timestamps can lose precision, defeating download filtering

Error code	10015
Error constant	LOSING_UPLOAD_TIMESTAMP_PRECISION
Parameter 1	Table name.

Probable cause

A remote database is synchronizing a table with at least one timestamp column while the timestamp precision on the remote database is higher than that of the consolidated database. The uploaded value will lose precision after being stored in the consolidated database. The MobiLink server compares upload rows and download rows in order to filter away redundant download rows. The loss of precision may create a virtual difference that defeats the download filtering. This situation can affect download performance. To avoid this performance penalty, you should align timestamp precision across all databases involved in your synchronization system.

Table '%1' has no entry in the ml_table table

Error code	10024
Error constant	TABLE_NO_ENTRY
Parameter 1	Table name.

Probable cause

The tables ml_table, ml_table_script, ml_script contain the scripts for every table that participates in synchronization. The MobiLink server will show this warning for all the synchronization tables that have no script or that have no entry in the table ml_table.

The client has provided %1 authentication parameter(s), but no authenticate_parameters script exists

Error code	10055
Error constant	NO_AUTH_PARMS_SCRIPT
Parameter 1	The number of authentication parameter(s).

Probable cause

The MobiLink synchronization client sent the listed number of authentication parameters. However, there is no authentication parameter script defined in the consolidated database. To avoid this warning, please define the authenticate_parameters script in the consolidated database or do not send authentication parameter(s) from the client.

The command line option '%1' is ignored

Error code	10079
Error constant	CMD_SWITCH_IGNORED
Parameter 1	Command line option.

Probable cause

The command line option is ignored by the MobiLink server. Please make sure if the command line option can be applied.

The consolidated and remote databases disagree on when the last synchronization took place. The remote is being asked to send a new upload that starts at the last known synchronization point

Error code	10012
Error constant	TXN_LOG_COOKIE_MISMATCH

Probable cause

The MobiLink server stores the remote ending log offsets in its system tables after every synchronization and it compares these ending log offsets with the remote beginning offsets when a new synchronization comes in. If the ending offsets do not match the beginning offsets, the server will show this warning and also inform the client about the mismatching offsets.

The consolidated and remote databases have different timestamp precisions. Consolidated database timestamps are precise to %1 digit(s) in the fractional second while the remote database timestamps are precise to %2 digit(s)

Error code	10017
Error constant	LOSING_TIMESTAMP_PRECISION
Parameter 1	Timestamp precision of the consolidated database in terms of number of decimal digits in the fractional second.
Parameter 2	Timestamp precision of the remote database in terms of number of decimal digits in the fractional second.

Probable cause

Inconsistent timestamp precisions were found between the remote database and the consolidated database. Align the databases to the same precision to avoid a performance penalty or inconsistent data.

The current SQL statement has been running for too long in the consolidated database. The connection ID is %1

Error code	10088
Error constant	SQL_STMT_TIMEOUT

Probable cause

The MobiLink server has detected the SQL statement has been running for too long and the synchronization may be stuck. Please check the consolidated database server to see if the connection is still healthy

The ODBC driver '%1' is deprecated

Error code	10086
Error constant	DD_DRIVER_IS_DEPRECATED
Parameter 1	ODBC driver name.

Probable cause

This ODBC driver is deprecated and its support may be removed from the MobiLink server in future releases. Please check the manual to find an appropriate ODBC driver supported by the MobiLink server.

The remote and consolidated databases have different timestamp precisions, and a timestamp value with a precision higher than the lower-precision side was used for conflict detection purposes. Consider using the -zp option

Error code	10021
Error constant	SUSPICIOUS_TIMESTAMP_DIFFERENCE

Probable cause

An upload conflict is detected based on a tolerable timestamp difference while the -zp command line option is not used. If you decided not to align precision on the databases involved in your synchronization system, you may use the -zp switch to start the MobiLink server. If the command line option is used, MobiLink server will tolerate conflict caused by timestamp differences smaller than the lower precision among the two databases.

The remote client's synchronization log ended prematurely, and was probably truncated

Error code	10035
Error constant	ERROR_LOG_TRUNCATED

Probable cause

The MobiLink server was not able to completely get the remote error log from the client, so the remote error log may have been truncated. To avoid this warning, please do not kill the client when it is running and also make sure the network connection is okay.

The remote database is not capable of matching the timestamp precision of the consolidated database. Your application, schema, and scripts must contain logic that copes with the precision mismatch

Error code	10019
Error constant	REMOTE_CANNOT_MATCH_CONSOLIDATE_TIMESTAMP_PRECISION

Probable cause

Timestamp precision of the consolidated database is found to be higher than attainable by the remote database. If possible you may lower the timestamp precision on the consolidated database in order to avoid inconsistent timestamp data between the remote and the consolidated database. Otherwise, you may need to avoid synchronizing timestamps in your synchronization schema; or you may need to have conflict detection scripts aware of the virtual difference; or you may need to use the `-zp` command line option to tolerate the conflict. Your application should also be able to deal with the inconsistency.

The timestamp precision mismatch may affect upload conflict detection. Use the `-zp` option to cause the MobiLink server to use the lowest timestamp precision for conflict detection purposes

Error code	10020
Error constant	MAY_USE_AUTO_TIMESTAMP_TOLERANCE

Probable cause

Timestamp precision mismatch between the remote database and the consolidated database has been detected. The mismatch can affect upload conflict detection as the MobiLink server will compare the rows for the two databases. If you decided not to align precision on the databases involved in your synchronization system, you may use the `-zp` switch to start the MobiLink server. If this command line option is used, the MobiLink server will tolerate conflict caused by timestamp differences smaller than the lower precision among the two databases.

The update row for table '%1' is a conflict update and this row is ignored

Error code	10072
Error constant	NO_CONFLICT_SCRIPT_IGNORE_UPDATE
Parameter 1	Table name.

Probable cause

A conflict-update has occurred, but there is no conflict resolution script defined for this table.

The upload will be committed and the synchronization aborted. The next time this remote synchronizes, it will ask what happened to the previous upload

Error code	10041
Error constant	LOSE_COMMITTED_UPLOAD

Probable cause

This is an internal warning that is primarily used for testing, but may also be seen as part of technical support engagements.

The upload will be rolled back and the synchronization aborted. The next time this remote synchronizes, it will ask what happened to the previous upload

Error code	10023
Error constant	LOSE_UPLOAD

Probable cause

This is an internal warning that is primarily used for testing, but may also be seen as part of technical support engagements.

There is no download data script defined for table: %1. Synchronization has the risk of potentially losing download data

Error code	10056
Error constant	WARN_NO_DOWNLOAD_DATA_SCRIPT
Parameter 1	Table name.

Probable cause

The listed table is involved in a download-only synchronization. However, there is no download script for this table in the consolidated database. To avoid this warning, please define download script(s) for this table in the consolidated database, or always do full synchronization.

There is no upload data script defined for table: %1. Synchronization has the risk of potentially losing upload data

Error code	10057
Error constant	WARN_NO_UPLOAD_DATA_SCRIPT
Parameter 1	Table name.

Probable cause

The listed table is involved in the synchronization and there are some changes to this table in the remote data. However, there is no upload script for this table in the dbmlsync consolidated database. To avoid this warning, please define upload script(s) for this table in the consolidated database, or do not make any changes in the remote database using any other application except the MobiLink synchronization client.

Unable to access ASE table 'master..systransactions'. The MobiLink server will use system time for download

Error code	10087
Error constant	ASE_ACCESS_MASTER_PERMISSION

Probable cause

The MobiLink server needs to access some tables in the master database in order to get transaction starting time during synchronization. Please make sure the userid used to connect the MobiLink server to the Microsoft SQL Server has permission to access the 'master..systransactions' table.

Unable to access Microsoft SQL Server virtual table 'sys.dm_tran_active_transactions'. The MobiLink server will not use snapshot isolation

Error code	10078
Error constant	MSS_SNAPSHOT_PERMISSION

Probable cause

The MobiLink server needs to access some virtual tables in order to use snapshot isolation during synchronization. Please make sure the userid used to connect the MobiLink server to the Microsoft SQL Server has permission to access the 'sys.dm_tran_active_transactions' table.

Unable to access ORACLE table 'v_\$transaction'. Access is needed in order to ensure no data is missed if using timestamp-based downloads

Error code	10075
Error constant	ORACLE_VTXN_PERMISSION

Probable cause

The timestamp generated to filter the download may be incorrect due to ORACLE's non-blocking read feature. Please make sure the userid used to connect the MobiLink server to the ORACLE database has permission to access the v_\$transaction table.

Unable to determine current timestamp from consolidated database

Error code	10043
Error constant	ODBC_UNABLE_TO_GET_TIMESTAMP

Probable cause

The MobiLink server was not able to get the current timestamp from the consolidated database. Please make sure the database server is running and the network connection is okay.

Unable to fetch the download timestamp from the consolidated database

Error code	10074
Error constant	ODBC_UNABLE_TO_GET_DOWNLOAD_TIMESTAMP

Probable cause

The MobiLink server was unable to get the download timestamp from the consolidated database. Please make sure the database server is running and the network connection is okay.

Unable to open the file to store the client synchronization logs. The filename is '%1'

Error code	10032
Error constant	ERROR_OPENING_ERROR_LOG
Parameter 1	File name.

Probable cause

The MobiLink server was unable to open the local remote log file given by option -e or -et. Please make sure the file name and path are valid and the file is writable.

Unable to retrieve the column data types for table '%1' from the consolidated database

Error code	10081
Error constant	UNABLE_TO_RETRIEVE_DATA_TYPES
Parameter 1	Table name.

Probable cause

The MobiLink server was not able to retrieve the column data types for the given table from the consolidated database using SQLDescribeParam. Therefore the server will assume that the data types for this table in the consolidated database are equivalent to those defined in the remote database.

Unable to write to the local file that contains remote synchronization logs

Error code	10034
Error constant	ERROR_WRITING_ERROR_LOG

Probable cause

The MobiLink server was unable to write the remote error log to a local file. To avoid this warning, please make sure the file name and path given by option -e or -et are valid and the file is writable.

Unknown users will be added automatically (when there is no authenticate_user script)

Error code	10064
Error constant	REPORT_AUTO_ADD_USERS

Probable cause

This is a friendly warning message when the MobiLink server command line option, -zu+ is used.

Unrecognized ODBC driver '%1'. The functionality and quality of ODBC drivers varies greatly. This driver may lack functionality required for successful synchronizations. Use at your own risk

Error code	10051
Error constant	DRIVER_IS_NOT_RECOMMENDED
Parameter 1	The file name of an ODBC driver.

Probable cause

The MobiLink server is very well tested with a set of ODBC drivers. However, the ODBC driver you are currently using is not on the list. To avoid this warning, please run the MobiLink server with a recommended ODBC driver.

Windows XP Firewall is enabled, and the MobiLink server is not in the exception list. Clients on remote machines may not be able to connect to this server

Error code	10073
Error constant	XP_FIREWALL_ENABLED

Probable cause

The Windows XP Firewall is enabled and either the MobiLink server is not in the exception list or it is in the exception list but disabled. This configuration will prevent remote clients from connecting to the server.

You are using a DSN created using an out-of-date ODBC driver '%1'. Please use a DSN created with a recommended driver described at <http://www.sybase.com/detail?id=1011880>

Error code	10077
Error constant	DRIVER_IS_OUT_OF_DATE
Parameter 1	Driver name.

Probable cause

You are using an out-of-date ODBC driver. Using an out-of-date ODBC driver may lack some new functionality and bug fixes. Please use a latest recommended driver

MobiLink communication error messages

Contents

Introduction to MobiLink communication error messages	686
MobiLink communication error messages sorted by error code	687
MobiLink communication error messages sorted by error constant	694
MobiLink communication error messages sorted by message text	702

Introduction to MobiLink communication error messages

The error messages are written to the MobiLink server message log and the MobiLink SQL Anywhere client message log. The error codes are returned to UltraLite clients in the **ss_error_code** member of the **stream_error** parameter.

MobiLink communication error messages sorted by error code

Error code	Message text
0	“No error or unknown error” on page 716
1	“Invalid parameter '%1'” on page 712
2	“Parameter value '%1' is not an unsigned integer” on page 719
3	“Parameter value '%1' is not an unsigned integer value or range. A range has the form NNN-NNN” on page 718
4	“Parameter value '%1' is not a valid boolean value. The value must be 0 or 1” on page 718
5	“Parameter value '%1' is not a valid hexadecimal value” on page 718
6	“Unable to allocate sufficient memory” on page 724
7	“Unable to parse the parameter string '%1'” on page 733
8	“Unable to read %1 bytes” on page 733
9	“Unable to write %1 bytes” on page 737
10	“An end write failed” on page 704
11	“An end read failed” on page 703
12	“Feature not implemented” on page 708
13	“The operation would cause blocking” on page 721
14	“Unable to generate a random number” on page 729
15	“Unable to initialize the random number generator” on page 731
16	“Unable to seed the random number generator” on page 735
17	“Unable to create a random number object” on page 726
18	“An error occurred during shutdown” on page 704
19	“Unable to dequeue from the connection queue” on page 728
20	“Invalid root certificate” on page 713

Error code	Message text
21	“Unrecognized organization '%1’” on page 740
24	“Server certificate not trusted” on page 720
25	“Unable to duplicate security context” on page 728
26	“Unable to attach the network layer to the security layer” on page 724
33	“Unable to open certificate file '%1’” on page 732
34	“Unable to read certificates” on page 734
35	“Unable to read the private key” on page 735
36	“Unable to set the private key” on page 736
37	“Unable to fetch a certificate expiry date” on page 728
38	“Unable to copy a certificate” on page 726
39	“Unable to add a certificate to a certificate chain” on page 723
40	“Unable to find the trusted certificate file '%1’” on page 729
41	“Error reading from the trusted certificate file '%1’” on page 706
42	“No trusted certificates found in %1” on page 717
43	“Unable to allocate a certificate” on page 724
44	“Unable to import a certificate” on page 730
48	“Unable to add a trusted certificate” on page 724
49	“Unable to create a private key object” on page 726
50	“A certificate has expired” on page 702
51	“Unrecognized organization unit '%1’” on page 740
52	“Unrecognized common name '%1’” on page 739
53	“Handshake error” on page 709
54	“Unsupported HTTP version: %1” on page 741
57	“The host name '%1' could not be found” on page 721

Error code	Message text
58	“Unable to create a TCP/IP socket” on page 727
59	“Unable to create a UDP socket” on page 727
60	“Unable to bind a socket to port %1” on page 725
61	“Unable to clean up the socket layer” on page 725
62	“Unable to close a socket” on page 725
63	“Unable to connect a socket” on page 726
64	“Unable to get a socket's local name” on page 729
65	“Unable to get socket option number %1” on page 730
66	“Unable to set socket option number %1” on page 736
67	“Unable to listen on a socket. The backlog is %1” on page 731
68	“Unable to shut down a socket” on page 736
69	“Unable to select a socket status” on page 735
70	“Unable to initialize the sockets layer” on page 731
71	“Unable to determine localhost” on page 728
72	“Unable to get host by address” on page 730
73	“Unable to load the network interface library” on page 732
74	“Invalid port number %1. The value must be between zero and 65535” on page 713
75	“ActiveSync synchronization cannot be initiated by an application” on page 703
76	“ActiveSync provider has not been installed” on page 703
77	“The content type '%1' is unknown” on page 720
78	“Client id is not available for use in HTTP header” on page 705
79	“The HTTP buffer size specified is out of the valid range” on page 721
80	“Extra data found in the HTTP body: %1” on page 707
81	“Failed to read encoded CR LF” on page 708

Error code	Message text
82	“Failed to read CR LF” on page 708
83	“Timed out while waiting for the next HTTP request in this synchronization” on page 723
84	“Failed to read encoded chunk length” on page 708
85	“An unexpected character was read while parsing the chunk length. %1” on page 704
86	“An error status was returned: %1” on page 704
87	“Unknown transfer encoding: %1” on page 739
88	“Unable to parse cookie: %1” on page 733
89	“Expected data from remote but current request is not a POST” on page 706
200	“Invalid liveness timeout value %1. The value must be between zero and 65535” on page 712
201	“Timed out trying to read %1 bytes” on page 722
202	“Timed out trying to write %1 bytes” on page 723
203	“Automatic dialup is not supported on this machine” on page 705
204	“Failed dialing to %1” on page 707
205	“No server certificate was provided” on page 717
206	“No server certificate password was provided” on page 716
207	“No trusted root certificates were provided” on page 717
208	“Password specified for an unencrypted server key” on page 719
209	“A userid and password are required for HTTP authentication” on page 702
210	“A userid and password are required for HTTP proxy authentication” on page 702
211	“HTTP Authentication failed” on page 709
212	“HTTP Proxy Authentication failed” on page 709
213	“No userid was supplied” on page 717
214	“No password was supplied” on page 716

Error code	Message text
215	“Unsupported http authentication algorithm: %1” on page 741
216	“Error parsing HTTP header: %1” on page 706
217	“HTTP server authentication failed” on page 710
218	“Operation interrupted” on page 718
219	“Invalid HTTP character” on page 711
220	“Internal error (%1)” on page 710
221	“Failed to open system certificate store” on page 708
222	“Failed to import a certificate from the system certificate store” on page 707
223	“No certificate found in system certificate store” on page 716
224	“Failed to load library %1” on page 707
225	“Function %1 could not be found” on page 709
226	“Invalid synchronization protocol: %1” on page 713
227	“Internal protocol not loaded: %1” on page 711
228	“Server error %1” on page 720
229	“Missing parameter: %1” on page 715
230	“Could not open %1 for write” on page 705
231	“Protocol error” on page 719
232	“Invalid compression type: %1” on page 711
233	“The value specified for %1 is out of range” on page 722
234	“Unexpected request type: %1” on page 738
235	“Malformed session cookie (ML_SESSION_ID) value: %1” on page 714
236	“Unexpected HTTP state %1 when decoding the header” on page 737
237	“Unexpected internal HTTP request type %1” on page 737
238	“Internal error: %1 returned %2” on page 710

Error code	Message text
239	“ECC encryption is not FIPS-compliant” on page 706
240	“Unrecognized TLS type %1” on page 740
241	“Connection attempt timed out” on page 705
242	“A secure stream has FIPS explicitly disabled, but the -fips option is in effect” on page 702
243	“Invalid local path %1 for the downloaded file” on page 712
244	“The session key type '%1' is unknown” on page 721
245	“Invalid or corrupt network interface library: %1” on page 712
248	“Network interface library version mismatch. Expecting version %1.%2, but found version %3.%4” on page 715
249	“MobiLink authentication failed” on page 715
250	“SACI implementation mismatch” on page 720
251	“Unknown public key end-to-end encryption type sent from client: %1” on page 739
252	“Unexpected public key end-to-end encryption type. Expecting %1 but received %2” on page 738
253	“Mismatched end-to-end encryption keys” on page 714
254	“Unexpected private key type. Expecting %1 but found %2 in the e2ee_private_key file '%3'” on page 738
255	“Unable to read the e2ee_private_key file '%1'. The error code is %2” on page 734
256	“There is no private key in the e2ee_private_key file '%1'” on page 722
257	“Unable to decode the e2ee_private_key file '%1'. The error code is %2” on page 727
258	“Unable to read the e2ee_private_key file '%1'. The error code is %2” on page 735
259	“Missing e2ee_private_key_password for the e2ee_private_key file '%1'” on page 714
260	“Missing e2ee_private_key” on page 714
261	“Invalid e2ee_type '%1'” on page 711

Error code	Message text
262	“Unable to initialize ECC for end-to-end encryption. The error code is %1” on page 731
263	“Unable to read the e2ee public key” on page 734
264	“Unable to open '%1’” on page 732

MobiLink communication error messages sorted by error constant

Error constant	Message text
ACTSYNC_NO_PORT	“ActiveSync synchronization cannot be initiated by an application” on page 703
ACTSYNC_NOT_INSTALLED	“ActiveSync provider has not been installed” on page 703
AUTHENTICATION_FAILED	“MobiLink authentication failed” on page 715
CONNECT_TIMEOUT	“Connection attempt timed out” on page 705
COULD_NOT_OPEN_FILE	“Unable to open '%1’” on page 732
COULD_NOT_OPEN_FILE_FOR_WRITE	“Could not open %1 for write” on page 705
CREATE_RANDOM_OBJECT	“Unable to create a random number object” on page 726
DEQUEUEING_CONNECTION	“Unable to dequeue from the connection queue” on page 728
DUN_DIAL_FAILED	“Failed dialing to %1” on page 707
DUN_NOT_SUPPORTED	“Automatic dialup is not supported on this machine” on page 705
E2EE_DECODING_PRIVATE_KEY_FILE	“Unable to decode the e2ee_private_key file '%1'. The error code is %2” on page 727
E2EE_INIT_ECC	“Unable to initialize ECC for end-to-end encryption. The error code is %1” on page 731
E2EE_INVALID_TYPE	“Invalid e2ee_type '%1’” on page 711
E2EE_MISMATCHED_KEYS	“Mismatched end-to-end encryption keys” on page 714
E2EE_MISSING_PRIVATE_KEY	“Missing e2ee_private_key” on page 714
E2EE_MISSING_PRIVATE_KEY_PASSWORD	“Missing e2ee_private_key_password for the e2ee_private_key file '%1’” on page 714

Error constant	Message text
E2EE_NO_PRIVATE_KEY_IN_FILE	“There is no private key in the e2ee_private_key file '%1'” on page 722
E2EE_PUBLIC_KEY	“Unable to read the e2ee public key” on page 734
E2EE_READING_PRIVATE_KEY	“Unable to read the e2ee_private_key file '%1'. The error code is %2” on page 734
E2EE_READING_PRIVATE_KEY_FILE	“Unable to read the e2ee_private_key file '%1'. The error code is %2” on page 735
E2EE_UNEXPECTED_PRIVATE_KEY_TYPE	“Unexpected private key type. Expecting %1 but found %2 in the e2ee_private_key file '%3'” on page 738
E2EE_UNEXPECTED_PUBLIC_KEY_ENC_TYPE	“Unexpected public key end-to-end encryption type. Expecting %1 but received %2” on page 738
E2EE_UNKNOWN_PUBLIC_KEY_ENC_TYPE	“Unknown public key end-to-end encryption type sent from client: %1” on page 739
END_READ	“An end read failed” on page 703
END_WRITE	“An end write failed” on page 704
GENERATE_RANDOM	“Unable to generate a random number” on page 729
HTTP_AUTHENTICATION_FAILED	“HTTP Authentication failed” on page 709
HTTP_AUTHENTICATION_REQUIRED	“A userid and password are required for HTTP authentication” on page 702
HTTP_BAD_STATUS_CODE	“An error status was returned: '%1'” on page 704
HTTP_BUFFER_SIZE_OUT_OF_RANGE	“The HTTP buffer size specified is out of the valid range” on page 721
HTTP_CHUNK_LEN_BAD_CHARACTER	“An unexpected character was read while parsing the chunk length. %1” on page 704
HTTP_CHUNK_LEN_ENCODED_MISSING	“Failed to read encoded chunk length” on page 708
HTTP_CLIENT_ID_NOT_SET	“Client id is not available for use in HTTP header” on page 705
HTTP_CONTENT_TYPE_NOT_SPECIFIED	“The content type '%1' is unknown” on page 720

Error constant	Message text
HTTP_CRLF_ENCODED_MISSING	“Failed to read encoded CR LF” on page 708
HTTP_CRLF_MISSING	“Failed to read CR LF” on page 708
HTTP_EXPECTED_POST	“Expected data from remote but current request is not a POST” on page 706
HTTP_EXTRA_DATA_END_READ	“Extra data found in the HTTP body: %1” on page 707
HTTP_HEADER_PARSE_ERROR	“Error parsing HTTP header: %1” on page 706
HTTP_INTERNAL_HEADER_STATE	“Unexpected HTTP state %1 when decoding the header” on page 737
HTTP_INTERNAL_REQUEST_TYPE	“Unexpected internal HTTP request type %1” on page 737
HTTP_INVALID_CHARACTER	“Invalid HTTP character” on page 711
HTTP_INVALID_SESSION_KEY	“The session key type '%1' is unknown” on page 721
HTTP_MALFORMED_SESSION_COOKIE	“Malformed session cookie (ML_SESSION_ID) value: %1” on page 714
HTTP_NO_CONTD_CONNECTION	“Timed out while waiting for the next HTTP request in this synchronization” on page 723
HTTP_NO_PASSWORD	“No password was supplied” on page 716
HTTP_NO_USERID	“No userid was supplied” on page 717
HTTP_PROXY_AUTHENTICATION_FAILED	“HTTP Proxy Authentication failed” on page 709
HTTP_PROXY_AUTHENTICATION_REQUIRED	“A userid and password are required for HTTP proxy authentication” on page 702
HTTP_SERVER_AUTH_FAILED	“HTTP server authentication failed” on page 710
HTTP_UNABLE_TO_PARSE_COOKIE	“Unable to parse cookie: '%1'” on page 733
HTTP_UNKNOWN_TRANSFER_ENCODING	“Unknown transfer encoding: '%1'” on page 739

Error constant	Message text
HTTP_UNSUPPORTED_AUTH_ALGORITHM	“Unsupported http authentication algorithm: %1” on page 741
HTTP_VERSION	“Unsupported HTTP version: %1” on page 741
INCONSISTENT_FIPS	“A secure stream has FIPS explicitly disabled, but the -fips option is in effect” on page 702
INIT_RANDOM	“Unable to initialize the random number generator” on page 731
INTERNAL	“Internal error (%1)” on page 710
INTERNAL_API	“Internal error: %1 returned %2” on page 710
INTERNAL_PROTOCOL_NOT_LOADED	“Internal protocol not loaded: %1” on page 711
INTERRUPTED	“Operation interrupted” on page 718
INVALID_COMPRESSION_TYPE	“Invalid compression type: %1” on page 711
INVALID_LOCAL_PATH	“Invalid local path %1 for the downloaded file” on page 712
INVALID_NETWORK_LIBRARY	“Invalid or corrupt network interface library: %1” on page 712
INVALID_SYNC_PROTOCOL	“Invalid synchronization protocol: %1” on page 713
LIBRARY_ENTRY_POINT_NOT_FOUND	“Function %1 could not be found” on page 709
LOAD_LIBRARY_FAILURE	“Failed to load library %1” on page 707
LOAD_NETWORK_LIBRARY	“Unable to load the network interface library” on page 732
MEMORY_ALLOCATION	“Unable to allocate sufficient memory” on page 724
MISSING_PARAMETER	“Missing parameter: %1” on page 715
NETWORK_LIBRARY_VERSION_MISMATCH	“Network interface library version mismatch. Expecting version %1.%2, but found version %3.%4” on page 715

Error constant	Message text
NO_ECC_FIPS	“ECC encryption is not FIPS-compliant” on page 706
NONE	“No error or unknown error” on page 716
NOT_IMPLEMENTED	“Feature not implemented” on page 708
PARAMETER	“Invalid parameter '%1’” on page 712
PARAMETER_NOT_BOOLEAN	“Parameter value '%1’ is not a valid boolean value. The value must be 0 or 1” on page 718
PARAMETER_NOT_HEX	“Parameter value '%1’ is not a valid hexadecimal value” on page 718
PARAMETER_NOT_UINT32	“Parameter value '%1’ is not an unsigned integer” on page 719
PARAMETER_NOT_UINT32_RANGE	“Parameter value '%1’ is not an unsigned integer value or range. A range has the form NNN-NNN” on page 718
PARSE	“Unable to parse the parameter string '%1’” on page 733
PROTOCOL_ERROR	“Protocol error” on page 719
READ	“Unable to read %1 bytes” on page 733
READ_TIMEOUT	“Timed out trying to read %1 bytes” on page 722
SACI_IMPLEMENTATION_MISMATCH	“SACI implementation mismatch” on page 720
SECURE_ADD_CERTIFICATE	“Unable to add a certificate to a certificate chain” on page 723
SECURE_ADD_TRUSTED_CERTIFICATE	“Unable to add a trusted certificate” on page 724
SECURE_CERTIFICATE_COMMON_NAME	“Unrecognized common name '%1’” on page 739
SECURE_CERTIFICATE_COMPANY_NAME	“Unrecognized organization '%1’” on page 740
SECURE_CERTIFICATE_COMPANY_UNIT	“Unrecognized organization unit '%1’” on page 740

Error constant	Message text
SECURE_CERTIFICATE_COUNT	“No trusted certificates found in %1” on page 717
SECURE_CERTIFICATE_EXPIRED	“A certificate has expired” on page 702
SECURE_CERTIFICATE_EXPIRY_DATE	“Unable to fetch a certificate expiry date” on page 728
SECURE_CERTIFICATE_FILE_NOT_FOUND	“Unable to open certificate file '%1’” on page 732
SECURE_CERTIFICATE_NOT_TRUSTED	“Server certificate not trusted” on page 720
SECURE_CERTIFICATE_ROOT	“Invalid root certificate” on page 713
SECURE_CREATE_CERTIFICATE	“Unable to allocate a certificate” on page 724
SECURE_CREATE_PRIVATE_KEY_OBJECT	“Unable to create a private key object” on page 726
SECURE_DUPLICATE_CONTEXT	“Unable to duplicate security context” on page 728
SECURE_EXPORT_CERTIFICATE	“Unable to copy a certificate” on page 726
SECURE_HANDSHAKE	“Handshake error” on page 709
SECURE_IMPORT_CERT_FROM_SYSTEM_STORE	“Failed to import a certificate from the system certificate store” on page 707
SECURE_IMPORT_CERTIFICATE	“Unable to import a certificate” on page 730
SECURE_NO_CERTS_IN_SYS_STORE	“No certificate found in system certificate store” on page 716
SECURE_NO_SERVER_CERTIFICATE	“No server certificate was provided” on page 717
SECURE_NO_SERVER_CERTIFICATE_PASSWORD	“No server certificate password was provided” on page 716
SECURE_NO_TRUSTED_ROOTS	“No trusted root certificates were provided” on page 717
SECURE_OPEN_SYSTEM_CERT_STORE	“Failed to open system certificate store” on page 708
SECURE_READ_CERTIFICATE	“Unable to read certificates” on page 734
SECURE_READ_PRIVATE_KEY	“Unable to read the private key” on page 735

Error constant	Message text
SECURE_REDUNDANT_SERVER_CERTIFICATE_PASSWORD	“Password specified for an unencrypted server key” on page 719
SECURE_SET_IO	“Unable to attach the network layer to the security layer” on page 724
SECURE_SET_PRIVATE_KEY	“Unable to set the private key” on page 736
SECURE_TRUSTED_CERTIFICATE_FILE_NOT_FOUND	“Unable to find the trusted certificate file '%1'” on page 729
SECURE_TRUSTED_CERTIFICATE_READ	“Error reading from the trusted certificate file '%1'” on page 706
SEED_RANDOM	“Unable to seed the random number generator” on page 735
SERVER_ERROR	“Server error %1” on page 720
SHUTTING_DOWN	“An error occurred during shutdown” on page 704
SOCKET_BIND	“Unable to bind a socket to port %1” on page 725
SOCKET_CLEANUP	“Unable to clean up the socket layer” on page 725
SOCKET_CLOSE	“Unable to close a socket” on page 725
SOCKET_CONNECT	“Unable to connect a socket” on page 726
SOCKET_CREATE_TCPIP	“Unable to create a TCP/IP socket” on page 727
SOCKET_CREATE_UDP	“Unable to create a UDP socket” on page 727
SOCKET_GET_HOST_BY_ADDR	“Unable to get host by address” on page 730
SOCKET_GET_NAME	“Unable to get a socket's local name” on page 729
SOCKET_GET_OPTION	“Unable to get socket option number %1” on page 730
SOCKET_HOST_NAME_NOT_FOUND	“The host name '%1' could not be found” on page 721
SOCKET_LISTEN	“Unable to listen on a socket. The backlog is %1” on page 731

Error constant	Message text
SOCKET_LIVENESS_OUT_OF_RANGE	“Invalid liveness timeout value %1. The value must be between zero and 65535” on page 712
SOCKET_LOCAL- HOST_NAME_NOT_FOUND	“Unable to determine localhost” on page 728
SOCKET_PORT_OUT_OF_RANGE	“Invalid port number %1. The value must be between zero and 65535” on page 713
SOCKET_SELECT	“Unable to select a socket status” on page 735
SOCKET_SET_OPTION	“Unable to set socket option number %1” on page 736
SOCKET_SHUTDOWN	“Unable to shut down a socket” on page 736
SOCKET_STARTUP	“Unable to initialize the sockets layer” on page 731
UNEXPECTED_HTTP_REQUEST_TYPE	“Unexpected request type: %1” on page 738
UNRECOGNIZED_TLS_TYPE	“Unrecognized TLS type %1” on page 740
VALUE_OUT_OF_RANGE	“The value specified for %1 is out of range” on page 722
WOULD_BLOCK	“The operation would cause blocking” on page 721
WRITE	“Unable to write %1 bytes” on page 737
WRITE_TIMEOUT	“Timed out trying to write %1 bytes” on page 723

MobiLink communication error messages sorted by message text

A certificate has expired

Error code	50
Error constant	SECURE_CERTIFICATE_EXPIRED

Probable cause

A certificate in the certificate chain has expired. Obtain a new certificate with a later expiry date and retry the operation.

A secure stream has FIPS explicitly disabled, but the -fips option is in effect

Error code	242
Error constant	INCONSISTENT_FIPS

Probable cause

Use of the -fips switch on the MobiLink server command line requires that all secure streams be FIPS-compliant. If a secure stream is not configured with the fips option, it will automatically be FIPS-compliant (for example, fips=y). Either remove the fips option from the secure stream, or enable it with fips=y.

A userid and password are required for HTTP authentication

Error code	209
Error constant	HTTP_AUTHENTICATION_REQUIRED

Probable cause

An HTTP server or gateway requested HTTP authentication. Please supply a userid and password using the HTTP synchronization parameters http_userid and http_password.

A userid and password are required for HTTP proxy authentication

Error code	210
------------	-----

Error constant	HTTP_PROXY_AUTHENTICATION_REQUIRED
----------------	------------------------------------

Probable cause

An HTTP proxy requested HTTP authentication. Please supply a userid and password using the HTTP synchronization parameters http_proxy_userid and http_proxy_password.

ActiveSync provider has not been installed

Error code	76
Error constant	ACTSYNC_NOT_INSTALLED

Probable cause

The ActiveSync provider has not been installed. Run mlasinst to install it (see documentation for details).

ActiveSync synchronization cannot be initiated by an application

Error code	75
Error constant	ACTSYNC_NO_PORT

Probable cause

ActiveSync synchronization can only be initiated by ActiveSync itself, either by placing the device in its cradle or by selecting "Synchronize" from the ActiveSync Manager. To initiate a synchronization from an application, use the TCP/IP socket synchronization stream.

An end read failed

Error code	11
Error constant	END_READ

Probable cause

Unable to finish a sequence of reads from the network. See also: READ

An end write failed

Error code	10
Error constant	END_WRITE

Probable cause

Unable to finish a sequence of writes to the network. See also: WRITE

An error occurred during shutdown

Error code	18
Error constant	SHUTTING_DOWN

Probable cause

The MobiLink server encountered an error in the network layer during shutdown. It is possible that some network operations pending at the time of shutdown were affected.

An error status was returned: '%1'

Error code	86
Error constant	HTTP_BAD_STATUS_CODE
Parameter 1	The status line read.

Probable cause

Examine the status line to determine the cause of the failure.

An unexpected character was read while parsing the chunk length. %1

Error code	85
Error constant	HTTP_CHUNK_LEN_BAD_CHARACTER
Parameter 1	The unexpected character.

Probable cause

Try using a fixed length HTTP body.

Automatic dialup is not supported on this machine

Error code	203
Error constant	DUN_NOT_SUPPORTED

Probable cause

An attempt to dialup has failed due to insufficient system support. On PocketPC you must use cellcore.dll and on Windows you must use wininet.dll from IE 4.0 or above. Dialup is not supported on other platforms.

Client id is not available for use in HTTP header

Error code	78
Error constant	HTTP_CLIENT_ID_NOT_SET

Probable cause

The client id was not passed into the HTTP client code. Contact technical support for a fix.

Connection attempt timed out

Error code	241
Error constant	CONNECT_TIMEOUT

Probable cause

The connection attempt timed out. Either the server is not running on the indicated host and port or the timeout value needs to be increased to allow more time to connect.

Could not open %1 for write

Error code	230
Error constant	COULD_NOT_OPEN_FILE_FOR_WRITE
Parameter 1	The name of the file.

Probable cause

The specified file could not be opened for write. Make sure that this is the correct file and that no other application is using it.

ECC encryption is not FIPS-compliant

Error code	239
Error constant	NO_ECC_FIPS

Probable cause

There was a problem performing the given compression operation. Please contact technical support.

Error parsing HTTP header: %1

Error code	216
Error constant	HTTP_HEADER_PARSE_ERROR

Probable cause

An error occurred while trying to parse an HTTP header. The header may be malformed.

Error reading from the trusted certificate file '%1'

Error code	41
Error constant	SECURE_TRUSTED_CERTIFICATE_READ
Parameter 1	The trusted certificate file name.

Probable cause

The secure network layer was unable to read the trusted certificate file. Check the following: 1) The certificate file name was properly specified. 2) The certificate file exists. 3) The certificate file contains one or more certificates. 4) The certificate file contains the correct certificate(s). 5) The program attempting to open the certificate file has sufficient privileges to see the file. This only applies to operating systems having user and/or file permissions.

Expected data from remote but current request is not a POST

Error code	89
Error constant	HTTP_EXPECTED_POST

Probable cause

The proxy you are using may not be compatible with MobiLink. Please check your configuration.

Extra data found in the HTTP body: %1

Error code	80
Error constant	HTTP_EXTRA_DATA_END_READ
Parameter 1	First few characters in the extra data.

Probable cause

Extra data has been introduced into the HTTP body. This may have been added by a proxy agent. Try eliminating the proxy.

Failed dialing to %1

Error code	204
Error constant	DUN_DIAL_FAILED

Probable cause

Automatic dialup failed to establish connection to the specified dial up network.

Failed to import a certificate from the system certificate store

Error code	222
Error constant	SECURE_IMPORT_CERT_FROM_SYSTEM_STORE

Probable cause

Failed to import a certificate from the system certificate store.

Failed to load library %1

Error code	224
Error constant	LOAD_LIBRARY_FAILURE

Probable cause

The indicated library could not be found in the path. If you are trying to use TLS encryption for synchronization, make sure you have acquired the proper license.

Failed to open system certificate store

Error code	221
Error constant	SECURE_OPEN_SYSTEM_CERT_STORE

Probable cause

An attempt to open a system certificate store failed.

Failed to read CR LF

Error code	82
Error constant	HTTP_CRLF_MISSING

Probable cause

The proxy you are using may not be compatible with MobiLink. Please check your configuration.

Failed to read encoded chunk length

Error code	84
Error constant	HTTP_CHUNK_LEN_ENCODED_MISSING

Probable cause

Try using a fixed length HTTP body.

Failed to read encoded CR LF

Error code	81
Error constant	HTTP_CRLF_ENCODED_MISSING

Probable cause

The proxy you are using may not be compatible with MobiLink. Please check your configuration.

Feature not implemented

Error code	12
------------	----

Error constant	NOT_IMPLEMENTED
----------------	-----------------

Probable cause

An unimplemented internal feature was requested. Please contact technical support.

Function %1 could not be found

Error code	225
Error constant	LIBRARY_ENTRY_POINT_NOT_FOUND

Probable cause

The indicated library entry point could not be found.

Handshake error

Error code	53
Error constant	SECURE_HANDSHAKE

Probable cause

The secure handshake failed. Check the following: 1) On the client, the correct host machine and port number were specified. 2) On the server, the correct port number was specified. 3) The correct trusted certificate was specified on the client and the correct identity file was specified on the server.

HTTP Authentication failed

Error code	211
Error constant	HTTP_AUTHENTICATION_FAILED

Probable cause

The supplied userid and password were rejected. Check that they were entered correctly. If so, contact your systems administrator to ensure you have proper access.

HTTP Proxy Authentication failed

Error code	212
------------	-----

Error constant	HTTP_PROXY_AUTHENTICATION_FAILED
----------------	----------------------------------

Probable cause

The supplied userid and password were rejected by the proxy server. Check that they were entered correctly. If so, contact your systems administrator to ensure you have proper access.

HTTP server authentication failed

Error code	217
Error constant	HTTP_SERVER_AUTH_FAILED

Probable cause

The Authentication-Info header sent from the server contained an incorrect value, causing authentication to fail. Make sure that you are connecting to a legitimate HTTP server.

Internal error (%1)

Error code	220
Error constant	INTERNAL
Parameter 1	The internal error code.

Probable cause

An internal error has occurred in the network layer. Please contact technical support.

Internal error: %1 returned %2

Error code	238
Error constant	INTERNAL_API
Parameter 1	The name of the internal API.
Parameter 2	The internal error code.

Probable cause

An internal error has occurred in the network layer. Please contact technical support.

Internal protocol not loaded: %1

Error code	227
Error constant	INTERNAL_PROTOCOL_NOT_LOADED

Probable cause

A synchronization protocol could not be loaded. If you are using UltraLite, make sure you have called the proper ULEnable method.

Invalid compression type: %1

Error code	232
Error constant	INVALID_COMPRESSION_TYPE
Parameter 1	The invalid compression type

Probable cause

The specified compression type was not recognized.

Invalid e2ee_type '%1'

Error code	261
Error constant	E2EE_INVALID_TYPE
Parameter 1	The invalid end-to-end private key type

Probable cause

An invalid e2ee_type was specified. Please specify a valid value.

Invalid HTTP character

Error code	219
Error constant	HTTP_INVALID_CHARACTER

Probable cause

An unexpected character was read in an HTTP header. The header may be malformed or the other side may not be sending HTTP at all.

Invalid liveness timeout value %1. The value must be between zero and 65535

Error code	200
Error constant	SOCKET_LIVENESS_OUT_OF_RANGE
Parameter 1	The liveness timeout value.

Probable cause

An invalid liveness timeout value was specified. The liveness timeout value must be an integer between zero and 65535.

Invalid local path %1 for the downloaded file

Error code	243
Error constant	INVALID_LOCAL_PATH
Parameter 1	The local path.

Probable cause

The local path for the downloaded file is invalid. Consult the documentation for details.

Invalid or corrupt network interface library: %1

Error code	245
Error constant	INVALID_NETWORK_LIBRARY
Parameter 1	The network library path.

Probable cause

The given network interface DLL or shared object could not be loaded, possibly because it is invalid or corrupt.

Invalid parameter '%1'

Error code	1
Error constant	PARAMETER

Parameter 1	The invalid parameter value.
-------------	------------------------------

Probable cause

Network parameters are of the form "name=value;[name2=value2[;...]]". This code indicates an invalid parameter value. Consult the documentation for the corresponding parameter name, and correct the parameter value.

Invalid port number %1. The value must be between zero and 65535

Error code	74
Error constant	SOCKET_PORT_OUT_OF_RANGE
Parameter 1	The port number.

Probable cause

An invalid port number was specified. The port number must be an integer between zero and 65535.

Invalid root certificate

Error code	20
Error constant	SECURE_CERTIFICATE_ROOT

Probable cause

The root certificate in the chain is invalid. At the time of publication, this error was defined but not used.

Invalid synchronization protocol: %1

Error code	226
Error constant	INVALID_SYNC_PROTOCOL

Probable cause

The specified protocol is not a valid synchronization protocol.

Malformed session cookie (ML_SESSION_ID) value: %1

Error code	235
Error constant	HTTP_MALFORMED_SESSION_COOKIE
Parameter 1	The cookie value

Probable cause

The HTTP cookie used to manage the synchronization session is corrupt. Determine where the cookie is being corrupted. The most likely cause is a client error, or perhaps an HTTP intermediary misbehaving,

Mismatched end-to-end encryption keys

Error code	253
Error constant	E2EE_MISMATCHED_KEYS

Probable cause

The client and server are unable to communicate because the e2ee_public_key used for end-to-end encryption at the remote does not match the e2ee_private_key at the server.

Missing e2ee_private_key

Error code	260
Error constant	E2EE_MISSING_PRIVATE_KEY

Probable cause

Another end-to-end encryption option was specified, but not the e2ee_private_key option. Either specify all end-to-end encryption options or remove them all. Required end-to-end encryption options include: e2ee_type, e2ee_private_key, e2ee_private_key_password.

Missing e2ee_private_key_password for the e2ee_private_key file '%1'

Error code	259
Error constant	E2EE_MISSING_PRIVATE_KEY_PASSWORD
Parameter 1	The private key file from the e2ee_private_key option.

Probable cause

The e2ee_private_key file cannot be read without an e2ee_private_key_password. Please provide the e2ee_private_key_password.

Missing parameter: %1

Error code	229
Error constant	MISSING_PARAMETER
Parameter 1	The name of the missing parameter.

Probable cause

The specified parameter was expected but not supplied.

MobiLink authentication failed

Error code	249
Error constant	AUTHENTICATION_FAILED

Probable cause

The client failed to authenticate itself to MobiLink.

Network interface library version mismatch. Expecting version %1.%2, but found version %3.%4

Error code	248
Error constant	NETWORK_LIBRARY_VERSION_MISMATCH
Parameter 1	The major version expected.
Parameter 2	The minor version expected.
Parameter 3	The major version found.
Parameter 4	The minor version found.

Probable cause

A network interface DLL or shared object could not be loaded because it is the wrong version.

No certificate found in system certificate store

Error code	223
Error constant	SECURE_NO_CERTS_IN_SYS_STORE

Probable cause

No certificates were found in the system's certificate store.

No error or unknown error

Error code	0
Error constant	NONE

Probable cause

This code indicates there was either no network error, or an unknown network error occurred.

No password was supplied

Error code	214
Error constant	HTTP_NO_PASSWORD

Probable cause

A userid was supplied for HTTP authentication but no password. Both are required for authentication.

No server certificate password was provided

Error code	206
Error constant	SECURE_NO_SERVER_CERTIFICATE_PASSWORD

Probable cause

No server certificate password was provided. This password is required to decrypt the server's encrypted private key.

No server certificate was provided

Error code	205
Error constant	SECURE_NO_SERVER_CERTIFICATE

Probable cause

No server certificate was provided. A server certificate is required for secure communications. The file provided must contain the full chain of certificates for the server as well as its private key.

No trusted certificates found in %1

Error code	42
Error constant	SECURE_CERTIFICATE_COUNT

Probable cause

The given file does not contain a certificate. Check the following: 1) The certificate file name was properly specified. 2) The certificate file contains one or more certificates. 3) The certificate file contains the correct certificate(s).

No trusted root certificates were provided

Error code	207
Error constant	SECURE_NO_TRUSTED_ROOTS

Probable cause

No trusted root certificates were provided. At least one trusted root certificate is required for secure communications.

No userid was supplied

Error code	213
Error constant	HTTP_NO_USERID

Probable cause

A password was supplied for HTTP authentication but no userid. Both are required for authentication.

Operation interrupted

Error code	218
Error constant	INTERRUPTED

Probable cause

The current operation was interrupted by the caller.

Parameter value '%1' is not a valid boolean value. The value must be 0 or 1

Error code	4
Error constant	PARAMETER_NOT_BOOLEAN
Parameter 1	The invalid parameter value.

Probable cause

Network parameters are of the form "name=value;[name2=value2[;...]]". The parameter value is not a boolean value. Locate the offending parameter specification and change the value of the parameter to either 0 (for off or false) or 1 (for on or true).

Parameter value '%1' is not a valid hexadecimal value

Error code	5
Error constant	PARAMETER_NOT_HEX
Parameter 1	The invalid parameter value.

Probable cause

Network parameters are of the form "name=value;[name2=value2[;...]]". The parameter value is not a hexadecimal (base 16) value. Locate the offending parameter specification and change the value of the parameter to a hexadecimal value.

Parameter value '%1' is not an unsigned integer value or range. A range has the form NNN-NNN

Error code	3
------------	---

Error constant	PARAMETER_NOT_UINT32_RANGE
Parameter 1	The invalid parameter value.

Probable cause

Network parameters are of the form "name=value;[name2=value2[;...]]". The parameter value is not an unsigned integer value or range. Locate the offending parameter specification and change the value of the parameter to an unsigned integer or an unsigned range. An unsigned range has the form: NNN-NNN.

Parameter value '%1' is not an unsigned integer

Error code	2
Error constant	PARAMETER_NOT_UINT32
Parameter 1	The invalid parameter value.

Probable cause

Network parameters are of the form "name=value;[name2=value2[;...]]". The parameter value is not an unsigned integer. Locate the offending parameter specification and change the value of the parameter to an unsigned integer.

Password specified for an unencrypted server key

Error code	208
Error constant	SECURE_REDUNDANT_SERVER_CERTIFICATE_PASSWORD

Probable cause

A password was specified when the server's private key wasn't encrypted by any password.

Protocol error

Error code	231
Error constant	PROTOCOL_ERROR

Probable cause

An unexpected value or token was read.

SACI implementation mismatch

Error code	250
Error constant	SACI_IMPLEMENTATION_MISMATCH

Probable cause

The SACI implementation could not be loaded because it had an incompatible implementation ID.

Server certificate not trusted

Error code	24
Error constant	SECURE_CERTIFICATE_NOT_TRUSTED

Probable cause

The server's certificate was not signed by a trusted authority. Check the following: 1) The certificate file name was properly specified. 2) The certificate file contains one or more certificates. 3) The certificate file contains the correct certificate(s). 4) The client's list of trusted root certificates includes the server's root certificate.

Server error %1

Error code	228
Error constant	SERVER_ERROR
Parameter 1	The error reported by the server.

Probable cause

The server reported an error. Contact the MobiLink administrator to learn more.

The content type '%1' is unknown

Error code	77
Error constant	HTTP_CONTENT_TYPE_NOT_SPECIFIED
Parameter 1	The content type.

Probable cause

An unknown content type was specified. Refer to the documentation and change the content type to one of the supported types.

The host name '%1' could not be found

Error code	57
Error constant	SOCKET_HOST_NAME_NOT_FOUND
Parameter 1	The name of the host.

Probable cause

The given host name could not be found. Check the following: 1) The host name was correctly specified. 2) The host is accessible. Many systems include a "ping" utility that can be used to verify access to a named host. 3) The Domain Name Server (DNS), or its equivalent, is available. If the DNS is not available, try specifying the host's IP number (for example, NNN.NNN.NNN.NNN) instead of the host name. 4) The HOSTS file contains an entry that maps the host name to an IP number.

The HTTP buffer size specified is out of the valid range

Error code	79
Error constant	HTTP_BUFFER_SIZE_OUT_OF_RANGE

Probable cause

Fix the HTTP buffer size. A valid buffer size is positive and not overly large for the host platform.

The operation would cause blocking

Error code	13
Error constant	WOULD_BLOCK

Probable cause

A requested operation would block where blocking is undesirable or unexpected.

The session key type '%1' is unknown

Error code	244
------------	-----

Error constant	HTTP_INVALID_SESSION_KEY
Parameter 1	The session key type.

Probable cause

An unknown session key type was specified. Refer to the documentation and change the session key type to one of the supported types.

The value specified for %1 is out of range

Error code	233
Error constant	VALUE_OUT_OF_RANGE
Parameter 1	The name of the parameter

Probable cause

The specified value was not in the range of acceptable values for that parameter. Check the documentation for the parameter to learn the acceptable range of values.

There is no private key in the e2ee_private_key file '%1'

Error code	256
Error constant	E2EE_NO_PRIVATE_KEY_IN_FILE
Parameter 1	The private key file from the e2ee_private_key option.

Probable cause

The given filename does not contain a private key.

Timed out trying to read %1 bytes

Error code	201
Error constant	READ_TIMEOUT
Parameter 1	The number of bytes that could not be read.

Probable cause

Unable to read the given number of bytes from the network layer in the given time. Check that the network is functioning correctly, and that the sending application is still running.

Timed out trying to write %1 bytes

Error code	202
Error constant	WRITE_TIMEOUT
Parameter 1	The number of bytes that could not be written.

Probable cause

Unable to write the given number of bytes to the network layer in the given time. Check that the network is functioning correctly, and that the receiving application is still running.

Timed out while waiting for the next HTTP request in this synchronization

Error code	83
Error constant	HTTP_NO_CONTD_CONNECTION

Probable cause

The server timed out while waiting for the next HTTP request from the remote site. Determine why this request failed to reach the server or try a persistent connection.

Unable to add a certificate to a certificate chain

Error code	39
Error constant	SECURE_ADD_CERTIFICATE

Probable cause

The secure network layer was unable to add a certificate to a certificate chain. Free up system resources and retry the operation.

Unable to add a trusted certificate

Error code	48
Error constant	SECURE_ADD_TRUSTED_CERTIFICATE

Probable cause

The secure network layer was unable to add a trusted certificate to a certificate chain. The most likely cause is a shortage of system resources. Free up system resources and retry the operation.

Unable to allocate a certificate

Error code	43
Error constant	SECURE_CREATE_CERTIFICATE

Probable cause

The secure network layer was unable to allocate storage for a certificate. Free up system resources and retry the operation.

Unable to allocate sufficient memory

Error code	6
Error constant	MEMORY_ALLOCATION

Probable cause

The network layer was unable to allocate enough bytes of storage. Free up system memory and retry the operation. The technique used to free up system memory depends on the operating system and how it is configured. The simplest technique is to reduce the number of active processes. Consult your operating system documentation for details.

Unable to attach the network layer to the security layer

Error code	26
Error constant	SECURE_SET_IO

Probable cause

The secure network layer was unable to attach to the network layer. Free up system resources and retry the operation.

Unable to bind a socket to port %1

Error code	60
Error constant	SOCKET_BIND
Parameter 1	The port number.

Probable cause

The network layer was unable to bind a socket to the given port. Check the following. 1) (Server only) Verify that the port isn't already in use. If the port is in use, either shut down the application listening on that port, or specify a different port. 2) (Server only) Verify that there are no firewall restrictions on the use of the port. 3) (Client only) If the client_port option was used, verify that the given port isn't already in use. If only one client port was specified, consider using a range (for example, NNN-NNN). If a range was specified, consider making it a wider range, or a different range. 4) (Client only) If the client_port option was used, verify that there are no firewall restrictions on the use of the port.

Unable to clean up the socket layer

Error code	61
Error constant	SOCKET_CLEANUP

Probable cause

The network layer was unable to clean up the socket layer. This error should only occur after all connections are finished, so no current connections should be affected.

Unable to close a socket

Error code	62
Error constant	SOCKET_CLOSE

Probable cause

The network layer was unable to close a socket. The network session may or may not have terminated prematurely, due to pending writes that were not flushed. Check the following: 1) The other side of the network connection had any errors. 2) The other side of the connection is running normally. 3) The machine is still connected to the network, and the network is responsive.

Unable to connect a socket

Error code	63
Error constant	SOCKET_CONNECT

Probable cause

The network layer was unable to connect a socket. Check the following: 1) The machine is connected to the network. 2) The socket layer is properly initialized. 3) The correct host machine and port were specified. 4) The host server is running normally and listening on the correct port. 5) The host machine is listening for the proper socket type (TCP/IP vs. UDP). 6) If the client_port option was used, verify that there are no firewall restrictions on the use of the port. 7) If the device has a limit on the number of open sockets, verify that the limit has not been reached. 8) There are enough system resources available. Free up system resources if they are running low.

Unable to copy a certificate

Error code	38
Error constant	SECURE_EXPORT_CERTIFICATE

Probable cause

The secure network layer was unable to copy a certificate. Free up system resources and retry the operation.

Unable to create a private key object

Error code	49
Error constant	SECURE_CREATE_PRIVATE_KEY_OBJECT

Probable cause

The secure network layer was unable to create a private key object, prior to loading the private key. The most likely cause is a shortage of system resources. Free up system resources and retry the operation.

Unable to create a random number object

Error code	17
Error constant	CREATE_RANDOM_OBJECT

Probable cause

The secure network layer could not create a random-number-generating object. Free up system resources, reconnect and retry the operation.

Unable to create a TCP/IP socket

Error code	58
Error constant	SOCKET_CREATE_TCPIP

Probable cause

The network layer was unable to create a TCP/IP socket. Check the following: 1) The machine is connected to the network. 2) The socket layer is properly initialized. 5) If the device has a limit on the number of open sockets, verify that the limit has not been reached. 6) There are enough system resources available. Free up system resources if they are running low.

Unable to create a UDP socket

Error code	59
Error constant	SOCKET_CREATE_UDP

Probable cause

The network layer was unable to create a UDP socket. Check the following: 1) The machine is connected to the network. 2) The socket layer is properly initialized. 3) If the client_port option was used, verify that the given port isn't already in use. If only one client port was specified, consider using a range (for example, NNN-NNN). If a range was specified, consider making it a wider range, or a different range. 4) If the client_port option was used, verify that there are no firewall restrictions on the use of the port. 5) If the device has a limit on the number of open sockets, verify that the limit has not been reached. 6) There are enough system resources available. Free up system resources if they are running low.

Unable to decode the e2ee_private_key file '%1'. The error code is %2

Error code	257
Error constant	E2EE_DECODING_PRIVATE_KEY_FILE
Parameter 1	The private key file from the e2ee_private_key option.
Parameter 2	The error code.

Probable cause

The file was found and its contents were read, but there was an error decoding the file. Please contact technical support and provide the error code.

Unable to dequeue from the connection queue

Error code	19
Error constant	DEQUEUEING_CONNECTION

Probable cause

The MobiLink server encountered an error while attempting to get a queued connection (synchronization) request. Free up system resources. If the problem persists, restart the MobiLink server.

Unable to determine localhost

Error code	71
Error constant	SOCKET_LOCALHOST_NAME_NOT_FOUND

Probable cause

The network layer was unable to determine the IP address of "localhost". Check the following: 1) The Domain Name Server (DNS), or its equivalent, is available. If the DNS is not available, try explicitly specifying the localhost IP number (usually 127.0.0.1) instead. 2) The HOSTS file contains an entry that maps the "localhost" name to an IP number. 3) There are enough system resources available. Free up system resources if they are running low.

Unable to duplicate security context

Error code	25
Error constant	SECURE_DUPLICATE_CONTEXT

Probable cause

The secure network layer was unable to duplicate a security context. Free up system resources and retry the operation.

Unable to fetch a certificate expiry date

Error code	37
------------	----

Error constant	SECURE_CERTIFICATE_EXPIRY_DATE
----------------	--------------------------------

Probable cause

A certificate's expiry date could not be read. Check the following: 1) The password was entered correctly. 2) The certificate file contains one or more certificates. 3) The certificate file contains the correct certificate(s). 4) The certificate file is undamaged.

Unable to find the trusted certificate file '%1'

Error code	40
Error constant	SECURE_TRUSTED_CERTIFICATE_FILE_NOT_FOUND
Parameter 1	The trusted certificate file name.

Probable cause

The certificate file could not be found. Check the following: 1) The certificate file name was properly specified. 2) The certificate file exists. 3) The certificate file contains one or more certificates. 4) The certificate file contains the correct certificate(s). 5) The program attempting to open the certificate file has sufficient privileges to see the file. This only applies to operating systems having user and/or file permissions.

Unable to generate a random number

Error code	14
Error constant	GENERATE_RANDOM

Probable cause

The secure network layer requires a random number but was unable to generate one. Free up system resources, reconnect and retry the operation.

Unable to get a socket's local name

Error code	64
Error constant	SOCKET_GET_NAME

Probable cause

The network layer was unable to determine a socket's local name. In a TCP/IP connection, each end of the connection has a socket exclusively attached to a port. A socket's local name includes this port number, which is assigned by the network at connection time. Check the following: 1) The machine is still connected

to the network, and the network is responsive. 2) The other side of the connection is running normally. 3) There are enough system resources available. Free up system resources if they are running low.

Unable to get host by address

Error code	72
Error constant	SOCKET_GET_HOST_BY_ADDR

Probable cause

The network layer was unable to get the name of a host using its IP address. At the time of publication, this error was defined but not used.

Unable to get socket option number %1

Error code	65
Error constant	SOCKET_GET_OPTION
Parameter 1	The socket option being retrieved.

Probable cause

The network layer was unable to get a socket option. This error may be the first indication that a connection has been lost. Check the following: 1) The machine is still connected to the network, and the network is responsive. 2) The other side of the connection is running normally. 3) There are enough system resources available. Free up system resources if they are running low.

Unable to import a certificate

Error code	44
Error constant	SECURE_IMPORT_CERTIFICATE

Probable cause

The secure network layer was unable to import a certificate. Check the following: 1) The certificate file name was properly specified. 2) The certificate file exists. 3) The certificate file contains one or more certificates. 4) The certificate file contains the correct certificate(s).

Unable to initialize ECC for end-to-end encryption. The error code is %1

Error code	262
Error constant	E2EE_INIT_ECC
Parameter 1	The error code.

Probable cause

An error occurred when attempting to initialize ECC. Please make sure the ECC option is installed.

Unable to initialize the random number generator

Error code	15
Error constant	INIT_RANDOM

Probable cause

The secure network layer could not initialize its random number generator. Free up system resources, reconnect and retry the operation.

Unable to initialize the sockets layer

Error code	70
Error constant	SOCKET_STARTUP

Probable cause

The network layer was unable to initialize the socket layer. Check the following: 1) The sockets layer is properly installed. The correct network interface library must be present and accessible. 2) The machine is connected to the network, and the network is responsive. 3) There are enough system resources available. Free up system resources if they are running low.

Unable to listen on a socket. The backlog is %1

Error code	67
Error constant	SOCKET_LISTEN
Parameter 1	The requested listener backlog.

Probable cause

The server is unable to listen on a socket. The backlog refers to the maximum number of queued connection requests that may be pending at any given time. Check the following: 1) The machine is still connected to the network, and the network is responsive. 2) There are no firewall or other restrictions preventing a socket listener from running on the current machine. 3) The backlog setting is within the limit, if any, on the machine. 4) There are enough system resources available. Free up system resources if they are running low.

Unable to load the network interface library

Error code	73
Error constant	LOAD_NETWORK_LIBRARY

Probable cause

The network interface library could not be found and/or loaded. Please check the following: 1) The sockets layer is properly installed. The correct network interface library (or DLL or shared object) must be present and accessible. 2) There are enough system resources available. Free up system resources if they are running low.

Unable to open '%1'

Error code	264
Error constant	COULD_NOT_OPEN_FILE
Parameter 1	The name of the file.

Probable cause

The specified file could not be opened.

Unable to open certificate file '%1'

Error code	33
Error constant	SECURE_CERTIFICATE_FILE_NOT_FOUND
Parameter 1	The certificate file name.

Probable cause

The certificate file could not be opened. Check the following: 1) The certificate file name was properly specified. 2) The certificate file exists. 3) The certificate file contains one or more certificates. 4) The certificate file contains the correct certificate(s). 5) The program attempting to open the certificate file has

sufficient privileges to read the file. This only applies to operating systems having user and/or file permissions.

Unable to parse cookie: '%1'

Error code	88
Error constant	HTTP_UNABLE_TO_PARSE_COOKIE
Parameter 1	The set cookie header.

Probable cause

Determine where the set cookie header is being corrupted.

Unable to parse the parameter string '%1'

Error code	7
Error constant	PARSE
Parameter 1	The parameter string that could not be parsed.

Probable cause

Network parameters are of the form "name=value;[name2=value2[;...]]". Optionally, the entire list of parameters may be enclosed in parentheses. The given string does not follow this convention. Inspect the string, fix any formatting problems, and retry the operation.

Unable to read %1 bytes

Error code	8
Error constant	READ
Parameter 1	The number of bytes that could not be read.

Probable cause

Unable to read the given number of bytes from the network layer. Note that reads may occur as part of any larger network operation. For example, some network layers have sub-layers that perform several reads and writes as part of a basic operation in the upper layer. The cause of a read error is usually one of the following: 1) The network had a problem that caused the read to fail. Reconnect and retry the operation. 2) The connection timed out. Reconnect and retry the operation. 3) The other side of the connection cleanly terminated the connection. Consult the client and/or server logs for errors that indicate why the connection

has been dropped. Consult the output-log errors and fix the cause, then retry the operation. 4) The process at the other side of the connection was aborted. Consult the client and/or server output logs for errors that indicate why the process was aborted. If the process was shut down by other than normal means, there may not be any errors in its output log. Reconnect and retry the operation. 5) The system is low on resources, and cannot perform the read. Free up system resources, reconnect and retry the operation. If subsequent retry attempts fail, consult your network administrator.

Unable to read certificates

Error code	34
Error constant	SECURE_READ_CERTIFICATE

Probable cause

The certificate file could not be read. Check the following: 1) The password was entered correctly. 2) The certificate file contains one or more certificates. 3) The certificate file contains the correct certificate(s). 4) The certificate file is undamaged.

Unable to read the e2ee public key

Error code	263
Error constant	E2EE_PUBLIC_KEY

Probable cause

An error occurred while trying to read the end-to-end encryption public key.

Unable to read the e2ee_private_key file '%1'. The error code is %2

Error code	255
Error constant	E2EE_READING_PRIVATE_KEY
Parameter 1	The private key file from the e2ee_private_key option.
Parameter 2	The error code.

Probable cause

An error occurred reading the e2ee_private_key file. Please contact technical support and provide the error code.

Unable to read the e2ee_private_key file '%1'. The error code is %2

Error code	258
Error constant	E2EE_READING_PRIVATE_KEY_FILE
Parameter 1	The private key file from the e2ee_private_key option.
Parameter 2	The error code.

Probable cause

The given file could not be read. Please contact technical support and provide the error code.

Unable to read the private key

Error code	35
Error constant	SECURE_READ_PRIVATE_KEY

Probable cause

The private key could not be read from the certificate file. Check the following: 1) The password was entered correctly. 2) The certificate file contains one or more certificates. 3) The certificate file contains the correct certificate(s). 4) The certificate file is undamaged.

Unable to seed the random number generator

Error code	16
Error constant	SEED_RANDOM

Probable cause

The secure network layer could not seed its random number generator. Free up system resources, reconnect and retry the operation.

Unable to select a socket status

Error code	69
Error constant	SOCKET_SELECT

Probable cause

The network layer encountered an error attempting to wait for a socket to be ready for reading or writing. Check the following: 1) The machine is connected to the network, and the network is responsive. 2) The other side of the connection is running normally. 3) There are enough system resources available. Free up system resources if they are running low.

Unable to set socket option number %1

Error code	66
Error constant	SOCKET_SET_OPTION
Parameter 1	The socket option being set.

Probable cause

The network layer was unable to set a socket option. This error may be the first indication that a connection has been lost. Check the following: 1) The machine is still connected to the network, and the network is responsive. 2) The other side of the connection is running normally. 3) There are enough system resources available. Free up system resources if they are running low.

Unable to set the private key

Error code	36
Error constant	SECURE_SET_PRIVATE_KEY

Probable cause

The private key could not be used. Check the following: 1) The password was entered correctly. 2) The certificate file contains one or more certificates. 3) The certificate file contains the correct certificate(s). 4) The certificate file is undamaged.

Unable to shut down a socket

Error code	68
Error constant	SOCKET_SHUTDOWN

Probable cause

The network layer was unable to shut down a socket. Check the following: 1) The machine is connected to the network, and the network is responsive. 2) The other side of the connection is running normally. 3) There are enough system resources available. Free up system resources if they are running low.

Unable to write %1 bytes

Error code	9
Error constant	WRITE
Parameter 1	The number of bytes that could not be written.

Probable cause

Unable to write the given number of bytes to the network layer. Note that writes may occur as part of any larger network operation. For example, some network layers have sub-layers that perform several reads and writes as part of a basic operation in the upper layer. The cause of a write error is usually one of the following:

- 1) The network had a problem that caused the write to fail. Reconnect and retry the operation.
- 2) The connection timed out. Reconnect and retry the operation.
- 3) The other side of the connection cleanly terminated the connection. Consult the client and/or server logs for errors that indicate why the connection has been dropped. Consult the output-log errors and fix the cause, then retry the operation.
- 4) The process at the other side of the connection was aborted. Consult the client and/or server output logs for errors that indicate why the process was aborted. If the process was shut down by other than normal means, there may not be any errors in its output log. Reconnect and retry the operation.
- 5) The system is low on resources, and cannot perform the write. Free up system resources, reconnect and retry the operation. If subsequent retry attempts fail, consult your network administrator.

Unexpected HTTP state %1 when decoding the header

Error code	236
Error constant	HTTP_INTERNAL_HEADER_STATE
Parameter 1	The internal header state

Probable cause

There was a problem decoding the HTTP header. This is an internal error that should never occur. Please contact technical support.

Unexpected internal HTTP request type %1

Error code	237
Error constant	HTTP_INTERNAL_REQUEST_TYPE
Parameter 1	The internal HTTP request type

Probable cause

There was a problem determining the HTTP request type. This is an internal error that should never occur. Please contact technical support.

Unexpected private key type. Expecting %1 but found %2 in the e2ee_private_key file '%3'

Error code	254
Error constant	E2EE_UNEXPECTED_PRIVATE_KEY_TYPE
Parameter 1	The end-to-end private key type from the e2ee_type option.
Parameter 2	The end-to-end private key type from the file.
Parameter 3	The private key file from the e2ee_private_key option.

Probable cause

The private key type found in the e2ee_private_key file does not match the type specified in the e2ee_type.

Unexpected public key end-to-end encryption type. Expecting %1 but received %2

Error code	252
Error constant	E2EE_UNEXPECTED_PUBLIC_KEY_ENC_TYPE
Parameter 1	The end-to-end encryption type from the server.
Parameter 2	The end-to-end encryption type from the client.

Probable cause

The client sent an e2ee_type value that is different from the e2ee_type specified at the server. Please make sure these are the same.

Unexpected request type: %1

Error code	234
Error constant	UNEXPECTED_HTTP_REQUEST_TYPE

Parameter 1	The HTTP request type
-------------	-----------------------

Probable cause

The given HTTP request type was unexpected at this time. The most likely cause is an HTTP client that is not a MobiLink client.

Unknown public key end-to-end encryption type sent from client: %1

Error code	251
Error constant	E2EE_UNKNOWN_PUBLIC_KEY_ENC_TYPE
Parameter 1	The end-to-end encryption type code

Probable cause

The client sent an e2ee_type value that is not recognized by the server. Please make sure the server version is equal to or greater than the version of the remote.

Unknown transfer encoding: '%1'

Error code	87
Error constant	HTTP_UNKNOWN_TRANSFER_ENCODING
Parameter 1	The unknown encoding.

Probable cause

Determine how the unknown transfer encoding is getting generated.

Unrecognized common name '%1'

Error code	52
Error constant	SECURE_CERTIFICATE_COMMON_NAME
Parameter 1	The common name.

Probable cause

The given common name is not in the certificate chain. Check the following: 1) The common name was properly entered. 2) The correct certificate file was specified. 3) The common name is in the certificate chain. You can verify this with the viewcert utility.

Unrecognized organization '%1'

Error code	21
Error constant	SECURE_CERTIFICATE_COMPANY_NAME
Parameter 1	The organization name.

Probable cause

The given organization name is not in the certificate chain. Check the following: 1) The organization name was properly entered. 2) The correct certificate file was specified. 3) The organization name is in the certificate chain. You can verify this with the viewcert utility.

Unrecognized organization unit '%1'

Error code	51
Error constant	SECURE_CERTIFICATE_COMPANY_UNIT
Parameter 1	The organization unit name.

Probable cause

The given organization unit is not in the certificate chain. Check the following: 1) The in company name was properly entered. 2) The correct certificate file was specified. 3) The company name is in the certificate chain. You can verify this with the viewcert utility.

Unrecognized TLS type %1

Error code	240
Error constant	UNRECOGNIZED_TLS_TYPE
Parameter 1	The TLS type

Probable cause

The TLS type is invalid. Consult the documentation for valid types.

Unsupported http authentication algorithm: %1

Error code	215
Error constant	HTTP_UNSUPPORTED_AUTH_ALGORITHM

Probable cause

The HTTP Digest authentication algorithm requested by the server is unsupported. Only "MD5" and "MD5-sess" are supported.

Unsupported HTTP version: %1

Error code	54
Error constant	HTTP_VERSION
Parameter 1	The requested HTTP version.

Probable cause

The requested HTTP version is unsupported. Consult the documentation and specify a supported HTTP version. At the time of publication the supported HTTP versions are 1.0 and 1.1.

SQL preprocessor error messages

Contents

SQL preprocessor error messages sorted by error code	744
SQL preprocessor error messages sorted by message text	747

SQL preprocessor error messages sorted by error code

Error code	Message text
2601	“Subscript value %1 too large” on page 758
2602	“Combined pointer and arrays not supported for hosttypes” on page 749
2603	“Only one-dimensional arrays supported for CHAR type” on page 757
2604	“VARCHAR type must have a length” on page 760
2605	“Arrays of VARCHAR not supported” on page 748
2606	“VARCHAR host variables cannot be pointers” on page 759
2607	“Initializer not allowed on VARCHAR host variable” on page 753
2608	“FIXCHAR type must have a length” on page 750
2609	“Arrays of FIXCHAR not supported” on page 748
2610	“Arrays of this type not supported” on page 748
2611	“Precision must be specified for DECIMAL type” on page 757
2612	“Arrays of DECIMAL not allowed” on page 747
2613	“Unknown host variable type” on page 759
2614	“Invalid integer” on page 754
2615	“%1' host variable must be a C string type” on page 747
2617	“%1' symbol already defined” on page 747
2618	“Invalid type for SQL statement variable” on page 755
2619	“Cannot find include file '%1'” on page 749
2620	“Host variable '%1' is unknown” on page 751
2621	“Indicator variable '%1' is unknown” on page 753
2622	“Invalid type for indicator variable '%1'” on page 754
2623	“Invalid host variable type on '%1'” on page 754

Error code	Message text
2625	“Host variable '%1' has two different definitions” on page 751
2626	“Statement '%1' not previously prepared” on page 757
2627	“Cursor '%1' not previously declared” on page 749
2628	“Unknown statement '%1’” on page 759
2629	“Host variables not allowed for this cursor” on page 752
2630	“Host variables specified twice - on DECLARE and OPEN” on page 752
2631	“Must specify a host list or using clause on %1” on page 756
2633	“No INTO clause on SELECT statement” on page 756
2636	“Incorrect Embedded SQL syntax” on page 753
2637	“Missing ending quote of string literal” on page 756
2639	“Token too long” on page 758
2640	“‘%1' host variable must be an integer type” on page 747
2642	“Two SQLDAs specified of the same type (INTO or USING)” on page 758
2646	“Cannot describe static cursors” on page 748
2647	“Macros cannot be redefined” on page 755
2648	“Invalid array dimension” on page 753
2649	“Invalid descriptor index” on page 754
2650	“Invalid field for SET DESCRIPTOR” on page 754
2651	“Field used more than once in SET DESCRIPTOR statement” on page 750
2652	“Data value must be a host variable” on page 749
2660	“INTO clause not allowed on DECLARE cursor - ignored” on page 753
2661	“Unrecognized SQL syntax” on page 759
2662	“Unknown SQL function '%1’” on page 759
2663	“Wrong number of arguments to SQL function '%1’” on page 760

Error code	Message text
2664	“Static statement names will not work properly if used by 2 threads” on page 758
2665	“Host variable '%1' has been redefined” on page 751
2666	“Disallowed language extension detected in syntax” on page 750
2667	“Language extension detected in syntax” on page 755
2680	“No DECLARE SECTION and no INCLUDE SQLCA statement” on page 756
2681	“Unable to open temporary file” on page 758
2682	“Error reading temporary file” on page 750
2683	“Error writing output file” on page 750
2690	“Inconsistent number of host variables for this cursor” on page 752
2691	“Inconsistent host variable types for this cursor” on page 752
2692	“Inconsistent indicator variables for this cursor” on page 752
2694	“No OPEN for cursor '%1’” on page 757
2695	“No FETCH or PUT for cursor '%1’” on page 756
2696	“Host variable '%1' is in use more than once with different indicators” on page 751
2697	“LONG BINARY/LONG VARCHAR size limit is 65535 for UltraLite” on page 755
2698	“WCHAR and TCHAR host variable types are not supported” on page 760
2699	“char, WCHAR, and TCHAR string parameters cannot be mixed” on page 749
2700	“SQL syntax is only supported by UltraLite” on page 757

SQL preprocessor error messages sorted by message text

This section lists messages generated by the SQL preprocessor. Depending on which command line options are set, each message may be an error, a warning, or a non-conformance flag, which itself may be an error or a warning.

For more information about the SQL preprocessor and its command-line options, see [“SQL preprocessor”](#) [*SQL Anywhere Server - Programming*].

'%1' host variable must be a C string type

Error code	2615
------------	------

Probable cause

A C string was required in an embedded SQL statement (for a cursor name, option name, and so on) and the value supplied was not a C string.

'%1' host variable must be an integer type

Error code	2640
------------	------

Probable cause

You have used a host variable that is not of integer type in a statement where only an integer type host variable is allowed.

'%1' symbol already defined

Error code	2617
------------	------

Probable cause

You defined a host variable twice.

Arrays of DECIMAL not allowed

Error code	2612
------------	------

Probable cause

You have attempted to declare a host variable as an array of DECIMAL. A decimal array is not a legal host variable type.

Arrays of FIXCHAR not supported

Error code	2609
------------	------

Probable cause

You have attempted to declare a host variable as an array of FIXCHAR arrays. This is not a legal host variable type.

Arrays of this type not supported

Error code	2610
------------	------

Probable cause

You have attempted to declare a host variable array of a type that is not supported.

Arrays of VARCHAR not supported

Error code	2605
------------	------

Probable cause

You have attempted to declare a host variable as an array of VARCHAR or BINARY. This is not a legal host variable type.

Cannot describe static cursors

Error code	2646
------------	------

Probable cause

You have described a static cursor. When describing a cursor, the cursor name must be specified in a host variable.

Cannot find include file '%1'

Error code	2619
------------	------

Probable cause

The specified include file was not found. Note that the preprocessor will use the INCLUDE environment variable to search for include files.

char, WCHAR, and TCHAR string parameters cannot be mixed

Error code	2699
------------	------

Probable cause

You have attempted to use parameters to one statement that are not all char strings, WCHAR strings or TCHAR strings. String parameters (other than INTO and USING parameters) for one statement must all be the same type of string. Note that literal strings are treated as char strings.

Combined pointer and arrays not supported for hosttypes

Error code	2602
------------	------

Probable cause

You have used an array of pointers as a host variable. This is not legal.

Cursor '%1' not previously declared

Error code	2627
------------	------

Probable cause

An embedded SQL cursor name has been used (such as in a FETCH, OPEN, or CLOSE) without first being declared.

Data value must be a host variable

Error code	2652
------------	------

Probable cause

The variable used in the SET DESCRIPTOR statement hasn't been declared as a host variable.

Disallowed language extension detected in syntax

Error code	2666
------------	------

Probable cause

You have used a SQL Anywhere feature that is not supported by the current flagging level (set using the -e option).

Error reading temporary file

Error code	2682
------------	------

Probable cause

An error occurred while reading from a temporary file.

Error writing output file

Error code	2683
------------	------

Probable cause

An error occurred while writing to the output file.

Field used more than once in SET DESCRIPTOR statement

Error code	2651
------------	------

Probable cause

The same keyword has been used more than once inside a single SET DESCRIPTOR statement.

FIXCHAR type must have a length

Error code	2608
------------	------

Probable cause

You have used the DECL_FIXCHAR macro to declare a host variable of type FIXCHAR but have not specified a length.

Host variable '%1' has been redefined

Error code	2665
------------	------

Probable cause

You have redefined the same host variable with a different host type. As far as the preprocessor is concerned, host variables are global; two host variables with different types cannot have the same name.

Host variable '%1' has two different definitions

Error code	2625
------------	------

Probable cause

The same host variable name was defined with two different types within the same module. Note that host variable names are global to a C module.

Host variable '%1' is in use more than once with different indicators

Error code	2696
------------	------

Probable cause

You have used the same host variable multiple times with different indicator variables in the same statement. This is not supported.

Host variable '%1' is unknown

Error code	2620
------------	------

Probable cause

You have used a host variable in a statement and that host variable has not been declared in a DECLARE SECTION.

Host variables not allowed for this cursor

Error code	2629
------------	------

Probable cause

Host variables are not allowed on the DECLARE statement for the specified cursor. If the cursor name is provided through a host variable, then you should use full dynamic SQL and prepare the statement. A prepared statement may have host variables in it.

Host variables specified twice - on DECLARE and OPEN

Error code	2630
------------	------

Probable cause

You have specified host variables for a cursor on both the DECLARE and the OPEN statements. In the static case, you should specify the host variables on the DECLARE statement. In the dynamic case, specify them on the OPEN.

Inconsistent host variable types for this cursor

Error code	2691
------------	------

Probable cause

You have used a host variable with a different type or length than the type or length previously used with the cursor. Host variable types must be consistent for the cursor.

Inconsistent indicator variables for this cursor

Error code	2692
------------	------

Probable cause

You have used an indicator variable when one was not previously used with the cursor, or you have not used an indicator variable when one was previously used with the cursor. Indicator variable usage must be consistent for the cursor.

Inconsistent number of host variables for this cursor

Error code	2690
------------	------

Probable cause

You have used a different number of host variables than the number previously used with the cursor. The number of host variables must be consistent for the cursor.

Incorrect Embedded SQL syntax

Error code	2636
------------	------

Probable cause

An embedded SQL specific statement (OPEN, DECLARE, FETCH, and so on) has a syntax error.

Indicator variable '%1' is unknown

Error code	2621
------------	------

Probable cause

You have used an indicator variable in a statement and that indicator variable has not been declared in a DECLARE SECTION.

Initializer not allowed on VARCHAR host variable

Error code	2607
------------	------

Probable cause

You can not specify a C variable initializer for a host variable of type VARCHAR or BINARY. You must initialize this variable in regular C executable code.

INTO clause not allowed on DECLARE cursor - ignored

Error code	2660
------------	------

Probable cause

You have used an INTO clause on a DECLARE cursor statement. The INTO clause will be ignored.

Invalid array dimension

Error code	2648
------------	------

Probable cause

The array dimension of the variable is negative.

Invalid descriptor index

Error code	2649
------------	------

Probable cause

You have allocated less than one variable with the ALLOCATE DESCRIPTOR statement.

Invalid field for SET DESCRIPTOR

Error code	2650
------------	------

Probable cause

An invalid or unknown keyword is present in a SET DESCRIPTOR statement. The keywords can only be TYPE, PRECISION, SCALE, LENGTH, INDICATOR, or DATA.

Invalid host variable type on '%1'

Error code	2623
------------	------

Probable cause

You have used a host variable that is not a string type in a place where the preprocessor was expecting a host variable of a string type.

Invalid integer

Error code	2614
------------	------

Probable cause

An integer was required in an embedded SQL statement (for a fetch offset, or a host variable array index, and so on) and the preprocessor was unable to convert what was supplied into an integer.

Invalid type for indicator variable '%1'

Error code	2622
------------	------

Probable cause

Indicator variables must be of type short int. You have used a variable of a different type as an indicator variable.

Invalid type for SQL statement variable

Error code	2618
------------	------

Probable cause

A host variable used as a statement identifier should be of type `a_sql_statement_number`. You attempted to use a host variable of some other type as a statement identifier.

Language extension detected in syntax

Error code	2667
------------	------

Probable cause

You have used a SQL Anywhere feature that is not supported by the current flagging level (set using the `-w` option).

LONG BINARY/LONG VARCHAR size limit is 65535 for UltraLite

Error code	2697
------------	------

Probable cause

When using `DECL_LONGBINARY` or `DECL_LONGVARCHAR` with UltraLite, the maximum size for the array is 64KB.

Macros cannot be redefined

Error code	2647
------------	------

Probable cause

A preprocessor macro has been defined twice, possibly in a header file.

Missing ending quote of string literal

Error code	2637
------------	------

Probable cause

You have specified a string literal in an embedded SQL statement, but there is no ending quote before the end of line or end of file.

Must specify a host list or using clause on %1

Error code	2631
------------	------

Probable cause

The specified statement requires host variables to be specified either in a host variable list or from a SQLDA.

No DECLARE SECTION and no INCLUDE SQLCA statement

Error code	2680
------------	------

Probable cause

The EXEC SQL INCLUDE SQLCA statement is missing from the source file.

No FETCH or PUT for cursor '%1'

Error code	2695
------------	------

Probable cause

A cursor is declared and opened, but is never used.

No INTO clause on SELECT statement

Error code	2633
------------	------

Probable cause

You specified an embedded static SELECT statement but you did not specify an INTO clause for the results.

No OPEN for cursor '%1'

Error code	2694
------------	------

Probable cause

A cursor is declared, and possibly used, but is never opened.

Only one-dimensional arrays supported for CHAR type

Error code	2603
------------	------

Probable cause

You have attempted to declare a host variable as an array of character arrays. This is not a legal host variable type.

Precision must be specified for DECIMAL type

Error code	2611
------------	------

Probable cause

You must specify the precision when declaring a packed decimal host variable using the DECL_DECIMAL macro. The scale is optional.

SQL syntax is only supported by UltraLite

Error code	2700
------------	------

Probable cause

You have attempted to use a statement that is only supported by UltraLite when you are not generating code for UltraLite.

Statement '%1' not previously prepared

Error code	2626
------------	------

Probable cause

An embedded SQL statement name has been used (EXECUTE) without first being prepared.

Static statement names will not work properly if used by 2 threads

Error code	2664
------------	------

Probable cause

You have used a static statement name and preprocessed with the -r reentrancy option. Static statement names cause static variables to be generated that are filled in by the database. If two threads use the same statement, contention arises over this variable. Use a local host variable as the statement identifier instead of a static name.

Subscript value %1 too large

Error code	2601
------------	------

Probable cause

You have attempted to index a host variable that is an array with a value too large for the array.

Token too long

Error code	2639
------------	------

Probable cause

The SQL preprocessor has a maximum token length of 2KB. Any token longer than 2KB will produce this error. For constant strings in embedded SQL commands (the main place this error shows up) use string concatenation to make a longer string.

Two SQLDAs specified of the same type (INTO or USING)

Error code	2642
------------	------

Probable cause

You have specified two INTO DESCRIPTOR or two USING DESCRIPTOR clauses for this statement.

Unable to open temporary file

Error code	2681
------------	------

Probable cause

An error occurred while attempting to open a temporary file.

Unknown host variable type

Error code	2613
------------	------

Probable cause

You declared a host variable of a type not understood by the SQL preprocessor.

Unknown SQL function '%1'

Error code	2662
------------	------

Probable cause

You have used a SQL function that is unknown to the preprocessor and will probably cause an error when the statement is sent to the database server.

Unknown statement '%1'

Error code	2628
------------	------

Probable cause

You attempted to drop an embedded SQL statement that doesn't exist.

Unrecognized SQL syntax

Error code	2661
------------	------

Probable cause

You have used a SQL statement that will probably cause a syntax error when the statement is sent to the database server.

VARCHAR host variables cannot be pointers

Error code	2606
------------	------

Probable cause

You have attempted to declare a host variable as a pointer to a VARCHAR or BINARY. This is not a legal host variable type.

VARCHAR type must have a length

Error code	2604
------------	------

Probable cause

You have attempted to declare a VARCHAR or BINARY host variable using the DECL_VARCHAR or DECL_BINARY macro but have not specified a size for the array.

WCHAR and TCHAR host variable types are not supported

Error code	2698
------------	------

Probable cause

You have attempted to declare a host variable as a WCHAR or TCHAR string. These are only supported by UltraLite on Windows platforms.

Wrong number of arguments to SQL function '%1'

Error code	2663
------------	------

Probable cause

You have used a SQL function with the wrong number of parameters. This will likely cause an error when the statement is sent to the database server.