Mobile Analytics Kit Tutorial: HTML5

Sybase Unwired Platform 2.1 ESD #2

Document ID: DC01728-01-0212-02
Last Revised: May 2012
Copyright © 2012 by Sybase, Inc. All rights reserved.

This publication pertains to Sybase software and to any subsequent release until otherwise indicated in new editions or technical notes. Information in this document is subject to change without notice. The software described herein is furnished under a license agreement, and it may be used or copied only in accordance with the terms of that agreement.

Upgrades are provided only at regularly scheduled software release dates. No part of this publication may be reproduced, transmitted, or translated in any form or by any means, electronic, mechanical, manual, optical, or otherwise, without the prior written permission of Sybase, Inc.

Sybase trademarks can be viewed at the Sybase trademarks page at http://www.sybase.com/detail?id=1011207. Sybase and the marks listed are trademarks of Sybase, Inc. ® indicates registration in the United States of America.

SAP and other SAP products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of SAP AG in Germany and in several other countries all over the world.

Java and all Java-based marks are trademarks or registered trademarks of Oracle and/or its affiliates in the U.S. and other countries.

Unicode and the Unicode Logo are registered trademarks of Unicode, Inc.

IBM and Tivoli are registered trademarks of International Business Machines Corporation in the United States, other countries, or both.

All other company and product names mentioned may be trademarks of the respective companies with which they are associated.

Use, duplication, or disclosure by the government is subject to the restrictions set forth in subparagraph (c)(1)(ii) of DFARS 52.227-7013 for the DOD and as set forth in FAR 52.227-19(a)-(d) for civilian agencies.

Sybase, Inc., One Sybase Drive, Dublin, CA 94568.

Contents

Introduction 4

Prerequisites 4

Using the MAKit HTML5 Library in Sybase Unwired WorkSpace 4

- Creating a Static Web Project 4
- Adding the MAKit HTML5 Library to the Project 7
- Adding MAKit HTML5 CSS Files to the Project 10
- Adding MAKit HTML5 PNG Files to the Project 10
- Adding Layout and Query File to the Project 10

Creating the XML Metadata File 12

Creating an MAChart View 12

Running the MAKit HTML5 Project 13

- Changing to an External Web Browser 13
- Running the MAKit Project 14

Introduction

Mobile Analytics Kit (MAKit) allows users to graphically view data in different types of charts. The *MAKit Tutorial: HTML5* is to help developers quickly understand MAKit concepts and expedite application development.

MAKit HTML5, which runs on Internet Explorer 9.0, Google Chrome 9.0, FireFox 4.0, Safari 5.0 and iPad , uses a metadata configuration file to define chart types and datasource files. MAKit can be used with the Sybase® Unwired Platform Hybrid Web Container.

Prerequisites

- Windows machine 32-bit /64-bit
- Install Sybase Unwired WorkSpace (SUP) 2.1 ESD #2; including the Mobile SDK
- On the C:\ drive, create a folder named `MAKit_HTML5`

Using the MAKit HTML5 Library in Sybase Unwired WorkSpace

Creating a Static Web Project

1. Start the Sybase Unwired WorkSpace IDE.
2. Select **File** > **New** > **Project.**
3. In the New Project dialog, select **Web** > **Static Web Project**, then click **Next**.



4. In the New Static Web Project dialog, enter `MAKit_Tutorial` as the project name and `C:\MAKit_HTML5` as the project location. Click **Finish.**


New Static Web Project
Static Web Project
Create a Web project for simple content (HTML files) only.
Project name:
MAKit_Tutorial
Project location
Use default location
Location:
C:\MAKit_HTML5
Browse...
Target runtime
<None>
New Runtime...
Configuration
Default Configuration
Modify...
The default configuration provides a good starting point. Additional facets can later be installed to add new functionality to the project.
Working sets
Add project to working sets
Working sets:
Select...
< Back
Next >
Finish
Cancel

Adding the MAKit HTML5 Library to the Project

1. In Sybase Unwired WorkSpace, open the `MAKit_Tutorial` project.
2. In the Project Explorer, expand the project folder `MAKit_Tutorial`.



3. Right-click the **WebContent** folder under the `MAKit_Tutorial` project and select **Import**.



4. In the **Import** dialog, select **File System** as the import source under the **General** folder, and click **Next**.



5. In the File System dialog, for the "From directory," browse to `%SYBASE_UNWIRED_INSTALLLED%\UnwiredPlatform\MobileSDK\MAKit\HTML5\scripts`.



6. Select the check box next to the `scripts` folder as shown above.
7. Select **Overwrite existing resources without warning** and **Create top-level folder**, then click **Finish**.

Adding MAKit HTML5 CSS Files to the Project

1. In the Project Explorer, expand the `MAKit_Tutorial` folder.
2. Right-click the **WebContent** folder and select **Import.**
3. Select **File System** as import source, then click **Next**.
4. In the File System dialog, for the "From directory," browse to `%SYBASE_UNWIRED_INSTALLLED%\UnwiredPlatform\MobileSDK\MAKit\HTML5\css`.
5. Select the check box next to the `css` folder.
6. Select **Overwrite existing resources without warning** and **Create top-level folder**, then click **Finish**.
7. You must import one more CSS file. In the Project Explorer, expand the `MAKit_Tutorial` folder again, then expand the **WebContent** folder.
8. Right-click the **css** folder and select **Import.**
9. Select **File System** as the import source and click **Next**.
10. In the File System dialog, select `toolbar.css` and `tollbar.png` from `%SYBASE_UNWIRED_INSTALLLED%\UnwiredPlatform\MobileSDK\MAKit\HTML5\demo\css.`
11. Unselect **Create top-level folder**, then click **Finish**.

Adding MAKit HTML5 PNG Files to the Project

1. In the Project Explorer, expand the `MAKit_Tutorial` folder.
2. Right-click the **WebContent** folder and select **Import.**
3. Select **File System** as the import source, then click **Next**.
4. In the File System dialog, for the "From directory," browse to `%SYBASE_UNWIRED_INSTALLLED%\UnwiredPlatform\MobileSDK\MAKit\HTML5\images.`
5. Select the check box next to the `images` folder.
6. Select **Overwrite existing resources without warning** and **Create top-level folder**, then click **Finish**.

Adding Layout and Query File to the Project

1. In the Project Explorer, expand the `MAKit_Tutorial` folder, then expand the **WebContent** folder.
2. Right-click the **Scripts** subfolder (under `WebContent`) and select **Import.**
3. In the Import dialog, select **File System** as the import source and click **Next**.

4. In the File System dialog, select **`MyLayout.js`** and **`MyQuery.js`** from `%SYBASE_UNWIRED_INSTALLLED%\UnwiredPlatform\MobileSDK\MAKit\HTML5\demo`.
5. Unselect **Create top-level folder**, then click **Finish**.
6. Open the imported **MyLayout.js** file, modify the following script to point the image folder.

```
$MA.setImagesFolder("../images/");
            change to
$MA.setImagesFolder("./images/");
```



Creating the XML Metadata File

Chart configuration, which includes items such as chart type, query, category, series, and value axis information, resides in an XML metadata file, within the *<Chart>....</Chart>* tag.

1. In the Project Explorer, expand the `MAKit_Tutorial` folder.
2. Right-click the **WebContent** subfolder under `MAKit_Tutorial` and select **New** > **Other.**
3. Select **XML File** under the XML folder and click **Next**.
4. Enter `MAFV_Bar.xml`as as the file name and click **Finish.**
5. Add the following content to the file, then click **Save.**

```
<Chart Name="chart_1" ChartType="column" Query="productRevenueByYear"
Title="Revenue 2010">

    <Category Column="year"/>
    <Values>
        <Value Expression="revenue" Format="currency"/>
   </Values>

</Chart>
```

Creating an MAChart View

In this section, we are going to demonstrate how to create MAChart using APIs. MAChart is metadata-based; therefore, you must prepare a metadata file for configuration. You can find the details about MAChart metadata in the next section. The data used in MAChart must be in a CSV format.

1. In the Sybase Unwired WorkSpace IDE, open the `MAKit_Tutorial` project.
2. In the Project Explorer, expand the `MAKit_Tutorial` folder.
3. Right-click the **WebContent** folder under `MAKit_Tutorial` and select **New** > **HTML File.**
4. In the New HTML File wizard, enter `main.html` as the file name and click **Next.**
5. In the Select HTML Template wizard**,** select **New HTML File (5)** and click **Finish.**
6. Open the `main.html` file and add these meta tags to the header tag:

```
<meta name="viewport" content="initial-scale=1;maximum-scale=1;user-scalable=0;
width=device-width;" />
<meta name="apple-mobile-web-app-capable" content="yes"  />
```

7. Add these css reference links to the header tag:

```
<link rel="stylesheet" href="css/toolbar.css" type="text/css" />
<link rel="stylesheet" href="css/default.css" type="text/css" class="ui-theme" />
```

8. Add these MAKit JavaScript (*js) reference links to the header tag:

```
<script src="scripts/Sybase.MA-min.js"></script>
<script src="scripts/MyQuery.js"></script>
<script src="scripts/MyLayout.js"></script>
```

9. Create these two DIV elements to define the chart and title to the body tag:

```
<div class="toolbar" id="toolbar">
    <h1 id="title"></h1>
</div>
<div id="contents">
    <div id="chart_1" style="float:left;"></div>
</div>
```

10. Adding the chart variable to the DIV element indicates the corresponding chart control. Write JavaScript to assign the DIV element to the chart control and load the XML file. Add this script to the body tag:

```
<script type="text/javascript">

   window.onload = function () {
        arrange(1, 1);
        var chart = new $MA.Chart("chart_1", true);
        chart.bind("titlechanged", onTitleChanged);
        chart.load("MAFV_Bar.xml");
}


   function onTitleChanged(title) {
        var elem = document.getElementById("title");
        elem.innerHTML = title;
}

     function onOrientationChanged() {
        arrange(1,1,true);
}


</script>
```

11. **Save** the file.

Running the MAKit HTML5 Project

MAKit HTML5 can run on an Eclipse Web browser, or on several browsers that are external to Eclipse, including Internet Explorer 9.0, Google Chrome 9.0, FireFox 4.0, Safari 5.0, and iPad. Users can change from the Eclipse Web browser to one of these external browsers

Changing to an External Web Browser

1. From the Eclipse main menu, select **Window > Preferences**.
2. Select **General > Web Browser**.
3. Click **New.**
4. Enter the name and location of the executable for the browser to which you are changing. Click **OK**.



5. From the list of external Web browsers, select the one you just added. Click **Apply**.

Running the MAKit Project

1. Right-click the **main.html** file you created on page 12 and select **Run > Run on Server**.
2. In the Run On Server dialog, select **Choose an existing server.**



3. From the `localhost` folder, select **HTTP Preview at localhost.**

4. Select **Always use this server when running this project**.



5. Move resources to the right to configure them on the server. Click **Finish.**

6. MAKit shows the chart you specified in the main.html file using the Web browser you have specified.